Commission Implementing Regulation (EU) 2018/1974 of 14 December 2018 amending Regulation (EU) No 1178/2011 laying down technical requirements and administrative procedures related to civil aviation aircrew pursuant to Regulation (EU) 2018/1139 of the European Parliament and of the Council (Text with EEA relevance)

COMMISSION IMPLEMENTING REGULATION (EU) 2018/1974

of 14 December 2018

amending Regulation (EU) No 1178/2011 laying down technical requirements and administrative procedures related to civil aviation aircrew pursuant to Regulation (EU) 2018/1139 of the European Parliament and of the Council

(Text with EEA relevance)

THE EUROPEAN COMMISSION,

Having regard to the Treaty on the Functioning of the European Union,

Having regard to Regulation (EU) 2018/1139 of the European Parliament and of the Council of 4 July 2018 on common rules in the field of civil aviation and establishing a European Union Aviation Safety Agency, and amending Regulations (EC) No 2111/2005, (EC) No 1008/2008, (EU) No 996/2010, (EU) No 376/2014 and Directives 2014/30/EU and 2014/53/EU of the European Parliament and of the Council, and repealing Regulation (EC) No 552/2004 and (EC) No 216/2008 of the European Parliament and of the Council and Council Regulation (EEC) No 3922/91⁽¹⁾, and in particular Article 23 thereof,

Whereas:

- (1) Commission Regulation (EU) No 1178/2011⁽²⁾ lays down technical requirements for the certification of flight simulation training devices, the certification of pilots involved in the operation of certain aircraft, and the certification of persons and organisations involved in the pilot training, testing and checking.
- (2) Since the last decade, aeroplane upset or loss of control have been identified among the major risk factors that could lead to fatal accidents in commercial air transport operations and its prevention became a strategic priority in Europe⁽³⁾ and at a global level. This included new training requirements to better prepare pilots for adverse situations of aircraft upset and loss of control.
- (3) By Commission Regulation (EU) 2015/445⁽⁴⁾, the existing training requirements for commercial pilots were updated to include upset prevention and recovery training (UPRT) as a mandatory constituent of the theoretical knowledge of pilots. Further detailed training elements and training objectives are needed to improve pilot competencies for both prevention of and recovery from aeroplane upsets that can lead to a loss of control and, eventually, to a fatal accident.

- (4) UPRT needs to be integrated at various stages of a professional pilot's career and should be reflected in the privileges stated in the individual pilot licence. A well-developed and well-maintained competence of professional pilots in upset prevention and recovery should be ensured. UPRT should become a mandatory part of the multi-crew pilot licence (MPL) training course and the integrated training course for airline transport pilots for aeroplanes (ATP(A)) and a training course for a commercial pilot licence for aeroplanes (CPL(A)) as well as for class and type-ratings for single-pilot aeroplanes operated in multi-pilot operations, single-pilot non-high-performance complex, high-performance complex aeroplanes and multi-pilot aeroplanes ratings. In order to allow pilots to develop advanced competencies in upset prevention and recovery, the relevant training course should include related air exercises in an aeroplane.
- (5) Further to the introduction of the new course related to the development of advanced pilot competencies in upset prevention and recovery, the requirements for instructor certificates should be revised in order to ensure that persons instructing on this course are appropriately qualified.
- (6) This Regulation reflects the provisions adopted by the International Civil Aviation Organisation (ICAO) in 2014 on UPRT for multi-crew pilot licences and for multi-pilot aeroplane type ratings through the amendment to Annex 1 to the Chicago Convention on Personnel Licensing.
- (7) It is in the interest of aviation safety that the new UPRT elements should be implemented as soon as possible. Transitional provisions should be put in place to allow training courses that have started before these UPRT-related amendments to the requirements on pilot training become effective, to be completed without any further adaptation. In this context, it should be considered that pilots flying for commercial air operators in accordance with Commission Regulation (EU) No 965/2012⁽⁵⁾ need to undergo regular operator training which already today contains UPRT elements. Additionally, pilot training organisations should be given a transitional period to adapt their training programmes to comply with the new UPRT requirements. At the end of that transitional period, all relevant training courses should be conducted in accordance with the new UPRT requirements.
- (8) Negotiations between the Union and certain third countries are currently still ongoing, including on the conversion of pilot licences and associated medical certificates. In order to ensure that Member States may continue to recognise third country licences and medical certificates for an interim period in light of those negotiations, it is necessary to prolong the period during which Member States may decide not to apply the provisions of Regulation (EU) No 1178/2011 in their territory to pilots holding a licence and associated medical certificate issued by a third country involved in the non-commercial operation of certain aircraft.
- (9) The European Union Aviation Safety Agency submitted draft implementing rules to the European Commission together with its Opinion No 06/2017.
- (10) The measures provided for in this Regulation are in accordance with the opinion of the Committee established by Article 127 of Regulation (EU) 2018/1139,

Changes to legislation: There are currently no known outstanding effects for the Commission Implementing Regulation (EU) 2018/1974. (See end of Document for details)

HAS ADOPTED THIS REGULATION:

Article 1

Regulation (EU) No 1178/2011 is amended as follows:

(1) after Article 4a, the following Article 4b is inserted:

Article 4h

Upset prevention and recovery training

- Upset prevention and recovery training shall become a mandatory part of a training course for a multi-crew pilot licence (MPL), an integrated training course for airline transport pilots for aeroplanes (ATP(A)), a training course for a commercial pilot licence for aeroplanes (CPL(A)) and training courses for a class or type rating for:
 - a single-pilot aeroplanes operated in multi-pilot operations;
 - b single-pilot non-high-performance complex aeroplanes;
 - c single-pilot high-performance complex aeroplanes; or
 - d multi-pilot aeroplanes;

in accordance with Annex I (Part-FCL).

- For training courses referred to in paragraph 1 that commence before 20 December 2019 at an approved training organisation (ATO), upset prevention and recovery training shall not be mandatory provided that:
 - a CPL(A), ATP(A) or MPL training course is otherwise completed in accordance with Annex I (Part-FCL) and the skill test is completed in compliance with points FCL.320 (CPL), FCL.620 (IR) or FCL.415.A (MPL) of Annex I (Part-FCL) by 20 December 2021 at the latest; or
 - b class or type rating training course for the aeroplanes is otherwise completed in accordance with Annex I (Part-FCL) and the skill test is completed in compliance with the second subparagraph of paragraph (c) of point FCL.725 of Annex I (Part-FCL) to this Regulation by 20 December 2021 at the latest.

For the purpose of paragraph 1, the competent authority may on its own assessment and pursuant to a recommendation from an ATO give credit for any upset prevention and recovery training completed before 20 December 2019 under national training requirements.;

- (2) in Article 12, paragraph 4 is replaced by the following:
- 4. By way of derogation from paragraph 1, Member States may decide not to apply the provisions of this Regulation until 20 June 2020, to pilots holding a licence and associated medical certificate issued by a third country involved in the non-commercial operation of aircraft as specified in Article 2(1)(b), points (i) or (ii), of Regulation (EU) 2018/1139. Member States shall make those decisions publicly available.;
- (3) Article 12, paragraph 8, is replaced by the following:
- 8. By way of derogation from paragraph 1, point FCL.315.A, the second sentence of paragraph (a) of point FCL.410.A and paragraph (c) of point FCL.725.A of Annex I (Part-FCL) shall apply from 20 December 2019.;

(4) Annex I to Regulation (EU) No 1178/2011 is amended in accordance with the Annex to this Regulation.

Article 2

This Regulation shall enter into force on the twentieth day following that of its publication in the *Official Journal of the European Union*.

However:

- (a) Article 1(1) shall apply from 20 December 2019.
- (b) Article 1(4) shall apply from 20 December 2019.
- (c) Notwithstanding point (b) above, points (2), (4), (5) and (12) of the Annex to this Regulation shall apply from 31 January 2022.

This Regulation shall be binding in its entirety and directly applicable in all Member States.

Done at Brussels, 14 December 2018.

For the Commission

Violeta BULC

Member of the Commission

Changes to legislation: There are currently no known outstanding effects for the Commission Implementing Regulation (EU) 2018/1974. (See end of Document for details)

ANNEX

Annex I to Regulation (EU) No 1178/2011 (Part-FCL) is amended as follows:

- (1) Point FCL.010 is amended as follows:
 - (a) the introductory sentence is replaced by the following:

For the purposes of this Annex (Part-FCL), the following definitions shall apply:;

- (b) a new definition of 'Accessible' is inserted before the definition of 'Aerobatic flight' as follows:
 - "Accessible" means that a device can be used by:
 - the approved training organisation (ATO) under whose approval a training course for a class or type rating is being conducted; or
 - the examiner conducting the assessment of competence, skill test or proficiency check for the purpose of assessing, testing or checking.;
- (c) the definition of 'Aerobatic flight' is replaced by the following:
 - "Aerobatic flight" means an intentional manoeuvre involving an abrupt change in an aircraft's attitude, an abnormal attitude, or abnormal acceleration, not necessary for normal flight or for instruction for licences, certificates, or ratings other than the aerobatic rating.;
- (d) After the definition of 'Aeroplane required to be operated with a co-pilot', a new definition of 'Aeroplane upset prevention and recovery training' is inserted as follows:
 - "Aeroplane upset prevention and recovery training" (UPRT) means training consisting of:
 - aeroplane upset prevention training: a combination of theoretical knowledge and flying training with the aim of providing flight crew with the required competencies to prevent aeroplane upsets;
 and
 - aeroplane upset recovery training: a combination of theoretical knowledge and flying training with the aim of providing flight crew with the required competencies to recover from aeroplane upsets.;
- (e) After the definition of 'Airship', a new definition of 'Available FSTD' is inserted as follows:
 - 'Available FSTD' means any flight simulation training device (FSTD) that is vacant for use of the FSTD operator or of the customer irrespective of any time considerations.;
- (2) Point FCL.310 is replaced by the following:

FCL.310 CPL — Theoretical knowledge examinations

Applicants for the issue of a CPL shall demonstrate a level of knowledge appropriate to the privileges granted in the following subjects:

(a) air law;

Changes to legislation: There are currently no known outstanding effects for the Commission Implementing Regulation (EU) 2018/1974. (See end of Document for details)

- (b) aircraft general knowledge airframe/systems/power plant;
- (c) aircraft general knowledge instrumentation;
- (d) mass and balance;
- (e) performance;
- (f) flight planning and monitoring;
- (g) human performance;
- (h) meteorology;
- (i) general navigation;
- (j) radio navigation;
- (k) operational procedures;
- (l) principles of flight; and
- (m) communications.;
- (3) Point FCL.410.A is replaced by the following:

FCL.410.A MPL – Training course and theoretical knowledge examinations

(a) Course

Applicants for the issue of an MPL shall have completed a training course of theoretical knowledge and flight instruction at an ATO in accordance with Appendix 5 to this Annex (Part-FCL).

(b) Examination

Applicants for the issue of an MPL shall demonstrate a level of theoretical knowledge appropriate to the holders of an ATPL(A), in accordance with FCL.515, and to a multipilot type rating.;

(4) Point FCL.515 is replaced by the following:

FCL.515 ATPL — Training course and theoretical knowledge examinations

(a) Course

Applicants for an ATPL shall have completed a training course at an ATO. The course shall be either an integrated training course or a modular course, in accordance with Appendix 3 to this Annex (Part-FCL).

(b) Examination

Applicants for the issue of an ATPL shall demonstrate a level of knowledge appropriate to the privileges granted in the following subjects:

- (1) air law;
- (2) aircraft general knowledge airframe/systems/power plant;
- (3) aircraft general knowledge instrumentation;
- (4) mass and balance;

Changes to legislation: There are currently no known outstanding effects for the Commission Implementing Regulation (EU) 2018/1974. (See end of Document for details)

- (5) performance;
- (6) flight planning and monitoring;
- (7) human performance;
- (8) meteorology;
- (9) general navigation;
- (10) radio navigation;
- (11) operational procedures;
- (12) principles of flight; and
- (13) communications.;
- (5) Point FCL.615 is replaced by the following:

FCL.615 IR — Theoretical knowledge and flight instruction

(a) Course

Applicants for an IR shall have completed a course of theoretical knowledge and flight instruction at an ATO. The course shall be:

- (1) an integrated training course which includes training for the IR, in accordance with Appendix 3 to this Annex (Part-FCL); or
- (2) a modular course in accordance with Appendix 6 to this Annex (Part-FCL).
- (b) Examination

Applicants shall demonstrate a level of theoretical knowledge appropriate to the privileges granted in the following subjects:

- (1) air law;
- (2) aircraft general knowledge instrumentation;
- (3) flight planning and monitoring;
- (4) human performance;
- (5) meteorology;
- (6) radio navigation; and
- (7) communications.;
- (6) Point FCL.725 paragraph (d) is replaced by the following:
 - (d) An applicant who already holds a type rating for an aircraft type, with the privilege for either single-pilot or multi-pilot operations, shall be considered to have already fulfilled the theoretical requirements when applying to add the privilege for the other form of operation on the same aircraft type. Such an applicant shall complete additional flight training for the other form of operation at an ATO or an AOC holder specifically authorised for such training by the competent authority. The form of operation shall be entered in the licence.

(7) Point FCL.720.A is replaced by the following:

FCL.720.A Experience requirements and prerequisites for the issue of class or type ratings — aeroplanes

Unless otherwise determined in the operational suitability data established in accordance with Annex I (Part-21) to Regulation (EU) No 748/2012 (OSD), applicants for the issue of a class or type rating shall comply with the following experience requirements and prerequisites for the issue of the relevant rating:

(a) Single-pilot aeroplanes

Applicants for the issue of a first class or type rating on a single-pilot aeroplane seeking the privilege to operate the aeroplane in multi-pilot operations shall meet the requirements in points (b)(4) and (b)(5).

Additionally, for:

(1) Single-pilot multi-engine aeroplanes

Applicants for the issue of a first class or type rating on a single-pilot multi-engine aeroplane shall have completed at least 70 hours as PIC in aeroplanes.

(2) Single-pilot high-performance non-complex aeroplanes

Before starting flight training, applicants for the issue of a class or type rating for a single-pilot aeroplane classified as a high-performance aeroplane shall:

- (i) have at least 200 hours of total flying experience, of which 70 hours as PIC in aeroplanes; and
- (ii) comply with one of the following requirements:
 - (A) hold a certificate of satisfactory completion of a course for additional theoretical knowledge undertaken at an ATO; or
 - (B) have passed the ATPL(A) theoretical knowledge examinations in accordance with this Annex (Part-FCL); or
 - (C) hold, in addition to a licence issued in accordance with this Annex (Part-FCL), an ATPL(A) or CPL(A)/IR with theoretical knowledge credit for ATPL(A), issued in accordance with Annex 1 to the Chicago Convention.
- (3) Single-pilot high-performance complex aeroplanes

Applicants for the issue of a type rating for a complex single-pilot aeroplane classified as a high-performance aeroplane shall, in addition to meeting the requirements in point (2), hold or have held a single- or multi-engine IR(A), as appropriate and as established in Subpart G and shall meet the requirements in point (b)(5).

(b) Multi-pilot aeroplanes

Applicants for the issue of the first type rating course for a multi-pilot aeroplane shall be student pilots currently undergoing training on an MPL training course or comply with the following requirements:

- (1) have at least 70 hours of flight experience as PIC in aeroplanes;
- (2) hold or have held a multi-engine IR(A);

Changes to legislation: There are currently no known outstanding effects for the Commission Implementing Regulation (EU) 2018/1974. (See end of Document for details)

- have passed the ATPL(A) theoretical knowledge examinations in accordance with this Annex (Part-FCL);
- (4) except when the type rating course is combined with an MCC course:
 - (i) hold a certificate of satisfactory completion of an MCC course in aeroplanes; or
 - (ii) hold a certificate of satisfactory completion of MCC in helicopters and have more than 100 hours of flight experience as pilots of multi-pilot helicopters; or
 - (iii) have at least 500 hours as pilots of multi-pilot helicopters; or
 - (iv) have at least 500 hours as pilots in multi-pilot operations on single-pilot multi-engine aeroplanes, in commercial air transport in accordance with the applicable air operations requirements; and
- (5) have completed the training course specified in FCL.745.A.
- (c) Notwithstanding point (b), a Member State may issue a type rating with restricted privileges for a multi-pilot aeroplane that allows holders of such a rating to act as cruise relief co-pilots above Flight Level 200, provided that two other members of the crew have a type rating in accordance with point (b).
- (d) When so determined in the OSD, the exercise of the privileges of a type rating may be initially limited to flight under the supervision of an instructor. The flight hours under supervision shall be entered in the pilots' logbook or equivalent record and signed by the instructor. The limitation shall be removed when pilots demonstrate that the hours of flight under supervision required in the OSD have been completed.;
- (8) Point FCL.725.A is replaced by the following:

FCL.725.A Theoretical knowledge and flight instruction for the issue of class and type ratings — aeroplanes

Unless otherwise determined in in the operational suitability data established in accordance with Annex I (Part-21) to Regulation (EU) No 748/2012:

- (a) for single-pilot multi-engine aeroplanes:
 - (1) the theoretical knowledge course for a single-pilot multi-engine class rating shall include at least 7 hours of instruction in multi-engine aeroplane operations; and
 - (2) the flight training course for a single-pilot multi-engine class or type rating shall include at least 2 hours and 30 minutes of dual flight instruction under normal conditions of multi-engine aeroplane operations, and not less than 3 hours 30 minutes of dual flight instruction in engine failure procedures and asymmetric flight techniques.
- (b) for single-pilot aeroplanes (sea):
 - (1) the training course for single-pilot aeroplane (sea) ratings shall include theoretical knowledge and flight instruction; and

Changes to legislation: There are currently no known outstanding effects for the Commission Implementing Regulation (EU) 2018/1974. (See end of Document for details)

- (2) the flight training for a class or type rating (sea) for singlepilot aeroplanes (sea) shall include at least 8 hours of dual flight instruction if applicants hold the land version of the relevant class or type rating, or 10 hours if applicants do not hold such a rating; and
- (c) for single-pilot non-high-performance complex aeroplanes, single-pilot high-performance complex aeroplanes and multi-pilot aeroplanes, the training courses shall include UPRT theoretical knowledge and flight instruction related to the specificities of the relevant class or type.;
- (9) A new point FCL.745.A is inserted as follows:

FCL.745.A Advanced UPRT course — aeroplanes

- (a) The advanced UPRT course shall be completed at an ATO and shall comprise at least:
 - (1) 5 hours of theoretical knowledge instruction;
 - (2) preflight briefings and postflight debriefings; and
 - (3) 3 hours of dual flight instruction with a flight instructor for aeroplanes FI(A) qualified in accordance with point FCL.915 (e) and consisting of advanced UPRT in an aeroplane qualified for the training task.
- (b) Upon completion of the UPRT course, applicants shall be issued with a certificate of completion by the ATO.;
- (10) Point (b)(1) of point FCL.900 is replaced by the following:
 - (1) The competent authority may issue a specific certificate granting privileges for flight instruction when compliance with the requirements established in this Subpart is not possible in the case of the introduction of:
 - (i) new aircraft in the Member States or in an operator's fleet; or
 - (ii) new training courses in this Annex (Part-FCL).

Such a certificate shall be limited to the training flights necessary for the introduction of the new type of aircraft or the new training course and its validity shall not, in any case, exceed 1 year.;

(11) Point FCL.915 is amended as follows:

FCL.915 General prerequisites and requirements for instructors

(a) General

Applicants for the issue of an instructor certificate shall be at least 18 years of age.

(b) Additional requirements for instructors providing flight instruction in aircraft

Applicants for the issue of or holders of an instructor certificate with privileges to conduct flight instruction in an aircraft shall:

- (1) for licence training, hold at least the licence or, in the case of point FCL.900(c), the equivalent licence, for which flight instruction is to be given;
- for a rating training, hold the relevant rating or, in the case of point FCL.900(c), the equivalent rating, for which flight instruction is to be given;
- (3) except in the case of flight test instructors (FTIs), have:
 - (i) completed at least 15 hours of flight time as pilots of the class or type of aircraft on which flight instruction is to be given, of which a maximum of 7 hours may be in an FSTD representing the class or type of aircraft, if applicable; or
 - (ii) passed an assessment of competence for the relevant category of instructor on that class or type of aircraft; and
- (4) be entitled to act as PIC in the aircraft during such flight instruction.
- (c) Credit towards further ratings and for the purpose of revalidation
- (1) Applicants for further instructor certificates may be credited with the teaching and learning skills already demonstrated for the instructor certificate held.
- (2) Hours flown as an examiner during skill tests or proficiency checks shall be credited in full towards revalidation requirements for all instructor certificates held.
- (d) Credit for extension to further types shall take into account the relevant elements as defined in the operational suitability data established in accordance with Annex I (Part-21) to Regulation (EU) No 748/2012 (OSD).
- (e) Additional requirements for instructing in a training course in accordance with FCL.745.A:
- (1) In addition to (b), before acting as instructors for a training course according to FCL.745.A, holders of an instructor certificate shall:
 - (i) have at least 500 hours of flight time as pilots of aeroplanes, including 200 hours of flight instruction;
 - (ii) after complying with the experience requirements in point (e) (1)(i), have completed a UPRT instructor training course at an ATO, during which the competence of applicants shall have been assessed continuously; and
 - (iii) upon completion of the course, have been issued with a certificate of course completion by the ATO, whose Head of Training (HT) shall have entered the privileges specified in point (e)(1) in the logbook of the applicants.
- (2) The privileges referred to in point (e)(1) shall only be exercised if instructors have, during the last year, received refresher training at an ATO during which the competence required to instruct on a course in accordance with point FCL.745.A is assessed to the satisfaction of the HT.

- (3) Instructors holding the privileges specified in point (e)(1) may act as instructors for a course as specified in point (e)(1)(ii), provided that they:
 - (i) have 25 hours of flight instruction experience during training according to FCL745.A;
 - (ii) have completed an assessment of competence for this privilege; and
 - (iii) comply with the recency requirements in point (e)(2).
- (4) These privileges shall be entered in the logbook of the instructors and signed by the examiner.;
- (12) Appendix 1 is replaced by the following:

AppendixCrediting of theoretical knowledgeCREDITING OF THEORETICAL

1 KNOWLEDGE IN THE SAME OR ANOTHER CATEGORY OF
AIRCRAFT — BRIDGE INSTRUCTION AND EXAMINATION
REQUIREMENTS1.LAPL, PPL, BPL and SPL1.1.

For the issue of an LAPL, holders of an LAPL in another category of aircraft shall be fully credited with theoretical knowledge on the common subjects established in FCL.120(a).

1.2.

Without prejudice to paragraph 1.1., for the issue of an LAPL, a PPL, a BPL or an SPL, holders of a licence in another category of aircraft shall receive theoretical knowledge instruction and pass theoretical knowledge examinations to the appropriate level in the following subjects:

- principles of flight;
- operational procedures;
- flight performance and planning;
- aircraft general knowledge; and
- navigation.

1.3.

For the issue of a PPL, a BPL or an SPL, holders of an LAPL in the same category of aircraft shall be credited in full towards the theoretical knowledge instruction and examination requirements. 1.4.

Notwithstanding point 1.2, for the issue of an LAPL(A), holders of an LAPL(S) with TMG extension shall demonstrate an adequate level of theoretical knowledge for the SEP(land) class in accordance with FCL.135.A(a)(2).

2.CPL2.1.

Applicants for the issue of a CPL holding a CPL in another category of aircraft shall have received theoretical knowledge bridge instruction at an ATO on an approved course according to the differences identified between the CPL syllabi for different aircraft categories.

2.2.

Changes to legislation: There are currently no known outstanding effects for the Commission Implementing Regulation (EU) 2018/1974. (See end of Document for details)

Applicants shall pass theoretical knowledge examinations as defined in this Annex (Part-FCL) for the following subjects in the appropriate aircraft category:

021 — Aircraft general knowledge: airframe and systems, electrics, power plant and emergency equipment;

022 — Aircraft general knowledge: instrumentation;

032/034 — Performance aeroplanes or helicopters, as applicable;

070 — Operational procedures; and

080 — Principles of flight.

2.3.

Applicants for the issue of a CPL having passed the relevant theoretical knowledge examinations for an IR in the same category of aircraft are credited towards the theoretical knowledge requirements in human performance and meteorology unless they have completed the IR training course in accordance with Appendix 6, Section Aa, to this Annex (Part-FCL).

2.4.

Applicants for a CPL having passed the relevant theoretical knowledge examinations for an IR or EIR in the same category of aircraft are credited towards the theoretical knowledge requirements in the communications subject.

3.ATPL3.1.

Applicants for the issue of an ATPL holding an ATPL in another category of aircraft shall have received theoretical knowledge bridge instruction at an ATO on an approved course according to the differences identified between the ATPL syllabi for different aircraft categories.

Applicants shall pass theoretical knowledge examinations as defined in this Annex (Part-FCL) for the following subjects in the appropriate aircraft category:

021 — Aircraft general knowledge: airframe and systems, electrics, power plant and emergency equipment;

022 — Aircraft general knowledge: instrumentation;

032/034 — Performance aeroplanes or helicopters, as applicable;

070 — Operational procedures; and

080 — Principles of flight.

3.3.

Applicants for the issue of an ATPL(A) having passed the relevant theoretical examination for a CPL(A) are credited towards the theoretical knowledge requirements in the subject 'communications'.

3.4.

Applicants for the issue of an ATPL(H) having passed the relevant theoretical examinations for a CPL(H) are credited towards the theoretical knowledge requirements in the following subjects:

- air law:
- principles of flight (helicopter); and

Changes to legislation: There are currently no known outstanding effects for the Commission Implementing Regulation (EU) 2018/1974. (See end of Document for details)

communications.

Applicants for the issue of an ATPL(A) having passed the relevant theoretical examination for an IR(A) are credited towards the theoretical knowledge requirements in the subject 'communications'.

3.6.

Applicants for the issue of an ATPL(H) with an IR(H) having passed the relevant theoretical examinations for a CPL(H) are credited towards the theoretical knowledge requirements in the following subjects:

- principles of flight (helicopter); and
- communications.

4.IR4.1.

Applicants for the issue of an IR or an EIR having passed the relevant theoretical examinations for a CPL in the same aircraft category are credited towards the theoretical knowledge requirements in the following subjects:

- human performance;
- meteorology; and
- communications.

4.2.

Applicants for the issue of an IR(H) having passed the relevant theoretical examinations for an ATPL(H) VFR are required to pass the following examination subjects:

- air law;
- flight planning and flight monitoring; and
- radio navigation.;
- (13) Appendix 3, Section A is amended as follows:
 - (a) point (4) is replaced by the following:
 - 4. The course shall comprise:
 - (a) theoretical knowledge instruction to the ATPL(A) knowledge level;
 - (b) visual and instrument flying training;
 - (c) training in MCC for the operation of multi-pilot aeroplanes; and
 - (d) UPRT in accordance with FCL.745.A unless applicants have already completed this training course before starting the ATP integrated course.;
 - (b) point (5) is replaced by the following:
 - 5. Applicants failing or being unable to complete the entire ATP(A) course may apply to the competent authority for the theoretical knowledge examination and skill test for a licence with lower privileges and an IR if the applicable requirements are met.;
 - (c) point 7 is renamed '7.1.' and a new point (7.2.) is inserted as follows:

Changes to legislation: There are currently no known outstanding effects for the Commission Implementing Regulation (EU) 2018/1974. (See end of Document for details)

- 7.2. The theoretical knowledge instruction in UPRT shall be conducted in accordance with FCL.745.A.;
- (d) point (9) is replaced by the following:
 - 9. The flying training, not including type rating training, shall comprise a total of at least 195 hours, including all progress tests, of which up to 55 hours for the entire course may be instrument ground time. Within the total of 195 hours, applicants shall complete at least:
 - (a) 95 hours of dual instruction, of which up to 55 hours may be instrument ground time;
 - (b) 70 hours as PIC including VFR flight, and instrument flight time as SPIC. The instrument flight time as SPIC shall only be counted as PIC flight time up to a maximum of 20 hours;
 - (c) 50 hours of cross-country flight as PIC, including one VFR cross-country flight of at least 540 km (300 NM), in the course of which full-stop landings at two aerodromes different from the aerodrome of departure shall be made; and
 - (d) 5 hours of flight time at night, comprising 3 hours of dual instruction, which shall include at least:
 - (1) 1 hour of cross-country navigation;
 - (2) five solo take-offs; and
 - (3) five solo full-stop landings;
 - (e) UPRT flight instruction in accordance with FCL.745.A;
 - (f) 115 hours of instrument time comprising, at least:
 - (1) 20 hours as SPIC;
 - (2) 15 hours of MCC, for which an FFS or an FNPT II may be used;
 - (3) 50 hours of instrument flight instruction, of which up to:
 - (i) 25 hours may be instrument ground time in an FNPT I; or
 - (ii) 40 hours may be instrument ground time in an FNPT II, an FTD 2 or an FFS, of which up to 10 hours may be conducted in an FNPT I.

Applicants holding a module completion certificate for the Basic Instrument Flight Module shall be credited with up to 10 hours towards the required instrument instruction time. Hours done in a BITD shall not be credited; and

(g) 5 hours in an aeroplane which:

Changes to legislation: There are currently no known outstanding effects for the Commission Implementing Regulation (EU) 2018/1974. (See end of Document for details)

- (1) is certificated for the carriage of at least 4 persons; and
- (2) has a variable pitch propeller and retractable landing gear.;
- (14) Appendix 5 is amended as follows:
 - (a) point (7) is replaced by the following:
 - 7. An approved MPL theoretical knowledge course shall comprise at least 750 hours of instruction for the ATPL(A) knowledge level, as well as the hours required for:
 - (a) theoretical knowledge instruction for the relevant type rating, in accordance with Subpart H; and
 - (b) UPRT theoretical knowledge instruction in accordance with FCL.745.A.;
 - (b) point (8) is replaced by the following:
 - 8. The flying training shall comprise a total of at least 240 hours, composed of hours as PF and PM, in actual and simulated flight, and covering the following four phases of training:
 - (a) Phase 1 Core flying skills

Specific basic single-pilot training in an aeroplane

(b) Phase 2 — Basic

Introduction of multi-crew operations and instrument flight

(c) Phase 3 — Intermediate

Application of multi-crew operations to a multi-engine turbine aeroplane certified as a high-performance aeroplane in accordance with Annex I (Part-21) to Regulation (EU) No 748/2012

(d) Phase 4 — Advanced

Type rating training within an airline-oriented environment.

MCC requirements shall be incorporated into the relevant phases above.

Training in asymmetric flight shall be given either in an aeroplane or an FFS.

- (c) a new point (8a) is inserted as follows:
 - 8a. Flight experience in actual flight shall include:
 - (a) all the experience requirements of Subpart H;
 - (b) UPRT flight instruction in accordance with FCL.745.A;
 - (c) aeroplane UPRT exercises related to the specificities of the relevant type in accordance with FCL.725.A(c);
 - (d) night flying;

Changes to legislation: There are currently no known outstanding effects for the Commission Implementing Regulation (EU) 2018/1974. (See end of Document for details)

- (e) flight solely by reference to instruments; and
- (f) the experience required to achieve the relevant airmanship.;
- (15) Appendix 9 is replaced by the following:

Appendix 9

Training, skill test and proficiency check for MPL, ATPL, type and class ratings, and proficiency check for IRs

A. General

1. Applicants for a skill test shall have received instruction in the same class or type of aircraft to be used in the test.

The training for MPA and PL type ratings shall be conducted in an FFS or in a combination of FSTD(s) and FFS. The skill test or proficiency check for MPA and PL type ratings and the issue of an ATPL and an MPL, shall be conducted in an FFS, if available.

The training, skill test or proficiency check for class or type ratings for SPA and helicopters shall be conducted in:

- (a) an available and accessible FFS, or
- (b) a combination of FSTD(s) and the aircraft if an FFS is not available or accessible; or
- (c) the aircraft if no FSTD is available or accessible.

If FSTDs are used during training, testing or checking, the suitability of the FSTDs used shall be verified against the applicable 'Table of functions and subjective tests' and the applicable 'Table of FSTD validation tests' contained in the primary reference document applicable for the device used. All restrictions and limitations indicated on the device's qualification certificate shall be considered.

- 2. Failure to achieve a pass in all sections of the test in two attempts will require further training.
- 3. There is no limit to the number of skill tests that may be attempted. CONTENT OF THE TRAINING/SKILL TEST/PROFICIENCY CHECK
- 4. Unless otherwise determined in the operational suitability data established in accordance with Annex I (Part-21) to Regulation (EU) No 748/2012 (OSD), the syllabus of flight instruction, the skill test and the proficiency check shall comply with this Appendix. The syllabus, skill test and proficiency check may be reduced to give credit for previous experience on similar aircraft types, as determined in the OSD.
- 5. Except in the case of skill tests for the issue of an ATPL, when so defined in the OSD for the specific aircraft, credit may be given for skill test items common to other types or variants where the pilots are qualified.

CONDUCT OF THE TEST/CHECK

ANNEX

Document Generated: 2023-10-18

Changes to legislation: There are currently no known outstanding effects for the Commission Implementing Regulation (EU) 2018/1974. (See end of Document for details)

- 6. The examiner may choose between different skill test or proficiency check scenarios containing simulated relevant operations. Full-flight simulators and other training devices shall be used, as established in this Annex (Part-FCL).
- 7. During the proficiency check, the examiner shall verify that holders of the class or type rating maintain an adequate level of theoretical knowledge.
- 8. Should applicants choose to terminate a skill test for reasons considered inadequate by the examiner, they shall retake the entire skill test. If the test is terminated for reasons considered adequate by the examiner, only those sections not completed shall be tested in a further flight.
- 9. At the discretion of the examiner, any manoeuvre or procedure of the test may be repeated once by the applicants. The examiner may stop the test at any stage if it is considered that the applicants' demonstration of flying skill requires a complete retest.
- 10. Applicants shall be required to fly the aircraft from a position where the PIC or co-pilot functions, as relevant, can be performed. Under single-pilot conditions, the test shall be performed as if there was no other crew member present.
- During preflight preparation for the test, applicants are required to determine power settings and speeds. Applicants shall indicate to the examiner the checks and duties carried out, including the identification of radio facilities. Checks shall be completed in accordance with the checklist for the aircraft on which the test is being taken and, if applicable, with the MCC concept. Performance data for take-off, approach and landing shall be calculated by applicants in compliance with the operations manual or flight manual for the aircraft used. Decision heights/altitudes, minimum descent heights/altitudes and missed approach point shall be agreed upon with the examiner.
- 12. The examiner shall take no part in the operation of the aircraft except where intervention is necessary in the interests of safety or to avoid unacceptable delay to other traffic.

SPECIFIC RÉQUIREMENTS FOR THE SKILL TEST/PROFICIENCY CHECK FOR MULTI-PILOT AIRCRAFT TYPE RATINGS, FOR SINGLE-PILOT AEROPLANE TYPE RATINGS WHEN OPERATED IN MULTI-PILOT OPERATIONS, FOR MPL AND ATPL

- 13. The skill test for a multi-pilot aircraft or a single-pilot aeroplane when operated in multi-pilot operations shall be performed in a multi-crew environment. Another applicant or another type rated qualified pilot may function as the second pilot. If an aircraft is used, the second pilot shall be the examiner or an instructor.
- 14. Applicants shall operate as PF during all sections of the skill test, except for abnormal and emergency procedures, which may be conducted as PF or PM in accordance with MCC. Applicants for the initial issue of a multi-pilot aircraft type rating or ATPL shall also demonstrate the ability to act as PM. Applicants may choose either the left-hand or the right-hand seat for the skill test if all items can be executed from the selected seat.

Changes to legislation: There are currently no known outstanding effects for the Commission Implementing Regulation (EU) 2018/1974. (See end of Document for details)

- 15. The following matters shall be specifically checked by the examiner for applicants for the ATPL or a type rating for multi-pilot aircraft or for multi-pilot operations in a single-pilot aeroplane extending to the duties of a PIC, irrespective of whether the applicants act as PF or PM:
- (a) managing crew cooperation;
- (b) maintaining a general survey of the aircraft operation by appropriate supervision; and
- (c) setting priorities and making decisions in accordance with safety aspects and relevant rules and regulations appropriate to the operational situation, including emergencies.
- 16. The test or check should be accomplished under IFR, if the IR rating is included, and as far as possible be accomplished in a simulated commercial air transport environment. An essential element to be checked is the ability to plan and conduct the flight from routine briefing material.
- 17. When the type rating course has included less than 2 hours of flight training in the aircraft, the skill test may be conducted in an FFS and may be completed before the flight training in the aircraft.

The approved flight training shall be performed by a qualified instructor under the responsibility of:

- (a) an ATO; or
- (b) an organisation holding an AOC issued in accordance with Annex III (Part-ORO) to Regulation (EU) No 965/2012 and specifically approved for such training; or
- (c) the instructor, in cases where no aircraft flight training for SP aircraft at an ATO or AOC holder is approved, and the aircraft flight training was approved by the applicants' competent authority.

A certificate of completion of the type rating course including the flight training in the aircraft shall be forwarded to the competent authority before the new type rating is entered in the applicants' licence.

- 18. For the upset recovery training, 'stall event' means either an approach-to-stall or a stall. An FFS can be used by the ATO to either train recovery from a stall or demonstrate the type-specific characteristics of a stall, or both, provided that:
- (a) the FFS has been qualified in accordance with the special evaluation requirements in CS-FSTD(A); and
- (b) the ATO has successfully demonstrated to the competent authority that any negative transfer of training is mitigated.

B. Specific requirements for the aeroplane category PASS MARKS

1. In the case of single-pilot aeroplanes, with the exception of single-pilot high-performance complex aeroplanes, applicants shall pass all sections of the skill test or proficiency check. Failure in any item of a section will

cause applicants to fail the entire section. If they fail only one section, they shall repeat only that section. Failure in more than one section will require applicants to repeat the entire test or check. Failure in any section in the case of a retest or recheck, including those sections that have been passed on a previous attempt, will require applicants to repeat the entire test or check again. For single-pilot multi-engine aeroplanes, Section 6 of the relevant test or check, addressing asymmetric flight, shall be passed.

2. In the case of multi-pilot and single-pilot high-performance complex aeroplanes, applicants shall pass all sections of the skill test or proficiency check. Failure in more than five items will require applicants to take the entire test or check again. Applicants failing 5 or fewer items shall take the failed items again. Failure in any item on the retest or recheck, including those items that have been passed on a previous attempt, will require applicants to repeat the entire check or test again. Section 6 is not part of the ATPL or MPL skill test. If applicants only fail or do not take Section 6, the type rating will be issued without CAT II or CAT III privileges. To extend the type rating privileges to CAT II or CAT III, applicants shall pass the Section 6 on the appropriate type of aircraft.

FLIGHT TEST TOLERANCE

- 3. Applicants shall demonstrate the ability to:
- (a) operate the aeroplane within its limitations;
- (b) complete all manoeuvres with smoothness and accuracy;
- (c) exercise good judgement and airmanship;
- (d) apply aeronautical knowledge;
- (e) maintain control of the aeroplane at all times in such a manner that the successful outcome of a procedure or manoeuvre is never in doubt;
- (f) understand and apply crew coordination and incapacitation procedures, if applicable; and
- (g) communicate effectively with the other crew members, if applicable.
- 4. The following limits shall apply, corrected to make allowance for turbulent conditions and the handling qualities and performance of the aeroplane used: Height

Generally	± 100 ft
Starting a go-around at decision height/altitude	+ 50 ft/- 0 ft
Minimum descent height/MAPt/altitude	+ 50 ft/- 0 ft
Tracking	
On radio aids	± 5°

Changes to legislation: There are currently no known outstanding effects for the Commission Implementing Regulation (EU) 2018/1974. (See end of Document for details)

For 'angular' deviations	Half-scale deflection, azimuth and glide path (e.g. LPV, ILS, MLS, GLS)				
2D (LNAV) and 3D (LNAV/ VNAV) 'linear' lateral deviations	cross-track error/deviation shall normally be limited to ± $\frac{1}{2}$ of the RNP value associated with the procedure. Brief deviations from this standard up to a maximum of one time the RNP value are allowable.				
3D linear vertical deviations (e.g. RNP APCH (LNAV/VNAV) using BaroVNAV)	not more than – 75 ft below the vertical profile at any time, and not more than + 75 ft above the vertical profile at or below 1 000 ft above aerodrome level.				
Heading					
all engines operating	± 5°				
with simulated engine failure	± 10°				
Speed					
all engines operating	± 5 knots				
with simulated engine failure	+ 10 knots/– 5 knots				

CONTENT OF THE TRAINING/SKILL TEST/PROFICIENCY CHECK

- 5. Single-pilot aeroplanes, except for high-performance complex aeroplanes
- (a) The following symbols mean:

P =	Trained as PIC or co-pilot and as PF and PM
OTD =	Other training devices may be used for this exercise
X =	An FFS shall be used for this exercise; otherwise, an aeroplane shall be used if appropriate for the manoeuvre or procedure
P# =	The training shall be complemented by supervised aeroplane inspection

(b) The practical training shall be conducted at least at the training equipment level shown as (P), or may be conducted on any higher level of equipment shown by the arrow (---->).

The following abbreviations are used to indicate the training equipment used:

A =	aeroplane
FFS =	full-flight simulator
FSTD =	flight simulation training device

- (c) The starred (*) items of Section 3B and, for multi-engine, Section 6, shall be flown solely by reference to instruments if revalidation/renewal of an IR is included in the skill test or proficiency check. If the starred (*) items are not flown solely by reference to instruments during the skill test or proficiency check, and when there is no crediting of IR privileges, the class or type rating will be restricted to VFR only.
- (d) Section 3A shall be completed to revalidate a type or multi-engine class rating, VFR only, where the required experience of 10 route sectors within the previous 12 months has not been completed. Section 3A is not required if Section 3B is completed.
- (e) Where the letter 'M' appears in the skill test or proficiency check column, this will indicate a mandatory exercise or a choice where more than one exercise appears.
- (f) An FSTD shall be used for practical training for type or ME class ratings if they form part of an approved class or type rating course. The following considerations will apply to the approval of the course:
 - (i) the qualification of the FSTD as set out in the relevant requirements of Annex VI (Part-ARA) and Annex VII (Part-ORA);
 - (ii) the qualifications of the instructors;
 - (iii) the amount of FSTD training provided on the course; and
 - (iv) the qualifications and previous experience on similar types of the pilots under training.
- (g) If privileges for multi-pilot operation are sought for the first time, pilots holding privileges for single-pilot operations shall:
 - (1) complete a bridge course containing manoeuvres and procedures including MCC as well as the exercises of Section 7 using tthreat and error management (TEM), CRM and human factors at an ATO; and
 - (2) pass a proficiency check in multi-pilot operations.
- (h) If privileges for single-pilot operations are sought for the first time, pilots holding privileges for multi-pilot operations shall be trained at an ATO and checked for the following additional manoeuvres and procedures in single-pilot operations:
 - (1) for SE aeroplanes, 1.6, 4.5, 4.6, 5.2 and, if applicable, one approach from Section 3.B; and
 - (2) for ME aeroplanes, 1.6, Section 6 and, if applicable, one approach from Section 3.B.

- (i) Pilots holding privileges for both single-pilot and multi-pilot operations in accordance with points (g) and (h) may revalidate privileges for both types of operations by completing a proficiency check in multi-pilot operations in addition to the exercises referred to in points (h)(1) or (h)(2), as applicable, in single-pilot operations.
- (j) If a skill test or a proficiency check is completed in multi-pilot operations only, the type rating shall be restricted to multi-pilot operations. The restriction shall be removed when pilots comply with point (h).
- (k) The training, testing and checking shall follow the table mentioned below.
 - (1) Training at an ATO, testing and checking requirements for singlepilot privileges
 - (2) Training at an ATO, testing and checking requirements for multipilot privileges
 - (3) Training at an ATO, testing and checking requirements for pilots holding single-pilot privileges seeking multi-pilot privileges for the first time (bridge course)
 - (4) Training at an ATO, testing and checking requirements for pilots holding multi-pilot privileges seeking single-pilot privileges for the first time (bridge course)
 - (5) Training at an ATO and checking requirements for combined revalidation and renewal of single and multi-pilot privileges

Турс	(1)		(2) MP		(3) SP -		(4) MP		(5) SP +	
of	5 51		IVII		MP	→	\rightarrow S	P	MP	
	ation					ial)	(init		1,111	
_		niTigst	in F rai	nihest	in F rai	niTigst	_ \		n iSa [€,	ME
			king		king					p lære plane
							and			
								kialnge		
							(SE			
							aero	pluure	p) lane	s)
Initia	lSecti	o Sie cti	o Sie cti	o Sie cti	oMscc	Secti	ohs6,	1.6,		
issue	1-6	1-6	1-7	1-7		1-7	4.5,	Secti	on	
SP	1-7	1-7			Hum		4.6,	6		
comp	- /	1 /			facto		5.2	and,		
Comp	10/1				TEM		and,	if	1.1	
					Secti	on	if		cable,	
					7			cahte,		
							one	appro a ich m	Jacii	
								Secti	on	
							Secti		OII	
							3.B	ט, ועט		
		~ .	,	~ .	,	,		,		1.57.0
Reva	l nda tio	nSecti	o m /sa	Secti	o m /sa	n/a	n/a	n/a	MPO	:MPO:
		1–6		1-7						

ANNEX

Document Generated: 2023-10-18

Changes to legislation: There are currently no known outstanding effects for the Commission Implementing Regulation (EU) 2018/1974. (See end of Document for details)

SP	1-7 blex	1-7							Sections 1-7 1-7 SPO: SPO: 1.6, 1.6, 4.5, Section 4.6, 6 5.2 and, and, if if applicable, applicable, one approach approachin from Section 3.B Section 3.B
Rene	wFaCL.	7 54e cti 1-6	oFn€L.	7 54e 0cti 1-6	om/sa	n/a	n/a	n/a	Traini Tig aining: FCL. 740 L.740
SP	1-7 olex	1-7							CheckCheck: as as for for the the revalidation

(l) To establish or maintain PBN privileges, one approach shall be an RNP APCH. Where an RNP APCH is not practicable, it shall be performed in an appropriately equipped FSTD.

TMGs AND SINGLE-PILOT AEROPLANES, EXCEPT FOR HIGH- PERFORMANCE COMPLEX AEROPLANES			ICAL TRA	CLASS OR TYPE RATING SKILL TEST OR PROFICIENCY CHECK		
Manoeuvres/ procedures		FSTD A Instructor initials when training complete			or checked in	Examiner initials when test or check completed
SECTIO 1 1.1	Departure Preflight including: — 0		tion;			

]	weather briefing; and NOTAM.			
1.2	Pre-start checks				
1.2.1	External	OTD P#	P	M	
1.2.2	Internal	OTD P#	P	M	
1.3	Engine starting: normal malfunction	P> ons.	>	M	
1.4	Taxiing	P>	>	M	
1.5	Pre- departure checks: engine run- up (if applicable	P>	>	M	
1.6		conditions are available).	>	M	
1.7	1 1 3	P> Vx/ Vy; turns onto headings; and evel off.	>	M	
1.8	ATC liaison — compliance	P> ee,		M	

	R/T				
	procedure	s			
SECTIO	N 2				
2 2.1	Airwork (visual meteorolo conditions (VMC)) Straight and level flight at various airspeeds including flight at critically low airspeed with and without fl (including approach to V V mca when applicable)	aps	>		
2.2	Steep turns (360° left and right at 45° bank)	P>	>	M	
2.3	(ii)	P> clean stall; approach to stall in descending turn with bank with approach configurati and power;		M	

2.4	(iv)	approach to stall in landing configuration and power; and approach to stall, climbing turn with take- off flap and climb power (single- engine aeroplanes only)		M	
2.4	Handling using autopilot and flight director (may be conducted in Section 3), if applicable		>	M	
2.5	ATC liaison — complian R/T procedure		>	M	
SECTIO	N 3A			 	
3A 3A.1	En route procedure VFR (see B.5 (c) and (d)) Flight plan,	P> es	>		

3A.2 3A.3	dead reckoning and map reading Maintenar of altitude, heading and speed Orientatio timing	n &e >	>		
	and revision of ETAs				
3A.4	Use of radio navigation aids (if applicable		>		
3A.5	Flight managem (flight log, routine checks including fuel, systems and icing)	P> ent	>		
3A.6	ATC liaison — compliand R/T procedure		>		
SECTIO	N 3B				
3B 3B.1*	Instrumen flight Departure IFR		>	M	
3B.2*	En route IFR	P>	>	M	
3B.3*	Holding procedure	P> s	>	M	
3B.4*	3D operations to	P>	>	M	

	11	I	I	I	I	I
	decision					
	height/					
	altitude					
	(DH/A)					
	of 200					
	ft (60					
	m) or to					
	higher					
	minima if					
	required					
	by the approach					
	procedure					
	(autopilot					
	may be					
	used to					
	the final					
	approach					
	segment					
	vertical					
	path					
	intercept)					
3B.5*	2D	P>	>		M	
35.3	operations		-		111	
	to					
	minimum					
	descent					
	height/					
	altitude					
	(MDH/					
	A)					
3B.6*	Flight	P>	>		M	
35.0	exercises		-		111	
	including					
	simulated					
	failure					
	of the					
	compass					
	and					
	attitude					
	indicator:					
	<u> </u>	rate				
		l nama:				
		turns; and				
		and recoveries				
		from				
		unusual				
		attitudes.				
-	<u>'</u>	attitudes.				

3B.7*	Failure of localiser or glideslope	P>	>		
3B.8*	ATC liaison — compliant R/T procedure		>	M	
	Intentional left blank	lly			
SECTION	ON 4	I			
4 4.1	Arrival and landings Aerodrom arrival procedure		>	M	
4.2	Normal landing	P>	>	M	
4.3	Flapless landing	P>	>	M	
4.4	Crosswind landing (if suitable conditions		>		
4.5	Approach and landing with idle power from up to 2 000 ft above the runway (single-engine aeroplane only)		>		
4.6	Go- around from minimum height	P>	>	М	

	I I	_	1	1	T	
4.7	Night go- around	P>	>			
	and					
	landing					
	(if	`				
	applicable					
4.8		P>	>		M	
	liaison —					
	complianc R/T	С,				
	procedure	S				
SECT	_					
5	Abnormal					
	and					
	emergency					
	procedure	S				
	(This section					
	may be					
	combined					
	with					
	Sections					
	1 through					
	4.)					
5.1	Rejected	P>	>		M	
	take-					
	off at a reasonable					
	speed	,				
5.2	Simulated		P		M	
3.2	engine		1		111	
	failure					
	after					
	take-off (single-					
	engine					
	aeroplanes	3				
	only)					
5.3	Simulated		P		M	
	forced					
	landing					
	without power					
	(single-					
	engine					
	aeroplanes	3				
	only)					
				l.	l.	

5.4	Simulated	P>	>			
	emergenc	ies:				
		fire				
		or				
		smoke				
		in				
		flight;				
		and				
		systems'				
	(11)	malfunction	ne			
		as				
		appropriate				
5.5	ME	P>	>			
	aeroplane	s				
	and					
	TMG					
	training					
	only:					
	engine					
	shutdown					
	and					
	restart					
	(at a safe					
	altitude					
	if					
	performed	1				
	in the					
	aircraft)					
5.6	ATC					
3.0	liaison —					
	compliance	20				
	R/T	,				
	procedure	NC.				
OF CELC	_	3				
SECTIO	1		I		T	T
6	Simulated	P>	>X		M	
6.1*	asymmetr	ic				
	flight					
	(This					
	section					
	may be					
	combined					
	with					
	Sections					
	1					
	through					
	5.)					
	Simulated					
	engine					
	failure					
	during					
	take-off					
	June 011	I	I	I	1	1

	(at a safe altitude unless carried out in an FFS or an FNPT II)				
6.2*	Asymmet approach and go-around	rii&>	>	M	
6.3*	Asymmet approach and full-stop landing	r ii2 >	>	M	
6.4	ATC liaison — compliand R/T procedure		>	M	
SECTIO	N 7				
7	UPRT				
7.1	Flight manoeuvr and procedure				
7.1.1	Manual flight with and without flight directors (no autopilot, no autothrust autothrott and at different control laws, where applicable	le,	>		
7.1.1.1	At different speeds (including	P>	>		

	slow flight)				
	and altitudes within the FSTD training envelope.				
7.1.1.2	Steep turns using 45° bank, 180° to 360° left and right	P>	>		
7.1.1.3	Turns with and without spoilers	P>	>		
7.1.1.4	Procedura instrumen flying and manoeuvr including instrumen departure and arrival, and visual approach	ing	>		
7.2 7.2.1	_	P> cake- off configuration configuration at ow altitude;			

	_	clean configurationear maximum operating altitude; and landing configuratione			
7.2.2		qualified	X An aeroplane shall not be used for this exercise	FFS only	
7.3	Go- around with all engines operating from various stages during an instrumer approach		>		
7.4		P> from various heights below	>		

DH/		
MDH		
15		
m		
(50		
ft)		
above		
the		
runway		
threshold		
 after		
touchdown		
(baulked		
landing)		
 In		
aeroplanes		
which		
are		
not		
certificated		
as transport		
transport category		
aeroplanes (JAR/		
FAR		
25)		
or		
as commuter		
commuter		
category		
aeroplanes (SFAR		
23),		
the		
rejected		
landing		
with		
all		
engines		
operating		
shall		
be		
initiated		
below		
MDH/		
Α		
or		
after		
touchdown.		

6. Multi-pilot aeroplanes and single-pilot high-performance complex aeroplanes

Changes to legislation: There are currently no known outstanding effects for the Commission Implementing Regulation (EU) 2018/1974. (See end of Document for details)

(a) The following symbols mean:

P =	Trained as PIC or co-pilot and as PF and PM for the issue of a type rating as applicable.
OTD =	Other training devices may be used for this exercise
X =	An FFS shall be used for this exercise; otherwise an aeroplane shall be used if appropriate for the manoeuvre or procedure
P# =	The training shall be complemented by supervised aeroplane inspection

(b) The practical training shall be conducted at least at the training equipment level shown as (P), or may be conducted up to any higher equipment level shown by the arrow (---->).

The following abbreviations are used to indicate the training equipment used:

A =	aeroplane
FFS =	full-flight simulator
FSTD =	flight simulation training device

- (c) The starred items (*) shall be flown solely by reference to instruments.
- (d) Where the letter 'M' appears in the skill test or proficiency check column, this will indicate a mandatory exercise.
- (e) An FFS shall be used for practical training and testing if the FFS forms part of an approved type rating course. The following considerations will apply to the approval of the course:
 - (i) the qualifications of the instructors;
 - (ii) the qualification and the amount of training provided on the course in an FSTD; and
 - (iii) the qualifications and previous experience on similar types of the pilots under training.
- (f) Manoeuvres and procedures shall include MCC for multi-pilot aeroplane and for single-pilot high-performance complex aeroplanes in multi-pilot operations.
- (g) Manoeuvres and procedures shall be conducted in single-pilot role for single-pilot high-performance complex aeroplanes in single-pilot operations.
- (h) In the case of single-pilot high-performance complex aeroplanes, when a skill test or proficiency check is performed in multi-pilot operations, the type

Changes to legislation: There are currently no known outstanding effects for the Commission Implementing Regulation (EU) 2018/1974. (See end of Document for details)

rating shall be restricted to multi-pilot operations. If privileges of single-pilot are sought, the manoeuvres/procedures in 2.5, 3.8.3.4, 4.4, 5.5 and at least one manoeuvre/procedure from Section 3.4 have to be completed in addition as single-pilot.

- (i) In the case of a restricted type rating issued in accordance with FCL.720.A(e), applicants shall fulfil the same requirements as other applicants for the type rating except for the practical exercises relating to the take-off and landing phases.
- (j) To establish or maintain PBN privileges, one approach shall be an RNP APCH. Where an RNP APCH is not practicable, it shall be performed in an appropriately equipped FSTD.

MULTI- PILOT AEROPLANES AND SINGLE- PILOT HIGH- PERFORMANCE COMPLEX AEROPLANES				ATPL/MP RATING S TEST OR CHECK	SKILL
Manoe proced	uvresFSTD ures	A	Instructor initials when training completed	Tested or checked in FSTD or A	Examiner initials when test or check completed
SECTI	ON 1				
1.1.	OTD Flight preparation Performance calculation				
1.2.	OTD P# Aeroplane external visual inspection; location of each item and purpose of inspection	P			
1.3.	P> Cockpit inspection	>			

1.4.	P> Use	>	M	
1.1.	of			
	checklist			
	prior			
	to			
	starting			
	engines,			
	starting			
	procedures,			
	radio			
	and			
	navigation			
	equipment			
	check, selection			
	and			
	setting			
	of			
	navigation			
	and			
	communication	h		
	frequencies			
	P>	>		
1.5.	P> Taxiing			
	in			
	compliance			
	with			
	ATC			
	instructions			
	or			
	instructions			
	of instructor			
	msuuctoi			
1.6.	P>	>	M	
1.0.	Before take-			
	off			
	checks			
SECTI				
SECTI				
2	P> Take-	>		
	offs			
	27 1			
2.1.	Normal			
	take-			
	offs with			
	with different			
	flap			
	settings,			
	including			
		1		

		1	1	i
	expedited			
	take-			
	off			
2.2*	P>	>		
2.2*	Instrument			
	take-			
	off;			
	transition			
	to			
	instrument			
	flight			
	is			
	required			
	during			
	rotation			
	or			
	immediately			
	after			
	becoming			
	airborne			
	anoone			
	P> Crosswind	>		
2.3.				
	take-			
	off			
	-			
2.4.	P> Take-	>		
∠. 4 .				
	off			
	at .			
	maximum			
	take-			
	off			
	mass			
	(actual			
	or			
	simulated			
	maximum			
	take-			
	off			
	mass)			
	_ P>	>		
2.5.	Take-			
	offs			
	with			
	simulated			
	engine			
	failure:			
	ranuic.			
2.5.1*	shortly			
	after			
	reaching V2			
	V <u>/</u>			
	·	·		

(In			 	
aeroplanes				
which				
are not				
certificated				
as				
transport				
category				
or commuter				
category				
aeroplanes,				
the engine				
failure				
shall				
not be				
simulated				
until				
reaching a				
minimum				
height				
of 500 ft				
above the				
runway				
end. In				
aeroplanes				
having				
the same				
performance	e			
as a				
transport				
category				
aeroplane				
regarding				
take-off				
mass and				
density				
altitude,				
the				
instructor				
may simulate				
the engine failure				
shortly				
after				
reaching				
V2)				
	P	X	M FFS	
2.5.2* be	tween		only	
V	1			

	and				
	V2				
	P>	>X		M	
2.6.	P> Rejected				
	take-				
	off				
	at				
	a				
	reasonable				
	speed				
	before				
	reaching				
	V1				
SECTI	ON 3	1	1		L
	P>	>			
3	Flight				
	manoeuvres				
	and				
	procedures				
2 1	Manual				
3.1.	Manual				
	flight with				
	and				
	without				
	flight directors				
(no	directors				
(no	.+				
autopilo	π,				
no autothru	ist/				
autothro					
and at	ittle,				
differen	.				
control	l				
laws,					
where					
applicat	ale)				
applicat					
3.1.1.	At P>	>			
3.1.1.	At different				
	speeds				
	speeds (including				
	slow				
	flight)				
	and				
	altitudes				
	within				
	the				
	FSTD				
	training				
	envelope				
	onvoiope				

3.1.2.	P> Steep turns using 45° bank, 180° to 360° left and right	>		
3.1.3.	P> Turns with and without spoilers	>		
3.1.4.	P> Procedural instrument flying and manoeuvring including instrument departure and arrival, and visual approach	>		
3.2.	P> Tuck under and Mach buffets (if applicable), and other specific flight characteristics of the aeroplane (e.g. Dutch Roll)	>X An aeroplane shall not be used for this exercise	FFS only	

3.3.	OTD Normal > operation of systems and controls engineer's panel (if applicable)	>		
3.4.	Normal and abnormal operations of following systems:		M	A mandatory minimum of 3 abnormal items shall be selected from 3.4.0 to 3.4.14 inclusive
3.4.0.	OTD Ensine > (if necessary propeller)	>		
3.4.1.	OTD Pressurisation and air conditioning	>		
3.4.2.	OTD Pitot/	>		
3.4.3.	OTD Fuel> system	>		
3.4.4.	OTD Ele <u>ptrical</u> system	>		
3.4.5.	OTD Hydraulic system	>		
3.4.6.	OTD Flight > control and trim system	>		

3.4.7.	OTD Anti> icing/ de- icing system, glare shield heating	>		
3.4.8.	OTD Autopilot/ flight director	>	M (single pilot only)	
3.4.9.	oTD Stapl> warning devices or stall avoidance devices, and stability augmentation devices	>		
3.4.10.	P> Ground proximity warning system, weather radar, radio altimeter, transponder	>		
3.4.11.	OTD Ractios, > navigation equipment, instruments, FMS	>		
3.4.12.	OTD Landing gear and brake	>		
3.4.13.	OTD Slat and flap system	>		

	OTD	>			
3.4.14.	OTD Au <u>piliary</u>				
	power				
	unit				
	(APU)				
Intentio	nolly				
left blan	lK				
				M	A
3.6.	Abnormal			IVI	
5.0.	and				mandatory
					minimum
	emergency				of 3 items
	procedures:				shall be
					selected
					from 3.6.1
					to 3.6.9
					inclusive
			-		
2 (1	P>	>			
3.6.1.	Fire				
	drills,				
	e.g.				
	engine,				
	APU,				
	cabin,				
	cargo				
	compartment,				
	flight				
	deck,				
	wing				
	and				
	electrical				
	fires				
	including				
	evacuation				
3.6.2.	P>	>			
3.0.2.	Smoke				
	control				
	and				
	removal				
			-		
2 (2	P> Engine	>			
3.6.3.					
	failures,				
	shutdown				
	and				
	restart				
	at				
	a				
	safe				
	height				
			<u> </u>		

3.6.4.	P> Fuel dumping (simulated)	>		
3.6.5.	P Wind shear at take- off/ landing	X	FFS only	
3.6.6.	P> Simulated cabin pressure failure/ emergency descent	>		
3.6.7.	P> Incapacitation of flight crew member	>		
3.6.8.	P> Other emergency procedures as outlined in the appropriate aeroplane flight manual (AFM)	>		
3.6.9.	OTD TCAS_> event	An aeroplane shall not be used	FFS only	
3.7.	P Upsets recoveryied traininghe	X An aeroplane shall not		
3.7.1.	Retraining from the stall stall events in:	be used for this exercise		

_	take-			
	off configuration;			
_	clean configuration			
_	at low altitude; clean configuration near maximum operating			
	altitude; and			
_	landing configuration.			
3.7.2.	P TheFFS	X An	FFS only	
_	tollowinged upset the exercises:	aeroplane shall not be used for this		
	recovery from nose-	exercise		
	high at			
	various bank			
	angles; and			
_	recovery from			
	nose- low			
	at various			
	bank angles			
3.8.	Instrument flight procedures			
3.8.1*	P> Adherence	>	M	
	to departure			
	and arrival			
	routes			
	and			

Changes to legislation: There are currently no known outstanding effects for the Commission Implementing Regulation (EU) 2018/1974. (See end of Document for details)

				i
	ATC			
	instructions			
	P>	>		
3.8.2*	P> Holding			
	procedures			
3.8.3*	3D			
	operations			
	to			
	DH/			
	A			
	of			
	200			
	ft			
	(60			
	m)			
	or			
	to			
	higher			
	minima			
	if			
	required			
	by			
	the			
	approach			
	procedure			

Note: According to the AFM, RNP APCH procedures may require the use of autopilot or flight director. The procedure to be flown manually shall be chosen taking into account such limitations (for example, choose an ILS for 3.8.3.1 in the case of such AFM limitation).

3.8.3.1*	P> Manually, without flight director	>	M (skill test only)
3.8.3.2*	P> Manually, with flight director	>	
3.8.3.3*	P> With autopilot	>	
3.8.3.4*	P> Manually, with one engine simulated inoperative; engine	>	M

failure has to be simulated during final approach before passing 000 ft above aerodrome level until touchdown or through the complete missed approach procedure. In aeroplanes which are not certificated as transport category aeroplanes (JAŔ/ FAR 25) or as commuter category aeroplanes (SFAR 23), the approach with simulated engine failure and the

ensuing		
go-		
around		
shall		
be		
initiated		
in		
conjunction		
with		
the		
non-		
precision		
approach		
as		
described		
in 3.8.4.		
The		
go-		
around		
shall		
be		
initiated		
when		
reaching		
the		
published		
obstacle		
clearance		
height/		
altitude		
(OCH/		
A);		
however,		
not		
later		
than		
reaching		
an MDH/		
MDH/		
A		
of		
500		
ft		
above		
the		
runway		
threshold		
elevation.		
In		
aeroplanes		
having		
the		
same		
·	,	

p	erformance			
a				
a				
	ansport			
	ategory			
al r	eroplane			
16	egarding			
lč	ake- ff			
	nass			
	nd			
	ensity			
	ltitude,			
	ne			
	nstructor			
n	nay			
	imulate			
	ne l			
e	ngine			
fa	ailure			
ir	ı			
a	ccordance			
W	/ith			
3	.8.3.4.			
			3.6	
3 8 3 5 * N	P> Manually	>	M	
3.8.3.5.* N	IP> Ianually,	>	1V1	
W	/ith	>	IVI	
W O	vith ne	>	IVI	
w o ei	vith ne ngine	>	IVI	
w o e si	vith ne ngine imulated	>	IVI	
w o er si ir	rith ne ngine imulated noperative;	>	IVI	
w o er si ir er	rith ne ngine imulated noperative; ngine	>	IVI	
w o e si ir er fa	rith ne ngine imulated noperative; ngine ailure	>	IVI	
w o e si ir e fa h	rith ne ngine imulated noperative; ngine ailure as	>	IVI	
w o er si ir e fa h	rith ne ngine ngine imulated noperative; ngine ailure as	>	IVI	
w o en si ir en fa h to b	rith ne ngine imulated noperative; ngine ailure as	>	IVI	
w o en si ir en fa h to b	rith ne ngine imulated noperative; ngine ailure as o e	>	IVI	
w o en si ir en fa h to b	rith ne ngine imulated noperative; ngine ailure as o e imulated uring	>	IVI	
woo ei si ir ei fa h to b si d	rith ne ngine imulated noperative; ngine ailure as o e imulated uring inal	>	IVI	
w o e si ir e fa h to b si d fi	rith ne ngine imulated noperative; ngine ailure as o e imulated uring inal pproach	>	IVI	
woo er si ir er fa h to b si d fi ap	rith ne ngine imulated noperative; ngine ailure as o e imulated uring inal pproach fter	>	IVI	
w o en si ir en fa h to b si d fi a p	rith ne ngine imulated noperative; ngine ailure as o e imulated uring inal pproach fter assing	>	IVI	
woo en si ir en fa h to b si d fi ap th	rith ne ngine imulated noperative; ngine ailure as o e imulated uring inal pproach fter assing ne	>	IVI	
woo en si ir en fa h to b si d fii ap th	rith ne ngine imulated noperative; ngine ailure as o e imulated uring inal pproach fter assing ne uter	>	IVI	
woo en si ir en fa h to b si d fi ap th o m	rith ne ngine imulated noperative; ngine ailure as o e imulated uring inal pproach fter assing ne uter narker	>	IVI	
woo en si ir en fa h to b si d fi an p th o m	rith ne ngine imulated noperative; ngine ailure as o e imulated uring inal pproach fter assing ne uter narker OM)	>	IVI	
woo en si ir en fa h to b si d fi an p th o m	rith ne ngine imulated noperative; ngine ailure as o e imulated uring inal pproach fter assing ne uter narker	>	IVI	
woodersising ending and	rith ne ngine imulated noperative; ngine ailure as o e imulated uring inal pproach fter assing ne uter narker OM)	>	IVI	
woodersiiren en siiren en	rith ne ngine imulated noperative; ngine ailure as o e imulated uring inal pproach fter assing ne uter narker OM) rithin	>	IVI	
woodersising ending and	rith ne ngine imulated noperative; ngine ailure as o e imulated uring inal pproach fter assing ne uter narker OM) rithin	>	IVI	
woo en si ir en fa h to b si d fii ap ar p th o m (() w a a d o o	rith ne ngine imulated noperative; ngine ailure as o e imulated uring inal pproach fter assing ne uter narker OM) rithin	>	IVI	
woo en si ir	rith ne ngine imulated noperative; ngine ailure as o e imulated uring inal pproach fter assing ne uter narker OM) vithin istance f	>	IVI	
woo en si ir	rith ne ngine imulated noperative; ngine ailure as o e imulated uring inal pproach fter assing ne uter narker OM) rithin istance f ot	>	IVI	

4			
NM			
until			
touchdown			
or			
through			
the			
complete			
missed			
approach			
procedure			
In			
aeroplanes			
which			
are not			
certificated			
as			
transport			
category			
aeroplanes			
(JAR/FAR			
25) or as			
commuter			
category aeroplanes			
(SFAR			
23), the			
approach			
with			
simulated			
engine			
failure			
and the			
ensuing			
go-around			
shall be			
initiated in			
conjunction			
with the			
non-			
precision			
approach			
as			
described			
in 3.8.4.			
The go-			
around			
shall be			
initiated			
when			
reaching			
the			
published			
puonsneu		ļ	

OCH/A; however				
not later than reaching				
an MDH A of 500 above the	ft			
runway threshold elevation	i			
In aeroplan having				
the same performa as a				
transport category				
aeroplan regarding take-off	g			
mass and density altitude,	1			
the instructo may	r			
simulate the engir failure in	1			
accordan with 3.8.3.4.	ace			
3.8.4*	P*> 2D operations	>	M	
	down to			
	the MDH/ A			
3.8.5.	P*> Circling approach	>		
	under the following			
(a)*	conditions: approach to			
	the			

	authorised		
	minimum		
	circling		
	approach		
	altitude		
	at		
	the		
	aerodrome		
	in		
	question		
	in		
	accordance		
	with		
	the		
	local		
	instrument		
	approach		
	facilities		
	in		
	simulated		
	instrument		
	flight		
	conditions;		
	followed		
	by:		
(b)	circling		
(-)	approach		
	to		
	another		
	runway		
	at		
	least		
	90°		
	off		
	centreline		
	from		
	the		
	final		
	approach		
	used		
	in		
	item		
	(a),		
	at		
	the		
	authorised		
	minimum		
	circling		
	approach		
	altitude.		
Remark:			
If (a) and			
(b) are no			
(-)	ı		ı

possible	;				
due to					
ATC					
reasons,	a				
simulate					
low					
visibilit	v				
pattern	,				
may be					
perform	ed				
репопп					
206	P> Visual	>			
3.8.6.					
	approaches				
SECTI	ON 4				
_	3.6:				
4	Missed				
	approach				
	procedures				
	P*>	>			
4.1.	Go-				
	around				
	with				
	all				
	engines				
	operating*				
	during				
	a				
	3D				
	operation				
	on				
	reaching				
	decision				
	height				
	P*>	>			
4.2.	Go-				
	around				
	with				
	all				
	engines				
	operating*				
	from				
	various				
	stages				
	during				
	an				
	instrument				
	approach				
4.3.	P*> Other	>			
1.5.	missed				
	11115500	I	I	1	I

approach procedures P*> 4.4* Manual go-around with the critical engine simulated inoperative after an instrument approach on reaching DH, MDH or MAPt 4.5. Rejected landing with all engines operating:	
P*> 4.4* Manual go- around with the critical engine simulated inoperative after an instrument approach on reaching DH, MDH or MAPt P> 4.5. Rejected landing with all engines	
4.4* Manual go- around with the critical engine simulated inoperative after an instrument approach on reaching DH, MDH or MAPt P> 4.5. Rejected landing with all engines	
4.4* Manual go- around with the critical engine simulated inoperative after an instrument approach on reaching DH, MDH or MAPt 4.5. Rejected landing with all engines	
go- around with the critical engine simulated inoperative after an instrument approach on reaching DH, MDH or MAPt 4.5. Rejected landing with all engines	
around with the critical engine simulated inoperative after an instrument approach on reaching DH, MDH or MAPt P> 4.5. Rejected landing with all engines	
with the critical engine simulated inoperative after an instrument approach on reaching DH, MDH or MAPt P> 4.5. Rejected landing with all engines	
the critical engine simulated inoperative after an instrument approach on reaching DH, MDH or MAPt 4.5. Rejected landing with all engines	
critical engine simulated inoperative after an instrument approach on reaching DH, MDH or MAPt P> 4.5. Rejected landing with all engines	
engine simulated inoperative after an instrument approach on reaching DH, MDH or MAPt P> 4.5. Rejected landing with all engines	
simulated inoperative after an instrument approach on reaching DH, MDH or MAPt P> 4.5. Rejected landing with all engines	
simulated inoperative after an instrument approach on reaching DH, MDH or MAPt P> 4.5. Rejected landing with all engines	
inoperative after an instrument approach on reaching DH, MDH or MAPt P> Rejected landing with all engines	
after an instrument approach on reaching DH, MDH or MAPt P> 4.5. Rejected landing with all engines	
an instrument approach on reaching DH, MDH or MAPt P> 4.5. Rejected landing with all engines	
instrument approach on reaching DH, MDH or MAPt P> 4.5. Rejected landing with all engines	
approach on reaching DH, MDH or MAPt P> 4.5. Rejected landing with all engines	
on reaching DH, MDH or MAPt P> 4.5. Rejected landing with all engines	
reaching DH, MDH or MAPt P> 4.5. Rejected landing with all engines	
DH, MDH or MAPt P> 4.5. Rejected landing with all engines	
DH, MDH or MAPt P> 4.5. Rejected landing with all engines	
MDH or MAPt P> 4.5. Rejected landing with all engines	
or MAPt P> 4.5. Rejected landing with all engines	
MAPt P> 4.5. Rejected landing with all engines	
P> 4.5. Rejected landing with all engines	
4.5. Rejected landing with all engines	
landing with all engines	
with all engines	
all engines	
engines	
engines	
— from	
various	
heights	
below	
DH/	
MDH;	
— after	
touchdown	
(baulked	
landing)	
In In	
aeroplanes	
which	
are not	
certificated	
as	
transport	
category	
aeroplanes	
(JAR/FAR	
25) or as	
commuter	
category	

aeroplan (SFAR 23), the rejected landing with all engines operating shall be initiated below MDH/A or after touchdo SECTI	ng I own.			
5	P Landings			
5.1.	Normal landings* with visual reference established when reaching DA/H following an instrument approach operation			
5.2.	P> Landing with simulated jammed horizontal stabiliser in any out- of- trim position	An aeroplane shall not be used for this exercise	FFS only	
5.3.	P> Crosswind landings (aircraft, if practicable)	>		

5.4.	P> Traffic pattern and landing without extended or with partly extended flaps and slats	>		
5.5.	P> Landing with critical engine simulated inoperative	>	M	
5.6.	P Landing with two engines inoperative:	X	M FFS only (skill test only)	
	aeroplanes with three engines: the centre engine and one outboard engine as far as practicable according to data of the AFM; and aeroplanes			
	with four			

ANNEX

Document Generated: 2023-10-18

Changes to legislation: There are currently no known outstanding effects for the Commission Implementing Regulation (EU) 2018/1974. (See end of Document for details)

engines: two		
two		
engines at		
at		
one		
one side		

General remarks:

Special requirements for the extension of a type rating for instrument approaches down to a decision height of less than 200 ft (60 m), i.e. CAT II/III operations.

II/III operations.	_		
SECTION 6			
Additional			
authorisation			
on a type			
rating for			
instrument			
approaches			
down to			
a DH of			
less than			
60 m (200			
ft) (CAT			
II/III)			
The			
following			
manoeuvres and			
procedures			
are the			
minimum			
training			
requirements			
to permit			
instrument			
approaches			
down to a			
DH of less			
than 60 m			
(200 ft).			
During the			
following			
instrument			
approaches			
and			
missed			
approach			
procedures,			
all			
aeroplane			
equipment			
required for type			
for type			

certification of instrument approaches down to a DH of less than 60 m (200 ft) shall be used.				
6.1* Rejectake- off at minii	mum orised ay il	An aeroplane shall not be used for this exercise	M*	
6.2* CAT II/ III	oaches:		M	

shall be observed.				
obscivcu.				
6.3* Go		>	M*	
	ound:			
after				
approaches				
as				
indicated				
in 6.2 on				
reaching				
DH.				
The				
training				
shall also				
include a				
go-around				
due to				
(simulated)				
insufficient				
RVR,				
wind				
shear,				
aeroplane				
deviation				
in excess				
of				
approach				
limits for a				
successful				
approach,				
ground/				
airborne				
equipment				
failure				
prior to				
reaching				
DH, and				
go-around				
with				
simulated				
airborne				
equipment				
failure.				
	P>	>	M	
6.4* La	P> inding(s):		171	
with visual				
reference				
established				
at DH				
following				
an				
	II.	1	l .	l .

Changes to legislation: There are currently no known outstanding effects for the Commission Implementing Regulation (EU) 2018/1974. (See end of Document for details)

instrument approach. Depending on the specific flight guidance system, an automatic landing shall be			
performed.			

NOTE: CAT II/III operations shall be performed in accordance with the applicable air operations requirements.

7. Class ratings — sea

Section 6 shall be completed to revalidate a multi-engine class rating sea, VFR only, where the required experience of 10 route sectors within the previous 12 months has not been completed.

CLASS RATING SEA		PRACTICAL TRAINING	CLASS RATING SKILL TEST OR PROFICIENCY CHECK	
Manoeuvres/procedures			Instructor's initials when training completed	Examiner's initials when test completed
SECT	TON 1			
1	Departure			
1.1. — — —	Preflight including: documentation; mass and balance; weather briefing; and NOTAM.			
1.2. Pre-start checks External/internal				
1.3. Engine start-up and shutdown Normal malfunctions				
1.4.	Taxiing			
1.5.	Step taxiin	g		
1.6.	Mooring:	Beach Jetty pier		

	Buoy	
1.7.	Engine-off sailing	
1.8. Engine r	Pre-departure checks: un-up (if applicable)	
1.9. —	Take-off procedure: normal with flight manual flap settings; and crosswind (if conditions are available).	
1.10. —	Climbing: turns onto headings level off	
1.11.	ATC liaison — compliance, R/T procedures	
SECTION	ON 2	
2	Airwork (VFR)	
2.1.	Straight and level flight at various airspeeds including flight at critically low airspeed with and without flaps (including approach to VMCA when applicable)	
2.2.	Steep turns (360° left and right at 45° bank)	
2.3. (i) (ii) (iii) (iv)	Stalls and recovery: clean stall; approach to stall in descending turn with bank with approach configuration and power; approach to stall in landing configuration and power; and approach to stall, climbing turn with take-off flap and climb power (single-engine aeroplanes only).	
2.4.	ATC liaison — compliance, R/ T procedures	
SECTION	ON 3	
3	En route procedures VFR	

3.1.	Flight plan, dead reckoning and map reading	
3.2.	Maintenance of altitude, heading and speed	
3.3.	Orientation, timing and revision of ETAs	
3.4.	Use of radio navigation aids (if applicable)	
3.5.	Flight management (flight log, routine checks including fuel, systems and icing)	
3.6.	ATC liaison — compliance, R/T procedures	
SECTI	ON 4	
4	Arrivals and landings	
4.1.	Aerodrome arrival procedure (amphibians only)	
4.2.	Normal landing	
4.3.	Flapless landing	
4.4.	Crosswind landing (if suitable conditions)	
4.5.	Approach and landing with idle power from up to 2 000' above the water (single-engine aeroplanes only)	
4.6.	Go-around from minimum height	
4.7. Rough v	Glassy water landing vater landing	
4.8.	ATC liaison — compliance, R/ T procedures	
SECTI	ON 5	
5	Abnormal and emergency procedures	

ANNEX

Document Generated: 2023-10-18

Changes to legislation: There are currently no known outstanding effects for the Commission Implementing Regulation (EU) 2018/1974. (See end of Document for details)

	etion may be combined with 1 through 4.)	
5.1.	Rejected take-off at a reasonable speed	
5.2.	Simulated engine failure after take-off (single-engine aeroplanes only)	
5.3.	Simulated forced landing without power (single-engine aeroplanes only)	
5.4. (i) (ii)	Simulated emergencies: fire or smoke in flight; and systems' malfunctions as appropriate.	
5.5.	ATC liaison — compliance, R/T procedures	
SECTION	ON 6	
,	Simulated asymmetric flight etion may be combined with 1 through 5.)	
6.1.	Simulated engine failure during take-off (at a safe altitude unless carried out in an FFS and an FNPT II)	
6.2.	Engine shutdown and restart (ME skill test only)	
6.3.	Asymmetric approach and go- around	
6.4.	Asymmetric approach and full- stop landing	
6.5.		

C. Specific requirements for the helicopter category

1. In the case of skill test or proficiency check for type ratings and the ATPL, applicants shall pass Sections 1 to 4 and 6 (as applicable) of the skill test or proficiency check. Failure in more than five items will require applicants to repeat the entire test or check. Applicants failing not more than five items shall repeat the failed items. Failure in any item in the case of a retest

- or a recheck or failure in any other items already passed will require the applicants to repeat the entire test or check again. All sections of the skill test or proficiency check shall be completed within 6 months.
- 2. In the case of proficiency check for an IR, applicants shall pass Section 5 of the proficiency check. Failure in more than 3 items will require applicants to repeat the entire Section 5. Applicants failing not more than 3 items shall repeat the failed items. Failure in any item in the case of a recheck or failure in any other items of Section 5 already passed will require applicants to repeat the entire check.

FLIGHT TEST TOLERANCE

- 3. Applicants shall demonstrate the ability to:
- (a) operate the helicopter within its limitations;
- (b) complete all manoeuvres with smoothness and accuracy;
- (c) exercise good judgement and airmanship;
- (d) apply aeronautical knowledge;
- (e) maintain control of the helicopter at all times in such a manner that the successful outcome of a procedure or manoeuvre is never in doubt;
- (f) understand and apply crew coordination and incapacitation procedures, if applicable; and
- (g) communicate effectively with the other crew members, if applicable.
- 4. The following limits shall apply, corrected to make allowance for turbulent conditions and the handling qualities and performance of the helicopter used.
- (a) IFR flight limits

Height

Generally	± 100 ft
Starting a go-around at decision height/altitude	+ 50 ft/- 0 ft
Minimum descent height/ MAPt/altitude	+ 50 ft/- 0 ft
MAPVaintude T. 1:	

Tracking

On radio aids	± 5°
For 'angular' deviations	Half-scale deflection, azimuth and glide path (e.g. LPV, ILS, MLS, GLS)
2D (LNAV) and 3D (LNAV/ VNAV) 'linear' lateral deviations	cross-track error/deviation shall normally be limited to ± 1/2 of the RNP value associated
	with the procedure. Brief

	deviations from this standard up to a maximum of one time the RNP value are allowable.
3D linear vertical deviations (e.g. RNP APCH (LNAV/ VNAV) using BaroVNAV)	not more than – 75 ft below the vertical profile at any time, and not more than + 75 ft above the vertical profile at or below 1 000 ft above aerodrome level.
Heading	
all engines operating	± 5°
with simulated engine failure	± 10°
Speed	
all engines operating	± 5 knots
with simulated engine failure	+ 10 knots/– 5 knots

(b) VFR flight limits

Height	
Generally	± 100 ft
Heading	
Normal operations	± 5°
Abnormal operations/emergencies	± 10°
Speed	
Generally	± 10 knots
With simulated engine failure	+ 10 knots/– 5 knots
Ground drift	
T.O. hover I.G.E.	± 3 ft
Landing	± 2 ft (with 0 ft rearward or lateral flight)

CONTENTENERAL
OF THE
TRAINING/
SKILL
TEST/
PROFICIENCY
CHECK

P

5. The following symbol means:

= Trained as PIC for the issue of a type rating for singlepilot helicopters (SPH) or trained as PIC or co-pilot and

as PF and PM for the issue of a type rating for multi pilot helicopters (MPH).

6. The practical training shall be conducted at least at the training equipment level shown as (P), or may be conducted up to any higher equipment level shown by the arrow (---->).

The following abbreviations are used to indicate the training equipment used:

FFS =	full-flight simulator
FTD =	flight training device
H =	helicopter

- 7. The starred items (*) shall be flown in actual or simulated IMC, only by applicants wishing to renew or revalidate an IR(H) or extend the privileges of that rating to another type.
- 8. Instrument flight procedures (Section 5) shall be performed only by applicants wishing to renew or revalidate an IR(H) or extend the privileges of that rating to another type. An FFS or an FTD 2/3 may be used for this purpose.
- 9. Where the letter 'M' appears in the skill test or proficiency check column, this will indicate a mandatory exercise.
- 10. An FSTD shall be used for practical training and testing if the FSTD forms part of a type rating course. The following considerations will apply to the course:
- the qualification of the FSTD as set out in the relevant requirements of Annex VI (Part-ARA) and Annex VII (Part-ORA);
- (b) the qualifications of the instructor and examiner;
- (c) the amount of FSTD training provided on the course;
- (d) the qualifications and previous experience in similar types of the pilots under training; and
- (e) the amount of supervised flying experience provided after the issue of the new type rating.

MULTI-PILOT HELICOPTERS

- 11. Applicants for the skill test for the issue of the multi-pilot helicopter type rating and ATPL(H) shall pass only Sections 1 to 4 and, if applicable, Section 6
- 12. Applicants for the revalidation or renewal of the multi-pilot helicopter type rating proficiency check shall pass only Sections 1 to 4 and, if applicable, Section 6.

SINGLE/	PRACTICAL TRAINING	SKILL TEST OR
MULTI-PILOT		PROFICIENCY
HELICOPTERS		CHECK

Manoeuvres/ procedures		FSTD	Н	Instructor initials when training completed	Checked in FSTD or H	Examiner initials when test completed
SECT	ION 1 — Prefli	ght prepar	ations and c	hecks		
1.1	Helicopter exterior visual inspection; location of each item and purpose of inspection		P		M (if performed in the helicopter)	
1.2	Cockpit inspection	P	>		M	
1.3	Starting procedures radio and navigation equipment check, selection and setting of navigation and communica frequencies	ation	>		M	
1.4	Taxiing/ air taxiing in compliance with ATC instructions or with instructions of an instructor		>		M	
1.5	Pre- take-off procedures and checks	P	>		M	
SECT	ION 2 — Fligh	t manoeuvr	es and proc	edures		
2.1	Take-offs (various profiles)	P	>		M	

2.2	Sloping ground or crosswind take- offs & landings	P	>		
2.3	Take- off at maximum take- off mass (actual or simulated maximum take-off mass)	P	>		
2.4	Take- off with simulated engine failure shortly before reaching TDP or DPATO	P	>	M	
2.4.1	Take- off with simulated engine failure shortly after reaching TDP or DPATO	P	>	M	
2.5	Climbing and descending turns to specified headings	P	>	M	
2.5.1	Turns with 30° bank, 180° to 360° left and right, by sole reference	P	>	М	

	to instruments	}					
2.6	Autorotativ descent	ď	>		M		
2.6.1	For single-engine helicopters (SEH) autorotative landing or for multi-engine helicopters (MEH) power recovery		>		M		
2.7	Landings, various profiles	P	>		M		
2.7.1	Go- around or landing following simulated engine failure before LDP or DPBL	P	>		M		
2.7.2	Landing following simulated engine failure after LDP or DPBL	P	>		M		
SECTION 3 — Normal and abnormal operations of the following systems and procedures							
3	Normal and abnormal operations of the following systems and procedures:				M	A mandatory minimum of 3 items shall be selected from this section	
3.1	Engine	P	>				

director 3.10 Stability P> augmentation devices 3.11 Weather P radar, radio altimeter, transponder 3.12 Area navigation system director > 3.10 Stability P> augmentation devices >
3.11 Weather radar, radio altimeter, transponder 3.12 Area navigation system
radar, radio altimeter, transponder 3.12 Area navigation system P>
navigation system
· · · · · · · · · · · · · · · · · · ·
3.13 Landing P>
system 2.14 APIL P
3.14 APU P>
7 16 Dadia D S
3.15 Radio, navigation equipment, instruments and FMS

4	Abnormal and emergency procedures			M	A mandatory minimum of 3 items shall be selected from this section
4.1	Fire drills (including evacuation if applicable)	P	>		
4.2	Smoke control and removal	P	>		
4.3	Engine failures, shutdown and restart at a safe height	P	>		
4.4	Fuel dumping (simulated)	P	>		
4.5	Tail rotor control failure (if applicable)	P	>		
4.5.1	Tail rotor loss (if applicable)	P	A helicopter shall not be used for this exercise		
4.6	Incapacitat of crew member — MPH only	đh	>		
4.7	Transmission malfunction		>		
4.8	Other emergency procedures as outlined in the	P	>		

	appropriate flight manual					
SECTION simulated	5 — Instru	ıment flight	procedure	s (to be perf	formed in I	MC or
5.1	Instrument take-off: transition to instrument flight is required as soon as possible after becoming airborne	P*	>*			
5.1.1	Simulated engine failure during departure	P*	>*		M*	
5.2	Adherence to departure and arrival routes and ATC instructions		>*		M*	
5.3	Holding procedures	P*	>*			
5.4	3D operations to DH/A of 200 ft (60 m) or to higher minima if required by the approach procedure	P*	>*			
5.4.1	Manually, without flight director. Note: According	P*	>*		M*	

	to the AFM, RNP APCH procedures may require the use of autopilot or flight director. The procedure to be flown manually shall be chosen taken into account such limitations (for example, choose an ILS for 5.4.1 in the case of such AFM limitation).				
5.4.2	Manually, with flight director	P*	>*	M*	
5.4.3	With coupled autopilot	P*	>*		
5.4.4	Manually, with one engine simulated inoperative engine failure has to be simulated during final approach before passing	P*	>*	M*	

	1 000 ft above aerodrome level until touchdown or until completion of the missed approach procedure				
5.5	2D operations down to the MDA/	P*	>*	M*	
5.6	Go- around with all engines operating on reaching DA/H or MDA/ MDH	p*	>*		
5.6.1	Other missed approach procedures	P*	>*		
5.6.2	Go- around with one engine simulated inoperative on reaching DA/H or MDA/ MDH	P*	>*	M*	
5.7	IMC autorotation with power recovery	P* 1	>*	M*	
5.8	Recovery from	P*	>*	M*	

Changes to legislation: There are currently no known outstanding effects for the Commission Implementing Regulation (EU) 2018/1974. (See end of Document for details)

	unusual attitudes					
SECTION 6 — Use of optional equipment						
6	Use of optional equipment	P	>			

D. Specific requirements for the powered-lift aircraft category

1. In the case of skill tests or proficiency checks for powered-lift aircraft type ratings, applicants shall pass Sections 1 to 5 and 6 (as applicable) of the skill test or proficiency check. Failure in more than five items will require applicants to repeat the entire test or check. Applicants failing not more than five items shall repeat the failed items. Failure in any item in the case of a retest or a recheck or failure in any other items already passed will require applicants to repeat the entire test or check. All sections of the skill test or proficiency check shall be completed within 6 months.

FLIGHT TEST TOLERANCE

- 2. Applicants shall demonstrate the ability to:
- (a) operate the powered-lift aircraft within its limitations;
- (b) complete all manoeuvres with smoothness and accuracy;
- (c) exercise good judgement and airmanship;
- (d) apply aeronautical knowledge;
- (e) maintain control of the powered-lift aircraft at all times in such a manner that the successful outcome of a procedure or manoeuvre is never in doubt;
- (f) understand and apply crew coordination and incapacitation procedures; and
- (g) communicate effectively with the other crew members.
- 3. The following limits shall apply, corrected to make allowance for turbulent conditions and the handling qualities and performance of the powered-lift aircraft used.

(a) IFR flight limits

Height	
Generally	± 100 ft
Starting a go-around at decision height/altitude	+ 50 ft/- 0 ft
Minimum descent height/altitude	+ 50 ft/- 0 ft
Tracking	
On radio aids	± 5°
Precision approach	half-scale deflection, azimuth and glide path

ANNEX

Document Generated: 2023-10-18

Changes to legislation: There are currently no known outstanding effects for the Commission Implementing Regulation (EU) 2018/1974. (See end of Document for details)

Heading	
Normal operations	± 5°
Abnormal operations/emergencies	± 10°
Speed	
Generally	± 10 knots
With simulated engine failure	+ 10 knots/– 5 knots

(b) VFR flight limits:

Height	
Generally	± 100 ft
Heading	
Normal operations	± 5°
Abnormal operations/emergencies	± 10°
Speed	
Generally	± 10 knots
With simulated engine failure	+ 10 knots/– 5 knots
Ground drift	
T.O. hover I.G.E.	± 3 ft
Landing	± 2 ft (with 0 ft rearward or lateral flight)

CONTENT OF THE TRAINING/SKILL TEST/PROFICIENCY CHECK

4. The following symbol means:

P = Trained as PIC or co-pilot and as PF and PM for the issue of a type rating as applicable

- 5. The practical training shall be conducted at least at the training equipment level shown as (P), or may be conducted up to any higher equipment level shown by the arrow (---->).
- 6. The following abbreviations are used to indicate the training equipment used:

FFS =	full-flight simulator
FTD =	flight training device
OTD =	other training device
PL =	powered-lift aircraft

(a) Applicants for the skill test for the issue of the powered-lift aircraft type rating shall pass Sections 1 to 5 and, if applicable, Section 6.

...) NO 1178/2011... ANNEX

Document Generated: 2023-10-18

- (b) Applicants for the revalidation or renewal of the powered-lift aircraft type rating proficiency check shall pass Sections 1 to 5 and, if applicable, Section 6 and/or Section 7.
- (c) The starred items (*) shall be flown solely by reference to instruments. If this condition is not met during the skill test or proficiency check, the type rating will be restricted to VFR only.
- 7. Where the letter 'M' appears in the skill test or proficiency check column, this will indicate a mandatory exercise.
- 8. FSTDs shall be used for practical training and testing if they form part of an approved type rating course. The following considerations will apply to the approval of the course:
- (a) the qualification of the FSTDs as set out in the relevant requirements of Annex VI (Part-ARA) and Annex VII (Part-ORA); and
- (b) the qualifications of the instructor.

POWERED-		PRAC	TICAL	TRAIN	ING		SKILI		
LIFT							TEST	OR	
AIRC	RAFT						PROF	ICIENC	Y
CATE	GORY						CHEC	CK	
Mano	euvres/	OTD	FTD	FFS	PL	Instru	ct6Heck	e Œ xamir	ier's
proced	lures					initials	in	initials	
-						when	FFS	when	
						trainir	ngPL	test	
						compl		comple	ted
SECT	ION 1 —	- Preflig	ht prep	arations	and ch		I.		
1.1	Powere				P				
	lift								
	aircraft								
	exterior								
	visual								
	inspecti	on;							
	location	l							
	of								
	each								
	item								
	and								
	purpose	,							
	of								
	inspecti	on							
1.2	Cockpit	· P	>	>	>				
1.2	inspecti								
	•						3.6		
1.3	Starting		>	>	>		M		
	procedu	ires,							
	radio								
	and								
	navigati								
	equipm	ent							

	check, selection and setting of navigation and communifrequent	ion nication						
1.4	Taxiing in complia with ATC instruct or with instruct of an instruct	ions	P	>	>			
1.5	Pre- take- off procedu and checks includir power check		>	>	>		M	
SECT	ION 2 —	- Flight	manoeu	vres and	d proced	lures		I.
2.1	Normal VFR take- off profiles		ions g l) al	>	>		M	

	includi crossw Elevate helipor Ground level helipor	rind ed rts d	
2.2	off at maximum take- off mass (actual or simulated maximum take- off mass)	P>	
2.3.1	Rejected take- off: — during runway operati during elevate helipor operati and during ground level operati	y ions; ed rt ions;	M
2.3.2	Take- off with simulated engine failure after passing decision point: during runway operati during elevate helipor	y ions; ed	M

	operation and during ground level operation			
2.4	Autorotative descent in helicopter mode to ground (an aircraft shall not be used for this exercise)	>		M FFS only
2.4.1	Windmill descent in aeroplane mode (an aircraft shall not be used for this exercise)	>		M FFS only
2.5	Normal VFR landing profiles: runway operation (STOL and VTOL) elevated heliports ground level heliports	ns	>	M
2.5.1	Landing with simulated			

	engine							
	failure							
	after							
	reachin	σ						
	decision							
		1						
	point:	1						
	_	during						
		runwa	*					
		operat						
		during						
		elevate						
		helipo	rt					
		operat						
		and						
	_	during						
		ground						
		level						
		operat	ions					
		орегис						
2.6	Go-		P	>			M	
	around							
	or							
	landing							
	followi	ng						
	simulat							
	engine							
	failure							
	before							
	decision	n n						
	point							
CECT	_	NT.			1	C 4		•
	ION 3 —			bnorma	operati	ions of t	ne tollov	ving
	ns and p		es:					<u> </u>
3	Normal						M	A
	and							mandatory
	abnorm	al						minimum
	operation	ons						of 3
	of the							items
	followi	ng						shall
	systems							be
	and							selected
	procedu	ires						from
	(may	1105						this
	be							section
	comple	tad						Section
		teu						
	in an							
	FSTD							
	if	1						
	qualifie	a						
	for the							
	exercise	‡):						
3.1	Engine	Р	>	>				
J.1	50	1 -		1	1			

3.2	Pressurisa and air conditioni (heating, ventilation	ing	>	>		
3.3	Pitot/ static system		>	>		
3.4	Fuel P system		>	>		
3.5	Electrical system		>	>		
3.6	Hydraul Resulted	;	>	>		
3.7	Flight control and trim system		>	>		
3.8	Anti- icing and de- icing system, glare shield heating (if fitted)		>	>		
3.9	Autopild?/ flight director	/	>	>		
3.10	Stall P warning devices or stall avoidance devices and stability augmentar devices	•	>	>		
3.11	WeatherP radar, radio altimeter, transpond		>	>		

3.12	ground proxim warning system (if fitted) Landing gear system	ity g gP	>	>				
3.13	APU	P	>	>				
3.14	Radio, navigat equipm instrum and FMS	ent,	>	>				
3.15	Flap system	P	>	>				
SECT	ION 4 –		mal and	l emerg	ency pro	cedures		<u> </u>
4	Abnormand emerge procedu (may be comple in an FSTD if qualifie for the exercise	ncy ares ted					M	A mandatory minimum of 3 items shall be selected from this section
4.1	Fire drills, engine, APU, cargo compar flight deck and electric fires includin evacuat if applica	tment, al ng iion	>	>				
4.2	Smoke control		>	>				

	and remova	1					
4.3	Engine failures shutdow and restart (an aircraft shall not be used for this exercise including one engine inoperation convers from helicopt to aeroplate modes and vice versa	yn vn tive tion ter	>	>		FFS only	
4.4	Fuel dumpin (simula if fitted)	P g ted,	>	>			
4.5	Wind shear at take-off and landing (an aircraft shall not be used for this exercise			P		FFS only	
4.6	Simulat cabin pressure		>	>		FFS only	

	failure/ emergency descent (an aircraft shall not be used for this exercise)					
4.7	ACAS P event (an aircraft shall not be used for this exercise)	>	>		FFS only	
4.8	IncapaciPation of crew member	>	>			
4.9	Transmission malfunctions	>	>		FFS only	
4.10	RecoverP from a full stall (power on and off) or after activation of stall warning devices in climb, cruise and approach configurations (an aircraft shall not be used for	>	>		FFS only	

	this exercise	e)						
4.11	Other emerge procedulas detailed in the appropri flight manual	ires I iate	>	>				
SECTI IMC o	ION 5 — or simula	– Instru ited IM	ment fli C)	ght proc	edures (to be pe	erforme	d in
5.1	Instrumtake- off: transition to instrumtight is required as soon as possible after becominairborne	ent	>*	>*				
5.1.1	Simulat engine failure during departu after decision point	re	>*	>*			M*	
5.2	Adhere to departu and arrival routes and ATC instruct	re	>*	>*			M*	
5.3	Holding procedu	P* ires	>*	>*				

5.4	Precision* approach down to a decision height not less than 60 m (200 ft)	>*	>*		
5.4.1	Manuall 9,* without flight director	>*	>*	M* (Skill test only)	
5.4.2	Manuall 9,* with flight director	>*	>*		
5.4.3	With use of autopilot	>*	>*		
5.4.4	Manually,* with one engine simulated inoperative; engine failure has to be simulated during final approach before passing the OM and continued either to touchdown or until completion of the	>*	>*	M*	

	missed approach procedure					
5.5	Non-precision approach down to the MDA/H	>*	>*		M*	
5.6	Go- around with all engines operating on reaching DA/ H or MDA/ MDH	>*	>*			
5.6.1	Other P* missed approach procedures	>*	>*			
5.6.2	Go- around with one engine simulated inoperative on reaching DA/ H or MDA/ MDH				M*	
5.7	IMC P* autorotation with power recovery to land on runway in helicopter mode	>*	>*		M* FFS only	

	only (an						
	aircraft						
	shall not be						
	used						
	for						
	this						
	exercise)						
5.8	Recover!*	>*	>*			M*	
	from						
	unusual attitudes						
	(this						
	one						
	depends						
	on the						
	quality of the						
	FFS)						
SECT	ION 6 — Ad	ditional au	 thorisati	on on a	tvne rat	ing for	
instru	ment approa	ches down	to a deci	sion hei	ght of le	ss than	60 m
(200 ft) (CAT II/III	()				r	
6	Additional						
	authorisation	ı					
	on a type						
	rating						
	for						
	instrument						
	approaches						
	down to a						
	decision heig	ght					
	of less						
	than						
	60 m (CAT						
	II/III).						
	The						
	following						
	manoeuvres						
	and procedures						
	are the						
	minimum						
	training						
	requirements	5					
	to permit						
	instrument						
	approaches of	down					
	•						

	to a DH of less than 60 m (200 ft). During the followin instrume approach and missed approach all powered lift aircraft equipme required for the type certificat of instrume approach down to a DH of less than 60 m (200 ft) shall be used.	ent hes h res, l- ent					
6.1	Rejected take- off at minimum authorise RVR	n	P	>		M*	
6.2	ILS approach in simulate instrume flight condition down	ed ent	P	>	>	M*	

DF usi flig gui sys Sta ope pro	olicable I, ng					
of cre	w ordination					
after approximate a sind in concentration on real DF The trains a shall also incentrate a grand due (sin instance) and the sind also incentrate a shall also incentrate a shal	cund: coroaches cicated 6.2 ching I. ce ching III co clude co- cund ce to mulated) ufficient TR, nd car, ceraft viation cess coroach nits	P	>		M*	

Changes to legislation: There are currently no known outstanding effects for the Commission Implementing Regulation (EU) 2018/1974. (See end of Document for details)

	equipment					
	failure					
	prior					
	to reaching					
	DH,					
	and					
	go-					
	around					
	with					
	simulated					
	airborne					
	equipment					
	failure.					
6.4	Landing(s):	P	>		M*	
	with					
	visual reference					
	established					
	at DH					
	following					
	an					
	instrument					
	approach.					
	Depending					
	on the					
	specific flight					
	guidance					
	system,					
	an					
	automatic					
	landing					
	shall					
	be					
GE CI	performed.	<u> </u>	<u> </u>			
	TION 7 — Option					
7	Use of	P	>	>		
	optional					
	equipment					

E. Specific requirements for the airship category

1. In the case of skill tests or proficiency checks for airship type ratings, applicants shall pass Sections 1 to 5 and 6 (as applicable) of the skill test or proficiency check. Failure in more than five items will require applicants to repeat the entire test or check. Applicants failing not more than five items shall take the failed items again. Failure in any item in the case of a retest or a recheck, or failure in any other items already passed will require applicants to repeat the entire test or check again. All sections of the skill test or proficiency check shall be completed within 6 months.

FLIGHT TEST TOLERANCE

Changes to legislation: There are currently no known outstanding effects for the Commission Implementing Regulation (EU) 2018/1974. (See end of Document for details)

- 2. Applicants shall demonstrate the ability to:
- (a) operate the airship within its limitations;
- (b) complete all manoeuvres with smoothness and accuracy;
- (c) exercise good judgement and airmanship;
- (d) apply aeronautical knowledge;
- (e) maintain control of the airship at all times in such a manner that the successful outcome of a procedure or manoeuvre is never in doubt;
- (f) understand and apply crew coordination and incapacitation procedures; and
- (g) communicate effectively with the other crew members.
- 3. The following limits shall apply, corrected to make allowance for turbulent conditions and the handling qualities and performance of the airship used.

(a) IFR flight limits:

Height	
Generally	± 100 ft
Starting a go-around at decision height/altitude	+ 50 ft/- 0 ft
Minimum descent height/altitude	+ 50 ft/- 0 ft
Tracking	
On radio aids	± 5°
Precision approach	half-scale deflection, azimuth and glide path
Heading	
Normal operations	± 5°
Abnormal operations/emergencies	± 10°

(b) VFR flight limits:

Height	
Generally	± 100 ft
Heading	
Normal operations	± 5°
Abnormal operations/emergencies	± 10°

CONTENT OF THE TRAINING/SKILL TEST/PROFICIENCY CHECK

4. The following symbol means:

P = Trained as PIC or co-pilot and as PF and PM for the issue of a type rating as applicable.

ANNEX

Document Generated: 2023-10-18

- 5. The practical training shall be conducted at least at the training equipment level shown as (P), or may be conducted up to any higher equipment level shown by the arrow (---->).
- 6. The following abbreviations are used to indicate the training equipment used:

FFS =	full-flight simulator
FTD =	flight training device
OTD =	other training device
As =	airship

- (a) Applicants for the skill test for the issue of the airship shall pass Sections 1 to 5 and, if applicable, Section 6.
- (b) Applicants for the revalidation or renewal of the airship type rating proficiency check shall pass Sections 1 to 5 and, if applicable Section 6.
- (c) The starred items (*) shall be flown solely by reference to instruments. If this condition is not met during the skill test or proficiency check, the type rating will be restricted to VFR only.
- 7. Where the letter 'M' appears in the skill test or proficiency check column, this will indicate a mandatory exercise.
- 8. FSTDs shall be used for practical training and testing if they form part of a type rating course. The following considerations will apply to the course:
- (a) the qualification of the FSTDs as set out in the relevant requirements of Annex VI (Part-ARA) and Annex VII (Part-ORA); and
- (b) the qualifications of the instructor.

Manoeuvres/procedures OTD		PRAC	CTICAL	TRAIN	SKILL TEST OR PROFICIENCY CHECK			
		_	FTD	FFS	As	initials when training	FFS IgAs	keŒxaminer's initials when test completed
SECT	TON 1 —	– Preflig	ght prep	aration	s and ch	ecks		
1.1	Prefligh inspecti				P			
1.2	Cockpit		>	>	>			
1.3	Starting proceduradio and		P	>	>		M	

	frequen	ent n ion nication		D			M	
1.4	Off- mast procedu and ground manoeu			P	>		M	
1.5	Pre- take- off procedu and checks		>	>	>		M	
SECT	ION 2 —	– Flight	manoeu	vres and	d proced	lures		
2.1	Normal VFR take- off profile			P	>		M	
2.2	Take- off with simulate engine failure	ed		P	>		M	
2.3	Take- off with heavine > 0 (Heavy T/O)			P	>			
2.4	Take- off with heavine < 0 (Light/ TO)	SS		P	>			

2.5	Normal climb procedure	P	>		
2.6	Climb to pressure height	P	>		
2.7	Recognising of pressure height	P	>		
2.8	Flight at or close to pressure height	P	>	M	
2.9	Normal descent and approach	P	>		
2.10	Normal VFR landing profile	P	>	M	
2.11	Landing with heaviness > 0 (Heavy Ldg.)	P	>	M	
2.12	Landing with heaviness < 0 (Light Ldg.)	P	>	M	
	Intentionally left blank				
SECT system	FION 3 — Normal ams and procedures	and abnorr	nal operation	s of the foll	owing
3	Normal and abnormal operations of the following			M	A mandatory minimum of 3 items shall

	systems and procedures (may be completed in an FSTD if qualified for the exercise):					be selected from this section
3.1	Engine P	>	>	>		
3.2	Envelop ? pressurisation	>	>	>		
3.3	Pitot/ static system	>	>	>		
3.4	Fuel P system	>	>	>		
3.5	Electrical system	>	>	>		
3.6	Hydraul & system	>	>	>		
3.7	Flight control and trim system	>	>	>		
3.8	BallonetP system	>	>	>		
3.9	Autopilo#/ flight director	>	>	>		
3.10	StabilityP augmentation devices	>	>	>		
3.11	Weather P radar, radio altimeter, transponder, ground proximity warning system	>	>	>		

	(if fitted)							
3.12	Landing gear system	gP	>	>	>			
3.13	APU	P	>	>	>			
3.14	Radio, navigat equipm instrum and FMS	ion ent,	>	>	>			
	Intention left blank							
	TION 4 —		mal and	l emerge	ency pro	cedures	1	
4	Abnormand emerger procedu (may be compler in an FSTD if qualifier for the exercise)	ncy ires ted					M	A mandatory minimum of three items shall be selected from this section
4.1	Fire drills, engine, APU, cargo compar flight deck and electric fires, includir evacuat if applical	al ng ion	>	>	>			
4.2	Smoke control and remova		>	>	>			

4.3	Engine P failures, shutdown and restart: in particular phases of flight, inclusive multiple engine	>	>	>		
4.4	failure Incapacifa of crew member	tion>	·>	>		
4.5	Transmiss gearbox malfunction		>	>	FFS only	
4.6	Other P emergency procedures as outlined in the appropriat flight manual	S	>	>		
			Flight Pr	ocedures	(to be perform	ed in
IMC o	or simulate	d IMC)				1
5.1	Instrument take- off: transition to instrument flight is required as soon as possible after becoming airborne	t	*>*			
5.1.1	Simulated engine	k>	*>*	>*	M*	

	failure during departure					
5.2	Adheren Pet to departure and arrival routes and ATC instructions	>*	>*	>*	M*	
5.3	HoldingP* procedures	>*	>*	>*		
5.4	Precision* approach down to a decision height not less than 60 m (200 ft)	>*	>*	>*		
5.4.1	Manually,* without flight director	>*	>*	>*	M* (Skill test only)	
5.4.2	Manually,* with flight director	>*	>*	>*		
5.4.3	With P* use of autopilot	>*	>*	>*		
5.4.4	Manual P,* with one engine simulated inoperative; engine failure has to be simulated during	>*	>*	>*	M*	

	final approach before passing the OM and continued to touchdown or until completion of the missed approach procedure					
5.5	Non- P* precision approach down to the MDA/ H	>*	>*	>*	M*	
5.6	Go-around with all engines operating on reaching DA/H or MDA/MDH	>*	>*	>*		
5.6.1	Other missed approach procedures	>*	>*	>*		
5.6.2	Go- around with one engine simulated inoperative on reaching DA/ H or				M*	

Changes to legislation: There are currently no known outstanding effects for the Commission Implementing Regulation (EU) 2018/1974. (See end of Document for details)

	MDA/ MDH						
5.7	Recove from unusual attitude (this one depends on the quality of the FFS)	S	>*	>*	>*	M*	

(200 ft) (CAT II/III)

(200 10	(CAI II/III)
6	Additional
	authorisation
	on a
	type
	rating
	for
	instrument
	approaches
	down
	to a
	decision
	height
	of less
	than
	60 m
	(200
	ft)
	(CAT
	II/III).
	The
	following
	manoeuvres
	and
	procedures
	are the minimum
	training
	requirements to
	permit
	instrument
	approaches down
	to a
	DH of
	less
	than
	uiuii

	60 m (200 ft). During the following instrument approaches and missed approach procedures, all airship equipment required for the type certification of instrument approaches down to a DH of less than 60 m (200 ft) shall be used.					
6.1	Rejected take- off at minimum authorised RVR	P	>		M*	
6.2	ILS approaches: in simulated instrument flight conditions down to the applicable DH, using flight guidance	P	>		M*	

	system. SOPs						
	of						
	crew						
	coordin	ation					
	shall						
	be						
	observe	d.					
6.3	Go-		P	>		M*	
0.5	around		1			141	
	After						
	approac	hec					
	as	iics					
	indicate	d					
	in 6.2	u					
	on						
	reachin	σ					
	DH.	5					
	The						
	training						
	shall						
	also						
	include						
	a go-						
	around						
	due to						
	(simula	ted)					
	insuffic	ient					
	RVR,						
	wind						
	shear,						
	aircraft						
	deviation	n					
	in						
	excess						
	of	1					
	approac	n					
	limits						
	for a success	6.1					
	approac						
	ground	111,					
	airborn	a					
	equipm						
	failure	-110					
	prior						
	to						
	reachin	g					
	DH						
	and,						
	go-						
	around						
	1	1	1				

	with simulated airborne equipment failure.						
6.4	Landing(s): with visual reference established at DH following an instrument approach. Depending on the specific flight guidance system, an automatic landing shall be performed	P	>			M*	
SECT	ION 7 — Option	nal equi	pment	I	I	I.	I
7	Use of optional equipment	P	>				

- (1) Regulation (EU) 2018/1139 of the European Parliament and of the Council of 4 July 2018 on common rules in the field of civil aviation and establishing a European Union Aviation Safety Agency, and amending Regulations (EC) No 2111/2005, (EC) No 1008/2008, (EU) No 996/2010, (EU) No 376/2014 and Directives 2014/30/EU and 2014/53/EU of the European Parliament and of the Council, and repealing Regulations (EC) No 552/2004 and (EC) No 216/2008 of the European Parliament and of the Council and Council Regulation (EEC) No 3922/91 (OJ L 212, 22.8.2018, p. 1).
- (2) Commission Regulation (EU) No 1178/2011 of 3 November 2011 laying down technical requirements and administrative procedures related to civil aviation aircrew pursuant to Regulation (EC) No 216/2008 of the European Parliament and of the Council (OJ L 311, 25.11.2011, p. 1).
- (3) European Plan for Aviation Safety 2018-2022, pt. 5.3.1, p. 33.
- (4) Commission Regulation (EU) 2015/445 of 17 March 2015 amending Regulation (EU) No 1178/2011 as regards technical requirements and administrative procedures related to civil aviation aircrew (OJ L 74, 18.3.2015, p. 1).
- (5) Commission Regulation (EU) No 965/2012 of 5 October 2012 laying down technical requirements and administrative procedures related to air operations pursuant to Regulation (EC) No 216/2008 of the European Parliament and of the Council (OJ L 296, 25.10.2012, p. 1).

Changes to legislation:

There are currently no known outstanding effects for the Commission Implementing Regulation (EU) 2018/1974.