

---

STATUTORY RULES OF NORTHERN IRELAND

---

**2012 No. 379**

**CLEAN AIR**

**The Smoke Control Areas (Exempted Fireplaces)  
(No. 2) Regulations (Northern Ireland) 2012**

*Made - - - - 17th October 2012*

*Coming into operation 21st November 2012*

The Department of the Environment makes the following Regulations in exercise of the powers conferred by Article 17(7) of the Clean Air (Northern Ireland) Order 1981<sup>(1)</sup>.

The Department is satisfied that the classes of fireplaces prescribed in column (1) of the Schedule can, subject to the conditions prescribed in column (2) of the Schedule, be used for burning fuel other than authorised fuels<sup>(2)</sup> without producing any smoke or a substantial quantity of smoke.

**Citation and commencement**

1. These Regulations may be cited as the Smoke Control Areas (Exempted Fireplaces) (No.2) Regulations (Northern Ireland) 2012 and shall come into operation on 21st November 2012.

**Exempted Fireplaces**

2. The classes of fireplaces prescribed in column (1) of the Schedule shall, subject to the conditions prescribed in column (2) of the Schedule, be exempt from the provisions of Article 17 of the Clean Air (Northern Ireland) Order 1981.

**Revocation**

3. The Smoke Control Areas (Exempted Fireplaces) Regulations (Northern Ireland) 2012<sup>(3)</sup> are revoked.

---

(1) [S.I. 1981/158 \(N.I. 4\)](#)

(2) Fuels declared by the Department of the Environment to be authorised fuels for the purposes of Article 2(2) of the Clean Air (Northern Ireland) Order 1981 are specified in [S.R. 2011 No. 374](#).

(3) [S.R. 2012 No. 250](#)

Sealed with the official seal of the Department of the Environment on 17th October 2012.



*Wesley Shannon*  
A senior officer of the  
Department of the Environment

## SCHEDULE

Regulation 2

<i>(1) Class of fireplace</i>	<i>(2) Conditions</i>	
	<i>The fireplace must be installed, maintained and operated in accordance with the following specifications:</i>	<i>Permitted fuels (other than authorised fuels):</i>
Any fireplace specially designed or adapted for combustion of liquid fuel.		
Any fireplace (other than a fireplace fired by pulverised fuel) constructed on or after 1st July 1965 and installed before 1st September 1970 and equipped with mechanical stokers, or adapted between those dates for use with such stokers.		No fuel shall be used other than that for which the mechanical stoker was designed.
Any fireplace designed to burn coal (other than a fireplace fired by pulverised coal) with a heating capacity exceeding 160 megajoules per hour constructed and installed on or after 1st July 1965 and equipped with mechanical stokers or adapted on or after that date for use with such stokers.		No fuel shall be used other than that for which the mechanical stoker was designed.
18i and 60i stoves manufactured by Jetmaster Fires Limited, Unit 2 Peacock Trading Estate, Goodwood Road, Eastleigh, Hampshire, SO50 4NT.	Installation and use instruction manual reference: "Part No 106870 Issue No. 1" dated February 2010 and supplementary instruction manual reference: "Part No 106872 Issue No. 1" dated May 2010.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.
100SE Smoke Exempt Woodburning Stove manufactured by ESSE Engineering Limited, Long Ing, Barnoldswick, Lancashire. BB18 6BN.	The manufacturer's instruction manual dated March 2009, reference 100SE Issue 1.  A permanent stop must be in place on the secondary air inlet to prevent closure beyond the 50% open position.	Untreated dry wood with a maximum moisture content of 20%, maximum length of 200mm and maximum width or diameter of 120mm. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.

*Status: This is the original version (as it was originally made).*

<p>Aarrow Signature 5 SC, Aarrow Ecoburn 5 SC, Hamlet Solution 5 SC and Villager Espirit 5 SC Stoves manufactured by Arada Limited, The Fire Works, Millwey Industrial Estate, Axminster, Devon. EX13 5HU.</p>	<p>Instruction manual references “Rev 02” dated April 2010.</p> <p>All the appliances will be fitted with a mechanical stop to prevent closure of the air control beyond 20mm from the closed position and 50mm beyond the fully open position.</p>	<p>Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.</p>
<p>Acquisitions Bloomsbury 5kW stove manufactured by Esse Engineering Limited, Ouzedale Foundry, Long Ing, Barnoldswick, BB18 6BN.</p>	<p>Instruction manual references “01/12(PP)” dated January 2012. The fitting of a system to prevent closure of the air controls beyond the 50% open position must be implemented.</p>	<p>Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.</p>
<p>Acquisitions Cannonbury 4 and 5 manufactured by Esse Engineering Ltd, The Ouzledale Foundry, Long Ing, Barnoldswick, Colne, Lancashire, BB8 6BN.</p>	<p>Installation and Operating Instruction manual reference “v71 of 09/11/2010” dated 09/11/2010.</p>	<p>Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.</p>
<p>Aduro 3D, 8D, 10D, 11D and Asgård 1D, 2D and 7D wood burning stoves manufactured by Aduro A/S, Silkeborgvej 765 8220, Brabrand, Denmark.</p>	<p>Instruction manual references “Pevex1001/AH/ver1” and dated June 2011.</p> <p>Fitted with permanent stops to ensure that the primary and secondary air controls do not close beyond 95% and 50% respectively.</p>	<p>Dry wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.</p>
<p>Aduro 9D wood burning stove manufactured by Aduro A/S, Silkeborgvej 765 8220, Brabrand, Denmark.</p>	<p>Instruction manual references “Pevex1002/AH/ver1” and dated June 2011.</p> <p>Fitted with permanent stops to ensure that the primary and secondary air controls do not close beyond 95% and 50% respectively.</p>	<p>Dry wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.</p>
<p>Alberg 7 manufactured by Elite Group Trading Limited, Room 1208 Kak Tak Commercial Building 317-319 Des Voeux Road, Central Hong Kong 999077.</p>	<p>Instruction manual references “EGTL03A Version 1.4” dated 21<sup>st</sup> December 2011.</p>	<p>Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.</p>
<p>Alpha I model number AL905-SE Wood Burning Stove.</p>	<p>Instruction manual references “HF277-SE/UK-NI-ROI/V2D.18-07-12” dated July 2012.</p>	<p>Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as</p>

<p>Manufactured by Hi-Flame Fireplace UK Limited</p> <p>Unit 5A Holmes Chapel Business Park</p> <p>Manor Lane</p> <p>Holmes Chapel</p> <p>Cheshire</p> <p>CW4 8AF.</p>	<p>Fitted with a mechanical stop to prevent closure of the main air control beyond the 50% open position.</p>	<p>a result of treatment with wood- preservatives or coatings.</p>
<p>Alpha II model number AL907-SE Wood Burning Stove.</p> <p>Manufactured by Hi-Flame Fireplace UK Limited</p> <p>Unit 5A Holmes Chapel Business Park</p> <p>Manor Lane</p> <p>Holmes Chapel</p> <p>Cheshire</p> <p>CW4 8AF.</p>	<p>Instruction manual references “AL907-SE/UK-NI-ROI/V3- D.14-07-12” dated July 2012.</p> <p>Fitted with a mechanical stop to prevent secondary air control closure beyond the 20% open position, and a 70mm opening of the door rope seal to allow a constant flow of air when sold into smoke control areas.</p>	<p>Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood- preservatives or coatings.</p>
<p>Angus Orligno 200 40, 60 and 80kW gasification boilers manufactured by Eko-Vimar Orlanski Spółka z ograniczoną odpowiedzialnością, ul. Nyska 17 b 48-385 Otmuchów, Poland.</p>	<p>Instruction manual references “ EV-20111002” dated October 2011.</p>	<p>Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood- preservatives or coatings.</p>
<p>Angus Super 18, 25, 40, 60 and 80kW gasification boilers manufactured by Eko-Vimar Orlanski Spółka z ograniczoną odpowiedzialnością, ul. Nyska 17 b 48-385 Otmuchów, Poland.</p>	<p>Instruction manual references “ EV-20111001” dated October 2011.</p>	<p>Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood- preservatives or coatings.</p>
<p>Apollo 8 Inset stove manufactured by Chesneys Limited, 194-200 Battersea Park Road, London, SW11 4ND.</p>	<p>Instruction manual references “CH8K Apollo – V2” dated 31 October 2011.</p> <p>The fitting of a system that prevents closure of the air controls further than</p>	<p>Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood- preservatives or coatings.</p>

**Status:** This is the original version (as it was originally made).

	40mm from open must be implemented.	
Apollo incinerator types 10, 25 and 50 manufactured by Apollo Incineration Systems Limited.	The incinerators shall be installed, maintained and operated in accordance with the manufacturer's instructions dated 2 <sup>nd</sup> November 1992 and bearing the reference "Apollo 10-25-50".	No fuel shall be used other than wood and wood shavings. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Arimax Bio 300kW Arimax Bio 400kW Arimax Bio 500kW boilers  Manufactured by Artierm Oy, PO Box 59, Fin – 43101, Saarijarvi.	Instruction manual references "INSTALLATION AND OPERATION MANUAL Arimax Bio 120-3000kW" dated 30/03/2010.	6-8mm wood pellets with a moisture content less than 10%. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.
Ashwell Green-Tec 150 boiler manufactured by Ashwell Biomass Limited, Unit 12, 35 Pinfold Road, Thurmaston, Leicester, LE4 8AT.	Instruction manual reference "ASH-gt150/101 Version 1.2" dated 06/2009.	Wood pellets. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Ashwell Green-Tec 195 boiler manufactured by Ashwell Biomass Limited, Unit 12, 35 Pinfold Road, Thurmaston, Leicester, LE4 8AT.	Instruction manual reference "ASH-gt195/102 Version 1.2" dated 06/2009.	Wood pellets. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Ashwell Green-Tec 300 boiler manufactured by Ashwell Biomass Limited, Unit 12, 35 Pinfold Road, Thurmaston, Leicester, LE4 8AT.	Instruction manual reference "ASH-gt300/103 Version 1.2" dated 06/2009.	Wood pellets. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
B9 Energy Wood Chip Gasifer Unit manufactured by B9 Energy Biomass Limited.	The manufacturer's instructions dated 2002 and bearing the reference "001/B9ENERGY BIOMASS".	No fuel shall be used other than untreated wood chips, shredded wood or small untreated pieces of wood. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.
Barbas ECO 52 Stove manufactured by Interfocos, Hallenstraat 17, 5531 AB Bladel, The Netherlands.	Instruction manual references "02 – 327332" dated March 2010.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment

		with wood-preservatives or coatings.
Barbas Unilux-3 40, 5kW wood burning insert and Barbas ECO 40, 5kW wood burning roomheater manufactured by Interfocos BV, Hallenstraat 17, NL-5531, AB, BLADEL, Netherlands.	The Unilux-3 40 Instruction Manual, document Version 01-326587 dated August 2009.  The ECO 40 Instruction Manual, document Version 01-327332 dated October 2009.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.
Barbas Unilux 3- 52 Stove manufactured by Interfocos, Hallenstraat 17, 5531 AB Bladel, The Netherlands.	Instruction manual references “03 – 326587” dated March 2010.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Barrington 8, Belgravia 8, Flatford 8, Hampstead 8, Hampstead LS 8, Hampstead XLS 8, and Petworth 8 stoves manufactured by Chesneys Limited, 194-200 Battersea Park Road, London SW11 4ND.	Instruction manual references “CH8K – V12” dated 31 October 2011.  The fitting of a system that prevents closure of the air controls further than 40mm from open must be implemented.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Baxi Bioflo manufactured by Windhager Zentralheizung GmbH , Anton-Windhager-Str. 20, A-5201 Seekirchen bei Salzburg, Austria.	Operating instruction manual references “720574401” dated 2010 and installation and servicing instruction manual “720574501” dated 2010.	Wood pellets. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Be Modern Monroe 5, Monroe 5, Be Modern Monterrey 5, Monterrey 5 and York Midi Multi Fuel Stoves manufactured by Broseley Fires Ltd, Knights Way, Battlefield Enterprise Park, Shrewsbury, Shropshire, SY1 3AB.	Instruction manual references “OCT10/GB” dated 6 <sup>th</sup> October 2010. The fitting of a system that prevents the closure of the secondary air flaps to be less than 8mm open position should be implemented.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Be Modern Monterrey 7, Monterrey 7, Be Modern Monroe 7 and Monroe 7 Multi Fuel Stoves manufactured by Broseley Fires Ltd, Knights Way, Battlefield Enterprise Park, Shrewsbury, Shropshire, SY1 3AB.	Instruction manual references “OCT10/GB” dated 6 <sup>th</sup> October 2010. The fitting of a system that prevents the closure of the secondary air flaps to be less than 10mm open position should be implemented.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

*Status: This is the original version (as it was originally made).*

Beech Wood Fired Pizza Oven manufactured by Beech Wood Fired Ovens, Brisbane, Australia.	The manufacturer's instructions dated 3 <sup>rd</sup> March 2000 and bearing the reference "BBP236UK".	No fuel shall be used other than untreated dry hardwood. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.
Binder Wood Fired Boiler models RRK 22-49 (49kW output), manufactured by Binder Gesellschaft mit beschränkter Haftung (GmbH) of Austria.	The manufacturer's and Wood Energy Limited's instructions entitled "Binder Equipment Installation, Commissioning and Maintenance" dated 17 <sup>th</sup> May 2005, and bearing the reference WELBinderManualrev0.doc, revision 0.	Wood pellets or wood chips. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.
Binder Wood Fired Boiler models RRK 80-175 (75-149kW output) with cyclone models ZA 80-175, manufactured by Binder Gesellschaft mit beschränkter Haftung (GmbH) of Austria.	The manufacturer's and Wood Energy Limited's instructions entitled "Binder Equipment Installation, Commissioning and Maintenance" dated 17 <sup>th</sup> May 2005 reference WELBinderManualrev0.doc, revision 0.	Wood pellets or wood chips. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.
Binder Wood Fired Boiler model RRK 130-250 (185-230kW output), RRK 200-350 (250-300kW output), RRK 400-600 (350-500kW output) and RRK 640-850 (650-840kW output) with cyclone model type ZA, manufactured by Binder Gesellschaft mit beschränkter Haftung (GmbH) of Austria.	The manufacturer's and Wood Energy Limited's instructions "Binder Equipment Installation, Commissioning and Maintenance" dated 17 <sup>th</sup> May 2005, reference WELBinderManualrev0.doc, revision 0.	Wood pellets or wood chips. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.
Binder Wood Fired Boiler model RRK 1000 (1200kW output), with multi-cyclone model MZA, manufactured by Binder Gesellschaft mit beschränkter Haftung (GmbH) of Austria.	The manufacturer's and Wood Energy Limited's instructions "Binder Equipment Installation, Commissioning and Maintenance" dated 17 <sup>th</sup> May 2005, reference WELBinderManualrev0.doc, revision 0.	Wood pellets or wood chips. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.
Binder Wood Fired Boiler model RRK 1200-1650 with Binder model MZA multicyclone and automatic ignition manufactured by Binder Gesellschaft mit	Wood Energy Limited's operating instructions for Binder Appliances referenced: 2009 July Binder O&M revision8.doc Operation and	Wood pellets or wood chips. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.



beschränkter Haftung (GmbH) of Austria.	Maintenance Manual, Revision 8, dated 15 July 2009.	
Binder Wood Fired Boiler model RRK 1800-2300 Binder model MZA multicyclone and automatic ignition manufactured by Binder Gesellschaft mit beschränkter Haftung (GmbH) of Austria.	Wood Energy Limited's operating instructions for Binder appliances referenced: 2009 July Binder O&M revision8.doc Operation and Maintenance Manual, Revision 8, dated 15 July 2009.	Wood pellets or wood chips. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.
Binder Wood Fired Boiler model RRK 2500-3000 Binder model MZA multicyclone and automatic ignition manufactured by Binder Gesellschaft mit beschränkter Haftung (GmbH) of Austria.	Wood Energy Limited's operating instructions for Binder appliances referenced: 2009 July Binder O&M revision8.doc Operation and Maintenance Manual, Revision 8, dated 15 July 2009.	Wood pellets or wood chips. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.
Biomatic 220 and 250 fitted with Zyklusent 220-250 cyclone separator manufactured by HERZ Armaturen Ges.m.b.H, Geschäftsbereich HERZ, Feuerungstechnik, A-8272 Sebersdorf 138, Austria.	The manufacturer's instructions dated April 2005, reference Bedienungsanleitung Englisch v2.0 doc.	Chipped wood, wood pellets or planed wood shavings.  The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.
Biomatic 300, 350, 400 and 500 fitted with Zyklusent 300-500 cyclone separator manufactured by HERZ Armaturen Ges.m.b.H, Geschäftsbereich, Feuerungstechnik, A-8272 Sebersdorf 138, Austria.	The manufacturer's instructions dated April 2005, reference Bedienungsanleitung Englisch v2.0 doc.	Chipped wood, wood pellets or planed wood shavings.  The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.
Biomatic +20 boiler manufactured by Ariterm Sweden AB,  Flottiljvägen 15, 392 41 Kalmar, Sweden.	Instruction manual references "ARITERM-VTT-S-07229-11.1" dated 21/05/2012.	Wood pellets. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Biomatic +20 light boiler and Biomatic +20 ultra light boiler manufactured by Ariterm Sweden AB Flottiljvägen 15, 392 41 Kalmar, Sweden.	Instruction manual references "ARITERM-VTT-S-07229-11.2" dated 21/05/2012.	Wood pellets. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Biomatic +40 boiler manufactured by Ariterm Sweden AB	Instruction manual references "ARITERM-VTT-S-06765-11.1" dated 21/05/2012.	Wood pellets. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment

*Status: This is the original version (as it was originally made).*

Flottiljvägen 15, 392 41 Kalmar, Sweden.		with wood-preservatives or coatings.
Biomatic +40 light boiler and Biomatic +40 ultra light boiler manufactured by Ariterm Sweden AB Flottiljvägen 15, 392 41 Kalmar, Sweden.	Instruction manual references “ARITERM-VTT-S-06765-11.2” dated 21/05/2012.	Wood pellets. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Boru 4.9kW Stove manufactured by Righpur Limited, T/A Boru Stoves, The Hive, Ballydine, Gooldscross, Ireland.	Instruction manual reference “BFF010” dated 26/01/2011.  The air controls must be fixed such that they can’t be closed more than: — Primary air slide 2mm — Secondary air slide 2mm — Tertiary air slide 30%.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Burley Brampton 8kW stove manufactured by Burley Appliances, Lands’ End Way, Oakham, Rutland, LE15 6RB.	Instruction manual references “BUR/11/10” dated October 2011.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Burley Debdale 4kW stove manufactured by Burley Appliances, Lands’ End Way, Oakham, Rutland, LE15 6RB.	Instruction manual references “BUR/11/10” dated October 2011. The radius of the air inlet hole must be 19mm.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Burley Hollywell SE, manufactured by Burley Appliances Ltd, Lands End Way, Oakham, Rutland, LE15 6RB.	Instruction manual references “BUR/11/05” dated January 2011. The appliance must be fitted with an air plate that prevents the tertiary air controller from closing more than 17mm and opening more than 45mm.	Wood. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Bushman Large Commercial Pizza Oven manufactured by Dingley Dell Enterprises Ltd, PO Box 3534, Kidderminster, Worcestershire, DY14 9ZE.	Instruction manual references “LCOINST” dated 01/2011.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Bushman Large Domestic Pizza Oven manufactured by Dingley Dell Enterprises Ltd, PO Box 3534, Kidderminster, Worcestershire, DY14 9ZE.	Instruction manual references “LDOINST” dated 01/2011.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Bushman Medium Commercial Pizza Oven manufactured by Dingley Dell Enterprises Ltd, PO Box 3534, Kidderminster, Worcestershire, DY14 9ZE.	Instruction manual references “MCOINST” dated 01/2011.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Bushman Medium Domestic Pizza Oven manufactured by Dingley Dell Enterprises Ltd, PO Box 3534, Kidderminster, Worcestershire, DY14 9ZE.	Instruction manual references “MDOINST” dated 01/2011.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Bushman Small Commercial Pizza Oven manufactured by Dingley Dell Enterprises Ltd, PO Box 3534, Kidderminster, Worcestershire, DY14 9ZE.	Instruction manual references “SCOINST” dated 01/2011.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Bushman Small Domestic Pizza Oven manufactured by Dingley Dell Enterprises Ltd, PO Box 3534, Kidderminster, Worcestershire, DY14 9ZE.	Instruction manual references “SDOINST” dated 01/2011.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Carillon 4:3 manufactured by La Nordica Spa, Via Summano 104 M. Precalcino, 36030 Vicenza, Italy.	Instruction manual references “7196755-Rev.09” dated 22 <sup>nd</sup> December 2010.  Fitted with a mechanical stop to prevent closure of the secondary air control beyond the 40% open position.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Carillon 16:9 Crystal manufactured by La Nordica Spa, Via Summano 104 M. Precalcino, 36030 Vicenza, Italy.	Instruction manual references “7196755-Rev.09” dated 22 <sup>nd</sup> December 2010.  Fitted with a mechanical stop to prevent closure of the secondary air control beyond the 40% open position.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Carron Dante SE Manufactured by Jig UK Limited, Hurlingham Business Park, Fulbeck Heath, Grantham, Lincolnshire, NG32 3HL.	Instruction manual references “BHC401-406” dated 12 <sup>th</sup> January 2011.  Fitted with a system preventing the closure of the secondary air control openings beyond 14mm.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

**Status:** This is the original version (as it was originally made).

<p>Carron Stove manufactured by Jig UK Limited Hurlingham Business Park, Fulbeck Heath, Grantham, Lincolnshire NG32 3HL.</p>	<p>Instruction manual references “91-62351” dated July 2009.</p>	<p>Dry and split wood logs of a maximum length of 23cm. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.</p>
<p>Carron Stove SE Manufactured by Jig UK Limited, Hurlingham Business Park, Fulbeck Heath, Grantham, Lincolnshire, NG32 3HL.</p>	<p>Instruction manual references “BHC501-506” dated 12<sup>th</sup> January 2011.  Fitted with a system preventing the closure of the secondary air control openings beyond 3mm.</p>	<p>Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.</p>
<p>CB800 Skagen manufactured by Hunter Stoves Limited, Unit 6, The Old Mill Industrial Estate, Stoke Canon, Exeter, Devon, EX5 4RJ.</p>	<p>Instruction manual references “JINHCE08 revE” dated 06/12/11 and instruction manual “JINHCE08SCK revB” dated 06/12/11.  Fitted with smoke control area kit “JHCE0801” when sold into smoke control areas.</p>	<p>Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.</p>
<p>CBR Flexifuel Heater, models 150 and 200 manufactured by CBR Engineers Limited.</p>	<p>The manufacturer’s instructions published in 1989 and bearing the reference “FF/CBR Flexifuel 150/200/1989”.</p>	<p><b>(a)</b> No fuel shall be used other than hardwood or softwood offcuts, or chipboard. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings;  <b>(b)</b> The fireplaces shall not be used to burn sawdust in bulk.</p>
<p>CBR Flexifuel Heater, models 300, 400 and 600 manufactured by CBR Engineers Limited.</p>	<p>The manufacturer’s instructions, published in 1987 and bearing the reference “FF/CBR Flexifuel 87”.</p>	<p><b>(a)</b> No fuel shall be used other than hardwood or softwood offcuts, or chipboard. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings;</p>

		<p><b>(b)</b></p> <p>The fireplaces shall not be used to burn sawdust in bulk.</p>
<p>CBR Turbo Heat, models 200, 300, 400, 500, 600 and 800 manufactured by CBR Engineers Limited.</p>	<p>The manufacturer's instructions published in 1988 and bearing the reference "FF/CBR Turbo Heat 88".</p>	<p><b>(a)</b></p> <p>No fuel shall be used other than hardwood or softwood offcuts, or chipboard. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings;</p> <p><b>(b)</b></p> <p>The fireplaces shall not be used to burn sawdust in bulk.</p>
<p>Charnwood C-Four stove manufactured by A.J Wells &amp; Sons Ltd, Bishops Way, Newport, Isle of Wight, PO30 5WS.</p>	<p>Instruction manual references "CFOUR V1" dated 08/2011.</p>	<p>Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.</p>
<p>Charnwood C-Six stove manufactured by A.J Wells &amp; Sons Ltd, Bishops Way, Newport, Isle of Wight, PO30 5WS.</p>	<p>Instruction manual references "Ref. C-4 C-6 v1" dated March 2012.</p> <p>The fitting of a system that prevents the closure of the air control opening beyond 58mm of the open position must be implemented.</p>	<p>Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.</p>
<p>Charnwood Country 4 wood burning stove manufactured by A.J Wells &amp; Sons, Bishops Way, Newport, Isle of Wight, PO30 5WS.</p>	<p>Modification instruction manual references "TIS.95" dated 01/2011 and instruction manual "Country 4 MKII" dated 01/2011.</p> <p>The appliance must be fitted with the manufacturer's smoke reduction kit when used within a smoke control area to fix the minimum aperture of the secondary air inlets to a minimum of 21mm open.</p>	<p>Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.</p>
<p>Charnwood Cove 1SR stove manufactured by A.J.Wells and Sons Ltd, Bishops Way,</p>	<p>Installation and Use Instruction manual references "COVE 1 SR01. 10 Issue A".</p>	<p>Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as</p>

*Status: This is the original version (as it was originally made).*

Newport, Isle of Wight, PO30 5WS.	An adjustment of the air control such that the minimum closure of the air control is equivalent to that found with the control pushed in 15mm from the fully open position.	a result of treatment with wood preservatives or coatings.
Charnwood Island 1 manufactured by A.J. Wells and Son Limited, Bishops Way, Newport, Isle of Wight, PO30 5WS.	Instruction manual references “Island I.II.III 12.10 IssueB” dated December 2010. Fitted with a stop bracket (Kit No. 010/AY83/S) to prevent the airwash flaps at the back of the stove from being closed beyond 2mm.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Charnwood Island 2 manufactured by A.J. Wells and Son Limited, Bishops Way, Newport, Isle of Wight, PO30 5WS.	Instruction manual references “Island I.II.III 12.10 IssueB” dated December 2010. Fitted with a stop bracket (Kit No. 010/BY83/S) to prevent the airwash flaps at the back of the stove from being closed beyond 2mm.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Charnwood Island 3 manufactured by A.J. Wells and Son Limited, Bishops Way, Newport, Isle of Wight, PO30 5WS.	Instruction manual references “Island I.II.III 12.10 IssueB” dated December 2010.  Fitted with a stop bracket (Kit No. 010/CY83/S) to prevent the airwash flaps at the back of the stove from being closed beyond 2mm.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Charnwood Tor Pico manufactured by A.J. Wells and Son Limited, Bishops Way, Newport, Isle of Wight, PO30 5WS.	Instruction manual references “Tor & Tor Pico 12.10 IssueB” dated December 2010.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Charnwood Tor stove manufactured by A.J.Wells and Sons Ltd, Bishops Way, Newport, Isle of Wight, PO30 5WS.	Installation and Use Instruction manual references “Tor 02. 10 Issue A”.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.
Chesneys 4 Series (4.6kW) Stoves: Flatford4, Hampstead 4, Alpine 4 also sold as: Sunbeam 4, Dakota 4, Providence 4.  Pacific 4 also sold as: Murano 4, Apollo 4.	Chesneys 4 series Instruction manual references “CH4K-V4” dated 7 <sup>th</sup> December 2009.  The appliance must be fitted with a mechanical stop to prevent closure of the air	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.

Chelsea 4 also sold as: Wellington 4, Guernsey 4, Belgravia 4.  Manufactured by Chesneys, 194-200 Battersea Park Road, London, SW11 4ND.	control beyond the 34mm open position.	
Chesneys 6 Series (7kW) Stoves:  Flatford 6, Barrington 6, Petworth 6, Hampstead 6, Alpine 6, also sold as:  Sunbeam 6, Dakota 6, Providence 6 and the Chelsea 6, also sold as: Wellington 6, Guernsey 6, Belgravia 6.  Manufactured by Chesneys, 194-200 Battersea Park Road, London, SW11 4ND.	Chesneys 6 series Instruction manual references “CH6K- V4” dated 7 <sup>th</sup> December 2009.  The appliance must be fitted with a mechanical stop to prevent closure of the air control beyond the 10mm open position.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.
Classic model 25, 35, 40, 49 and 60 wood pellet boilers manufactured by Hargassner Gesellschaft mit beschränkter Haftung (GmbH), Gunderding 8, A-4952, Weng, Austria.	The manufacturer’s installation manual for the Classic Pellet Boilers reference No. 22, Pellet Boilers, Type Classic 25,31,35,40,49,60, reference BA Classic 25L-60L Nr 21 0508.	Wood pellets. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.
Clean Air Systems CAS 200, 400 and 600 hand fired airheaters manufactured by Inventair Limited, Lancaster Road, Carnaby Industrial Estate, Bridlington, East Yorkshire, YO15 3QY.	To be operated in accordance with the Handbook for CAS hand fired airheater range reference 24600H version 1 dated January 2011.	Softwood, hardwood, medium density fibreboard (MDF) or chipboard offcuts. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Clean Air Systems CAS 300 Max airheater and cyclone manufactured by Inventair Limited, Lancaster Road, Carnaby Industrial Estate, Bridlington, East Yorkshire, YO15 3QY.	To be operated in accordance with the Handbook for CAS 300 Max airheater reference 300A version 1 dated January 2011.	Chipped or sawdust softwood, hardwood, medium density fibreboard (MDF) or chipboard offcuts. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Cleanburn CB900 Inset & Cleanburn CB900 Sonderskoven Inset, Wood	Instruction manual references “JINHCN09 Slider Stop Rev A” dated 17/01/12 and instruction manual	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as

*Status: This is the original version (as it was originally made).*

burning stoves. Manufactured by Hunter Stoves Limited,  Unit 6, The Old Mill Industrial Estate, Stoke Canon, Exeter, Devon, EX5 4RJ.	“JINHON09 Rev F” dated 24/01/12. Fitted with a mechanical stop to prevent secondary air control closure beyond the 20% open position when sold into smoke control areas.	a result of treatment with wood-preservatives or coatings.
Cleanburn R4 manufactured by Hunter Stoves Limited, Unit 6, The Old Mill Industrial Estate, Stoke Canon, Exeter, Devon, EX5 4RJ.	Instruction manual references “JINCLR04 Rev E” dated 02/12/11 and instruction manual “JINCLR04SCK revB” dated 05/12/11.  Fitted with “smoke control area kit JCLR0401” when sold into smoke control areas.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Clearburn Junior SE. Manufactured by Dean Forge Limited,  Dean Prior  Buckfastleigh  Devon  TQ11 0LS.	Instruction manual references “JRSE Issue 1” dated March 2012.  Fitted with a mechanical stop to prevent secondary air control closure beyond 83mm open position when sold into smoke control areas.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Clearview models 650 and 750 and the Vision 500 model, manufactured by Clearview Stoves Limited.	The manufacturer’s instructions dated 1 January 1993 and in the case of the Clearview models 650 and 750, bearing the reference “1/42” and in the case of Vision 500 model, bearing the reference “V1/42”.	No fuel shall be used other than firewood which has been split, stacked and air dried. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Clearview Pioneer 400, Solution 400 and Pioneer Oven wood burning stoves fitted with a tamperproof mechanical stop on the air slide/damper, manufactured by clearview Stoves of More Works, Bishops Castle, Shropshire, SY9 5HH.	The manufacturer’s instructions “Operating Instructions Clearview Vision/ Vision Inset/Pioneer & Solution” dated 1 <sup>st</sup> July 2006, reference V1/42, stamped and signed “Smoke Control”.	Air-dried wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.
Contura 510, Contura 520T, Contura 550, Contura 550A, Contura 550W, Contura 560T, Contura 560K, Contura 570, Contura 580, Contura 585,	Installation Instruction IAV SE/EX 0726-6 611821 Lighting Instruction BAV SE/ EX 0717-2 611820.	Untreated dry wood with less than 20% moisture.  The fuel must not contain halogenated organic



Contura 590, Contura 590T, manufactured by NIBE AB Box 134, 285 23 Markaryd, Sweden.	A permanent stop must be in place on the air inlet to prevent closure beyond the 20% open position.	compounds or heavy metals as a result of treatment with wood preservatives or coatings.
Contura 580W manufactured by NIBE AB Box 134, 285 23 Markaryd, Sweden.	Installation Instruction IAV SE/EX 0740-1 511911.  A permanent stop must be in place on the air inlet to prevent closure beyond the 20% open position.	Untreated dry wood with less than 20% moisture.  The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.
Contura 750 manufactured by Nibe, Box 134, S-285 23 Markaryd, Sweden.	Instruction manual references “811064 BAV SE-EX C750/780-1”.  The appliance must be fitted with a mechanical stop to prevent closure beyond the 28% open position.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Contura 750A manufactured by Nibe, Box 134, S-285 23 Markaryd, Sweden.	Instruction manual references “811064 BAV SE-EX C750/780-1”.  The appliance must be fitted with a mechanical stop to prevent closure beyond the 28% open position.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Contura 780 manufactured by Nibe, Box 134, S-285 23 Markaryd, Sweden.	Instruction manual references “811064 BAV SE-EX C750/780-1”.  The appliance must be fitted with a mechanical stop to prevent closure beyond the 28% open position.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Contura 810, 820 T, 850, 860 T, and 880, manufactured by Nibe Stoves, Box 134, S-285 23 Markaryd, Sweden.	Instruction manual references “811118 BAV SE-EX C800-1” dated 28-06-2011 and Supplementary operating instructions “811142 BAV GB-2” dated June 2011.  Fitted with a mechanical stop to prevent air control closure beyond the 38% open position.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Contura i4 Modern and Contura i4 Classic manufactured by Nibe Stoves, Box 134, S-285 23 Markaryd, Sweden.	Instruction manual references “811136 BAV C i4 GB-1” dated 04-07-2011 and supplementary operating	Dry wood logs. The fuel must not contain halogenated organic compounds or heavy metals as

*Status: This is the original version (as it was originally made).*

	<p>instructions “811142 BAV GB-2” dated June 2011.</p> <p>Fitted with a mechanical stop to prevent closure beyond the 28% open position.</p>	<p>a result of treatment with wood-preservatives or coatings.</p>
<p>Cove 2 SR manufactured by A.J.Wells &amp; Sons Ltd of Bishops Way, Newport, Isle of Wright, PO30 5WS.</p>	<p>Instruction manual references “Cove2SR 07.09 IssB” dated July 2009.</p> <p>A permanent stop must be in place on air control to prevent closure beyond the 14mm from the fully closed position.</p>	<p>Dry and split wood logs of a maximum length of 23cm.</p> <p>The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.</p>
<p>Crator JS5500 multi-fuel stove manufactured by James Smellie Limited, Unit N</p> <p>Leona Industrial Estate</p> <p>Nimmings Road</p> <p>Halesowen</p> <p>West Midlands</p> <p>B62 9JQ.</p>	<p>Instruction manual references “Crator multi-fuel stove instruction manual Issue 1” dated June 2012.</p>	<p>Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.</p>
<p>Cronspisen stove, using the 5 channel chimney system, manufactured by Cronspisen Produktion AB.</p>	<p>The manufacturer’s instructions bearing the reference “January 1992 Serial No. UM 351B”.</p>	<p>No fuel shall be used other than firewood which has been split, stacked and air dried. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.</p>
<p>CTC Ecoflex 15 and 20 manufactured by Enertech AB, Box 313, S-341 26 Ljungby, Sweden.</p>	<p>The manufacturer’s instructions dated 20<sup>th</sup> February 2007, reference 161 505 27 06/1.</p>	<p>Wood pellets. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.</p>
<p>D’Alessandro GSA 130 manufactured by D’Alessandro Termomeccanica, Contrada Cerreto, 55, 66010 Miglianico, Chieti, Italy.</p>	<p>Instruction manual references “2.0-1-QGSA130XEN0612” dated 26/06/2012.</p>	<p>Wood chips. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.</p>
<p>D’Alessandro Termomeccanica CS and CSA</p>	<p>Instruction manual references “Ver. 2.0 – QCSA2000XEN0209</p>	<p>Wood pellets. The fuel must not contain halogenated organic</p>

130, 180, 230 and 300kW manufactured by D'Alessandro Termomeccanica, Contrada Cerreto, 55, 66010 Miglianico, Chieti, Italy.	[UK SMOKE CONTROL]" dated 02/2009.	compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
D'Alessandro Termomeccanica CS and CSA 400, 500, 650, 800, 950, 1300, 1650 and 2000kW manufactured by D'Alessandro Termomeccanica, Contrada Cerreto, 55, 66010 Miglianico, Chieti, Italy.	Instruction manual references " Ver. 2.0 – QCSA2000XEN0209 [UK SMOKE CONTROL]" dated 02/2009.  The optional multi-cyclone must be fitted.	Wood pellets. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
D'Alessandro Termomeccanica CS and CSA boilers 40, 60, 80 and 100kW manufactured by D'Alessandro Termomeccanica, Contrada Cerreto, 55, 66010 Miglianico, Chieti, Italy.	Instruction manual references " Ver. 2.0 – QCSA100XXIT0209 [UK SMOKE CONTROL]" dated 02/2009.	Wood pellets. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
D'Alessandro Termomeccanica CSI 20kW manufactured by D'Alessandro Termomeccanica, Contrada Cerreto, 55, 66010 Miglianico, Chieti, Italy.	Instruction manual references "Ver. 2.0 – QCSI100XXIT0209" dated 02/2009.	Wood pellets. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Dartmoor 5 SE.  Manufactured by Dean Forge Limited  Dean Prior  Buckfastleigh  Devon  TQ11 0LS.	Instruction manual references "DM5 Issue 1" dated March 2012.  Fitted with a mechanical stop to prevent secondary air control closure beyond the 30% open position when sold into smoke control areas.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Defiant Encore manufactured by VCW International Limited.	The manufacturer's instructions dated November 1991 and bearing the reference "200-8632".	No fuel shall be used other than firewood that has been split, stacked and air-dried. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Design 800 Green, Wood Burning Stove.	Instruction manual reference "07DH8000A" dated 11/11.	Wood logs. The fuel must not contain halogenated organic

**Status:** This is the original version (as it was originally made).

<p>Manufactured by Bodart &amp; Gonay Limited, Rue De Lambinon, 3 Harze, Belgium 4920.</p>	<p>Fitted with a “UK kit for smokeless areas Design 800” when sold into smoke control areas.</p>	<p>compounds or heavy metals as a result of treatment with wood-preservatives or coatings.</p>
<p>Di Lusso R4 manufactured by Hunter Stoves Limited, Unit 6, The Old Mill Industrial Estate, Stoke Canon, Exeter, Devon, EX5 4RJ.</p>	<p>Instruction manual references “JINDLU04 Rev E” dated 02/12/11 and instruction manual “JINDLU04SCK revB” dated 05/12/11.  Fitted with “smoke control area kit JDLU0401” when sold into smoke control areas.</p>	<p>Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.</p>
<p>Dimplex SE Selborne 5 stove manufactured by ESSE Engineering Ltd, Ouzledale Foundry, Long Ing, Barnoldswick, Lancashire, BB18 6BN.</p>	<p>Instruction manual references “SE Selbourne 5 Issue 1” dated 08 2009.  All appliances will be fitted with a mechanical stop to prevent closure beyond the 50% open position when sold into smoke control areas.</p>	<p>Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.</p>
<p>Dovre 250 (model DV-250) manufactured by Dovre NV, Nijverheidsstraat 18, BE-2381 Weelde, Belgium.</p>	<p>The manufacturer’s instructions, reference PM 250 Issue 1.  A permanent stop must be in place on the secondary air inlet to prevent closure beyond the 75% open position.</p>	<p>Untreated dry wood. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.</p>
<p>Dovre Vintage 30 (DV-VIN30, DV-VIN30WH, DV-TBVIN30 and DV-TBVIN30WH), Dovre Vintage 35 (DV-VIN35, DV-VIN35WH, DV-TBVIN35 and DV-TBVIN35WH) and Dovre Vintage 50 (DV-VIN50, DV-VIN50WH, DV-TBVIN50 and DV-TBVIN50WH) stoves manufactured by Dovre N.V. Nijverheidsstraat 18, B-2381 Weelde, Belgium.</p>	<p>Instruction manual references 03.27681.100 dated April 2011 and PM813 Issue 1 dated May 2012 and when fitted with a permanent stop preventing closure of the secondary air supply beyond 50%.</p>	<p>Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.</p>

<p>Dovre woodstove models 500G and 700G manufactured by Dovre Castings Limited.</p>	<p>The manufacturer’s instructions dated October 1995 bearing the following reference—</p> <p><b>(i)</b> model 500G: “500G”;</p> <p><b>(ii)</b> model 700G: “700G”.</p>	<p>No fuel shall be used other than wood. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.</p>
<p>Dunsley Yorkshire Multifuel Stove manufactured by Dunsley Heat Limited.</p>	<p>The manufacturer’s instructions dated 5<sup>th</sup> August 1998, reference A/22160 as amended by those dated 4<sup>th</sup> December 2004, reference D13.</p>	<p>Untreated dry wood. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.</p> <p>Peat or peat briquettes with, in either case, less than 25% moisture.</p> <p>Union Coal Briquettes, manufactured by Rheinbraun AG of Germany comprising lignite compressed into briquettes of approximately 15cm in length with square ends and with a sulphur content not exceeding 1% of the total weight.</p> <p>CPL Wildfire, manufactured by Coal Products Limited, Immingham, which comprise bituminous coal with a volatile content of 32% to 36% (as to approximately 96% of the total weight) and a cold cure resin binder (as to the remaining weight); are manufactured from those constituents by a process involving roll-pressing; have an average weight of either 80-90 grams or 160-170 grams; and have a sulphur content not exceeding 1.8% of the total weight.</p>

**Status:** This is the original version (as it was originally made).

<p>Dunsley Yorkshire Multifuel Stove and Boiler manufactured by Dunsley Heat Limited.</p>	<p>The manufacturer's instruction dated 5<sup>th</sup> August 1998, reference A/22160, as amended by those dated 4<sup>th</sup> October 2004, reference GHD/DUN4B/1.</p>	<p>Untreated dry wood. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.</p> <p>Peat or peat briquettes with, in either case, less than 25% moisture.</p> <p>Union Coal Briquettes, manufactured by Rheinbraun AG of Germany comprising lignite compressed into briquettes of approximately 15cm in length with square ends and with a sulphur content not exceeding 1% of the total weight.</p> <p>CPL Wildfire, manufactured by Coal Products Limited, Immingham, which comprise bituminous coal with a volatile content of 32% to 36% (as to approximately 96% of the total weight) and a cold cure resin binder (as to the remaining weight); are manufactured from those constituents by a process involving roll-pressing; have an average weight of between 80-90 grams or between 160-170 grams; and have a sulphur content not exceeding 1.8% of the total weight.</p>
<p>Dunsley Yorkshire Stove, manufactured by Dunsley Heat Limited.</p>	<p>The manufacturer's instructions dated 5<sup>th</sup> August 1998, reference A/22160 as amended by those dated 4<sup>th</sup> December 2004, reference D13.</p>	<p>Untreated dry wood. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.</p> <p>Peat or peat briquettes with, in either case, less than 25% moisture.</p> <p>Union Coal Briquettes, manufactured by Rheinbraun AG of Germany comprising</p>

		<p>lignite compressed into briquettes of approximately 15cm in length with square ends and with a sulphur content not exceeding 1% of the total weight.</p> <p>CPL Wildfire, manufactured by Coal Products Limited, Immingham, which comprise bituminous coal with a volatile content of 32% to 36% (as to approximately 96% of the total weight) and a cold cure resin binder (as to the remaining weight); are manufactured from those constituents by a process involving roll-pressing; have an average weight of either 80-90 grams or 160-170 grams; and have a sulphur content not exceeding 1.8% of the total weight.</p>
Dunsley Yorkshire Woodburning Stove, manufactured by Dunsley Heat Limited.	The manufacturer's instructions dated 4 <sup>th</sup> December 2004, reference D13W.	Untreated dry wood. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Dunsley Yorkshire Woodburning Stove and Boiler manufactured by Dunsley Heat Limited.	The manufacturer's instructions dated 4 <sup>th</sup> December 2004, reference D13W together with the manufacturer's instructions dated 4 <sup>th</sup> October 2004 reference GHD/DUN4B/1.	Untreated dry wood. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Earlwood manufactured by ACR Heat Products Limited, Unit One Weston Works, Weston Lane, Tyseley, Birmingham B11 3RP.	Instruction manual reference "EW 1MF technical manual" dated 02 2009.  When the primary air control is in the closed position, it remains permanently open by 5mm and is prevented from closing fully by a screw.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.
Ecco Stove E580 Manufactured by Landy Vent UK Limited, Foster House, 2 Redditch Road, Studley, Warwickshire, B80 7AX.	Instruction manual reference "Ecco Stove 580 manual" dated 12/12/11.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment

*Status: This is the original version (as it was originally made).*

		with wood-preservatives or coatings.
Ecco Stove E678 manufactured by Landy Vent UK Limited, Foster House, 2 Redditch Road, Studley, Warwickshire, B80 7AX.	Instruction manual references “01/11/3” dated 28/01/2011.  Fitted with a system to fix the secondary air (airwash) to a 4mm open position.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Ecco Stove E850 manufactured by Landy Vent UK Limited, Foster House, 2 Redditch Road, Studley, Warwickshire, B80 7AX.	Instruction manual references “02/10” dated 10 <sup>th</sup> October 2010. The appliance must be fitted with a system that prevents the closure of the secondary air flaps beyond 4mm (3 turns).	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Eclipse Junior, Standard, Senior Jumbo 30 and Jumbo 50 incinerators, manufactured by Northern Incinerators Limited.	The manufacturer’s instructions dated 21 June 1988 and bearing the reference “NORCIN TECH 88”.	No fuel shall be used, other than fuel consisting of scrap wood and foliage. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Ecofire Barbara wood pellet stove boiler manufactured by Palazzetti Lelio S.p.A, Via Roveredo 103, Porcia (PN), 33080, Italy.	Instruction manual references “cod. 004770900” dated 10/2011 and supplementary information “Clean Air Act 1993 and Smoke Control Areas” reference 004723000 dated 01/2012.	Wood pellets. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Ecofire Giulia Idro, Ecofire Kelly Idro Plus and Ecofire Tania Idro wood pellet stove boilers manufactured by Palazzetti Lelio S.p.A, Via Roveredo 103, Porcia (PN), 33080, Italy.	Instruction manual references “cod.004770432” dated 02/11 and supplementary information “Clean Air Act 1993 and Smoke Control Areas” reference 004723000 dated 01/2012.	Wood pellets. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Eco-Ideal Eco 1 Stove manufactured by Hunter Stoves Limited, unit 6, Old Mill Industrial Estate, Stoke Canon, Exeter. Devon EX5 4RJ.	Instruction manual references “JINECO01 revC” dated 20/07/11.  The appliance must be fitted with a permanent stop that prevents closure of the secondary air slider beyond 30% open.	Dry wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Eco-Ideal Eco 2 Stove manufactured by Hunter Stoves Limited, unit 6, Old Mill	Instruction manual references “JINECO02 revC” dated 20/07/11.	Dry wood logs. The fuel must not contain halogenated organic compounds or heavy metals as



Industrial Estate, Stoke Canon, Exeter. Devon EX5 4RJ.	The appliance must be fitted with a permanent stop that prevents closure of the secondary air slider beyond 30% open.	a result of treatment with wood-preservatives or coatings.
Eco-Ideal Eco 4 Stove manufactured by Hunter Stoves Limited, unit 6, Old Mill Industrial Estate, Stoke Canon, Exeter, Devon EX5 4RJ.	Instruction manual references “JINECO04 revC” dated 20/07/11.	Dry wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Eco-Ideal Eco 6 Stove manufactured by Hunter Stoves Limited, unit 6, Old Mill Industrial Estate, Stoke Canon, Exeter, Devon EX5 4RJ.	Instruction manual references “JINECO06 revC” dated 20/07/11.	Dry wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
E-Compact 15 wood pellet stove boiler manufactured by Wood Energy Solutions  Donaskeigh  Tipperary  Co. Tipperary  Ireland.	Instruction manual references “ E-COMPACT 15 Outdoor Pellet Boiler v1.5” dated 05 2012.	6mm wood pellets. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Ecowarm Crystal 6 Manufactured by Saltfire Stoves Limited, Units 1 and 2, The Omega Centre, Sandford Lane, Wareham, BH20 4DY.	Instruction manual references “ECO7operation-Revision 2A” dated 24.01.2011.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Ellipse manufactured by La Nordica Spa, Via Summano 104 M. Precalcino, 36030 Vicenza, Italy.	Instruction manual references “7196901-Rev.09” dated 22 <sup>nd</sup> December 2010.  Fitted with a mechanical stop to prevent closure of the secondary air control beyond the 40% open position.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Endress USF-W 250 manufactured by Endress Holzfeuerungsanlagen GmbH, Industriestraße 18, D-91593 Burgbernheim.	Instruction manual references “Operating and Maintenance manual Endress USF –W250” dated 03/2010.  Reference EMAN – USFW250.	Wood Chips and pellets. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

*Status: This is the original version (as it was originally made).*

Endress USF-W 350 manufactured by Endress Holzfeuerungsanlagen GmbH, Industriestraße 18, D-91593 Burgbernheim.	Instruction manual references “Operating and Maintenance manual Endress USF –W350” dated 03/2010 Reference EMAN – USFW350.	Wood Chips and pellets. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Endress USF-W 500 manufactured by Endress Holzfeuerungsanlagen GmbH, Industriestraße 18, D-91593 Burgbernheim.	Instruction manual references “Operating and Maintenance manual Endress USF –W500” dated 03/2010 Reference EMAN – USFW500.	Wood Chips and pellets. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Endress USF-W 800 manufactured by Endress Holzfeuerungsanlagen GmbH, Industriestraße 18, D-91593 Burgbernheim.	Instruction manual references “Operating and Maintenance manual Endress USF –W800” dated 03/2010 Reference EMAN – USFW800.	Wood Chips and pellets. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Endress USF-W 1000 manufactured by Endress Holzfeuerungsanlagen GmbH, Industriestraße 18, D-91593 Burgbernheim.	Instruction manual references “Operating and Maintenance manual Endress USF –W1000” dated 03/2010 Reference EMAN – USFW1000.	Wood Chips and pellets. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Endress VR-S 300 manufactured by Endress Holzfeuerungsanlagen GmbH, Industriestraße 18, D-91593 Burgbernheim.	Instruction manual references “Operating and Maintenance manual Endress VR-S300” dated 03/2010 Reference EMAN – VRS300.	Wood Chips and pellets. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Endress VR-W 400 manufactured by Endress Holzfeuerungsanlagen GmbH, Industriestraße 18, D-91593 Burgbernheim.	Instruction manual references “Operating and Maintenance manual Endress VR –W400” dated 03/2010 Reference EMAN – VRW400.	Wood Chips and pellets. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Endress VR-W 600 manufactured by Endress Holzfeuerungsanlagen GmbH, Industriestraße 18, D-91593 Burgbernheim.	Instruction manual references “Operating and Maintenance manual Endress VR-W600” dated 03/2010 Reference EMAN – VRW600.	Wood Chips and pellets. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Endress VR-W 900 manufactured by Endress Holzfeuerungsanlagen GmbH, Industriestraße 18, D-91593 Burgbernheim.	Instruction manual references “Operating and Maintenance manual Endress VR-W900” dated 03/2010 Reference EMAN – VRW900.	Wood Chips and pellets. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
En-tech model ENP 10, 15, 18, 25 and 35 boilers manufactured by En-tech Energietechnikproduktion Gesellschaft mit beschränkter Haftung (GmbH), Gewerbezone 3, A-9300 St Veit, Glan-Hunnenbrunn, Austria.	The manufacturer’s installation manual dated 11/2009, reference IMENP 10-35 11/2009 for the Firefox pellet boiler.	Wood pellets. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.
En-tech model PK 15 and 25 boilers manufactured by En-tech Energietechnikproduktion Gesellschaft mit beschränkter Haftung (GmbH), Gewerbezone 3, A-9300 St Veit, Glan-Hunnenbrunn, Austria.	The manufacturer’s installation manual dated 11/2009, reference IMPK PK15/25 11/2009 EN for the Firefox pellet boiler.	Wood pellets. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.
En-tech model PK 45 boilers manufactured by En-tech Energietechnikproduktion Gesellschaft mit beschränkter Haftung (GmbH), Gewerbezone 3, A-9300 St Veit, Glan-Hunnenbrunn, Austria.	The manufacturer’s installation manual dated 11/2009, reference IMPK PK45 11/2009 EN for the Firefox pellet boiler.	Wood pellets. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.
EOS 30 346kW output wood pellet boiler with multicyclone manufactured by: Uniconfort srl, Via dell’Industria 21, 35018, San Martino Di Lupari (PD) Italy.	Use and Maintenance manual reference “Uniconfort EOS30 Manual v1” dated July 2011.	Wood pellets. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.
EOS 35 407kW output wood pellet boiler with multicyclone manufactured by: Uniconfort srl, Via dell’Industria 21, 35018, San Martino Di Lupari (PD) Italy.	Use and Maintenance manual reference “Uniconfort EOS35 Manual v1” dated July 2011.	Wood pellets. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.
EOS 40 464kW output wood pellet boiler with multicyclone manufactured by: Uniconfort srl, Via dell’Industria 21,	Use and Maintenance manual reference “Uniconfort EOS40 Manual v1” dated July 2011.	Wood pellets. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment

**Status:** This is the original version (as it was originally made).

35018, San Martino Di Lupari (PD) Italy.		with wood preservatives or coatings.
EOS 60 700kW output wood pellet boiler with multicyclone manufactured by: Uniconfort srl, Via dell'Industria 21, 35018 San Martino Di Lupari (PD), Italy.	Installation Instruction manual references "K135-07332 Uniconfort MUN v 2" dated September 2010.	6mm diameter wood pellets. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Esse 100DD SE 5kW stove manufactured by Esse Engineering Limited, Ouzedale Foundry, Long Ing, Barnoldswick, BB18 6BN.	Instruction manual references "10/11 (PP) INSTR.ST-100DDSE/u" dated October 2011.  The fitting of a system to prevent closure of the air controls beyond the 50% open position must be implemented.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Esse 125SE stove manufactured by Esse Engineering Ltd, Ouzedale Foundry, Long Ing, Barnoldswick, Lancashire, BB18 6BN.	Instruction manual references "Esse 125SE Issue 1" dated 08 2009. All appliances will be fitted with a mechanical stop to prevent closure beyond the 50% open position when sold into smoke control areas.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with word preservatives or coatings.
Esse 301 SE stove manufactured by Esse Engineering Ltd, Ouzledale Foundry, Long Ing, Barnoldswick, Lancashire, BB18 6BN.	Instruction manual references "v45" dated 09/11/2010. The primary air control must not be fully air tight when closed.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Esse 350 SE stove manufactured by Esse Engineering Ltd, Ouzledale Foundry, Long Ing, Barnoldswick, Lancashire, BB18 6BN.	Instruction manual references "v45" dated 09/11/2010.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Esse 1622 inset stove manufactured by Esse Engineering Limited, Long Ing, Barnoldswick, Lancashire, BB18 6BN.	Installation and operation manual reference "1622/ Integra INSET revision c" dated July 2010.  All appliances used in smoke control areas must be fitted with a mechanical stop to fix secondary air control fully open.	Dry wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.
ETA HACK 20, 25, 35, 50, 70, 90, 130 and 200 woodchip	Instruction manual reference "HACK20-200_Bedienung_2011-06-01"	Wood chips. The fuel must not contain halogenated organic

boilers. Manufactured by ETA Heiztechnik Gesellschaft mit beschränkter Haftung (GmbH), A 4716, Hofkirchen an der Trattnach, Gewerbepark 1, Austria.	dated 06/2011. Integrated flue gas recirculation system must be used when using wood chips with a moisture content below 15%.	compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
ETA HACK 20, 25, 35, 50, 70, 90, 130 and 200 woodchip boilers. Manufactured by ETA Heiztechnik Gesellschaft mit beschränkter Haftung (GmbH), A 4716, Hofkirchen an der Trattnach, Gewerbepark 1, Austria.	Instruction manual reference “HACK20-200_Bedienung_2011-06-EN” dated 06/2011. Integrated flue gas recirculation system must be used when burning wood pellets.	Wood pellets. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
ETA PC 20, 25 and 32 wood pellet boilers. Manufactured by ETA Heiztechnik Gesellschaft mit beschränkter Haftung (GmbH), A 4716, Hofkirchen an der Trattnach, Gewerbepark 1, Austria.	Instruction manual reference “PC20-32_Bedienung_2011-06-EN” dated 06/2011.	Wood pellets. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
ETA PE-K 35, 50, 70 and 90 wood pellet boilers. Manufactured by ETA Heiztechnik Gesellschaft mit beschränkter Haftung (GmbH), A 4716, Hofkirchen an der Trattnach, Gewerbepark 1, Austria.	Instruction manual reference “PE-K35-90_Bedienung_2011-06-EN” dated 06/2011.	Wood pellets. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
ETA PU 7, 11 and 15 wood pellet boilers. Manufactured by ETA Heiztechnik Gesellschaft mit beschränkter Haftung (GmbH), A 4716, Hofkirchen an der Trattnach, Gewerbepark 1, Austria.	Instruction manual reference “PU7-15_Bedienung_2011-06-EN” dated 06/2011.	Wood pellets. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
ETA SH 20, 30, 40, 50 and 60 wood gasification boilers. Manufactured by ETA Heiztechnik Gesellschaft mit beschränkter Haftung (GmbH), A 4716, Hofkirchen an der Trattnach, Gewerbepark 1, Austria.	Instruction manual reference “SH20-60_Bedienung_2011-06-EN” dated 06/2011.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
eVolution 4 Inset manufactured by Broseley Fires Limited, Knights Way, Battlefields Ent Park, Shrewsbury, Shropshire, SY1 3AB.	Instruction manual references “eVo 4&7 Inset MS11-11” dated 9 <sup>th</sup> November 2011.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

**Status:** This is the original version (as it was originally made).

	Fitted with a system to prevent closure of the secondary air control beyond the 15mm open position.	
eVolution 5 model number M-EVO5 manufactured by Broseley Fires Limited, Knights Way, Battlefield Enterprise Park, Shrewsbury, Shropshire, SY1 3AB.	Instruction manual references “eVo 5 MS07-11” dated 8 <sup>th</sup> July 2011 fitted with a system that prevents the closure of the air control to less than 70% open.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
eVolution 7 Inset manufactured by Broseley Fires Limited, Knights Way, Battlefields Ent Park, Shrewsbury, Shropshire, SY1 3AB.	Instruction manual references “eVo 4&7 Inset MS11-11” dated 9 <sup>th</sup> November 2011.  Fitted with a system to prevent closure of the secondary air control beyond the 8mm open position.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
eVolution 26 boiler stove manufactured by Broseley Fires Ltd, Knights Way, Battlefield Ent Park, Shrewsbury, Shropshire, SY1 3AB.	Instruction manual references “MS10-11c” dated 09/01/2012.  The appliance must be fitted with a mechanical stop to prevent closure beyond the 40% open position when sold into smoke control areas.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Evotherm P50, P100, P120, P150, P170, P200 pellet boilers manufactured by Evotherm, Heiztechnik Vertriebs Gesellschaft mit beschränkter Haftung (GmbH), Seeleiten 24, AT 5120, St Pantaleon, Austria.	The manufacturer’s instructions “Operating manual” reference Version 1/2010/Rev 4.21.	Wood pellets. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.
Extraflame: Babyfiamma, Bella and Bella Lux, Clementina, Comfort Maxi, Contessa, Davina, Davina Plus and Davina Steel, Duchessa and Duchessa Steel, Ecologica, Esmeralda and Esmeralda Crystal, Falò 1CP, Falò 2CP and Falò 1XP, Isabella, Karolina and Preziosa, all of which are manufactured by Extraflame S.p.a in Montecchio Precalcino (Vicenza), Italy.	The manufacturer’s operating instructions dated 5 <sup>th</sup> March 2007, reference 004275101 011.	Wood pellets. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.

Extraflame Comfort Mini manufactured by Extraflame S.p.a. in Montecchio Precalcino (Vicenza), Italy.	The manufacturer's operating instructions dated 2 <sup>nd</sup> October 2006, reference 004275115 REV 005.	Wood pellets. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.
Extraflame Idro manufactured by Extraflame S.p.a in Montecchio Precalcino (Vicenza), Italy.	The manufacturer's operating instructions dated 28 <sup>th</sup> August 2006, reference 004275128 REV 002.	Wood pellets. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.
Extraflame Lucrezia Idro and Lucrezia Steel manufactured by Extraflame S.p.a in Montecchio Precalcino (Vicenza), Italy.	The manufacturer's operating instructions dated 12 <sup>th</sup> July 2006, reference 004275110 REV 011.	Wood pellets. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.
Farm 2000 boiler models BB154, BB154A and BB154/2 (when used with the Farm 2000 conversion kit BB154/2Vcx), manufactured by Farm 2000 Limited.	The manufacturer's instructions dated May 1994 bearing the reference "BB154/2VC", and maintained and operated in accordance with the manufacturer's instructions dated September 1993 bearing the reference "BB154/2V".	No fuel shall be used other than cereal straw.
Farm 2000 boiler models HT60, HT70, HT80 and BB154/2V manufactured by Farm 2000 Limited.	The manufacturer's instructions which in the case of models HT60, HT70 and HT80, are dated 1 <sup>st</sup> July 1993 and bear the reference "HT60/70/80", and in the case of model BB154/2V are dated 1 <sup>st</sup> September 1993 and bear the reference "9/93".	No fuel shall be used other than cereal straw.
Farm 2000 model HT6 (when used with the Farm 2000 conversion kit HT60cx), the HT6PLUS and HT600 (when each is used with the Farm 2000 conversion kit HT70cx), and the HT7 and the HT8 (when each is used with the Farm 2000 conversion kit HT80cx), manufactured by Farm 2000 Limited.	The manufacturer's instructions dated May 1994 bearing the references "HT6780", and "HT6781" and maintained and operated in accordance with the manufacturer's instructions dated 1 <sup>st</sup> July 1993 bearing the reference "HT60/70/80".	No fuel shall be used other than cereal straw.
FDC5 Stove manufactured by Charlton & Jenrick Ltd	Instruction manual references "FDC Issue 02" dated 04/12.	Wood logs. The fuel must not contain halogenated organic

**Status:** This is the original version (as it was originally made).

<p>Unit D Stafford Park 2 Telford Shropshire TF3 3AR.</p>	<p>The fitting of a system that prevents closure of the secondary air control slots beyond the 3.5mm open position must be implemented.</p>	<p>compounds or heavy metals as a result of treatment with wood-preservatives or coatings.</p>
<p>FDC5i inset stove manufactured by Charlton &amp; Jenrick Ltd Unit D Stafford Park 2 Telford Shropshire TF3 3AR.</p>	<p>Instruction manual references “FDCi Issue 06” dated 03/12.  The fitting of a system that prevents closure of the secondary air control slots beyond the 3.5mm open position must be implemented.</p>	<p>Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.</p>
<p>FDC5iT Taper inset stove manufactured by Charlton &amp; Jenrick Ltd Unit D Stafford Park 2 Telford Shropshire TF3 3AR.</p>	<p>Instruction manual references “FDCiT Issue 1” dated 04/12.  The fitting of a system that prevents closure of the secondary air control slots beyond the 5mm open position must be implemented.</p>	<p>Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.</p>
<p>FDC5iW Wide inset stoves manufactured by Charlton &amp; Jenrick Ltd Unit D Stafford Park 2 Telford Shropshire TF3 3AR.</p>	<p>Instruction manual references “FDCi Issue 06” dated 03/12.  The fitting of a system that prevents closure of the secondary air control slots beyond the 9mm open position must be implemented.</p>	<p>Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.</p>
<p>FDC5W Wide stove manufactured by Charlton &amp; Jenrick Ltd Unit D Stafford Park 2 Telford Shropshire</p>	<p>Instruction manual references “FDC Issue 02” dated 04/12.  The fitting of a system that prevents closure of the secondary air control slots beyond the 7mm open position must be implemented.</p>	<p>Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.</p>



TF3 3AR.		
Fireball manufactured by La Nordica Spa, Via Summano 104 M. Precalcino, 36030 Vicenza, Italy.	Instruction manual references “7196801-Rev.07” dated 22 <sup>nd</sup> December 2010. Fitted with a mechanical stop to prevent closure of the secondary air control beyond the 40% open position.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Firefox 5CB, Vega 100CB Sirius 405CB and Flame 5CB (4.9kW) stoves manufactured by Percy Doughty & Co, Imperial Point, Express Trading Estate, Stonehill Road, Farnworth, Bolton, BL4 9TN.	Instruction manual references “FFXCBA” dated January 2010.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.
Firefox 5 Clean Burn II, Gallery Classic 5 Clean Burn, Sirius 405 Clean Burn and Sirius 405 Classic Clean Burn, manufactured by Percy Doughty & Co Limited, Imperial Point, Express Trading Estate, Stone Hill Road, Farnworth, Bolton, BL4 9TN.	Instruction manual references “FF5CBII REV:A” dated June 2011.  Fitted with a mechanical stop to prevent secondary air closure beyond the 50% open position.	Dry wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Firefox 8 Clean Burn, Gallery Classic 8 Clean Burn, Sirius 545 Clean Burn and Sirius 545 Classic Clean Burn manufactured by Percy Doughty & Co Limited, Imperial Point, Express Trading Estate, Stone Hill Road, Farnworth, Bolton, BL4 9TN.	Instruction manual references “FF8CB REV:A” dated June 2011.  Fitted with a mechanical stop to prevent secondary air closure beyond the 50% open position.	Dry wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Fireglow Eco 7, Manufactured by Saltfire Stoves Limited, Units 1 and 2, The Omega Centre, Sandford Lane, Wareham, BH20 4DY.	Instruction manual references “ECO7operation-Revision 2A” dated 24.01.2011.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Fireline FGi5 stove manufactured by Charlton & Jenrick Ltd  Unit D Stafford Park 2  Telford	Instruction manual references “FGi.FPi.FXi Issue 06” dated 03/12.  The fitting of a system that prevents closure of the secondary air control slots	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

*Status: This is the original version (as it was originally made).*

Shropshire TF3 3AR.	beyond the 3.5mm open position must be implemented.	
Fireline FP5, Fireline FX5, Fireline Fpi 5kW and Fireline Fxi 5kW manufactured by Charlton and Jenrick Ltd, Charlton and Jenrick G1-G2, Halesfield 5, Telford, Shropshire, TF7 4QJ.	Instruction manual references “Issue 03” dated 03/10.  The fitting of a system that prevents the closure of the secondary air control beyond the 3.5mm open position should be implemented.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.
Fireline FP5W and FX5W Freestanding stove manufactured by Charlton & Jenrick Ltd  Unit D Stafford Park 2  Telford  Shropshire  TF3 3AR.	Instruction manual references “FX.FP.Issue 06” dated 03/12.  The fitting of a system that prevents closure of the secondary air control slots beyond the 7mm open position must be implemented.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Fireline FPi5T, FGi5T, FXi5T Taper inset stoves manufactured by Charlton & Jenrick Ltd  Unit D Stafford Park 2  Telford  Shropshire  TF3 3AR.	Instruction manual references “FXiT.FPiT.FGiT Issue 01” dated 03/12.  The fitting of a system that prevents closure of the secondary air control slots beyond the 5mm open position must be implemented.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Fireline FPi5W, FGi5W, FXi5W Wide inset stoves manufactured by Charlton & Jenrick Ltd  Unit D Stafford Park 2  Telford  Shropshire  TF3 3AR.	Instruction manual references “FGi.FPi.FXi Issue 06” dated 03/12.  The fitting of a system that prevents closure of the secondary air control slots beyond the 9mm open position must be implemented.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Firematic 25, 50, 90 and 150 manufactured by HERZ Armaturen	The manufacturer’s instructions dated June 2005,	Chipped wood, wood pellets or planed wood shavings.

<p>Ges.m.b.H, Geschäftsbereich HERZ, Feuerungstechnik, A-8272 Sebersdorf 138, Austria.</p>	<p>reference Bedienungsanleitung Firematic V 1.1 ENG doc.</p>	<p>The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.</p>
<p>Firematic 45 and 60 manufactured by HERZ Armaturen Ges.m.b.H, Geschäftsbereich HERZ, Feuerungstechnik, A-8272 Sebersdorf 138, Austria.</p>	<p>Instruction manual references “05.007 Operating instructions – FM (1Ph) 20 35 45 60 v2.3” dated “08/2009”.</p>	<p>Wood pellets conforming to ÖNORM M7135 with diameter of 6mm or wood chips up to a maximum size of 50mm and maximum water content 35%.</p> <p>The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.</p>
<p>Firematic FM 130, FM 151, FM180, FM199 manufactured by Herz Energietechnik GmbH, Herzstraße, 1, 7423 Pinkafeld, Österreich/Austria.</p>	<p>Instruction manual references “Operating Instructions Herz firematic 130 – 199 BioControl” version Betriebsanleitung firematic 20-201 BioControl Englisch V 3.1.</p>	<p>Wood Chips and Wood Pellets. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.</p>
<p>Firestorm 4.5 SE manufactured by The Heat Resistant Glass Company  Limited  Unit 2 Bracewell Avenue  Poulton Industrial Estate  Poulton Le Fylde  FY6 8JF.</p>	<p>Instruction manual references “4.5KW SE Issue (6928) 1” dated 28th April 2012.</p> <p>Fitted with a stop that will only allow a minimum 3mm air gap between the air control plate and the appliance when the secondary air is turned down to its minimum position.</p>	<p>Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.</p>
<p>Firestorm 6.5 SE manufactured by The Heat Resistant Glass Company  Limited  Unit 2 Bracewell Avenue  Poulton Industrial Estate  Poulton Le Fylde  FY6 8JF.</p>	<p>Instruction manual references “6.5KW SE Issue (6928) 3” dated 28th April 2012.</p> <p>Fitted with a stop that will only allow a minimum air gap 6mm between the air control plate and the appliance when the secondary air is turned down to its minimum position.</p>	<p>Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.</p>

*Status: This is the original version (as it was originally made).*

<p>Firestorm 10 SE manufactured by The Heat Resistant Glass Company Limited Unit 2 Bracewell Avenue Poulton Industrial Estate Poulton Le Fylde FY6 8JF.</p>	<p>Instruction manual references “10 KW SE Issue (6928) 2” dated 28th April 2012.  Fitted with a stop that will only allow a minimum air gap 6mm between the air control plate and the appliance when the secondary air is turned down to its minimum position.</p>	<p>Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.</p>
<p>Firewarm 06C inset stove manufactured by Heat Design, 30 Hawthorn Road, Western Industrial Estate, Naas Road, Dublin 12, Ireland.</p>	<p>Instruction manual references “FW06C” dated 26/07/12.  A permanent stop to prevent closure of the secondary air control beyond 20% open must be implemented.</p>	<p>Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.</p>
<p>Firewarm 4SE stove manufactured by Heat Design, 30 Hawthorn Road, Western Industrial Estate, Naas Road, Dublin 12, Ireland.</p>	<p>Instruction manual references “FW468SE” dated 25/07/12.  The fitting of a system to prevent closure of the secondary air control beyond 5mm open must be implemented.</p>	<p>Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.</p>
<p>Firewarm 6SE stove manufactured by Heat Design, 30 Hawthorn Road, Western Industrial Estate, Naas Road, Dublin 12, Ireland.</p>	<p>Instruction manual references “FW468SE” dated 25/07/12.  The fitting of a system to prevent closure of the secondary air control beyond 75% from closed must be implemented.</p>	<p>Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.</p>
<p>Firewarm 8SE stove manufactured by Heat Design, 30 Hawthorn Road, Western Industrial Estate, Naas Road, Dublin 12, Ireland.</p>	<p>Instruction manual references “FW468SE” dated 25/07/12.  The fitting of a system to prevent closure of the secondary air control beyond 25% from closed must be implemented.</p>	<p>Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.</p>
<p>Firewarm 11C inset stove manufactured by Heat Design, 30 Hawthorn Road, Western Industrial Estate, Naas Road, Dublin 12, Ireland.</p>	<p>Instruction manual references “FW11C” dated 26/07/12.  A permanent stop to prevent closure of the secondary air</p>	<p>Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment</p>

	control beyond 20% open must be implemented.	with wood-preservatives or coatings.
Flatford 5K, Barrington 5K, Hampstead 5K Wood Burning Stoves.  Manufactured by Chesneys Limited, 192 – 200 Battersea Park Road  London  SW11 4ND.	Instruction manual references “CH5K – V1” dated 14 <sup>th</sup> March 2012.  Fitted with a mechanical stop to prevent secondary air control closure beyond the 18mm open position when sold into smoke control areas.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Franco Belge Model 134 08 11 Savoy EA 8kW output wood burning stove;  Franco Belge Model 134 08 09 Savoy MK II Elegance multifuel stove with KEA 13408 smoke control kit manufactured by: Franco Belge, Staub Fonderie SA, Rue Orphée Variscotte, 59660, Merville, France.	The Savoy EA Technical Manual, document reference 1290-1, reviewed 9 July 2009.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Franco Belge Montfort MK2 wood burning stove manufactured by:  Franco Belge, Staub Fonderie SA, Rue Orphée Variscotte, 59660, Merville, France.	Instruction manual reference “1295-3” dated 17 <sup>th</sup> November 2009.  The appliance must be fitted with a mechanical stop to prevent closure of the secondary air control beyond the 25% open position.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Fröling Lambdamat Commercial wood chip boiler models 500, 750 and 1000 manufactured by Fröling Heizkessel-und Behälterbau Gesellschaft mit beschränkter Haftung (GmbH), A-4710 Grieskirchen, Industriestrasse 12, Austria.	Lambdamat Communal Operating and Installation Manual reference B 069 01 04 of February 2004.	Wood chips. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.
Fröling P4 8, 15, 20, 25, 32, 38, 48 and 60 Pellet Boilers manufactured by Fröling Heizkessel-und Behälterbau Ges.m.b.H, Industriestraße 12, A-4710 Grieskirchen, Austria.	Instruction manual reference “B0430408_en” dated July 2009.	Wood pellets with a diameter of 6mm. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.

*Status: This is the original version (as it was originally made).*

<p>Fröling P4 80 and P4 100 wood pellet boilers manufactured by Fröling Heizkessel- und Behälterbau Ges.m.b.H.</p> <p>Industriestraße 12</p> <p>A - 4710 Grieskirchen.</p>	<p>Instruction manual references “B043 – Version 8” dated 05 2012.</p>	<p>Wood pellets. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.</p>
<p>Fröling S4 Turbo 15 15kW, Fröling S4 Turbo 22 22kW, Fröling S4 Turbo 28 28kW, Fröling S4 Turbo 34 34kW, Fröling S4 Turbo 40 40kW, Fröling S4 Turbo 50 50kW, and Fröling S4 Turbo 60 60kW manufactured by Fröling Heizkessel- und Behälterbau Ges.m.b.H, Industriestraße 12, A – 4710 Grieskirchen, Austria.</p>	<p>Assembly Instruction manual “M0970208” dated November 2008 and Operating instruction manual “B0510108” dated November 2008.</p>	<p>Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.</p>
<p>Fröling T4 24, 30, 40, 50, 60, 75, 90, 100 and 110kW boilers manufactured by Fröling Heizkessel- und Behälterbau Ges.m.b.H. Industriestraße 12 A - 4710 Grieskirchen.</p>	<p>Instruction manual references “B071 - Version 05” dated 05 2012.</p>	<p>Wood pellets or wood chips. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.</p>
<p>Fröling Turbomatic 28, 35, 48 and 55 manufactured by Fröling Heizkessel-und Behälterbau Ges.m.b.H, Industriestraße 12, A-4710 Grieskirchen, Austria.</p>	<p>The manufacturer’s installation manual dated November 2003, reference M 060 01 03.</p> <p>The manufacturer’s operating manual dated August 2002, reference 99229a.</p>	<p>Wood chip less than 35% moisture content and meeting ÖNORM M 7133: 1998 size class G30. Wood pellets of 6mm diameter and a moisture content below 10%. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.</p>
<p>Fröling Turbomatic 85, 100 and 110 manufactured by Fröling Heizkessel-und Behälterbau Ges.m.b.H, Industriestraße 12, A-4710 Grieskirchen, Austria.</p>	<p>The manufacturer’s instruction manual dated November 2003, reference M 060 01 03.</p> <p>The manufacturer’s operating manual dated August 2002, reference 99229a.</p>	<p>Wood chip less than 35% moisture content and meeting ÖNORM M 7133: 1998 of either size class G30 or G50. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.</p>

		Wood pellets of 6mm diameter and a moisture content below 10%. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.
Fröling Turbomat 150 and 220 manufactured by Fröling Heizkessel-und Behälterbau Ges.m.b.H, Industriestraße 12, A-4710 Grieskirchen, Austria.	The manufacturer's operating instructions dated August 2003, reference B0310003.	Wood pellets or wood chips.  The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.
Fröling Turbomat 320 and 500 manufactured by Fröling Heizkessel-und Behälterbau Ges.m.b.H, Industriestraße 12, A-4710 Grieskirchen, Austria.	The manufacturer's operating instructions dated November 2004, reference B0340004.	Wood pellets or wood chips.  The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.
Fröling TX150 150kW boiler with Exhaust Gas Recirculation device manufactured by Fröling Heizkessel-und Behälterbau Ges.m.b.H., Industriestraße 12, Austria.	Installation Instruction manual references "M1130009" dated 09/2010 and operating instruction manual "B 067 00 09" dated 09/2010.	Wood chips with a moisture content $\leq 30\%$ and a maximum cross sectional area of $5\text{cm}^2$ or wood pellets with a moisture content of $\leq 10\%$ and a maximum diameter of 10mm. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Fröling TX 200 199kW and TX 250 250kW boilers with Exhaust Gas Recirculation device manufactured by Fröling Heizkessel- und Behälterbau Ges.m.b.H.  Industriestraße 12  A - 4710 Grieskirchen.	Instruction manual references "B067 – Version 03" dated 05 2012.	Wood chips or wood pellets. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Gilles HPKI-K 180, 195, 240, 300, 360, 450, 550, 700, 900, 995, 1200 and 1600 boilers. Manufactured by Gilles Energie und Umwelttechnik GmbH, Koaserbauer Str. 16A-4810 Gmunden, Austria.	"Operating Instruction HPKI-K Underfeed Stoking. 1-general HPKI-K underfeed stoking" dated November 2008.	Wood pellets or wood chips. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

*Status: This is the original version (as it was originally made).*

<p>Gilles HPK-RA 13kW, 15kW, 20kW, 25kW, 30kW, 35kW, 40kW, 45kW, 49kW, 60kW, 70kW, 75kW, 85kW, 95kW, 100kW, 120kW and 145kW manufactured by GILLES Energie-und Umwelttechnik GmbH, Koaserbauer Str. 16 A-4810 Gmunden, Austria.</p>	<p>Operating instructions dated January 2007, reference Gilles/0-145/1.</p>	<p>Wood pellets or wood chips.  The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.</p>
<p>Gilles HPK-RA 160 Manufactured by Gilles Energie – und Umwelttechnik GmbH, Koaserbauer Str. 16A-4810 Gmunden, Austria.</p>	<p>Instruction and operation manuals “BD 200-01a-01” and dated 11/2008, “BD 200-01a-02” and dated 11/2008, “BD 200-01a-03” and dated 11/2008, “BD 200-01a-04” and dated 11/2008, “BD 200-01a-06” and dated 11/2008, “BD 200-03a-07” and dated 11/2008, and “BD 200-03a-09” and dated 11/2008.</p>	<p>Wood Chips and pellets. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.</p>
<p>Gilles HPK UTSK 150kW, 180kW, 240kW and 300kW boilers manufactured by GILLES Energie und Umwelttechnik GmbH, Koaserbauer Str. 16, A-4810 Gmunden, Austria.</p>	<p>Operating instructions dated January 2007, reference Gilles/150-300/1.</p>	<p>Wood pellets or wood chips.  The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.</p>
<p>Gilles HPK UTSK 360kW Boiler manufactured by GILLES Energie und Umwelttechnik GmbH, Koaserbauer Str. 16, A-4810 Gmunden, Austria.</p>	<p>Operating instructions dated January 2008, reference Gilles/360/1.</p>	<p>Wood pellets or wood chips. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.</p>
<p>Gilles UTSK 450kW, 550kW boilers manufactured by GILLES Energie-und Umwelttechnik GmbH, Koaserbauer Str. 16 A-4810 Gmunden, Austria.</p>	<p>Operating instructions dated January 2008, reference Gilles /360/1.</p>	<p>Wood pellets or wood chips.  The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.</p>
<p>Gilles UTSK 700kW, 900kW boilers manufactured by GILLES Energie-und Umwelttechnik GmbH, Koaserbauer Str. 16 A-4810 Gmunden, Austria.</p>	<p>Operating instructions dated January 2008, reference Gilles /360/1.</p>	<p>Wood pellets or wood chips.  The fuel must not contain halogenated organic compounds or heavy metals as</p>



		a result of treatment with wood preservatives or coatings.
Gilles UTSK 1200kW, 1600kW boilers manufactured by GILLES Energie- und Umwelttechnik GmbH, Koaserbauer Str. 16 A-4810 Gmunden, Austria.	Operating instructions dated January 2008, reference Gilles /360/1.	Wood pellets or wood chips.  The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.
Grant Spira Condensing Wood Pellet Boiler 6-26kW model number WPS626 and 9-36kW model number WPS936 manufactured by Grant UK Ltd, Hopton House, Hopton Industrial Estate, Devizes, Wiltshire, SN10 2EU.	Instruction manual references “IRL NO.012 Rev; 1” dated April 2012.	6mm wood pellets. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Guntamatic Biocom and Powercorn 50 and 75 manufactured by GUNTAMATIC Heiztechnik GmbH A-4722 PEUERBACH, Bruck 7.	Instruction manual references “GUN/BIO/OP/V1/0709” dated 29/07/09.	Wood pellets with a diameter of 6mm and a length of between 10 and 30mm.  The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.
Guntamatic Biocom and Powercorn 100 manufactured by GUNTAMATIC Heiztechnik GmbH A-4722 PEUERBACH, Bruck 7.	Instruction manual references “GUN/BIO/OP/V1/0709” dated 29/07/09.	Wood pellets with a diameter of 6mm and a length of between 10 and 30mm or wood chip less than 35% moisture content and meeting ÖNORM M 7133: 1998 size class G30.  The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.
Guntamatic Powerchip 50 and 75 manufactured by GUNTAMATIC Heiztechnik GmbH A-4722 PEUERBACH, Bruck 7.	Instruction manual references “GUN/POW/OP/V1/0709” dated 29/07/09.	Wood pellets with a diameter of 6mm and a length of between 10 and 30mm.  The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.

**Status:** This is the original version (as it was originally made).

<p>Guntamatic Powerchip 100 manufactured by GUNTAMATIC Heiztechnik GmbH A-4722 PEUERBACH, Bruck 7.</p>	<p>Instruction manual references “GUN/POW/OP/V1/0709” dated 29/07/09.</p>	<p>Wood pellets with a diameter of 6mm and a length of between 10 and 30mm or wood chip less than 35% moisture content and meeting ÖNORM M 7133: 1998 size class G30.</p> <p>The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.</p>
<p>Haat LD, MD and HD Incinerators manufactured by Haat Incineration Limited.</p>	<p>The manufacturer’s instructions dated March 1988 and bearing the reference “HAAT/1/CAA/3/88”.</p>	<p>No fuel shall be used other than fuel consisting of scrap wood and foliage. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.</p>
<p>Haat Pioneer AB1 Incinerators models 12, 20, 28 and 36 manufactured by Haat Incineration Limited.</p>	<p>The manufacturer’s instructions published in October 1989 and bearing the reference “HAAT/2/CAA/10/89”.</p>	<p>No fuel shall be used other than wood, used in the mixtures by volume recommended in Appendix A of the manufacturer’s instructions. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.</p>
<p>Hamont CATfire 350 USZI pellet boiler fitted with CATfire 300 cyclone, both manufactured by Hamont Contracting and Trading, spol. S.r.o., Sedlište 227, postal code 739 36, district Frýdek-Místek Czech Republic.</p>	<p>Operating instruction reference “Operating Manual for Boilers CATfire 150-500kW” effective from 1/1/2008.</p>	<p>Wood pellets with a 6mm diameter and a maximum length of 30mm.</p> <p>The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.</p>
<p>Handöl 31, Handöl 31A, Handöl 32, Handöl 32A, Handöl 33T, Handöl 34T, Handöl 35T, Varde Ovne Look 1, Varde Ovne Look 2, Varde Ovne Look 3, manufactured by NIBE AB Box 134, 285 23 Markaryd, Sweden.</p>	<p>Installation Instructions IAV SE/EX 0811-4 511941 Lighting Instructions BAV SE/EX H30 511942.</p> <p>A permanent stop must be in place on the air inlet to prevent closure beyond the 45% open position.</p>	<p>Untreated dry wood with less than 20% moisture.</p> <p>The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.</p>

Handöl 50, Handöl 51, Handöl 52, Handöl 52T, Handöl 53, Handöl 54, Handöl 54T, Handöl 51L, Varde Ovne S1, Varde Ovne S2, Varde Ovne S3, manufactured by NIBE AB Box 134, 285 23 Markaryd, Sweden.	Installation Instructions IAV SE/EX 0737-4 511866 Lighting Instructions BAV SE/EX 0717-1 511865.  A permanent stop must be in place on the air inlet to prevent closure beyond the 45% open position.	Untreated dry wood with less than 20% moisture.  The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.
Harrie Leenders Cylon, Harrie Leenders Doran 160, Harrie Leenders Doran 190, Harrie Leenders Fuga S, Harrie Leenders Fuga eL, Harrie Leenders Stor, Harrie Leenders Signa, Stoves manufactured by Harrie Leenders, Industrieweg 25, 5688 DP Oirschot, Netherlands.	Instruction manual references “Supplementary Instructions Amended June 2010”.  All appliances will be fitted with a mechanical stop to prevent closure of the air slide beyond the 15mm open position when sold into smoke control areas.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.
HDG Compact models 25/35 (25kW, 35kW) wood chip and pellet boilers manufactured by HDG Bavaria Gesellschaft mit beschränkter Haftung (GmbH), Siemensstrasse 22, 84323 Massing, Germany.	The manufacturer’s operating instructions for the HDG Compact 25/35 with HDG Compact Hydronic reference HDG Compact Version V01 of April 2009.	Wood chip or wood pellets. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.
HDG Compact models 50/65 (50kW, 65kW) wood chip and pellet boilers manufactured by HDG Bavaria Gesellschaft mit beschränkter Haftung (GmbH), Siemensstrasse 22, 84323 Massing, Germany.	The manufacturer’s operating instructions for the HDG Compact 50/65 with HDG Hydronic reference HDG Compact Version V03 of April 2009.	Wood chip or wood pellets. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.
HDG Compact models 80 (80kW) wood chip and pellet boiler manufactured by HDG Bavaria Gesellschaft mit beschränkter Haftung (GmbH), Siemensstrasse 22, 84323 Massing, Germany.	The manufacturer’s operating instructions for the HDG Compact 80 with HDG Hydronic reference HDG Compact Version V03 of April 2009.	Wood chip or wood pellets. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.
HDG Compact models 100 (100kW) wood chip and pellet boilers manufactured by HDG Bavaria Gesellschaft mit beschränkter Haftung (GmbH), Siemensstrasse 22, 84323 Massing, Germany.	The manufacturer’s operating instructions for the HDG Compact 100/150/200 reference HDG Compact 100-200 Version V1 of July 2008.	Wood chip or wood pellets. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.
HDG Compact models 150, 200 (150kW, 200kW) wood	The manufacturer’s operating instructions for the HDG	Wood chip or wood pellets. The fuel must not

*Status: This is the original version (as it was originally made).*

<p>chip and pellet boiler with model HDG 3113 cyclone manufactured by HDG Bavaria Gesellschaft mit beschränkter Haftung (GmbH), Siemensstrasse 22, 84323 Massing, Germany.</p>	<p>Compact 100/150/200 reference HDG Compact 100-200 Version V1 of July 2008.</p>	<p>contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.</p>
<p>HDG Euro models 30, 40 and 50 (30kW, 40kW and 50kW) wood log boilers manufactured by HDG Bavaria Gesellschaft mit beschränkter Haftung (GmbH), Siemensstrasse 22, 84323 Massing, Germany.</p>	<p>The manufacturer’s operating instructions for the HDG Euro 30/40/50 with Lambda Control 1 reference HDG Euro V3.0 with HDG Lambda Control 1 Version V1 of June 2008.</p>	<p>Split wood logs of 500 mm length and maximum edge length of 120 mm and a residual moisture content of 20%. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.</p>
<p>HDG Navora models 20, 25 and 30 (20kW, 25kW and 30kW) wood log boilers manufactured by HDG Bavaria Gesellschaft mit beschränkter Haftung (GmbH), Siemensstrasse 22, 84323 Massing, Germany.</p>	<p>The manufacturer’s operating instructions for the HDG Navora 20/25/30 with Lambda Control 1 reference HDG Navora 20/25/30 with HDG Lambda Control 1 Version V2 of June 2008.</p>	<p>Split wood logs of 500 mm length and maximum edge length of 120 mm and a residual moisture content of 20%. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.</p>
<p>HDG Pelletmaster model PM15, 15kW wood pellet boiler manufactured by HDG Bavaria Gesellschaft mit beschränkter Haftung (GmbH), Siemensstrasse 22, 84323 Massing, Germany.</p>	<p>The manufacturer’s operating instructions for the HDG Pelletmaster 15/25 reference HDG Pelletmaster Version V1 of October 2006.</p>	<p>Wood pellets. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.</p>
<p>Heat Design TR5c inset stove manufactured by Charlton &amp; Jenrick Ltd  Unit D Stafford Park 2  Telford  Shropshire  TF3 3AR.</p>	<p>Instruction manual references “TRc Issue 02” dated 04/12.  The fitting of a system that prevents closure of the secondary air control slots beyond the 3.5mm open position must be implemented.</p>	<p>Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.</p>
<p>Heat Design TR5iT Taper inset stove manufactured by Charlton &amp; Jenrick Ltd  Unit D Stafford Park 2  Telford</p>	<p>Instruction manual references “TRiT Issue 01” dated 04/12.  The fitting of a system that prevents closure of the secondary air control slots</p>	<p>Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.</p>

Shropshire TF3 3AR.	beyond the 5mm open position must be implemented.	
Heat Design TR6c Wide inset stove manufactured by Charlton & Jenrick Ltd Unit D Stafford Park 2 Telford Shropshire TF3 3AR.	Instruction manual references “TRc Issue 02” dated 04/12.  The fitting of a system that prevents closure of the secondary air control slots beyond the 9mm open position must be implemented.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Herz BioFire BF 500 manufactured by Herz Engietechnik GmbH, Herstraße 1, 7423 Pinkafeld, Österreich/Austria.	Instruction manual references “Operating instructions HERZ BioFire 500 – 1000 Biocontrol” Reference “Betriebsanleitung Biofire 500-1000 Biocontrol Englisch V1.2.doc”.	Wood chips and pellets. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Herz BioFire BF 600 manufactured by Herz Engietechnik GmbH, Herstraße 1, 7423 Pinkafeld, Österreich/Austria.	Instruction manual references “Operating instructions HERZ BioFire 500 – 1000 Biocontrol” Reference “Betriebsanleitung Biofire 500-1000 Biocontrol Englisch V1.2.doc”.	Wood chips and pellets. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Herz BioFire BF 800 manufactured by Herz Engietechnik GmbH, Herstraße 1, 7423 Pinkafeld, Österreich/Austria.	Instruction manual references “Operating instructions HERZ BioFire 500 – 1000 Biocontrol” Reference “Betriebsanleitung Biofire 500-1000 Biocontrol Englisch V1.2.doc”.	Wood chips and pellets. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Herz BioFire BF 1000 manufactured by Herz Engietechnik GmbH, Herstraße 1, 7423 Pinkafeld, Österreich/Austria.	Instruction manual references “Operating instructions HERZ BioFire 500 – 1000 Biocontrol” Reference “Betriebsanleitung Biofire 500-1000 Biocontrol Englisch V1.2.doc”.	Wood chips and pellets. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Herz Firematic FM 80 manufactured by Herz Engietechnik GmbH, Herstraße 1, 7423 Pinkafeld, Österreich/Austria.	Assembly and installation instructions  “HERZ firematic 20 – 101 BioControl”	Wood chips and pellets. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

**Status:** This is the original version (as it was originally made).

	<p>Reference “04.001” Installation Instructions – “Herz Firematic (1Ph) 20-101”</p> <p>Operating instructions</p> <p>“HERZ firematic 20 – 101 BioControl”</p> <p>Reference “Betriebsanleitung firematic 20-101 BioControl Englisch V 2.53.doc”.</p>	
<p>Herz Firematic FM 100 manufactured by Herz Engietechnik GmbH, Herstraße 1, 7423 Pinkafeld, Österreich/ Austria.</p>	<p>Assembly and installation Instructions “HERZ firematic 20 – 101 BioControl” Reference “04.001” Installation Instructions – “Herz Firematic (1Ph) 20-101”. Operating instructions “HERZ firematic 20 – 101 BioControl” Reference “Betriebsanleitung firematic 20-101 BioControl Englisch V 2.53.doc.</p>	<p>Wood chips and pellets. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood- preservatives or coatings.</p>
<p>Heta Scanline 7D, 7AD, 7BD, 7CD and 7DD wood burning stoves distributed in the UK by Pevex Enterprises Limited, Unit 16 Seven Acres Business Park, Newbourne Road, Waldringfield Nr Woodbridge, IP12 4PS.</p>	<p>Instruction manual references “Pevex1006/AH/ver2” and dated June 2011.</p> <p>Fitted with permanent stops to ensure that the primary and secondary air controls do not close beyond 95% and 50% respectively.</p>	<p>Dry wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood- preservatives or coatings.</p>
<p>Heta Scanline 500D, 510D, 520D and 530D wood burning stoves distributed in the UK by Pevex Enterprises Limited, Unit 16 Seven Acres Business Park, Newbourne Road, Waldringfield Nr Woodbridge, IP12 4PS.</p>	<p>Instruction manual references “Pevex1005/AH/ver2” and dated June 2011.</p> <p>Fitted with permanent stops to ensure that the primary and secondary air controls do not close beyond 95% and 50% respectively.</p>	<p>Dry wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood- preservatives or coatings.</p>
<p>Highlander 5 Clean Burn Manufactured by Dunsley Heat Limited, Bridge Mills, Huddersfield, Holmfirth, West Yorkshire, HD9 3TW.</p>	<p>Instruction manual references “Highlander. The Dunsley – Enviroburn-5. Clean Burn Stove Installation and operating instructions. D12-01-09, D060-01-09, D13-01-09, D12-12-08”.</p>	<p>Wood logs conforming to BS EN 13240:2001.</p> <p>The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.</p>

<p>Highlander 7 Enviroburn Solo multi-fuel stove (product codes 00325, 00326 and 00327) manufactured by Dunsley Heat Limited, Bridge Mills, Huddersfield Road, Holmfirth, Huddersfield, HD9 3TW.</p>	<p>Installation and operating instructions manual reference “ENVIRO 7 DB001” dated 15/6/2012.</p> <p>Appliance fitted with a mechanical stop to prevent closure of the secondary air-wash beyond 2mm. Four fixed 5mm diameter air holes are provided for the tertiary air supply.</p>	<p>Dry wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.</p>
<p>Horse Flame Little Artemis model number HF277-SE Wood Burning Stove. Manufactured by Hi-Flame Fireplace UK Limited</p> <p>Unit 5A Holmes Chapel Business Park</p> <p>Manor Lane</p> <p>Holmes Chapel</p> <p>Cheshire</p> <p>CW4 8AF.</p>	<p>Instruction manual references “AL905-SE/UK-NI-ROI/V2-D.18-07-12” dated July 2012.</p> <p>Fitted with a mechanical stop to prevent closure of the secondary air control beyond the 3mm open position.</p>	<p>Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.</p>
<p>Horse Flame Precision 1 model number HF905-SE, UK Distribution Hi-Flame Limited, Unit 7B, Holmes Chapel Business Park, Manor Lane, Holmes Chapel, Cheshire, CW4 8AF.</p>	<p>Instruction manual references “HF905/UK-NI-ROI/V2.1-06-11” dated June 2011.</p> <p>Fitted with a mechanical stop to prevent closure of the main air control beyond the 50% open position.</p>	<p>Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.</p>
<p>Horse Flame Precision II model number HF907-SE Wood Burning Stove. Manufactured by Hi-Flame Fireplace UK Limited</p> <p>Unit 5A Holmes Chapel Business Park</p> <p>Manor Lane</p> <p>Holmes Chapel</p> <p>Cheshire</p>	<p>Instruction manual references “HF907-SE/UK-NI-ROI/V3-D. 14-07-12” dated July 2012.</p> <p>Fitted with a mechanical stop to prevent secondary air control closure beyond the 20% open position, and a 70mm opening of the door rope seal to allow a constant flow of air when sold into smoke control areas.</p>	<p>Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.</p>

*Status: This is the original version (as it was originally made).*

CW4 8AF.		
Hothouse 06C inset stove manufactured by Heat Design, 30 Hawthorn Road, Western Industrial Estate, Naas Road, Dublin 12, Ireland.	Instruction manual references “HH06C” dated 26/07/12. A permanent stop to prevent closure of the secondary air control beyond 20% open must be implemented.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Hothouse 4SE manufactured by Heat Design, 30 Hawthorn Road, Western Industrial Estate, Naas Road, Dublin 12, Ireland.	Instruction manual references “HH468SE” dated 25/07/12.  The fitting of a system to prevent closure of the secondary air control beyond 5mm open must be implemented.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Hothouse 6SE stove manufactured by Heat Design, 30 Hawthorn Road, Western Industrial Estate, Naas Road, Dublin 12, Ireland.	Instruction manual references “HH468SE” dated 25/07/12.  The fitting of a system to prevent closure of the secondary air control beyond 75% from closed must be implemented.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Hothouse 8SE stove manufactured by Heat Design, 30 Hawthorn Road, Western Industrial Estate, Naas Road, Dublin 12, Ireland.	Instruction manual references “HH468SE” dated 25/07/12.  The fitting of a system to prevent closure of the secondary air control beyond 25% from closed must be implemented.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Hothouse 11C inset stove manufactured by Heat Design, 30 Hawthorn Road, Western Industrial Estate, Naas Road, Dublin 12, Ireland.	Instruction manual references “HH11C” dated 26/07/12.  A permanent stop to prevent closure of the secondary air control beyond 20% open must be implemented.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Hotpod Limited Edition manufactured by Hotpod LLP, PO Box 137, St Ives, Cornwall, TR26 2WW.	Instruction manual reference “Version 3” dated June 2011.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Hotpod Unlimited manufactured by Hotpod LLP, PO Box 137, St Ives, Cornwall, TR26 2WW.	Instruction manual reference “Version 3” dated June 2011.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment



		with wood-preservatives or coatings.
Hoval AgroLyt 20, 25, 35, 45 and 50 manufactured by Hoval AG, Austrasse 70, 9490 Vaduz, Liechtenstein.	Installation and operation manuals dated January 2006, reference 4 205/ 194/00, and June 2006, reference 205 193/00.	Wood logs with less than 20% moisture. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.
Hoval BioLyt 160 pellet boiler manufactured by Hoval Limited, Northgate, Newark, Nottinghamshire, NG24 1JN.	Instruction manual references “Hoval Operating instructions, wood pellet heating boiler BioLyt (50, 70, 120, 140, 160)” dated 03/07/2008 and “Technical information Assembly instructions” dated 03/10/2009.	Wood pellets. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.
Hoval BioLyt 50 wood pellet fired boiler (49kW thermal output), manufactured in Slovakia by Hoval AG, Austrasse 70, FL-9490, Vaduz.	The manufacturer’s technical information and installation instructions dated October 2005, reference 4 204794/000 and operating instructions dated January 2006, reference 4 204 793/01.	Wood pellets. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.
Hoval BioLyt 50 and 70 manufactured by Hoval AG, Austrasse 70, 9490 Vaduz, Liechtenstein.	Installation and operation manuals referenced 4 204 794/01, and 4 204 793/02, dated June 2007.	Wood pellets. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.
Hoval Forester MGS 150, 180, 240, 300, 360, 450, 550, 700, 900 boilers manufactured by Schmid AG, Wood firing systems PO Box 42, CH-8380 Eschikon Switzerland.	Instruction manual references “Hoval Forester MGS_MMXXXv1” (Where XXX is the unit size i.e. 150) dated July 2011.	Wood pellets or wood chips following CEN/TS 14961. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Hoval Forester UFS 180, 240, 300, 360, 450, 550, 700, 900, 1200, 1600 manufactured by Schmid AG, Wood firing Systems PO Box 42, CH-8360 Eschlikon, Switzerland.	Instruction manual references “Forester UFS” dated November 2009.	Wood pellets or wood chips following CEN/TS 14961.  The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.
Hoval STU 150, 200, 250, 300, 350, 425 and 500 manufactured by Hoval	Installation and operation manuals referenced STUman/01, dated November	Wood pellets. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment

*Status: This is the original version (as it was originally made).*

Ltd, Northgate, Newark, Nottinghamshire, NG24 1JN.	2007, or referenced STU/man/01/1, dated June 2008.	with wood preservatives or coatings.
Hoval STU 600, 800, and 1000 manufactured by Hoval Ltd, Northgate, Newark-on-Trent, Nottinghamshire, NG24 1JN.	Installation and operation manual referenced STU/man/01, dated July 2007, or the installation and operation manual referenced STU/man/01/1, dated June 2008.	Wood pellets. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.
HSV 50 + WTH 45, 49 or 55 boilers manufactured by Hargassner Gesellschaft mit beschränkter Haftung (GmbH), Gunderding 8, A-4952, Weng, Austria.	The manufacturer's installation manual version 44 for Wood Chip and Pellet Stoves, type HSV 30-100. Reference BA HSV30-100 RA/RAP V44 0608.	Wood chip or wood pellets.  The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.
HSV 80 + WTH 70, or 80 boilers manufactured by Hargassner Gesellschaft mit beschränkter Haftung (GmbH), Gunderding 8, A-4952, Weng, Austria.	The manufacturer's installation manual version 44 for Wood Chip and Pellet Stoves, type HSV 30-100. Reference BA HSV30-100 RA/RAP V44 0608.	Wood chip or wood pellets.  The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.
HSV 100 + WTH 100 boilers manufactured by Hargassner Gesellschaft mit beschränkter Haftung (GmbH), Gunderding 8, A-4952, Weng, Austria.	The manufacturer's installation manual version 44 for Wood Chip and Pellet Stoves, type HSV 30-100. Reference BA HSV30-100 RA/RAP V44 0608.	Wood chip or wood pellets.  The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.
Hunter Herald 4 manufactured by Hunter Stoves Limited, Unit 6, Old Mill Industrial Estate, Stoke Canon, Devon, EX5 4RJ.	Instruction manual references "JINHH04 revC" dated 22/09/2011 and "JINHH04&HHC05 Slider Stop revA" dated 22/07/11.  The appliance must be fitted with a permanent stop that prevents closure of the secondary air slider beyond 30% open.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Hunter Herald 5 Compact manufactured by Hunter Stoves Limited, Unit 6, Old Mill Industrial Estate, Stoke Canon, Devon, EX5 4RJ.	Instruction manual references "JINHH05 revC" dated 22/09/2011 and "JINHH04&HHC05 Slider Stop revA" dated 22/07/11.  The appliance must be fitted with a permanent stop that prevents closure of the	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

	secondary air slider beyond 30% open.	
Hunter Herald 5 Slimline manufactured by Hunter Stoves Limited, Unit 6, Old Mill Industrial Estate, Stoke Canon, Devon, EX5 4RJ.	Instruction manual references “JINHHW05 revC” dated 22/09/2011.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Hunter Herald 6 manufactured by Hunter Stoves Limited, Unit 6, Old Mill Industrial Estate, Stoke Canon, Devon, EX5 4RJ.	Instruction manual references “JINHH04 revC” dated 22/09/2011.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Hunter Herald i4 manufactured by Hunter Stoves Limited, Unit 6, The Old Mill Industrial Estate, Stoke Canon, Exeter, Devon, EX5 4RJ.	Instruction manual references “JINHVR04 Rev E” dated 02/12/11 and instruction manual “JINHVR04SCK revB” dated 05/12/11.  Fitted with “smoke control area kit JHVR0401” when sold into smoke control areas.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Huntingdon 25 clear door (model number 7057) and Huntingdon 25 tracery door (model number 7058) manufactured by Stovax Limited, Falcon Road, Sowton Industrial Estate, Exeter, Devon, EX2 7LF.	The manufacturer’s instruction manual reference PM 249 Issue 1.  A permanent stop must be in place on the secondary air inlet to prevent closure beyond the 75% open position.	Untreated dry wood. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.
Hwam 30 (4.5kW Nominal Thermal Output) fitted with mechanism to prevent closure of the air wash/secondary air control, manufactured by HWAM Heat Design AS Nydamsvej 53 8362 Horning, Denmark.	Euroheat Distributors (HBS) Limited’s operational instructions dated November 2006, Reference: “IN 1141 Ed.”.  The appliance must be fitted with a mechanism to prevent closure of the air wash/ secondary air control.	Untreated dry wood. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.
Hwam Beethoven and Hwam Beethoven H (4.5kW Nominal Thermal Output) manufactured by HWAM Heat Design AS Nydamsvej 53 8362 Horning, Denmark.	Euroheat Distributors (HBS) Limited’s operational instructions dated November 2006, Reference: “IN 1141 Ed B”.  The appliance must be fitted with a mechanism to prevent	Untreated dry wood. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.

*Status: This is the original version (as it was originally made).*

	closure of the air wash/ secondary air control.	
Hwam Mozart (4.5kW Nominal Thermal Output) fitted with mechanism to prevent closure of the air wash/secondary air control, manufactured by HWAM Heat Design AS Nydamsvej 538362 Horning, Denmark.	Euroheat Distributors (HBS) Limited's operational instructions dated November 2006, Reference: "IN 1141 Ed B".  The appliance must be fitted with a mechanism to prevent closure of the air wash/ secondary air control.	Untreated dry wood. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.
Hwam Ravel (4.5kW Nominal thermal Output) fitted with mechanism to prevent closure of the air wash/secondary air control, manufactured by HWAM Heat Design AS Nydamsvej 53 8362 Horning, Denmark.	Euroheat Distributors (HBS) Limited's operational instructions dated November 2006, Reference: "IN 1141 Ed B".  The appliance must be fitted with a mechanism to prevent closure of the air wash/ secondary air control.	Untreated dry wood. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.
Hwam Vivaldi (4.5kW nominal thermal output) manufactured by HWAM Heat Design AS Nydamsvej 53, 8362 Hørning, Denmark.	Euroheat Distributors (HBS) Limited's operational instructions dated November 2006, Reference: "IN 1141 Ed B".  The appliance must be fitted with a mechanism to prevent closure of the air wash/ secondary air control.	Untreated dry wood. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.
Insert 50 Crystal manufactured by La Nordica Spa, Via Summano 104 M. Precalcino, 36030 Vicenza, Italy.	Instruction manual references "6096801-Rev.17" dated 22 <sup>nd</sup> December 2010. Fitted with a mechanical stop to prevent closure of the secondary air control beyond the 40% open position when sold into smoke control areas.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Insert 70 Crystal manufactured by La Nordica Spa, Via Summano 104 M. Precalcino, 36030 Vicenza, Italy.	Instruction manual references "6096801-Rev.17" dated 22 <sup>nd</sup> December 2010.  Fitted with a mechanical stop to prevent closure of the secondary air control beyond the 40% open position.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Insert 80 Crystal manufactured by La Nordica Spa, Via Summano 104 M. Precalcino, 36030 Vicenza, Italy.	Instruction manual references “6096801-Rev.17” dated 22 <sup>nd</sup> December 2010. Fitted with a mechanical stop to prevent closure of the secondary air control beyond the 40% open position.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Insert 100 Crystal manufactured by La Nordica Spa, Via Summano 104 M. Precalcino, 36030 Vicenza, Italy.	Instruction manual references “6096801-Rev.17” dated 22 <sup>nd</sup> December 2010.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Instyle 400 and 550 stoves manufactured by Dik Geurts Haardkachels BV, Industreweg Oost 11, 6662, NE Elst (Gld), The Netherlands.	Instruction manual referenced “Instruction_manual_Instyle_1209_ENG”.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.
Intrepid II woodstove manufactured by Vermont Castings Inc.	The manufacturer’s instructions bearing the reference “AMENDED NO. 20917C UK MAY 1990”.	No fuel shall be used other than 400 millimetre firewood that has been split, stacked and air-dried. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.
Italy Built In manufactured by La Nordica Spa, Via Summano 104 M, Precalcino, 36030, Vicenza, Italy.	Instruction manual references “7095401 Rev.02” dated 13/12/2010.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Italy Termo DSA manufactured by La Nordica Spa, Via Summano 104 M. Precalcino 36030, Vicenza, Italy.	Instruction manual references “7095802 Rev.06” dated 01/02/2011.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Ivanhoe JS5000 multi-fuel stove manufactured by James Smellie Limited, Unit N  Leona Industrial Estate  Nimmings Road  Halesowen  West Midlands	Instruction manual references “Ivanhoe multi-fuel stove instruction manual Issue 1” dated June 2012.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

**Status:** This is the original version (as it was originally made).

B62 9JQ.		
Jansen Design stove using the 5 channel system, manufactured by Kakkelovnsmakeriet A/S.	The fireplace shall be installed, maintained and operated in accordance with the manufacturer's instructions bearing the reference "CSC-JDS-01" dated 21/10/91.	No fuel should be used other than wood. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Jetmaster 18f stove manufactured by Jetmaster Fires Limited, Unit 2, Peacock Trading Estate, Goodwood Road, Eastleigh, Hampshire  SO50 4NT.	Instruction manual references "106870/18f/60f/Issue No.5" dated June 2011.	Dry wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Jotul catalyst stove models 8TDIC and 12TDIC manufactured by Jotul Limited.	The manufacturer's instructions dated November 1995 bearing the following reference—  <b>(i)</b>  model 8TDIC: "JT8/001" and "J/S/001";  <b>(ii)</b>  model 12TDIC: "JT12/001" and "JT/S/001".	No fuel should be used other than wood. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Jotul F100 manufactured by Jotul UK Limited, Unit 1, The IO Centre, Nash Road, Park Farm, Redditch, Worcestershire, B98 7AS.	Instruction manual reference "129980" dated September 2002 and smoke control area modification reference "UK F100 SC appendix" dated 2010. The appliance must be fitted with a permanent stop that prevents the closure of the secondary air control beyond the 50% open position.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Jotul F162, F163, F262 and F263.  Manufactured by Jotul UK Limited,  1 The IO Centre  Nash Road  Redditch	Instruction manual references "Jotul F162/F162C/F163 Manual Version Po6" dated January 2011 and Supplementary instruction manual "Jotul F162/F163/262/263 SMOKE" dated 01/01/2012.  Fitted with a mechanical stop to prevent secondary air	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

B98 7AS.	control closure beyond the 20% open position when sold into smoke control areas.	
Jydepejsen Country 510 and 760 5kW stoves manufactured by Jydepejsen A/S, Ahornsvinget 3-7, Nr.Felding, DK-7500, Holstebro, Denmark.	Instruction user manual “Country001” reference “Jydepejsen A/S – June 2011” dated June 2011 A permanent stop must be fitted to the secondary air control such that it cannot be closed less than 35%.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
KARA KW990 woodchip boiler manufactured by KARA Energy Systems B.V. P.O. Box 570. 7600 AN Almelo. Plesmanweg 27, 7602 PD Almelo, the Netherlands.	Instruction manual references “Maintenance and Operation Guide KARA Wood Fired Boiler Version 2012.02” dated 26-07-2012.	Woodchip. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
KÖB Pyromat-DYN (KPM-DYN) Models 45, 65 and 85 manufactured by Viessmann Ltd, Hortonwood 30, Telford, Shropshire, TF1 7YP.	Instruction manual references “ID 103689-L English” dated 01.01.2005 and instruction manual “ID: 103708-G English”.	Wood logs (up to 0.5m) and off cuts of natural timber, wood chips and pellets.  The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.
KÖB Pyromat-ECO (KPM-ECO) Models 35, 45, 55, 65, 75, 85 manufactured by Viessmann Ltd, Hortonwood 30, Telford, Shropshire, TF1 7YP.	Instruction manual references “ID 104646-D English” dated 01.01.2005 and instruction manual “ID: 104642-B English”.	Wood logs (up to 0.5m) and off cuts of natural timber.  The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.
KÖB Pyromat-ECO (KPM-ECO) Models 61, 81, 101 and 151 manufactured by Viessmann Ltd, Hortonwood 30, Telford, Shropshire, TF1 7YP.	Instruction manual references “ID 104646-D English” dated 01.01.2005 and instruction manual “ID: 104642-B English”.	Wood logs (up to 1.0m) and off cuts of natural timber.  The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.
KÖB Pyrot (KRT) Models 100, 150, 220, 300, 400 and 540 manufactured by Viessmann Ltd, Hortonwood 30, Telford, Shropshire, TF1 7YP.	Instruction manual references “ID 104654-H English” dated 01.01.2005 and instruction manual “ID: 106811-H English”.	Wood chips or pellets.  The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.

*Status: This is the original version (as it was originally made).*

<p>KÖB Pyrtec (KPT) Models 390, 530, 720, 950 and 1250 manufactured by Viessmann Ltd, Hortonwood 30, Telford, Shropshire, TF1 7YP.</p>	<p>Instruction manual references “ID 104661-F English” dated 01.01.2005 and instruction manual “ID: 105174-F English”. Appliances must be fitted with multicyclone dedusters.</p>	<p>Wood chips or pellets.  The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.</p>
<p>Kooga Cleanburn Stove manufactured by Percy Doughty &amp; Co, Imperial Point, Express Trading Estate, Stone Hill Road, Farnworth, Bolton, BL4 9TN.</p>	<p>Instruction manual references “KCB 04/10A” dated April 2010.</p>	<p>Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.</p>
<p>KOZ550, 639kW output pellet boiler manufactured by Kayalıoğlu Kasabası (İzmir-İstanbul Yolu Üzeri) P.K 23 Akhisar/Manisa, Turkey.</p>	<p>Only when used with a Glosfume model BMF208 ceramic particulate filter. The Green energy engineering Ltd (GEE) KOZ550 pellet boiler owner/operator’s manual reference version 1A 2010 dated December 2010. The Glosfume Ltd maintenance and instruction manual for Glosfume BMF Biomass Filter units (50 to 1000kW) version AEE001-VER4 dated December 2010.</p>	<p>6mm diameter wood pellets. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.</p>
<p>KP12, KP22 and KP62 Wood pellet boilers manufactured by PONAST spol. s r.o.  Na Potůčkách 163  757 01 Valašské Meziříčí  Czech Republic.</p>	<p>Service manual references “QPP051-2” dated 25/05/2012 and instructions for operation manual “QPP049-3” dated 25/05/2012.</p>	<p>Wood pellets. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.</p>
<p>KWB Easyfire EF2 S/GS/V 8, 12, 15, 22, 25, 30 and 35 wood pellet boilers manufactured by KWB – Kraft und Wärme aus Biomasse Gesellschaft mit beschränkter Haftung, A-8321 St. Margarethen/Raab Industriestraße 235, Austria.</p>	<p>Operation manual reference “B KWB Easyfire EN, 05.2011” dated 05 2011 and installation manual “M KWB Easyfire, 05.2011” dated 05 2011.</p>	<p>Wood pellets. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.</p>
<p>KWB Multifire USV 15, 25, 30, 40, 50, 60, 80, 99 and 100 wood-pellet and wood-chip fired boilers manufactured by Kraft und Wärme aus Biomasse Gesellschaft</p>	<p>The fireplace(s) must be installed, maintained and operated in accordance with the manufacturer’s instructions dated August 2003, reference BA-USV 0803.</p>	<p>Wood chips and wood pellets. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.</p>



mit Beschränkter Haftung, Industriestrasse 235  8321 St. Margarethen/Raab, Austria, 8321.		
KWB Multifire USV 49.5kW Wood chip and wood pellet boiler manufactured by Kraft und Wärme aus Biomasse Gesellschaft mit Beschränkter Haftung, Industriestrasse 235  8321 St. Margarethen/Raab, Austria, 8321.	Instruction manual references “BA Multifire 06.2010” dated June 2010.	Wood chips and wood pellets. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood- preservatives or coatings.
KWB TDS Powerfire 130, 240 and 300 manufactured by KWB-Kraft und Wärme aus Biomasse Gesellschaft mit Beschränkter Haftung (GmbH) of Industriestrasse 235, A-8321 St. Margarethen an der Raab.	The manufacturer’s instructions dated 14 <sup>th</sup> May 2008, reference BA TDS-05.2008, including specification of recommended fuels.	Wood pellets or wood chips. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.
KWB TDS Powerfire 150, manufactured by KWB- Kraft und Wärme aus Biomasse Gesellschaft mit Beschränkter Haftung (GmbH) of Industriestrasse 235, A-8321 St. Margarethen an der Raab.	The manufacturer’s instructions dated August 2005, reference BA TDS-0805.	Wood pellets or wood chips. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.
Lin-ka H1500 Hot Water Boiler fitted with either a mono-cyclone (type LIN-KA 2000) or a multi-cyclone (type LIN-KA 3x2) manufactured by LIN-KA Maskinfabrik A/S, Nylandsvej 38 DK-6940 Lem St. Denmark..	Instruction manual reference “LIN-KA H 1500 Hot Water Manual/Ver. 2005/Rev. 1.10” dated 27/01/2010.	Wood Pellets of maximum diameter 8mm.  The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.
Little Thurlow Smoke Control Wood Burning Stove manufactured by Town & Country Fires Limited, 1 Enterprise Way, Thornton Road Industrial Estate, Pickering, North Yorkshire, YO18 7NA.	Town and country Fires’ operating instructions dated 30 June 2007, issue No.3.	Seasoned logs of less than 20% moisture and of a maximum length of 350 mm. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.
Little Wenlock Classic SE Wood Fuel Stove manufactured by Aga, Station Road, Ketley, Telford, Shropshire. TF1 5AQ.	Operating instructions dated 19 <sup>th</sup> December 2008, reference	Dry and split wood logs of a maximum length of 25 cm and a maximum diameter of 10 cm. The fuel must not

*Status: This is the original version (as it was originally made).*

	N00471 AXX Rev 001 DP081219.	contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.
Lotus Liva 1, Liva 2, Liva 3 and Liva 4G Stoves manufactured by Lotus Heating Systems A/S, Agertoften 6, 5550 Langeskov, Denmark.	Instruction manual “Mounting and User Instructions Lotus-Liva series Stoves” Version 4, dated January 2010.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.
Lotus Sola, Sola S, Sola M and Sola MST Stoves manufactured by Lotus Heating Systems A/S Agertoften 6, 5550 Langeskov, Denmark.	Instruction manual “Mounting and User Instructions Lotus-Sola series Stoves” Version 2 dated January 2010.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.
Løvenholm manufactured by Hunter Stoves Limited, Unit 6, Old Mill Industrial Estate, Stoke Canon, Exeter, Devon. EX5 4RJ.	Løvenholm Multifuel stove installation and operation manual version 07/08.	Untreated wood with a moisture content below 20%. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.
Løvenholm, Løvenholm Traditional, Løvenholm European, Løvenholm Pedestal stoves manufactured by Hunter Stoves Limited, Unit 6, Old Mill Industrial Estate, Stoke Canon, Exeter, Devon, UK EX5 4RJ.	Løvenholm Multifuel stove installation and operation manual version 06/09.	Untreated wood with a moisture content below 20%.  The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.
Loxton 3 stoves manufactured by Mendip Stoves Limited, Unit H1, Mendip Industrial Estate, Mendip Road, Rooksbridge, Somerset, BS26 2UG.	Instruction manual references “Mendip Stoves Ltd, 2012, ver 3,” dated July 2012.  A permanent stop to fix the secondary air control such that it cannot be closed more than 25% open must be implemented.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Loxton 5, Churchill 5 and Sqabox Uno stoves manufactured by Mendip Stoves Limited, Unit H1, Mendip Industrial Estate, Mendip Road, Rooksbridge, Somerset, BS26 2UG.	Instruction manual references “Mendip Stoves Ltd, 2012, ver 3” dated July 2012.  A permanent stop such that the secondary air ‘closed position’ results in a 2.5mm gap in the two secondary air openings must be implemented.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

<p>Loxton 6, Loxton 8, Churchill 6, Churchill 8 and Sqabox Duo stoves manufactured by Mendip Stoves Limited, Unit H1, Mendip Industrial Estate, Mendip Road, Rooksbridge, Somerset, BS26 2UG.</p>	<p>Instruction manual references “Mendip Stoves Ltd, 2012, ver 3” dated July 2012.</p> <p>A permanent stop on the secondary air control such that it cannot be closed more than 35% open must be implemented.</p>	<p>Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.</p>
<p>Ludlow Wood Burning Smoke Exempt Stove (Ludlow Stove SE) manufactured by Aga, Station Road, Ketley, Telford, Shropshire, TF1 5AQ.</p>	<p>Instruction manual references “N00529AXX REV:001” dated 13<sup>th</sup> July 2011.</p>	<p>Dry wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.</p>
<p>Marvic Multifuel Cassette (inset) roomheater manufactured by Wanders Fires &amp; Stoves, Amtweg 4, Netterden, NL-7077 AL, Netherlands.</p>	<p>Instruction manual reference “INK.00.7927” dated 20/12/2011.</p> <p>All appliances will be fitted with a modification to the secondary air control to ensure that the air supply holes remain 3mm open when the operator has nominally shut the control.</p>	<p>Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.</p>
<p>Mawera Fu-ria models 110, 140, 180, 220, 280 and 350 manufactured by Mawera (UK) Limited.</p>	<p>The manufacturer’s instructions dated 31<sup>st</sup> October 2002 and bearing the reference 098234-01.</p>	<p>No fuel should be used other than natural wood or wood products, forest residues and forest thinnings, uncoated MDF chipboard, plywood and compound wood products. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.</p>
<p>MEG 4.5 (also known as the Sirius 450) manufactured by Meg Stoves, F.E. Robinson (Hooton) Ltd, Station Works, Hooton Road, Hooton, South Wirral, CH66 7NF.</p>	<p>Instruction manual references “Meg Solid Fuel Stoves Manual (107)” dated 28<sup>th</sup> January 2011.</p>	<p>Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.</p>
<p>Meg 5.0 stove and Sirius 600 Inset stove.</p> <p>Manufactured by F.E. Robinson (Hooton) Ltd. Station Works</p>	<p>Instruction manual references “Manual Version 1.3” dated 27/07/2012.</p> <p>Fitted with a mechanical stop to prevent secondary air</p>	<p>Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.</p>

*Status: This is the original version (as it was originally made).*

Hooton Road Hooton South Wirral CH66 7NF.	control closure beyond the 10mm open position when sold into smoke control areas.	
MEG 7.5 (also known as the Sirius 750) manufactured by Meg Stoves, F.E. Robinson (Hooton) Ltd, Station Works, Hooton Road, Hooton, South Wirral, CH66 7NF.	Instruction manual references “Meg Solid Fuel Stoves Manual (107)” dated 28 <sup>th</sup> January 2011.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Mendip SE Wood Burning 5kW Space Heating Stove manufactured by TR Engineering Limited, Unit 7, Newton Chambers Way, Thorncliffe Industrial Estate, Chapeltown, Sheffield S35 2PH.	Instruction manual references “700273 Iss. 2 Rev. 1” dated January 2012.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Mendip SE Wood Burning 8kW Space Heating Stove manufactured by TR Engineering Limited, Unit 7, Newton Chambers Way, Thorncliffe Industrial Estate, Chapeltown, Sheffield, S35 2PH.	Instruction manual references “700275 Iss. 2 Rev.1” dated January 2012.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Mescoli PB50 Mescoli PB35 Mescoli PB28 Manufactured by MESCOLI CALDAIE S.rl. Caldaie – Termocucine Via del Commercio, 285 4 1058 Vignola (MO) Italy.	Instruction and Installation manual reference “SY315EVO P, C, B – COMBIFIRE 2 PB28/35/50 BOILERS” Edition 1.7 dated 1/2006.	Wood Pellets following ÖNORM M7 135 or DIN plus (DIN 51731).  The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.
Micromet MEG 4.5 stove (also known as the Sirius 450) manufactured by Micromet, 125 Bridge Street, Birkenhead, Merseyside, CH41 1BD.	Instruction manual references “Micromet Solid Fuel Stoves Manual (24)” dated 16/06/2010.	Dry wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.
Micromet MEG 7.5 stove (also known as the Sirius 750) manufactured by Micromet, 125 Bridge Street, Birkenhead, Merseyside, CH41 1BD.	Instruction manual references “Micromet Solid Fuel Stoves Manual (24)” dated 16/06/2010.	Dry wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment

		with wood preservatives or coatings.
Milan Series 4 manufactured by Chesney's Limited, 194 – 200 Battersea Park Road, London SW11 4ND.	<p>Instruction manual references “CH4K Milan-V2” dated 18 November 2010.</p> <p>Fitted with a system to prevent closure of the air control beyond the 25mm open position.</p>	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Milan Series 6 manufactured by Chesney's Limited, 194 – 200 Battersea Park Road, London SW11 4ND.	<p>Instruction manual references “CH6K Milan-V2” dated 18 November 2010.</p> <p>Fitted with a system to prevent closure of the air control beyond the 40mm open position.</p>	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Monaco multifuel Stove, Staub Fonderie-Franco Belge model 1340605, manufactured by Staub Fonderie-Franco Belge, Rue Orphee Variscotte, BP73, 59660 Merville, France.	<p>Instruction manual references “1303 – 1” dated 04/05/2010.</p> <p>Appliances will be fitted with a mechanical stop to prevent closure of the secondary air control beyond 4mm from closed when sold into smoke control areas.</p>	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Monterrey 6, York Midi, Serrano 5 manufactured by Broseley Fires Ltd, Knights Way, Battlefield Enterprise Park, Shrewsbury, Shropshire, SY1 3AB.	<p>Instruction manual references “09TJD” dated 01 2010.</p> <p>The fitting of a system that prevents the closure of the secondary air flaps to be less than 8mm open position should be implemented.</p>	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.
MORSØ-Ø4 manufactured by MORSØ Limited, Unit 7 – io centre Valley Drive, Swift Valley, Rugby, Warwickshire, CV21 1TW.	<p>Instruction manual references “Ø-Collection” dated 01.02.2010 and instruction manual “72000400” dated 01.02.2010.</p> <p>Applies to units manufactured after 01 February 2010.</p>	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.
Morsø 1400 series consisting of the 1412 and 1442 manufactured by Morsø Jernstøberi A/S DK-7900 Nykøbing, Mors, Denmark.	Installation and operation manual dated 10 <sup>th</sup> January 2008, reference 72146800.	Wood logs with less than 20% moisture. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.

*Status: This is the original version (as it was originally made).*

<p>Morsø 1416, 1418, 1446 and 1448 4kW stoves manufactured by Morsø UK Limited, Unit 7 The io Centre, Valley Drive, Swift Valley, Rugby, CV21 1TW.</p>	<p>Instruction manual references “Morsø 1416, 1418, 1446 &amp; 1448. Instruction for installation and use” dated 31/01/2012. Part No: 72150000.</p>	<p>Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.</p>
<p>Morsø 3100 series consisting of the 3112 and 3142 models manufactured by Morsø Jernstøberi A/S DK-7900 Nykøbing, Mors, Denmark.</p>	<p>Installation and operation manual dated 4<sup>th</sup> February 2008, reference 72311200.</p>	<p>Wood logs with less than 20% moisture. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.</p>
<p>Morsø 3400 Owl GB Series for wood burning manufactured by Morsø Jernstøberi A/S, Denmark.</p>	<p>The manufacturer’s instructions dated 1<sup>st</sup> January 2000 and bearing the reference “72345600”.</p>	<p>No fuel shall be used other than—</p> <p><b>(a)</b></p> <p>untreated dry wood which has been split, stacked and air dried; or</p> <p><b>(b)</b></p> <p>air dried wood briquettes.</p> <p>The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.</p>
<p>Morsø 6140 and 6148 manufactured by Morsø Jernstøberi A/S DK-7900 Nykøbing, Mors, Denmark.</p>	<p>Installation and operation manual dated 4<sup>th</sup> September 2007, reference 72610400.</p>	<p>Wood logs with less than 20% moisture. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.</p>
<p>Morsø Model 7600 including Model 7642, 7644 and 7648 stoves manufactured by Morsø Limited, UK distribution by Morsø UK Limited, Unit 7, The io Centre, Valley Drive, Swift Valley, Rugby, Warwickshire, CV21 1TW.</p>	<p>Instructions for installation and use 7600 reference “72762200” dated 14.07.2010.</p> <p>The air control on UK models has been altered such that this equates to an increased minimum open position. Reference drawings Morsø 7600-137, 7600-138, 7600-139, 7600-140 and 7600-141.</p>	<p>Wood logs with less than 20% moisture. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.</p>

Morsø Owl 3410, 3420 and 3440 for wood burning manufactured by Morsø Jernstøberi A/S DK-7900 Nykøbing, Mors, Denmark.	The manufacturer's instruction dated 1 <sup>st</sup> January 2000, reference 72345600.	Untreated dry wood which has been split, stacked and air dried; or air dried wood briquettes. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.
Morsø S10-40 5kW stove manufactured by Morsø UK Limited, Unit 7 The io Centre, Valley Drive, Swift Valley, Rugby, CV21 1TW.	Instruction manual references "Morsø S10. Instruction for Installation and use" dated 31/01/2012. Part No: 72104000.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Morsø S10-70 5kW stove manufactured by Morsø UK Limited, Unit 7 The io Centre, Valley Drive, Swift Valley, Rugby, CV21 1TW.	Instruction manual references "Morsø S10-70. Instruction for installation and use" dated 31/01/2012. Part No: 72103000.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Morsø S11-40, S11-42, S11-43 and S11-90 4kW stoves manufactured by Morsø UK Limited, Unit 7 The io Centre, Valley Drive, Swift Valley, Rugby, CV21 1TW.	Instruction manual references "Morsø S11 serien. Instruction for Installation and use" dated 31/01/2012. Part No: 72114200.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Morsø S81-90 4kW stove manufactured by Morsø UK Limited, Unit 7 The io Centre, Valley Drive, Swift Valley, Rugby, CV21 1TW.	Instruction manual references "Morsø S81-90. Instruction for Installation and use" dated 30/01/2012.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Nestor Martin C23 multifuel stove (7.7kW) manufactured by Nestor Martin S.A., 11 Rue De Lion, B-5660, Frasnes Les Couvin, Belgium.	Euroheat Distributors (HBS) Limited's operation Instructions Reference: "IN1213 Edition B" and dated June 2010.	Untreated dry wood. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.
Nestor Martin C33 multifuel stove (9.2kW) manufactured by Nestor Martin S.A., 11 Rue De Lion, B-5660, Frasnes Les Couvin, Belgium.	Euroheat Distributors (HBS) Limited's operation. Instructions Reference: "IN1213 Edition B" and dated June 2010.	Untreated dry wood. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.
Nestor Martin D33 multifuel stove (8kW) manufactured by Nestor Martin S.A., 11 Rue De Lion, B-5660, Frasnes Les Couvin, Belgium.	Euroheat Distributors (HBS) Limited's operation Instructions Reference: "IN1213 Edition B", and dated June 2010.	Untreated dry wood. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment

*Status: This is the original version (as it was originally made).*

		with wood preservatives or coatings.
Nestor Martin 'Harmony' H13 multi-fuel stove (5kW) manufactured by Nestor Martin, S. A., 11 Rue De Lion, B-5660, Frasnes Les Couvin, Belgium.	Euroheat Distributors (HBS) Limited's operation. Instructions Reference: "IN 1116 Edition D5" and dated June 2010.  The minimum air bleed flap must be set at a minimum of 14.5mm.	Untreated dry wood. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.
Nestor Martin 'Harmony' H23 (6kW) and H33 (8kW) multi-fuel stoves manufactured by Nestor Martin S. A., 11 Rue De Lion, 5B-5660 Frasnes Les Couvin, Belgium.	Euroheat Distributors (HBS) Limited's operation. Instructions Reference: "IN 1116 Edition D5" and dated June 2010.	Untreated dry wood. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.
Nestor Martin IN13 Insert multi-fuel stove (5kW), manufactured by Nestor Martin S. A., 11 Rue De Lion, B-5660 Frasnes Les Couvin, Belgium.	Euroheat Distributors (HBS) Limited's operation. Instructions Reference: "IN 1214 Edition B" and dated June 2010.  The minimum air bleed flap must be set at a minimum of 14.5mm.	Untreated dry wood. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.
Nestor Martin IT13 multi-fuel stove (5kW), manufactured by Nestor Martin S A., 11 Rue De Lion, B-5660, Frasnes Les Couvin, Belgium.	Euroheat Distributors (HBS) Limited's operation. Instructions Reference: "IN 1180 Edition D1" and dated June 2010.  The minimum air bleed flap must be set at a minimum of 14.5mm.	Untreated dry wood. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.
Nestor Martin R23 Multi-fuel Stove (6kW) manufactured by Nestor Martin S. A., 11 Rue De Lion, B-5660, Frasnes Les Couvin, Belgium.	Euroheat Distributors (HBS) Limited's operation. Instructions Reference: "IN 1141 Edition B" and dated November 2006.	Untreated dry wood. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.
Nestor Martin R33 (8kW) multifuel stove, manufactured by Nestor Martin S A., 11 Rue De Lion, B-5660, Frasnes Les Couvin, Belgium.	Euroheat Distributors (HBS) Limited's operation. Instructions Reference: "IN1116 Edition D" and dated January 2007.	Untreated dry wood. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.
Nestor Martin 'Stanford' S13 Multi-fuel Stove (5kW)	Euroheat Distributors (HBS) Limited's operation.	Untreated dry wood. The fuel must not contain halogenated



manufactured by Nestor Martin S. A., 11 Rue De Lion, B-5660, Frasnes Les Couvin, Belgium.	Instructions Reference “IN 1116 Edition D5” and dated June 2010.  The minimum air bleed flap must be set at a minimum of 14.5mm.	organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.
Nestor Martin ‘Stanford’ S23 (6kW), SP23 (6kW), S33 (8kW) and SP33 (8kW) Multi-fuel stoves manufactured by Nestor Martin S. A., 11 Rue De Lion, B-5660, Frasnes Les Couvin, Belgium.	Euroheat Distributors (HBS) Limited’s operation. Instructions Reference: “IN 1116 Edition D5” and dated June 2010.	Untreated dry wood. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.
Newark EGTL05 manufactured by Elite Group Trading Limited, Room 1208, Kak Tak Commercial Building, 317-319 Des Voeux Road Central, Hong Kong 999077.	Instruction manual references “EGTL05 Version 1.4” dated 5 <sup>th</sup> July 2011.  Factory fitting of a permanent stop to prevent any closure of the tertiary air control.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Newton SE Wood Burning 5kW Space Heating Stove manufactured by TR Engineering Limited, Unit 7, Newton Chambers Way, Thorncliffe Industrial Estate, Chapeltown, Sheffield, S35 2PH.	Instruction manual references “700504 Iss. 2 Rev 1” dated January 2012.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Newton SE Wood Burning 8kW Space Heating Stove manufactured by TR Engineering Limited, Unit 7, Newton Chambers Way, Thorncliffe Industrial Estate, Chapeltown, Sheffield, S35 2PH.	Instruction manual references “700506 Iss. 3 Rev. 2” dated January 2012.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Nordic 350 manufactured by C DE A Ingenieria Ltda, Jose Miguel Carrera 6, Colina, Santiago, 9361294, Chile.	Instruction manual reference number “1001” dated 20/07/2012.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Nordist Waste Fired System, models 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 20, 21, 22 and 23 manufactured in part by Nordfab A/S and in part by Danstoker A/S.	The manufacturer’s instructions dated 9 <sup>th</sup> December 1988 and bearing the reference “P.S. 501 9/12/88”.	Softwood shavings, hardwood shavings or sawdust shall be used. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment

**Status:** This is the original version (as it was originally made).

		with wood-preservatives or coatings.
Nørreskoven MkII manufactured for Hunter Stoves Limited, Unit 6, Old Mill Industrial Estate, Stoke Canon, Devon, EX5 4RJ.	Instruction manual references “Cleanburn, Nørreskoven MkII, Multifuel Stove. Installation and Operating Instructions, v01.11.” dated January 2011. The device has a factory fitted stop to prevent closure of secondary air control beyond 40%.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Norvik 5 manufactured by Elite Group Trading Limited, Room 1208 Kak Tak, Commercial Building 317-319 Des voeux Road, Central Hong Kong 999077.	Instruction manual references “EGTL05A Version 1.5” dated 12 <sup>th</sup> September 2011. The appliance must be fitted with a permanent stop to prevent any closure of the tertiary air control.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Octoplus 10 and Octoplus 15 Boiler manufactured by Solarfocus, Werkstrasse 1, 4451 St.Ulrich, Steyr, Austria.	Installation instructions Version 1.1 dated 19/04/2010. Operating manual Version 10.051 dated 10/05/2010.	Wood pellets. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
ÖkoFEN Pellematic PE08, PE12, PE16, PE20, PE25, PE32, PEK12, PEK16, PEK20, PEK25, PEK32, PES12, PES16, PES20, PES25, PES32, PESK12, PESK16, PESK20, PESK25 and PESK32 manufactured by ÖkoFEN Forschungs- und Entwicklungs Ges.m.b.H of Gewerbepark 1, 4133 Niederkappel, Austria.	ÖkoFEN operation instructions dated February 2007, reference PE/HB/001.E.	Wood pellets of maximum diameter 6 mm and maximum length 4 cm. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.
ÖkoFEN Pellematic PE36, PE48, PE56, PEK36, PEK48, PEK56, PES36, PES48, PES56, PESK36, PESK48, PESK56 manufactured by ÖkoFEN Forschungs- und Entwicklungs Ges.m.b.H of Gewerbepark 1, 4133 Niederkappel, Austria.	ÖkoFEN operation instructions reference PBV 2000 CMP 1.4 (V2.31) and with revision dated March 2008.	Wood pellets of maximum diameter 6 mm and maximum length 4 cm. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.
Olymberyl Baby Gabriel model number HF217-SE. UK Distribution by Hi-Flame Limited, Unit 7B	Instruction manual references “HF217-SE/UK-NI-ROI/V2.16-06-11”. Dated June 2011.	Wood Logs. The fuel must not contain halogenated organic compounds or heavy metals as

Holmes Chapel Business Park, Manor Lane, Holmes Chapel, Cheshire, CW4 8AF.	Fitted with a mechanical stop to prevent closure of the secondary air control beyond the 3mm open position.	a result of treatment with wood- preservatives or coatings.
Optifire 800 Green, Infire 800 Green, Wood Burning Stoves. Manufactured by Bodart & Gonay Limited,  Rue De Lambinon  3 Harze  Belgium  4920.	Instruction manual reference “07DH8000A” dated 11/11.  Fitted with a “UK kit for smokeless areas OPTI IF 800” when sold into smoke control areas.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood- preservatives or coatings.
Orchard Ovens models: FVR Speciale 80, 100, 110, 110 x 160 and 120; TOP Superiore 100 and 120; GR 100, 120, 140, 120 x 160, 140 x 160, 140 x 180 and 180; OT 100, 120, 140, 120 x 160, 140 x 160, 140 x 180 and 180; the Valoriani Piccolo, all of which are manufactured by Valoriani of Via Caselli alla Fornace, 213, 50066 Reggello, Firenze, Italy.	The manufacturer’s instructions dated 25 <sup>th</sup> October 2004, references:  Instruction Model  OOLinst.1 FVR 80  OOLinst.2 FVR.100  OOLinst.3 FVR 110  OOLinst.4 FVR 120  OOLinst.5 FVR 110 x 160  OOLinst.6 TOP 100  OOLinst.7 TOP. 120  OOLinst.8 GR 100 and OT 100  OOLinst.9 GR 120 and OT 120  OOLinst.10 GR 140 and OT 140  OOLinst.11 GR 120 x 160 and OT 120 x 160  OOLinst.12 GR 140 x 160 and	Untreated dry wood. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.

**Status:** This is the original version (as it was originally made).

	<p>OT 140 x 160</p> <p>OOLinst.13 GR 140 x 180 and</p> <p>OT 140 x 180</p> <p>OOLinst.14 GR 180 and OT</p> <p>180</p> <p>OOLinst.15 Valoriani Piccolo.</p>	
<p>Oregon EGTL03 manufactured by Elite Group Trading Limited, Room 1208, Kak Tak Commercial Building, 317-319 Des Voeux Road Central, Hong Kong 999077.</p>	<p>Instruction manual references “EGTL03 Version 1.3” dated 5<sup>th</sup> July 2011.</p>	<p>Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.</p>
<p>Osby Parca PB2 2000kW boiler manufactured by Enertech AB, Osby Parca Division, PO Box 93, SE-283 22 Osby, Sweden.</p>	<p>Operating &amp; Maintenance manual, PB2 boiler reference “manual PB2_ENG_Rev2_JAN2012” dated Jan 2012.</p>	<p>Wood pellets. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.</p>
<p>Osby Parca PB2 3000kW boiler manufactured by Enertech AB, Osby Parca Division, PO Box 93, SE-283 22 Osby, Sweden.</p>	<p>Operating &amp; Maintenance manual, PB2 boiler reference “manual PB2_ENG_Rev2_JAN2012” dated Jan 2012.</p>	<p>Wood pellets, wood chips, wood briquettes. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.</p>
<p>Parkray Caprice 4 manufactured by Hunter Stoves Limited, Unit 6, The Old Mill Industrial Estate, Stoke Canon, Exeter, Devon, EX5 4RJ.</p>	<p>Instruction manual references “JINCAP04 Rev E” dated 02/12/11 and instruction manual “JINCAP04SCK revB” dated 05/12/11.</p> <p>Fitted with “smoke control area kit JCAP0401” when sold into smoke control areas.</p>	<p>Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.</p>
<p>Parkray Consort 5 Compact manufactured by Hunter Stoves Limited, Unit 6, Old Mill Industrial Estate, Stoke Canon, Devon, EX5 4RJ.</p>	<p>Instruction manual references “JINCNC05 revC” dated 22/09/2011 and “JINCND05&amp;CNC05 Slider Stop revA” dated 22/07/11.</p> <p>The appliance must be fitted with a permanent stop that prevents closure of the secondary air slider beyond 30% open.</p>	<p>Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.</p>

Parkray Consort 5 manufactured by Hunter Stoves Limited, Unit 6, Old Mill Industrial Estate, Stoke Canon, Devon, EX5 4RJ.	Instruction manual references “JINCND05 revC” dated 22/09/2011 and “JINCND05&CNC05 Slider Stop revA” dated 22/07/11.  The appliance must be fitted with a permanent stop that prevents closure of the secondary air slider beyond 30% open.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Parkray Consort 5 Slimline manufactured by Hunter Stoves Limited, Unit 6, Old Mill Industrial Estate, Stoke Canon, Devon, EX5 4RJ.	Instruction manual reference “JINHHW05 revC” dated 22/09/11.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Parkray Consort 7 manufactured by Hunter Stoves Limited, Unit 6, Old Mill Industrial Estate, Stoke Canon, Devon, EX5 4RJ.	Instruction manual references “JNCS07 revC” dated 22/09/11.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Pelle 5kW stove, Vidar Small 5kW stove and Vidar Medium 7.6kW stove manufactured by Dik Geurts Haardkachels BV, Industrieweg Oost 11, 6662 NE Elst (Gld), The Netherlands.	Instruction manual reference “8900009004” dated July 2011.	Dry wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Pelletstar 10, 20, 30, 45 and 60 manufactured by HERZ Armaturen Ges.m.b.H, Geschäftsbereich HERZ Feuerungstechnik, A-8272 Sebersdorf 138, Austria.	Operating instructions dated November 2007, reference V2.2.	Wood pellets corresponding to ÖNORM M7135 of 6 mm diameter. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.
PelletTop 15 and PelletTop 25 Boiler manufactured by Solarfocus, Werkstrasse 1, 4451 St.Ulrich, Steyr, Austria.	Installation instructions version 020905 dated 02/09/2005. Operating manual version 270906 dated 27/09/2006.	Wood pellets. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Pevex Bohemia X 30, X 40, X 40 Cube, X 50 and X 60 multi-fuel stoves manufactured by Pevex Enterprises Limited, Unit 16 Seven Acres Business	Instruction manual references “AH/Ver3” and dated July 2010.	Dry wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.

*Status: This is the original version (as it was originally made).*

<p>Park, Newbourne Road, Waldringfield</p> <p>Nr Woodbridge, IP12 4PS.</p>		
<p>Pevex Bohemia X 40 Inset multi-fuel appliance manufactured by Pevex Enterprises Limited, Unit 16 Seven Acres Business Park, Newbourne Road, Waldringfield, Nr Woodbridge, IP12 4PS.</p>	<p>Instruction manual references “Pevex1004/AH/ver2” and dated June 2011.</p> <p>Fitted with permanent stops that ensure the primary and tertiary air controls do not close beyond 0.5cm open and 2cm open positions respectively.</p>	<p>Dry wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood- preservatives or coatings.</p>
<p>Pevex Serenity 40D inset multi- fuel appliance manufactured by Pevex Enterprises Limited, Unit 16 Seven Acres Business Park, Newbourne Road, Waldringfield Nr Woodbridge, IP12 4PS.</p>	<p>Instruction manual references “Pevex1003/AH/ver2” and dated June 2011.</p> <p>Fitted with permanent stops that ensure the secondary and tertiary air controls do not close beyond 1.1cm open and 2cm open positions respectively.</p>	<p>Dry wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood- preservatives or coatings.</p>
<p>Portway 1 Stove manufactured by BFM Europe Limited, Trentham Lakes, Stoke on Trent, Staffordshire, ST4 4TJ.</p>	<p>Instruction manual referenced: “Solid Fuel Stoves Manual issued – 20/08/2009 (291) 2”. The appliance must be used with a modification to the secondary air slide which inhibits closure further than the 25mm from the left position.</p>	<p>Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.</p>
<p>Portway 2 and 3 Stoves manufactured by BFM Europe Limited, Trentham Lakes, Stoke on Trent, Staffordshire, ST4 4TJ.</p>	<p>Instruction manual referenced: “Solid Fuel Stoves Manual issued – 20/08/2009 (291) 2”. The appliance must be used with a modification to the secondary air slide which inhibits closure further than the 20mm from the left position.</p>	<p>Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.</p>
<p>Portway Inset Stove manufactured by BFM Europe Limited, Trentham Lakes, Stoke on Trent, Staffordshire, ST4 4TJ.</p>	<p>Instruction manual referenced: “Solid Fuel Stoves Manual issued – 20/08/2009 (291) 2”. A modification of the secondary air control must be implemented such that the 20mm from left position is maintained during use. In addition the primary air control must be modified such that</p>	<p>Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.</p>

	the minimum setting allows a bleed of air to pass through.	
Pyroclassic IV manufactured by Pyroclassic Fires Limited, PO Box 28150, Havelock North 4157, Hawke Bay, New Zealand.	Instruction manual reference “PYROS 04” dated August 2011.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
PZ 65 RL and PZ 100 RL.  Manufactured by Biotech Energietechnik GmbH  Furtmühlstrasse 32  A-5101 Bergheim bei Salzburg.	Instruction manual references “Assembly instruction – Instruction manual – servicing & cleaning PZ65RL/PZ100RL/PZ101RL” dated July 2012. Reference BTMoBeWe ENG.	Wood pellets. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Quadra-Fire 2100 Millennium Freestanding Wood Burning Stove, manufactured by Hearth & Home Technologies 1445 North Highway, Colville, WA 99114, USA.	The manufacturer’s instructions dated 9 <sup>th</sup> October 2003, reference 250-6931B.	Dry cured untreated wood of maximum size 38.1cm x 10.16cm x 5.08cm. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Quadra-Fire Cumberland Gap Freestanding Wood Burning Stove, manufactured by Hearth & Home Technologies 1445 North Highway, Colville, WA 99114, USA.	The manufacturer’s instructions dated 8 <sup>th</sup> July 2003, reference 7006-186.	Dry cured untreated wood of maximum size 43.18cm x 10.16cm x 10.16cm. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Quadra-Fire Yosemite Freestanding Wood Burning Stove, manufactured by Hearth & Home Technologies 1445 North Highway, Colville, WA 99114, USA.	The manufacturer’s instructions dated 4 <sup>th</sup> June 2003, reference 7004-187.	Dry cured untreated wood of maximum size 38.1cm x 10.16cm x 5.08cm. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Rais 2:1 inset stove manufactured by Rais A/S Industrivej 20, 9900, Frederikshavn, Denmark.	Instruction manual reference “USER MANUAL Rais 2:1 Revision 2”. Dated December 2009. Part number 9106510.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.
Rais 700 inset stove manufactured by Rais A/	Instruction manual reference “USER MANUAL Rais 700 Revision 0”. Dated 2010.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as

*Status: This is the original version (as it was originally made).*

S Industrivej 20, 9900, Frederikshavn, Denmark.		a result of treatment with wood preservatives or coatings.
Rais Epoca, Rais Poleo 95 and Rais Poleo 106 stoves manufactured by Rais A/S Industrivej 20, 9900, Frederikshavn, Denmark.	Instruction manual reference “USER MANUAL Rais Poleo 95 & Rais Poleo 106 & Rais Epoca Revision 1”. Dated December 2009. Part number 2106510.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.
RAIS Q-Tee 57  manufactured by Rais A/S Industrivej 20, 9900, Frederikshavn, Denmark.	Instruction manual references “Manual for RAIS Q-Tee Revision 1” dated 28th June 2011 and Supplementary instructions Rais Q-Tee dated 7th July 2011.  Fitted with a mechanical stop to prevent air control closure beyond the 11.7mm open position.	Dry wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
RAIS Q-Tee 65  manufactured by Rais A/S Industrivej 20, 9900, Frederikshavn, Denmark.	Instruction manual references “Manual for RAIS Q-Tee Revision 1” dated 28th June 2011, and Supplementary instructions Rais Q-Tee dated 7th July 2011.  Fitted with a mechanical stop to prevent air control closure beyond the 11.7mm open position.	Dry wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
RAIS Q-Tee 85  manufactured by Rais A/S Industrivej 20, 9900, Frederikshavn, Denmark.	Instruction manual references “Manual for RAIS Q-Tee Revision 1” dated 28th June 2011, and Supplementary instructions Rais Q-Tee dated 7th July 2011.  Fitted with a mechanical stop to prevent air control closure beyond the 11.7mm open position.	Dry wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Rais Rondo Classic and Rais Mino II stoves manufactured by Rais A/S Industrivej 20, 9900, Frederikshavn, Denmark.	Instruction manual reference “USER MANUAL Rais Rondo & Rais Mino II revision 2”. Dated March 2008. Part number 5056510.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.
Rais Rondo 92 and Rais Rondo 120 stoves manufactured by Rais A/S Industrivej 20, 9900, Frederikshavn, Denmark.	Instruction manual reference “USER MANUAL Rais Rondo 92 & Rais Rondo 120 revision	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as



	2". Dated December 2009. Part number 4076510.	a result of treatment with wood preservatives or coatings.
RAIS VIVA 98, RAIS VIVA 98G, RAIS VIVA 120, RAIS VIVA 120G, RAIS RINA 90 Wood Burning Stoves, manufactured by Rais A/S, Industrivej 20, Vangen, DK-9900, Frederikshavn, Denmark.	Instruction manual references "Manual for RAIS Rina, RAIS Viva" dated 29 <sup>th</sup> August 2011, and instruction manual "Supplementary Instructions Rais" dated 27 <sup>th</sup> September 2011.  Fitted with a mechanical stop to prevent closure of the air damper beyond the 8.5mm open position when sold into smoke control areas.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
RanHeat appliances models MSU150, MSU300, MSU500, WA150, WA300 and Wa500, manufactured by RanHeat Energy Limited.	The manufacturer's instructions dated July 1994 bearing the following reference—  <b>(i)</b>  models MSU150, MSU300 and MSU500: "MSU150/500 1994";  <b>(ii)</b>  models WA150, WA300 and WA500: "WA150/500 1994".	No fuel shall be used other than chipboard, wood offcuts, softwood or hardwood, or fibre board. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
RanHeat Boiler Type RHA 20, manufactured by RanHeat Energy A/S.	The fireplace shall be installed, maintained and operated in accordance with the manufacturer's instructions dated 30 <sup>th</sup> March 1988 and bearing the reference "RHGBEA 30388".	No fuel shall be used other than hardwood and softwood shavings. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
RanHeat Boiler Types RHA 160, 200 and 250, manufactured by RanHeat Energy GB Limited.	The fireplaces shall be installed, maintained and operated in accordance with the manufacturer's instructions dated 30 <sup>th</sup> March 1988 and bearing the reference "RHGBEA 30388".	No fuel shall be used other than hardwood and softwood shavings. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Redfyre Kensal 20 Flat top (product code RF-EN20M), Redfyre Kensal 33 Flat top (product code RF-	The manufacturer's instruction manual dated July 2008, reference PM247 Issue 1, and instruction manual dated	Untreated dry wood. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment

*Status: This is the original version (as it was originally made).*

KEN33M and RF-KEN33W), manufactured by Redfyre Cookers, Osprey Road, Sowton Industrial Estate, Exeter, Devon, EX2 7JG.	January 2009, reference PM280 Issue 1.  A permanent stop must be in place on the secondary air inlet to prevent closure beyond the 50% open position.	with wood preservatives or coatings.
Resolute Acclaim woodstove manufactured by Vermont Castings Inc.	The fireplaces shall be installed, maintained and operated in accordance with the manufacturer's instructions bearing the reference "AMENDED NO. 200 – 0908 UK OCTOBER 1991".	No fuel shall be used other than 400 millimetre firewood that has been split, stacked and air-dried. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.
Rika Como pellet stove manufactured by RIKA Innovative Ofentechnik GmbH Müllerviertel 20 AT - 4563 Micheldorf, Austria.	Instruction manual references "IN1226 Edition 1" dated June 2011.	6 mm wood pellets. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Rika Evo Aqua 9 and 15 manufactured by SHT Heiztechnik aus Salzburg GmbH, Rechtes Salzachufer 40 A-5101, Salzburg-Bergheim, Austria.	Instruction manual references "J18/HB" dated 27/02/2009.	6mm wood pellets. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Rika Memo pellet stove manufactured by RIKA Innovative Ofentechnik GmbH Müllerviertel 20 AT - 4563 Micheldorf, Austria.	Instruction manual references "IN1228 Edition 1" dated June 2011.	6 mm wood pellets. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Rika Pico pellet stove manufactured by RIKA Innovative Ofentechnik GmbH Müllerviertel 20 AT - 4563 Micheldorf, Austria.	Instruction manual references "IN1230 Edition 1" dated June 2011.	6 mm wood pellets. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Rika Revo pellet stove manufactured by RIKA Innovative Ofentechnik GmbH Müllerviertel 20 AT - 4563 Micheldorf, Austria.	Instruction manual references "IN1229 Edition 1" dated June 2011.	6 mm wood pellets. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Rika Tema 6kW stove manufactured by Rika Innovative Ofentechnik GmbH,	Instruction manual references "IN1218 Edition 2" dated January 2012.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment

Müllerviertel 20, AT- 4563 Micheldorf, Austria.		with wood-preservatives or coatings.
Rika Topo pellet stove manufactured by RIKA Innovative Ofentechnik GmbH Müllerviertel 20 AT – 4563 Micheldorf, Austria.	Instruction manual references “IN1227 Edition 1” dated June 2011.	6 mm wood pellets. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Riva 40 Cassette 4.9kW stoves manufactured by Stovax Limited, Falcon Road, Sowton Industrial Estate, Exeter, Devon, EX2 7LF.	Instruction manual references PM235 Issue 2 dated August 2009 and smoke control kit instruction manual PM375 Issue 2 dated January 2010.  A permanent stop must be positioned to prevent closure of the secondary air control below the 50% open position.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.
Riva 40 Freestanding, Riva 40 Avanti, Riva 40 Avanti Midi and Riva 40 Avanti Highline 4.9kW stoves manufactured by Stovax Limited, Falcon Road, Sowton Industrial Estate, Exeter, Devon, EX2 7LF.	Instruction manual references PM226 Issue 2 dated August 2009, and smoke control kit instruction manual PM375. Issue 2 dated January 2010.  A permanent stop must be positioned to prevent closure of the secondary air control below the 50% open position.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.
Riva 45 Cassette (model numbers RV45 & RV45B) Wood Burning Stoves.  Manufactured by Stovax Limited,  Falcon Road  Sowton Industrial Estate  Exeter  Devon  EX2 7LF.	Instruction manual references “PM375 Issue 5” dated June 2012 and Instruction manual references “PM235 Issue 5” dated June 2012.  A permanent stop must be positioned to prevent closure of the secondary air control below the 50% open position.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Riva 50 Cassette (model numbers RV50 & RV50B) Wood Burning Stoves. Manufactured by Stovax Limited,	Instruction manual references “PM375 Issue 5” dated June 2012 and Instruction manual references “PM235 Issue 5” dated June 2012.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

**Status:** This is the original version (as it was originally made).

<p>Falcon Road Sowton Industrial Estate Exeter Devon EX2 7LF.</p>	<p>A permanent stop must be positioned to prevent closure of the secondary air control below the 50% open position and the primary air control fixed to allow a bleed of air to enter the firebox from underneath the grate.</p>	
<p>Riva 55 Avanti Midi and Riva 66 Freestanding 8kW stoves manufactured by Stovax Limited, Falcon Road, Sowton Industrial Estate, Exeter, Devon, EX2 7LF.</p>	<p>Instruction manual references PM226 Issue 2 dated August 2009 and smoke control kit instruction manual PM375. Issue 2 dated January 2010.</p> <p>A permanent stop must be positioned to prevent closure of the secondary air control below the 50% open position and the primary air control fixed to allow a bleed of air to enter the firebox from underneath the grate.</p>	<p>Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.</p>
<p>Riva 55 Cassette, Riva 66 Cassette, Riva 66 Avanti Cassette stoves manufactured by Stovax Limited, Falcon Road, Sowton Industrial Estate, Exeter, Devon, EX2 7LF.</p>	<p>Instruction manual references PM235 Issue 2 dated August 2009 and smoke control kit instruction manual PM375. Issue 2 dated January 2010.</p> <p>A permanent stop must be positioned to prevent closure of the secondary air control below the 50% open position and the primary air control fixed to allow a bleed of air to enter the firebox from underneath the grate.</p>	<p>Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.</p>
<p>Riva Plus Small (5kW), Midi (6.5kW) and Medium (8kW) Stoves manufactured by Stovax Limited, Falcon Road, Sowton Industrial Estate, Exeter, Devon, EX2 7LF.</p>	<p>Instruction manual references PM231 Issue 3 dated June 2009 and smoke control kit instruction manual PM402 Issue 1 dated November 2009.</p> <p>A permanent stop must be positioned to prevent closure of the secondary air control below the 25% open position.</p>	<p>Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.</p>
<p>Riva Studio 1 (5kW) freestanding wood stove manufactured by Stovax Limited, Falcon Road, Sowton</p>	<p>Instruction manual references PM452 Issue 1 dated June 2010 and smoke control kit</p>	<p>Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as</p>

<p>Industrial Estate, Exeter, Devon, EX2 7LF.</p>	<p>instruction manual PM400 Issue 3 dated June 2010.</p> <p>A permanent stop must be positioned to prevent closure of the secondary air control below the 45% open position and the primary air control fixed to prevent full closure to allow a bleed of air to enter the firebox at the base of the fuel bed.</p>	<p>a result of treatment with wood preservatives or coatings.</p>
<p>Riva Studio 2 (8kW) freestanding wood stove manufactured by Stovax Limited, Falcon Road, Sowton Industrial Estate, Exeter, Devon, EX2 7LF.</p>	<p>Instruction manual references PM452 Issue 1 dated June 2010 and smoke control kit instruction manual PM400 Issue 3 dated June 2010.</p> <p>A permanent stop must be positioned to prevent closure of the secondary air control below the 25% open position and the primary air control fixed to prevent full closure to allow a bleed of air to enter the firebox at the base of the fuel bed.</p>	<p>Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.</p>
<p>Riva Studio 1 Cassette (5kW) Stove manufactured by Stovax Limited, Falcon Road, Sowton Industrial Estate, Exeter, Devon, EX2 7LF.</p>	<p>Instruction manual references PM274 Issue 2 dated October 2009 and smoke control kit instruction manual PM400 Issue 1 dated November 2009.</p> <p>A permanent stop must be positioned to prevent closure of the secondary air control below the 45% open position and the primary air control fixed to prevent full closure to allow a bleed of air to enter the firebox at the base of the fuel bed.</p>	<p>Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.</p>
<p>Riva Studio 2 Cassette (8kW) Stove manufactured by Stovax Limited, Falcon Road, Sowton Industrial Estate, Exeter, Devon, EX2 7LF.</p>	<p>Instruction manual references PM274 Issue 2 dated October 2009 and smoke control kit instruction manual PM400 Issue 1 dated November 2009.</p> <p>A permanent stop must be positioned to prevent closure of the secondary air control</p>	<p>Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.</p>

**Status:** This is the original version (as it was originally made).

	below the 25% open position and the primary air control fixed to prevent full closure to allow a bleed of air to enter the firebox at the base of the fuel bed.	
Riva Vision Medium (8kW) Multifuel Stove manufactured by Stovax Limited, Falcon Road, Sowton Industrial Estate, Exeter, Devon, EX2 7LF.	<p>Instruction manual references PM278 Issue 2a dated October 2009 and smoke control kit instruction manual PM401 Issue 1 dated January 2010.</p> <p>A permanent stop must be positioned to prevent closure of the secondary air control below the 25% open position.</p>	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.
Riva Vision Small (5kW) and Riva Vision Midi (6.5kW) Multifuel Stoves manufactured by Stovax Limited, Falcon Road, Sowton Industrial Estate, Exeter, Devon, EX2 7LF.	<p>Instruction manual references PM278 Issue 2a dated October 2009 and smoke control kit instruction manual PM401 Issue 1 dated January 2010.</p> <p>A permanent stop must be positioned to prevent closure of the secondary air control below the 50% open position.</p>	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.
<p>Rosedale Inset Smoke Control inset roomheater manufactured by Town and Country Fires Limited,</p> <p>Unit 1 Enterprise Way</p> <p>Thornton Road Industrial Estate</p> <p>Pickering</p> <p>North Yorkshire</p> <p>YO18 7NA</p>	<p>Instruction manual reference “Issue No. 04” dated 11.01.2012.</p> <p>Fitted with a mechanical stop to prevent secondary air control closure beyond the 30% open position when sold into smoke control areas.</p>	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Rosedale SC Multifuel Stove manufactured by Town & Country Fires Limited, 1 Enterprise Way, Thornton Road Industrial Estate, Pickering, North Yorkshire, YO18 7NA.	<p>Rosedale Smoke Control Stove Installation and User Instructions “Issue 1” dated 1<sup>st</sup> May 2010.</p> <p>The appliance must be fitted with a mechanical stop to prevent closure of the secondary air control beyond</p>	<p>Wood logs with a maximum of 20% moisture.</p> <p>The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.</p>

	the 50% open position when sold into smoke control areas.	
Royal Klima 18 Idro wood pellet stove boiler manufactured by Palazzetti Lelio S.p.A, Via Roveredo 103, Porcia (PN), 33080, Italy.	Instruction manual references “cod. 0047700880” dated 09/2011 and supplementary information “Clean Air Act 1993 and Smoke Control Areas” reference 004723000 dated 01/2012.	Wood pellets. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Saltfire Ecoview 5, Fireglow Eco 5, and Ecowarm Crystal 5 stoves.  Manufactured by Saltfire Stoves Limited, Units 1 and 2, The Omega Centre, Sandford Lane, Wareham, Dorset, BH20 4DY.	Instruction manual references “Evoview5 Manual 1.0” dated 15/12/2011.  Fitted with a mechanical stop to prevent closure of the tertiary air beyond the 4mm open position when sold into smoke control areas.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Saltfire Ecoview 12, Fireglow Eco 12, and Ecowarm Crystal 12 stoves.  Manufactured by Saltfire Stoves Limited, Units 1 and 2, The Omega Centre, Sandford Lane, Wareham, Dorset, BH20 4DY.	Instruction manual references “Evoview12 Manual 1.0” dated 15/2/2011.  Fitted with a mechanical stop to prevent closure of the tertiary air beyond the 4mm open position when sold into smoke control areas.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Saltfire Oslo-Eco Manufactured by Saltfire Stoves Limited, Units 1 and 2, The Omega Centre, Sandford Lane, Wareham, BH20 4DY.	Instruction manual references “ECO7operation-Revision 2A” dated 24.01.2011.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
San Remo 4SE manufactured by Heat Design, 30 Hawthorn Road, Western Industrial Estate, Naas Road, Dublin 12, Ireland.	Instruction manual references “SR468SE” dated 25/07/12.  The fitting of a system to prevent closure of the secondary air control beyond 5mm open must be implemented.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
San Remo 6SE stove manufactured by Heat Design, 30 Hawthorn Road, Western Industrial Estate, Naas Road, Dublin 12, Ireland.	Instruction manual references “SR468SE” dated 25/07/12.  The fitting of a system to prevent closure of the secondary air control beyond 75% from closed must be implemented.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

**Status:** This is the original version (as it was originally made).

<p>San Remo 8SE stove manufactured by Heat Design, 30 Hawthorn Road, Western Industrial Estate, Naas Road, Dublin 12, Ireland.</p>	<p>Instruction manual references “SR468SE” dated 25/07/12.</p> <p>The fitting of a system to prevent closure of the secondary air control beyond 25% from closed must be implemented.</p>	<p>Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.</p>
<p>Scan Andersen 4-5 manufactured by Krog Iversen &amp; Co. A/S DK-5492 Vissenbjerg, Denmark.</p>	<p>The manufacturer’s instruction manual dated 15 November 2007 entitled “Scan Andersen 4-5”, reference Edition 09/05-GB.</p> <p>A permanent stop must be in place on the secondary air inlet to prevent closure beyond 20mm.</p>	<p>Untreated dry wood. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.</p>
<p>Scan DSA 7-5 wood-burning Inset roomheater.</p> <p>Manufactured by Scan A/S, PO Box 20, 5492 Vissenbjerg, Denmark.</p>	<p>Instruction manual “Instructions for installation and use : SCAN DSA 6 &amp; DSA 7-5” Edition 17.09.2010 – GB, supplement “DSA 7-5 – UK smoke control areas” reference “DSA 7-5 SMOKE” dated 01/01/2012, and instructions for installation (including directions for use and stoking) reference “Edition 05.10.2010 – GB”.</p> <p>Fitted with a mechanical stop to prevent closure of the air wash control lever beyond the 50% open position.</p>	<p>Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.</p>
<p>Scan Ild 1 and 4 stoves manufactured by Scan A/S, Glasvaenget 3-9, 5492 Vissenbjerg, Denmark.</p>	<p>Instruction manual references “11.1c” dated 02/2012.</p> <p>Fitted with a mechanical stop to prevent closure of the secondary air control beyond the 83mm open position.</p>	<p>Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.</p>
<p>Scan Ild 2 and 5 stoves manufactured by Scan A/S, Glasvaenget 3-9, 5492 Vissenbjerg, Denmark.</p>	<p>Instruction manual references “11-1d” dated 02/2012.</p> <p>Fitted with a mechanical stop to prevent closure of the secondary air control beyond the 83mm open position.</p>	<p>Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.</p>
<p>Scan Warm 1 and 4 stoves manufactured by Scan A/</p>	<p>Instruction manual references “11-1a” dated 02/2012.</p> <p>Fitted with a mechanical</p>	<p>Wood logs. The fuel must not contain halogenated organic compounds or heavy</p>



S, Glasvaenget 3-9, 5492 Vissenbjerg, Denmark.	stop to prevent closure of the secondary air control beyond the 83mm open position.	metals as a result of treatment with wood-preservatives or coatings.
Scan Warm 2 and 5 stoves manufactured by Scan A/S, Glasvaenget 3-9, 5492 Vissenbjerg, Denmark.	Instruction manual references “11-1b” dated 02/2012. Fitted with a mechanical stop to prevent closure of the secondary air control beyond the 83mm open position.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Schmid UTSK 180, 240, 300, 360, 450, 550, 700, 900, 1200, 1600kW.  Manufactured by Schmid AG Wood Firing Systems  PO Box 42  CH-8380 Eschikon.	“Instruction manual UTSK – ABC.22 – AME – S – PPU”  Dated 25.09.2008.  Where ABC is Model Number ie. 180, 240, 300, 360, 450, 550, 700, 900, 1200, 1600.	Wood Pellets or Wood Chips following CEN/TS 14961: 2005.  The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.
Schmid UTSL 30, 40, 50, 65, 80, 110, 150kW.  Manufactured by Schmid AG Wood Firing Systems  PO Box 42  CH-8380 Eschikon.	Instruction manual references “Operating Manual Wooden Chips and Pellets Plant. Lignumat UTSL” dated 23.12.2004.	Wood Pellets or Wood Chips following CEN/TS 14961: 2005.  The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.
Schmid UTSP 180, 240, 300kW.  Manufactured by Schmid AG Wood Firing Systems  PO Box 42  CH-8380 Eschikon.	Instruction manual “UTSK – ABC.22 – AME – S – PPU”. Dated 25.09.2008.  Where ABC is Model Number ie. 180, 240, 300.	Wood Pellets following CEN/TS 14961: 2005.  The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.
Schmid UTSR 150, 180, 240, 300, 360, 450, 550, 700, 900kW.  Manufactured by Schmid AG Wood Firing Systems  PO Box 42  CH-8380 Eschikon.	Instruction manual “UTSR – ABC.22 – AME – S – PPV”. Dated 25.09.2008.  Where ABC is Model Number ie. 150, 180, 240, 300, 360, 450, 550, 700, 900.	Wood Pellets or Wood Chips following CEN/TS 14961: 2005.  The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.
Serrano 5 and Monterrey 6 Multi Fuel Stoves manufactured by Broseley	Instruction manual references “TJ09C” dated 21 <sup>st</sup> December	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as

**Status:** This is the original version (as it was originally made).

<p>Fires Ltd, Knights Way, Battlefield Enterprise Park, Shrewsbury, Shropshire, SY1 3AB.</p>	<p>2009. The fitting of a system that prevents the closure of the secondary air flaps to be less than 8mm open position should be implemented.</p>	<p>a result of treatment with wood-preservatives or coatings.</p>
<p>Serrano 7 Multi Fuel stove manufactured by Broseley Fires Ltd, Knights Way, Battlefield Enterprise Park, Shrewsbury, Shropshire, SY1 3AB.</p>	<p>Instruction manual references “TJ09C” dated 21<sup>st</sup> December 2009. The fitting of a system that prevents the closure of the secondary air flaps to be less than 10mm open position should be implemented.</p>	<p>Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.</p>
<p>Silent Glow Incinerator, models CCD 450, 600 and 750 manufactured by Silent Glow Incinerators Limited.</p>	<p>The manufacturer’s instructions dated May 1989.</p>	<p>No fuel shall be used other than solid waste of the type specified in the manufacturer’s instructions dated May 1989.</p>
<p>Sirius Traditional Stove manufactured by Tianjin Focus Arts &amp; Crafts Co, Industrial Area Gao Zhuangzi Village, Xin Zhuang Town, Jin Nan District, Tianjin, P.R. China 300350.</p>	<p>Instruction and Operating Instruction manual reference “v173 of 09/11/2010” dated 09/11/2010.</p>	<p>Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.</p>
<p>Spacewarmer B200, manufactured by Clearair Limited.</p>	<p>The manufacturer’s instructions published December 1983 and bearing the reference “B200/DEC 83”.</p>	<p><b>a)</b> No fuel shall be used other than hardwood or softwood offcuts, a mixture of offcuts (hardwood or softwood) and sandwich with no more than 50 per cent of the mixture being sawdust, or chipboard offcuts. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings;</p> <p><b>(b)</b> The fireplace shall not be used to burn chipboard unless an afterburner supplied by the manufacturer of the fireplace and capable of producing 50 megajoules of heat per hour has been fitted to the fireplace.</p>

Spacewarmer B500, manufactured by Clearair Limited.	The manufacturer's instructions published in December 1983 and bearing the reference "B500/DEC 83".	No fuel shall be used other than hardwood or softwood offcuts. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Stockton 3 Flat top (product code 7118), Stockton 4 Flat top (product codes 7101 and 7102), Stockton 5 Flat top (product code 7127), Stockton 5 midline (product code 7130), Stockton 6 Flat top (product codes 7100 and 7162), Stockton 6 Highline (product code 7117) and Stockton 7 Flat top (product codes 7120 and 7163) manufactured by Stovax Limited, Falcon Road, Sowton Industrial Estate, Exeter, Devon, EX2 7LF.	The manufacturer's instruction manual dated July 2008, reference PM227 ENG Issue 2, and instruction manual dated January 2009, reference PM271 Issue 2.  A permanent stop must be in place on the secondary air inlet to prevent closure beyond the 50% open position.	Untreated dry wood. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.
Stockton 5 Flat top (model number 7119), Stockton 5 Canopy (model number 7160) and Stockton 5 Midline (model number 7133) manufactured by Stovax Limited, Falcon Road, Sowton Industrial Estate, Exeter, Devon, EX2 7LF.	The manufacturer's instruction manual reference PM 176 – Issue 4.  A permanent stop must be in place on the secondary air inlet to prevent closure beyond the 50% open position.	Untreated dry wood. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.
Stockton 7 Inset Convector (product codes 7125F and 7125C) manufactured by Stovax Limited, Falcon Road, Sowton Industrial Estate, Exeter, Devon, EX2 7LF.	The manufacturer's instruction manual dated May 2008, reference PM230 Issue 1, instruction manual dated January 2009, reference PM281 Issue 1.  A permanent stop must be in place on the secondary air inlet to prevent closure beyond the 50% open position.	Untreated dry wood. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.
Stockton Milner (4.6kW) inset stove – smoke control version – manufactured by Stovax Limited, Falcon Road, Sowton Industrial Estate, Exeter, Devon, EX2 7LF.	Instruction manual reference PM416 Issue 1, (June 2010) and smoke control kit instruction manual PM501 Issue 1 (June 2010).	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.

*Status: This is the original version (as it was originally made).*

	A permanent stop must be positioned to prevent closure of the secondary air control below the 50% open position.	
Stoven Mayfair SE & Stoven Kensington SE 5kW Wood Burning Stoves. Manufactured by Ciang Stoves Limited, South Chuangye Road, (Hanling Industrial Estate), Beiguan Section, Anyang City, Henan Province, China. 455000.	Newman Fireplaces Limited's Instruction manual references "3-4" dated 27 <sup>th</sup> November 2011. Fitted with mechanical stops to prevent closure of the secondary air control beyond the 25% open position and the tertiary air beyond the 1mm open position when sold into smoke control areas.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Strebel SRP TR 90, 90kW output pellet boiler manufactured by Strebel Ltd, 1f Albany Park, Camberley, Surrey, GU16 7PB.	The Strebel SRP TR 90 pellet boiler installation manual reference "Installation and operation instructions for special pellet-furnace" version 09:2010.	6mm diameter wood pellets. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Stretton Insert Smoke Exempt Wood Fuel Stove (Stretton Stove SE) manufactured by Aga, Station Road, Ketley, Telford, Shropshire TF1 5AQ.	Instruction manual references "N00530AXX REV:001" dated 12 <sup>th</sup> July 2011.	Dry wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
STU 195 and STU 975 biomass boilers manufactured by Hoval Limited, Northgate, Newark, Nottinghamshire, NG24 1JN.	Instruction, operation and maintenance. Instruction manual for STU wood-pellet fired hot water boiler skid assembly "STUman" dated May 2011.	Wood Pellets. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Suprema, Mamy and Italy Hard Top manufactured by La Nordica Spa, Via Summano 104 M, Precalcino, 36030, Vicenza, Italy.	Instruction manual references "7095701 Rev.09" dated 13/12/2010.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Talbott 150-CMH 150kW output Biomass Air Heater manufactured by Talbott's Biomass Energy Systems Limited, Tollgate Drive, Tollgate Industrial Estate, Stafford ST16 3HS.	Instruction manual for Talbott 150-CMH hand-fed Biomass Air Heater operating package reference "OM-150-CMH version.1" dated January 2011.	Softwood, Hardwood, medium density fibreboard (MDF) or chipboard offcuts. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

<p>Talbott T5-1M Automatic Heater, manufactured by Talbott's Heating Limited.</p>	<p>The manufacturer's instructions published in January 1989 and bearing the reference "Jan.89, T5-A-1-89".</p>	<p>No fuel shall be used other than softwood shavings, hardwood shavings or chipboard dust. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.</p>
<p>Talbott's Automatic Biomass Air Heaters, models T1.5/A, T3/A, T5/A and TM/A formerly manufactured by Talbott's Heating Limited and now manufactured by Talbott's Biomass Energy Systems Limited, Tollgate Drive, Tollgate Industrial Estate, Stafford ST16 3HS.</p>	<p>The manufacturer's instructions bearing the reference "T/A January 1990".</p>	<p>No fuel shall be used other than hardwood or softwood shavings or sawdust. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.</p>
<p>The Talbott's Biomass Energy Models C1, C2, C3 and C4 formerly manufactured by Talbott's Heating Limited and now manufactured by Talbott's Biomass Energy Systems Limited, Tollgate Drive, Tollgate Industrial Estate, Stafford ST16 3HS.</p>	<p>The manufacturer's instructions dated August 1995 bearing the reference "Issue C1000/C/Range".</p>	<p>No fuel shall be used other than chipboard or wood shavings or forestry chips. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.</p>
<p>Talbott's Energy Saving Wood Waste Burning Automatic Warm Air Heaters models T1.5/A, T3/A, T5/A and TM/A manufactured by Talbott's Heating Limited.</p>	<p>The manufacturer's instructions published in January 1990 and bearing the reference "T/A JANUARY 1990".</p>	<p>No fuel shall be used other than hardwood or softwood shavings or sawdust. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.</p>
<p>Talbott's model T75, T150, T300 Biomass Air Heaters formerly manufactured by Talbott's Heating Limited and now manufactured by Talbott's Biomass Energy Systems Limited, Tollgate Drive, Tollgate Industrial Estate, Stafford ST16 3HS.</p>	<p>The manufacturer's instructions dated 1st January 1995 bearing the following reference - models T75, T150 and T300: "gen/sttech".</p>	<p>No fuel shall be used other than wood offcuts, wood waste, pallets, or chipboard. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.</p>
<p>Talbott Pirojet P150 Heater manufactured by Talbott's Heating Limited.</p>	<p>The manufacturer's instructions dated February</p>	<p>(a)</p>

**Status:** This is the original version (as it was originally made).

	<p>1987 and bearing the reference “No.P150-2.87”.</p>	<p>No fuel shall be used other than hardwood or softwood offcuts, or chipboard. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings;</p> <p><b>(b)</b></p> <p>When the fireplace is used to burn chipboard, an afterburner which is supplied with the fireplace and which must be capable of continuously producing 20 megajoules of heat per hour shall be used;</p> <p><b>(c)</b></p> <p>The fireplace shall not be used to burn sawdust in bulk.</p>
<p>Talbott Pirojet P300 Heater manufactured by Talbott’s Heating Limited.</p>	<p>The manufacturer’s instructions dated February 1987 and bearing the reference “No.P300-2-87”.</p>	<p><b>(a)</b></p> <p>No other fuel shall be used other than hardwood or softwood offcuts, or chipboard. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings;</p> <p><b>(b)</b></p> <p>When the fireplace is used to burn chipboard, an afterburner which is supplied with the fireplace and which must be capable of continuously producing 40 megajoules of heat per hour shall be used;</p> <p><b>(c)</b></p> <p>The fireplace shall not be used to burn sawdust in bulk.</p>
<p>Talbott Pirojet P600 Heater manufactured by Talbott’s Heating Limited.</p>	<p>The manufacturer’s instructions dated December</p>	<p><b>(a)</b></p>

	1986 and bearing the reference “No.P600-12.86”.	<p>No fuel shall be used other than hardwood or softwood offcuts or chipboard. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings;</p> <p><b>(b)</b></p> <p>When the fireplace is used to burn chipboard, an afterburner which is supplied with the fireplace and which must be capable of continuously producing 75 megajoules of heat per hour shall be used;</p> <p><b>(c)</b></p> <p>The fireplace shall not be used to burn sawdust in bulk.</p>
Talbott Down Firing range of warm air heaters, models D250, D500 and D700 manufactured by Talbott’s Heating Limited.	The manufacturer’s instructions bearing the reference “May 1991 Ref No. D257”.	No fuel shall be used other than chipboard. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Talbott’s Energy Saving Wood Waste Burning Automatic Hot Water Heaters, models T1.5/AB, T3/AB, T5/AB and TM/AB, manufactured by Talbott’s Heating Limited.	The manufacturer’s instructions dated October 1993 and bearing the reference “Issue: A1001”.	No fuel shall be used other than hardwood or softwood shavings or sawdust. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Talbott’s Combustion Units models CM1, CM2, CM3 and CM4 manufactured by Talbott’s Heating Limited.	The manufacturer’s instructions dated August 1997 and bearing the reference “Issue: CM897”.	No fuel shall be used other than wood waste, pallets, medium density fibreboard, or untreated and airdried wood offcuts. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Talbott’s Combustion Units models C1, C2, C3 and C4	The manufacturer’s instructions dated August 1995	No fuel shall be used other than chipboard or wood shavings, or forestry chips. The fuel must

**Status:** This is the original version (as it was originally made).

manufactured by Talbott's Heating Limited.	bearing the reference "Issue: C10000/C/Range".	not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Talbott's Heating models T75, T150, T300, D250B, D500B and D700B, manufactured by Talbott's Heating Limited.	The manufacturer's instructions dated 1 <sup>st</sup> January 1995 bearing the following reference—  <b>(i)</b> models T75, T150 and T300: "gen/sttech";  <b>(ii)</b> models D250B, D500B and D700B: "Gen/Tech".	No fuel shall be used other than the following—  <b>(i)</b> models T75, T150 and T300: wood offcuts, wood waste, pallets, or chipboard;  <b>(ii)</b> models D250B, D500B and D700B: hardwood or softwood offcuts, or chipboard.  The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Talbott's T500 Biomass Air heater (afterburn model) formerly manufactured by Talbott's Heating Limited and now manufactured by Talbott's Biomass Energy Systems Limited, Tollgate Drive, Tollgate Industrial Estate, Stafford ST16 3HS.	The manufacturer's instructions dated 1 <sup>st</sup> January 1983, and bearing the reference A10000.  The afterburn cycle shall last not less than 25 minutes and shall come into operation each time the loading door is opened.	No fuel shall be used other than wood offcuts, wood waste, pallets, or chipboard.  The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Termosuprema Compact DSA manufactured by La Nordica Spa, Via Summano 104 M. Precalcino 36030, Vicenza, Italy.	Instruction manual references "7095802 Rev.06" dated 01/02/2011.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Therminator II 22 and Therminator II 30 Boiler manufactured by Solarfocus, Werkstrasse 1, 4451 St.Ulrich, Steyr, Austria.	Installation Instructions "Version 11/08/06" dated 07/2006. Operating Manual "V8.051" dated 09/2009. Maintenance Instructions "Ver 01/09/06" dated 2006.	Wood pellets. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Therminator II 27 and Therminator II 36 Boiler manufactured by Solarfocus,	Installation Instructions "Version 11/08/06" dated 07/2006. Operating Manual	Wood logs. The fuel must not contain halogenated organic compounds or heavy



Werkstrasse 1, 4451 St.Ulrich, Steyr, Austria.	“V8.051” dated 09/2009. Maintenance Instructions “Ver 01/09/06” dated 2006.	metals as a result of treatment with wood-preservatives or coatings.
Therminator II 40 Boiler manufactured by Solarfocus, Werkstrasse 1, 4451 St.Ulrich, Steyr, Austria.	Installation Instructions “Version 11/08/06” dated 07/2006. Operating Manual “V8.051” dated 09/2009. Maintenance Instructions “Ver 01/09/06” dated 2006.	Wood pellets or wood chips. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Therminator II 49 and Therminator II 60 Boiler manufactured by Solarfocus, Werkstrasse 1, 4451 St.Ulrich, Steyr, Austria.	Installation Instructions “Version 11/08/06” dated 07/2006. Operating Manual “V8.051” dated 09/2009. Maintenance Instructions “Ver 01/09/06” dated 2006.	Wood logs or wood pellets or wood chips. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Thornhill T3 small manufactured by Thornhill Eco Design Ltd, 58/60 Wincheap, Canterbury, Kent, CT1 3RS.	Instruction manual references “ED/11/05” dated January 2011. The appliance must be fitted with an air plate that prevents the tertiary air controller from closing more than 17mm and opening more than 45mm.	Wood. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Tiger SuperClean stove manufactured by Tiger stoves, Focus Arts & Crafts Co, Industrial Area Gao Zhuangzi Village, Xin Zhuang Town, Jin Nan District, Tianjin, P.R. China 300350.	Instruction manual references “INSTALLATION AND OPERATING INSTRUCTIONS document v. 148” (dated April 2010).	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.
Triancomatic 90 boiler manufactured by Trianco Redfyre Limited.	The manufacturer’s instructions dated July 1987 and which—  <b>(i)</b>  in the case of installation instructions bear the reference “No. 46576”; and  <b>(ii)</b>  in the case of the user instructions bear the reference “No. 46574”.	No fuel shall be used other than the washed coals recommended in the manufacturer’s instructions.
Triancomatic 140 boiler manufactured by Trianco Redfyre Limited.	The manufacturer’s instructions dated November 1986 and which—	No fuel shall be used other than the washed coals recommended

**Status:** This is the original version (as it was originally made).

	<p><b>(i)</b></p> <p>in the case of the installation instructions bear the reference “No. 48375”; and</p> <p><b>(ii)</b></p> <p>in the case of the user instructions bear the reference “No. 48374”.</p>	in the manufacturer’s user instructions.
Turbhogar Alfa 80T and 65T, Turbhogar Beta 80T, Turbhogar Delta 80T and 65T, Turbhogar Lambda 80T and 65T, Turbhogar Sigma 80T and 65T, Turbhogar Omega 80T and Turbhogar Tau 80T and 65T fireplace inserts manufactured by Rofer & Rodi UK Ltd, Unit 10, Millennium Road, Airedale Business Centre, Skipton, North Yorkshire, BD23 2TZ.	<p>Manual of assembly and use referenced “RR100920” dated 20/09/2010 and supplementary instruction manual “UK100920” dated 20/09/2010.</p> <p>Appliances will be fitted with a system that prevents the full closure of the air control opening, so that the air openings remain 3mm (30%) open at the minimum setting.</p>	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Turbo Heat, models 1000 and 1200 manufactured by CBR Engineers Limited.	The manufacturer’s instructions published in 1990 and bearing the reference “CBR Turbo Heat 1000/1200 1990”.	No fuel shall be used other than hardwood or softwood offcuts, or chipboard. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Twin Heat CS150i manufactured by TWIN HEAT A/S, Nørrevangen 7, DK-9631 Gedsted, Denmark.	Operating instructions dated 17 <sup>th</sup> December 2008, reference version 6.0.03.	Wood pellets of a maximum length of 30 mm and diameter of 6 mm and conforming to CEN/TS 14961:2005. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.
Type USP wood pellet-fired boilers, model numbers USP-10, 15, 20, 25 and 30, manufactured by KWB-Kraft and Wärme aus Biomasse Gesellschaft mit beschränkter Haftung (GmbH) of Industriestrasse 235,	The manufacturer’s instructions dated 28 <sup>th</sup> July 2003, reference BA-USP 0703.	Wood pellets. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.

A-8321 St. Margarethen an der Raab, Austria.		
Uniconfort EOS 45, EOS 50, EOS 55, EOS 65, EOS 70, EOS 75, EOS 80, EOS 85 fitted with a multi-cyclone manufactured by Uniconfort srl, Via dell'Industria, 21, 35018 San Martino di Lupari, PD, Italy.	Instruction manual references "Uniconfort EOS MANUAL: R1" dated May 2012.	Wood pellets. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Uniconfort EOS 90 fitted with a multi-cyclone manufactured by Uniconfort srl, Via dell'Industria, 21, 35018 San Martino di Lupari, PD, Italy.	Instruction manual references "Uniconfort EOS MANUAL: R1" dated May 2012.	Wood pellets or wood chips. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
VarioWIN VA 120 12kW wood pellet boiler manufactured by Windhager Zentralheizung GmbH, Anton-Windhager-Str. 20, A-5201 Seerkirchen bei Salzburg, Austria.	Installation Instruction manual references "092947/00" dated 01/2010 and operating instruction manual "092945/00" dated 01 2010.	Wood pellets, 6mm diameter, length 80% between 15-30mm and a density of at least 1.1kg/dm <sup>3</sup> .
Vesuvio 400kW automatic pizza oven manufactured by CLM srl, Via I Maggio 35, 31043, Fontanelle (Treviso), Italy.	CLM Vesuvio oven instruction manual reference "Instruction and maintenance manual ENGLISH" version Review 0.1 dated 29/11/2011.	'CalorPan' 100% beech briquette, octagonal section, length 260-300mm, width and height 75-90mm. Manufactured from dried beech sawdust. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
View 3 (3.8kW) and View 5 (4.9kW) multifuel stoves manufactured by Stovax Limited, Falcon Road, Sowton Industrial Estate, Exeter, Devon, EX2 7LF.	Instruction manual references PM485 Issue 1 dated June 2010 and smoke control kit instruction manual PM490 Issue 1 dated June 2010.  A permanent stop must be positioned to prevent closure of the secondary air control below the 50% open position.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.
View 5 (4.9kW) wood stove manufactured by Stovax Limited, Falcon Road, Sowton Industrial Estate, Exeter, Devon, EX2 7LF.	Instruction manual references PM485 Issue 1 dated June 2010 and smoke control kit instruction manual PM490 Issue 1 dated June 2010.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.

*Status: This is the original version (as it was originally made).*

	A permanent stop must be positioned to prevent closure of the secondary air control below the 50% open position.	
View 7 (7kW) inset appliance Product code VW-7NMF manufactured by Stovax Limited, Falcon Road, Sowton Industrial Estate, Exeter, Devon, EX2 7LF.	Instruction manual reference “PM552 - Issue 1” dated June 2011 and smoke control kit instruction manual reference “PM490 Issue 2” dated July 2011.  A permanent stop must be in place on the secondary air inlet to prevent closure beyond the 50% open position.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Vista Magnifico SE & Vista Perfetto SE 4.9kW Wood Burning Stove. Manufactured by Ciang Stoves Limited, South Chuangye Road, (Hanling Industrial Estate), Beiguan Section, Anyang City, Henan Province, China 455000.	Newman Fireplaces Limited’s Instruction manual references “1-2” dated 24 <sup>th</sup> October 2011. Fitted with mechanical stops to prevent closure of the secondary air control beyond the 30% open position and the tertiary air beyond the 50% open position when sold into smoke control areas.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Vitae 06C inset stove manufactured by Heat Design, 30 Hawthorn Road, Western Industrial Estate, Naas Road, Dublin 12, Ireland.	Instruction manual references “VIT06C” dated 26/07/12. A permanent stop to prevent closure of the secondary air control beyond 20% open must be implemented.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Vitae 11C inset stove manufactured by Heat Design, 30 Hawthorn Road, Western Industrial Estate, Naas Road, Dublin 12, Ireland.	Instruction manual references “VIT11C” dated 26/07/12. A permanent stop to prevent closure of the secondary air control beyond 20% open must be implemented.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Westcott 5SE manufactured by Dimplex, GDC Group Limited, Millbrook House, Grange Drive, Hedge End, Southampton, SO30 2DF.	Instruction manual references 08/51351/0 - Issue 0 Dated 07/09/10.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Westfire Series One stove and Westfire Series Two stove manufactured by Westfire, Tømmervej 3, DK-6800 Varde, Denmark.	Westfire WF One and Two series installation manual and operating instructions and supplementary Instruction manual reference “Westfire supplementary instructions	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

	June 2011/Version 1” dated 1st June 2011. The appliance must be fitted with a permanent stop to prevent closure of the secondary air control less than 50% open.	
Westfire Uniq 15, 16 and 20 (also known as WF UNIQ 15, 16 and 20) manufactured by Westfire Tømrervej 3 DK-6800 Varde, Denmark.	Installation and operating instructions dated 2007, reference WF15-WF16-WF20, together with supplementary instructions dated 2007, reference 01 wfuk.2007.  A permanent stop must be in place on the secondary air inlet to prevent closure beyond 50mm.	Untreated dry wood. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.
Westfire Uniq 18 Westfire Uniq 17 Westfire Uniq 19 Westfire Uniq 23 Westfire Uniq 23 side Glass Westfire Uniq 23 Inset stoves manufactured by Westfire APS, Tømrervej 3 DK-6800 Varde, Denmark.	Instruction manual references “WESTFIRE SUPPLEMENTARY INSTRUCTIONS JUNE 2010”.  All appliances will be fitted with a mechanical stop to prevent closure of the secondary air slide beyond the 30mm open position when sold into smoke control areas.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.
Westfire Uniq 21 stove, Westfire Uniq 21 pedestal stove and Westfire Uniq 21 wall hung stove manufactured by Westfire, Tømrervej 3, DK-6800 Varde, Denmark.	Westfire WF21 installation manual and operating instructions and supplementary Instruction manual reference “Westfire supplementary instructions June 2011/Version 1” dated 1st June 2011. The appliance must be fitted with a permanent stop to prevent closure of the secondary air control less than 60% open.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Westfire Uniq 26 stove, Westfire Uniq 27 stove and Westfire Uniq 28 stove manufactured by Westfire, Tømrervej 3, DK-6800 Varde, Denmark.	Westfire WF26, WF27, WF28 installation manual and operating instructions and supplementary Instruction manual reference “Westfire supplementary instructions June 2011/Version 1” dated 1st June 2011. The appliance must be fitted with a permanent	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

**Status:** This is the original version (as it was originally made).

	stop to the secondary air slider control to prevent closure more than 20mm from the fully closed position.	
Westfire Uniq 32 Inset stove and Westfire Uniq 32 Freestanding stove manufactured by Westfire, Tømrervej 3, DK-6800 Varde, Denmark.	Westfire WF23/Uniq23, WF32/Uniq 32 inset stove installation manual and operating instructions and supplementary Instruction manual reference “Westfire supplementary instructions June 2011/Version 1” dated 1st June 2011. The appliance must be fitted with a permanent stop to prevent closure of the secondary air control less than 50% open.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Windhager BioWin 100, 150, 210 and 260 manufactured by Windhager Zentralheizung GmbH, Anton-Windhager-Str. 20, A-5201 Seerkirchen bei Salzberg, Austria.	The manufacturer’s instruction manual reference 0916197/00, dated May 2008.	Wood pellets. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.
Windhager FireWin 90 and 120 manufactured by Windhager Zentralheizung GmbH, Anton-Windhager-Str. 20, A-5201 Seerkirchen bei Salzberg, Austria.	The manufacturer’s instruction manual reference 092125/00, dated August 2008.	Wood pellets. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.
Wood Fired Ovens by Jamie Oliver Limited’s Valoriani Casa 80 manufactured by Valoriani of Via Caselli alla Fornace, 213, 50066 Reggello, Firenze, Italy.	Instruction manual reference “OOLinst.1 FVR 80 v2” and dated January 2011.	Untreated wood of less than 20% moisture. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Wood Fired Ovens by Jamie Oliver Limited’s Valoriani Casa 100 manufactured by Valoriani of Via Caselli alla Fornace, 213, 50066 Reggello, Firenze, Italy.	Instruction manual reference “OOLinst.2 FVR 100 v2” and dated January 2011.	Untreated wood of less than 20% moisture. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Wood Fired Ovens by Jamie Oliver Limited’s Valoriani Casa 110 manufactured by Valoriani of Via Caselli alla Fornace, 213, 50066 Reggello, Firenze, Italy.	Instruction manual reference “OOLinst.3 FVR 110 v2” and dated January 2011.	Untreated wood of less than 20% moisture. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment

		with wood-preservatives or coatings.
Wood Fired Ovens by Jamie Oliver Limited's Valoriani Casa 120 manufactured by Valoriani of Via Caselli alla Fornace, 213, 50066 Reggello, Firenze, Italy.	Instruction manual reference "OOLinst.4 FVR120 v2" and dated January 2011.	Untreated wood of less than 20% moisture. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Wood Fired Ovens by Jamie Oliver Limited's Valoriani Casa 110x160 manufactured by Valoriani of Via Caselli alla Fornace, 213, 50066 Reggello, Firenze, Italy.	Instruction manual reference "OOLinst.5 FVR 110x160 v2" and dated January 2011.	Untreated wood of less than 20% moisture. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Wood Fired Ovens by Jamie Oliver Limited's Valoriani Villa 100 manufactured by Valoriani of Via Caselli alla Fornace, 213, 50066 Reggello, Firenze, Italy.	Instruction manual reference "OOLinst.6 TOP 100 v2" dated January 2011.	Untreated wood of less than 20% moisture. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Wood Fired Ovens by Jamie Oliver Limited's Valoriani Villa 120 manufactured by Valoriani of Via Caselli alla Fornace, 213, 50066 Reggello, Firenze, Italy.	Instruction manual reference "OOLinst.7 TOP 120 v2" dated January 2011.	Untreated wood of less than 20% moisture. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Wood Fired Ovens by Jamie Oliver Limited's GR Valoriani Ristorante 100 and OT Valoriani Ristorante 100 manufactured by Valoriani of Via Caselli alla Fornace, 213, 50066 Reggello, Firenze, Italy.	Instruction manual reference "OOLinst.8 GR 100 and OT 100 v2" and dated January 2011.	Untreated wood of less than 20% moisture. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Wood Fired Ovens by Jamie Oliver Limited's GR Valoriani Ristorante 120 and OT Valoriani Ristorante 120 manufactured by Valoriani of Via Caselli alla Fornace, 213, 50066 Reggello, Firenze, Italy.	Instruction manual reference "OOLinst.9 GR 120 and OT 120 v2" and dated January 2011.	Untreated wood of less than 20% moisture. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Wood Fired Ovens by Jamie Oliver Limited's GR Valoriani Ristorante 140 and OT Valoriani Ristorante 140 manufactured by Valoriani of	Instruction manual reference "OOLinst.10 GR 140 and OT 140 v2" and dated January 2011.	Untreated wood of less than 20% moisture. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment

*Status: This is the original version (as it was originally made).*

Via Caselli alla Fornace, 213, 50066 Reggello, Firenze, Italy.		with wood-preservatives or coatings.
Wood Fired Ovens by Jamie Oliver Limited's GR Valoriani Ristorante 120x160 and OT Valoriani Ristorante 120x160 manufactured by Valoriani of Via Caselli alla Fornace, 213, 50066 Reggello, Firenze, Italy.	Instruction manual reference "OOLinst.11 GR 120x160 and OT 120x160 v2". Dated January 2011.	Untreated wood of less than 20% moisture. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Wood Fired Ovens by Jamie Oliver Limited's GR Valoriani Ristorante 140x160 and OT Valoriani Ristorante 140x160 manufactured by Valoriani of Via Caselli alla Fornace, 213, 50066 Reggello, Firenze, Italy.	Instruction manual reference "OOLinst.12 GR 140x160 and OT 140x160 v2" and dated January 2011.	Untreated wood of less than 20% moisture. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Wood Fired Ovens by Jamie Oliver Limited's GR Valoriani Ristorante 140x180 and OT Valoriani Ristorante 140x180 manufactured by Valoriani of Via Caselli alla Fornace, 213, 50066 Reggello, Firenze, Italy.	Instruction manual reference "OOLinst.13 GR 140x180 and OT 140x180 v2" and dated January 2011.	Untreated wood of less than 20% moisture. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Wood Fired Ovens by Jamie Oliver Limited's GR Valoriani Ristorante 180 and OT Valoriani Ristorante 180 manufactured by Valoriani of Via Caselli alla Fornace, 213, 50066 Reggello, Firenze, Italy.	Instruction manual reference "OOLinst.14 GR 180 and OT 180 v2" and dated January 2011.	Untreated wood of less than 20% moisture. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Wood Fired Ovens by Jamie Oliver Limited's Valoriani Piccolo manufactured by Valoriani of Via Caselli alla Fornace, 213, 50066 Reggello, Firenze, Italy.	Instruction manual reference "OOLinst.15 Valoriani Piccolo v2" and dated January 2011.	Untreated wood of less than 20% moisture. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Woodpecker 15, 25 and 45 wood pellet boilers manufactured by Woodpecker Energy UK, Abbey Manor Business Centre, Preston Road, Yeovil, BA20 2EN. Previously manufactured by Garranlea Renewables Ltd of Barnard, Garranlea, New Inn, Cashel, Co. Tipperary, Ireland.	Instruction manual references "Installation and Operating Manual Issue 6 dated May 2012".	Wood pellets conforming to CEN TS 14961. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.
Woodpecker 50kW wood pellet boilers manufactured	Instruction manual references "Installation and Operating	Wood pellets conforming to CEN TS 14961. The fuel



by Woodpecker Energy, Abbey Manor Business Centre, Preston Road, Yeovil, Somerset, BA20 2EN.	Manual Woodpecker 50 Model Wood Pellet Boiler System Version 2 dated May 2012”.	must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Woodpecker Thermon 150, 200, 250 and 300 boilers manufactured by Woodpecker Energy UK, Abbey Manor Business Centre, Preston Road, Yeovil, BA20 2EN.	Instruction manual references “Installation and Operating Manual Issue 2 dated February 2012”.	6mm wood pellets. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Woodpecker Thermon 199 kW pellet boiler manufactured by Woodpecker Energy UK, Abbey Manor Business Centre, Preston Road, Yeovil, BA20 2EN.	Instruction manual references “Issue 2.0” dated February 2012.	6mm wood pellets. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Wood Waste Technology Ltd WT5, manufactured by Wood Waste Technology Limited, Units 1&2, Drummond Road, Astonfields Industrial Estate, Stafford, Staffordshire ST16 3HJ.	The manufacturer’s instruction manual reference WT5 v2, dated 16 <sup>th</sup> February 2009.	Medium density fibreboard, chipboard and hard and softwood offcuts. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.
Wood Waste Technology Heater, models WT10 and WT15, manufactured by Wood Waste Technology Limited, Units 1&2, Drummond Road, Astonfields Industrial Estate, Stafford, Staffordshire ST16 3HJ.	The manufacturer’s instructions dated 19 <sup>th</sup> January 2005 and bearing the reference WT10 and WT15.	Medium density fibreboard, chipboard and hard and softwood offcuts. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.
Worcester Centair 40 Solid Fuel Warm Air Heater manufactured by Worcester Engineering Co. Limited.	The manufacturer’s instructions which— <b>(i)</b> in the case of installation instructions bear the reference “BC40.1.2 July 1983”; and <b>(ii)</b> in the case of operating and maintenance instructions bear the reference “BC40.OM2 July 1983”.	Union Coal Briquettes, manufactured by Rheinbraun AG of Germany and comprising lignite compressed into briquettes of approximately 15 centimetres in length with square ends and with a sulphur content not exceeding one per cent. Shall be treated as a fuel which may be used in accordance with those manufacturer’s instructions.
WTA WT Auto 200kW Airheater manufactured by	Instruction manual references “WTA Installation Operation	Chipboard, Medium Density Fibreboard, Softwood,

**Status:** This is the original version (as it was originally made).

Wood Waste Technology Limited, Units 1, 2 & 3, Drummond Road, Astonfields Industrial Estate, Stafford, ST16 3HJ.	& Maintenance Instructions” WTA v1 Issue A dated April 2011.	Hardwood. All fuels to be chipped to a maximum size of 25mm and a maximum moisture content of 20%. Maximum fines (sawdust) content 5%. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
WTH 150 and WTH 200 boilers manufactured by Hargassner Gesellschaft mit beschränkter Haftung (GmbH), Gundering 8, A-4952, Weng, Austria.	The manufacturer’s installation manual version 91 for Large Capacity Boiler WTH 150-200. Reference BA GK V90b 0309.	Wood chip or wood pellets. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.
Xeos 5kW stove Versions – Natur, Style, Harmony, Pur, Classic, Elegance and Stone Xeos 8kW stove Versions – Basic, Pur, Classic, Elegance Stone and Air Instruction manual references. Manufactured by Specht Modulare Ofensysteme GmbH & Co, KG i.V. Dipl. – Ing. Frank Werner Projektmanagement Bahnhofstr.2 D 35116 Hatzfeld.	“Operating and Installation Instructions Xeos 5kW/8kW Model 2008” Reference; Revisions – Index 01/08 Fassung January 2008.	Wood logs Conforming to DIN 51731.  The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.
Yeoman CL Milner Stove Product code YM-CLMB manufactured by Stovax Limited, Falcon Road, Sowton Industrial Estate, Exeter, Devon, EX2 7LF.	Instruction manual reference “PM559 - Issue 1” dated June 2011 and smoke control kit instruction manual reference “PM491 Issue 2” dated June 2011.  A permanent stop must be positioned to prevent closure of the secondary air control below the 50% open position.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Yeoman CL3 (3.8kW) and CL5 (4.9kW) multifuel stoves manufactured by Stovax Limited, Falcon Road, Sowton Industrial Estate, Exeter, Devon, EX2 7LF.	Instruction manual references PM489 Issue 1 dated June 2010 and smoke control kit instruction manual PM491 Issue 1 dated 5 <sup>th</sup> April 2010.  A permanent stop must be positioned to prevent closure	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.

	of the secondary air control below the 50% open position.	
Yeoman CL5 (4.9kW) wood stove manufactured by Stovax Limited, Falcon Road, Sowton Industrial Estate, Exeter, Devon, EX2 7LF.	<p>Instruction manual references PM489 Issue 1 dated June 2010 and smoke control kit instruction manual PM491 Issue 1 dated 5 April 2010.</p> <p>A permanent stop must be positioned to prevent closure of the secondary air control below the 50% open position.</p>	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.
Yeoman CL 7 (7kW) inset appliance Product code YM-CL7NMF manufactured by Stovax Limited, Falcon Road, Sowton Industrial Estate, Exeter, Devon, EX2 7LF.	<p>Instruction manual reference “PM553 - Issue 1” dated June 2011 and smoke control kit instruction manual reference “PM491 Issue 2” dated June 2011.</p> <p>A permanent stop must be in place on the secondary air inlet to prevent closure beyond the 50% open position.</p>	<p>Wood logs.</p> <p>The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.</p>
Yeoman Devon Multifuel Flat Top 1 Door, Flat Top 2 Door, Low Canopy 1 Door, Low Canopy 2 Door, High Canopy 1 Door and High Canopy 2 Door (9kW) Stoves manufactured by Stovax Limited, Falcon Road, Sowton Industrial Estate, Exeter, Devon, EX2 7LF.	<p>Instruction manual references PM184 Issue 3 dated February 2008 and smoke control kit instruction manual PM403 Issue 1 dated January 2010.</p> <p>A permanent stop must be positioned to prevent closure of the secondary air control below the 50% open position and a system that ensures a gap of 1mm for bleed of primary air when the spin wheels are rotated to their fully closed positions.</p>	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.
Yeoman Exe Multifuel Flat Top 1 Door, Flat Top 2 Door, Low Canopy 1 Door and Low Canopy 2 Door (4.9kW) Stoves manufactured by Stovax Limited, Falcon Road, Sowton Industrial Estate, Exeter, Devon, EX2 7LF.	<p>Instruction manual references PM184 Issue 3 dated February 2008 and smoke control kit instruction manual PM403 Issue 1 dated January 2010.</p> <p>A permanent stop must be positioned to prevent closure of the secondary air control below the 60% open position and a system that prevents</p>	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.

**Status:** This is the original version (as it was originally made).

	full closure of the primary air controls.	
Yeoman Exmoor Multifuel Flat Top and Multifuel Low Canopy (4.9kW) Stoves manufactured by Stovax Limited, Falcon Road, Sowton Industrial Estate, Exeter, Devon, EX2 7LF.	<p>Instruction manual references PM184 Issue 3 dated February 2008 and smoke control kit instruction manual PM403 Issue 1 dated January 2010.</p> <p>A permanent stop must be positioned to prevent closure of the secondary air control below the 60% open position and a system that prevents full closure of the primary air controls.</p>	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.

## EXPLANATORY NOTE

*(This note is not part of the Regulations)*

These Regulations revoke the Smoke Control Areas (Exempted Fireplaces) Regulations (Northern Ireland) 2012 (S.R. 2012 No. 250), and subsequently re-instate the provisions.

In addition, a number of new classes of fireplace are declared exempt from the provisions of Article 17 of the Clean Air (Northern Ireland) Order 1981 (S.I. 1981/158 (N.I. 4)) (“the Clean Air Order”). The list of all exempted fireplaces can be found in the Schedule to these Regulations.

An exemption from the requirements of Article 17 of the Clean Air Order does not confer exemption under any other statutory regime which may be applicable. For example, the burning of waste may be subject to other controls, such as licensing under the Waste Management Licensing Regulations (Northern Ireland) 2003 (S.R. 2003 No. 493), or permitting under the Pollution, Prevention and Control Regulations (Northern Ireland) 2003 (S.R. 2003 No. 46).