STATUTORY INSTRUMENTS

2013 No. 462

CLEAN AIR, ENGLAND

The Smoke Control Areas (Exempted Fireplaces) (England) Order 2013

Made - - - - 2nd March 2013

Laid before Parliament 5th March 2013

Coming into force - - 6th April 2013

The Secretary of State makes the following Order in exercise of the powers conferred by section 21 of the Clean Air Act 1993(1).

The Secretary of State is satisfied that the fireplaces exempted by this Order can be used for burning fuel other than authorised fuels(2) without producing any smoke or a substantial quantity of smoke.

Citation, application and commencement

- 1. This Order—
 - (a) may be cited as the Smoke Control Areas (Exempted Fireplaces) (England) Order 2013;
 - (b) applies in England; and
 - (c) comes into force on 6th April 2013.

Fireplaces exempted from the provisions of section 20 of the Clean Air Act 1993

2. The fireplaces listed in the Schedule are exempt from the provisions of section 20 of the Clean Air Act 1993 (prohibition on emission of smoke in smoke control area), subject to the conditions listed in the Schedule.

Revocation

3. The Smoke Control Areas (Exempted Fireplaces) (England) (No. 2) Order 2012(**3**) is revoked.

^{(1) 1993} c. 11

⁽²⁾ Fuels declared by the Secretary of State to be authorised fuels for the purposes of Part 3 of the Clean Air Act 1993 under section 20(6) of that Act are specified in S.I. 2013/447.

⁽³⁾ S.I. 2012/2282.

de Mauley
Parliamentary Under Secretary of State
Department for Environment, Food and Rural
Affairs

2nd March 2013

SCHEDULE

Article 2

Exempted Fireplaces

Fireplace	Conditi	ons
	The fireplace must be installed maintained and operated in accordance with the following specifications:	Permitted fuels (other than authorised fuels):
100SE Smoke Exempt Woodburning Stove manufactured by ESSE Engineering Limited Limited, Long Ing Barnoldswick Lancashire, BB18 6BN	The manufacturer's instruction manual dated February 2009, reference: 100SE Issue 1. A permanent stop must be in place on the secondary air inlet to prevent closure beyond the 50% open position.	Untreated dry wood with a maximum moisture content of 20% maximum length of 200 mm and maximum width or diameter of 120 mm
18i and 60i stoves manufactured by Jetmaster Fires Limited, Unit 2 Peacock Trading Estate, Goodwood Road, Eastleigh, Hampshire, SO50 4NT	Installation and use instruction manual dated February 2010, reference: Part No 106870 Issue No. 1. Supplementary instruction manual dated May 2010, reference: Part No 106872 Issue No. 1. The appliance must be fitted with a mechanical stop to prevent closure of the air control beyond the 40% open position.	Wood logs ⁽¹⁾
Aarrow Signature 5 SC, Aarrow Ecoburn 5 SC, Hamlet Solution 5 SC and Villager Espirit 5 SC Stoves manufactured by Arada Limited, The Fire Works, Millwey Industrial Estate, Axminster, Devon, EX13 5HU	Instruction manual dated April 2010, reference: Rev 02. The appliance must be fitted with a mechanical stop to prevent closure of the air control beyond 20 mm from the closed position and 50 mm beyond the fully open position.	Wood logs ⁽¹⁾
Acquisitions Bloomsbury 5 kW stove manufactured by Esse Engineering Limited, Ouzedale Foundry, Long Ing, Barnoldswick, BB18 6BN	Instruction manual dated January 2012, reference: 01/12 (PP). The fitting of a system to prevent closure of the air controls beyond the 50% open position must be implemented.	Wood logs ⁽¹⁾

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditi	ions
	Installation and Operating Instruction manual dated 9th November 2010, reference: v71 of 09/11/2010.	Wood logs ⁽¹⁾
ACR Astwood Multifuel Stove AW1MF manufactured by ACR Heat Products Ltd, Unit 1 Weston Works, Weston Lane, Tyseley, Birmingham, B11 3RP	28th January 2013, reference:	Wood logs ⁽¹⁾
Aduro 3D, 8D, 10D, 11D and Asgård 1D, 2D and 7D wood burning stoves manufactured by Aduro A/S, Silkeborgvej 765 8220, Brabrand, Denmark	Instruction manual dated June 2011, reference: Pevex1001/AH/ver1. The appliance must be fitted with permanent stops to ensure that the primary and secondary air controls do not close beyond 95% and 50% respectively	Dry wood logs ⁽¹⁾
Aduro 9D wood burning stove manufactured by Aduro A/ S, Silkeborgvej 765 8220, Brabrand, Denmark	Instruction manual dated June 2011, reference: Pevex1002/AH/ver1. The appliance must be fitted with permanent stops to ensure that the primary and secondary air controls do not close beyond 95% and 50% respectively	Dry wood logs ⁽¹⁾
Alberg 7 manufactured by Elite Group Trading Limited, Room 1208 Kak Tak Commercial Building 317-319 Des Voeux Road, Central Hong Kong 999077	December 2011, reference:	Wood logs ⁽¹⁾
Alpha I model number AL905- SE Wood Burning Stove manufactured by Hi-Flame Fireplace UK Limited, Unit 5A Holmes Chapel Business Park, Manor Lane, Holmes Chapel. Cheshire. CW4 8AF	Instruction manual dated July 2012, reference: HF277-SE/UK-NI-ROI/V2D.18-07-12. The appliance must be fitted with a mechanical stop to prevent closure of the main air	Wood logs ⁽¹⁾

The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives
or coatings.

Fireplace	Conditi	ions
	control beyond the 50% open position	
Alpha II model number AL907- SE Wood Burning Stove manufactured by Hi-Flame Fireplace UK Limited, Unit 5A Holmes Chapel Business Park, Manor Lane, Holmes Chapel, Cheshire. CW4 8AF	Instruction manual dated July 2012, reference: AL907-SE/UK-NI-ROI/V3-D.14-07-12. The appliance must be fitted with a mechanical stop to prevent secondary air control closure beyond the 20% open position, and a 70 mm opening of the door rope seal to allow a constant flow of air when sold into smoke control areas.	Wood logs ⁽¹⁾
Angus Orligno 200 18 kW, 25 kW, 40 kW, 60 kW and 80 kW gasification boilers manufactured by Eko-Vimar Orlanski Spółka z ograniczoną odpowiedzialnością, ul. Nyska 17 b 48-385 Otmuchów, Poland		Wood logs ⁽¹⁾
Angus Orligno 500 7-25 kW boiler manufactured by Eko-Vimar Orlanski Spółka z ograniczoną odpowiedzialnością, ul. Nyska 17 b 48-385 Otmuchów, Poland	Instruction manual dated 3rd October 2012, reference: EV-20121003	Wood pellets ⁽¹⁾
Angus Super 18, 25, 40, 60 and 80 kW gasification boilers manufactured by Eko-Vimar Orlanski Spółka z ograniczoną odpowiedzialnością, ul. Nyska 17 b, 48-385 Otmuchów, Poland	Instruction manual dated October 2011, reference: EV-20111001	Wood logs ⁽¹⁾
Apollo 8 Inset stove manufactured by Chesneys Limited, 194-200 Battersea Park Road, London, SW11 4ND	Instruction manual dated 31st October 2011, reference: CH8K Apollo – V2. The fitting of a system that prevents closure of the air controls further than 40 mm from open must be implemented.	Wood logs ⁽¹⁾

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditi	ons
Arimax Bio 300 kW Arimax Bio 400 kW Arimax Bio 500 kW	Instruction manual dated 30th March 2010, reference: INSTALLATION AND OPERATION MANUAL Arimax Bio 120-3000 kW	6-8 mm wood pellets with a moisture content less than $10\%^{(1)}$
boilers manufactured by Artierm Oy PO Box 59 Fin – 43101 Saarijarvi, Finland		
Ariterm Ekerum 6 kW pellet stove and Neptuni 6 kW pellet stove manufactured by Ariterm Sweden AB, Flottiljvägen 15, 392 41 Kalmar, Sweden		Wood pellets ⁽¹⁾
Ariterm Mysinge 6 kW pellet stove manufactured by Ariterm Sweden AB, Flottiljvägen 15, 392 41 Kalmar, Sweden	Instruction manual dated 15th December 2011, reference: ARITERM-SP-PX26868-B.1	Wood pellets ⁽¹⁾
Ashwell Green-Tec 150 boiler manufactured by Ashwell Biomass Limited, Unit 12, 35 Pinfold Road, Thurmaston, Leicester, LE4 8AT	Instruction manual dated June 2009, reference: ASH-gt150/101 Version 1.2	Wood pellets ⁽¹⁾
Ashwell Green-Tec 195 boiler, manufactured by Ashwell Biomass Limited, Unit 12, 35 Pinfold Road, Thurmaston, Leicester, LE4 8AT		Wood pellets ⁽¹⁾
Ashwell Green-Tec 300 boiler manufactured by Ashwell Biomass Limited, Unit 12, 35 Pinfold Road, Thurmaston, Leicester, LE4 8AT	Instruction manual dated June 2009, reference: ASH-gt300/103 Version 1.2	Wood pellets ⁽¹⁾
Avalon 4 stove manufactured by Hunter Stoves Ltd, Trevilla Park, Slaughterbridge, Camelford, Cornwall, PL32	Instruction manual dated 13th June 2012, reference: JINAV04 Rev C.	Wood logs ⁽¹⁾
9TT	The appliance must be fitted with a permanent stop that prevents closure of the secondary air slider beyond 30% open.	
Avalon 5 slimline stove manufactured by Hunter Stoves Ltd, Trevilla Park,	June 2012, reference: JINAVS05	Wood logs ⁽¹⁾

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
Slaughterbridge, Camelford, Cornwall, PL32 9TT		
Avalon 6 stove manufactured by Hunter Stoves Ltd, Trevilla Park, Slaughterbridge, Camelford, Cornwall, PL32 9TT	,	Wood logs ⁽¹⁾
Avalon Compact 5 stove manufactured by Hunter Stoves Ltd, Trevilla Park, Slaughterbridge, Camelford, Cornwall, PL32 9TT	,	Wood logs ⁽¹⁾
	Instruction manual dated 27th June 2012, reference: JINAVS08 rev B	Wood logs ⁽¹⁾
Barbas ECO 52 Stove manufactured by Interfocos, Hallenstraat 17, 5531 AB Bladel, The Netherlands.	Instruction manual dated March 2010, reference: 02 -327332	Wood logs ⁽¹⁾
Barbas Unilux 3 –40, 5 kW wood burning insert and Barbas ECO 40, 5 kW wood burning roomheater manufactured by Interfocos BV, Hallenstraat 17, 5531, AB, Bladel, The Netherlands	document version 01- 326587 dated August 2009. The ECO 40 instruction manual,	Wood logs ⁽¹⁾
Barbas Unilux 3 -52 Stove manufactured by Interfocos, Hallenstraat 17, 5531 AB Bladel, The Netherlands.	Instruction manual dated March 2010, reference: 03 -326587	Wood logs ⁽¹⁾
Baxi Bioflo manufactured by Windhager Zentralheizung GmbH, Anton-Windhager-Str. 20, A-5201 Seekirchen bei, Salzburg, Austria.	Operating instruction manual dated 2010, reference: 720574401. Installation and servicing instruction manual dated 2010, reference: 720574501	Wood pellets ⁽¹⁾

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditi	ons
Be Modern Monroe 5, Monroe 5, Be Modern Monterrey 5, Monterrey 5 and York Midi Multi Fuel Stoves manufactured by Broseley Fires Ltd, Knights Way Battlefield Enterprise Park, Shrewsbury, Shropshire SY1 3AB	October 2010, reference: OCT	Wood logs ⁽¹⁾
Be Modern Monterrey 7, Monterrey 7, Be Modern Monroe 7 and Monroe 7 Multi Fuel Stoves manufactured by Broseley Fires Ltd, Knights Way Battlefield Enterprise Park, Shrewsbury, Shropshire SY1 3AB	Instruction manual dated 6th	Wood logs ⁽¹⁾
I and the second	Instruction manual dated 21st May 2012, reference: ARITERM-VTT-S-07229-11.1	Wood pellets ⁽¹⁾
	Instruction manual dated 21st May 2012, reference: ARITERM-VTT-S-07229-11.2	Wood pellets ⁽¹⁾
	Instruction manual dated 21st May 2012, reference: ARITERM-VTT-S-06765-11.1	Wood pellets ⁽¹⁾
Biomatic +40 light boiler and Biomatic +40 ultra light boiler manufactured by Ariterm Sweden AB, Flottiljvägen 15, 392 41 Kalmar, Sweden		Wood pellets ⁽¹⁾
Biomatic 220 and 250 fitted with Zyklovent 220–250 cyclone separator manufactured by HERZ Armaturen Ges.m.b.H, Geschäftsbereich HERZ, Feuerungstechnik, A–8272 Sebersdorf 138, Austria	dated April 2005, reference:	Chipped wood, wood pellets or planed wood shavings ⁽¹⁾
Biomatic 300, 350, 400 and 500 fitted with Zyklovent 300-500 cyclone		Chipped wood, wood pellets or planed wood shavings ⁽¹⁾

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditi	ons
separator manufactured by HERZ Armaturen Ges.m.b.H, Geschäftsbereich HERZ, Feuerungstechnik, A-8272 Sebersdorf 138, Austria	Bedienungsanleitung Englisch v2.0 doc	
Boru 4.9 kW Stove manufactured by Righpur Limited, T/A Boru Stoves, the Hive, Ballydine, Gooldscross, Ireland	Instruction manual dated 26th January 2011, reference: BFF010. The air controls must be fixed such that they cannot be closed more than: Primary air slide 2 mm, Secondary air slide 2 mm, Tertiary air slide 30%	Wood logs ⁽¹⁾
Burley Brampton 8 kW stove (also known as Navitron Stalham 8 kW) manufactured by Burley Appliances, Lands' End Way, Oakham, Rutland, LE15 6RB	Instruction manual dated October 2011, reference: BUR/11/10	Wood logs ⁽¹⁾
Burley Debdale 4 kW stove (also known as Navitron Bacton 4 kW) manufactured by Burley Appliances, Lands' End Way, Oakham, Rutland, LE15 6RB	Instruction manual dated October 2011, reference: BUR/11/10. The radius of the air inlet hole must be 19 mm	Wood logs (1)
Burley Hollywell SE (also known as Navitron Cromer 5 kW) manufactured by Burley Appliances Ltd, Lands End Way, Oakham, Rutland LE15 6RB	Instruction manual dated January 2011, reference: BUR/11/05. The appliance must be fitted with an air plate that prevents the tertiary air controller from closing more than 17 mm and opening more than 45 mm	Wood logs ⁽¹⁾
Bushman Large Commercial Pizza Oven manufactured by Dingley Dell Enterprises Ltd, PO Box 3534, Kidderminster, Worcestershire, DY14 9ZE	Instruction manual dated January 2011, reference: LCOINST	Wood logs ⁽¹⁾
Bushman Large Domestic Pizza Oven manufactured by Dingley Dell Enterprises Ltd, PO Box 3534, Kidderminster, Worcestershire, DY14 9ZE	Instruction manual dated January 2011, reference: LDOINST	Wood logs ⁽¹⁾
Bushman Medium Commercial Pizza Oven manufactured by Dingley Dell Enterprises Ltd,	Instruction manual dated January 2011, reference: MCOINST	Wood logs ⁽¹⁾

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
PO Box 3534, Kidderminster, Worcestershire, DY14 9ZE		
Bushman Medium Domestic Pizza Oven manufactured by Dingley Dell Enterprises Ltd, PO Box 3534, Kidderminster, Worcestershire, DY14 9ZE	Instruction manual dated January 2011, reference: MDOINST	Wood logs ⁽¹⁾
Bushman Small Commercial Pizza Oven manufactured by Dingley Dell Enterprises Ltd, PO Box 3534, Kidderminster, Worcestershire, DY14 9ZE	Instruction manual dated January 2011, reference: SCOINST	Wood logs ⁽¹⁾
Bushman Small Domestic Pizza Oven manufactured by Dingley Dell Enterprises Ltd, PO Box 3534, Kidderminster, Worcestershire, DY14 9ZE	Instruction manual dated January 2011, reference: SDOINST	Wood logs ⁽¹⁾
Camelot 4 stove manufactured by Hunter Stoves Ltd, Trevilla Park, Slaughterbridge, Camelford, Cornwall, PL32 9TT	Instruction manual dated 24th April 2012, reference: JINCAM04 Rev B. The appliance must be fitted with a permanent stop that prevents closure of the secondary air slider beyond 30% open.	Wood logs ⁽¹⁾
Camelot 5 Compact stove manufactured by Hunter Stoves Ltd, Trevilla Park, Slaughterbridge, Camelford, Cornwall, PL32 9TT	Instruction manual dated 14th June 2012, reference: JINCAC05 Rev B. The appliance must be fitted with a permanent stop that prevents closure of the secondary air slider beyond 30% open.	Wood logs ⁽¹⁾
Camelot 5 slimline stove manufactured by Hunter Stoves Ltd, Trevilla Park, Slaughterbridge, Camelford, Cornwall, PL32 9TT		Wood logs ⁽¹⁾
Camelot 6 stove manufactured by Hunter Stoves Ltd, Trevilla Park, Slaughterbridge, Camelford, Cornwall, PL32 9TT	24th April 2012, reference:	Wood logs ⁽¹⁾

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
Camelot slimline 8 stove manufactured by Hunter Stoves Ltd, Trevilla Park, Slaughterbridge, Camelford, Cornwall, PL32 9TT	Instruction manual dated 27th June 2012, reference: JINCAS08 Rev B	Wood logs ⁽¹⁾
Carillon 16:9 Crystal manufactured by La Nordica Spa, Via Summano 104 M.Precalcino, 36030 Vicenza, Italy	Instruction manual dated 22nd December 2010, reference: 7196755-Rev 09. The appliance must be fitted with a mechanical stop to prevent closure of the secondary air control beyond the 40% open position.	Wood logs ⁽¹⁾
Carillon 4:3 manufactured by La Nordica Spa, Via Summano 104 M.Precalcino, 36030 Vicenza, Italy	Instruction manual dated 22nd December 2010, reference: 7196755-Rev 09. The appliance must be fitted with a mechanical stop to prevent closure of the secondary air control beyond the 40% open position.	Wood logs ⁽¹⁾
Carron 11 kW SE Stove manufactured by JIG UK Ltd, Hurlingham Business Park, Fulbeck Heath, Grantham, Lincolnshire, NG32 3HL	Instruction manual reference: Carron 11 kW Stove model September 2012 (Smoke Exempt). A modification to the secondary air control preventing closure beyond 4 mm open must be implemented.	Wood logs ⁽¹⁾
Carron Dante SE manufactured by Jig UK Limited, Hurlingham Business Park, Fulbeck Heath, Grantham, Lincolnshire NG32 3HL		Wood logs ⁽¹⁾
Carron Stove manufactured by Jig UK Limited, Hurlingham Business Park, Fulbeck Heath, Grantham, Lincolnshire NG32 3HL	Instruction manual dated July 2009, reference: 91-62351	Dry and split wood logs of a maximum length of 23 cm ⁽¹⁾

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
Carron Stove SE manufactured by Jig UK Limited Hurlingham Business Park, Fulbeck Heath, Grantham, Lincolnshire NG32 3HL	Instruction manual dated 12th January 2011, reference: BHC501-506. The appliance must be fitted with a system preventing the closure of the secondary air	Wood logs ⁽¹⁾
CB800 Skagen manufactured by Hunter Stoves Limited, Unit 6, The Old Mill Industrial Estate, Stoke Canon, Exeter, Devon, EX5 4RJ	control openings beyond 3 mm. Instruction manual dated 6th December 2011, reference: JINHCE08 rev E. Instruction manual dated 6th December 2011, reference: JINHCE08SCK rev B. The appliance must be fitted with smoke control area kit JHCE080.	Wood logs ⁽¹⁾
Charnwood C-Eight Wood Burning Stove manufactured by A.J. Wells and Sons Limited, Bishops Way, Newport, Isle of Wight, PO30 5WS	Instruction manual dated September 2012, reference: C- series v2. The appliance must be fitted with a mechanical stop to prevent air control opening closure beyond the 64 mm open position.	Wood logs ⁽¹⁾
Charnwood C-Five Wood Burning Stove manufactured by A.J. Wells and Sons Limited, Bishops Way, Newport, Isle of Wight, PO30 5WS	Instruction manual dated September 2012, reference: C- series v2. The appliance must be fitted with a mechanical stop to prevent air control opening closure beyond the 58 mm open position.	Wood logs ⁽¹⁾
Charnwood C-Four stove manufactured by A.J Wells & Sons Ltd, Bishops Way, Newport, Isle of Wight, PO30 5WS	Instruction manual dated August 2011, reference: CFOUR V1	Wood logs ⁽¹⁾
Charnwood Country 4 wood burning stove manufactured by AJ Wells and Sons, Bishops Way, Newport, Isle of Wight, PO30 5WS	Modification instruction manual dated January 2011, reference: TIS.95.	Wood logs ⁽¹⁾

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditi	ions
	Instruction manual dated January 2011, reference: Country 4 MKII.	
	The appliance must be fitted with the manufacturer's smoke reduction kit when used within a smoke control area to fix the minimum aperture of the secondary air inlets to a minimum of 21 mm open.	
Charnwood Cove 1SR stove manufactured by A.J. Wells and Sons Ltd, Bishops Way, Newport, Isle of Wight, PO30 5WS	Installation and use instruction manual reference: COVE1SR01.10 Issue A. An adjustment of the air control such that the minimum closure of the air control is equivalent to that found with the control pushed in 15 mm from the fully open position must be made.	Wood logs ⁽¹⁾
Charnwood C-Seven Wood Burning Stove manufactured by A.J. Wells and Sons Limited, Bishops Way, Newport, Isle of Wight, PO30 5WS	Instruction manual dated September 2012, reference: C- series v2. The appliance must be fitted with a mechanical stop to prevent air control opening closure beyond 64 mm open position.	Wood logs ⁽¹⁾
Charnwood C-Six stove manufactured by A.J. Wells & Sons Ltd, Bishops Way, Newport, Isle of Wight, PO30 5WS		Wood logs ⁽¹⁾
Charnwood Island 1 stove manufactured by AJ Wells and Sons, Bishops Way, Newport, Isle of Wight, PO30 5WS	Instruction manual dated December 2010, reference: Island I.II.III 12.10 Issue B. The appliance must be fitted with a stop bracket (kit no. 010/ AY83/S) to prevent the airwash	Wood logs ⁽¹⁾

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditi	ons
	flaps at the back of the stove from being closed beyond 2 mm.	
Charnwood Island 2 stove manufactured by AJ Wells and Sons, Bishops Way, Newport, Isle of Wight, PO30 5WS	Instruction manual dated December 2010, reference: Island I.II.III 12.10 Issue B. The appliance must be fitted with a stop bracket (kit no. 010/BY83/S) to prevent the airwash flaps at the back of the stove from being closed beyond 2 mm.	Wood logs ⁽¹⁾
Charnwood Island 3 stove manufactured by AJ Wells and Sons, Bishops Way, Newport, Isle of Wight, PO30 5WS	Instruction manual dated December 2010, reference: Island I.II.III 12.10 Issue B. The appliance must be fitted with a stop bracket (kit no. 010/CY83/S) to prevent the airwash flaps at the back of the stove from being closed beyond 2 mm.	Wood logs ⁽¹⁾
	Instruction manual dated December 2010, reference: Tor and Tor Pico 12.10 Issue B	Wood logs ⁽¹⁾
	Installation and Use Instruction manual reference: Tor 02.10 Issue A	Wood logs ⁽¹⁾
Chesneys 4 Series (4.6 kW) Stoves: Flatford 4, Hampstead 4, Alpine 4 also sold as: Sunbeam 4, Dakota 4, Providence 4. Pacific 4 also sold as: Murano 4, Apollo 4. Chelsea 4 also sold as: Wellington 4, Guernsey 4, Belgravia 4 manufactured by Chesneys,194-200 Battersea Park Road, London, SW11 4ND	manual dated 7th December 2009, reference: CH4K-V4. The appliance must be fitted with a mechanical stop to	Wood logs ⁽¹⁾
Chesneys 6 Series (7 kW) Stoves:	Chesneys 6 series Instruction manual dated 7th December 2009, reference: CH6K-V4.	Wood logs ⁽¹⁾

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditi	ions
Flatford 6, Barrington 6, Petworth 6, Hampstead 6, Alpine 6 also sold as: Sunbeam 6, Dakota 6, Providence 6 and the Chelsea 6 also sold as: Wellington 6, Guernsey 6, Belgravia 6 manufactured by Chesneys, 194-200 Battersea Park Road, London, SW11 4ND	The appliance must be fitted with a mechanical stop to prevent closure of the air control beyond the 10 mm open position	
Clean Air Systems CAS 200, 400 and 600 handfed airheaters manufactured by Inventair Ltd, Lancaster Road, Carnaby Industrial Estate, Bridlington, East Yorkshire, YO15 3QY	To be operated in accordance with the Handbook for CAS hand fired airheater range dated January 2011, reference: 24600H version 1	Softwood, hardwood, medium density fibreboard (MDF) or chipboard offcuts ⁽¹⁾
Clean Air Systems CAS 300 Max airheater and cyclone manufactured by Inventair Ltd, Lancaster Road, Carnaby Industrial Estate, Bridlington, East Yorkshire, YO15 3QY	To be operated in accordance with the Handbook for CAS 300 Max airheater range dated January 2011, reference: 300A version 1	Softwood, hardwood, medium density fibreboard (MDF) or chipboard offcuts ⁽¹⁾
Cleanburn CB900 Inset & Cleanburn CB900 Sønderskoven Inset, Wood burning stoves manufactured by Hunter Stoves Limited, Unit 6, The Old Mill Industrial Estate, Stoke Canon, Exeter, Devon, EX5 4RJ	Instruction manual dated 17th January 2012, reference: JINHCN09 Slider Stop Rev A. Instruction manual dated 24th January 2012, reference: JINHCN09 Rev F. The appliance must be fitted with a mechanical stop to prevent secondary air control closure beyond the 20% open position when sold into smoke control areas.	Wood logs ⁽¹⁾
Cleanburn R4 manufactured by Hunter Stoves Limited, Unit 6, The Old Mill Industrial Estate, Stoke Canon, Exeter, Devon, EX5 4RJ	Instruction manual dated 2nd December 2011, reference: JINCLR04 Rev E. Instruction manual dated 5th December 2011, reference: JINCLR04SCK rev B. The appliance must be fitted with smoke control area kit JCLR0401.	Wood logs ⁽¹⁾

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
Cleanburn R5 inset stove manufactured by Hunter Stoves Ltd, Trevilla Park, Slaughterbridge, Camelford, Cornwall, PL32 9TT	Instruction manual dated 10th December 2012, reference: JINCLR05 Rev B. Instruction manual dated 6th July 2012, reference: JINCLR05SCK rev A. The appliance must be fitted with smoke control area kit JCLR0501.	Wood logs ⁽¹⁾
Cleanburn R6 inset stove manufactured by Hunter Stoves Ltd, Trevilla Park, Slaughterbridge, Camelford, Cornwall, PL32 9TT	Instruction manual dated 10th December 2012, reference: JINCLR06 rev B. Instruction manual dated 6th July 2012, reference: JINCLR05SCK rev A. The appliance must be fitted with smoke control area kit JCLR0501.	Wood logs ⁽¹⁾
Cleanburn Sonderskoven 5 inset stove manufactured by Hunter Stoves Ltd, Trevilla Park, Slaughterbridge, Camelford, Cornwall, PL32 9TT	Instruction manual dated 4th October 2012, reference: JINHCN05 Rev B. The valve plate adjusted by the secondary air control must contain six 5 mm holes.	Wood logs ⁽¹⁾
Clearburn Junior SE stove manufactured by Dean Forge Limited, Dean Prior, Buckfastleigh, Devon. TQ11 0LS	Instruction manual dated March 2012, reference: JRSE Issue 1. The appliance must be fitted with a mechanical stop to prevent secondary air control closure beyond 83 mm open position.	Wood logs ⁽¹⁾
Contura 510, Contura 520T, Contura 550, Contura 550A, Contura 550W, Contura 560T, Contura 560K, Contura 570, Contura 580, Contura 585, Contura 590, Contura T, all manufactured by NIBE AB Box 134, 285 23 Markaryd, Sweden	Installation instruction reference: IAV SE/EX 0726-6 611821 Lighting instruction BAV SE/EX 0717-2 611820. A permanent stop must be in place on the air inlet to prevent closure beyond the 20% open position.	Untreated dry wood with a maximum moisture content of 20%
Contura 580W manufactured by NIBE AB Box 134, 285 23 Markaryd, Sweden	Installation instruction reference: IAV SE/EX 0740-1 511911.	Untreated dry wood with a maximum moisture content of 20%

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
^	A permanent stop must be in place on the air inlet to prevent closure beyond the 20% open position.	
Contura 750 manufactured by Nibe, Box 134, S-285 23 Markaryd. Sweden		Wood logs ⁽¹⁾
	The appliance must be fitted with a mechanical stop to prevent closure beyond the 28% open position	
Contura 750A manufactured by Nibe, Box 134, S-285 23 Markaryd, Sweden	Instruction manual reference: 811064 BAV SE-EX C750/780-1.	Wood logs ⁽¹⁾
	The appliance must be fitted with a mechanical stop to prevent closure beyond the 28% open position.	
Contura 780 manufactured by Nibe, Box 134, S-285 23 Markaryd, Sweden		Wood logs ⁽¹⁾
	The appliance must be fitted with a mechanical stop to prevent closure beyond the 28% open position.	
Contura 810, 820 T, 850, 860 T, and 880 manufactured by Nibe Stoves, Box 134, S-285 23 Markaryd, Sweden		Wood logs ⁽¹⁾
Walkarya, Sweden	Supplementary operating instructions dated June 2011, reference: 811142 BAV GB-2.	
	The appliance must be fitted with a mechanical stop to prevent air control closure beyond the 38% open position.	
Contura i4 Modern and Contura i4 Classic manufactured by Nibe Stoves, Box 134, S-285 23 Markaryd. Sweden	Instruction manual dated 4th July 2011, reference: 811136 BAV C i4 GB-1.	Dry wood logs ⁽¹⁾
	Supplementary operating instructions dated June 2011, reference: 811142 BAV GB-2.	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditi	ons
	The appliance must be fitted with a mechanical stop to prevent closure beyond the 28% open position.	
Cove 2 SR manufactured by A.J.Wells & Sons Ltd of Bishops Way, Newport, Isle of Wight, PO30 5WS	2009, reference: Cove2SR 07.09	Dry and split wood logs of a maximum length of 23 cm ⁽¹⁾
	A permanent stop must be in place on air control to prevent closure beyond 14 mm from the fully closed position.	
Crator JS5500 multi-fuel stove manufactured by James Smellie Limited, Unit N, Leona Industrial Estate, Nimmings Road, Halesowen, West Midlands. B62 9JQ	Instruction manual dated June 2012, reference: Crator multi-fuel stove instruction manual Issue 1	Wood logs ⁽¹⁾
CTC Ecoflex 15 and 20 manufactured by Enertech AB, Box 313, S-341 26 Ljungby, Sweden	1	Wood pellets ⁽¹⁾
D'Alessandro GSA 130 airheater manufactured by D'Alessandro Termomeccanica, Contrada Cerreto, 55, 66010 Miglianico, Chieti, Italy	Instruction manual dated 26th June 2012, reference: 2.0-1- QGSA130XEN0612	Wood chips ⁽¹⁾
D'Alessandro Termomeccanica CS and CSA 130, 180, 230 and 300 manufactured by D'Alessandro Termomeccanica, Contrada Cerreto, 55, 66010 Miglianico, Chieti, Italy	February 2009, reference: Ver. 2.0 - QCSA2000XEN0209 [UK	Wood pellets ⁽¹⁾
D'Alessandro Termomeccanica CS and CSA 400, 500, 650, 800, 950, 1300, 1650 and 2000 kW manufactured by D'Alessandro Termomeccanica, Contrada Cerreto, 55, 66010 Miglianico, Chieti, Italy	Instruction manual dated February 2009, reference: Ver. 2.0 - QCSA2000XEN0209 [UK SMOKE CONTROL]. The optional multi-cyclone must be fitted.	Wood pellets ⁽¹⁾
D'Alessandro Termomeccanica CS and CSA boilers 40, 60, 80 and 100 kW	Instruction manual dated February 2009, reference: Ver.	Wood pellets ⁽¹⁾

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditi	ons
manufactured by D'Alessandro Termomeccanica, Contrada Cerreto, 55, 66010 Miglianico, Chieti, Italy	2.0 - QCSA100XXIT0209 [UK SMOKE CONTROL]	
D'Alessandro Termomeccanica CSI 20 kW manufactured by D'Alessandro Termomeccanica, Contrada Cerreto, 55, 66010 Miglianico, Chieti, Italy	Instruction manual dated February 2009, reference: Ver. 2.0 - QCSI100XXIT0209	Wood pellets ⁽¹⁾
Dartmoor 5 SE stove manufactured by Dean Forge Limited, Dean Prior, Buckfastleigh, Devon. TQ11 0LS		Wood logs ⁽¹⁾
Design 800 Green, Wood Burning Stove, manufactured by Bodart & Gonay Limited, Rue De Lambinon, 3 Harze, Belgium, 4920		Wood logs ⁽¹⁾
Di Lusso R4 manufactured by Hunter Stoves Limited, Unit 6, The Old Mill Industrial Estate, Stoke Canon, Exeter, Devon, EX5 4RJ	Instruction manual dated 2nd December 2011, reference: JINDLU04 Rev E. Instruction manual dated 5th December 2011, reference: JINDLU04SCK rev B. The appliance must be fitted with smoke control area kit JDLU0401.	Wood logs ⁽¹⁾
Di Lusso R5 inset stove manufactured by Hunter Stoves Ltd, Trevilla Park, Slaughterbridge, Camelford, Cornwall, PL32 9TT	Instruction manual dated 10th December 2012, reference: JINDLU05 Rev B. Additional instruction manual dated 6th July 2012, reference: JINDLU05SCK Rev A. The appliance must be fitted with smoke control area kit JDLU0501.	Wood logs ⁽¹⁾

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditi	ions
Di Lusso R6 inset stove manufactured by Hunter Stoves Ltd, Trevilla Park, Slaughterbridge Camelford, Cornwall, PL32 9TT		Wood logs ⁽¹⁾
Dimplex Langbrook 5 kW Clean Burn Stove manufactured by Dimplex GDC Group Limited, Millbrook House, Grange Drive, Hedge End, Southhampton	Issue 3. The appliance must be fitted	Wood logs ⁽¹⁾
Dimplex SE Selborne 5 stove manufactured by ESSE Engineering Ltd, Ouzledale Foundry Long Ing Barnoldswick Lancashire BB18 6BN	Instruction manual dated August 2009, reference: SE Selborne 5 Issue 1. The appliance must be fitted with a mechanical stop to prevent closure beyond the 50% open position.	Wood logs ⁽¹⁾
Dovre 250 (model DV-250) manufactured by Dovre NV, Nijverheidsstraat 18, BE-2381 Weelde, Belgium	The manufacturer's instructions, reference: PM 250 Issue 1. A permanent stop must be in place on the secondary air inlet to prevent closure beyond the 75% open position.	Untreated dry wood
Dovre Vintage 30 (DV-VIN30, DV-VIN30WH, DV-TBVIN30 and DV-TBVIN30WH), Dovre Vintage 35 (DV-VIN35, DV-VIN35WH, DV-TBVIN35 and DV-TBVIN35WH) and Dovre Vintage 50 (DV-VIN50, DV-VIN50WH, DV-TBVIN50 and DV-TBVIN50WH, DV-TBVIN50 and DV-TBVIN50WH) stoves manufactured by Dovre N.V. Nijverheidsstraat 18, B-2381 Weelde, Belgium	Instruction manual dated April 2011, reference: 03.27681.100. Instruction manual dated May 2012, reference: PM813 Issue 1. The appliance must be fitted with a permanent stop preventing closure of the secondary air supply beyond 50%.	Wood logs ⁽¹⁾

The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives
or coatings.

Fireplace	Conditi	ions
Earlswood manufactured by ACR Heat Products Limited, Unit One Weston Works, Weston Lane, Tyseley, Birmingham B11 3RP		Wood logs ⁽¹⁾
Ecco Stove E580 manufactured by Landy Vent UK Limited, Foster House, 2 Redditch Road, Studley, Warwickshire, B80 7AX	Instruction manual dated 12th December 2011, reference: Ecco Stove 580 manual.	Wood logs ⁽¹⁾
Ecco Stove E678 manufactured by Landy Vent UK Ltd, Foster House, 2 Redditch Road, Studley, Warwickshire B80 7AX	Instruction manual dated 28th January 2011, reference: 01/11/3. The appliance must be fitted with a system to fix the secondary air (airwash) to a 4 mm open position.	Wood logs ⁽¹⁾
Ecco Stove E850 manufactured by Landy Vent UK Ltd, Foster House, 2 Redditch Road, Studley, Warwickshire B80 7AX	October 2010, reference: 02/10.	Wood logs ⁽¹⁾
Ecofire Barbara wood pellet stove boiler manufactured by Palazzetti Lelio S.p.A, Via Roveredo 103, Porcia (PN), 33080, Italy	October 2011, reference: cod.	Wood pellets ⁽¹⁾
Ecofire Giulia Idro, Ecofire Kelly Idro Plus and Ecofire Tania Idro wood pellet stove boilers manufactured by Palazzetti Lelio S.p.A, Via Roveredo 103, Porcia (PN), 33080, Italy	February 2011, reference: cod. 004770432.	Wood pellets ⁽¹⁾

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditi	ions
Eco-Ideal Eco 1 Stove manufactured by Hunter Stoves Limited, unit 6, Old Mill Industrial Estate, Stoke Canon, Exeter. Devon EX5 4RJ	Instruction manual dated 20th July 2011, reference: JINECO01 rev C. The appliance must be fitted with a permanent stop that prevents closure of the secondary air slider beyond 30% open.	Dry wood logs ⁽¹⁾
Eco-Ideal Eco 2 Stove manufactured by Hunter Stoves Limited, unit 6, Old Mill Industrial Estate, Stoke Canon, Exeter. Devon EX5 4RJ	Instruction manual dated 20th July 2011, reference: JINECO02 rev C. The appliance must be fitted with a permanent stop that prevents closure of the secondary air slider beyond 30% open.	Dry wood logs ⁽¹⁾
Eco-Ideal Eco 4 Stove manufactured by Hunter Stoves Limited, unit 6, Old Mill Industrial Estate, Stoke Canon, Exeter. Devon EX5 4RJ	Instruction manual dated 20th July 2011, reference: JINECO04 rev C	Dry wood logs ⁽¹⁾
Eco-Ideal Eco 6 Stove manufactured by Hunter Stoves Limited, unit 6, Old Mill Industrial Estate, Stoke Canon, Exeter. Devon EX5 4RJ	Instruction manual dated 20th July 2011, reference: JINECO06 rev C	Dry wood logs ⁽¹⁾
E-Compact 15 wood pellet boiler manufactured by Wood Energy Solutions, Donaskeigh, Tipperary, Co. Tipperary, Ireland	Instruction manual dated May 2012, reference: E-COMPACT 15 Outdoor Pellet Boiler v1.5	6 mm wood pellets ⁽¹⁾
E-Compact 28 Pellet Boiler manufactured by Wood Energy Solutions Limited, Donaskeigh, Tipperary, Co. Tipperary, Ireland	Instruction manual dated July 2012, reference: Installation & Operation Manual V.2.1	6 mm Wood logs ⁽¹⁾
Ecowarm Crystal 6 (also known as Ekol Crystal 8) manufactured by Saltfire Stoves Ltd, Station Works, John's Road, Wareham, BH20 4BG		Wood logs ⁽¹⁾

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditi	ions
Ellipse manufactured by La Nordica Spa, Via Summano 104, M. Precalcino, 36030 Vicenza, Italy		Wood logs ⁽¹⁾
Endress USF-W 1000 manufactured by Endress Holzfeuerungsanlagen GmbH, Industriestraße 18, D-91593 Burgbernheim	Instruction manual entitled "Operating and Maintenance manual Endress USF –W1000" dated March 2010, reference: EMAN – USFW1000	Wood chips and pellets ⁽¹⁾
Endress USF-W 250 manufactured by Endress Holzfeuerungsanlagen GmbH, Industriestraße 18, D-91593 Burgbernheim	Instruction manual entitled "Operating and Maintenance manual Endress USF -W250" dated March 2010, reference: EMAN – USFW250	Wood chips and pellets ⁽¹⁾
Endress USF-W 350 manufactured by Endress Holzfeuerungsanlagen GmbH, Industriestraße 18, D-91593 Burgbernheim	Instruction manual entitled "Operating and Maintenance manual Endress USF –W350" dated March 2010, reference: EMAN – USFW350	Wood chips and pellets ⁽¹⁾
Endress USF-W 500 manufactured by Endress Holzfeuerungsanlagen GmbH, Industriestraße 18, D-91593 Burgbernheim	Instruction manual entitled "Operating and Maintenance manual Endress USF -W500" dated March 2010, reference: EMAN – USFW500	Wood chips and pellets ⁽¹⁾
Endress USF-W 800 manufactured by Endress Holzfeuerungsanlagen GmbH, Industriestraße 18, D-91593 Burgbernheim	"Operating and Maintenance	Wood chips and pellets ⁽¹⁾
Endress VR-S 300 manufactured by Endress Holzfeuerungsanlagen GmbH, Industriestraße 18, D-91593 Burgbernheim	Instruction manual entitled "Operating and Maintenance manual Endress VR-S300" dated March 2010, reference: EMAN – VRS300	Wood chips and pellets ⁽¹⁾
Endress VR-W 400 manufactured by Endress Holzfeuerungsanlagen GmbH, Industriestraße 18, D-91593 Burgbernheim	Instruction manual entitled "Operating and Maintenance manual Endress VR –W400" dated March 2010, reference: EMAN – VRW400	Wood chips and pellets ⁽¹⁾

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
Endress VR-W 600 manufactured by Endress Holzfeuerungsanlagen GmbH, Industriestraße 18, D-91593 Burgbernheim	Instruction manual entitled "Operating and Maintenance manual Endress VR-W600" dated March 2010, reference: EMAN – VRW600	Wood chips and pellets ⁽¹⁾
Endress VR-W 900 manufactured by Endress Holzfeuerungsanlagen GmbH, Industriestraße 18, D-91593 Burgbernheim	Instruction manual entitled "Operating and Maintenance manual Endress VR-W900" dated March 2010, reference: EMAN – VRW900	Wood chips and pellets ⁽¹⁾
EOS 30 346 kW output wood pellet boiler with multicyclone manufactured by: Uniconfort srl, Via dell'Industria 21, 35018, San Martino Di Lupari (PD) Italy	dated July 2011, reference:	Wood pellets ⁽¹⁾
EOS 35 407 kW output wood pellet boiler with multicyclone manufactured by: Uniconfort srl, Via dell'Industria 21, 35018, San Martino Di Lupari (PD) Italy		Wood pellets ⁽¹⁾
EOS 40 464 kW output wood pellet boiler with multicyclone manufactured by: Uniconfort srl, Via dell'Industria 21, 35018, San Martino Di Lupari (PD) Italy	Use and Maintenance manual dated July 2011, reference: Uniconfort EOS40 Manual v1	Wood pellets ⁽¹⁾
EOS 60 700 kW output wood pellet boiler with multicyclone manufactured by Uniconfort sri, Via dell'Industria 21, 35018 San Martino Di Lupari (PD) Italy	Installation Instruction manual dated September 2010, reference: K135-07332 Uniconfort MUN v 2	6 mm diameter wood pellets ⁽¹⁾
Esse 100DD SE 5 kW stove manufactured by Esse Engineering Limited, Ouzedale Foundry, Long Ing, Barnoldswick, BB18 6BN	Instruction manual dated October 2011, reference: 10/11 (PP) INSTR.ST-100DDSE/u. The fitting of a system to prevent closure of the air controls beyond the 50% open position must be implemented.	Wood logs ⁽¹⁾
Esse 125 SE Stove manufactured by ESSE Engineering Ltd, Ouzledale Foundry, Long Ing,	Instruction manual dated August 2009, reference: Esse 125SE Issue 1.	Wood logs ⁽¹⁾

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditi	ions
Barnoldswick, Lancashire, BB18 6BN	The appliance must be fitted with a mechanical stop to prevent closure beyond the 50% open position.	
Esse 1622 inset stove manufactured by Esse Engineering Limited, Long Ing, Barnoldswick Lancashire BB18 6BN	reference: 1622/Integra INSET	Wood logs ⁽¹⁾
Esse 301 SE Stove manufactured by ESSE Engineering Ltd, Ouzledale Foundry, Long Ing, Barnoldswick, Lancashire, BB18 6BN	Instruction manual dated 9th November 2010, reference: v45. The primary air control must not be fully air tight when closed.	Wood logs ⁽¹⁾
Esse 350 SE Stove manufactured by ESSE Engineering Ltd, Ouzledale Foundry, Long Ing, Barnoldswick, Lancashire, BB18 6BN	Instruction manual dated 9th November 2010, reference: v45	Wood logs ⁽¹⁾
ETA HACK 20, 25, 35, 50, 70, 90, 130 and 200 woodchip boilers manufactured by ETA Heiztechnik Gesellschaft mit beschrankter Haftung (GmbH), A 4716, Hofkirchen an der Trattnach, Gewerbepark 1, Austria	Instruction manual dated June 2011, reference: HACK20-200_Bedienung_2011-0 Integrated flue gas recirculation system must be used when using wood chips with a moisture content below 15%.	Wood chips ⁽¹⁾ 16_EN.
ETA HACK 20, 25, 35, 50, 70, 90, 130 and 200 woodchip boilers manufactured by ETA Heiztechnik Gesellschaft mit beschrankter Haftung (GmbH), A 4716, Hofkirchen an der Trattnach, Gewerbepark 1, Austria	Instruction manual dated June 2011, reference: HACK20-200_Bedienung_2011-0 Integrated flue gas recirculation system must be used when burning wood pellets	Wood pellets ⁽¹⁾ 06_EN.
ETA PC 20, 25 and 32 wood pellet boilers manufactured by ETA Heiztechnik Gesellschaft mit beschrankter Haftung (GmbH), A 4716, Hofkirchen	Instruction manual dated June 2011, reference: PC20-32_Bedienung_2011-06_EN	Wood pellets ⁽¹⁾

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditi	ons
an der Trattnach, Gewerbepark 1, Austria		
and 90 wood pellet	Instruction manual dated June 2011, reference: PE-K35-90_Bedienung_2011-06_EN	Wood pellets ⁽¹⁾
ETA PU 7, 11 and 15 wood pellet boilers manufactured by ETA Heiztechnik Gesellschaft mit beschrankter Haftung (GmbH), A 4716, Hofkirchen an der Trattnach, Gewerbepark 1, Austria		Wood pellets ⁽¹⁾
ETA SH 20, 30, 40, 50 and 60 wood gasification boilers manufactured by ETA Heiztechnik Gesellschaft mit beschrankter Haftung (GmbH), A 4716, Hofkirchen an der Trattnach, Gewerbepark 1, Austria	June 2011, reference:	Wood logs ⁽¹⁾
eVolution 26 boiler stove manufactured by Broseley Fires Ltd, Knights Way, Battlefield Ent Park, Shrewsbury, Shropshire, SY1 3AB	Instruction manual dated 9th January 2012, reference: MS10-11c. The appliance must be fitted with a mechanical stop to prevent closure beyond the 40% open position when sold into smoke control areas.	Wood logs ⁽¹⁾
eVolution 4 Inset manufactured by Broseley Fires Limited, Knights Way, Battlefields Enterprise Park, Shrewsbury, Shropshire, SY1 3AB	Instruction manual dated 9th November 2011, reference: eVo 4&7 Inset MS11-11. The appliance must be fitted with a system to prevent closure of the secondary air control beyond the 15 mm open position.	Wood logs ⁽¹⁾
eVolution 5 model number M-EVO5 manufactured by Broseley Fires Limited,	Instruction manual dated 8th July 2011, reference: eVo 5 MS07-11.	Wood logs ⁽¹⁾

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
Knights Way, Battlefield Enterprise Park, Shrewsbury, Shropshire. SY1 3AB	The appliance must be fitted with a system that prevents the closure of the air control to less than 70% open	
eVolution 7 Inset manufactured by Broseley Fires Limited, Knights Way, Battlefields Enterprise Park, Shrewsbury, Shropshire, SY1 3AB	Instruction manual dated 9th November 2011, reference: eVo 4&7 Inset MS11-11. The appliance must be fitted with a system to prevent closure of the secondary air control beyond the 8 mm open position.	Wood logs ⁽¹⁾
Evotherm P50, P100, P120, P150, P170, P200 pellet boilers manufactured by Evotherm, Heiztechnik Vertriebs Gesellschaft mit beschrankter Haftung (GmbH), Seeleiten 24, AT 5120, St Pantaleon, Austria	entitled "Operating manual", reference: Version 1/2010/Rev	Wood pellets ⁽¹⁾
FDC5 Stove manufactured by Charlton & Jenrick Ltd, Unit D Stafford Park 2, Telford, Shropshire. TF3 3AR	Instruction manual dated April 2012, reference: FDC Issue 02. The fitting of a system that prevents closure of the secondary air control slots beyond the 3.5 mm open position must be implemented.	Wood logs ⁽¹⁾
FDC5i inset stove manufactured by Charlton & Jenrick Ltd, Unit D Stafford Park 2, Telford, Shropshire, TF3 3AR.		Wood logs ⁽¹⁾
FDC5iT Taper inset stove manufactured by Charlton & Jenrick Ltd. Unit D Stafford Park 2, Telford, Shropshire. TF3 3AR.	Instruction manual dated April 2012, reference: FDCiT Issue 1. The fitting of a system that prevents closure of the secondary air control slots beyond the 5 mm open position must be implemented.	Wood logs ⁽¹⁾
FDC5iW Wide inset stoves manufactured by Charlton & Jenrick Ltd, Unit D Stafford		Wood logs ⁽¹⁾

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
Park 2, Telford, Shropshire, TF3 3AR.	prevents closure of the secondary air control slots beyond the 9 mm open position must be implemented.	
FDC5W Wide stove manufactured by Charlton & Jenrick Ltd, Unit D Stafford Park 2, Telford, Shropshire. TF3 3AR	2012, reference: FDC Issue 02.	Wood logs ⁽¹⁾
FDC 8 Freestanding Wood Burning Stove manufactured by Charlton & Jenrick Limited, Unit D Stafford Park, 2 Telford, Shropshire TF3 3AR	Instruction manual dated July 2012, reference: FDC issue 03. The appliance must be fitted with a mechanical stop to prevent secondary air control closure beyond the 5 mm open position.	Wood logs ⁽¹⁾
FDC 8i Inset Wood Burning Stove manufactured by Charlton & Jenrick Limited, Unit D Stafford Park, 2 Telford, Shropshire TF3 3AR	Instruction manual dated July 2012, reference: FDCi issue 03. The appliance must be fitted with a mechanical stop to prevent secondary air control closure beyond the 1 mm open position.	Wood logs ⁽¹⁾
Fireball manufactured by La Nordica Spa, Via Summano 104, M. Precalcino 36030, Vicenza, Italy	Instruction manual dated 22nd December 2010, reference: 7196801-Rev 07. The appliance must be fitted with a mechanical stop to prevent closure of the secondary air control beyond the 40% open position.	Wood logs ⁽¹⁾
Firefox 5 Clean Burn II, Gallery Classic 5 Clean Burn, Sirius 405 Clean Burn and Sirius 405 Classic Clean Burn manufactured by Percy Doughty & Co Limited, Imperial Point, Express Trading Estate, Stone Hill Road, Farnworth, Bolton. BL4 9TN	Instruction manual dated June 2011, reference: FF5CBII REV:A. The appliance must be fitted with a mechanical stop to prevent secondary air closure beyond the 50% open position.	Dry wood logs ⁽¹⁾
Firefox 5CB, Vega 100CB, Sirius 405CB and Flame 5CB (4.9 kW) stoves manufactured	Instruction manual dated January 2010, reference: FFXCBA	Wood logs ⁽¹⁾

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
by Percy Doughty & Co, Imperial Point, Express Trading Estate, Stonehill Road, Farnworth, Bolton, BL4 9TN		
Firefox 8 Clean Burn, Gallery Classic 8 Clean Burn, Sirius 545 Clean Burn and Sirius 545 Classic Clean Burn manufactured by Percy Doughty & Co Limited, Imperial Point, Express Trading Estate, Stone Hill Road, Farnworth, Bolton. BL4 9TN	Instruction manual dated June 2011, reference: FF8CB REV:A. The appliance must be fitted with a mechanical stop to prevent secondary air closure beyond the 50% open position.	Dry wood logs ⁽¹⁾
Fireglow Eco 7 manufactured by Saltfire Stoves Ltd, Station Works, John's Road, Wareham, BH20 4BG	Instruction manual dated 24th January 2011, reference: ECO7 operation-Revision 2A	Wood logs ⁽¹⁾
Fireline FGi5 stove manufactured by Charlton & Jenrick Ltd, Unit D Stafford Park 2, Telford, Shropshire, TF3 3AR.	2012, reference: FGi.FPi.FXi	Wood logs ⁽¹⁾
Fireline FGi8, FXi8, & FPi8 Cassette Inset Wood Burning Stoves manufactured by Charlton & Jenrick Limited, Unit D Stafford Park 2, Telford, Shropshire, TF3 3AR	Instruction manual dated July 2012, reference: FGi.FPi.FXi issue 07. The appliance must be fitted with a mechanical stop to prevent secondary air control closure beyond the 1 mm open position.	Wood logs ⁽¹⁾
Fireline FP5, Fireline FX5, Fireline FPi 5 kW and Fireline Fxi 5 kW manufactured by Charlton and Jenrick, Ltd Charlton and Jenrick G1-G2, Halesfield 5, Telford, Shropshire,TF7 4QJ	Instruction manual dated March 2010, reference: Issue 03. The appliance must be fitted with a system that prevents the closure of the secondary air control beyond the 3.5 mm open position.	Wood logs ⁽¹⁾
Fireline FP5W and FX5W Freestanding stove manufactured by Charlton &	Instruction manual dated March 2012, reference: FX.FP.Issue 06.	Wood logs ⁽¹⁾

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions		
Jenrick Ltd, Unit D Stafford Park 2, Telford, Shropshire, TF3 3AR.	The fitting of a system that prevents closure of the secondary air control slots beyond the 7 mm open position must be implemented.		
Fireline Fpi5T, Fgi5T, Fxi5T Taper inset stoves manufactured by Charlton & Jenrick Ltd, Unit D Stafford Park 2, Telford, Shropshire, TF3 3AR	Instruction manual dated March 2012, reference: FxiT.FpiT.FgiT Issue 01. The fitting of a system that prevents closure of the secondary air control slots beyond the 5 mm open position must be implemented.	Wood logs ⁽¹⁾	
Fireline Fpi5W, Fgi5W, Fxi5W Wide inset stoves manufactured by Charlton & Jenrick Ltd, Unit D Stafford Park 2, Telford, Shropshire, TF3 3AR	Instruction manual dated March 2012, reference: Fgi.Fpi.Fxi Issue 06. The fitting of a system that prevents closure of the secondary air control slots beyond the 9 mm open position must be implemented.	Wood logs ⁽¹⁾	
Fireline FX8 & FP8 Freestanding Wood Burning Stoves manufactured by Charlton & Jenrick Limited, Unit D Stafford Park 2, Telford, Schropshire, TF3 3AR	Instruction manual dated September 2012, reference: FX.FP. Issue 08. The appliance must be fitted with a mechanical stop to prevent secondary air control closure beyond the 5 mm open position.	Wood logs ⁽¹⁾	
and 150 manufactured	The manufacturer's instructions dated June 2005, reference: Bedienungsanleitung Firematic V 1.1 ENG doc	Chipped wood, wood pellets or planed wood shavings ⁽¹⁾	
Firematic 45 and 60 manufactured by HERZ Armaturen Ges.m.b.H, Geschäftsbereich HERZ Feuerungstechnik, A-8272 Sebersdorf 138, Austria	,	Wood pellets conforming to ÖNORM M7135 with diameter of 6 mm or wood chips up to a maximum size of 50 mm and maximum water content 35% ⁽¹⁾	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditi	ons
	Instruction manual reference: Operating Instructions Herz firematic 130 – 199 BioControl version Betriebsanleitung firematic 20-201 BioControl Englisch V 3.1	Wood chips and wood pellets ⁽¹⁾
Firenzo Aucklander stove manufactured by Firenzo Woodfires UK Limited, 98 Niven Street, Napier 4142, New Zealand	Instruction manual dated 15th January 2013, reference: AL. Instruction manual dated 1st February 2013, reference: AU. The appliance must be fitted with a mechanical stop to prevent air control slots closure beyond the 6.5 mm open position.	Wood logs ⁽¹⁾
Firenzo Bronte stove manufactured by Firenzo Woodfires UK Limited, 98 Niven Street, Napier 4142, New Zealand	Instruction manual dated 15th January 2013, reference: B1. Instruction manual dated 1st February 2013, reference: BU. The appliance must be fitted with a mechanical stop to prevent air control slots closure beyond the 6.5 mm open position.	Wood logs ⁽¹⁾
Firenzo Contessa stove manufactured by Firenzo Woodfires UK Limited, 98 Niven Street, Napier 4142, New Zealand	Instruction manual dated 15th January 2013, reference: CI. Instruction manual dated 1st February 2013, reference: CU. The appliance must be fitted with a mechanical stop to prevent air control slots closure beyond the 6 mm open position.	Wood logs ⁽¹⁾
Firenzo Lady Kitchener stove manufactured by Firenzo Woodfires UK Limited, 98 Niven Street, Napier 4142, New Zealand	Instruction manual dated 15th January 2013, reference: LKI. Instruction manual dated 1st February 2013, reference: LKU. The appliance must be fitted with a mechanical stop to prevent air control slots closure	Wood logs ⁽¹⁾

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
-	beyond the 6.5 mm open position.	
Firenzo Wellingtonian stove manufactured by Firenzo Woodfires UK Limited, 98 Niven Street, Napier 4142, New Zealand	Instruction manual dated 15th January 2013, reference: WI. Instruction manual dated 1st February 2013, reference: WU. The appliance must be fitted with a mechanical stop to prevent air control slots closure beyond the 6.5 mm open position.	Wood logs ⁽¹⁾
Firestorm 10 SE stove manufactured by The Heat Resistant Glass Company Limited, Unit 2 Bracewell Avenue, Poulton Industrial Estate, Poulton Le Fylde. FY6 8JF	SE Issue (6928) 2.	Wood logs ⁽¹⁾
Firestorm 4.5 SE stove manufactured by The Heat Resistant Glass Company Limited, Unit 2 Bracewell Avenue, Poulton Industrial Estate. Poulton Le Fylde. FY6 8JF	SE Issue (6928) 1.	Wood logs ⁽¹⁾
Firestorm 6.5 SE stove manufactured by The Heat Resistant Glass Company Limited, Unit 2 Bracewell Avenue, Poulton Industrial Estate, Poulton Le Fylde. FY6 8JF	Instruction manual dated 28th April 2012, reference: 6.5 KW SE Issue (6928) 3. The appliance must be fitted with a stop that will only allow a minimum air gap 6 mm between the air control plate and the appliance when the secondary air is turned down to its minimum position.	Wood logs ⁽¹⁾

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditi	ons
Firewarm 06C inset stove manufactured by Heat Design, 30 Hawthorn Road, Western Industrial Estate, Naas Road, Dublin 12, Ireland	Instruction manual dated 26th July 2012, reference: FW06C. A permanent stop to prevent closure of the secondary air control beyond 20% open must be implemented.	Wood logs ⁽¹⁾
Firewarm 11C inset stove manufactured by Heat Design, 30 Hawthorn Road, Western Industrial Estate, Naas Road, Dublin 12, Ireland	Instruction manual dated 26th July 2012, reference: FW11C. A permanent stop to prevent closure of the secondary air control beyond 20% open must be implemented.	Wood logs ⁽¹⁾
Firewarm 4SE stove manufactured by Heat Design, 30 Hawthorn Road, Western Industrial Estate, Naas Road, Dublin 12, Ireland	Instruction manual dated 25th July 2012, reference: FW468SE. The fitting of a system to prevent closure of the secondary air control beyond 5 mm open must be implemented.	Wood logs ⁽¹⁾
Firewarm 6SE stove manufactured by Heat Design, 30 Hawthorn Road, Western Industrial Estate, Naas Road, Dublin 12, Ireland	Instruction manual dated 25th July 2012, reference: FW468SE. The fitting of a system to prevent closure of the secondary air control beyond 75% from closed must be implemented.	Wood logs ⁽¹⁾
Firewarm 8SE stove manufactured by Heat Design, 30 Hawthorn Road, Western Industrial Estate, Naas Road, Dublin 12, Ireland	Instruction manual dated 25th July 2012, reference: FW468SE. The fitting of a system to prevent closure of the secondary air control beyond 25% from closed must be implemented.	Wood logs ⁽¹⁾
	Instruction manual dated 14th March 2012, reference: CH5K – V1. The appliance must be fitted with a mechanical stop to prevent secondary air control closure beyond the 18 mm open position.	Wood logs ⁽¹⁾
Franco Belge Model 134 08 11 Savoy EA 8 kW output wood burning stove; Franco Belge Model 134 08 09 Savoy Mk II Elegance multifuel stove	The Savoy EA Technical, Manual reviewed 9th July 2009, reference: 1290-1	Wood logs ⁽¹⁾

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditi	ions
with KEA 13408 smoke control kit manufactured by Franco Belge, Staub Fonderie SA, Rue Orphée Variscotte, 59660, Merville, France		
Franco Belge Montfort MK2 wood burning stove manufactured by Franco Belge, Staub Fonderie SARL, Rue Orphée Variscotte, 59660, Merville, France	Instruction manual dated 17th November 2009, reference: 1295-3. The appliance must be fitted with a mechanical stop to prevent closure of the secondary air control beyond the 25% open position.	Wood logs ⁽¹⁾
Fröling Lambdamat Commercial wood chip boiler models 500, 750 and 1000 manufactured by Fröling Heizkessel und Behälterbau Gesellschaft mit beschränkter Haftung (GmbH), A-4710 Grieskirchen, Industriestrasse 12, Austria	Manual reference: B 069 01 04 of	Wood chips ⁽¹⁾
Fröling P4 8, 15, 20, 25, 32, 38, 48 and 60 Pellet Boilers manufactured by Fröling Heizkessel und Behälterbau Gesellschaft mit beschränkter Haftung (GmbH), A-4710 Grieskirchen, Industriestrasse 12, Austria	Instruction manual dated July 2009, reference: B0430408_en	Wood pellets with a diameter of 6 mm ⁽¹⁾
Fröling P4 80 and P4 100 wood pellet boilers manufactured by Fröling Heizkessel und Behälterbau Gesellschaft mit beschränkter Haftung (GmbH), A-4710 Grieskirchen, Industriestrasse 12, Austria		Wood pellets ⁽¹⁾
Fröling S4 Turbo 15 15 kW, Fröling S4 Turbo 22 22 kW, Fröling S4 Turbo 28 28 kW, Fröling S4 Turbo 34 34 kW, Fröling S4 Turbo 40 40 kW, Fröling S4 Turbo 50 50 kW, Fröling S4 Turbo 60 60 kW manufactured by Fröling		Wood logs ⁽¹⁾

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
Heizkessel und Behälterbau Gesellschaft mit beschränkter Haftung (GmbH), A-4710 Grieskirchen, Industriestrasse 12, Austria		
Fröling T4 24, 30, 40, 50, 60, 75, 90, 100 and 110 kW boilers manufactured by Fröling Heizkessel und Behälterbau Gesellschaft mit beschränkter Haftung (GmbH), A-4710 Grieskirchen, Industriestrasse 12, Austria	Instruction manual dated May 2012, reference: B071 - Version 05	Wood pellets or wood chips (1)
	The manufacturer's operating instructions dated August 2003, reference: V0310003	Wood pellets or wood chips ⁽¹⁾
Fröling Turbomat 320 and 500 manufactured by Fröling Heizkessel und Behälterbau Gesellschaft mit beschränkter Haftung (GmbH), A-4710 Grieskirchen, Industriestrasse 12, Austria		Wood pellets or wood chips ⁽¹⁾
Fröling Turbomatic 28, 35, 48 and 55 manufactured by Fröling Heizkessel und Behälterbau Gesellschaft mit beschränkter Haftung (GmbH), A-4710 Grieskirchen, Industriestrasse 12, Austria	The manufacturer's installation manual dated November 2003, reference: M 060 01 03 The manufacturer's operating manual dated August 2002, reference: 99229a	Wood chip less than 35% moisture content and meeting ÖNORM M 7133: 1998 size class G30 ⁽¹⁾ Wood pellets of 6 mm diameter and a moisture content below 10% ⁽¹⁾
Fröling Turbomatic 85, 100 and 110 manufactured by Fröling Heizkessel und Behälterbau Gesellschaft mit beschränkter Haftung (GmbH), A-4710 Grieskirchen, Industriestrasse 12, Austria	The manufacturer's instruction manual dated November 2003, reference: M 060 01 03. The manufacturer's operating manual dated August 2002, reference: 99229a.	Wood chip less than 35% moisture content and meeting ÖNORM M 7133: 1998 of either size class G30 or G50 ⁽¹⁾ Wood pellets of 6 mm diameter and a moisture content below 10% ⁽¹⁾
Fröling TX 200 199 kW and TX 250 250 kW boilers with Exhaust Gas Recirculation device manufactured by Fröling	2012, reference: B067 – Version	Wood chips or wood pellets ⁽¹⁾

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions		
Heizkessel und Behälterbau Gesellschaft mit beschränkter Haftung (GmbH), A-4710 Grieskirchen, Industriestrasse 12, Austria			
Fröling TX150 150 kW boiler with Exhaust Gas Recirculation device manufactured by Fröling Heizkessel und Behälterbau Gesellschaft mit beschränkter Haftung (GmbH), A-4710 Grieskirchen, Industriestrasse 12, Austria	Installation instruction manual dated September 2010, reference: M1130009. Operating instruction manual dated September 2010, reference: B 067 00 09.	Wood chips with a maximum moisture content of 30% and a maximum cross sectional area of 5 cm ² or wood pellets with a minimum moisture content of 10% and a maximum diameter of 10 mm ⁽¹⁾	
Future Fires Panoramic FX1 manufactured by Gen-Fab Limited, Swinton Bridge Industrial Estate, Whitelee Road, Swinton, S64 8BH	Instruction manual dated 31st October 2012, reference: PANFXREV2	Wood logs ⁽¹⁾	
Gilles HPK UTSK 150 kW, 180 kW, 240 kW and 300 kW boilers manufactured by Gilles Energie und Umwelttechnik GmbH, Koaserbauer Str. 16, A-4810, Gmunden, Austria	Operating instructions dated January 2007, reference: Gilles/150–300/1	Wood pellets or wood, chips ⁽¹⁾	
Gilles HPK UTSK 360 kW, Boiler manufactured by Gilles Energie und umwelttechnik GmbH, Koaserbauer Str. 16, A-4810 Gmunden, Austria	Operating instructions dated January 2008, reference: Gilles/360/1	Wood pellets or wood, chips	
Gilles HPKI-K 180, 195, 240, 300, 360, 450, 550, 700, 900, 995, 1200 and 1600 boilers. manufactured by Gilles, Energie und Umwelttechnik, Gmbh, Koaserbauer Str. 16A-4810, Gmunden, Austria	Operating instructions dated November 2008, reference: Operating Instruction HPKI-K, Underfeed Stoking. 1-general HPKI-K underfeed stoking	Wood pellets or wood chips ⁽¹⁾	
Gilles HPK-RA 13 kW, 15 kW, 20 kW, 25 kW, 30 kW, 35 kW, 40 kW, 45 kW, 49 kW, 60 kW, 70 kW, 75 kW, 85 kW, 95 kW, 100 kW, 120 kW and 145 kW manufactured by GILLES Energie- und Umwelttechnik GmbH, Koaserbauer Str. 16 A-4810 Gmunden, Austria	Operating instructions dated January 2007, reference: Gilles/0–145/1	Wood pellets or wood chips ⁽¹⁾	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditi	ons
Gilles HPK-RA 160 manufactured by Gilles Energie – und Umwelttechnik Gmbh, Koaserbauer Str.	Instruction and operation manuals dated November 2008, references:	Wood chips and pellets ⁽¹⁾
16A-4810 Gmunden, Austria	BD 200-01a-01;	
START	BD 200-01a-02;	
	BD 200-01a-03;	
	BD 200-01a-04;	
	BD 200-01a-06;	
	BD 200-03a-07; and	
	BD 200-03a-09	
Gilles UTSK 1200 kW, 1600 kW boilers manufactured by GILLES Energie- und Umwelttechnik GmbH, Koaserbauer Str. 16 A-4810 Gmunden, Austria	Operating instructions dated January 2008, reference: Gilles/360/1	Wood pellets or wood chips ⁽¹⁾
Gilles UTSK 450 kW, 550 kW boilers manufactured by GILLES Energieund Umwelttechnik GmbH, Koaserbauer Str. 16 A-4810 Gmunden, Austria	Operating instructions dated January 2008, reference: Gilles/360/1	Wood pellets or wood chips(1)
Gilles UTSK 700 kW, 900 kW boilers manufactured by GILLES Energie-und Umwelttechnik GmbH, Koaserbauer Str. 16 A-4810 Gmunden, Austria	Operating instructions dated January 2008, reference: Gilles/360/1	Wood pellets or wood chips ⁽¹⁾
1	Instruction manual dated April 2012, reference: IRL NO.012 Rev; 1	6 mm wood pellets ⁽¹⁾
Boiler manufactured by Trianco Limited, Thorncliffe,	Instruction manual dated July 2012, reference: Installation & Operation Manual V.2.1	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditi	ions
Chapletown, Sheffield, S35 2PH		
Guntamatic Biocom and Powercorn 100 manufactured by GUNTAMATIC Heiztechnik GmbH A – 4722 PEUERBACH, Bruck 7, Austria		Wood pellets with a diameter of 6 mm and a length of between 10 and 30 mm or wood chip less than 35% moisture content and meeting ÖNORM M 7133: 1998 size class G30 ⁽¹⁾
Guntamatic Biocom and Powercorn 50 and 75 manufactured by GUNTAMATIC Heiztechnik GmbH A – 4722 PEUERBACH, Bruck 7, Austria	Instruction manual dated 29th July 2009, reference: GUN/BIO/ OP/V1/0709	Wood pellets with a diameter of 6 mm and a length of between 10 and 30 mm ⁽¹⁾
Guntamatic Powerchip 100 manufactured by GUNTAMATIC Heiztechnik GmbH A – 4722 PEUERBACH, Bruck 7, Austria	-	Wood pellets with a diameter of 6 mm and a length of between 10 and 30 mm or wood chip less than 35% moisture content and meeting ÖNORM M 7133: 1998 size class G30 ⁽¹⁾
Guntamatic Powerchip 50 and 75 manufactured by GUNTAMATIC Heiztechnik GmbH A – 4722 PEUERBACH, Bruck 7, Austria	Instruction manual dated 29th July 2009, reference: GUN/POW/ OP/V1/0709	Wood pellets with a diameter of 6 mm and a length of between 10 and 30 mm ⁽¹⁾
Hamont CATfire 350 USZI pellet boiler fitted with CATfirte 300 cyclone manufactured by Hamont Contracting and Trading, spol. s.r.o., Sedlište 227, postal code 739 36, district Frydek-Mistek Czech Republic	"Operating Manual for Boilers	Wood pellets with a 6 mm diameter and a maximum length of 30 mm ⁽¹⁾
Hampstead 8, Hampstead LS 8, Hampstead XLS 8, Belgravia 8, Barrington 8, Petworth 8 and Flatford 8 stoves manufactured by Chesneys Limited, 194-200 Battersea Park Road, London, SW11 4ND	Instruction manual dated 31st October 2011, reference: CH8K - V12. The appliance must be fitted with a system that prevents closure of the air controls further than 40 mm from open.	Wood logs ⁽¹⁾

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditi	ions
Handöl 31, Handöl 31A, Handöl 32, Handöl 32A, Handöl 33T, Handöl 34T, Handöl 35T, Varde Ovne Look 1, Varde Ovne Look 2, Varde Ovne Look 3, all manufactured by NIBE AB Box 134, 285 23 Markaryd, Sweden	Installation instructions, reference: IAV SE/EX 0811-4 511941 Lighting instructions BAV SE/EX H30 511942. A permanent stop must be in place on the air inlet to prevent closure beyond the 45% open position.	Untreated dry wood with a maximum moisture content of 20%
Handöl 50, Handöl 51, Handöl 52, Handöl 52T, Handöl 53, Handöl 54, Handöl 54T, Handöl 51L, Varde Ovne S1, Varde Ovne S2, Varde Ovne S3, all manufactured by NIBE AB Box 134 285 23 Markaryd, Sweden	Installation instructions, reference: IAV SE/EX 0737-4 511866 Lighting instruction BAV SE/EX 0717-1 511865. A permanent stop must be in place on the air inlet to prevent closure beyond the 45% open position.	Untreated dry wood with a maximum moisture content of 20%
Harrie Leenders Cylon Harrie Leenders Doran 160	Instruction manual, reference: Supplementary Instructions Amended June 2010.	Wood logs ⁽¹⁾
Harrie Leenders Doran 190 Harrie Leenders Fuga S Harrie Leenders Fuga eL Harrie Leenders Stor Harrie Leenders Signa Stoves manufactured by Harrie Leenders Industrieweg 255688 DP Oirschot Netherlands	The appliance must be fitted with a mechanical stop to prevent closure of the air slide beyond the 15 mm open position	
HDG Compact model 100 (100 kW) wood chip and pellet boiler manufactured by HDG Bavaria Gesellschaft mit beschrankter Haftung (GmbH), Siemensstrasse 22, 84323 Massing, Germany	The manufacturer's operating instructions for the HDG Compact 100/150/200 dated July 2008, reference: HDG Compact 100-200 Version V1	Wood chip or wood pellets ⁽¹⁾
with model HDG 3113 cyclone manufactured by	The manufacturer's operating instructions for the HDG Compact 100/150/200 dated July 2008, reference: HDG Compact 100-200 Version V1	Wood chip or wood pellets ⁽¹⁾

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditi	ons
HDG Bavaria Gesellschaft mit beschrankter Haftung (GmbH), Siemensstrasse 22, 84323 Massing, Germany		
HDG Compact model 80 (80 kW) wood chip and pellet boiler manufactured by HDG Bavaria Gesellschaft mit beschrankter Haftung (GmbH), Siemensstrasse 22, 84323 Massing, Germany	Compact 80 with HDG Hydronic	Wood chip or wood pellets ⁽¹⁾
HDG Compact models 25/35 (25 kW, 35 kW) wood chip and pellet boilers manufactured by HDG Bavaria Gesellschaft mit beschrankter Haftung (GmbH), Siemensstrasse 22, 84323 Massing, Germany	The manufacturer's operating instructions for the HDG Compact 25/35 with HDG Hydronic dated April 2009, reference: HDG Compact Version V01	Wood chip or wood pellets ⁽¹⁾
HDG Compact models 50/65 (50 kW, 65 kW) wood chip and pellet boilers manufactured by HDG Bavaria Gesellschaft mit beschrankter Haftung (GmbH), Siemensstrasse 22, 84323 Massing, Germany	The manufacturer's operating instructions for the HDG Compact 50/65 with HDG Hydronic dated April 2009, reference: HDG Compact Version V03	Wood chip or wood pellets ⁽¹⁾
HDG Euro models 30, 40 and 50 (30 kW, 40 kW and 50 kW) wood log boilers manufactured by HDG Bavaria Gesellschaft mit beschrankter Haftung (GmbH), Siemensstrasse 22, 84323 Massing, Germany	The manufacturer's operating instructions for the HDG Euro 30/40/50 with Lambda Control 1 dated June 2008, reference: HDG Euro V3.0 with HDG Lambda Control 1 Version V1	Split wood logs of 500 mm length and maximum edge length of 120 mm and a residual moisture content of 20% ⁽¹⁾
wood log boilers manufactured by HDG Bavaria Gesellschaft	instructions for the HDG Navora 20/25/30 with Lambda Control 1 dated June 2008, reference: HDG Navora 20/25/30 with HDG	Split wood logs of 500 mm length and maximum edge length of 120 mm and a residual moisture content of 20% ⁽¹⁾
PM15, 15 kW wood pellet boiler manufactured by HDG	Pelletmaster 15/25 dated October 2006, reference: HDG	Wood pellets ⁽¹⁾

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
Heat Design of Dublin TR8 Curved Freestanding Wood Burning Stove manufactured by Charlton & Jenrick Limited, Unit D Stafford Park, 2 Telford, Shropshire, TF3 3AR	Instruction manual dated January 2013, reference: HD TR Freestanding .Issue 01. The appliance must be fitted with a mechanical stop to prevent secondary air control closure beyond the 5 mm open position.	Wood logs ⁽¹⁾
Heat Design of Dublin TR8c Cassette Inset Wood Burning Stove manufactured by Charlton & Jenrick Limited, Unit D Stafford Park, 2 Telford, Shropshire, TF3 3AR	Instruction manual dated July 2012, reference: TRc issue 03. The appliance must be fitted with a mechanical stop to prevent secondary air control closure beyond the 1 mm open position.	Wood logs ⁽¹⁾
Heat Design TR5c inset stove manufactured by Charlton & Jenrick Ltd, Unit D Stafford Park 2, Telford, Shropshire. TF3 3AR	Instruction manual dated April 2012, reference: TRc Issue 02. The fitting of a system that prevents closure of the secondary air control slots beyond the 3.5 mm open position must be implemented.	Wood logs ⁽¹⁾
Heat Design TR5iT Taper inset stove manufactured by Charlton & Jenrick Ltd, Unit D Stafford Park 2, Telford, Shropshire. TF3 3AR	Instruction manual dated April 2012, reference: TRiT Issue 01. The fitting of a system that prevents closure of the secondary air control slots beyond the 5 mm open position must be implemented.	Wood logs ⁽¹⁾
Heat Design TR6c Wide inset stove manufactured by Charlton & Jenrick Ltd, Unit D Stafford Park 2, Telford, Shropshire. TF3 3AR	Instruction manual dated April 2012, reference: TRc Issue 02. The fitting of a system that prevents closure of the secondary air control slots beyond the 9 mm open position must be implemented	Wood logs ⁽¹⁾
Henley Achill Wood Burning Stove manufactured by Henley Stoves Limited, Ard Ri Marble Curraheen Tralee, Co. Kerry, Ireland	Instruction manual dated November 2012, reference: Version 1. The appliance must be fitted with a mechanical stop to	Wood logs ⁽¹⁾

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	prevent closure of the secondary air control slots beyond the 50% open position.	
Herz BioFire BF 1000 manufactured by Herz Engietechnik GmbH. Herstraße 1, 7423 Pinkafeld Österreich/ Austria	Instruction manual entitled "Operating instructions HERZ BioFire 500 – 1000 Biocontrol", reference "Betriebsanleitung Biofire 500-1000 Biocontrol Englisch V1.2.doc"	Wood chips and pellets ⁽¹⁾
Herz BioFire BF 500 manufactured by Herz Engietechnik GmbH. Herstraße 1, 7423 Pinkafeld Österreich/ Austria	Instruction manual entitled "Operating instructions HERZ BioFire 500 – 1000 Biocontrol", reference "Betriebsanleitung Biofire 500-1000 Biocontrol Englisch V1.2.doc"	Wood chips and pellets ⁽¹⁾
Herz BioFire BF 600 manufactured by Herz Engietechnik GmbH. Herstraße 1, 7423 Pinkafeld Österreich/ Austria	Instruction manual entitled "Operating instructions HERZ BioFire 500 – 1000 Biocontrol", reference "Betriebsanleitung Biofire 500-1000 Biocontrol Englisch V1.2.doc"	Wood chips and pellets ⁽¹⁾
Herz BioFire BF 800 manufactured by Herz Engietechnik GmbH. Herstraße 1, 7423 Pinkafeld Österreich/ Austria		Wood chips and pellets ⁽¹⁾
Herz Firematic FM 100 manufactured by Herz Engietechnik GmbH. Herstraße 1, 7423 Pinkafeld Österreich/Austria	instructions entitled "HERZ firematic 20 – 101 BioControl", reference: 04.001. Installation instructions entitled "Herz Firematic (1Ph) 20-101". Operating instructions entitled "HERZ firematic 20 - 101 BioControl", reference: Betriebsanleitung firematic 20-101 BioControl Englisch V	Wood chips and pellets ⁽¹⁾
Herz Firematic FM 80	2.53.doc.	W 11' 11' (f)
Herz Firematic FM 80 manufactured by Herz Engietechnik GmbH. Herstraße 1, 7423 Pinkafeld Österreich/ Austria	Assembly and installation instructions entitled	Wood chips and pellets ⁽¹⁾

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditi	ons
•	"HERZ firematic 20 - 101 BioControl", reference: 04.001.	
	Installation Instructions "Herz Firematic (1Ph) 20-101".	
	Operating instructions entitled	
	"HERZ firematic 20 - 101 BioControl", reference: Betriebsanleitung firematic 20-101 BioControl Englisch V 2.53.doc	
Heta Scanline 500D, 510D, 520D and 530D wood burning stoves distributed in the UK by Pevex Enterprises Limited,	Instruction manual dated June 2011, reference: Pevex1005/AH/ver2.	Dry wood logs ⁽¹⁾
Unit 16 Seven Acres Business Park, Newbourne Road, Waldringfield Nr Woodbridge. IP12 4PS	The appliance must be fitted with permanent stops to ensure that the primary and secondary air controls do not close beyond 95% and 50% respectively.	
Heta Scanline 7D, 7AD, 7BD, 7CD and 7DD wood burning stoves distributed in the UK by Pevex Enterprises	Instruction manual dated June 2011, reference: Pevex1006/AH/ver2.	Dry wood logs ⁽¹⁾
Limited, Unit 16 Seven Acres Business Park, Newbourne Road, Waldringfield, Nr Woodbridge. IP12 4PS	The appliance must be fitted with permanent stops to ensure that the primary and secondary air controls do not close beyond 95% and 50% respectively	
0		Wood logs ⁽¹⁾
Highlander 7 Enviroburn Solo multi-fuel stove (product codes 00325, 00326 and 00327) manufactured by Dunsley Heat Limited, Bridge Mills,	Installation and operating instructions manual dated 15th June 2012, reference: ENVIRO 7 DB001.	Dry wood logs ⁽¹⁾
Huddersfield road, Holmfirth, Huddersfield. HD9 3TW	The appliance must be fitted with a mechanical stop to prevent closure of the secondary air-wash beyond 2 mm. Four fixed 5 mm diameter air holes	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	must be provided for the tertiary air supply.	
Horse Flame Little Artemis model number HF277- SE Wood Burning Stove manufactured by Hi-Flame Fireplace UK Limited, Unit 5A Holmes Chapel Business Park, Manor Lane, Holmes Chapel. Cheshire. CW4 8AF	Instruction manual dated July 2012, reference: AL905-SE/UK-NI-ROI/V2-D.18-07-12. The appliance must be fitted with a mechanical stop to prevent closure of the secondary air control beyond the 3 mm open position.	Wood logs ⁽¹⁾
Horse Flame Precision 1 model number HF905-SE. UK Distribution Hi-Flame Limited, Unit 7B Holmes Chapel Business Park Manor Lane Holmes Chapel Cheshire CW4 8AF	Instruction manual dated June 2011, reference: HF905/UK-NI-ROI/V2.1-06-11. The appliance must be fitted with a mechanical stop to prevent closure of the main air control beyond the 50% open position.	Wood logs ⁽¹⁾
Horse Flame Precision II model number HF907-SE wood burning stove manufactured by Hi-Flame Fireplace UK Limited, Unit 5A Holmes Chapel Business Park, Manor Lane, Holmes Chapel, Cheshire. CW4 8AF.	Instruction manual dated July 2012, reference: HF907-SE/UK-NI-ROI/V3-D. 14-07-12. The appliance must be fitted with a mechanical stop to prevent secondary air control closure beyond the 20% open position, and a 70 mm opening of the door rope seal to allow a constant flow of air.	Wood logs ⁽¹⁾
Hothouse 06C inset stove manufactured by Heat Design, 30 Hawthorn Road, Western Industrial Estate, Naas Road, Dublin, 12, Ireland	Instruction manual dated 26th July 2012, reference: HH06C. A permanent stop to prevent closure of the secondary air control beyond 20% open must be implemented.	Wood logs ⁽¹⁾
Hothouse 11C inset stove manufactured by Heat Design, 30 Hawthorn Road, Western Industrial Estate, Naas Road, Dublin 12, Ireland	July 2012, reference: HH11C.	Wood logs ⁽¹⁾

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditi	ions
Hothouse 4SE stove manufactured by Heat Design, 30 Hawthorn Road, Western Industrial Estate, Naas Road, Dublin 12, Ireland	Instruction manual dated 25th July 2012, reference: HH468SE. The fitting of a system to prevent closure of the secondary air control beyond 5 mm open must be implemented.	Wood logs ⁽¹⁾
Hothouse 6SE stove manufactured by Heat Design, 30 Hawthorn Road, Western Industrial Estate, Naas Road, Dublin 12, Ireland	Instruction manual dated 25th July 2012, reference: HH468SE. The fitting of a system to prevent closure of the secondary air control beyond 75% from closed must be implemented.	Wood logs ⁽¹⁾
Hothouse 8SE stove manufactured by Heat Design, 30 Hawthorn Road, Western Industrial Estate, Naas Road, Dublin 12, Ireland	Instruction manual dated 25th July 2012, reference: HH468SE. The fitting of a system to prevent closure of the secondary air control beyond 25% from closed must be implemented.	Wood logs ⁽¹⁾
Hotpod Limited Edition manufactured by Hotpod LLP, PO Box 137, St Ives Cornwall TR26 2WW	Instruction manual dated June 2011, reference: Version 3	Wood logs ⁽¹⁾
Hotpod Unlimited manufactured by Hotpod LLP, PO Box 137, St Ives Cornwall TR26 2WW	Instruction manual dated June 2011, reference: Version 3	Wood logs ⁽¹⁾
Hoval BioLyt 160 pellet boiler manufactured by Hoval Limited, Hoval Limited,Northgate, Newark, Nottinghamshire NG24 1JN	Operating instructions, wood pellet heating boiler BioLyt (50, 70, 120, 140, 160). Instruction manual dated 3rd October 2009, reference:	Wood pellets ⁽¹⁾
	Technical information Assembly instructions	
Hoval BioLyt 50 and 70 manufactured by Hoval AG, Austrasse 70, 9490 Vaduz, Liechtenstein	Installation and operating manuals dated June 2007, references:	Wood pellets ⁽¹⁾
	4 204 794/01; and 4 204 793/2	
Havel Forester MCS 150, 190		Wood pollets or wood aline
Hoval Forester MGS 150, 180, 240, 300, 360, 450, 550, 700, 900 boilers manufactured		following CEN/TS 14961 ⁽¹⁾

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
by Schmid AG, Wood firing systems PO Box 42, CH-8380 Eschikon Switzerland.	MGS_MMXXXv1 (where XXX is the unit size, e.g. 150)	
Hoval Forester UFS 180, 240, 300, 360, 450, 550, 700, 900, 1200, 1600 manufactured by Schmid AG, Wood firing Systems PO Box 42, CH-8360 Eschlikon, Switzerland	Instruction manual dated November 2009, reference: Forester UFS	Wood pellets or wood chips ⁽¹⁾ following CEN/TS 14961
Hoval STU 150, 200, 250, 300, 350, 425 and 500 manufactured by Hoval Limited, Hoval Limited, Northgate, Newark, Nottinghamshire, NG24 1JN	Installation and operation manual dated November 2007, reference: STU man/01; or Installation and operation manual dated June 2008, reference: STU/man/01/1	Wood pellets ⁽¹⁾
Hoval STU 600, 800 and 1000 manufactured by Hoval Limited, Hoval Limited,Northgate, Newark, Nottinghamshire. NG24 1JN		Wood pellets ⁽¹⁾
Hunter Avalon 5 Inset stove manufactured by Hunter Stoves Ltd, Trevilla Park, Slaughterbridge, Camelford, Cornwall, PL32 9TT	Instruction manual dated 10th October 2012, reference: JINAVI05 Rev B. The valve plate adjusted by the secondary air control must contain six 5 mm holes.	Wood logs ⁽¹⁾
Hunter Herald 4 manufactured by Hunter Stoves Limited, Unit 6, Old Mill Industrial Estate, Stoke Canon, Devon, EX5 4RJ	Instruction manual dated 22nd September 2011, reference: JINHH04 rev C. Instruction manual dated 22nd July 2011, reference: JINHH04&HHC05 Slider Stop rev A. The appliance must be fitted with a permanent stop that prevents closure of the secondary air slider beyond 30% open.	Wood logs ⁽¹⁾

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditi	ons
Hunter Herald 5 Compact manufactured by Hunter Stoves Limited, Unit 6, Old Mill Industrial Estate, Stoke Canon, Devon, EX5 4RJ	Instruction manual dated 22nd September 2011, reference: JINHHC05 rev C. Instruction manual dated 22nd July 2011, reference JINHH04&HHC05 Slider Stop rev A. The appliance must be fitted with a permanent stop that prevents closure of the secondary air slider beyond 30% open.	Wood logs ⁽¹⁾
Hunter Herald 5 Slimline manufactured by Hunter Stoves Limited, Unit 6, Old Mill Industrial Estate, Stoke Canon, Devon, EX5 4RJ	Instruction manual dated 22nd September 2011, reference: JINHHW05 rev C	Wood logs ⁽¹⁾
Hunter Herald 6 manufactured by Hunter Stoves Limited, Unit 6, Old Mill Industrial Estate, Stoke Canon, Devon, EX5 4RJ	Instruction manual dated 22nd September 2011, reference: JINHHW04 rev C	Wood logs ⁽¹⁾
Hunter Herald 8 slimline CE vII stove manufactured by Hunter Stoves Ltd, Trevilla Park, Slaughterbridge, Camelford, Cornwall, PL32 9TT	Instruction manual dated 24th January 2013, reference: JINHHW08 rev B	Wood logs ⁽¹⁾
Hunter Herald i4 manufactured by Hunter Stoves Limited, Unit 6, The Old Mill Industrial Estate, Stoke Canon, Exeter, Devon, EX5 4RJ		Wood logs ⁽¹⁾
Hunter Telford 5 Inset stove manufactured by Hunter Stoves Ltd, Trevilla Park, Slaughterbridge, Camelford, Cornwall, PL32 9TT	Instruction manual dated 10th October 2012, reference: JINTDI05 Rev B. The valve plate adjusted by the secondary air control must contain six 5 mm holes.	Wood logs ⁽¹⁾

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
Huntingdon 25 clear door (model number 7057) and Huntingdon 25 tracery door (model number 7058) manufactured by Stovax Limited, Falcon Road, Sowton Industrial Estate, Exeter, Devon, EX2 7LF	manual reference: PM 249 Issue 1. A permanent stop must be in	Untreated dry wood
Insert 100 Crystal manufactured by La Nordica Spa, Via Summany 104 M. Precalcino 36030, Vicenza, Italy		Wood logs ⁽¹⁾
Insert 50 Crystal manufactured by La Nordica Spa, Via Summany 104 M. Precalcino 36030, Vicenza, Italy	December 2010, reference:	Wood logs ⁽¹⁾
Insert 70 Crystal manufactured by La Nordica Spa, Via Summany 104 M. Precalcino 36030, Vicenza, Italy	Instruction manual dated 22nd December 2010, reference: 6096801-Rev. 17. A mechanical stop to prevent closure of the secondary air control beyond the 40% open position must be fitted.	Wood logs ⁽¹⁾
Insert 80 Crystal manufactured by La Nordica Spa, Via Summany 104 M. Precalcino 36030, Vicenza, Italy	Instruction manual dated 22nd December 2010, reference: 6096801-Rev. 17. A mechanical stop to prevent closure of the secondary air control beyond the 40% open position must be fitted	Wood logs ⁽¹⁾
Instyle 400 and 550 stoves manufactured by Dik Geurts Haardkachels BV, Industrieweg Oost 11, 6662 NE Elst (Gld), The Netherlands	Instruction manual reference: Instruction_manual_Instyle_1209	Wood logs ⁽¹⁾ ENG
Italy Built In manufactured by La Nordica Spa, Via Summany 104 M. Precalcino 36030, Vicenza, Italy	Instruction manual dated 13th December 2010, reference: 7095401 Rev. 02	Wood logs ⁽¹⁾

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditi	ons
Italy Termo DSA manufactured by La Nordica Spa, Via Summany 104 M. Precalcino 36030, Vicenza, Italy		Wood logs ⁽¹⁾
Ivanhoe JS5000 multi-fuel stove manufactured by James Smellie Limited, Unit N, Leona Industrial Estate, Nimmings Road, Halesowen, West Midlands. B62 9JQ		Wood logs ⁽¹⁾
Jetmaster 18f stove manufactured by Jetmaster Fires Limited, Unit 2, Peacock Trading Estate, Goodwood Road, Eastleigh, Hampshire SO50 4NT	2011, reference: 106870/18f/60f/	Dry wood logs ⁽¹⁾
Jotul F100 manufactured by Jotul UK Ltd, Unit 1, The IO Centre, Nash Road, Park Farm, Redditch, Worcestershire, B98 7AS	Instruction manual dated September 2002, reference: 129980 Smoke control area modification dated 2010, reference: UK F100 SC appendix. The appliance must be fitted with a permanent stop that prevents the closure of the secondary air control beyond the 50% open position.	Wood logs ⁽¹⁾
Jotul F162, F163, F262 and F263 stoves manufactured by Jotul UK Limited, 1 The IO Centre, Nash Road, Redditch, B98 7AS	Instruction manual dated January 2011, reference: Jotul F162/F162C/F163 Manual Version Po6. Supplementary instruction manual dated 1st January 2012, reference: Jotul F162/F163/262/263 SMOKE. The appliance must be fitted with a mechanical stop to prevent secondary air control closure beyond the 20% open position.	Wood logs ⁽¹⁾
Jydepejsen Country 510 and 760 5 kW stoves manufactured by	Instruction user manual entitled "Country001" dated June 2011,	Wood logs ⁽¹⁾

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditi	ons
Jydepejsen A/S, Ahornsvinget 3-7, Nr.Felding, DK-7500, Holstebro, Denmark	reference: Jydepejsen A/S - June 2011. A permanent stop must be fitted to the secondary air control such that it cannot be closed less than 35%.	
KARA KW990 woodchip boiler manufactured by KARA Energy Systems B.V. P.O. Box 570. 7600 AN Almelo. Plesmanweg 27, 7602 PD Almelo. The Netherlands		Woodchip ⁽¹⁾
KÖB Pyromat-DYN (KPM-DYN) Models 45, 65 and 85 manufactured by Viessmann Ltd, Hortonwood 30,Telford, Shropshire, TF1 7YP	Instruction manual dated 1st January 2005, reference: ID 103689-L English Instruction manual reference: ID: 103708-G English	Wood logs (up to 0.5m) and off cuts of natural timber, wood chips and pellets ⁽¹⁾
KÖB Pyromat-ECO (KPM-ECO) Models 35, 45, 55, 65, 75, 85,manufactured by Viessmann Ltd, Hortonwood 30,Telford, Shropshire, TF1 7YP	January 2005, reference:	Wood logs (up to 0.5m) and off cuts of natural timber ⁽¹⁾
KÖB Pyromat-ECO (KPM-ECO) Models 61, 81, 101 and 151 manufactured by Viessmann Ltd, Hortonwood 30,Telford, Shropshire, TF1 7YP	January 2005, reference:	Wood logs (up to 1.0m) and off cuts of natural timber ⁽¹⁾
KÖB Pyrot (KRT) Models 100, 150, 220, 300, 400 and 540 manufactured by Viessmann Ltd, Hortonwood 30, Telford, Shropshire, TF1 7YP	Instruction manuals dated 1st January 2005, reference: ID 104654-H English Instruction manual reference: ID: 106811-H English	Wood chips or pellets ⁽¹⁾
KÖB Pyrtec (KPT) Models 390, 530, 720, 950 and 1250 and manufactured by Viessmann Ltd, Hortonwood 30,Telford, Shropshire, TF1 7YP	Instruction manual dated 1st January 2005, reference: ID 104661-F English	Wood chips or pellets ⁽¹⁾

The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives
or coatings.

Fireplace	Conditions	
	Instruction manual reference: ID: 105174-F English The appliance must be fitted with multicyclone dedusters.	
Kooga Cleanburn Stove manufactured by Percy Doughty & Co, Imperial Point, Express Trading Estate, Stone Hill Road, Farnworth, Bolton, BL4 9TN	-	Wood logs ⁽¹⁾
KOZ550, 639 kW output pellet boiler manufactured by Kaylioglu Kasabasi (Izmir- Istanbul Yolu Uzeri) P.K 23 Akhisar/Manisa Turkey	Only when used with a Glosfume model BMF 208 ceramic particulate filter. The Green energy engineering Ltd (GEE) KOZ550 pellet boiler owner/operator's manual dated December 2010, reference: version 1A 2010. The Glosfume Ltd maintenance and instruction manual for Glosfume BMF Biomass Filter units (50 – 100 kW) dated December 2010, reference: version AEE001-VER 4	6 mm diameter wood pellets ⁽¹⁾
KP12, KP22 and KP62 wood pellet boilers manufactured by PONAST spol. s r.o. Na Potůčkách 163, 757 01 Valašské Meziříčí, Czech Republic	2012, reference: QPP051-2. Instructions for operation manual	Wood pellets ⁽¹⁾
KWB Easyfire EF2 S/GS/V 8, 12, 15, 22, 25, 30 and 35 wood pellet boilers manufactured by KWB - Kraft und Wärme aus Biomasse Gesellschaft mit beschränkter Haftung, A-8321 St. Margarethen/Raab, Industriestraβe 235, Austria	Operation manual dated May 2011, reference: B KWB Easyfire EN, 05.2011. Installation manual dated May 2011, reference: M KWB Easyfire, 05.2011	Wood pellets ⁽¹⁾
KWB Multifire 15, 25, 30, 40, 50, 60, 80, 99 and 100 woodpellet and wood-chip fired boilers manufactured by Kraft und Wärme aus Biomasse Gesellschaft mit Beschränkter	The fireplace(s) must be installed, maintained and operated in accordance with the manufacturer's instructions dated August 2003, reference: BA-USV 0803.	Wood chips and wood pellets ⁽¹⁾

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
Haftung, Industriestrasse 235 8321 St. Margarethen/Raab, Austria, 8321		
KWB Multifire USV 49.5 kW Wood chip and wood pellet boiler manufactured by Kraft und Wärme aus Biomasse Gesellschaft mit Beschränkter Haftung, Industriestrasse 235 8321 St. Margarethen/Raab, Austria, 8321	Instruction manual dated June 2010, reference: BA Multifire 06.2010	Wood chips and wood pellets ⁽¹⁾
KWB TDS Powerfire 130, 240 and 300 manufactured by KWB – Kraft und Wärme aus Biomasse Gesellschaft mit beschränkter Haftung (GmbH) of Industriestrasse 235, A-8321 St. Margarethen an der Raab, Austria	The manufacturer's instructions dated 14th May 2008, reference: BA TDS-05.2008, including specification of recommended fuels	Wood pellets or wood chips ⁽¹⁾
KWB TDS Powerfire 150 manufactured by KWB – Kraft und Wärme aus Biomasse Gesellschaft mit beschränkter Haftung (GmbH) of Industriestrasse 235, A-8321 St. Margarethen an der Raab, Austria	The manufacturer's instructions dated August 2005, reference: BA TDS-0805	Wood pellets or wood chips ⁽¹⁾
Lin-ka H1500 Hot Water Boiler fitted with either a monocyclone (type LIN-KA 2000) or a multi-cyclone (type LIN-KA 3x2) manufactured by LIN-KA Maskinfabrik A/S, Nylandsvej 38 DK-6940 Lem St. Denmark	Instruction manual dated 27th January 2010, reference: LIN-KA H 1500 Hot Water Manual/Ver. 2005/Rev. 1.10	Wood pellets of maximum diameter 8 mm ⁽¹⁾
Little Wenlock Classic SE Wood Fuel Stove manufactured by Aga, Station Road, Ketley, Telford, Shropshire, TF1 5AQ	Operating instructions dated 19th December 2008, reference: N00471AXX Rev 001 DP081219	Dry and split wood logs of a maximum length of 25 cm and a maximum diameter of 10 cm ⁽¹⁾
LogFire LF6cT Wood Burning Stove manufactured by LogFire Stoves Limited, Britannia House, Junction Street, Darwen, Lancashire, BB3 2RB	Instruction manual dated 18th December 2012, reference: LF6cT-1. The appliance must be fitted with a mechanical stop to prevent closure of the air control	Wood logs ⁽¹⁾

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditi	ions
	slots beyond the 21 mm open position.	
Lotus H370 Petite 6.6 kW insert stove manufactured by Lotus Heating Systems A/S, Agertoften 6 Denmark, 5550	Fireplace insert, Lotus H370 Petite Version 1.	Wood logs ⁽¹⁾
	A mechanical stop to prevent closure of the air damper beyond the 5 mm open position must be implemented.	
Lotus Liva 1, Liva 2, Liva 3 and Liva 4G Stoves manufactured by Lotus Heating Systems A/S, Agertoften 6, 5550 Langeskov, Denmark	Instruction manual dated January 2010, reference: Mounting and User Instructions Lotus-Liva series Stoves Version 4	Wood logs ⁽¹⁾
Lotus Sola, Sola S, Sola M and Sola MST Stoves manufactured by Lotus Heating Systems A/S Agertoften 6, 5550 Langeskov, Denmark	Instruction manual dated January 2010, reference: Mounting and User Instructions Lotus-Sola series Stoves Version 2	Wood logs ⁽¹⁾
Loxton 3 stoves manufactured by Mendip Stoves Limited, Unit H1, Mendip Industrial Estate, Mendip Road, Rooksbridge, Somerset, BS26 2UG	2012, reference: Mendip Stoves Ltd, 2012, ver 3.	Wood logs ⁽¹⁾
and Sqabox Uno stoves	Instruction manual dated July 2012, reference: Mendip Stoves Ltd, 2012, ver 3. A permanent stop such that the secondary air "closed position" results in a 2.5 mm gap in the two secondary air openings must be implemented.	Wood logs ⁽¹⁾
Loxton 6, Loxton 8, Churchill 6, Churchill 8 and Sqabox Duo stoves manufactured by Mendip Stoves Limited, Unit H1, Mendip Industrial Estate, Mendip Road, Rooksbridge, Somerset, BS26 2UG	Instruction manual dated July 2012, reference: Mendip Stoves Ltd, 2012, ver 3. A permanent stop on the secondary air control such that it cannot be closed more than 35% open must be implemented.	Wood logs ⁽¹⁾

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
Ludlow Wood Burning Smoke Exempt Stove (Ludlow Stove SE) manufactured by Aga Station Road, Ketley Telford Shropshire. TF1 5AQ	13th July 2011, reference:	Dry wood logs ⁽¹⁾
Marvic Multifuel Cassette (inset) roomheater. manufactured by Wanders Fires & Stoves, Amtweg 4, Netterden, NL-7077 AL, Netherlands	INK.00.7927.	Wood logs ⁽¹⁾
MEG 4.5 (also known as the Sirius 450) manufactured by Meg Stoves, FE Robinson (Hooton) Ltd, Station Works, Hooton Road, Hooton South Wirral CH66 7NF	Instruction manual dated 28th January 2011, reference: Meg Solid Fuel Stoves manual (107)	Wood logs ⁽¹⁾
Meg 5.0 stove and Sirius 600 inset stove manufactured by F.E Robinson (Hooton) Ltd, Station Works, Hooton Road, Hooton, South Wirral. CH66 7NF	Instruction manual dated 27th July 2012, reference: Manual Version 1.3. The appliance must be fitted with a mechanical stop to prevent secondary air control closure beyond the 10 mm open position.	Wood logs ⁽¹⁾
MEG 7.5 (also known as the Sirius 750) manufactured by Meg Stoves, FE Robinson (Hooton) Ltd, Station Works, Hooton Road, Hooton South Wirral CH66 7NF		Wood logs ⁽¹⁾
	Instruction manual dated January 2012, reference: 700273 Iss. 2 Rev. 1	Wood logs ⁽¹⁾
1 2	Instruction manual dated January 2012, reference: 700275 Iss. 2 Rev. 1	Wood logs ⁽¹⁾

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
Engineering Limited, Unit 7, Newton Chambers Way, Thorncliffe Industrial Estate, Chapeltown, Sheffield. S35 2PH		
PB35, and Mescoli PB28 manufactured by MESCOLI CALDAIE S.rl. Caldaie		Wood pellets ⁽¹⁾ following ÖNORM M7 135 or DIN plus (DIN 51731)
Micromet MEG 4.5 stove (also known as the Sirius 450) manufactured by Micromet 125 Bridge St Birkenhead Merseyside CH41 1BD	Instruction manual dated 16th June 2010, reference: Micromet Solid Fuel Stoves Manual (24)	Dry wood logs ⁽¹⁾
Micromet MEG 7.5 stove (also known as the Sirius 750) manufactured by Micromet 125 Bridge St Birkenhead Merseyside CH41 1BD	· · · · · · · · · · · · · · · · · · ·	Dry wood logs ⁽¹⁾
Milan Series 4 manufactured by Chesney's Ltd, 194-200 Battersea Park Road, London SW11 4ND	November 2010, reference:	Wood logs ⁽¹⁾
Milan Series 6 manufactured by Chesney's Ltd, 194-200 Battersea Park Road, London SW11 4ND	November 2010, reference:	Wood logs ⁽¹⁾
Monaco multifuel Stove, Staub Fonderie-Franco Belge model 1340605 manufactured by Staub Fonderie-Franco Belge, Rue Orphee Variscotte, BP73 59660 Merville, France	Instruction manual dated 4th May 2010, reference: 1303 -1. The appliance must be fitted with a mechanical stop to prevent closure of the secondary air control beyond 4 mm from closed.	Wood logs ⁽¹⁾

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
Mondo 1, Mondo 2 and Mondo petite stoves manufactured by Lotus Heating Systems A/S, Agertoften 6, 5550, Langeskov, Denmark	Instruction manual dated 15th October 2012, reference: Lotus-Mondo Series Stoves Version 1. A mechanical stop to prevent closure of the air dampers beyond the 8 mm open position must be implemented.	Wood logs ⁽¹⁾
Monterrey 6 , York Midi Serrano 5 manufactured by Broseley Fires Ltd, Knights Way, Battlefield Enterprise Park, Shrewsbury, Shropshire, SY1 3AB	Instruction manual dated January 2010, reference: 09TJD. The appliance must be fitted with a system that prevents the closure of the secondary air flaps to less than 8 mm open position.	Wood logs ⁽¹⁾
Morsø 1416, 1418, 1446 and 1448 4 kW stoves manufactured by Morsø UK Limited, Unit 7 The io Centre, Valley Drive, Swift Valley, Rugby, CV21 1TW	Instruction manual dated 31st January 2012, reference: Morsø 1416, 1418, 1446 & 1448. Instruction for Installation and use. Part No: 72150000.	Wood logs ⁽¹⁾
Morsø Model 7600 including Model 7642, 7644 and 7648 stoves manufactured by Morsø Limited, UK distribution by Morsø UK limited, Unit 7, The io Centre, Valley Drive, Swift Valley, CV21 1TW	Instructions for installation and use 7600 dated 14th July 2010, reference: 72762200. The air control on UK models has been altered such that this equates to an increased minimum open position. Reference drawings Morsø 7600-137, 7600-138, 7600-139, 7600-140 and 7600-141.	Wood logs with a maximum moisture content of 20% ⁽¹⁾
manufactured by Morsø UK	S10. Instruction for Installation	Wood logs ⁽¹⁾
Morsø S10-70 5 kW stove manufactured by Morsø UK Limited, Unit 7 The io Centre, Valley Drive, Swift Valley, Rugby, CV21 1TW	Instruction manual dated 31st January 2012, reference: Morsø S10-70. Instruction for Installation and use. Part No: 72103000.	Wood logs ⁽¹⁾
Morsø S11-40, S11-42, S11-43 and S11-90 4 kW stove manufactured by Morsø UK Limited, Unit 7 The io Centre,	Instruction manual dated 31st January 2012, reference: Morsø S11 serien. Instruction for Installation and use Part No: 72114200.	Wood logs ⁽¹⁾

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
Valley Drive, Swift Valley, Rugby, CV21 1TW		
Morsø S81-90 4 kW stove manufactured by Morsø UK Limited, Unit 7 The io Centre, Valley Drive, Swift Valley, Rugby, CV21 1TW	30th January 2012, reference:	Wood logs ⁽¹⁾
MORSØ-Ø4 manufactured by MORSØ Limited, Unit 7- io centre Valley Drive, Swift Valley, Rugby, Warwickshire, CV21 1TW		Wood logs ⁽¹⁾
1	Instruction manual dated 4th July 2012, reference: MB49/IM/ ISSUE 001	Wood pellets or olive kernels ⁽¹⁾
Nestor Martin "Harmony" H13 multifuel stove (5 kW) manufactured by Nestor Martin S.A., 11 Rue De Lion, B-5660, Frasnes Les Couvin, Belgium	Euroheat Distributors (HBS) Limited's operation instructions dated June 2010, reference: IN1116 Edition D5. The minimum air bleed flap must be set at a minimum of 14.5 mm.	Untreated dry wood
Nestor Martin "Harmony" H23 (6 kW) and H33 (8 kW) multifuel stoves manufactured by Nestor Martin S.A., 11 Rue De Lion, B-5660, Frasnes Les Couvin, Belgium	Limited's operation instructions dated June 2010, reference:	Untreated dry wood
Nestor Martin "Stanford" S13 multifuel stove (3.5 kW) manufactured by Nestor Martin S.A., 11 Rue De Lion, B-5660, Frasnes Les Couvin, Belgium.	Euroheat Distributors (HBS) Limited's operation instructions dated June 2010, reference: IN1116 Edition D5. The minimum air bleed flap must be set at a minimum of 14.5 mm	Untreated dry wood
Nestor Martin "Stanford" S23 (6 kW), SP23 (6 kW), S33 (8 kW) and SP33 (8 kW) multifuel stoves manufactured by Nestor	Euroheat Distributors (HBS) Limited's operation instructions dated June 2010, reference: IN1116 Edition D5.	Untreated dry wood

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
Martin S.A., 11 Rue De Lion, B-5660, Frasnes Les Couvin, Belgium.		
Nestor Martin C23 multifuel stove (7.7 kW) manufactured by Nestor Martin S.A., 11 Rue De Lion, B-5660, Frasnes Les Couvin, Belgium.	Euroheat Distributors (HBS) Limited's operation instructions dated June 2010, reference: IN1213 Edition B	Untreated dry wood
Nestor Martin C33 multifuel stove (9.2 kW) manufactured by Nestor Martin S.A., 11 Rue De Lion, B-5660, Frasnes Les Couvin, Belgium.	Limited's operation instructions	Untreated dry wood
Nestor Martin D33 multifuel stove (8 kW) manufactured by Nestor Martin S.A., 11 Rue De Lion, B-5660, Frasnes Les Couvin, Belgium.	Limited's operation instructions	Untreated dry wood
Nestor Martin IN13 Insert multifuel stove (5 kW) manufactured by Nestor Martin S.A., 11 Rue De Lion, B-5660, Frasnes Les Couvin, Belgium.	Euroheat Distributors (HBS) Limited's operation instructions dated June 2010, reference: IN1214 Edition B. The minimum air bleed flap must be set at a minimum of 14.5 mm	Untreated dry wood
Nestor Martin IT13 multifuel stove (3.5 kW) manufactured by Nestor Martin S.A., 11 Rue De Lion, B-5660, Frasnes Les Couvin, Belgium.	Euroheat Distributors (HBS) Limited's operation instructions dated June 2010, reference: IN1180 Edition D1. The minimum air bleed flap must be set at a minimum of 14.5 mm.	Untreated dry wood
Nestor Martin R33 (8 kW) multifuel stove manufactured by Nestor Martin S.A., 11 Rue De Lion, B-5660, Frasnes Les Couvin, Belgium.	Euroheat Distributors (HBS) Limited's operation instructions dated January 2007, reference: IN1116 Edition D	Untreated dry wood
Newark EGTL05 manufactured by Elite Group Trading Limited, Room 1208 Kak Tak, Commercial Building 317-319 Des Voeux Road,Central Hong Kong 999077	Instruction manual dated 5th July 2011, reference: EGTL05 Version 1.4. The appliance must be fitted with a permanent stop to prevent	Wood logs ⁽¹⁾

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditi	ions
	any closure of the tertiary air control.	
Newbourne 40 and Newbourne 50 Freestanding stoves manufactured by Pevex Enterprises Ltd Unit 16, Steven Acres, Waldringfield Suffolk IP2 4PS	Instruction manual dated January 2013, reference: Pevex 1012/AH/ver1. A permanent stop must be implemented ensuring a minimum opening area of 1 cm ² for the primary air slider when in the fully closed position and a tertiary air inlet area of 4 cm ² .	Wood logs ⁽¹⁾
Newbourne 40 inset stove manufactured by Pevex Enterprises Ltd, Unit 16, Seven Acres, Waldringfield, Suffolk, IP12 4PS	Instruction manual dated January 2013, reference: Pevex1015/AH/ver1. The appliance must be fitted with permanent stops that ensure the secondary and tertiary air controls do not close beyond 1.1 cm open and 2 cm open positions respectively.	Wood logs ⁽¹⁾
	Instruction manual dated January 2012, reference: 700504 Iss. 2 Rev 1	Wood logs ⁽¹⁾
	Instruction manual dated January 2012, reference: 700506 Iss. 3 Rev. 2	Wood logs ⁽¹⁾
Nordic 350 stove manufactured by C DE A Ingenieria Ltda, Jose Miguel Carrera 6, Colina, Santiago, 9361294, Chile.	Instruction manual dated 20th July 2012, reference: 1001	Wood logs ⁽¹⁾
Nørreskoven MkII manufactured for Hunter Stoves Ltd, Unit 6, Old Mill	Instruction manual dated January 2011, reference: Cleanburn, Nørreskoven MkII multifuel	Wood logs ⁽¹⁾

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditi	ons
Industrial Estate, Stoke Canon, Devon EX5 4RJ	stove installation and operating instructions, v01.11.	
	The appliance must be fitted with stop to prevent closure of secondary air control beyond 40%.	
Norvik 5 manufactured by Elite Group Trading Limited, Room 1208 Kak Tak, Commercial Building 317-319 Des Voeux Road,Central Hong Kong 999077	Instruction manual dated 12th September 2011, reference: EGTL05A Version 1.5. The appliance must be fitted with a permanent stop to prevent any closure of the tertiary air	Wood logs ⁽¹⁾
Octoplus 10 and Octoplus 15 Boiler manufactured by Solarfocus, Werkstrasse 1 4451 St. Ulrich, Steyr, Austria	Installation instructions dated 19th April 2010, reference: version 1.1. Operating manual dated 10th May 2010, reference: version 10.051.	Wood logs ⁽¹⁾
ÖkoFEN Pellematic PE08, PE12, PE16, PE20, PE25, PE32, PEK12, PEK16, PEK20, PEK25, PES12, PES16, PES20, PES25, PES32, PESK12, PESK16, PESK20, PESK25 and PESK32 manufactured by ÖkoFEN Forschungs- und Entwicklungs Ges.m.b.H of Gewerbepark 1, 4133 Niederkappel, Austria	ÖkoFEN operation instructions dated February 2007, reference: PE/HB/001.E	Wood pellets of maximum diameter 6 mm and maximum length 4 cm ⁽¹⁾
ÖkoFEN Pellematic PE36, PE48, PE56, PESK36, PESK48, PESK56, PEK36, PEK48, PEK56, PES36, PES48 and PES56 manufactured by ÖkoFEN Forschungs- und Entwicklungs Ges.m.b.H of Gewerbepark 1, 4133 Niederkappel, Austria	ÖkoFEN operation instructions reference: PBV 2000 CMP 1.4 (V2.31) and with revision dated March 2008	diameter 6 mm and maximum
Olymberyl Baby Gabriel model number HF217-SE. UK Distribution by Hi-Flame Limited, Unit 7B Holmes Chapel Business Park Manor	Instruction manual dated June 2011, reference: HF217-SE/UK-NI-ROI/V2.16-06-11.	Wood logs ⁽¹⁾

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditi	ons
Lane Holmes Chapel Cheshire CW4 8AF	The appliance must be fitted with a mechanical stop to prevent closure of the secondary air control beyond the 3 mm open position.	
Optifire 800 Green, Infire 800 Green, Wood Burning Stoves, manufactured by Bodart & Gonay Limited, Rue De Lambinon, 3 Harze, Belgium, 4920	November 2011, reference:	Wood logs ⁽¹⁾
Oregon EGTL03 manufactured by Elite Group Trading Limited, Room 1208 Kak Tak Commercial Building 317-319 Des Voeux Road, Central Hong Kong 999077		Wood logs ⁽¹⁾
kW boiler manufactured by	January 2012, reference: manual	Wood pellets ⁽¹⁾
Osby Parca PB2 3000 kW boiler manufactured by Enertech AB, Osby Parca Division, PO Box 93, SE-283 22 Osby, Sweden	manual, PB2 boiler, dated January 2012, reference: manual	Wood pellets, wood chips, wood briquettes ⁽¹⁾
1		Wood logs ⁽¹⁾
Parkray Caprice 5 inset stove manufactured by Hunter Stoves Ltd, Trevilla Park, Slaughterbridge, Camelford, Cornwall, PL32 9TT	Instruction manual dated 10th December 2012, reference: JINCAP05 Rev B. Instruction manual dated 6th July 2012, reference: JINCAP05SCK rev A	Wood logs ⁽¹⁾

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditi	ions
	The appliance must be fitted with smoke control area kit JCAP0501.	
Parkray Caprice 6 inset stove manufactured by Hunter Stoves Ltd, Trevilla Park, Slaughterbridge, Camelford, Cornwall, PL32 9TT		Wood logs ⁽¹⁾
Parkray Chevin 5 inset stove manufactured by Hunter Stoves Limited, Trevilla Park, Slaughterbridge, Camelford, Cornwall, PL32 9TT		Wood logs ⁽¹⁾
Parkray Consort 5 Compact manufactured by Hunter Stoves Limited, Unit 6, Old Mill Industrial Estate, Stoke Canon, Devon, EX5 4RJ	Instruction manual dated 22nd September 2011, reference: JINCNC05 rev C. Instruction manual dated 22nd July 2011, reference: JINCND05&CNC05 Slider Stop rev A. The appliance must be fitted with a permanent stop that prevents closure of the secondary air slider beyond 30% open.	Wood logs ⁽¹⁾
Parkray Consort 5 manufactured by Hunter Stoves Limited, Unit 6, Old Mill Industrial Estate, Stoke Canon, Devon, EX5 4RJ	Instruction manual dated 22nd September 2011, reference: JINCND05 rev C. Instruction manual dated 22nd July 2011, reference: JINCND05&CNC05 Slider Stop revA. The appliance must be fitted with a permanent stop that prevents closure of the	Wood logs ⁽¹⁾

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditi	ons
	secondary air slider beyond 30% open.	
Parkray Consort 5 Slimline manufactured by Hunter Stoves Limited, Unit 6, Old Mill Industrial Estate, Stoke Canon, Devon, EX5 4RJ	Instruction manual dated 22nd September 2011, reference: JINHHW05 rev C	Wood logs ⁽¹⁾
Parkray Consort 7 manufactured by Hunter Stoves Limited, Unit 6, Old Mill Industrial Estate, Stoke Canon, Devon, EX5 4RJ	Instruction manual dated 22nd September 2011, reference: JNCS07 rev C	Wood logs ⁽¹⁾
Parkray Consort slimline 9 manufactured by Hunter Stoves Ltd, Trevilla Park, Slaughterbridge, Camelford, Cornwall, PL32 9TT		Wood logs ⁽¹⁾
PCE 50 500 kW wood chip boiler manufactured by Groupe Compte. R, Zl de Vaureil, F – 63220 Arlanc, France	Instruction manual dated 29th January 2013, reference: PCE50 rev00	Wood chips ⁽¹⁾
PCE 70 700 kW wood chip boiler manufactured by Group Compte. R, Zl de Vaureil, F – 63220 Arlane, France	Instruction manual dated 29th January 2013, reference: PCE70 rev00	Wood chips ⁽¹⁾
PCE 90 900 kW wood chip boiler manufactured by Groupe Compte. R, Zl de Vaureil, F – 63220 Arlane, France	Instruction manual dated 29th January 2013, reference: PCE90 rev00	Wood chips ⁽¹⁾
PCE 120 1200 kW wood chip boiler manufactured by Groupe Comte. R, Zl de Vaureil, F – 63220 Arlanc, France		Wood chips ⁽¹⁾
PCE 150 1500 kW boiler manufactured by Groupe Compte. R, Zl de Vaureil, F – 63220 Arlanc, France	Instruction manual dated 29th January 2013, reference: PCE150 rev00	Wood chips ⁽¹⁾
Pelle 5 kW stove, Vidar Small 5 kW stove and Vidar Medium 7.6 kW stove manufactured by Dik Geurts Haardkachels BV, Industrieweg Oost 11, 6662 NE Elst (Gld), The Netherlands	Instruction manual dated July 2011, reference: 8900009004	Dry wood logs ⁽¹⁾

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditi	ons
Pelletstar 10, 20, 30, 45 and 60 manufactured by HERZ Armaturen Ges.m.b.H, Geschäftsbereich HERZ Feuerungstechnik, A-8272 Sebersdorf 138, Austria	1 0	Wood pellets corresponding to ÖNORM M7135 of 6 mm diameter ⁽¹⁾
PelletTop 15 and PelletTop 25 Boiler manufactured by Solarfocus, Werkstrasse 1 4451 St.Ulrich, Steyr, Austria	Installation instructions dated 2nd September 2005, reference: version 020905. Operating manual dated 27th September 2006, reference: version 270906.	Wood pellets ⁽¹⁾
Pevex 60 convector stove manufactured by Pevex Enterprises Ltd, Unit 16, Seven Acres, Waldringfield, Suffolk, IP12 4PS	Instruction manual dated January 2013, reference: Pevex1016/AH/ver1. A permanent stop fitted to the secondary air supply that does not allow the slider to be shut off completely and remains open by 40% of its full travel whilst the tertiary air remains open by 100% must be implemented.	Wood logs ⁽¹⁾
Pevex Bohemia X 30, X 40, X40 Cube, X 50 and X 60 multi-fuel stoves manufactured by Pevex Enterprises Limited, Unit 16 Seven Acres Business Park, Newbourne Road, Waldringfield Nr Woodbridge, IP12 4PS	Instruction manual dated July 2010, reference: AH/Ver3	Dry wood logs ⁽¹⁾
	Instruction manual dated June 2011, reference: Pevex1004/AH/ver2/. The appliance must be fitted with permanent stops that ensure the primary and tertiary air controls do not close beyond 0.5 cm open and 2 cm open positions respectively.	Dry wood logs ⁽¹⁾
Pevex Serenity 40D inset multi- fuel appliance manufactured by Pevex Enterprises Limited, Unit 16 Seven Acres Business	Instruction manual dated June 2011, reference: Pevex1003/AH/ver2.	Dry wood logs ⁽¹⁾

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
Park, Newbourne Road, Waldringfield, Nr Woodbridge, IP12 4PS	The appliance must be fitted with permanent stops that ensure the secondary and tertiary air controls do not close beyond 1.1 cm open and 2 cm open positions respectively.	
Portway 1 Stove manufactured by BFM Europe Limited, Trentham Lakes, Stoke on Trent, Staffordshire, ST4 4TJ	Instruction manual reference: Solid Fuel Stoves Manual issued - 20/08/2009 (291) 2. The appliance must be used with a modification to the secondary air slide which inhibits closure further than the 25 mm from the left position.	Wood logs ⁽¹⁾
Portway 2 and 3 Stoves manufactured by BFM Europe Limited, Trentham Lakes, Stoke on Trent, Staffordshire, ST4 4TJ	Instruction manual reference: Solid Fuel Stoves Manual issued - 20/08/2009 (291) 2. The appliance must be used with a modification to the secondary air slide which inhibits closure further than the 20 mm from the left position.	Wood logs ⁽¹⁾
Portway Inset Stove manufactured by BFM Europe Limited, Trentham Lakes, Stoke on Trent, Staffordshire, ST4 4TJ	Instruction manual reference: Solid Fuel Stoves Manual issued - 20/08/2009 (291) 2. A modification of the secondary air control must be implemented such that the 20 mm from left position is maintained during use. In addition the primary air control must be modified such that the minimum setting allows a bleed of air to pass through	Wood logs ⁽¹⁾
Pyroclassic IV manufactured by Pyroclassic Fires Limited, PO Box 28150, Havelock North 4157, Hawke Bay, New Zealand	Instruction manual dated August 2011, reference: PYROS 04	Wood logs ⁽¹⁾
PZ 65 RL and PZ 100 RL pellet boilers manufactured by Biotech Energietechnik GmbH, Furtmühlstrasse 32, A-5101 Bergheim bei Salzburg	Instruction manual entitled "Assembly instruction — Instruction manual — servicing & cleaning PZ65RL/PZ100RL/PZ101RL" dated July 2012, reference: BTMoBeWe ENG	Wood pellets (1)

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	Instruction manual dated December 2009, reference: USER MANUAL Rais 2:1 Revision 2. Part number 9106510.	Wood logs ⁽¹⁾
manufactured by Rais A/	Instruction manual dated 2010, reference: USER MANUAL Rais 700 Revision 0	Wood logs ⁽¹⁾
95 and Rais Poleo 106	USER MANUAL Rais Poleo	Wood logs ⁽¹⁾
RAIS Q-Tee 57 manufactured by Rais A/S Industrivej 20, 9900, Frederikshavn, Denmark	Instruction manual dated 28th June 2011, reference: Manual for RAIS Q-Tee Revision 1.	Dry wood logs ⁽¹⁾
	Supplementary instructions dated 7th July 2011, reference: Rais Q-Tee.	
	The appliance must be fitted with a mechanical stop to prevent air control closure beyond the 11.7 mm open position.	
RAIS Q-Tee 65 manufactured by Rais A/S Industrivej 20, 9900, Frederikshavn, Denmark	Instruction manual dated 28th June 2011, reference: Manual for RAIS Q-Tee Revision 1.	Dry wood logs ⁽¹⁾
	Supplementary instructions dated 7th July 2011, reference: Rais Q-Tee.	
	The appliance must be fitted with a mechanical stop to prevent air control closure beyond the 11.7 mm open position.	
RAIS Q-Tee 85 manufactured by Rais A/S Industrivej 20, 9900, Frederikshavn, Denmark	Instruction manual dated 28th June 2011, reference: Manual for RAIS Q-Tee Revision 1.	Dry wood logs ⁽¹⁾
	Supplementary instructions dated 7th July 2011, reference:	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditi	ions
	Supplementary instructions Rais Q-Tee. The appliance must be fitted with a mechanical stop to prevent air control closure beyond the 11.7 mm open position.	
RAIS Q-Tee Wall 57, Rais Q-Tee Wall 65 and Rais Q-Tee Inset manufactured by Rais A/S Industrivej 20, 9900 Frederiksshavn, Denmark	December 2012, reference:	Dry wood logs ⁽¹⁾
RAIS Rondo 92 and RAIS Rondo 120 stoves manufactured by Rais A/ S Industrivej 20, 9900, Frederikshavn, Denmark	1	Wood logs ⁽¹⁾
RAIS Rondo Classic and RAIS Mino II stoves manufactured by Rais A/S Industrivej 20, 9900, Frederikshavn, Denmark	Instruction manual dated March 2008, reference: USER MANUAL Rais Rondo & Rais Mino II revision 2. Part number 5056510.	Wood logs ⁽¹⁾
RAIS VIVA 98, RAIS VIVA 98G, RAIS VIVA 120, RAIS VIVA 120G, RAIS RINA 90 Wood Burning Stoves, manufactured by Rais A/S, Industrivej 20, Vangen, DK – 9900, Frederikshavn, Denmark	Instruction manual dated 29th August 2011, reference: Manual for RAIS Rina, RAIS Viva. Supplementary instructions dated 27th September 2011, reference: Supplementary Instructions Rais. The appliance must be fitted with a mechanical stop to prevent closure of the air damper beyond the 8.5 mm open position.	Wood logs ⁽¹⁾

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditi	ons
Redfyre Kensal 20 Flat top (product code RF- EN20M), Redfyre Kensal 33 Flat top (product code RF- KEN33M and RF-KEN33W) manufactured by Redfyre Cookers, Osprey Road, Sowton Industrial Estate, Exeter, Devon, EX2 7JG	The manufacturer's instruction manual dated July 2008, reference: PM 247 Issue 1. Instruction manual dated January 2009, reference: PM280 Issue 1 A permanent stop must be in place on the secondary air inlet to prevent closure beyond the 50% open position	Untreated dry wood
Rika Como pellet stove manufactured by RIKA Innovative Ofentechnik GmbH, Müllerviertel 20, AT - 4563 Micheldorf. Austria	Instruction manual dated June 2011, reference: IN1226 Edition 1	6 mm wood pellets ⁽¹⁾
Rika Evo Aqua 9 and 15 manufactured by SHT Heiztechik aus Salzburg GmbH, Rechtes Salzachufer 40, A-5101, Salzburg- Bergheim, Austria	1	6 mm wood pellets ⁽¹⁾
Rika Memo pellet stove manufactured by RIKA Innovative Ofentechnik GmbH, Müllerviertel 20, AT - 4563 Micheldorf. Austria	Instruction manual dated June 2011, reference: IN1228 Edition 1	6 mm wood pellets ⁽¹⁾
Rika Pico pellet stove manufactured by RIKA Innovative Ofentechnik GmbH, Müllerviertel 20, AT - 4563 Micheldorf. Austria	Instruction manual dated June 2011, reference: IN1230 Edition 1	6 mm wood pellets ⁽¹⁾
	Instruction manual dated June 2011, reference: IN1229 Edition 1	6 mm wood pellets ⁽¹⁾
Rika Tema 6 kW stove manufactured by Rika Innovative Ofentechnik GmbH, Müllerviertel 20, AT - 4563 Micheldorf, Austria	Instruction manual dated January 2012, reference: IN1218 Edition 2	Wood logs ⁽¹⁾
Rika Topo pellet stove manufactured by RIKA Innovative Ofentechnik GmbH	Instruction manual dated June 2011, reference: IN1227 Edition 1	6 mm wood pellets ⁽¹⁾

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
Müllerviertel 20, AT - 4563 Micheldorf. Austria		
Riva 40 Cassette 4.9 kW stoves manufactured by Stovax Limited, Falcon Road, Sowton Industrial Estate, Exeter, Devon, EX2 7LF	Instruction manual dated August 2009, reference: PM235 Issue 2. Smoke control kit instruction manual dated January 2010, reference: PM375 Issue 2. A permanent stop must be	Wood logs ⁽¹⁾
	positioned to prevent closure of the secondary air control below the 50% open position.	
Riva 40 Freestanding, Riva 40 Avanti, Riva 40 Avanti Midi and Riva 40 Avanti Highline 4.9 kW stoves manufactured by Stovax Limited, Falcon Road, Sowton Industrial Estate, Exeter, Devon, EX2 7LF	Instruction manual dated August 2009, reference: PM226 Issue 2. Smoke control kit instruction manual dated January 2010, reference: PM375 Issue 2. A permanent stop must be positioned to prevent closure of the secondary air control below the 50% open position.	Wood logs ⁽¹⁾
Riva 45 Cassette (model numbers RV45 & RV45B) inset wood burning stoves manufactured by Stovax Limited, Falcon Road, Sowton Industrial Estate, Exeter, Devon. EX2 7LF	Instruction manual dated June 2012, reference: PM375 Issue 5. Instruction manual dated June	Wood logs ⁽¹⁾
Riva 50 Cassette (model numbers RV50 & RV50B) inset wood Burning Stoves manufactured by Stovax Limited, Falcon Road, Sowton Industrial Estate, Exeter, Devon. EX2 7LF	Instruction manual dated June 2012, reference: PM375 Issue 5. Instruction manual dated June 2012, reference: PM235 Issue 5. A permanent stop must be positioned to prevent closure of the secondary air control below the 50% open position and the primary air control fixed to allow a bleed of air to enter the firebox from underneath the grate.	Wood logs ⁽¹⁾
Riva 55 Avanti Midi and Riva 66 Freestanding 8	Instruction manual dated August 2009, reference: PM226 Issue 2.	Wood logs ⁽¹⁾

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditi	ons
kW stoves manufactured by Stovax Limited, Falcon Road, Sowton Industrial Estate, Exeter, Devon, EX2 7LF	Smoke control kit instruction manual dated January 2010, reference: PM375 Issue 2. A permanent stop must be	
	positioned to prevent closure of the secondary air control below the 50% open position and the primary air control fixed to allow a bleed of air to enter the firebox from underneath the grate.	
Riva 55 Cassette, Riva 66 cassette, Riva 66 Avanti cassette stoves manufactured by Stovax Limited, Falcon Road, Sowton Industrial Estate, Exeter, Devon, EX2 7LF	Instruction manual dated August 2009, reference: PM235 Issue 2. Smoke control kit instruction manual dated January 2010, reference: PM375 Issue 2.	Wood logs ⁽¹⁾
	A permanent stop must be positioned to prevent closure of the secondary air control below the 50% open position and the primary air control fixed to allow a bleed of air to enter the firebox from underneath the grate.	
Riva Plus Small (5 kW), Midi (6.5 kW) and Medium (8 kW) Stoves manufactured by Stovax Limited, Falcon Road, Sowton Industrial Estate, Exeter, Devon, EX2 7LF	Instruction manual dated June 2009, reference: PM231 Issue 3. Smoke control kit instruction manual dated November 2009, reference: PM402 Issue 1.	Wood logs ⁽¹⁾
	A permanent stop must be positioned to prevent closure of the secondary air control below the 25% open position.	
Riva Studio 1 (5 kW) freestanding wood stove manufactured by Stovax Limited, Falcon Road, Sowton Industrial Estate, Exeter,	Instruction manual dated June 2010, reference: PM452 Issue 1. Smoke control kit instruction manual dated June 2010,	Wood logs ⁽¹⁾
Devon, EX2 7LF	reference: PM400 Issue 3. A permanent stop must be positioned to prevent closure of the secondary air control below the 45% open position and the primary air control fixed	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditi	ons
	to prevent full closure to allow a bleed of air to enter the firebox at the base of the fuel bed.	
Riva Studio 1 Cassette (5 kW) Stove manufactured by Stovax Limited, Falcon Road, Sowton Industrial Estate, Exeter, Devon, EX2 7LF	Instruction manual dated October 2009, reference: PM274 Issue 2. Smoke control kit instruction manual dated November 2009, reference: PM400 Issue 1. A permanent stop must be positioned to prevent closure of the secondary air control below the 45% open position and the primary air control fixed to prevent full closure to allow a bleed of air to enter the firebox at the base of the fuel bed.	Wood logs ⁽¹⁾
Riva Studio 2 (8 kW) freestanding wood stove manufactured by Stovax Limited, Falcon Road, Sowton Industrial Estate, Exeter, Devon, EX2 7LF	Instruction manual dated June 2010, reference: PM452 Issue 1. Smoke control kit instruction manual dated June 2010, reference: PM400 Issue 3. A permanent stop must be positioned to prevent closure of the secondary air control below the 25% open position and the primary air control fixed to prevent full closure to allow a bleed of air to enter the firebox at the base of the fuel bed.	Wood logs ⁽¹⁾
Riva Studio 2 Cassette (8 kW) Stove manufactured by Stovax Limited, Falcon Road, Sowton Industrial Estate, Exeter, Devon, EX2 7LF	Instruction manual dated October 2009, reference: PM274 Issue 2. Smoke control kit instruction manual dated November 2009, reference: PM400 Issue 1. A permanent stop must be positioned to prevent closure of the secondary air control below the 25% open position and the primary air control fixed to prevent full closure to allow a	Wood logs ⁽¹⁾

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	bleed of air to enter the firebox at the base of the fuel bed.	
Riva Studio Cassette 500 RVS-500 Wood Burning inset stove manufactured by Stovax Limited, Falcon Road, Sowton	Instruction manual dated October 2012, reference: PM400 Issue 4.	Wood logs ⁽¹⁾
Industrial Estate, Exeter, EX2 7LF	Instruction manual dated August 2012, reference: PM274 Issue 9.	
	The appliance must be fitted with Smoke Control Kit RVS500SCKIT to prevent secondary air closure beyond the 50% open position.	
Riva Studio Duplex RVS-2DS Wood Burning Stove manufactured by Stovax Limited, Falcon Road Sowton	Instruction manual dated October 2012, reference: PM935 Issue 1.	Wood logs ⁽¹⁾
Industrial Estate, Exeter EX2 7LF	Instruction manual dated August 2012, reference: PM904 – Issue 1.	
	The appliance must be fitted with Smoke Control Kit RVS-2DSSCKIT to prevent secondary air closure beyond the 91 mm open position.	
Riva Studio Freestanding 500 RVFS Wood Burning Stove manufactured by Stovax	Industrial manual dated October 2012, reference: PM400 Issue 4.	Wood logs ⁽¹⁾
Limited, Falcon Road, Sowton Industrial Estate, Exeter, EX2 7LF	Instruction manual dated August 2012, reference: PM452 Issue 3.	
	The appliance must be fitted with Smoke Control Kit RVS500SCKIT to prevent secondary air closure beyond the 50% open position.	
Riva Vision Medium (8 kW) Multifuel Stove manufactured by Stovax Limited, Falcon Road, Sowton Industrial Estate,	Instruction manual dated October 2009, reference: PM278 Issue 2a.	Wood logs ⁽¹⁾
Exeter, Devon, EX2 7LF	Smoke control kit instruction manual dated January 2010, reference: PM401 Issue 1.	
	A permanent stop must be positioned to prevent closure of	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditi	ions
	the secondary air control below the 25% open position.	
Riva Vision Small (5 kW) and Riva Vision Midi (6.5 kW) Multifuel Stoves manufactured by Stovax Limited, Falcon Road, Sowton Industrial Estate, Exeter, Devon, EX2 7LF	Instruction manual dated October 2009, reference: PM278 Issue 2a. Smoke control kit instruction manual dated January 2010, reference: PM401 Issue 1.	Wood logs ⁽¹⁾
	A permanent stop must be positioned to prevent closure of the secondary air control below the 50% open position.	
Rosedale Inset Smoke Control inset roomheater manufactured by Town and Country Fires Limited, Unit 1 Enterprise	Instruction manual dated 11th January 2012, reference: Issue No. 04.	Wood logs ⁽¹⁾
Way, Thornton Road Industrial Estate, Pickering, North Yorkshire, YO18 7NA	The appliance must be fitted with a mechanical stop to prevent secondary air control closure beyond the 30% open position.	
Rosedale SC Multifuel Stove manufactured by Town & Country Fires Limited, 1 Enterprise Way, Thornton Road Industrial Estate, Pickering, North Yorkshire, YO18 7NA	Rosedale Smoke Control Stove Installation and User Instructions "Issue 1" dated 1st May 2010. The appliance must be fitted with a mechanical stop to prevent closure of the secondary	Wood logs with a maximum moisture content of 20% ⁽¹⁾
	air control beyond the 50% open position.	
wood pellet stove boiler manufactured by Palazzetti Lelio S.p.A, Via Roveredo 103,		Wood pellets ⁽¹⁾
Porcia (PN), 33080, Italy	Supplementary information entitled "Clean Air Act 1993 and Smoke Control Areas" dated January 2012, reference: 004723000.	
Saltfire Ecoview 12, Fireglow Eco 12, and Ecowarm Crystal 12 stoves (also known as Ekol Crystal 12) manufactured by Saltfire Stoves Limited, Station	Instruction manual dated 15th December 2011, reference: Evoview12 Manual 1.0. The appliance must be fitted with a mechanical stop to	Wood logs ⁽¹⁾
	1 · · · · · · · · · · · · · · · · · · ·	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
Works, John's Road, Wareham, BH20 4BG	prevent closure of the tertiary air control beyond the 4 mm open position.	
Saltfire Ecoview 5, Fireglow Eco 5, and Ecowarm Crystal 5 stoves (also known as Ekol Crystal 5) manufactured by Saltfire Stoves Limited, Station Works, John's Road, Wareham, BH20 4BG	Instruction manual dated 15th December 2011, reference: Evoview5 Manual 1.0. The appliance must be fitted with a mechanical stop to prevent closure of the tertiary air beyond the 4 mm open position.	Wood logs ⁽¹⁾
Saltfire Oslo-Eco manufactured by Saltfire Stoves Ltd, Station Works, John's Road, Wareham, BH20 4BG	Instruction manual dated 24th January 2011, reference: ECO7 operation-Revision 2A	Wood logs ⁽¹⁾
San Remo 4SE stove manufactured by Heat Design, 30 Hawthorn Road, Western Industrial Estate, Naas Road, Dublin 12, Ireland	Instruction manual dated 25th July 2012, reference: SR468SE. The fitting of a system to prevent closure of the secondary air control beyond 5 mm open must be implemented	Wood logs ⁽¹⁾
San Remo 6SE stove manufactured by Heat Design, 30 Hawthorn Road, Western Industrial Estate, Naas Road, Dublin 12, Ireland	Instruction manual dated 25th July 2012, reference: SR468SE. The fitting of a system to prevent closure of the secondary air control beyond 75% from closed must be implemented.	Wood logs ⁽¹⁾
San Remo 8SE stove manufactured by Heat Design, 30 Hawthorn Road, Western Industrial Estate, Naas Road, Dublin 12, Ireland	Instruction manual dated 25th July 2012, reference: SR468SE. The fitting of a system to prevent closure of the secondary air control beyond 25% from closed must be implemented.	Wood logs ⁽¹⁾
Scan Andersen 4-5 manufactured by Krog Iversen & Co. A/S DK-5492 Vissenbjerg, Denmark	The manufacturer's instruction manual dated 15th November 2007 entitled "Scan Andersen 4-5", reference: Edition 09/05-GB. A permanent stop must be in place on the secondary air inlet to prevent closure beyond 20 mm	Untreated dry wood
Scan DSA 7-5 wood-burning Inset roomheater manufactured	Instruction manual entitled "Instructions for installation and	Wood logs ⁽¹⁾

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditi	ons
by Scan A/S, PO Box 20, 5492 Vissenberg, Denmark	use: SCAN DSA 6 & DSA 7-5", reference: Edition 17.09.2010. Instruction manual entitled "DSA 7-5 – UK smoke control areas" dated 1 January 2012, reference: DSA 7-5 SMOKE. Instruction manual entitled "Instructions for installation (including directions for use and stoking)", reference: Edition 05.10.2010 – GB. The appliance must be fitted with a mechanical stop to prevent closure of the air wash control lever beyond the 50% open position.	
	Instruction manual dated February 2012, reference: 11.1c. The appliance must be fitted with a mechanical stop to prevent closure of the secondary air control beyond the 83 mm open position.	Wood logs ⁽¹⁾
	Instruction manual dated February 2012, reference: 11-1d. The appliance must be fitted with a mechanical stop to prevent closure of the secondary air control beyond the 83 mm open position.	Wood logs ⁽¹⁾
Scan Warm 1 and 4 stoves manufactured by Scan A/ S, Glasvaenget 3-9, 5492 Vissenbjerg, Denmark	February 2012, reference: 11-1a.	Wood logs ⁽¹⁾
Scan Warm 2 and 5 stoves manufactured by Scan A/ S, Glasvaenget 3-9, 5492 Vissenbjerg, Denmark	Instruction manual dated February 2012, reference: 11-1b. The appliance must be fitted with a mechanical stop to prevent closure of the secondary air control beyond the 83 mm open position.	Wood logs ⁽¹⁾

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditi	ons
Scanline 80, Scanline 80 B and Scanline 80 BF stoves manufactured by Heta A/S, Jupitervej 22, 7620 Lemvig,	Instruction manual dated January 2013, reference: Pervex1019/AH/ver1.	Wood logs ⁽¹⁾
Denmark	A permanent stop fixing the air control to 31% open when fully closed must be implemented.	
Scanline 800 Aqua and Scanline 800 Aqua low boiler stoves manufactured by Heta A/S, Jupitervej 22, 7620 Lemvig,	Instruction manual dated January 2013, reference: Pevex1018/AH/ver1.	Wood logs ⁽¹⁾
Denmark	A permanent stop fixing the air control to 52% open when fully closed must be implemented.	
Scanline 800, Scanline 810 standard, Scanline 810 with high ash door and soapstone stoves manufactured by Heta A/	Instruction manual dated January 2013, reference: Pevex1019/AH/ver1.	Wood logs ⁽¹⁾
S Jupitervej 22, 7620 Lemvig Denmark	A permanent stop fixing the air control to 31% open when fully closed must be implemented.	
Scanline 820 baking oven, Scanline 820 with soapstone and baking oven, Scanline 820 accumulation, Scanline 820	Instruction manual dated January 2013, reference: Pevex1019/AH/ver1.	Wood logs ⁽¹⁾
soapstone and accumulation, Scanline 820 with shelf, Scanline 820 soapstone and shelf stoves manufactured by Heta A/S, Jupitervej 22, 7620 Lemvig Denmark	A permanent stop fixing the air control to 31% open when fully closed must be implemented.	
accumulation, Scanline 830	Instruction manual dated January 2013, reference: Pevex1019/AH/ver1.	Wood logs ⁽¹⁾
by Heta A/S, Jupitervej 22, 7620 Lemvig, Denmark	A permanent stop fixing the air control to 31% open when fully closed must be implemented.	
Scanline 840 high ash door and shelf, Scanline 840 high ash door shelf and soapstone, Scanline 840 high ash door and accumulation, Scanline 840 high ash door, accumulation and soapstone, Scanline 840 baking oven with high ash door,	Instruction manual dated January 2013, reference: Pevex1019/AH/ver1. A permanent stop fixing the air control to 31% open when fully closed must be implemented.	Wood logs ⁽¹⁾
Scanline 840 baking oven with		

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditi	ons
high ash door and soapstone stoves manufactured by Heta A/ S Jupitervej 22, 7620 Lemvig, Denmark		
Scanline 850 on pedestal and Scanline 850 soapstone on pedestal stoves manufactured by Heta A/S, Jupitervej 22, 7620 Lemvig, Denmark	Instruction manual dated January 2013, reference: Pevex1019/AH/ver1. A permanent stop fixing the air control to 31% open when fully closed must be implemented.	Wood logs ⁽¹⁾
Schmid UTSK 180, 240, 300, 360, 450, 550, 700, 900, 1200, 1600 kw manufactured by Schmid AG Wood Firing Systems, PO Box 42, CH-8380, Eschlikon, Switzerland	Instruction manual dated 25th September 2008, reference: Instruction manual UTSK – ABC.22 – AME – S- PPU (where ABC is Model Number i.e. 180, 240, 300, 360, 450, 550, 700, 900, 1200, 1600)	Wood pellets or wood chips following CEN/TS 14961:2005 ⁽¹⁾
Schmid UTSL 30, 40, 50, 65, 80, 110, 150 kW manufactured by Schmid AG Wood Firing Systems, PO Box 42, CH-8380 Eschlikon, Switzerland	Instruction manual dated 23rd December 2004, reference: Operating Manual Wooden Chips and Pellets Plant. Lignumat UTSL	Wood pellets or wood chips following CEN/TS 14961:2005 ⁽¹⁾
Schmid UTSP 180, 240, 300 kW manufactured by Schmid AG, Wood Firing Systems, PO Box 42, CH-8380 Eschlikon, Switzerland	Instruction manual dated 25th September 2008, reference: Instruction manual UTSK – ABC.22 – AME – S- PPU (where ABC is Model Number i.e. 180, 240, 300)	Wood pellets following CEN/ TS 14961:2005 ⁽¹⁾
Schmid UTSR, 150, 180, 240, 300, 360, 450, 550, 700, 900 kW manufactured by Schmid AG, Wood Firing Systems, PO Box 42, CH-8380 Eschlikon, Switzerland	Instruction manual dated 25th September 2008, reference: Instruction manual UTSR – ABC.22 – AME – S-PPV (where ABC is Model Number i.e. 150, 180, 240, 300, 360, 450, 550, 700, 900)	Wood pellets or wood chips following CEN/TS 14961:2005 ⁽¹⁾
Schmid UTSW 900.32 boiler manufactured by Schmid AG – woodfiring systems, Hörnlistrasse 12, CH-8360 Eschlikon, Switzerland	Instruction manual dated 7th January 2013, reference: Instruction manual. Wood chip furnace with boiler type Schmid Pyrotroinc Modular issue 1.	Wood chips and wood pellets ⁽¹⁾
	Instruction manual dated 2010, reference: PersonalTouch Version 2010. EVO10V531\PT_2010_C3	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
Serenity 40 FS, Serenity 40 LS, Serenity 40 FW stoves manufactured by Pevex Enterprises Ltd, Unit 16, Seven Acres, Waldringfield, Suffolk, IP12 4PS	Instruction manual dated January 2013, reference: Pevex1014/AH/ver1. The appliance must be fitted with permanent stops that ensure the secondary and tertiary air controls do not close beyond 1.1 cm open and 2 cm open positions respectively.	Wood logs ⁽¹⁾
Serenity 50FS, Serenity 50LS, Serenity 50FW and Serenity 50 Ped stoves manufactured by Pevex Enterprises Ltd, Unit 16 Seven Acres, Waldringfield, Suffolk, IP12 4PS	Instruction manual dated January 2013, reference: Pevex1014/AH/ver1. The secondary air slider has a built in stop that does not allow the slider to be shut off completely and remains open by 40% of its full travel. The tertiary air has no slider and is factory designed with a 2 cm open slot and remains 100% open.	Wood logs ⁽¹⁾
Serrano 5 and Monterrey 6 Multi Fuel Stoves manufactured by Broseley fires Ltd, Knights Way, Battlefield Enterprise Park, Shrewsbury, Shropshire SY1 3AB		Wood logs ⁽¹⁾
Serrano 7 Multi Fuel Stove manufactured by Broseley fires Ltd, Knights Way, Battlefield Enterprise Park, Shrewsbury, Shropshire SY1 3AB	Instruction manual dated 21st December 2009, reference: TJ09C. The appliance must be fitted with a system that prevents the closure of the secondary air flaps to less than 10 mm open position.	Wood logs ⁽¹⁾
Sirius 450 – see Micromet MEG 4.5 and MEG 4.5 stove		
Sirius 750 – see Micromet MEG 7.5 and MEG 7.5 stove		
Sirius Traditional Stove manufactured by Tianjin Focus	instruction manual dated 9th	Wood logs ⁽¹⁾

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditi	ions
Arts & Crafts Co, Industrial Area Gao Zhuangzi Village, Xin Zhuang Town, Jin Nan District, Tianjin, P.R. China 300350		
Stockton 3 Flat top (product code 7118), Stockton 4 Flat top (product code 7101 and 7102), Stockton 5 Flat top (product code 7127) Stockton 5 midline (product code 7130), Stockton 6 Flat top (product codes 7100 and 7162), Stockton 6 Highline (product code 7117) and Stockton 7 Flat top (product codes 7120 and 7163) manufactured by Stovax Limited, Falcon Road, Sowton Industrial Estate, Exeter, Devon, EX2 7LF	manual dated July 2008, reference: PM227 ENG Issue 2. The manufacturer's instruction manual dated January 2009, reference: PM271 Issue 2.	Untreated dry wood
Stockton 5 Flat top (model number 7119), Stockton 5 Canopy (model number 7160) and Stockton 5 Midline (model number 7133) manufactured by Stovax Limited, Falcon Road, Sowton Industrial Estate, Exeter, Devon, EX2 7LF	The manufacturer's instruction manual reference: PM 176 – Issue 4. A permanent stop must be in place on the secondary air inlet to prevent closure beyond the 50% open position.	Untreated dry wood
Stockton 7 Inset Convector (product codes 7125F and 7125C) manufactured by Stovax Limited, Falcon Road, Sowton Industrial Estate, Exeter, Devon, EX2 7LF	manual dated May 2008,	Untreated dry wood
Stockton Milner (4.6 kW) inset stove – smoke control version - manufactured by Stovax Limited, Falcon Road, Sowton Industrial Estate, Exeter, Devon, EX2 7LF	Instruction manual reference: PM416 Issue 1 (June 2010). Smoke control kit instruction manual reference: PM501 Issue 1 (June 2010). A permanent stop must be positioned to prevent closure of	Wood logs ⁽¹⁾

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditi	ions
	the secondary air control below the 50% open position.	
Stoven Mayfair SE & Stoven Kensington SE 5 kW Wood Burning Stoves manufactured by Ciang Stoves Limited, South Chuangye Road, (Hanling Industrial Estate), Beiguan Section, Anyang City, Henan Provence, China. 455000.	Newman Fireplaces Limited's Instruction manual dated 27th November 2011, reference: 3-4. The appliance must be fitted with mechanical stops to prevent closure of the secondary air control beyond the 25% open position and the tertiary air beyond the 1 mm open position.	Wood logs ⁽¹⁾
Strebel SRP TR 90, 90 kW output pellet boiler manufactured by Strebel Ltd, 1f Albany Park, Camberley, Surrey GU16 7PB	The Strebel SRP TR 90 pellet boiler installation manual reference: Installation and operation instructions for special pellet furnace version 09:2010	6 mm diameter wood pellets ⁽¹⁾
Stretton Insert Smoke Exempt Wood Fuel Stove (Stretton Stove SE) manufactured by Aga Station Road, Ketley Telford Shropshire. TF1 5AQ	Instruction manual dated 12th July 2011, reference: N00530AXX REV:001	Dry wood logs ⁽¹⁾
STU 195 and STU 975 biomass boilers manufactured by Hoval Limited, Northgate, Newark, Nottinghamshire, NG24 1 JN	Instruction, operation and maintenance instruction manual for STU wood-pellet fired hot water boiler skid assembly "STUman" dated May 2011	Wood pellets ⁽¹⁾
Stuv 30 Compact H stove manufactured by Stuv Sa, Rue Jules Borbouse 4, B-5170, Bois-de-Villers, Belgium	Instruction manual dated January 2013, reference: SN 131766. Installation instruction manual dated January 2013, reference: SN 131766. The appliance must be fitted with a mechanical stop to prevent air control closure beyond the positions between settings 3 and 4.	Wood logs ⁽¹⁾
Stuv 30 Compact IN and Stuv 30 Compact R stoves manufactured by Stuv Sa, Rue Jules Borbouse 4, B-5170, Bois-de-Villers, Belgium	Instruction manual dated January 2013, reference: SN112787. Installation instruction manual dated January 2013, reference: 112787.	Wood logs ⁽¹⁾

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditi	ions
	The appliance must be fitted with a mechanical stop to prevent air control closure beyond the positions between settings 3 and 4.	
Stuv 30 Compact stove manufactured by Stuv Sa, Rue Jules Borbouse 4, B-5170, Bois-de-Villers, Belgium	Instruction manual dated January 2013, reference: SN 94770. Installation instruction manual dated January 2013, reference: SN 94770. The appliance must be fitted with a mechanical stop to prevent air control closure beyond the positions between settings 3 and 4.	Wood logs ⁽¹⁾
Suprema, Mamy and Italy Hard Top manufactured by La Nordica Spa, Via Summano 104 M. Precalcino, 36030 Vicenza, Italy		Wood logs ⁽¹⁾
Talbott 150-CMH 150 kW output Biomass Air Heater manufactured by Talbott's Biomass Energy Systems Ltd, Tollgate Drive, Tollgate Industrial Estate, Stafford ST16 3HS	Instruction manual for Talbott 150-CMH hand-fed Biomass Air Heater operating package dated January 2011, reference: OM-150-CMH version 1	Softwood, hardwood, medium density fibreboard (MDF) or chipboard offcuts ⁽¹⁾
Termosuprema Compact DSA manufactured by La Nordica Spa, Via Summano 104 M. Precalcino, 36030, Vicenza, Italy		
The Binder Wood Fired Boiler model RRK 1000 (1200 kW output) with multi-cyclone model MZA manufactured by Binder Gesellschaft mit beschränkter Haftung (GmbH) of Austria	The manufacturer's and Wood Energy Limited's instructions entitled "Binder Equipment Installation, Commissioning and Maintenance" dated 17th May 2005, reference: WELBinderManualrev0.doc, revision 0	Wood pellets or wood chips ⁽¹⁾
The Binder Wood Fired Boiler model RRK 1200- 1650 with Binder model MZA multicyclone and automatic	Wood Energy Limited's operating instructions for Binder appliances dated 15th July 2009, reference: 2009 July Binder O&M	Wood pellets or wood chips ⁽¹⁾

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditi	ons
	revision8.doc Operation and Maintenance Manual, Revision 8	
The Binder Wood Fired Boiler model RRK 130-250 (185-230 kW output), RRK 200-350 (250-300 kW output), RRK 400-600 (350-500 kW output) and RRK 640-850 (650-840 kW output) with cyclone model type ZA manufactured by Binder Gesellschaft mit beschränkter Haftung (GmbH) of Austria	The manufacturer's and Wood Energy Limited's instructions entitled "Binder Equipment Installation, Commissioning and Maintenance" dated 17th May 2005, reference: WELBinderManualrev0.doc, revision 0	Wood pellets or wood chips ⁽¹⁾
Boiler model RRK 1800- 2300 Binder model MZA multicyclone and automatic ignition manufactured by	,	Wood pellets or wood chips ⁽¹⁾
model RRK 2500- 3000 with Binder model MZA multicyclone and automatic ignition manufactured by	Wood Energy Limited's operating instructions for Binder appliances dated 15th July 2009, reference: 2009 July Binder O&M revision8.doc Operation and Maintenance Manual, Revision 8	Wood pellets or wood chips ⁽¹⁾
The Binder Wood Fired Boiler models RRK 22-49 (49 kW output) manufactured by Binder Gesellschaft mit beschränkter Haftung (GmbH) of Austria	entitled "Binder Equipment	Wood pellets or wood chips ⁽¹⁾
The Binder Wood Fired Boiler models RRK 80-175 (75-149 kW output) with cyclone models ZA 80-175 manufactured by Binder Gesellschaft mit beschränkter Haftung (GmbH) of Austria	Energy Limited's instructions	Wood pellets or wood chips ⁽¹⁾

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
The Classic model 25, 35, 40, 49, and 60 wood pellet boilers manufactured by Hargassner Gesellschaft mit beschränkter Haftung (GmbH), Gunderding 8, A-4952, Weng, Austria	The manufacturer's installation manual for the Classic Pellet Boilers reference: No. 22, Pellet Boilers, Type Classic 25, 31, 35, 40, 49, 60, reference: BA Classic 25L-60L Nr 21 0508	Wood pellets ⁽¹⁾
The Clearview Pioneer 400, Solution 400 and Pioneer Oven wood burning stoves manufactured by Clearview Stoves of More Works, Bishops Castle, Shropshire, SY9 5HH	The manufacturer's instructions entitled "Operating Instructions Clearview Vision/Vision Inset/ Pioneer & Solution" dated 1st July 2006, reference: V1/42 stamped and signed "Smoke Control". The appliance must be fitted with a tamperproof mechanical stop on the air slide/damper.	Air-dried wood logs ⁽¹⁾
The Dunsley Yorkshire Multifuel Stove and Boiler manufactured by Dunsley Heat Limited	ر ا	Untreated dry wood Peat or peat briquettes with, in either case, less than 25% moisture Union Coal Briketts,
		manufactured by Rheinbraun AG of Germany and comprising lignite compressed into briquettes of approximately 15 cm in length with square ends and with a sulphur content not exceeding 1% of the total weight
		CPL Wildfire, manufactured by Coal Products Limited, Immingham, which comprise bituminous coal with a volatile content of 32-36% (as to approximately 96% of the total weight) and a cold cure resin binder (as to the remaining weight); are manufactured from those constituents by a process

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
		involving roll-pressing; have an average weight of between 80-90 grams or between 160-170 grams; and have a sulphur content not exceeding 1.8% of the total weight
The Dunsley Yorkshire Multifuel Stove manufactured	The manufacturer's instructions	Untreated dry wood
by Dunsley Heat Limited	dated 5th August 1998, reference: A/22160 as amended by those dated 4th December 2004, reference: D13	Peat or peat briquettes with, in either case, less than 25% moisture
		Union Coal Briketts, manufactured by Rheinbraun AG of Germany comprising lignite compressed into briquettes of approximately 15 cm in length with square ends and with a sulphur content not exceeding 1% of the total weight
		CPL Wildfire, manufactured by Coal Products Limited, Immingham, which—comprise bituminous coal with a volatile content of 32-36% (as to approximately 96% of the total weight) and a cold cure resin binder (as to the remaining weight); are manufactured from those constituents by a process involving roll-pressing; have an average weight of either 80-90 grams or 160-170 grams; and have a sulphur content not exceeding 1.8% of the total weight
		CPL Wildfire, manufactured by Coal Products Limited, Immingham, which — comprise bituminous coal with a volatile content of 32-36% (as to approximately
(1) 77 6 1	d organic compounds or heavy metals as a resi	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditi	ons
		96% of the total weight) and a cold cure resin binder (as to the remaining weight); are manufactured from those constituents by a process involving roll-pressing; have an average weight of either 80-90 grams or 160-170 grams; and have a sulphur content not exceeding 1.8% of the total weight
The Dunsley Yorkshire Stove, manufactured by Dunsley Heat Limited	The manufacturer's instructions dated 5th August 1998, reference: A/22160, as amended by those dated 4th December 2004, reference: D13	Untreated dry wood Peat or peat briquettes with, in either case, less than 25% moisture
		Union Coal Briketts, manufactured by Rheinbraun AG of Germany comprising lignite compressed into briquettes of approximately 15 cm in length with square ends and with a sulphur content not exceeding 1% of the total weight
		CPL Wildfire, manufactured by Coal Products Limited, Immingham, which — comprise bituminous coal with a volatile content of 32-36% (as to approximately 96% of the total weight) and a cold cure resin binder (as to the remaining weight); are manufactured from those constituents by a process involving roll-pressing; have an average weight of either 80-90 grams or 160-170 grams; and have a sulphur content not exceeding 1.8% of the total weight
The Dunsley Yorkshire Woodburning Stove and Boiler	I .	Untreated dry wood

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditi	ons
-	reference: D13W, together with those dated 4th October 2004, reference: GHD/DUN4B/1	
The Dunsley Yorkshire Woodburning Stove manufactured by Dunsley Heat Limited	· · · · · · · · · · · · · · · · · · ·	Untreated dry wood
The En-tech model ENP 10, 15, 18, 25 and 35 boilers manufactured by Entech Energietechnikproduktion Gesellschaft mit beschränkter Haftung (GmbH), Gewerbezone 3, A-9300 St Veit, Glan-Hunnenbrunn, Austria	manual dated November 2009, reference: IMENP 10-35 11/2009	Wood logs ⁽¹⁾
The En-tech model PK 15 and 25 boilers manufactured by Entech Energietechnikproduktion Gesellschaft mit beschränkter Haftung (GmbH), Gewerbezone 3, A-9300 St Veit, Glan-Hunnenbrunn, Austria	reference: IMPK PK15/25 11/2009 EN for the Firefox pellet	Wood pellets ⁽¹⁾
The En-tech model PK 45 boilers manufactured by Entech Energietechnikproduktion Gesellschaft mit beschränkter Haftung (GmbH), Gewerbezone 3, A-9300 St Veit, Glan-Hunnenbrunn, Austria	manual dated November 2009, reference: IMPK PK45 11/2009	Wood pellets ⁽¹⁾
The Extraflame Comfort Mini manufactured by Extraflame S.p.a in Montecchio Precalcino (Vicenza), Italy		Wood pellets ⁽¹⁾
The Extraflame Idro manufactured by Extraflame S.p.a in Montecchio Precalcino (Vicenza), Italy	The manufacturer's operating instructions dated 28th August 2006, reference: 004275128 REV 002	Wood pellets ⁽¹⁾
The Extraflame Lucrezia Idro and Lucrezia Steel manufactured by Extraflame S.p.a in Montecchio Precalcino (Vicenza), Italy	instructions dated 12th July 2006,	Wood pellets ⁽¹⁾

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions		
The Extraflame: Babyfiamma, Bella and Bella Lux, Clementina, Comfort Maxi, Contessa, Divina, Divina Plus and Divina Steel, Duchessa and Duchessa Steel, Ecologica, Esmeralda and Esmeralda Crystal, Falò 1CP, Falò 2CP and Falò 1XP, Isabella, Karolina and Preziosa, all of which are manufactured by Extraflame S.p.a in Montecchio Precalcino (Vicenza), Italy	The manufacturer's operating instructions dated 5th March 2007, reference: 004275101 011	Wood pellets ⁽¹⁾	
The Hoval AgroLyt 20, 25, 35, 45 and 50 manufactured by Hoval AG, Austrasse 70, 9490 Vaduz, Liechtenstein	Installation and operation manuals dated January 2006, reference: 4 205/ 194/00, and dated June 2006, reference: 205 193/00	Wood logs with a maximum moisture content of 20% ⁽¹⁾	
The HSV 100 + WTH 100 boiler manufactured by Hargassner Gesellschaft mit beschränkter Haftung (GmbH), Gunderding 8, A-4952, Weng, Austria	manual version 44 for Wood	Wood chip or wood pellets ⁽¹⁾	
The HSV 50 + WTH 45, 49 or 55 boilers manufactured by Hargassner Gesellschaft mit beschränkter Haftung (GmbH), Gunderding 8, A-4952, Weng, Austria	The manufacturer's installation manual version 44 for Wood Chip and Pellet Stoves, Type HSV 30-100, reference: BA HSV30-100 RA/RAP V44 0608	Wood chip or wood pellets ⁽¹⁾	
	The manufacturer's installation manual version 44 for Wood Chip and Pellet Stoves, Type HSV 30-100, reference: BA HSV30-100 RA/RAP V44 0608	Wood chip or wood pellets ⁽¹⁾	
The Hwam 30 (4.5 kW nominal thermal output) manufactured by HWAM Heat Design AS Nydamsvej 53, 8362 Hørning, Denmark	Euroheat Distributors (HBS) Limited's operational instructions dated November 2006, reference: IN1141 Ed B. The appliance must be fitted with a mechanism to prevent closure of the air wash/ secondary air control.	Untreated dry wood	
The Hwam Beethoven and Hwam Beethoven H (4.5 kW nominal thermal output	Euroheat Distributors (HBS) Limited's operational	Untreated dry wood	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditi	ons
manufactured by HWAM Heat Design AS Nydamsvej 53, 8362 Hørning, Denmark		
The Hwam Mozart (4.5 kW nominal thermal output) manufactured by HWAM Heat Design AS Nydamsvej 53, 8362 Hørning, Denmark	Euroheat Distributors (HBS) Limited's operational instructions dated November 2006, reference: IN1141 Ed B. The appliance must be fitted with a mechanism to prevent closure of the air wash/ secondary air control.	Untreated dry wood
The Hwam Ravel (4.5 kW nominal thermal output) manufactured by HWAM Heat Design AS Nydamsvej 53, 8362 Hørning, Denmark	Euroheat Distributors (HBS) Limited's operational instructions dated November 2006, reference: IN1141 Ed B. The appliance must be fitted with a mechanism to prevent closure of the air wash/ secondary air control.	Untreated dry wood
The Hwam Vivaldi (4.5 kW nominal thermal output) manufactured by HWAM Heat Design AS Nydamsvej 53, 8362 Hørning, Denmark	Euroheat Distributors (HBS) Limited's operational instructions dated November 2006, reference: IN1141 Ed B. The appliance must be fitted with a mechanism to prevent closure of the air wash/ secondary air control.	Untreated dry wood
The Little Thurlow Smoke Control Wood Burning Stove manufactured by Town & Country Fires Limited, 1 Enterprise Way, Thornton Road Industrial Estate, Pickering, North Yorkshire, YO18 7NA	Town and Country Fires' operating instructions dated 30th June 2007, issue No. 3	Seasoned logs of less than 20% moisture and of a maximum length of 350 mm ⁽¹⁾
The Løvenholm manufactured by Hunter Stoves Limited, Unit 6, Old Mill Industrial Estate, Stoke Canon, Exeter, Devon, EX5 4RJ	Løvenholm Multifuel stove installation and operation manual version 07/08	Untreated dry wood with a maximum moisture content of 20%
The Løvenholm, Løvenholm Traditional, Løvenholm European, Løvenholm Pedestal stoves manufactured by Hunter	Løvenholm Multifuel stove installation and operation manual version 06/09	Untreated dry wood with a maximum moisture content of 20%

The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives
or coatings.

Fireplace	Conditions		
Stoves Limited, Unit 6, Old Mill Industrial Estate, Stoke Canon, Exeter, Devon, UK EX5 4RJ			
The Morsø 1400 series consisting of the 1412 and 1442 manufactured by Morsø Jernstøberi A/S DK-7900 Nykøbing, Mors, Denmark		Wood logs with a maximum moisture content of 20% ⁽¹⁾	
The Morsø 3100 series consisting of the 3112 and 3142 models manufactured by Morsø Jernstøberi A/S DK-7900 Nykøbing, Mors, Denmark		Wood logs with a maximum moisture content of 20% ⁽¹⁾	
The Morsø 6140 and 6148 manufactured by Morsø Jernstøberi A/S DK-7900 Nykøbing, Mors, Denmark	Installation and operation manual dated 4th September 2007, reference: 72610400	Wood logs with a maximum moisture content of 20% ⁽¹⁾	
The Morsø Owl 3410, 3420 and 3440 for wood burning manufactured by manufactured by Morsø Jernstøberi A/S DK-7900 Nykøbing, Mors, Denmark	The manufacturer's instructions dated 1st January 2000, reference: 72345600	Untreated dry wood which has been split, stacked and air dried, or air dried wood briquettes	
multifuel Stove (6 kW)	Euroheat Distributors (HBS) Limited's operational instructions dated November 2006, reference: IN1141 Edition B	Untreated dry wood	
	The manufacturer's instructions dated 25th October 2004, references:	Untreated dry wood	
120 x 160, 140 x 160, 140 x 180 and 180; OT 100, 120, 140, 120 x 160, 140 x 180 and 180; the Valoriani Piccolo, all of which are manufactured by Valoriani of Via Caselli alla	Instruction Model OOLinst. 1 FVR 80 OOLinst. 2 FVR 100		
Fornace, 213, 50066 Reggello, Firenze, Italy	OOLinst. 3 FVR 110 OOLinst. 4 FVR 120		
	OOLinst. 5 FVR 110 x 160		
	OOLinst. 6 TOP 100		

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace		Conditi	ions
	OOLinst. 7	TOP 120	
	OOLinst. 8	GR 100 and OT	
		100	
	OOLinst. 9	GR 120 and OT 120	
	OOLinst. 10	GR 140 and OT 140	
	OOLinst. 11	GR 120 x 160 and OT 120 x 160	
	OOLinst. 12	GR 140 x 160 and OT 140 x 160	
	OOLinst. 13	GR 140 x 180 and OT 140 x 180	
	OOLinst. 14	GR 180 and OT 180	
	OOLinst. 15	Valoriani Piccolo	
The Quadra-Fire 2100 Millennium Freestanding Wood Burning Stove manufactured by Hearth & Home Technologies 1445 North Highway, Colville, WA 99114, USA	dated 9th	October 2003,	Dry cured untreated wood of maximum size 38.1 cm x 10.16 cm x 5.08 cm
The Quadra-Fire Cumberland Gap Freestanding Wood Burning Stove manufactured by Hearth & Home Technologies 1445 North Highway, Colville, WA 99114, USA	dated 8th July	urer's instructions 2003, reference:	-
The Quadra-Fire Yosemite Freestanding Wood Burning Stove manufactured by Hearth & Home Technologies 1445 North Highway, Colville, WA 99114, USA		urer's instructions 2003, reference:	Dry cured untreated wood of maximum size 38.1 cm x 10.16 cm x 5.08 cm
The Talbott's Automatic Biomass Air Heaters models T1.5/A, T3/A, T5/A and TM/		irer's instructions, JANUARY 1990	Hardwood or softwood shavings or sawdust ⁽¹⁾

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions		
A formerly manufactured by Talbott's Heating Ltd and now manufactured by Talbott's Biomass Energy Systems Ltd, Tollgate Drive, Tollgate Industrial Estate, Stafford ST16 3HS			
The Talbott's Biomass Energy Models C1, C2, C3 and C4 formerly manufactured by Talbott's Heating Ltd and now manufactured by Talbott's Biomass Energy Systems Ltd, Tollgate Drive, Tollgate Industrial Estate, Stafford ST16 3HS		Chipboard, wood shavings or forestry chips ⁽¹⁾	
The Talbott's model T75, T150, T300 Biomass Air Heaters formerly manufactured by Talbott's Heating Ltd and now manufactured by Talbott's Biomass Energy Systems Ltd, Tollgate Drive, Tollgate Industrial Estate, Stafford ST16 3HS	The manufacturer's instructions dated 1st January 1995, reference: models T75, T150 and T300 'gen/sttech'	Wood offcuts, wood waste, pellets or chipboard ⁽¹⁾	
The Talbott's T500 Biomass Air Heater (afterburn model) formerly manufactured by Talbott's Heating Ltd and now manufactured by Talbott's Biomass Energy Systems Ltd, Tollgate Drive, Tollgate Industrial Estate, Stafford ST16 3HS	The manufacturer's instructions dated 1st January 1983, reference: A10000. The afterburn cycle shall last not less than 25 minutes and must come into operation each time the loading door is opened.	Wood offcuts, wood waste, pellets or chipboard ⁽¹⁾	
The Type USP wood pellet-fired boilers, model numbers USP-10, 15, 20, 25 and 30, manufactured by KWB – Kraft und Wärme aus Biomasse Gesellschaft mit beschränkter Haftung (GmbH) of Industriestrasse 235, A-8321 St. Margarethen an der Raab, Austria	The manufacturer's instructions dated 28th July 2003, reference: BA–USP 0703	Wood pellets ⁽¹⁾	
The Type USV wood pellet- and wood chipfired boilers, model numbers USV-15, 25,	Instruction manual dated August 2003 2012, reference: BA-USV 0803	Wood pellets or wood chips ⁽¹⁾	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions		
30, 40, 50, 60, 80 and 100, manufactured by KWB – Kraft und Wärme aus Biomasse Gesellschaft mit beschränkter Haftung (GmbH) of Industriestrasse 235, A-8321 St Margarethen an der Raab, Austria			
The Wood Waste Technology Heater, models WT10 and WT15, manufactured by Wood Waste Technology Limited, Units 1 & 2, Drummond Road, Astonfields Industrial Estate, Stafford, Staffordshire ST16 3HJ	dated 19th January 2005,	Medium density fibreboard, chipboard and hard and softwood offcuts ⁽¹⁾	
The Wood Waste Technology Ltd WT5 manufactured by Wood Waste Technology Limited, Units 1 & 2, Drummond Road, Astonfields Industrial Estate, Stafford, Staffordshire ST16 3HJ	dated 16th February 2009,	Medium density fibreboard, chipboard and hard and softwood offcuts (1)	
The WTH 150 and WTH 200 boilers manufactured by Hargassner Gesellschaft mit beschränkter Haftung (GmbH), Gunderding 8, A-4952, Weng, Austria		Wood logs or wood pellets ⁽¹⁾	
Therminator II 22 and Therminator II 30 Boiler manufactured by Solarfocus, Werkstrasse 1, 4451 St.Ulrich, Steyr, Austria	Installation instructions dated July 2006, reference: Version 11/08/06. Operating manual dated September 2009, reference: V8.051. Maintenance instructions dated 2006, reference: Ver 1st September 2006	Wood pellets ⁽¹⁾	
Therminator II 27 and Therminator II 36 Boiler manufactured by Solarfocus, Werkstrasse 1, 4451 St.Ulrich, Steyr, Austria	Installation instructions dated July 2006, reference: Version 11/08/06. Operating manual dated September 2009, reference: V8.051.	Wood logs ⁽¹⁾	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions		
	Maintenance instructions dated 2006, reference: Ver 1st September 2006.		
Therminator II 40 Boiler manufactured by Solarfocus, Werkstrasse 1, 4451 St.Ulrich, Steyr, Austria	Installation instructions dated July 2006, reference: Version 11/08/06.	Wood pellets or wood chips ⁽¹⁾	
2007.5.2.2002.20	Operating manual dated September 2009, reference: V8.051.		
	Maintenance instructions dated 2006, reference: Ver 1st September 2006.		
Therminator II 49 and Therminator II 60 Boiler manufactured by Solarfocus, Werkstrasse 1, 4451 St.Ulrich,	Installation instructions dated July 2006, reference: Version 11/08/06.	Wood logs or wood pellets or wood chips ⁽¹⁾	
Steyr, Austria	Operating manual dated September 2009, reference: V8.051.		
	Maintenance instructions dated 2006, reference: Ver 1st September 2006.		
Thornhill T3 small manufactured by Thornhill Eco Design Ltd 58/60 Winsheap,	2011, reference: ED/11/05.	Wood logs ⁽¹⁾	
Canterbury, Kent CT1 3RS	The appliance must be fitted with an air plate that prevents the teriary air controller from closing more than 17 mm and opening more than 45 mm.		
Tiger SuperClean stove manufactured by Tiger stoves, Focus Arts & Crafts Co, Industrial Area Gao Zhuangzi Village, Xin Zhuang Town, Jin Nan District, Tianjin, P.R.China 300350	April 2010, reference: INSTALLATION AND OPERATING INSTRUCTIONS	Wood logs ⁽¹⁾	
Trianco Greenflame 15 wood pellet boiler manufactured by T.R. Engineering Ltd, Unit 7, Newton Chambers Way, Thorncliffe Industrial Estate, Chapeltown, Sheffield, S35 2PH		6 mm wood pellets ⁽¹⁾	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions		
Turbhogar Alfa 80T and 65T, Turbhogar Beta 80T, Turbhogar Delta 80T and 65T, Turbhogar Lamda 80T and 65T, Turbhogar Sigma 80T and 65T, Turbhogar Omega 80T and Turbhogar Tau 80T and 65T fireplace inserts manufactured by Rofer and Rodi UK Ltd, Unit 10, Millennium Road, Airedale Business Centre, Skipton, North Yorkshire BD23 2TZ	Manual of assembly and use dated 20th September 2010, reference: RR 100920, and supplementary instruction manual of the same date, reference: UK 100920. The appliance must be fitted with a system that prevents the full closure of the air control opening so that the air openings remain 3 mm (30%) open at the minimum setting.	Wood logs ⁽¹⁾	
Twin Heat CS150i manufactured by TWIN HEAT A/S, Nørrevangen 7, DK-9631 Gedsted, Denmark	Operating instructions dated 17th December 2008, reference: Version 6.0.03	Wood pellets of a maximum length of 30 mm and diameter of 6 mm and conforming to CEN/TS 14961:2005 ⁽¹⁾	
Uniconfort EOS 45, EOS 50, EOS 55, EOS 65, EOS 70, EOS 75, EOS 80, EOS 85 boilers fitted with a multi-cyclone manufactured by Uniconfort srl, Via dell'Industria, 21, 35018 San Martino di Lupari, PD, Italy	Instruction manual dated May 2012, reference: Uniconfort EOS MANUAL: R1	Wood pellets ⁽¹⁾	
Uniconfort EOS 90 boiler fitted with a multi-cyclone manufactured by Uniconfort srl, Via dell'Industria, 21, 35018 San Martino di Lupari, PD, Italy	2012, reference: Uniconfort EOS	Wood pellets or wood chips ⁽¹⁾	
VarioWIN VA 12 kW wood pellet boiler manufactured by Windhager Zentralheizung GmbH, Anton-Windhager Str.20, A-5201 Seerkirchen bei Salzburg, Austria	dated January 2010, reference: 092947/00.	Wood pellets ⁽¹⁾ , 6 mm diameter, length 80% between 15-30 mm and a density of at least 1.1kg.dm3	
Vega 100 Clean Burn II stove manufactured by Percy Doughty & Co Limited, Imperial Point, Express Trading Estate, Stone Hill Road, Farnworth, Bolton, BL4 9TN	Instruction manual dated January 2013, reference: Vega 100 Clean Burn II Installation and Operation Instructions REV: D. The appliance must be fitted with a mechanical stop to prevent secondary air control	Wood logs ⁽¹⁾	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions		
_	closure beyond the 50% open position.		
Vega 200 Clean Burn stove manufactured by Percy Doughty & Co Limited, Imperial Point, Express Trading Estate, Stone Hill Road, Farnworth, Bolton, BL4 9TN	Instruction manual dated January 2013, reference: Vega 200 Clean Burn Installation and Operation Instructions REV: D. The appliance must be fitted with a mechanical stop to prevent secondary air control closure beyond the 50% open position.	Wood logs ⁽¹⁾	
Vesuvio 400 kW automatic pizza oven manufactured by CLM Bakery System srl, Via Monteli, 3 - 33092 Meduno (PN), Italy and previously manufactured by CLM srl, Via I Maggio 35, 31043, Fontanelle (Treviso), Italy	CLM Vesuvio oven instruction manual dated 29th November 2011, reference: Instruction and maintenance manual ENGLISH version Review 0.1	'CalorPan' 100% beech briquette, octagonal section, length 260-300 mm, width and height 75-90 mm. manufactured from dried beech sawdust ⁽¹⁾	
View 3 (3.8 kW) and View 5 (4.9 kW) multifuel stoves manufactured by Stovax Limited, Falcon Road, Sowton Industrial Estate, Exeter, Devon, EX2 7LF	Instruction manual dated June 2010, reference: PM485 Issue 1. Smoke control kit instruction manual dated June 2010, reference: PM490 Issue 1. A permanent stop must be positioned to prevent closure of the secondary air control below the 50% open position.	Wood logs ⁽¹⁾	
View 5 (4.9 kW) wood stove manufactured by Stovax Limited, Falcon Road, Sowton Industrial Estate, Exeter, Devon, EX2 7LF	Instruction manual dated June 2010, reference: PM485 Issue 1. Smoke control kit instruction manual dated June 2010, reference: PM490 Issue 1. A permanent stop must be positioned to prevent closure of the secondary air control below the 50% open position	Wood logs ⁽¹⁾	
View 7 (7 kW) inset appliance Product code VW-7NMF manufactured by Stovax Limited, Falcon Road, Sowton	Instruction manual dated June 2011, reference: PM552 - Issue 1.	Wood logs ⁽¹⁾	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

T:1	Conditi	
Fireplace Industrial Estate, Exeter, Devon, EX2 7LF	Smoke control kit instruction manual dated July 2011, reference: PM490 Issue 2. A permanent stop must be in place on the secondary air inlet to prevent closure beyond the 50% open position.	Ons
Vista Magnifico SE & Vista Perfetto SE 4.9 kW Wood Burning Stove manufactured by Ciang Stoves Limited, South Chuangye Road, (Hanling Industrial Estate), Beiguan Section, Anyang City, Henan Provence, China. 455000.	Newman Fireplaces Limited's Instruction manual dated 24th October 2011, reference: 1-2. The appliance must be fitted with mechanical stops to prevent closure of the secondary air control beyond the 30% open position and the tertiary air beyond the 50% open position.	Wood logs ⁽¹⁾
Vitae 06C inset stove manufactured by Heat Design, 30 Hawthorn Road, Western Industrial Estate, Naas Road, Dublin 12, Ireland	Instruction manual dated 26th July 2012, reference: VIT06C. A permanent stop to prevent closure of the secondary air control beyond 20% open must be implemented	Wood logs ⁽¹⁾
Vitae 11C inset stove manufactured by Heat Design, 30 Hawthorn Road, Western Industrial Estate, Naas Road, Dublin 12, Ireland	Instruction manual dated 26th July 2012, reference: VIT11C. A permanent stop to prevent closure of the secondary air control beyond 20% open must be implemented.	Wood logs ⁽¹⁾
Westcott 5SE manufactured by Dimplex, GDC Group Ltd, Millbrook House, Grange Drive, Hedge End, Southampton SO30 2DF	Instruction manual dated 7th September 2010, reference: 08/51351/0 – Issue 0	Wood logs ⁽¹⁾
Westfire Series One stove and Westfire Series Two stove manufactured by Westfire, Tømrervej 3, DK-6800 Varde, Denmark	Westfire WF One and Two series installation manual and operating instructions and supplementary instruction manual dated 1st June 2011, reference: Westfire supplementary instructions June 2011/Version 1.	Wood logs ⁽¹⁾
	The appliance must be fitted with a permanent stop to prevent	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditi	ions
	closure of the secondary air control less than 50% open.	
Westfire Uniq 15, 16 and 20 (also known as WF UNIQ 15, 16 and 20) manufactured by Westfire Tømrervej 3 DK-6800 Varde, Denmark	Installation and operating instructions dated 2007, reference: WF15–WF16–WF20, together with supplementary instructions dated 2007, reference: 01wfuk.2007. A permanent stop must be in place on the secondary air inlet to prevent closure beyond 50 mm.	Untreated dry wood
Westfire Uniq 18 Westfire Uniq 17 Westfire Uniq 19 Westfire Uniq 23 Westfire Uniq 23 side Glass Westfire Uniq 23 Inset stoves manufactured by Westfire APS Tømrervej 3 DK-6800 Varde Denmark	Instruction manual reference: WESTFIRE SUPPLEMENTARY INSTRUCTIONS JUNE 2010. The appliance must be fitted with a mechanical stop to prevent closure of the secondary air slide beyond the 30 mm open position.	Wood logs ⁽¹⁾
Westfire Uniq 21 stove, Westfire Uniq 21 pedestal stove and Westfire Uniq 21 wall hung stove manufactured by Westfire, Tømrervej 3, DK-6800 Varde, Denmark	Westfire WF21 installation manual and operating instructions and supplementary instruction manual dated 1st June 2011, reference: Westfire supplementary instructions June 2011/Version 1. The appliance must be fitted with a permanent stop to prevent closure of the secondary air control less than 60% open.	Wood logs ⁽¹⁾
Westfire Uniq 26 stove, Westfire Uniq 27 stove and Westfire Uniq 28 stove manufactured by Westfire, Tømrervej 3, DK-6800 Varde, Denmark	Westfire WF26, WF27, WF28 installation manual and operating instructions and supplementary instruction manual dated 1st June 2011, reference: Westfire supplementary instructions June 2011/Version 1. The appliance must be fitted with a permanent stop to the	Wood logs ⁽¹⁾

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditi	ions
	secondary air slider control to prevent closure more than 20 mm from the fully closed position.	
Westfire Uniq 32 Inset stove and Westfire Uniq 32 Freestanding stove manufactured by Westfire, Tømrervej 3, DK-6800 Varde, Denmark	Westfire WF23/Uniq23, WF32/Uniq 32 inset stove installation manual and operating instructions and supplementary Instruction manual dated 1st June 2011, reference: Westfire supplementary instructions June 2011/Version 1. The appliance must be fitted with a permanent stop to prevent closure of the secondary air control less than 50% open.	Wood logs ⁽¹⁾
Windhager BioWin 100, 150, 210 and 260 manufactured by Windhager Zentralheizung GmbH, Anton-Windhager- Str. 20, A-5201 Seerkirchen bei Salzburg, Austria	The manufacturer's instruction manual dated May 2008, reference: 0916197/00	Wood pellets ⁽¹⁾
Windhager FireWin 90 and 120 manufactured by Windhager Zentralheizung GmbH, Anton-Windhager- Str. 20, A-5201 Seerkirchen bei Salzburg, Austria	The manufacturer's instruction manual dated August 2008, reference: 092125/00	Wood pellets ⁽¹⁾
	Instruction manual dated January 2011, reference: OOLinst.8 GR 100 and OT 100 v2	Untreated dry wood with a maximum moisture content of 20%
Wood Fired Ovens by Jamie Oliver Ltd's GR Valoriani Ristorante 120 and OT Valoriani Ristorante 120 manufactured by Valoriani of Via Caselli alla Fornace 213, 50066 Reggello, Firenze, Italy	Instruction manual dated January 2011, reference: OOLinst.9 GR 120 and OT 120 v2	Untreated dry wood with a maximum moisture content of 20%
Wood Fired Ovens by Jamie Oliver Ltd's GR Valoriani Ristorante 120x160 and OT	Instruction manual dated January 2011, reference: OOLinst.11 GR 120x160 and OT 120x160 v2	Untreated dry wood with a maximum moisture content of 20%

The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives
or coatings.

Fireplace	Conditi	ons
Valoriani Ristorante 120x160 manufactured by Valoriani of Via Caselli alla Fornace 213, 50066 Reggello, Firenze, Italy		
Wood Fired Ovens by Jamie Oliver Ltd's GR Valoriani Ristorante 140 and OT Valoriani Ristorante 140 manufactured by Valoriani of Via Caselli alla Fornace 213, 50066 Reggello, Firenze, Italy	Instruction manual dated January 2011, reference: OOLinst.10 GR 140 and OT 140 v2	Untreated dry wood with a maximum moisture content of 20%
Wood Fired Ovens by Jamie Oliver Ltd's GR Valoriani Ristorante 140x160 and OT Valoriani Ristorante 140x160 manufactured by Valoriani of Via Caselli alla Fornace 213, 50066 Reggello, Firenze, Italy	Instruction manual dated January 2011, reference: OOLinst.12 GR 140x160 and OT 140x160 v2	Untreated dry wood with a maximum moisture content of 20%
Wood Fired Ovens by Jamie Oliver Ltd's GR Valoriani Ristorante 140x180 and OT Valoriani Ristorante 140x180 manufactured by Valoriani of Via Caselli alla Fornace 213, 50066 Reggello, Firenze, Italy	Instruction manual dated January 2011, reference: OOLinst.13 GR 140x180 and OT 140x180 v2	Untreated dry wood with a maximum moisture content of 20%
Wood Fired Ovens by Jamie Oliver Ltd's GR Valoriani Ristorante 180 and OT Valoriani Ristorante 180 manufactured by Valoriani of Via Caselli alla Fornace 213, 50066 Reggello, Firenze, Italy		Untreated dry wood with a maximum moisture content of 20%
Wood Fired Ovens by Jamie Oliver Ltd's Valoriani Casa 100 manufactured by Valoriani of Via Caselli alla Fornace 213, 50066 Reggello, Firenze, Italy	Instruction manual dated January 2011, reference: OOLinst.2 FVR 100 v2	
Wood Fired Ovens by Jamie Oliver Ltd's Valoriani Casa 110 manufactured by Valoriani of Via Caselli alla Fornace 213, 50066 Reggello, Firenze, Italy	Instruction manual dated January 2011, reference: OOLinst.3 FVR 110 v2	Untreated dry wood with a maximum moisture content of 20%
Wood Fired Ovens by Jamie Oliver Ltd's Valoriani Casa 110x160 manufactured by Valoriani of Via Caselli alla	Instruction manual dated January 2011, reference: OOLinst.5 FVR 110x160 v2	Untreated dry wood with a maximum moisture content of 20%

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditi	ions
Fornace 213, 50066 Reggello, Firenze, Italy		
Wood Fired Ovens by Jamie Oliver Ltd's Valoriani Casa 120 manufactured by Valoriani of Via Caselli alla Fornace 213, 50066 Reggello, Firenze, Italy	Instruction manual dated January 2011, reference: OOLinst.4 FVR 120 v2	Untreated dry wood with a maximum moisture content of 20%
Wood Fired Ovens by Jamie Oliver Ltd's Valoriani Casa 80 manufactured by Valoriani of Via Caselli alla Fornace 213, 50066 Reggello, Firenze, Italy	Instruction manual dated January 2011, reference: OOLinst.1 FVR 80 v2	Untreated dry wood with a maximum moisture content of 20%
Wood Fired Ovens by Jamie Oliver Ltd's Valoriani Piccolo manufactured by Valoriani of Via Caselli alla Fornace 213, 50066 Reggello, Firenze, Italy	Instruction manual dated January 2011, reference: OOLinst.15 Valoriani Piccolo v2	Untreated dry wood with a maximum moisture content of 20%
Wood Fired Ovens by Jamie Oliver Ltd's Valoriani Villa 100 manufactured by Valoriani of Via Caselli alla Fornace 213, 50066 Reggello, Firenze, Italy	Instruction manual dated January 2011, reference: OOLinst.6 TOP 100 v2	Untreated dry wood with a maximum moisture content of 20%
Wood Fired Ovens by Jamie Oliver Ltd's Valoriani Villa 120 manufactured by Valoriani of Via Caselli alla Fornace 213, 50066 Reggello, Firenze, Italy	Instruction manual dated January 2011, reference: OOLinst.7 TOP 120 v2	Untreated dry wood with a maximum moisture content of 20%
Woodpecker 15, 25 and 45 wood pellet boilers manufactured by Woodpecker Energy UK, Abbey Manor Business Centre Preston Road. Yeovil. BA20 2EN. Previously manufactured by Garranlea Renewables Ltd of Barnard, Garranlea, New Inn, Cashel, Co. Tipperary, Ireland	Instruction manual dated May 2012, reference: Installation and Operating Manual Issue 6	Wood pellets conforming to CEN TS 14961 ⁽¹⁾
Woodpecker 50 kW wood pellet boilers manufactured by Woodpecker Energy UK, Abbey Manor Business Centre, Preston Road, Yeovil, Somerset. BA20 2EN	Instruction manual dated May 2012, reference: Installation and Operating Manual Woodpecker 50 Model Wood Pellet Boiler System Version 2	Wood pellets conforming to CEN TS 1496 ⁽¹⁾
1 *	Instruction manual dated February 2012, reference:	6 mm wood pellets ⁽¹⁾

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditi	ons
-	Installation and Operating Manual Issue 2	
1 *	February 2012, reference: Issue	6 mm wood pellets ⁽¹⁾
boiler manufactured by	February 2012, reference: Installation and Operating	6 mm wood pellets ⁽¹⁾
Woodpecker Thermon 250 boiler manufactured by Woodpecker Energy UK, Abbey Manor Business Centre, Preston Road. Yeovil. BA20 2EN	February 2012, reference: Installation and Operating	6 mm wood pellets ⁽¹⁾
1	1 0	6 mm wood pellets ⁽¹⁾
Wood Waste Technology	April 2011, reference: WTA Installation Operation & WTA Maintenance Instructions WTA	Chipboard, Medium Density Fibreboard, Softwood, Hardwood. All fuels to be chipped to a maximum size of 25 mm and a maximum moisture content of 20%. Maximum fines (sawdust) content 5% ⁽¹⁾
Xeoos 5 kW stove Versions - Natur, Style, Harmony, Pur, Classic, Elegance and Stone Xeoos 8 kW stove Versions - Basic, Pur, Classic, Elegance Stone and Air Instruction manual references manufactured by Specht Modulare Ofensysteme GmbH & Co, KG Projektmanagement	"Operating and Installation Instructions Xeoos 5 kW/ 8 kW Model 2008", reference:	Wood logs ⁽¹⁾ conforming to DIN 51731

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
Bahnhofstr. 2 D 35116 Hatzfeld, Germany		
Yeoman CL 7 (7 kW) inset appliance Product code YM-CL7NMF manufactured by Stovax Limited, Falcon Road, Sowton Industrial Estate, Exeter, Devon, EX2 7LF	Instruction manual dated June 2011, reference: PM553 - Issue 1. Smoke control kit instruction manual dated June 2011, reference: PM491 Issue 2. A permanent stop must be in place on the secondary air inlet to prevent closure beyond the 50% open position.	Wood logs ⁽¹⁾
Yeoman CL Milner Stove Product code YM-CLMB manufactured by Stovax Limited, Falcon Road, Sowton Industrial Estate, Exeter, Devon, EX2 7LF	Instruction manual dated June 2011, reference: PM559 - Issue 1. Smoke control kit instruction manual dated June 2011, reference: PM491 Issue 2. A permanent stop must be positioned to prevent closure of the secondary air control below the 50% open position.	Wood logs ⁽¹⁾
Yeoman CL3 (3.8 kW) and CL5 (4.9 kW) multifuel stoves manufactured by Stovax Limited, Falcon Road, Sowton Industrial Estate, Exeter, Devon, EX2 7LF	2010, reference: PM489 Issue 1.	Wood logs ⁽¹⁾
Yeoman CL5 (4.9 kW) wood Stove manufactured by Stovax Limited, Falcon Road, Sowton Industrial Estate, Exeter, Devon, EX2 7LF	Instruction manual dated June 2010, reference: PM489 Issue 1. Smoke control kit instruction manual dated 5 April 2010, reference: PM491 Issue 1. A permanent stop must be positioned to prevent closure of	Wood logs ⁽¹⁾

The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives
or coatings.

Fireplace	Conditions	
	the secondary air control below the 50% open position.	
Yeoman Devon Multifuel Flat Top 1 Door, Flat Top 2 Door, Low Canopy 1 Door, Low Canopy 2 Door, High Canopy 1 Door and High Canopy 2 Door (9 kW) Stoves manufactured by Stovax Limited, Falcon Road, Sowton Industrial Estate, Exeter, Devon, EX2 7LF	Instruction manual dated February 2008, reference: PM184 Issue 3. Smoke control kit instruction manual dated January 2010, reference: PM403 Issue 1. A permanent stop must be positioned to prevent closure of the secondary air control below the 50% open position and a system that ensures a gap of 1 mm for bleed of primary air when the spin wheels are rotated to their fully closed positions.	Wood logs ⁽¹⁾
Yeoman Exe Multifuel Flat Top 1 Door, Flat Top 2 Door, Low Canopy 1 Door and Low Canopy 2 Door (4.9 kW) Stoves manufactured by Stovax Limited, Falcon Road, Sowton Industrial Estate, Exeter, Devon, EX2 7LF	Instruction manual dated February 2008, reference: PM184 Issue 3. Smoke control kit instruction manual dated January 2010, reference: PM403 Issue 1. A permanent stop must be positioned to prevent closure of the secondary air control below the 60% open position and a system that prevents full closure of the primary air controls	Wood logs ⁽¹⁾
		Wood logs ⁽¹⁾

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

EXPLANATORY NOTE

(This note is not part of the Order)

This Order revokes and replaces with amendments the Smoke Control Areas (Exempted Fireplaces) (England) Order 2012 (S.I. 2012/2282).

It exempts the fireplaces listed in the Schedule from the provisions of section 20 of the Clean Air Act 1993 (prohibition of smoke emissions in smoke control areas), subject to the conditions set out in the Schedule. Several additional fireplaces have been exempted.

A full impact assessment has not been produced as no impact on the private, voluntary or public sectors is foreseen.

Changes to legislation:

There are outstanding changes not yet made by the legislation.gov.uk editorial team to The Smoke Control Areas (Exempted Fireplaces) (England) Order 2013. Any changes that have already been made by the team appear in the content and are referenced with annotations. View outstanding changes

Changes and effects yet to be applied to the whole Instrument associated Parts and Chapters:

Order revoked by S.I. 2013/2112 art. 3