WELSH STATUTORY INSTRUMENTS

2016 No. 811 (W. 201)

CLEAN AIR, WALES

The Smoke Control Areas (Exempted Classes of Fireplace) (Wales) Order 2016

Made - - - - 26 July 2016
Laid before the National
Assembly for Wales - - 29 July 2016
Coming into force - - 22 August 2016

The Welsh Ministers make the following Order in exercise of the power conferred by section 21(5) of the Clean Air Act 1993(1).

They are satisfied that the fireplaces exempted by this Order can be used for burning fuel other than authorised fuels without producing any smoke or a substantial quantity of smoke.

Title, commencement and application

- 1.—(1) The title of this Order is the Smoke Control Areas (Exempted Classes of Fireplace) (Wales) Order 2016 and it comes into force on 22 August 2016.
 - (2) This Order applies in relation to Wales.

Classes of fireplace exempted from the provisions of section 20 of the Clean Air Act 1993

2. Any class of fireplace described in the first column of the table in the Schedule is, upon the condition or conditions specified in the Schedule in relation to that fireplace, exempted from the provisions of section 20 of the Clean Air Act 1993 (prohibition of smoke emissions in smoke control area).

Revocation

3. The Smoke Control Areas (Exempted Fireplaces) (Wales) Order 2015(2) is revoked.

^{(1) 1993} c. 11. The function of the Secretary of State in section 21(5) was, so far as exercisable in relation to Wales, transferred to the National Assembly for Wales by virtue of article 2 of, and Schedule 1 to, the National Assembly for Wales (Transfer of Functions) Order 1999 (S.I. 1999/672). That function is now exercisable by the Welsh Ministers by virtue of section 162 of, and paragraph 30 of Schedule 11 to, the Government of Wales Act 2006 (c. 32).

⁽²⁾ S.I. 2015/1513 (W. 175).

Status: This is the original version (as it was originally made). This item of legislation is currently only available in its original format.

Lesley Griffiths
Cabinet Secretary for Environment and Rural
Affairs, one of the Welsh Ministers

26th July 2016

SCHEDULE Article 2

EXEMPTED CLASSES OF FIREPLACE

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Aarrow ECB5 Plus SC 5kW and ECB7 Plus SC 7kW woodburning stoves.		Wood logs (1).
Manufactured by Arada Limited, The Fireworks, Weycroft Avenue, Axminster, Devon, EX13 5HU.		
Aarrow Signature 5 SC, Aarrow Ecoburn 5 SC, Hamlet Solution 5 SC and Villager	Instruction manual reference "Rev 02" dated April 2010.	Wood logs ⁽¹⁾ .
Espirit 5 SC.	The appliance must be fitted with a mechanical stop to	
Manufactured by Arada Ltd.,	prevent closure of the air	
The Fire Works, Millwey Industrial Estate, Axminster,	control beyond 20mm from the closed position and 50 mm	
Devon, EX13 5HU.	beyond the fully open position.	
Aarrow 1 Series 400 wood burning inset roomheater and 400 T F wood burning stove.	Operating and installation manual reference "Part No. AFS 1589de" dated July 2014.	Wood logs ⁽¹⁾ .
Manufactured by Arada Stoves Ltd., The Fireworks, Weycroft Avenue, Axminster, Devon EX13 5HU.	The appliance must be fitted with a mechanical stop to prevent air control lever closure beyond the 10mm open position.	
Aarrow 1 Series 500 wood burning inset roomheater.	Operating and installation manual reference "Part No. AFS 1789de" dated July	Wood logs ⁽¹⁾ .
Manufactured by Arada Stoves Ltd., The Fireworks, Weycroft	2014.	
Avenue, Axminster, Devon EX13 5HU.	The appliance must be fitted with a mechanical stop to prevent air control lever closure beyond the 10mm open position.	
Aarrow 1 Series 600 wood burning inset roomheater.	Operating and installation manual reference "Part	Wood logs ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Manufactured by Arada Stoves Ltd., The Fireworks, Weycroft	No. AFS 1789de" dated July 2014.	
Avenue, Axminster, Devon EX13 5HU.	The appliance must be fitted with a mechanical stop to prevent air control lever closure beyond the 9mm open position.	
Aarrow 1 Series 750 wood burning inset roomheater.	Operating and installation manual reference "Part No. AFS 1789de" dated July	Wood logs ⁽¹⁾ .
Manufactured by Arada Stoves Ltd., The Fireworks, Weycroft	2014.	
Avenue, Axminster, Devon EX13 5HU.	The appliance must be fitted with a mechanical stop to prevent air control lever closure beyond the 7mm open position.	
Acquisitions Bloomsbury 5kW stove.	Instruction manual reference "01/12 (PP)" dated January 2012.	Wood logs ⁽¹⁾ .
Manufactured by Esse Engineering Ltd., Ouzledale Foundry, Long Ing, Barnoldswick, Lancashire, BB18 6BN.	The appliance must be fitted with a system that prevents the closure of the air controls beyond the 50% open position.	
Acquisitions Bloomsbury SE 8kW Smoke Exempt Multi- Fuel Stove.	Instruction manual reference "AB-8kW-I05-310114" dated 31st January 2014.	Wood logs ⁽¹⁾ .
Manufactured by Esse Engineering Ltd, Ouzledale Foundry, Long Ing, Barnoldswick, BB18 6BN.		
Acquisitions Cannonbury 4 and 5.	Installation and operating instruction manual reference "v71 of 9/11/2010" dated 9th	Wood logs ⁽¹⁾ .
Manufactured by Esse Engineering Ltd., Ouzledale Foundry, Long Ing, Barnoldswick, Lancashire, BB18 6BN.	November 2010.	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
ACR Astwood Multifuel stove AW1MF.	Instruction manual reference	Wood logs ⁽¹⁾ .
Manufactured by ACR Heat Products Ltd., Unit 1, Weston	"AW1MF 0101 Version 3" dated 28th January 2013.	
Works, Weston Lane, Tyseley, Birmingham, B11 3RP.	The appliance must be fitted with a mechanical stop to prevent the closure of the secondary air control lever beyond 12mm open position.	
Aduro 3D, 8D, 10D, 11D and Asgård 1D, 2D and 7D wood burning stoves.	Instruction manual reference "Pexex1001/AH/ver1" dated June 2011.	Dry wood logs ⁽¹⁾ .
Manufactured by Aduro AS, Beringvej 17, DK-8361, Hasselager, Denmark, and previously manufactured by Aduro A/S, Silkeborgvej 765 8220, Brabrand, Denmark.	The appliance must be fitted with permanent stops to ensure that the primary and secondary air controls do not close beyond 95% and 50% respectively.	
Aduro 9D wood burning stove. Manufactured by Aduro AS, Beringvej 17, DK-8361,	Instruction manual reference "Pevex1002/AH/ver1" dated June 2011.	Dry wood logs ⁽¹⁾ .
Hasselager, Denmark, and previously manufactured by Aduro A/S, Silkeborgvej 765 8220, Brabrand, Denmark.	The appliance must be fitted with permanent stops to ensure that the primary and secondary air controls do not close beyond 95% and 50% respectively.	
Aduro 15 and 15-1 6.5kW wood burning stoves.	Instruction manual reference "Version 1 – 2014-07" dated July 2014.	Wood logs ⁽¹⁾ .
Manufactured by Aduro AS, Beringvej 17, DK-8361, Hasselager, Denmark.	The appliance must be fitted with a permanent stop to prevent closure of the secondary air slider beyond the 55% open position.	
Aduro 16 5kW wood burning stove.	Instruction manual dated July 2015 and reference "Version 1	Wood logs ⁽¹⁾ .
	- Version 1	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

The fireplace must be No fuel is to be uninstalled, maintained and in the fireplace other to	Class of fireplace	Conditions	
Beringvej 17, DK-8361, Hasselager, Denmark. The appliance must be fitted with a permanent stop to prevent closure of the secondary air slider beyond the 67% open position AGA Dorrington SE 6kW slider beyond the 67% open position AGA Dorrington SE 6kW multi-fuel stove. Manufactured by AGA station Road, Ketley, Telford, Shropshire TF1 5AQ. AGA Ellesmere 6K Non Boiler SF Steel 5.9kW multi-fuel stove. Manufactured by AGA, Station Road, Ketley, Telford, Shropshire, TF1 5AQ Manufactured by AGA, Station Road, Ketley, Telford, Shropshire, TF1 5AQ AND OPERATING INSTALLATION AND OPERATING INSTRUCTIONS' dated 10th November 2015 reference "N00696AXX Rev:001 DP151110". The appliance must be fitted with a permanent stop to prevent closure of the secondary air control to maintain an opening of 922 mm² Aga Ellesmere 5K Non Boiler SF Steel 5.2kW multi-fuel stove. SF Steel 5.2kW multi-fuel stove. Wood logs(1). Wood logs(1). Wood logs(1). Wood logs(1).		installed, maintained and operated in accordance with the following specifications:	in the fireplace other than authorised fuels and the
Hasselager, Denmark. with a permanent stop to prevent closure of the secondary air slider beyond the 67% open position AGA Dorrington SE 6kW wood burning stove. Manufactured by AGA Rangemaster, Station Road, Ketley, Telford, Shropshire TF1 5AQ. The appliance must be fitted with a modified air control slider to prevent closure beyond the 7mm open position. AGA Ellesmere 6K Non Boiler SF Steel 5.9kW multi-fuel stove. AGA Ellesmere 6K Non Boiler SF Steel Stove (Smoke Exempt) INSTALLATION Manufactured by AGA, Station Road, Ketley, Telford, Shropshire, TF1 5AQ The appliance must be fitted with a modified air control slider to prevent closure beyond the 7mm open position. Wood logs(1). Wood logs(1). Wood logs(1). Wood logs(1). The appliance must be fitted with a permanent stop to prevent closure of the secondary air control to maintain an opening of 922 mm² Aga Ellesmere 5K Non Boiler SF Steel S.2kW multi-fuel stove. Fixed With a permanent stop to prevent closure of the secondary air control to maintain an opening of 922 mm² Wood logs(1).			
closure of the secondary air slider beyond the 67% open position AGA Dorrington SE 6kW wood burning stove. Manufactured by AGA Rangemaster, Station Road, Ketley, Telford, Shropshire TF1 5AQ. The appliance must be fitted with a modified air control slider to prevent closure beyond the 7mm open position. AGA Ellesmere 6K Non Boiler SF Steel 5.9kW multi-fuel stove. FS Steel 5.9kW multi-fuel stove. FS Steel 5.9kW multi-fuel stove. SF Steel 5.9kW multi-fuel stove. FS Steel 5.9kW multi-fuel stove. FS Steel 5.9kW multi-fuel SF Steel 5.2kW multi-fuel SF Steel 5.2kW multi-fuel SF Steel 5.2kW multi-fuel SF Steel 5.2kW multi-fuel SF Steel Stove (Smoke Exempt) INSTALLATION Wood logs(1). Wood logs(1). Wood logs(1).	Hasselager, Denmark.		
AGA Dorrington SE 6kW wood burning stove. Manufactured by AGA Rangemaster, Station Road, Ketley, Telford, Shropshire TF1 5AQ. AGA Ellesmere 6K Non Boiler SF Steel 5.9kW multi-fuel stove. Manufactured by AGA, Station Road, Ketley, Telford, Shropshire TF1 5AQ. AGA Ellesmere 6K Non Boiler SF Steel 5.9kW multi-fuel stove. AGA Ellesmere 6K Non Boiler SF Steel 5.9kW multi-fuel stove. AGA Ellesmere 6K Non Boiler SF Steel 5.9kW multi-fuel stove. AGA Ellesmere 6K Non Boiler SF Steel 5.9kW multi-fuel stove. AGA Ellesmere 6K Non Boiler SF Steel 5.9kW multi-fuel stove. AGA Ellesmere 5K Non Boiler SF Steel 5.9kW multi-fuel stove (Smoke Exempt) INSTALLATION AND OPERATING INSTRUCTIONS' dated 10th November 2015 reference "N00696AXX Rev:001 DP151110". The appliance must be fitted with a permanent stop to prevent closure of the secondary air control to maintain an opening of 922 mm² Aga Ellesmere 5K Non Boiler SF Steel 5.2kW multi-fuel stove. ELLESMERE 4K / SK / 6K Non Boiler SF Steel 5.2kW multi-fuel SF Steel 5.2kW multi-fuel stove. Wood logs (1). Wood logs (1). Wood logs (1).			
AGA Dorrington SE 6kW wood burning stove. Manufactured by AGA Rangemaster, Station Road, Ketley, Telford, Shropshire TF1 5AQ. AGA Ellesmere 6K Non Boiler SF Steel 5.9kW multi-fluel Shropshire, TF1 5AQ Manufactured by AGA, Station Road, Ketley, Telford, Shropshire, TF1 5AQ Aga Ellesmere 5K Non Boiler SF Steel 5.2kW multi-fluel Stove. Aga Ellesmere 5K Non Boiler SF Steel 5.2kW multi-fluel Stoye Character and properties of the secondary air control to maintain an opening of 922 mm² Aga Ellesmere 5K Non Boiler SF Steel 5.2kW multi-fluel SF Steel Stoye (Smoke Exempt) INSTALLATION Aga Ellesmere 5K Non Boiler SF Steel Stoye (Smoke Exempt) INSTALLATION Aga Ellesmere 5K Non Boiler SF Steel 5.2kW multi-fluel Stoye. SF Steel Stoye (Smoke Exempt) INSTALLATION Aga Ellesmere 5K Non Boiler SF Steel Stoye (Smoke Exempt) INSTALLATION Aga Ellesmere 5K Non Boiler SF Steel Stoye (Smoke Exempt) INSTALLATION		closure of the secondary air	
AGA Dorrington SE 6kW wood burning stove. Manufactured by AGA Rangemaster, Station Road, Ketley, Telford, Shropshire TF1 5AQ. AGA Ellesmere 6K Non Boiler SF Steel 5.9kW multi-fuel stove. Manufactured by AGA, Station Road, Ketley, Telford, Shropshire, TF1 5AQ Manufactured by AGA, Station Road, Ketley, Telford, Shropshire, TF1 5AQ Manufactured by AGA, Station Road, Ketley, Telford, Shropshire, TF1 5AQ Manufactured by AGA, Station Road, Ketley, Telford, Shropshire, TF1 5AQ Manufactured by AGA, Station Road, Ketley, Telford, Shropshire, TF1 5AQ Manufactured by AGA, Station Road, Ketley, Telford, Shropshire, TF1 5AQ Manufactured by AGA, Station Road, Ketley, Telford, Shropshire, TF1 5AQ Manufactured by AGA, Station Road, Ketley, Telford, Shropshire, TF1 5AQ Manufactured by AGA, Station Road, Ketley, Telford, Shropshire, TF1 5AQ Manufactured by AGA, Station Road, Ketley, Telford, Shropshire, TF1 5AQ Manufactured by AGA, Station Road, Ketley, Telford, Shropshire, TF1 5AQ Manufactured by AGA, Station Road, Ketley, Telford, Shropshire, TF1 5AQ Manufactured by AGA, Station Road, Ketley, Telford, Shropshire, TF1 5AQ Manufactured by AGA, Station Road, Ketley, Telford, Shropshire, TF1 5AQ Manufactured by AGA, Station Road, Ketley, Telford, Shropshire, TF1 5AQ Manufactured by AGA, Station Road Road, Manufactured by AGA, Station Road, Ketley, Telford, Shropshire Manufactured by AGA, Station Road, Ketley, Mood logs (1). The appliance must be fitted with a modified air control to Mood logs (1). The appliance must be fitted with a permanent stop to prevent closure of the secondary air control to maintain an opening of 922 mm² Mood		slider beyond the 67% open	
wood burning stove. Manufactured by AGA Rangemaster, Station Road, Ketley, Telford, Shropshire TF1 5AQ. AGA Ellesmere 6K Non Boiler SF Steel 5.9kW multi-fuel stove. Manufactured by AGA Station Road, Ketley, Telford, Shropshire, TF1 5AQ Manufactured by AGA, Station Road, Ketley, Telford, Shropshire, TF1 5AQ Manufactured by AGA, Station Road, Ketley, Telford, Shropshire, TF1 5AQ Manufactured by AGA, Station Road, Ketley, Telford, Shropshire, TF1 5AQ Manufactured by AGA, Station Road, Ketley, Telford, Shropshire, TF1 5AQ Manufactured by AGA, Station Road, Ketley, Telford, Shropshire, TF1 5AQ Manufactured by AGA, Station Road, Ketley, Telford, Shropshire, TF1 5AQ Manufactured by AGA, Station Road, Ketley, Telford, Shropshire, TF1 5AQ Movember 2015 reference "N00696AXX Rev:001 DP151110". The appliance must be fitted with a permanent stop to prevent closure of the secondary air control to maintain an opening of 922 mm² Aga Ellesmere 5K Non Boiler SF Steel 5.2kW multi-fuel stove. SF Steel Stove (Smoke Exempt) INSTALLATION		position	
Rangemaster, Station Road, Ketley, Telford, Shropshire TF1 5AQ. The appliance must be fitted with a modified air control slider to prevent closure beyond the 7mm open position. AGA Ellesmere 6K Non Boiler SF Steel 5.9kW multi-fuel stove. SF Steel Stove (Smoke Exempt) INSTALLATION AND OPERATING Shropshire, TF1 5AQ November 2015 reference "N00696AXX Rev:001 DP151110". The appliance must be fitted with a permanent stop to prevent closure of the secondary air control to maintain an opening of 922 mm² Aga Ellesmere 5K Non Boiler SF Steel S.2kW multi-fuel stove. SF Steel Stove (Smoke Exempt) INSTALLATION Wood logs(1). Wood logs(1). Wood logs(1). Wood logs(1). SF Steel Stove (Smoke Exempt) INSTALLATION		instructions, reference	Wood logs ⁽¹⁾ .
TF1 5AQ. fitted with a modified air control slider to prevent closure beyond the 7mm open position. AGA Ellesmere 6K Non Boiler SF Steel 5.9kW multi-fuel stove. SF Steel Stove (Smoke Exempt) INSTALLATION AND OPERATING Shropshire, TF1 5AQ November 2015 reference "N00696AXX Rev:001 DP151110". The appliance must be fitted with a permanent stop to prevent closure of the secondary air control to maintain an opening of 922 mm² Aga Ellesmere 5K Non Boiler SF Steel Stove (Smoke Exempt) INSTALLATION Wood logs(1).	Rangemaster, Station Road,	dated 16th July 2014	
SF Steel 5.9kW multi-fuel stove. SF Steel Stove (Smoke Exempt) INSTALLATION Manufactured by AGA, Station Road, Ketley, Telford, Shropshire, TF1 5AQ November 2015 reference "N00696AXX Rev:001 DP151110". The appliance must be fitted with a permanent stop to prevent closure of the secondary air control to maintain an opening of 922 mm² Aga Ellesmere 5K Non Boiler SF Steel 5.2kW multi-fuel stove. SF Steel Stove (Smoke Exempt) INSTALLATION SK / 6K Non Boiler SF Steel Stove (Smoke Exempt) INSTALLATION		fitted with a modified air control slider to prevent closure beyond the 7mm open	
Manufactured by AGA, Station Road, Ketley, Telford, Shropshire, TF1 5AQ November 2015 reference "N00696AXX Rev:001 DP151110". The appliance must be fitted with a permanent stop to prevent closure of the secondary air control to maintain an opening of 922 mm² Aga Ellesmere 5K Non Boiler SF Steel 5.2kW multi-fuel stove. "ELLESMERE 4K / 5K / 6K Non Boiler SF Steel Stove (Smoke Exempt) INSTALLATION Wood logs(1).	SF Steel 5.9kW multi-fuel	5K / 6K Non Boiler SF Steel Stove (Smoke	Wood logs ⁽¹⁾ .
fitted with a permanent stop to prevent closure of the secondary air control to maintain an opening of 922 mm² Aga Ellesmere 5K Non Boiler SF Steel 5.2kW multi-fuel stove. "ELLESMERE 4K / Wood logs(1). 5K / 6K Non Boiler SF Steel Stove (Smoke Exempt) INSTALLATION	Station Road, Ketley, Telford,	AND OPERATING INSTRUCTIONS" dated 10th November 2015 reference "N00696AXX Rev:001	
SF Steel 5.2kW multi-fuel 5K / 6K Non Boiler stove. SF Steel Stove (Smoke Exempt) INSTALLATION		fitted with a permanent stop to prevent closure of the secondary air control to maintain an opening of 922	
INSTRUCTIONS" dated 10th	SF Steel 5.2kW multi-fuel	5K / 6K Non Boiler SF Steel Stove (Smoke Exempt) INSTALLATION AND OPERATING	Wood logs ⁽¹⁾ .

The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives
or coatings.

Class of fireplace	Conditions	
Manufactured by Aga,	The fireplace must be installed, maintained and operated in accordance with the following specifications: November 2015 reference	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Station Road, Ketley, Telford, Shropshire, TF1 5AQ	"N00696AXX Rev:001 DP151110".	
	The appliance must be fitted with a permanent stop to prevent closure of the secondary air control to maintain an opening of 715 mm ²	
Aga Ellesmere 4K Non Boiler SF Steel 4.5kW multi-fuel stove. Manufactured by Aga, Station Road, Ketley, Telford, Shropshire, TF1 5AQ	"ELLESMERE 4K / 5K / 6K Non Boiler SF Steel Stove (Smoke Exempt) INSTALLATION AND OPERATING INSTRUCTIONS" dated 10th November 2015 reference "N00696AXX Rev:001 DP151110".	Wood logs ⁽¹⁾ .
	The appliance must be fitted with a permanent stop to prevent closure of the secondary air control to maintain an opening of 499 mm ²	
AGA Hadley SE 8kW wood burning stove. Manufactured by AGA Rangemaster, Station Road,	Installation and operating instructions reference "NOO645AXX Rev.001" dated 16th July 2014.	Wood logs ⁽¹⁾ .
Ketley, Telford, Shropshire TF1 5AQ.	The appliance must be fitted with a modified air control slider to prevent closure beyond the 5mm open position.	
AGA Hanwood SE 9kW wood burning stove. Manufactured by AGA Rangemaster, Station Road, Ketley, Telford, Shropshire TF1 5AQ.	Installation and operating instructions reference "NOO643AXX Rev.001" dated 17th July 2014.	Wood logs ⁽¹⁾ .

The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives
or coatings.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
AGA Lawley SE 4kW wood burning stove.	Installation and operating instructions reference "NOO646AXX Rev.001"	Wood logs ⁽¹⁾ .
Manufactured by AGA Rangemaster, Station Road,	dated 17th July 2014.	
Ketley, Telford, Shropshire TF1 5AQ.	The appliance must be fitted with a modified air control slider to prevent closure beyond the 4mm open position.	
AGA Shawbury SE 7kW wood burning stove. Manufactured by AGA	Installation and operating instructions reference "NOO642AXX Rev.001" dated 16th July 2014.	Wood logs ⁽¹⁾ .
Rangemaster, Station Road, Ketley, Telford, Shropshire TF1 5AQ.	The appliance must be fitted with a modified air control slider to prevent closure beyond the 6mm open position.	
AGA Westbury SE 6kW wood burning stove. Manufactured by AGA	Installation and operating instructions reference "NOO644AXX Rev.001" dated 15th July 2014.	Wood logs ⁽¹⁾ .
Rangemaster, Station Road, Ketley, Telford, Shropshire TF1 5AQ.	The appliance must be fitted with a modified air control slider to prevent closure beyond the 35mm open position.	
AGA Wren Non Boiler 4.8kW Multi-fuel stove.	"AGA Wren Non Boiler Stove (Smoke Exempt) INSTALLATION	Wood logs ⁽¹⁾ .
Manufactured by AGA, Station Road, Ketley, Telford, Shropshire, TF1 5AQ	AND OPERATING INSTRUCTIONS" dated 10th November 2015 reference "N00698AXX Rev:001 DP151110".	
	The appliance must be fitted with a permanent stop to prevent closure of the secondary air control to	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
	maintain an opening of 510 mm ²	
Alberg 7. Manufactured by Elite Group	Instruction manual reference "EGTL03A Version 1.4" dated 21st December 2012.	Wood logs ⁽¹⁾ .
Trading Ltd., Room 1208, Kak Tak Commercial Building, 317-319 Des Voeux Road Central, Hong Kong, 999077.		
Alpha I model number AL905- SE Wood Burning Stove. Manufactured by Hi-Flame	Instruction manual reference "HF277-SE/UK-NI-ROI/ V2D.18-07-12" dated July 2012.	Wood logs ⁽¹⁾ .
Fireplace UK Ltd., Unit 5A, Holmes Chapel Business Park, Manor Lane, Holmes Chapel, Cheshire, CW4 8AF.	The appliance must be fitted with a mechanical stop to prevent closure of the main air control beyond the 50% open position.	
Alpha II model number AL907-SE Wood Burning Stove.	Instruction manual reference "AL907-SE/UK-NI-ROI/V3-D.14-07-12" dated July 2012.	Wood logs ⁽¹⁾ .
Manufactured by Hi-Flame Fireplace UK Ltd., Unit 5A, Holmes Chapel Business Park, Manor Lane, Holmes Chapel, Cheshire, CW4 8AF.	The appliance must be fitted with a mechanical stop to prevent secondary air control closure beyond the 20% open position, and a 70mm opening of the door rope seal to allow a constant flow of air.	
Andalo 2, Lovero 2, Solaro 2 6.7 kW multifuel stoves.	Instructions manual reference "Instructions: Installation, Operation, Function,	Wood Logs ⁽¹⁾ .
Manufactured by Drooff Kaminöfen GmbH & Co. KG, Drooff Kaminöfen GmbH & Co. KG, Keffelker Str. 40 D-59929 Brilon, Germany	Maintenance" and Technical information dated July 2015 reference "Andalo 2–Lovero 2–Solaro 2, Technical data" version SDK/0715	
D-37727 Billoll, Octilially	The appliance must be fitted with a mechanical stop to prevent closure of the air	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
	control beyond the 50% open position	
Andorra model F9489, Sevilla model F9489 V, Delia model F9489 A, Cadiz model F9489 C, Rodano model F9489 P,	Installation and Operation Manual dated 27th July 2015 reference "ANDORRA – Version A"	Wood logs ⁽¹⁾ .
Atika model F9489 D,	The appliance must be fitted with a modified air regulator	
Zion Keramik model F9489 K,	which has a permanent opening of 620mm2 when in	
Zion Serpentino model F9489 F, Andorra Exclusive model F9489 O and, Toledo model F9489 I 5kW multifuel stoves.	the fully closed position.	
Manufactured by THORMA Vyroba k.s., Šavoľská cesta 323/1, 986 01,		
Fil'akovo-Priemyselný obvod,		
Slovakia		
Angus Orligno 200 18kW, 25kW, 40kW, 60kW and 80kW gasification boilers.	Instruction manual reference "EV-20111002" dated October 2011.	Wood logs ⁽¹⁾ .
Manufactured by Eko-Vimar Orlanski Spółka z ograniczoną odpowiedzialnością, ul. Nyska 17 b, 48-385 Otmuchów, Poland.		
Angus Orligno 500 7-25kW boiler.	Instruction manual reference "EV 20121003" dated 3rd October 2012.	Wood pellets ⁽¹⁾ .
Manufactured by Eko-Vimar Orlanski Spółka z ograniczoną odpowiedzialnością, ul. Nyska 17 b, 48-385 Otmuchów, Poland.		
Angus Super 18, 25, 40, 60 and 80kW gasification boilers.	Instruction manual reference "EV- 20111001" dated October 2011.	Wood logs ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Manufactured by Eko-Vimar Orlanski Spółka z ograniczoną odpowiedzialnością, ul. Nyska 17 b, 48-385 Otmuchów, Poland.		
Angus Super 96 and 130kW gasification boilers.	Instruction manual reference "EV- 20131002" dated October 2013.	Wood logs ⁽¹⁾ .
Manufactured by Eko-Vimar Orlanski, Spólka z ograniczona odpowiedzialnoscia, ul. Nyska 17 b, 48-385 Otmuchów, Poland.		
Apollo 8 Inset stove. Manufactured by Chesneys	Instruction manual reference "CH8K Apollo – V2" dated 31st October 2011.	Wood logs ⁽¹⁾ .
Ltd., 194-200 Battersea Park Road, London, SW11 4ND.	The appliance must be fitted with a system that prevents closure of the air controls further than 40mm from open.	
Aquila 450 Contemporary, Corvus 450 Traditional, Corvus 450 Contemporary and, Vega 450 Traditional 4.5kW multifuel inset stoves.	Instruction manual dated 28th July 2015, reference: "Aquila 450 / Corvus 450 / Vega 450 Solid Fuel Stoves Manual Version 1.1 Issued 28/07/2015	Wood Logs ⁽¹⁾ .
Manufactured by F.E.Robinson(Hooton)Limited,	Inset Versions Supplement"	
Station Works, Hooton Road,		
Hooton, South Wirral,		
CH66 7NF		
Arimax Bio 300kW, Arimax Bio 400kW and Arimax Bio 500kW.	Instruction manual reference "Installation and Operation Manual Arimax Bio 120-3000kW" dated 30th	6-8mm wood pellets with a moisture content less than 10% (1).
Manufactured by Artierm Oy, Kimmo Kantalainen, PO Box 59, Fin – 43101, Saarijärvi, Finland.	March 2010.	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Ariterm Arimax Bio – 999kW Boiler with Ariterm Multijet 999kW burner fitted with cyclone. Manufactured by Ariterm Oy, PO Box 59 Fin – 43101, Saarijarvi, Finland	Ariterm Arimax Bio 120-3000 kW Installation and operation manual dated 05/10/2015 reference "05.10.2015 Version 1", and Ariterm Multijet 500-1500 hydraulic burner. Installation, operation and maintenance manual dated 05/10/2015 reference "06.05.2014".	Wood chips ⁽¹⁾ .
Ariterm BioCompPX boiler and PX52 pellet burner and Ariterm BioCompPX Ultra- light boiler and PX52 pellet burner.	Instruction manual reference "Ariterm-SP-PX28327.1" dated 6th November 2014.	Wood pellets ⁽¹⁾ .
Manufactured by Ariterm Sweden AB, Flottijvagen 15, 392 41 KALMAR, Sweden Limited.		
Ariterm Ekerum 6kW pellet stove and Neptuni 6kW pellet stove.	Instruction manual reference "ARITERM-SP-PX26868-B.2" dated 15th December 2011.	Wood pellets ⁽¹⁾ .
Manufactured by Ariterm Sweden AB, Flottiljvägen 15, 392 41 Kalmar, Sweden.		
Ariterm Mysinge 6kW pellet stove.	Instruction manual reference "ARITERM-SP-PX26868-B.1" dated 15th December	Wood pellets ⁽¹⁾ .
Manufactured by Ariterm Sweden AB, Flottiljvägen 15, 392 41 Kalmar, Sweden.	2011.	
Arizona Stoves Crete inset multi-fuel stove.	Operation and installation manual reference "Version A (MZSCRE5SE)" dated 24th	Wood logs ⁽¹⁾ .
Manufactured by Micon Distribution Ltd., 1a Hallstown	November 2014.	
Road, Ballinderry Upper, Lisburn BT28 2NE.	The appliance must be fitted with a mechanical stop to prevent secondary air control closure beyond the 75% open position.	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

	G 1: :	
Class of fireplace	Conditions	No. Co. 1 in the land of the control
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Arte 1Vh 66 – A – P3, Arte 1Vh 66 – A1 – P3, Arte 1Vh 66 X – A – P3 and, Arte 1Vh 66 X – A1 – P3 6.6kW wood	Instruction manual dated September 2014 reference "Version 09 / 2014"	Wood Logs ⁽¹⁾ .
burning inset roomheaters.	The appliance must be fitted with a mechanical stop to	
Manufactured by Spartherm Feuerungstechnik GmbH, Maschweg 38, 49324 Melle, Germany	prevent closure of the air control beyond the 8mm open position	
Arte 2LRh 66 - A - P3 and, Arte 2LRh 66 - A1 - P3 12kW wood burning inset roomheaters.	Instruction manual dated July 2015 reference "Version 07 / 2015"	Wood Logs ⁽¹⁾ .
Manufactured by Spartherm Feuerungstechnik GmbH, Maschweg 38, 49324 Melle, Germany	The appliance must be fitted with a mechanical stop to prevent closure of the air control beyond the 14mm open position	
Ashdale FB2MF 7kW multifuel stove.	Technical manual dated 13th May 2015 reference "Document FB2MF 0101	Wood logs ⁽¹⁾ .
Manufactured by ACR Heat Products Ltd, Unit 1 Weston	Version 3"	
Works, Weston Lane, Tyseley, Birmingham, B11 3RP	The appliance must be fitted with a mechanical stop to prevent closure of the secondary air slider beyond the	
	12mm open position and, the tertiary air control will be fixed in the 50% open position.	
Ashwell Green-Tec 150 boiler.	Instruction manual reference "ASH-gt150/101 Version 1.2"	Wood pellets ⁽¹⁾ .
Manufactured by Ashwell Biomass Ltd., Unit 12, 35 Pinfold Road, Thurmaston, Leicester, LE4 8AT.	dated June 2009.	
Ashwell Green-Tec 195 boiler.	Instruction manual reference "ASH-gt195/102 Version 1.2"	Wood pellets (1).
Manufactured by Ashwell Biomass Ltd., Unit 12, 35 Pinfold Road, Thurmaston, Leicester, LE4 8AT.	dated June 2009.	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Ashwell Green-Tec 300 boiler. Manufactured by Ashwell Biomass Ltd., Unit 12, 35 Pinfold Road, Thurmaston, Leicester, LE4 8AT.	Instruction manual reference "ASH-gt300/103 Version 1.2" dated June 2009.	Wood pellets ⁽¹⁾ .
ATOM 198kW boiler and cyclone. Manufactured by Uniconfort srl, Via dell'Industria 21, 35018, San Martino Di Lupari, (PD), Italy.	Operating and maintenance instruction manual reference "2.1114.00 – EN Release 1.1" dated July 2014.	Wood chips or wood pellets ⁽¹⁾ .
Avalon 4 stove. Manufactured by Hunter Stoves Ltd., Trevilla Park, Slaughterbridge, Camelford, Cornwall, PL32 9TT.	Instruction manual reference "JINAV04 Rev C" dated 13th June 2012. The appliance must be fitted with a permanent stop that prevents closure of the secondary air slider beyond 30% open.	Wood logs ⁽¹⁾ .
Avalon 5 Slimline stove. Manufactured by Hunter Stoves Ltd., Trevilla Park, Slaughterbridge, Camelford, Cornwall, PL32 9TT.	Instruction manual reference "JINAVS05 Rev C" dated 13th June 2012.	Wood logs ⁽¹⁾ .
Avalon 6 stove. Manufactured by Hunter Stoves Ltd., Trevilla Park, Slaughterbridge, Camelford, Cornwall, PL32 9TT.	Instruction manual reference "JINAVA06 Rev C" dated 13th June 2012.	Wood logs ⁽¹⁾ .
Avalon Compact 5 stove. Manufactured by Hunter Stoves Ltd., Trevilla Park, Slaughterbridge, Camelford, Cornwall, PL32 9TT.	Instruction manual reference "JINAVC05 Rev C" dated 13th June 2012. The appliance must be fitted with a permanent stop that prevents closure of the	Wood logs ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications: secondary air slider beyond 30% open.	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Avalon Slimline 8 stove. Manufactured by Hunter Stoves Ltd., Trevilla Park, Slaughterbridge, Camelford, Cornwall, PL32 9TT.	Instruction manual reference "JINAVS08 Rev B" dated 27th June 2012.	Wood logs ⁽¹⁾ .
Barbas Cuatro-3 57 Inset appliance. Manufactured by Interfocos BV, Hallenstraat 17, 5531 AB, Bladel, The Netherlands.	Installation instructions and manual for annual maintenance reference "01-333659" dated 15th June 2013 and instructions for use & maintenance manual reference "01-333655" dated 15th June 2013. The appliance must be fitted	Wood logs ⁽¹⁾ .
	with a redesigned air slide equivalent to a minimum closure position of 23.5 cm of the type-tested prototype appliance.	
Barbas Cuatro-3 70 Inset appliance. Manufactured by Interfocos BV, Hallenstraat 17, 5531 AB Bladel, The Netherlands.	Installation instructions and manual for annual maintenance reference "03-336146" dated 26th May 2014 and instructions for use and maintenance manual reference "03-336145" dated 27th May 2014.	Wood logs ⁽¹⁾ .
	The appliance must be fitted with an air slide which has a circular opening of 32mm diameter (800 mm ² area) so as to provide air supply when the air slide is fully closed.	
Barbas Cuatro-3 75 Inset appliance.	Installation instructions and manual for annual maintenance reference "01-333861" dated 15th June 2013 and instructions for use &	Wood logs ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
Manufactured by Interfocos BV, Hallenstraat 17, 5531 AB, Bladel, The Netherlands.	The fireplace must be installed, maintained and operated in accordance with the following specifications: maintenance manual reference "01-333855" dated 15th June 2013.	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Barbas Cuatro-3 80 Inset appliance. Manufactured by Interfocos BV, Hallenstraat 17, 5531 AB Bladel, The Netherlands.	Installation instructions and manual for annual maintenance dated reference "03-335878" dated 26th May 2014 and instructions for use and maintenance manual reference "03-335877" dated 26th May 2014. The appliance must be fitted with an air slide which has a circular opening of 32mm diameter (800 mm² area) so as to provide air supply when the air slide is fully closed.	Wood logs ⁽¹⁾ .
Barbas Cuatro-3 90 Inset appliance. Manufactured by Interfocos BV, Hallenstraat 17, 5531 AB, Bladel, The Netherlands.	Installation instructions and manual for annual maintenance reference "01-332965" dated 15th June 2013 and instructions for use and maintenance manual reference "01-332875" dated 10th June 2013.	Wood logs ⁽¹⁾ .
Barbas ECO 40, 5kW wood burning roomheater. Manufactured by Interfocos BV, Hallenstraat 17, 5531 AB, Bladel, The Netherlands.	Instruction manual reference "Version 01-327332" dated October 2009.	Wood logs ⁽¹⁾ .
Barbas ECO 52 Stove. Manufactured by Interfocos BV, Hallenstraat 17, 5531 AB, Bladel, The Netherlands.	Instruction manual reference "02 - 327332" dated March 2010.	Wood logs ⁽¹⁾ .
Barbas ECO-55 stove appliance. Manufactured by Interfocos BV, Hallenstraat 17, 5531 AB, BLADEL, The Netherlands.	Installation instructions manual and directions for use reference "03-334744" dated January 2014.	Wood logs ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications: The appliance must be fitted with an air valve incorporating seven rectangular holes of dimension 24 x 20 mm and marked 'UK55'.	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Barbas EVO 80-65 Inset appliance. Manufactured by Interfocos BV, Hallenstraat 17, 5531 AB, BLADEL, The Netherlands.	Installation instructions and manual for annual maintenance reference "02-334801" dated 20th May 2014 and instructions for use and maintenance manual reference "02-334744" dated 20th May 2014.	Wood logs ⁽¹⁾ .
	The appliance must be fitted with an air slide which has a circular opening of 30mm diameter (700mm ² area) so as to provide air supply when the air slide is fully closed.	
Barbas EVO 100-50 Inset appliance. Manufactured by Interfocos BV, Hallenstraat 17, 5531 AB, BLADEL, The Netherlands.	Installation instructions and manual for annual maintenance reference "02-336024" dated 20th May 2014 and instructions for use and maintenance manual reference "02-336020" dated 20th May 2014.	Wood logs ⁽¹⁾ .
	The appliance must be fitted with an air slide which has a circular opening of 30mm diameter (700mm² area) so as to provide air supply when the air slide is fully closed.	
Barbas Unilux 3-40, 5kW wood burning insert. Manufactured by Interfocos BV, Hallenstraat 17, 5531 AB, Bladel, The Netherlands.	Instruction manual reference "Version 01 – 326587" dated August 2009.	Wood logs ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

C1	C 1:4:	
Class of fireplace	Conditions The fireplace must be installed, maintained and	No fuel is to be used in the fireplace other than
	operated in accordance with the following specifications:	authorised fuels and the following fuel or fuels:
Barbas Unilux 3-52 Stove.	Instruction manual reference "03 - 326587" dated March	Wood logs ⁽¹⁾ .
Manufactured by Interfocos BV, Hallenstraat 17, 5531 AB, Bladel, The Netherlands.	2010.	
Barbas Unilux-3 55 Inset appliance.	Installation instructions and directions for use manual reference "05-326587" dated	Wood logs ⁽¹⁾ .
Manufactured by Interfocos BV, Hallenstraat 17, 5531 AB,	January 2014.	
BLADEL, The Netherlands.	The appliance must be fitted with an air valve incorporating seven rectangular holes of dimension 24 x 20 mm and	
	marked 'UK55'.	
Barbas Unilux-3 65 Inset appliance.	Installation instructions and directions for use manual reference "05-326587" dated	Wood logs ⁽¹⁾ .
Manufactured by Interfocos BV, Hallenstraat 17, 5531 AB,	January 2014.	
BLADEL, The Netherlands.	The appliance must be fitted with an air valve incorporating seven rectangular holes of dimension 24 x 20 mm and marked 'UK65'.	
Barbas Unilux-6 40 5kW wood-burning Inset appliance.	Instructions for use & Maintenance Manual dated 12th October 2015 reference	Wood logs ⁽¹⁾ .
Manufactured by Interfocos BV, Hallenstraat 17, NL-5531	"Version number: 01-340650".	
AB, BLADEL, Netherlands.	The appliance must be fitted with an air slider which has a permanent opening of 530 mm2 so as to provide air supply when the air slider is fully closed	
Barbas Unilux-6 52 8kW wood-burning Inset appliance.	Instructions for use & Maintenance Manual dated 12th October 2015 reference	Wood logs ⁽¹⁾ .
Manufactured by Interfocos BV, Hallenstraat 17, NL-5531 AB, BLADEL, Netherlands.	"Version number: 01-340443". The appliance must be fitted with an air slider which has	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
	a permanent opening of 530 mm2 so as to provide air supply when the air slider is fully closed	
Barbas Unilux-6 55 9kW wood-burning Inset appliance.	Instructions for use & Maintenance Manual dated 12th October 2015 reference	Wood logs ⁽¹⁾ .
Manufactured by Interfocos BV, Hallenstraat 17, NL-5531 AB, BLADEL, Netherlands.	"Version number: 01-340859".	
Barbas Unilux-6 65 8kW wood-burning Inset appliance.	Instructions for use & Maintenance Manual dated 12th October 2015 reference	Wood logs ⁽¹⁾ .
Manufactured by Interfocos BV, Hallenstraat 17, NL-5531 AB, BLADEL, Netherlands.	"Version number: 01-340184".	
Barbas Universal-6 60 9 kW inset roomheater. Manufactured by Interfocos BV, Hallenstraat 17, NL-5531, AB, BLADEL, Netherlands.	Barbas Universal-6 60 installation instructions dated 30 March 2015 reference "01 - 339664". Barbas Universal-6 60 instructions manual dated 30 March 2015 reference "01 – 339660".	Wood logs ⁽¹⁾ .
	The appliance must be fitted with an air slider which has a permanent circular opening of 27 mm diameter (570 mm2) so as to provide air supply when the air slider is fully closed.	
Barbas Universal-6 65 9 kW inset roomheater.	Barbas Universal-6 65 installation instructions dated 30 March 2015 reference "01	Wood logs ⁽¹⁾ .
Manufactured by Interfocos BV, Hallenstraat 17, NL-5531, AB, BLADEL, Netherlands.	- 339764". Barbas Universal-6 65 instructions manual dated 30 March 2015 reference "01 – 339760"	
	The appliance must be fitted with an air slider which has a permanent circular opening of 27 mm diameter (570 mm2)	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fundas	Canditions	
Class of fireplace	Conditions The fireplace must be	No fuel is to be used
	installed, maintained and operated in accordance with the following specifications:	in the fireplace other than authorised fuels and the following fuel or fuels:
	so as to provide air supply when the air slider is fully closed.	
Barbas Universal-6 70 9 kW inset roomheater. Manufactured by Interfocos BV, Hallenstraat 17, NL-5531, AB, BLADEL, Netherlands.	Barbas Universal-6 70 installation instructions dated 30 March 2015 reference "01 - 338117". Barbas Universal-6 70 instructions manual dated 30 March 2015 reference "01 - 338113".	Wood logs ⁽¹⁾ .
	The appliance must be fitted with an air slider which has a permanent circular opening of 27 mm diameter (570 mm2)	
	so as to provide air supply when the air slider is fully closed.	
Barbas Universal-6 75 10 kW inset roomheater. Manufactured by Interfocos BV, Hallenstraat 17, NL-5531, AB, BLADEL, Netherlands.	Barbas Universal-6 75 installation instructions dated 30 March 2015 reference "01 - 339319". Barbas Universal-6 75 instructions manual dated 30 March 2015 reference "01 - 339315".	Wood logs ⁽¹⁾ .
	The appliance must be fitted with an air slider which has a permanent circular opening of 27 mm diameter (570 mm2)	
	so as to provide air supply when the air slider is fully closed.	
Barbas Universal-6 80 12 kW inset roomheater. Manufactured by Interfocos	Barbas Universal-6 80 installation instructions dated 30 March 2015 reference "01 - 338396". Barbas	Wood logs ⁽¹⁾ .
ivianuraciureu by interrocos	220270 . Datuas	
BV, Hallenstraat 17, NL-5531, AB, BLADEL, Netherlands.	Universal-6 80 instructions manual dated 30 March 2015 reference "01 - 338392".	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications: The appliance must be fitted with an air slider which has a permanent circular opening of 27 mm diameter (570 mm2) so as to provide air supply when the air slider is fully closed.	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Barbas Universal-6 85 12 kW inset roomheater. Manufactured by Interfocos BV, Hallenstraat 17, NL-5531, AB, BLADEL, Netherlands.	Barbas Universal-6 85 installation instructions dated 30 March 2015 reference "01 - 339439". Barbas Universal-6 85 instructions manual dated 30 March 2015 reference "01 - 339435". The appliance must be fitted with an air slider which has a permanent circular opening of 27 mm diameter (570 mm2) so as to provide air supply when the air slider is fully closed.	Wood logs ⁽¹⁾ .
Bari C.11 wood burning stove. Manufactured by Hase Kaminofenbau GmbH, Niederkircher Strasse 14, D-54294 Trier.	Instruction manual reference "Bari_R1" dated November 2014. The appliance must be fitted with a mechanical stop to prevent air control closure beyond the 42mm open position.	Wood logs ⁽¹⁾ .
Baxi Bioflo. Manufactured by Windhager Zentralheizung GmbH, Anton- Windhager-Str. 20, A-5201 Seekirchen bei Salzburg, Austria.	Operating instruction manual reference "720574401" dated 2010 and installation and servicing instruction manual reference "720574501" dated 2010.	Wood pellets ⁽¹⁾ .
Be Modern Monroe 5, Monroe 5, Be Modern Monterrey 5,	Instruction manual reference "OCT10/GB" dated 6th October 2010.	Wood logs ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fivenland	Conditions	
Class of fireplace	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Monterrey 5 and York Midi Multi Fuel Stoves.	The appliance must be fitted with a system that prevents the closure of the secondary air	Jenening Julie Lynna.
Manufactured by Broseley Fires Ltd., Knights Way, Battlefield Enterprise Park, Shrewsbury, Shropshire, SY1 3AB.	flaps to less than 8mm open position.	
Bella UK model 14980000,	Instruction manual dated July 2015, reference "Installation	Wood logs ⁽¹⁾ .
Bella UK without Sideglass model 14980100, Bella High UK model 14981000 and,	and Operating manual Revision 1, 23-07-2015"	
Bella High without Sideglass UK model 14981500 5kW	The appliance must be modified	
woodburning stoves.	to fix the secondary air control	
Manufactured by Jydepejsen	to 1300mm2 in its minimum position	
A/S, Ahornsvinget 3-7, Nr	position	
Felding, DK-7500, Holstebro,		
Denmark		
Be Modern Monterrey 7, Monterrey 7, Be Modern Monroe 7 and Monroe 7 Multi Fuel Stoves.	Instruction manual reference "OCT10/GB" dated 6th October 2010.	Wood logs ⁽¹⁾ .
Manufactured by Broseley Fires Ltd., Knights Way, Battlefield Enterprise Park, Shrewsbury, Shropshire, SY1 3AB.	The appliance must be fitted with a system that prevents the closure of the secondary air flaps to be less than 10mm open position.	
Berkeley SE multifuel stove and Berkeley SE multifuel stove with stoveasy grate.	Instruction manual reference "NS 7 Issue 1" dated 8th January 2014.	Wood logs ⁽¹⁾ .
Manufactured by Newman Fireplaces Limited, Unit 6 & 7 Rawreth Barns, Dollymans Farm, Doublegate Lane,	The tertiary air control must be fully open when burning wood.	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Rawreth, Wickford, Essex, SS11 8UD.		
Binder Wood Fired Boiler models RRK 22 – 49 (49kW output). Manufactured by Binder Gesellschaft mit beschränkter Haftung (GmbH) Mitterdorfer Strasse 5, A-8572 Barnbach, Austria.	Installation, commissioning and maintenance manual reference "WELBinderManual rev0.doc, revision 0" dated 17th May 2005.	Wood pellets or wood chips (1).
Binder Wood Fired Boiler models RRK 80 – 175 (75 – 149kW output) with cyclone models ZA 80 – 175. Manufactured by Binder Gesellschaft mit beschränkter Haftung (GmbH) Mitterdorfer Strasse 5, A-8572 Barnbach, Austria.	Installation, commissioning and maintenance manual reference "WELBinderManual rev0.doc, revision 0" dated 17th May 2005.	Wood pellets or wood chips ⁽¹⁾ .
Binder Wood Fired Boiler model RRK 130 – 250 (185 - 230kW output) 200-350 (250-300kW output) 400-600 (350-500kW output) 640-850 (650-840kW output) with cyclone (model type ZA). Manufactured by Binder Gesellschaft mit beschränkter Haftung (GmbH) Mitterdorfer Strasse 5, A-8572 Barnbach, Austria.	Installation, commissioning and maintenance manual reference "WELBinderManual rev0.doc, revision 0" dated 17th May 2005.	Wood pellets or wood chips ⁽¹⁾ .
Binder Wood Fired Boiler model RRK 1000 (1200kW output) with multi-cyclone (model MZA). Manufactured by Binder Gesellschaft mit beschränkter Haftung (GmbH) Mitterdorfer	Installation, commissioning and maintenance manual reference "WELBinderManual rev0.doc, revision 0" dated 17th May 2005.	Wood pellets or wood chips ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Strasse 5, A-8572 Barnbach, Austria.		
Binder Wood Fired Boiler model RRK 1200-1650 with Binder model MZA multi- cyclone and automatic ignition. Manufactured by Binder Gesellschaft mit beschränkter Haftung (GmbH) Mitterdorfer	Operating instructions reference "2009 July Binder O&M revision 8.doc Operation and Maintenance Manual, revision 8" dated 15th July 2009.	Wood pellets or wood chips (1).
Strasse 5, A-8572 Barnbach, Austria.		
The Binder Wood Fired Boiler model RRK 1800-2300 with Binder model MZA multicyclone and automatic ignition.	Operating instructions reference "2009 July Binder O&M revision 8.doc Operation and Maintenance Manual, revision 8" dated 15th July	Wood pellets or wood chips ⁽¹⁾ .
Manufactured by Binder Gesellschaft mit beschränkter Haftung (GmbH) Mitterdorfer Strasse 5, A-8572 Barnbach, Austria.	2009.	
Binder Wood Fired Boiler model RRK 2500-3000 with Binder model MZA multi- cyclone and automatic ignition.	Operating instructions reference "2009 July Binder O&M revision 8.doc Operation and Maintenance Manual, revision 8" dated 15th July 2009.	Wood pellets or wood chips ⁽¹⁾ .
Manufactured by Binder Gesellschaft mit beschränkter Haftung (GmbH) Mitterdorfer Strasse 5, A-8572 Barnbach, Austria.		
Bioclass NG 10, NG 16,	Installation and operating	Wood pellets ⁽¹⁾ .
NG 25 and NG 43 wood pellet boilers.	Instructions manual reference "CDOC000682" dated July 2014.	
Manufactured by		
Domusa S.Coop		
B° San Esteban s/n		

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
20737, Errezil, Spain.		, , ,
Bioflame 15 Slim Wood Pellet Boiler.	Installation and operation manual reference "V.1.1" dated June 2014.	Wood pellets ⁽¹⁾ .
Manufactured by Wood Energy Solutions Limited, Donaskeigh, Tipperary, Co. Tipperary, Ireland.		
Biokaitra BIO models 30 and 50 pellet boilers.	Instruction manual version 1 reference "User manual, User	Wood pellets ⁽¹⁾ .
Manufactured by UAB Biokaitra, Šv. Stepono 27, LT-01312, Vilnius, Lithuania.	guide, Installation, Use and Maintenance of the Boiler" dated November 2013.	
Biomatic +20 boiler.	Instruction manual reference "ARITERM-VTT-	Wood pellets ⁽¹⁾ .
Manufactured by Ariterm, Sweden AB, Flottiljvägen 15, 392 41 Kalmar, Sweden.	S-07229-11.1" dated 21st May 2012.	
Biomatic +20 light boiler and Biomatic +20 ultra light boiler.	Instruction manual reference "ARITERM-VTT-S-07229-11.2" dated 21st May	Wood pellets ⁽¹⁾ .
Manufactured by Ariterm, Sweden AB, Flottiljvägen 15, 392 41 Kalmar, Sweden.	2012.	
Biomatic +40 boiler.	Instruction manual reference "ARITERM-VTT-	Wood pellets ⁽¹⁾ .
Manufactured by Ariterm, Sweden AB, Flottiljvägen 15, 392 41 Kalmar, Sweden.	S-06765-11.1" dated 21st May 2012.	
Biomatic +40 light boiler and Biomatic +40 ultra light boiler.	Instruction manual reference "ARITERM-VTT-S-06765-11.2" dated 21st May	Wood pellets ⁽¹⁾ .
Manufactured by Ariterm, Sweden AB, Flottiljvägen 15, 392 41 Kalmar, Sweden.	2012.	
Biomatic 220 and 250 fitted with Zyklovent 220-250 cyclone separator.	Manufacturer's instructions reference "Bedienungsanleitung Englisch v2.0 doc." dated	Wood chips, wood pellets, or planed wood shavings ⁽¹⁾ .
Manufactured by HERZ Armaturen Ges.m.b.H,	April 2005.	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Richard-Strauss-Straße 22, A-1230 Wien, Austria.		
Biomatic 300, 350, 400 and 500 fitted with Zyklovent 300-500 cyclone separator. Manufactured by HERZ Armaturen Ges.m.b.H, Richard-Strauss-Straße 22, A-1230 Wien, Austria.	Manufacturer's instructions reference "Bedienungsanleitung Englisch v2.0 doc." dated April 2005.	Wood chips, wood pellets, or planed wood shavings ⁽¹⁾ .
Biotech Top Light, Top Light M, Top Light M MBW, PZ8RL, PZ25RL and PZ35RL wood pellet boilers. Manufactured by Biotech Energietechnik GmbH, Mayrwiesstrasse 125300 Hallwang bei Salzburg, Austria.	Instruction manual reference "Top Light/Top Light M/ Top Light M/MBW/PZ8RL/ PZ25RL/PZ32RL/PZ35RL Version 9400000100030 06/13 ENG" dated June 2013.	Wood pellets ⁽¹⁾ .
BioWIN2 wood pellet boilers models: BWE 102, BWK 102, BWP 102, BWE 152, BWK 152, BWF 152, BWF 212, BWK 212, BWF 212, BWF 262, BWK 262 and BWP 262. Manufactured by Windhager Zentralheizung GmbH, Anton-Windhager- Str. 20, A-5201 Seerkirchen bei Salzburg, Austria	Operating Manual BioWIN 2 dated July 2015 reference "093406/03" Assembly instructions BioWIN 2 dated July 2015 references "093403/04"	Wood Pellets ⁽¹⁾ .
BLISS Ariel 5S & 5G 5kW Inset multi-fuel Stoves. Manufactured by Tile Tec Fireplaces Limited Private Road 2, Colwick Industrial Estate, Colwick, Nottingham	Installation and Operating Instructions dated 04/15 reference "BLISS Inserts Issue 01" Fitted with a mechanical stop to prevent secondary air control closure beyond the 50% open position	Wood logs ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

	C 1:.:	
Class of fireplace	Conditions The fireplace must be installed, maintained and	No fuel is to be used in the fireplace other than
	operated in accordance with the following specifications:	authorised fuels and the following fuel or fuels:
NG4 2JR		
BLISS TFG 5 5kW	Installation and Operating	Wood logs ⁽¹⁾ .
Freestanding wood burning Stove.	Instructions dated 04/15 reference "TFG Stoves BLISS Issue 01"	
Manufactured by Tile Tec Fireplaces Limited	Fitted with a mechanical stop to prevent secondary air	
Private Road 2,	control closure beyond the 50% and Primary air control	
Colwick Industrial Estate, Colwick, Nottingham	beyond the 10% open positions	
NG4 2JR		
BLISS TFG 8 8kW Freestanding wood burning Stove.	Installation and Operating Instructions dated 04/15 reference "TFG Stoves BLISS Issue 01"	Wood logs ⁽¹⁾ .
Manufactured by Tile Tec Fireplaces Limited	Fitted with a mechanical stop to prevent secondary air	
Private Road 2,	control closure beyond the 25% open position	
Colwick Industrial Estate, Colwick, Nottingham		
NG4 2JR		
BLISS Charon 10S & 10G 10kW Inset multi-fuel Stoves.	Installation and Operating Instructions dated 04/15 reference "BLISS Inserts Issue	Wood logs ⁽¹⁾ .
Manufactured by Tile Tec Fireplaces Limited	01" Fitted with a mechanical	
Private Road 2,	stop to prevent secondary air control closure beyond the	
Colwick Industrial Estate, Colwick, Nottingham	10% open position	
NG4 2JR		
Bohemia X40 Xtra wide 5.5kW multifuel stove	Installation and Operating Instructions for Bohemia X Freestanding Multfuel stoves	Wood Logs ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
Manufactured by Pevex Enterprises Ltd, Unit MP7, Kirrawah Business Park, Newbourne Road,	The fireplace must be installed, maintained and operated in accordance with the following specifications: dated June 2015 reference "Pevex1021/AH/ver1"	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Nr Woodbridge, IP12 4PR.	The appliance must be fitted with a permanent stop that ensures the primary and secondary air controls cannot close beyond 10% open position.	
Bohemia X40 Cube Panorama 4.5kW multifuel stove. Manufactured by Pevex Enterprises Ltd, Unit MP7, Kirrawah Business Park, Newbourne Road, Nr Woodbridge, IP12 4PR	Installation and Operating Instructions for Bohemia X Freestanding Multfuel stoves dated June 2015 reference "Pevex1021/AH/ver1" A permanent stop must be implemented ensuring a minimum opening area of 1 cm2 for the primary air slider when in the fully closed position and a tertiary air inlet area of 4 cm2.	Wood Logs ⁽¹⁾ .
Bohemia X60 Cube and Bohemia X60 Cube Panorama 7kW multifuel stoves. Manufactured by Pevex Enterprises Ltd, Unit MP7, Kirrawah Business Park, Newbourne Road, Nr Woodbridge, IP12 4PR.	Installation and Operating Instructions for Bohemia X Freestanding Multfuel stoves dated June 2015 reference "Pevex1021/AH/ver1"	Wood Logs ⁽¹⁾ .
Boru 4.9kW Stove. Manufactured by Righpur Ltd., T/A Boru Stoves, The Hive, Ballydine, Gooldscross, Ireland.	Instruction manual reference "BFF010" dated 26th January 2011. The air controls must be fixed such they cannot be closed more than: — Primary air slide 2mm; — Secondary air slide 2mm; — Tertiary air slide 30%.	Wood logs ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fivenless	Conditions	
Class of fireplace	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Breckwell ETR002. Manufactured by United States Stove Company, 227 Industrial	Operation and instruction manual reference "852288" dated October 2014.	Wood logs ⁽¹⁾ .
Park Road, South Pittsburg, TN 37380 USA.	The appliance must be fitted with a mechanical stop to prevent air control closure beyond the 12mm open position.	
Breckwell model ESWC 11 wood burning stove.	Instruction manual reference "852330" dated December 2014.	Wood logs ⁽¹⁾ .
Manufactured by United States Stove Company, 227 Industrial Park Road, South Pittsburg, TN 37380 USA.	The appliance must be fitted with a system to prevent closure of one of the eight secondary air slots beyond the 3.5mm open position, and with the tertiary air control fixed in the fully open position.	
Breckwell ESWC31. Manufactured by United States Stove Company, 227 Industrial	Operation and instruction manual reference "852286 A" dated October 2014.	Wood logs ⁽¹⁾ .
Park Road, South Pittsburg, TN 37380 USA.	The appliance must be fitted with a mechanical stop to prevent air control closure beyond the 6mm open position.	
Breckwell ESWC21. Manufactured by United States Stove Company, 227 Industrial Park Road, South Pittsburg, TN 37380 USA.	Operation and instruction manual reference "852284 A" dated October 2014.	Wood logs ⁽¹⁾ .
Bristol 4.6kW multi-fuel inset appliance.	Bronpi Installation Instructions.	Wood logs ⁽¹⁾ .
Manufactured by Bronpi Calefaccion, Carretera	Version 3 Issued 15-12-2014	
Cordoba-Malaga Km 78.2. Spain	Bronpi Supplementary Instructions Mod. Bristol. Version 7 Issued 23-01-2015	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
	Appliances must be fitted with a permanent stop to prevent closure of the air control beyond 25% open position	
Bristol-Vision 4.6kW multifuel insert. Manufactured by Bronpi Calefaccion, Carretera Cordoba-Malaga Km 78.2.	Bronpi Installation Instructions. Version 3 Issued 15-12-2014 Bronpi Supplementary Instructions Mod. Bristol-C. Version 7 Issued 23-01-2015	Wood logs ⁽¹⁾ .
Spain	Appliances must be fitted with a permanent stop to prevent closure of the air control beyond 25% open position	
Bristol–C 4.6kW multi-fuel stove.	Bronpi Installation Instructions.	Wood logs ⁽¹⁾ .
Manufactured by Bronpi Calefaccion, Carretera Cordoba-Malaga Km 78.2. Spain	Version 3 Issued 15-12-2014Bronpi Supplementary Instructions Mod. Bristol-V. Version 7 Issued 23-01-2015	
	Appliances must be fitted with a permanent stop to prevent closure of the air control beyond 25% open position	
BST71S wood-burning 6.5kW stove. Manufactured by Hebei Chida	Installation and Operation manual Stove BST71S dated 01/10/2015 reference "Version 8".	Wood logs ⁽¹⁾ .
Manufacture and Trade Co Limited, No. B2305, Times Ark Building, 36 Guang'an Street, Shijiazhuang, 050011 China	The appliance must be fitted with a mechanical stop to prevent closure of the secondary air control beyond the 25% open position	
BST71M wood-burning 8.3kW stove. Manufactured by Hebei Chida	Installation and Operation manual Stove BST71M dated 01/10/2015 reference "Version 8".	Wood logs ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Limited, No. B2305, Times Ark Building, 36 Guang'an Street, Shijiazhuang, 050011 China	The appliance must be fitted with a mechanical stop to prevent closure of the secondary air control beyond the 50% open position	
BST71L wood-burning 10kW stove. Manufactured by Hebei Chida Manufacture and Trade Co Limited, No. B2305, Times Ark Building, 36 Guang'an Street, Shijiazhuang, 050011 China	Installation and Operation manual Stove BST71L dated 01/10/2015 reference "Version 8". The appliance must be fitted with a mechanical stop to prevent closure of the secondary air control beyond the 50% open position	Wood logs ⁽¹⁾ .
BST83X multifuel stove. Manufactured by Hebei Chida	Installation and operation manual reference "1.01" dated July 2013.	Wood logs ⁽¹⁾ .
Manufacture and Trade Co Ltd., No. B2305, Times Ark Building, 36 Guang'an Street, Shijiazhuang, 050011, China.	The appliance must be fitted with a mechanical stop to prevent secondary air closure beyond the 15mm open position.	
Bucklesham 35FS, and Bucklesham 35FS Panorama, 3.8kW multifuel stoves. Manufactured by Pevex Enterprises Ltd, Unit MP7, Kirrawah Business Park, Newbourne Road,	Installation and Operating Instructions for Bucklesham 35/40/50/60 FS Multfuel stoves dated June 2015 reference "Pevex1020/AH/ ver1" The appliance must be fitted with a permanent stop that	Wood Logs ⁽¹⁾ .
Nr Woodbridge, IP12 4PR	ensures the air control cannot close beyond 15% open position.	
Bucklesham 40FS, and Bucklesham 40FS Panorama, 4.5kW multifuel stoves. Manufactured by Pevex Enterprises Ltd, Unit MP7,	Installation and Operating Instructions for Bucklesham 35/40/50/60 FS Multfuel stoves dated June 2015 reference "Pevex1020/AH/ ver1"	Wood Logs ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Kirrawah Business Park, Newbourne Road,	A permanent stop must be implemented ensuring a minimum opening area of	
Nr Woodbridge, IP12 4PR	1 cm2 for the primary air slider when in the fully closed position and a tertiary air inlet area of 4 cm2.	
Bucklesham 50FS, and Bucklesham 50FS Panorama, 5kW multifuel stoves. Manufactured by Pevex Enterprises Ltd, Unit MP7, Kirrawah Business Park, Nawahawara Baad	Installation and Operating Instructions for Bucklesham 35/40/50/60 FS Multfuel stoves dated June 2015 reference "Pevex1020/AH/ ver1" A permanent stop must be	Wood Logs ⁽¹⁾ .
Newbourne Road, Nr Woodbridge, IP12 4PR	implemented ensuring a minimum opening area of 1 cm2 for the primary air slider when in the fully closed position and a tertiary air inlet area of 4 cm2	
Bucklesham 60FS Panorama and Bucklesham 60FS 7kW multifuel stove.	Installation and Operating Instructions for Bucklesham 35/40/50/60 FS Multfuel stoves dated June 2015	Wood Logs ⁽¹⁾ .
Manufactured by Pevex Enterprises Ltd, Unit MP7, Kirrawah Business Park, Newbourne Road,	reference "Pevex1020/AH/ver1"	
Nr Woodbridge, IP12 4PR		
Burley Brampton 8kW stove.	Instruction manual reference "BUR/11/10" dated October	Wood logs ⁽¹⁾ .
Manufactured by Burley Appliances Ltd., Lands' End Way, Oakham, Rutland, LE15 6RB.	2011.	
Burley Debdale 4kW stove.	Instruction manual reference "BUR/11/10" dated October	Wood logs ⁽¹⁾ .
Manufactured by Burley Appliances Ltd., Lands' End Way Oakham Butland LE15	2011.	
Way, Oakham, Rutland, LE15 6RB.	The radius of the air inlet hole must be 19mm.	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Instruction manual reference "Bushman Large Commercial Pizza Oven. Instruction manual reference "LDOINST" dated January 2011. Bushman Large Domestic Pizza Oven. Instruction manual reference "LDOINST" dated January 2011. Bushman Large Domestic Pizza Oven. Instruction manual reference "LDOINST" dated January 2011. Manufactured by Dingley Dell Enterprises Ltd., PO Box 3534, Kidderminster, Worcestershire, DY14 9ZE. Instruction manual reference "LDOINST" dated January 2011. Manufactured by Dingley Dell Enterprises Ltd., PO Box 3534, Kidderminster, Worcestershire, DY14 9ZE. Instruction manual reference "LDOINST" dated January 2011. Manufactured by Dingley Dell Enterprises Ltd., PO Box 3534, Kidderminster, Worcestershire, DY14 9ZE. Instruction manual reference "MCOINST" dated January 2011. Manufactured by Dingley Dell Enterprises Ltd., PO Box 3534, Kidderminster, Worcestershire, DY14 9ZE. Instruction manual reference "MCOINST" dated January 2011. Manufactured by Dingley Dell Enterprises Ltd., PO Box 3534, Kidderminster, Worcestershire, DY14 9ZE. Instruction manual reference "MCOINST" dated January 2011. Manufactured by Dingley Dell Enterprises Ltd., PO Box 3534, Kidderminster, Worcestershire, DY14 9ZE. Instruction manual reference "MDOINST" dated January 2011. Manufactured by Dingley Dell Enterprises Ltd., PO Box 3534, Kidderminster, Worcestershire, DY14 9ZE. Instruction manual reference "MDOINST" dated January 2011. Manufactured by Dingley Dell Enterprises Ltd., PO Box 3534, Kidderminster, Worcestershire, DY14 9ZE. Instruction manual reference "MDOINST" dated January 2011. Manufactured by Dingley Dell Enterprises Ltd., PO Box 3534, Kidderminster, Worcestershire, DY14 9ZE. Instruction manual reference "SCOINST" dated January 2011. Mood logs (1). Wood logs			
Installed, maintained and operated in accordance with the following specifications: Instruction manual reference "BUR/11/05" dated January 2011. Wood logs (1).	Class of fireplace		
Manufactured by Burley Appliances Ltd., Lands' End Way, Oakham, Rutland, LE15 6RB. Bushman Large Commercial Pizza Oven. Bushman Large Domestic Pizza Oven. Manufactured by Dingley Dell Enterprises Ltd., PO Box 3534, Kidderminster, Worcestershire, DY14 9ZE. Bushman Medium Commercial Pizza Oven. Instruction manual reference "LOINST" dated January 2011. Wood logs (1). Instruction manual reference "MCOINST" dated January 2011. Manufactured by Dingley Dell Enterprises Ltd., PO Box 3534, Kidderminster, Worcestershire, DY14 9ZE. Bushman Medium Commercial Pizza Oven. Instruction manual reference "MCOINST" dated January 2011. Manufactured by Dingley Dell Enterprises Ltd., PO Box 3534, Kidderminster, Worcestershire, DY14 9ZE. Bushman Medium Domestic Pizza Oven. Instruction manual reference "MCOINST" dated January 2011. Wood logs (1).		installed, maintained and operated in accordance with	in the fireplace other than authorised fuels and the
Appliances Ltd., Lands' End Way, Oakham, Rutland, LE15 GRB. The appliance must be fitted with an air plate that prevents the tertiary air controller from closing more than 17mm and opening more than 45mm. Bushman Large Commercial Pizza Oven. Bushman Large Domestic Pizza Oven. Bushman Large Domestic Pizza Oven. Bushman Large Domestic Pizza Oven. Instruction manual reference "LCOINST" dated January 2011. Instruction manual reference "LOINST" dated January 2011. Instruction manual reference "LOINST" dated January 2011. Instruction manual reference "LOINST" dated January 2011. Manufactured by Dingley Dell Enterprises Ltd., PO Box 3534, Kidderminster, Worcestershire, DY14 9ZE. Bushman Medium Commercial Pizza Oven. Instruction manual reference "MCOINST" dated January 2011. Instruction manual reference "MCOINST" dated January 2011. Instruction manual reference "MOINST" dated January 2011. Manufactured by Dingley Dell Enterprises Ltd., PO Box 3534, Kidderminster, Worcestershire, DY14 9ZE. Bushman Medium Domestic Pizza Oven. Instruction manual reference "MDOINST" dated January 2011. Instruction manual reference "MOINST" dated January 2011. Instruction manual reference "MOINST" dated January 2011.		"BUR/11/05" dated January	Wood logs ⁽¹⁾ .
with an air plate that prevents the tertiary air controller from closing more than 17mm and opening more than 45mm. Bushman Large Commercial Pizza Oven. Manufactured by Dingley Dell Enterprises Ltd., PO Box 3534, Kidderminster, Worcestershire, DY14 9ZE. Bushman Large Domestic Pizza Oven. Manufactured by Dingley Dell Enterprises Ltd., PO Box 3534, Kidderminster, Worcestershire, DY14 9ZE. Bushman Medium Commercial Pizza Oven. Manufactured by Dingley Dell Enterprises Ltd., PO Box 3534, Kidderminster, Worcestershire, DY14 9ZE. Bushman Medium Commercial Pizza Oven. Manufactured by Dingley Dell Enterprises Ltd., PO Box 3534, Kidderminster, Worcestershire, DY14 9ZE. Bushman Medium Domestic Pizza Oven. Instruction manual reference "MCOINST" dated January 2011. Manufactured by Dingley Dell Enterprises Ltd., PO Box 3534, Kidderminster, Worcestershire, DY14 9ZE. Bushman Medium Domestic Pizza Oven. Manufactured by Dingley Dell Enterprises Ltd., PO Box 3534, Kidderminster, Worcestershire, DY14 9ZE. Bushman Small Commercial Pizza Oven. Instruction manual reference "MDOINST" dated January 2011. Wood logs (1). Wood logs (1). Wood logs (1).	Appliances Ltd., Lands' End		
Pizza Oven. "LCOINST" dated January 2011. Manufactured by Dingley Dell Enterprises Ltd., PO Box 3534, Kidderminster, Worcestershire, DY14 9ZE. Bushman Large Domestic Pizza Oven. Manufactured by Dingley Dell Enterprises Ltd., PO Box 3534, Kidderminster, Worcestershire, DY14 9ZE. Bushman Medium Commercial Pizza Oven. "MCOINST" dated January 2011. Manufactured by Dingley Dell Enterprises Ltd., PO Box 3534, Kidderminster, Worcestershire, DY14 9ZE. Bushman Medium Commercial Pizza Oven. "MCOINST" dated January 2011. Manufactured by Dingley Dell Enterprises Ltd., PO Box 3534, Kidderminster, Worcestershire, DY14 9ZE. Bushman Medium Domestic Pizza Oven. "MDOINST" dated January 2011. Manufactured by Dingley Dell Enterprises Ltd., PO Box 3534, Kidderminster, Worcestershire, DY14 9ZE. Bushman Small Commercial Pizza Oven. "Instruction manual reference "MDOINST" dated January 2011. Wood logs (1). Wood logs (1). Wood logs (1).	• • • • • • • • • • • • • • • • • • • •	with an air plate that prevents the tertiary air controller from closing more than 17mm and	
Enterprises Ltd., PO Box 3534, Kidderminster, Worcestershire, DY14 9ZE. Bushman Large Domestic Pizza Oven. Manufactured by Dingley Dell Enterprises Ltd., PO Box 3534, Kidderminster, Worcestershire, DY14 9ZE. Bushman Medium Commercial Pizza Oven. Manufactured by Dingley Dell Enterprises Ltd., PO Box 3534, Kidderminster, Worcestershire, DY14 9ZE. Bushman Medium Commercial Enterprises Ltd., PO Box 3534, Kidderminster, Worcestershire, DY14 9ZE. Bushman Medium Domestic Pizza Oven. Manufactured by Dingley Dell Enterprises Ltd., PO Box 3534, Kidderminster, Worcestershire, DY14 9ZE. Bushman Medium Domestic Pizza Oven. Manufactured by Dingley Dell Enterprises Ltd., PO Box 3534, Kidderminster, Worcestershire, DY14 9ZE. Bushman Small Commercial Pizza Oven. Instruction manual reference "Mool logs (1). Wood logs (1). Wood logs (1). Wood logs (1). Wood logs (1).	_	"LCOINST" dated January	Wood logs ⁽¹⁾ .
Pizza Oven. "LDOINST" dated January 2011. Manufactured by Dingley Dell Enterprises Ltd., PO Box 3534, Kidderminster, Worcestershire, DY14 9ZE. Bushman Medium Commercial Pizza Oven. Manufactured by Dingley Dell Enterprises Ltd., PO Box 3534, Kidderminster, Worcestershire, DY14 9ZE. Bushman Medium Domestic Pizza Oven. Instruction manual reference "MCOINST" dated January 2011. Manufactured by Dingley Dell Enterprises Ltd., PO Box 3534, Kidderminster, Worcestershire, DY14 9ZE. Bushman Medium Domestic Pizza Oven. Manufactured by Dingley Dell Enterprises Ltd., PO Box 3534, Kidderminster, Worcestershire, DY14 9ZE. Bushman Small Commercial Pizza Oven. Instruction manual reference "SCOINST" dated January 2011. Wood logs (1).	Enterprises Ltd., PO Box 3534, Kidderminster, Worcestershire,		
Manufactured by Dingley Dell Enterprises Ltd., PO Box 3534, Kidderminster, Worcestershire, DY14 9ZE. Bushman Medium Commercial Pizza Oven. Manufactured by Dingley Dell Enterprises Ltd., PO Box 3534, Kidderminster, Worcestershire, DY14 9ZE. Bushman Medium Domestic Pizza Oven. Instruction manual reference "MCOINST" dated January 2011. Wood logs (1). Instruction manual reference "MDOINST" dated January 2011. Bushman Small Commercial Pizza Oven. Instruction manual reference "SCOINST" dated January 2011.		"LDOINST" dated January	Wood logs ⁽¹⁾ .
Pizza Oven. "MCOINST" dated January 2011. Manufactured by Dingley Dell Enterprises Ltd., PO Box 3534, Kidderminster, Worcestershire, DY14 9ZE. Bushman Medium Domestic Pizza Oven. Manufactured by Dingley Dell Enterprises Ltd., PO Box 3534, Kidderminster, Worcestershire, DY14 9ZE. Bushman Small Commercial Pizza Oven. Instruction manual reference "MDOINST" dated January 2011. Wood logs (1). Wood logs (1). Wood logs (1).	Enterprises Ltd., PO Box 3534, Kidderminster, Worcestershire,		
Enterprises Ltd., PO Box 3534, Kidderminster, Worcestershire, DY14 9ZE. Bushman Medium Domestic Pizza Oven. Instruction manual reference "MDOINST" dated January 2011. Manufactured by Dingley Dell Enterprises Ltd., PO Box 3534, Kidderminster, Worcestershire, DY14 9ZE. Bushman Small Commercial Pizza Oven. Instruction manual reference "SCOINST" dated January 2011. Wood logs (1).		"MCOINST" dated January	Wood logs ⁽¹⁾ .
Pizza Oven. "MDOINST" dated January 2011. Manufactured by Dingley Dell Enterprises Ltd., PO Box 3534, Kidderminster, Worcestershire, DY14 9ZE. Bushman Small Commercial Pizza Oven. Instruction manual reference "SCOINST" dated January 2011.	Enterprises Ltd., PO Box 3534, Kidderminster, Worcestershire,		
Manufactured by Dingley Dell Enterprises Ltd., PO Box 3534, Kidderminster, Worcestershire, DY14 9ZE. Bushman Small Commercial Pizza Oven. Instruction manual reference "SCOINST" dated January 2011.		"MDOINST" dated January	Wood logs ⁽¹⁾ .
Pizza Oven. "SCOINST" dated January 2011.	Enterprises Ltd., PO Box 3534, Kidderminster, Worcestershire,		
		"SCOINST" dated January	Wood logs ⁽¹⁾ .
Enterprises Ltd., PO Box 3534, (1) The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preserved.			and Garage and Control

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Kidderminster, Worcestershire, DY14 9ZE.		
Bushman Small Domestic Pizza Oven.	Instruction manual reference "SDOINST" dated January 2011.	Wood logs ⁽¹⁾ .
Manufactured by Dingley Dell Enterprises Ltd., PO Box 3534, Kidderminster, Worcestershire, DY14 9ZE.		
Buxton Multifuel stove (Model BX1MF).	Technical manual reference "BX1MF 0101" dated 17th October 2013.	Wood logs ⁽¹⁾ .
Manufactured by ACR Heat Products Ltd, Unit 1, Weston Works, Weston Lane, Tyseley, Birmingham, West Midlands,	The appliance must be fitted with a mechanical stop to prevent closure of the secondary air control lever	
B11 3RP.	beyond 12mm open.	
Camelot 4 stove. Manufactured by Hunter Stoves Ltd., Trevilla Park, Slaughterbridge, Camelford, Cornwall, PL32 9TT.	Instruction manual reference "JINCAM04 Rev B" dated 24th April 2012. The appliance must be fitted with a permanent stop that prevents closure of the	Wood logs ⁽¹⁾ .
	secondary air slider beyond 30% open.	
Camelot 5 Compact stove. Manufactured by Hunter Stoves Ltd., Trevilla Park,	Instruction manual reference "JINCAC05 Rev B" dated 14th June 2012.	Wood logs ⁽¹⁾ .
Slaughterbridge, Camelford, Cornwall, PL32 9TT.	The appliance must be fitted with a permanent stop that prevents closure of the secondary air slider beyond 30% open.	
Camelot 5 Slimline stove. Manufactured by Hunter Stoves Ltd., Trevilla Park, Slaughterbridge, Camelford, Cornwall, PL32 9TT.	Instruction manual reference "JINCAS05 Rev B" dated 15th June 2012.	Wood logs ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Camelot 6 stove. Manufactured by Hunter Stoves Ltd., Trevilla Park, Slaughterbridge, Camelford, Cornwall, PL32 9TT.	Instruction manual reference "JINCAM06 Rev B" dated 24th April 2012.	Wood logs ⁽¹⁾ .
Camelot Slimline 8 stove. Manufactured by Hunter Stoves Ltd., Trevilla Park, Slaughterbridge, Camelford, Cornwall, PL32 9TT.	Instruction manual reference "JINCAS08 Rev B" dated 27th June 2012.	Wood logs ⁽¹⁾ .
Capital Fireplaces Qube 450 multifuel stove. Manufactured by F.E. Robinson (Hooton) Ltd, Station Works, Hooton Road, Hooton, South Wirral, CH66 7NF	Instruction manual dated 28 July 2015 reference "Qube 450/Vega 450 Qube Solid Fuel Stoves Manual Version 1.1	Wood logs ⁽¹⁾ .
Carillon 4:3 and Carillon 16:9 Crystal. Manufactured by LaNordica Spa, Via Summano 104 M. Precalcino, 36030, Vicenza, Italy.	Instruction manual reference "7196755-Rev.09" dated 22nd December 2010. The appliance must be fitted with a mechanical stop to prevent closure of the secondary air control beyond the 40% open position.	Wood logs ⁽¹⁾ .
Carron Dante SE. Manufactured by JIG UK Ltd., Hurlingham Business Park, Fulbeck Heath, Grantham, Lincolnshire, NG32 3HL.	Instruction manual reference "BHC401-406" dated 12th January 2011. The appliance must be fitted with a system preventing the closure of the secondary air control openings beyond 14mm.	Wood logs ⁽¹⁾ .
Carron Stove. Manufactured by JIG UK Ltd., Hurlingham Business Park,	Instruction manual reference '91-62351' dated July 2009.	Dry and split wood logs of a maximum length of 23cm ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Fulbeck Heath, Grantham, Lincolnshire, NG32 3HL.		
Carron Stove SE. Manufactured by JIG UK Ltd., Hurlingham Business Park, Fulbeck Heath, Grantham,	Instruction manual reference "BHC501-506" dated 12th January 2011. The appliance must be fitted	Wood logs ⁽¹⁾ .
Lincolnshire, NG32 3HL.	with a system preventing the closure of the secondary air control openings beyond 3mm.	
Carron 11kW SE Stove. Manufactured by JIG UK Ltd.,	Instruction manual reference "Carron 11kW Stove model September 2012 (Smoke Exempt)".	Wood logs ⁽¹⁾ .
Hurlingham Business Park, Fulbeck Heath, Grantham, Lincolnshire, NG32 3HL.	The appliance must be fitted with a modification to the secondary air control preventing closure beyond 4mm.	
Cascada 5CB 4.6kW multi-fuel stove. Manufactured by Percy Doughty & Co Limited, Imperial Point, Express Trading Estate, Stone Hill Road, Farnworth, Bolton, BL4 9TN	Installation and Operating instructions dated 1st November 2016 reference "CASCADA5CB INSTRUCTION - REV A".	Wood logs ⁽¹⁾ .
Cast Tec Arbeia Juno freestanding wood-burning stove. Manufactured by Charlton &	Installation and operating instructions reference "Juno & Vulcan Issue 01" dated June 2013.	Wood logs ⁽¹⁾ .
Jenrick Ltd., Unit D, Stafford Park 2, Telford, Shropshire, TF3 3AR.	The appliance must be fitted with a system that prevents closure of the secondary air control slots beyond the 7mm open position.	
Cast Tec Arbeia Titus woodburning inset stove.	Installation and operating instructions reference "Trajan & Titus Issue 01" dated June 2013.	Wood logs ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
Manufactured by Charlton & Jenrick Ltd., Unit D, Stafford Park 2, Telford, Shropshire, TF3 3AR.	The fireplace must be installed, maintained and operated in accordance with the following specifications: The appliance must be fitted with a system that prevents closure of the secondary air control slots beyond the 9mm open position.	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Cast Tec Arbeia Trajan woodburning inset stove. Manufactured by Charlton & Jenrick Ltd., Unit D, Stafford Park 2, Telford, Shropshire, TF3 3AR.	Installation and operating instructions reference "Trajan & Titus Issue 01" dated June 2013. The appliance must be fitted with a system that prevents closure of the secondary air control slots beyond the 3.5mm open position.	Wood logs ⁽¹⁾ .
Cast Tec Arbeia Vulcan freestanding wood-burning stove. Manufactured by Charlton & Jenrick Ltd., Unit D, Stafford Park 2, Telford, Shropshire, TF3 3AR.	Installation and operating instructions reference "Juno & Vulcan Issue 01" dated June 2013. The appliance must be fitted with a mechanical stop to prevent closure of the secondary air control beyond the 5mm open position.	Wood logs ⁽¹⁾ .
Cast Tec Cougar 4.7kW multifuel stove. Manufactured by Arbeia Trading Ltd, Unti 3A East Side, Tyne Dock, South Shields, Tyne and Wear, NE33 5SP.	Instruction manual reference "T1202 v1" dated 22nd April 2014. The appliance must be fitted with a mechanical stop to prevent closure of the secondary air control beyond the 25% open position. The appliance must be fitted with a mechanical stop to fix the tertiary air control fully open.	Wood logs ⁽¹⁾ .
CB800 Skagen. Manufactured by Hunter Stoves Ltd., Trevilla Park, Slaughterbridge, Camelford, Cornwall, PL32 9TT.	Instruction manual reference "JINHCE08 revE" dated 6th December 2011 and instruction manual reference "JINHCE08SCK revB" dated 6th December 2011.	Wood logs ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications: The appliance must be fitted with smoke control area kit JHCE0801.	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Charnwood Bay 5 GT 5.8kW wood burning inset stove.	Operating and installation instructions reference "Bay 5.5GTv3" dated April 2014.	Wood logs ⁽¹⁾ .
Manufactured by A.J. Wells and Sons Limited, Bishops Way, Newport, Isle of Wight, PO30 5WS.		
Charnwood Bembridge 5kW wood burning stove	Instruction manual references "The Bembridge Operating & Installation Instructions v1	Wood Logs ⁽¹⁾ .
Manufactured by A.J. Wells and Sons Limited, Bishops	03.015" dated March 2015	
Way, Newport, Isle of Wight, PO30 5WS	The appliance must be fitted with a mechanical stop to prevent air control opening closure beyond the 58 mm open position.	
Charnwood C-FOUR insert 5kW multi-fuel inset roomheater.	Operating & Installation Instructions manual dated October 2014 reference "REV.C CFOURI 10.14"	Wood logs ⁽¹⁾ .
Manufactured by A.J. Wells and Sons Ltd, Bishops Way, Newport, Isle of Wight, PO30 5WS	Blanking plate (part number 010/TR099) must be in place when burning wood	
Charnwood C-Four stove.	Instruction manual reference "CFOUR V1" dated August	Wood logs ⁽¹⁾ .
Manufactured by A.J Wells and Sons Ltd., Bishops Way, Newport, Isle of Wight, PO30 5WS.	2011.	
Charnwood C-Five wood burning stove.	Instruction manual reference "C-series v2" dated September 2012.	Wood logs ⁽¹⁾ .
Manufactured by A.J Wells and Sons Ltd., Bishops Way, Newport, Isle of Wight, PO30 5WS.	The appliance must be fitted with a mechanical stop that prevents the closure of the air control opening beyond the 58mm open position.	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of frances	Conditions	
Class of fireplace	<u> </u>	No fuel is to be used
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	in the fireplace other than authorised fuels and the following fuel or fuels:
Charnwood C-Six stove.	Instruction manual reference	
Manufactured by A.J Wells and Sons Ltd., Bishops Way,	"Ref. C-4 C-6 v1" dated March 2012.	Wood logs ⁽¹⁾ .
Newport, Isle of Wight, PO30 5WS.	The appliance must be fitted with a system that prevents the closure of the air control opening beyond 58mm of the open position.	
Charnwood C-Seven wood burning stove.	Instruction manual reference "C-series v2" dated September 2012.	Wood logs ⁽¹⁾ .
Manufactured by A.J Wells and Sons Ltd., Bishops Way, Newport, Isle of Wight, PO30 5WS.	The appliance must be fitted with a mechanical stop that prevents the closure of the air control opening beyond the 64mm open position.	
Charnwood C-Eight wood burning stove.	Instruction manual reference "C-series v2" dated September 2012.	Wood logs ⁽¹⁾ .
Manufactured by A.J Wells and Sons Ltd., Bishops Way, Newport, Isle of Wight, PO30 5WS.	The appliance must be fitted with a mechanical stop that prevents the closure of the air control opening beyond the 64mm open position.	
Charnwood Country 4 wood burning stove.	Modification instruction manual reference "TIS.95" dated January 2011 and	Wood logs ⁽¹⁾ .
Manufactured by A.J Wells and Sons Ltd., Bishops Way, Newport, Isle of Wight, PO30 5WS.	instruction manual reference "Country 4 MKII" dated January 2011.	
	The appliance must be fitted with the manufacturer's smoke reduction kit to fix the minimum aperture of the secondary air inlets to a minimum of 21mm open.	
Charnwood Cove 1SR.	Installation and use instruction manual reference "COVE1SR01.10 Issue A".	Wood logs ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
Manufactured by A.J Wells and Sons Ltd., Bishops Way, Newport, Isle of Wight, PO30 5WS.	The fireplace must be installed, maintained and operated in accordance with the following specifications: The air control must be adjusted such that the minimum closure of the air control is equivalent to that found with the control pushed in 15mm from the fully open	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Charnwood Island 1. Manufactured by A.J Wells	position. Instruction manual reference "Island I.II.III 12.10 IssueB" dated December 2010.	Wood logs ⁽¹⁾ .
and Sons Ltd., Bishops Way, Newport, Isle of Wight, PO30 5WS.	The appliance must be fitted with a stop bracket (Kit No. 010/AY83/S) to prevent the airwash flaps at the back of the stove from being closed beyond 2mm.	
Charnwood Island 2. Manufactured by A.J Wells and Sons Ltd., Bishops Way, Newport, Isle of Wight, PO30 5WS.	Instruction manual reference "Island I.II.III 12.10 IssueB" dated December 2010. The appliance must be fitted with a stop bracket (Kit No. 010/BY83/S) to prevent the airwash flaps at the back of the stove from being closed beyond 2mm.	Wood logs ⁽¹⁾ .
Charnwood Island 3. Manufactured by A.J Wells and Sons Ltd., Bishops Way, Newport, Isle of Wight, PO30 5WS.	Instruction manual reference "Island I.II.III 12.10 IssueB" dated December 2010. The appliance must be fitted with a stop bracket (Kit No. 010/CY83/S) to prevent the airwash flaps at the back of the stove from being closed beyond 2mm.	Wood logs ⁽¹⁾ .
Charnwood Tor stove. Manufactured by A.J Wells and Sons Ltd., Bishops Way, Newport, Isle of Wight, PO30 5WS.	Installation and use instruction manual reference "Tor 02.10 Issue A".	Wood logs ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Conditions	
The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Instruction manual reference "Tor & Tor Pico 12.10 IssueB" dated December 2010.	Wood logs ⁽¹⁾ .
Installation and user instructions manual reference "NS-4 Issue 1" dated 8th January 2014. The appliance must be fitted with a permanent stop to prevent closure of the secondary air supply control beyond 7mm open.	Wood logs ⁽¹⁾ .
Instruction manual reference "CH4K-V4" dated 7th December 2009. The appliance must be fitted with a mechanical stop to prevent closure of the air control beyond the 34mm open position.	Wood logs ⁽¹⁾ .
Instruction manual reference "CH6K-V4" dated 7th December 2009. The appliance must be fitted with a mechanical stop to prevent closure of the air control beyond the 10mm open position.	Wood logs ⁽¹⁾ .
Installation and instructions for use manual dated	Wood logs ⁽¹⁾ .
	installed, maintained and operated in accordance with the following specifications: Instruction manual reference "Tor & Tor Pico 12.10 IssueB" dated December 2010. Installation and user instructions manual reference "NS-4 Issue 1" dated 8th January 2014. The appliance must be fitted with a permanent stop to prevent closure of the secondary air supply control beyond 7mm open. Instruction manual reference "CH4K-V4" dated 7th December 2009. The appliance must be fitted with a mechanical stop to prevent closure of the air control beyond the 34mm open position. Instruction manual reference "CH6K-V4" dated 7th December 2009. The appliance must be fitted with a mechanical stop to prevent closure of the air control beyond the 10mm open position.

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
CITIZEN MF 900-45 WHE 1S	29th July 2015 reference	
– DEFRA 12kW,	"CIT_WHE_EN_02_DEFRA"	
CITIZEN MF 900-60 WHE 1S – DEFRA 15kW and,		
CITIZEN MF 1050-45 WHE 1S – DEFRA 13kW woodburning inset roomheaters.		
Manufactured by MetalFire nv. Noorwegenstraat 28, B-9940 Evergem, Belgium		
Classic model 25, 35, 40, 49 and 60 wood pellet boilers.	Installation manual reference "No. 22, Pellet Boilers, Type Classic 25, 31, 35, 40, 49, 60,	Wood pellets ⁽¹⁾ .
Manufactured by Hargassner Gesellschaft mit beschränkter Haftung (GmbH), Gunderding 8, A-4952, Weng, Austria.	reference BA Classic 25L-60L Nr 21 0508".	
Clean Air Systems CAS 200, 400 and 600 hand-fed airheaters.	Handbook reference "24600H version 1" dated January 2011.	Softwood, hardwood, medium density fibreboard (MDF) or chipboard offcuts ⁽¹⁾ .
Manufactured by Inventair Ltd., Lancaster Road, Carnaby Industrial Estate, Bridlington, East Yorkshire, YO15 3QY.		
Clean Air Systems CAS 300 Max airheater and cyclone.	Handbook reference "300A version 1" dated January 2011.	Chipped or sawdust softwood, hardwood, medium density fibreboard (MDF) or chipboard
Manufactured by Inventair Ltd., Lancaster Road, Carnaby Industrial Estate, Bridlington, East Yorkshire, YO15 3QY.		(1)
Cleanburn CB900 Inset & Cleanburn CB900 Sonderskoven Inset wood burning stoves.	Instruction manual reference "JINHCN09 Slider Stop Rev A" dated 17th January 2012 and instruction manual reference "JINHCN09 Rev F"	Wood logs ⁽¹⁾ .
Manufactured by Hunter Stoves Ltd., Trevilla Park,	dated 24th January 2012.	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
Slaughterbridge, Camelford, Cornwall, PL32 9TT.	The fireplace must be installed, maintained and operated in accordance with the following specifications: The appliance must be fitted with a mechanical stop to prevent secondary air control closure beyond the 20% open position.	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Cleanburn Inset 5 CBC 4.7kW wood-burning inset stove. Manufactured by Hunter Stoves Ltd, Trevilla Park, Slaughterbridge, Camelford, Cornwall, PL32 9TT	Installation and Operating Instructions dated 30/06/2015 reference "JINCCB04 RevB"	Wood logs ⁽¹⁾ .
Cleanburn Inset Sønderskoven 8 multi-fuel inset stove. Manufactured by Hunter Stoves Limited, Trevilla Park, Slaughterbridge, Camelford, Cornwall, PL32 9TT.	Installation and operating instructions manual reference "JINCN09 RevF" dated 20th March 2012 and modification instructions reference "JINHCN09 Slider Stop Rev B" dated 25th September 2013. The appliance must be fitted with a mechanical stop to	Wood logs ⁽¹⁾ .
Cleanburn R4. Manufactured by Hunter Stoves Ltd., Trevilla Park, Slaughterbridge, Camelford, Cornwall, PL32 9TT.	prevent secondary air control closure beyond the 20% open position. Instruction manual reference "JINCLR04 Rev E" dated 2nd December 2011 and instruction manual reference "JINCLR04SCK revB" dated 5th December 2011.	Wood logs ⁽¹⁾ .
Cleanburn R4 Euro 4.9kW	The appliance must be fitted with smoke control area kit JCLR0401. Installation and Operating	Wood logs ⁽¹⁾ .
wood-burning stove. Manufactured by Hunter Stoves Ltd, Trevilla Park, Slaughterbridge, Camelford, Cornwall, PL32 9TT	Instructions dated 29/01/2015 reference "JINCLE04 RevA" and Smoke Control Area Kit Installation Instructions dated 05/12/11 reference "JINCLR04SCK revB"	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications: Fitted with "smoke control area kit "JCLR0401"	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Cleanburn R5 Inset stove. Manufactured by Hunter Stoves Ltd., Trevilla Park, Slaughterbridge, Camelford, Cornwall, PL32 9TT.	Instruction manual reference "JINCLR05 Rev B" dated 10th December 2012 and instruction manual reference "JINCLR05SCK Rev A" dated 6th July 2012. The appliance must be fitted with smoke control area kit	Wood logs ⁽¹⁾ .
Cleanburn R6 Inset stove. Manufactured by Hunter Stoves Ltd., Trevilla Park, Slaughterbridge, Camelford, Cornwall, PL32 9TT.	Instruction manual reference "JINCLR06 Rev B" dated 10th December 2012 and instruction manual reference "JINCLR05SCK Rev A" dated 6th July 2012.	Wood logs ⁽¹⁾ .
	The appliance must be fitted with smoke control area kit JCLR0501.	
Clearburn Junior SE. Manufactured by Dean Forge Ltd., Dean Prior,	Instruction manual reference "JRSE Issue 1" dated March 2012.	Wood logs ⁽¹⁾ .
Buckfastleigh, Devon, TQ11 0LS.	The appliance must be fitted with a mechanical stop to prevent secondary air control closure beyond the 83mm open position.	
wood burning stoves.	Operating instructions reference "V1/42" stamped and signed "Smoke Control" dated 1st July 2006.	Air-dried wood logs ⁽¹⁾ .
Manufactured by Clearview Stoves, More Works, Bishops Castle, Shropshire, SY9 5HH.	The appliance must be fitted with a tamperproof mechanical stop on the air slide/damper.	
Cleanburn Skagen 5 HCE85 4.9kW wood-burning stove.	Installation and operating instructions manual dated 23rd June 2015 reference "JINHCE85 Rev B" and	Wood logs ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Manufactured by Hunter Stoves Ltd, Trevilla Park, Slaughterbridge, Camelford, Cornwall, PL32 9TT	Smoke Control Area Kit Installation Instructions dated 22nd January 2015 reference "JINHCE85SCK revA"	
	Appliance must be fitted with the manufacturer's smoke control kit reference JHCE8501	
Cleanburn Sonderskoven 5 Inset stove.	Instruction manual reference "JINHCN05 Rev B" dated 4th October 2012.	Wood logs ⁽¹⁾ .
Manufactured by Hunter Stoves Ltd., Trevilla Park, Slaughterbridge, Camelford, Cornwall, PL32 9TT.	The valve plate adjusted by the secondary air control must contain six 5mm holes.	
CLM Vesuvio 400kW stone wood-fired automatic pizza oven.	Instruction manual reference "Manual English Review 2.1" dated 25th July 2013.	'CalorPan' 100% beech briquette, octagonal section, length 260-300mm, width and height 75-90mm manufactured
Formerly known as the Vesuvio 400kW automatic pizza oven manufactured by CLM srl, Via I Maggio 35, 31043, Fontanelle (Treviso), Italy, and now manufactured by CLM Bakery System srl, Via Monteli, 3 - 33092 Meduno (PN), Italy.		from dried beech sawdust or 'Eden Beech Wood Briquettes' that are cylindrical and of length 247-273mm and have diameter of 95mm manufactured from dried beech sawdust ⁽¹⁾ .
Compte R ATC250 boiler fitted with an electrostatic precipitator (ESP).	Instruction manual "Instructions service Clean air act application for the ATC250 boiler" dated 18/03/2015	Wood chips ⁽¹⁾ .
Manufactured by Compte R, Z.I. de Vaureil, 63220 Arlanc, France.	references "AQ-00-PP-0028"	
Contura 510, 520T, 550, 550A, 550W, 560T, 560K, 570, 580, 585, 590 and Contura T.	Manufacturer's installation instructions reference "IAV SE/EX 0726-6 611821" and	Untreated dry wood with less than 20% moisture ⁽¹⁾ .
Manufactured by Nibe AB, Box 134, SE-285 23 Markaryd, Sweden.	Lighting instruction reference "BAV SA/EX 0717-2 611820".	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
	A permanent stop must be in place on the air inlet to prevent closure beyond the 20% open position.	
Contura 556 wood-burning stove. Manufactured by Nibe AB, Box 134, SE-285 23 Markaryd, Sweden.	User manual reference "611 820 BAV C500 SE/EX – 6" dated 20th October 2011 and installation instruction manual reference "811116 IAV SE-EX C556 - 2" dated 14th November 2012 and supplementary instruction manual reference "811142 BAV GB - 3" dated August 2011.	Wood logs ⁽¹⁾ .
	The appliance must be fitted with a system to prevent closure of the air control vent beyond the 20% open position.	
Contura 580W. Manufactured by Nibe AB, Box 134, SE-285 23	Manufacturer's installation instructions reference "IAV SE/EX 0740-1 511911".	Untreated dry wood with less than 20% moisture ⁽¹⁾ .
Markaryd, Sweden.	A permanent stop must be in place on the air inlet to prevent closure beyond the 20% open position.	
Contura 586 wood-burning stove. Manufactured by Nibe AB, Box 134, SE-285 23 Markaryd, Sweden.	User manual reference "611 820 BAV C500 SE/EX – 6" dated 20th October 2011, installation instruction manual reference "811117 IAV SE-EX C586 -2" dated 15th November 2012 and supplementary instruction manual reference "811142 BAV GB - 3" dated August 2011.	Wood logs ⁽¹⁾ .
	The appliance must be fitted with a system to prevent closure of the air control vent beyond the 20% open position.	

The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives
or coatings.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Contura 750, 750A and 780. Manufactured by Nibe AB, Box 134, SE-285 23	Instruction manual reference "811064 BAV SE-EX C750/780-1".	Wood logs ⁽¹⁾ .
Markaryd, Sweden.	The appliance must be fitted with a mechanical stop to prevent closure of the air control vent beyond the 28% open position.	
Contura 810, Contura 820 T, Contura 850, Contura 860 T and Contura 880. Manufactured by Nibe AB, Box 134, SE-285 23	Instruction manual reference "811118 BAV SE-EX C800-1" dated 28th June 2011 and supplementary operating instructions reference "811142 BAV GB-2" dated June 2011.	Wood logs ⁽¹⁾ .
Markaryd, Sweden.	The appliance must be fitted with a mechanical stop to	
	prevent air control closure beyond the 38% open position.	
Contura i4 FS Classic and Contura i4 FS Modern multi- fuel stoves.	Instruction manual reference "811164 BAV C i4 SE-EX-1" dated 03/02/2012, installation instruction manual reference	Wood logs ⁽¹⁾ .
Manufactured by Nibe AB, Box 134, SE-285 23 Markaryd, Sweden.	"811191 IAV Ci4 FS GB-1" dated 3rd June 2013 and supplementary operating instruction manual reference "811142 BAV GB - 4" dated August 2011.	
	The appliance must be fitted with a system to prevent closure of the air control vent beyond the 30% open position.	
Contura i4 Modern and Contura i4 Classic.	Instruction manual reference "811136 BAV C i4 GB-1" dated 0	Dry wood logs ⁽¹⁾ .
Manufactured by Nibe AB, Box 134, SE-285 23 Markaryd, Sweden.	4th July 2011 and supplementary operating instructions reference "811142 BAV GB-2" dated June 2011.	
(1) TI 0 1		

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
Cluss of fireplace	The fireplace must be installed, maintained and operated in accordance with the following specifications: The appliance must be fitted with a mechanical stop to prevent closure beyond the 28% open position.	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Contura i5 Panorama and i5 Double Door wood-burning insert stoves. Manufactured by Nibe AB, Box 134, SE-285 23 Markaryd, Sweden.	Installation and lighting instruction manual reference "811175 IAC SE-EX Ci5-5" dated November 2012, additional installation instruction manual reference "811188 Kompletterande IAV Ci5 - 2" dated 14th September 2012 and supplementary instruction manual reference "811142 BAV GB - 4" dated August 2011.	Wood logs ⁽¹⁾ .
	The appliance must be fitted with a system to prevent closure of the air control vent beyond the 30% open position.	
Contura i6 Glass front insert and Contura i6 Cast iron front insert wood-burning stoves. Manufactured by Nibe AB Limited, Box 134, SE-285 23 Markaryd, Sweden	Instruction manual dated July 2015, reference "811142 BAV GB-8" and Lighting and Installation Instructions dated March 2015 reference "811216 IAV SE-EX Ci6-4" The fitting of a system to prevent closure of the air control vent beyond the 30% open position must be implemented to be installed in accordance with Additional installation instruction ref "811188 Kompletterande IAV Ci5 GB – 4" Dated 2014-02-13	Wood logs ⁽¹⁾ .
Contura i30, i31, i40, i41 Wood burning inset appliances.	Instruction manual reference	Wood logs ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Manufactured by Nibe AB, Box 134, SE-285 23, Markaryd, Sweden.	"811142 BAV GB–5" dated January 2014.	
	The appliance must be fitted with a mechanical stop to prevent air control closure beyond the 27% open position.	
Coseyfire CF001SE. Manufactured by Stove World UK Limited, Unit 24 Folly	Installation and operating instructions reference "Version 1.0" dated April 2014.	Wood logs ⁽¹⁾ .
Farm, Ramsdell, RG26 5RJ.	The appliance must be fitted with a modified secondary air supply fixed in the fully open position.	
Cosmo Classic UK, Cosmo 1147 UK, Cosmo 1147 Soapstone UK, Cosmo 971 UK, Cosmo 971 Soapstone UK, Cosmo High Soapstone	User's manual dated June 2011 reference "Cosmo & Midi. User's manual. Jydepejsen A/S - June 2011"	Wood logs ⁽¹⁾ .
UK, Cosmo 1500 UK and, Cosmo 1500 soapstone UK 6kW stoves.	The appliance must be fitted with a mechanical stop to prevent closure of the air control valve beyond the 16%	
Manufactured by Jydepejsen A/S, Ahornsvinget 3-7, Nr. Felding, DK-7500 Holstebro, Denmark	open position	
Country 575 and 765 5kW stoves.	Installation and Operation manual dated March 2015 reference "Installation and	Wood logs ⁽¹⁾ .
Manufactured by Jydepejsen A/S, Ahornsvinget 3-7, Nr. Felding, DK-7500 Holstebro,	Operation Manual Country Revision 1, 25.03.2015"	
Denmark	The appliance must be fitted with a mechanical stop to prevent closure of the air control valve beyond the 35% open position	
Country Hearth EC410.	Instruction manual reference "852292" dated October 2014.	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Manufactured by United States Stove Company, 227 Industrial Park Road, South Pittsburg, TN 37380 USA.		
Country Hearth EC1100.	Instruction manual reference "852290" dated October 2014.	Wood logs ⁽¹⁾ .
Manufactured by United States Stove Company, 227 Industrial Park Road, South Pittsburg, TN 37380 USA.	The appliance must be fitted with a mechanical stop to prevent air control closure beyond the 12mm open position.	
Cove 2 SR. Manufactured by A.J Wells and Sons Ltd. of Bishops Way,	Manufacturer's instruction manual reference "Cove2SR 07.09 IssB" dated July 2009.	Dry and split wood logs of a maximum length of 23cm ⁽¹⁾ .
Newport, Isle of Wight, PO30 5WS.	The appliance must be fitted with a permanent stop on air control to prevent closure beyond 14mm from the fully closed position.	
Crator JS5500 multi-fuel stove.	Instruction manual reference "Crator multi-fuel stove	Wood logs ⁽¹⁾ .
Manufactured by James Smellie Ltd., Unit N, Leona Industrial Estate, Nimmings Road, Halesowen, West Midlands, B62 9JQ.	instruction manual Issue 1" dated June 2012.	
CTC Ecoflex 15 and 20.	Manufacturer's instructions reference "161 505 27 06/1"	Wood pellets (1).
Manufactured by Enertech AB, Box 313, S-341 26 Ljungby, Sweden.		
Cubic Wall UK, Cubic 109 UK, Cubic 166 UK, Cubic 215 UK and, Cubic W200 UK 6kW stoves.	User's manual dated June 2011 reference "Cosmo & Midi. User's manual. Jydepejsen A/S - June 2011"	Wood logs ⁽¹⁾ .
Manufactured by Jydepejsen A/S, Ahornsvinget 3-7, Nr. Felding, DK-7500 Holstebro, Denmark	The appliance must be fitted with a mechanical stop to prevent closure of the air control valve beyond the 16% open position	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

	T = -	
Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Dalby Smoke Control and Saltburn Smoke Control 5kW wood-burning stoves. Manufactured by Town & Country Fires Limited, 1 Enterprise Way, Thornton	Saltburn Smoke Control / Dalby Smoke Control and wood burning stove Installation and user Instructions dated 6 July 2015 reference "Saltburn/Dalby Smoke Control Issue 2"	Wood logs ⁽¹⁾ .
Road Industrial Estate, Pickering, North Yorkshire, YO18 7NA	The appliances must be fitted with a mechanical stop to prevent closure of the air control slider beyond the 30mm open position	
D'Alessandro GSA 130. Manufactured by D'Alessandro Termomeccanica, Contrada Cerreto, 55, 66010 Miglianico, Chieti, Italy.	Instruction manual reference "2.0-1-QGSA130XEN0612" dated 26th June 2012.	Wood chips ⁽¹⁾ .
D'Alessandro Termomeccanica CS and CSA boilers 40, 60, 80 and 100kW. Manufactured by D'Alessandro Termomeccanica, Contrada Cerreto, 55, 66010 Miglianico, Chieti, Italy.	Instruction manual reference "Ver. 2.0 - QCSA100XXIT0209 [UK SMOKE CONTROL]" dated February 2009.	Wood pellets ⁽¹⁾ .
D'Alessandro Termomeccanica CS and CSA 130, 180, 230 and 300kW. Manufactured by D'Alessandro Termomeccanica, Contrada Cerreto, 55, 66010 Miglianico, Chieti, Italy.	Instruction manual reference "Ver. 2.0 - QCSA2000XEN0209 [UK SMOKE CONTROL]" dated February 2009.	Wood pellets ⁽¹⁾ .
D'Alessandro Termomeccanica CS and CSA 400, 500, 650, 800, 950, 1300, 1650 and 2000kW.	Instruction manual reference "Ver. 2.0 - QCSA2000XEN0209 [UK SMOKE CONTROL]" dated February 2009.	Wood pellets ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
Manufactured by D'Alessandro	The fireplace must be installed, maintained and operated in accordance with the following specifications: The appliance must be fitted with the optional multi-	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Termomeccanica, Contrada Cerreto, 55, 66010 Miglianico, Chieti, Italy.	cyclone.	
D'Alessandro Termomeccanica CSI 20kW.	Instruction manual reference "Ver. 2.0 -QCSI100XXIT0209" dated February 2009.	Wood pellets ⁽¹⁾ .
Manufactured by D'Alessandro Termomeccanica, Contrada Cerreto, 55, 66010 Miglianico, Chieti, Italy.		
Dartmoor 5 SE. Manufactured by Dean Forge	Instruction manual reference "DM5 Issue 1" dated March 2012.	Wood logs ⁽¹⁾ .
Fabrication Ltd., Dean Prior, Buckfastleigh, Devon, TQ11 OLS.	The appliance must be fitted with a mechanical stop to prevent secondary air control closure beyond the 30% open position.	
Dean Stoves Clearburn Slimline 5 SE multifuel stove.	Instruction manual reference "SL5SE issue 1" dated 25th April 2014.	Wood logs ⁽¹⁾ .
Manufactured by Dean Forge Fabrication Ltd., Dean Prior, Buckfastleigh, Devon, TQ11 OLS.	The appliance must be fitted with a mechanical stop to prevent closure of the secondary air control beyond 15mm open position.	
Dean Stoves Clearburn Small SE multifuel stove.	Instruction manual reference "CBS8SE issue 1" dated 25 April 2014.	Wood logs ⁽¹⁾ .
Manufactured by Dean Forge Fabrication Ltd., Dean Prior, Buckfastleigh, Devon, TQ11 OLS.	The appliance must be fitted with a mechanical stop to prevent closure of the secondary air control beyond 15mm open position.	
Dean Stoves Dartmoor 6 SE Wood Burning Stove.	Operating instructions manual reference "DM6 issue 1" dated 2nd July 2013.	Wood logs ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
Manufactured by Dean Forge Fabrication Ltd., Dean Prior, Buckfastleigh, Devon, TQ11 OLS.	The fireplace must be installed, maintained and operated in accordance with the following specifications: The appliance must be fitted with a mechanical stop to prevent secondary air spin wheel control closure beyond the 40% open position.	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Dean Stoves Dartmoor W5 SE Wood Burning Stove.	Operating instructions manual reference "DMW5 issue 1" dated 2nd July 2013.	Wood logs ⁽¹⁾ .
Manufactured by Dean Forge Fabrication Ltd., Dean Prior, Buckfastleigh, Devon, TQ11 OLS.	The appliance must be fitted with a mechanical stop to prevent secondary air spin wheel control closure beyond the 40% open position.	
Dean Stoves Hembury 5 SE Wood Burning Stove.	Operating Instructions manual reference "HEM5SE issue" dated 2nd July 2013.	Wood logs ⁽¹⁾ .
Manufactured by Dean Forge Ltd., Dean Prior, Buckfastleigh, Devon, TQ11 0LS.	The appliance must be fitted with a mechanical stop to prevent secondary air control closure beyond the 83mm open position.	
Dean Stoves Hembury Slimline 5 SE multifuel stove.	Instruction manual reference "HEMSL5SE issue 1" dated 25 April 2014.	Wood logs ⁽¹⁾ .
Manufactured by Dean Forge Fabrication Ltd., Dean Prior, Buckfastleigh, Devon, TQ11 OLS.	The appliance must be fitted with a mechanical stop to prevent closure of the secondary air control beyond 8mm open position.	
Dean Stoves Hembury 8 SE multifuel stove.	Instruction manual reference "HEM8SE issue 1" dated 25 April 2014.	Wood logs ⁽¹⁾ .
Manufactured by Dean Forge Fabrication Ltd., Dean Prior, Buckfastleigh, Devon, TQ11 OLS.	The appliance must be fitted with a mechanical stop to prevent closure of the secondary air control beyond 8mm open position.	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Dean Stoves Junior 105 SE Wood Burning Stove.	Operating instructions manual reference "JR105SE Issue 1" dated May 2013.	Wood logs ⁽¹⁾ .
Manufactured by Dean Forge Fabrication Ltd., Dean Prior, Buckfastleigh, Devon, TQ11 OLS.	The appliance must be fitted with a mechanical stop to prevent secondary air control closure beyond the 83mm open position.	
Design 800 Green wood burning stove.	Instruction manual reference "07DH8000A" dated November 2011.	Wood logs ⁽¹⁾ .
Manufactured by Bodart & Gonay Ltd., Rue De Lambinon, 3 Harze, Belgium, 4920.	The appliance must be fitted with a "UK kit for smokeless areas Design 800".	
Desire 5, Desire 5LS, Desire 6, Desire 6LS, Desire 7, Desire 7LS, Ignite 5, Ignite 5LS, Ignite 6, Ignite 6LS, Ignite 7 and Ignite 7LS multi fuel	Installation and operating instructions manual reference "Mar 14/GB Issue 4" dated 3rd December 2014.	Wood logs ⁽¹⁾ .
stoves. Manufactured by Broseley Fires Ltd, First Floor, Unit B Knights Court, Archers Way, Battlefield Enterprise Park, Shrewsbury, Shropshire, SY1 3GA.	The appliance must be fitted with a mechanical stop to prevent closure of the secondary air control slide beyond the 10mm open position.	
Di Lusso R4. Manufactured by Hunter Stoves Ltd., Trevilla Park, Slaughterbridge, Camelford, Cornwall, PL32 9TT.	Instruction manual reference "JINDLU04 Rev E" dated 2nd December 2011 and instruction manual reference "JINDLU04SCK revB" dated 5th December 2011.	Wood logs ⁽¹⁾ .
	The appliance must be fitted with smoke control area kit JDLU0401.	
Di Lusso R4 Euro 4.9kW wood-burning stove.	Installation and Operating Instructions dated 29/01/2015 reference "JINDLE04 RevA" and Smoke Control Area	Wood logs ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Manufactured by Hunter Stoves Ltd, Trevilla Park, Slaughterbridge, Camelford, Cornwall, PL32 9TT	Kit Installation Instructions dated 05/12/11 reference "JINDLU04SCK revB"	
	Fitted with "smoke control area kit "JDLU0401"	
Di Lusso R5 inset stove. Manufactured by Hunter Stoves Ltd., Trevilla Park, Slaughterbridge, Camelford, Cornwall, PL32 9TT.	Instruction manual reference "JINDLU05 Rev B" dated 10th December 2012 and additional instructions reference "JINDLU05SCK Rev A" dated 6th July 2012.	Wood logs ⁽¹⁾ .
	The appliance must be fitted with smoke control area kit JDLU0501.	
Di Lusso R6 inset stove. Manufactured by Hunter Stoves Ltd., Trevilla Park, Slaughterbridge, Camelford, Cornwall, PL32 9TT.	Instruction manual reference "JINDLU06 Rev B" dated 10th December 2012 and instruction manual reference "JINDLU05SCK Rev A" dated 6th July 2012.	Wood logs ⁽¹⁾ .
	The appliance must be fitted with smoke control area kit JDLU0501.	
Dik Geurts Instyle 500,	Installation instruction manual reference	Wood logs ⁽¹⁾ .
Dik Geurts Prostyle 500,	"DRU392187-409050-NL- NL-0614-5" dated March 2014	
Dik Geurts Instyle 550,	and user manual reference "DRU180452-363097-nl-	
Dik Geurts Prostyle 550	NL-0614-3 1" dated 19th June 2014.	
5 kW inset roomheaters.		
Manufactured by DRU Verwarming B.V, Postbus 1021, 6920 BA, Duiven, Ratio 8, 6921 RW Duiven, The Netherlands.		
Dik Geurts Instyle 600,	Installation instruction manual reference	Wood logs ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Dik Geurts Prostyle 600 5 kW	"DRU392187-410127-NL-	
inset roomheaters and	NL-0614-3" dated June 2014 and user manual reference	
Dik Geurts Instyle 650,	"DRU180452-363097-nl- NL-0614-3. 1" dated 19th June	
Dik Geurts Prostyle 650 6kW	2014.	
Inset roomheaters.		
Manufactured by DRU Verwarming B.V, Postbus 1021, 6920 BA, Duiven, Ratio 8, 6921 RW Duiven, Nederland.		
Dik Geurts Instyle 700,	Installation instruction manual reference	Wood logs ⁽¹⁾ .
Dik Geurts Prostyle 700 10kW	"DRU392187-408668-NL-	
inset roomheaters.	NL-0314-7" dated June 2014 and user manual reference	
Manufactured by DRU Verwarming B.V, Postbus 1021, 6920 BA, Duiven, Ratio 8, 6921 RW Duiven, Nederland.	"DRU180452-363097-nl-NL-0614-3. 1" dated 19th June 2014.	
Dik Geurts Ivar 8 Store EA 7.6kW wood-burning stove.	User Manual dated 03/03/2016 reference "DRU-363097-NL-NL-0316-7", and	Wood logs ⁽¹⁾ .
Manufactured by DRU	Instructions for installation	
Verwarming B.V, Postbus	Ivar 8 LowEA Ivar 8 StoreEA	
1021, 6920 BA, Duiven, Ratio		
8, 6921 RW Duiven, The Netherlands	reference "DRU-678061-NL-NL-0316-3".	
	The appliance must be fitted with a modification to prevent closure of the air control beyond the 6.0cm open position.	
Dik Geurts Keld Low EA,	Installation manual reference "DRU392187-566405-	Wood logs ⁽¹⁾ .
Keld High EA,	nl-NL-0614-1 39"dated 19th June 2014 and	
Ivar Low EA,	user manual reference "DRU180452-363097-nl-	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
56

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Ivar High EA,	NL-0614-3" dated 19th June 2014.	
Jannik Medium Low EA 5kW wood-burning stoves. Manufactured by	The appliance must be fitted with a modification to prevent closure of the secondary air control beyond 22mm open in	
DRU Verwarming B.V, Postbus 1021, 6920 BA, Duiven, Ratio 8, 6921 RW Duiven, Nederland.	its minimum position.	
Dik Geurts Olaf EA 8.7kW wood-burning stove.	User Manual reference "DRU-363097-NL-	Wood logs ⁽¹⁾ .
Manufactured by DRU Verwarming B.V, Postbus 1021, 6920 BA, Duiven, Ratio 8, 6921 RW Duiven, The Netherlands	NL-0316-7", and Instructions for installation Ivar 8 LowEA Ivar 8 StoreEA OlafEA reference "DRU-678061-NL- NL-0316-3".	
	The appliance must be fitted with a modification to prevent closure of the air control beyond the 5.3cm open position.	
Dimplex Bellingham 4.7kW Multifuel Inset Stove Model BLM4iSE. Manufactured by Dimplex GDC Group Limited,	Bellingham 4.7kW Multifuel Inset Stove For Standard 16" Fireplace Opening dated 11/03/2015 reference "08/52386/0 - Issue 5".	Wood logs ⁽¹⁾ .
Millbrook House, Grange Drive, Hedge End, Southampton, SO30 2DF	The appliance must be factory fitted with an air control providing a minimum 44mm ² opening in the secondary air control	
Dimplex Bellingham 4.7kW Wood Only Inset Stove Model BLM4iWB. Manufactured by Dimplex	"Bellingham 4.7kW Wood Only Inset Stove For Standard 16" Fireplace Opening" dated 11/03/2015 reference "08/52739/0 - Issue 6".	Wood logs ⁽¹⁾ .
GDC Group Limited, Millbrook House, Grange Drive, Hedge End,	The appliance must be factory fitted with an air control	
Southampton, SO30 2DF	providing a minimum 44 mm ²	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

G1 CA 1	G 1:.:	
Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
	opening in the secondary air control	<u> </u>
Dimplex Bellingham 5kW Multifuel stove Model BLM5SE	Bellingham 5kW Multi- fuel stove (BLM5SE) dated 01/03/2015 reference "08/52386/0 - Issue 3".	Wood logs ⁽¹⁾ .
manufactured by Dimplex GDC Group Limited, Millbrook House, Grange Drive, Hedge End, Southampton, SO30 2DF	The appliance must be factory fitted with an air control providing a minimum 280 mm ² opening in the secondary air control	
Dimplex Bellingham 12kW Multifuel stove Model BLM12SE.	Bellingham 12kW Multi- fuel stove (BLM12SE) dated 01/03/2016 reference "08/52388/0 - Issue 3".	Wood logs ⁽¹⁾ .
Manufactured by Dimplex GDC Group Limited, Millbrook House, Grange Drive, Hedge End, Southampton, SO30 2DF	The appliance must be factory fitted with an air control providing a minimum 342 mm² opening in the secondary air control	
Dimplex Langbrook 5kW Clean Burn Stove.	Instruction manual reference "08/51568/0 – Issue 3" dated 28th June 2012.	Wood logs ⁽¹⁾ .
Manufactured by Dimplex, GDC Group Ltd., Millbrook House, Grange Drive, Hedge End, Southampton, SO30 2DF.	The appliance must be fitted with a mechanical stop to prevent secondary air control slider closure beyond the 40% open position.	
Dimplex SE Selbourne 5. Manufactured by ESSE	Instruction manual reference "SE Selbourne 5 Issue 1" dated August 2009.	Wood logs ⁽¹⁾ .
Engineering Ltd., Ouzledale Foundry, Long Ing, Barnoldswick, Lancashire, BB18 6BN.	The appliance must be fitted with a mechanical stop to prevent closure beyond the 50% open position.	
Dovre 225 MF 4.6 kW multifuel stove.	Installation instructions and operating manual reference "03.27125.000" dated June 2013 and additional instruction	Wood logs ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Manufactured by Dovre NV, Nijverheidsstraat 18, BE-2381 Weelde, Belgium.	manual reference "PM1030 Issue 2" dated January 2014.	
, 0	The appliance must be fitted with the smoke control kit DV-225SCKIT.	
Dovre 250 (model DV-250).	Manufacturer's instructions reference "PM250 Issue 1".	Untreated dry wood ⁽¹⁾ .
Manufactured by Dovre NV, Nijverheidsstraat 18, BE-2381 Weelde, Belgium.	The appliance must be fitted with a permanent stop on the secondary air inlet to prevent closure beyond the 75% open position.	
Dovre 425 CBW wood burning stove.	Installation instructions and operating manual reference "03.27986.100" dated	Wood logs ⁽¹⁾ .
Manufactured by Dovre NV, Nijverheidsstraat 18, BE-2381 Weelde, Belgium.	February 2012 and additional installation and operating instructions for use in smoke control areas reference "PM1191 Issue 1" dated December 2014.	
	The appliance must be fitted with smoke control kit Part. No. DV425SZKIT to prevent closure of the secondary air control slider beyond the 15mm open position.	
Dovre 525MF 8 kW multifuel stove.	Installation instructions and operating manual reference "03.27109.100"	Wood logs ⁽¹⁾ .
Manufactured by Dovre NV, Nijverheidsstraat 18, BE-2381 Weelde, Belgium.	dated February 2013 and smoke control kit additional installation and operating instructions reference "PM1030 Issue 2" dated January 2014.	
	The appliance must be fitted with the smoke control kit DV-225SCKIT.	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Conditions	
The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Installation instructions and operating manual reference "03.27151.000" dated July 2014 and smoke control kit additional installation and operating instructions for use in smoke control areas reference "PM1070 Issue 2" dated July 2014. The appliance must be fitted with a mechanical stop to prevent closure of the air control beyond 8mm open.	Wood logs ⁽¹⁾ .
Instruction manual reference "03.27681.100" dated April 2011 and instruction manual reference "PM813 Issue 1" dated May 2012. The appliance must be fitted with a permanent stop preventing closure of the secondary air supply beyond 50%.	Wood logs ⁽¹⁾ .
Manufacturer's instructions reference "A/22160" dated 5th August 1998 as amended by manufacturer's instructions reference "D13" dated 4th December 2004.	Untreated dry wood ⁽¹⁾ ; Peat or peat briquettes with, in either case, less than 25% moisture; Union Coal Briketts, manufactured by Rheinbraun AG of Germany comprising lignite compressed into briquettes of approx. 15cm in length with square ends and with a sulphur content
	The fireplace must be installed, maintained and operated in accordance with the following specifications: Installation instructions and operating manual reference "03.27151.000" dated July 2014 and smoke control kit additional installation and operating instructions for use in smoke control areas reference "PM1070 Issue 2" dated July 2014. The appliance must be fitted with a mechanical stop to prevent closure of the air control beyond 8mm open. Instruction manual reference "03.27681.100" dated April 2011 and instruction manual reference "PM813 Issue 1" dated May 2012. The appliance must be fitted with a permanent stop preventing closure of the secondary air supply beyond 50%. Manufacturer's instructions reference "A/22160" dated 5th August 1998 as amended by manufacturer's instructions reference "D13" dated 4th

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Status: This is the original version (as it was originally made). This item of legislation is currently only available in its original format.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels: CPL Wildfire, manufactured
		by Coal Products Ltd., Immingham, which comprise bituminous coal with a volatile content of 32-36% (as to approx. 96% of the total weight) and a cold cure resin binder (as to the remaining weight) are manufactured from those constituents by a process involving roll pressing, have an average weight of either 80-90 grams or 160-170 grams, and have a sulphur content not exceeding 1.8% of the total weight.
Dunsley Yorkshire Multifuel Stove.	Manufacturer's instructions reference "A/22160" dated 5th	Untreated dry wood ⁽¹⁾ ;
Manufactured by Dunsley Heat Ltd., Bridge Mills, Huddersfield Road, Holmfirth,	August 1998 as amended by manufacturer's instructions reference "D13" dated 4th December 2004.	Peat or peat briquettes with, in either case, less than 25% moisture;
Yorkshire, HD9 3TW.		Union Coal Briketts, manufactured by Rheinbraun AG of Germany comprising lignite compressed into briquettes of approx. 15cm in length with square ends and with a sulphur content not exceeding 1% of the total weight;
		CPL Wildfire, manufactured by Coal Products Ltd., Immingham, which comprise bituminous coal with a volatile content of 32-36% (as to approx. 96% of the total weight) and a cold cure resin binder (as to the remaining weight) are manufactured from those constituents by a process involving roll pressing, have an average weight of either 80-90 grams or 160-170

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels: grams, and have a sulphur content not exceeding 1.8% of the total weight.
Dunsley Yorkshire Multifuel Stove and Boiler. Manufactured by Dunsley Heat Ltd., Bridge Mills, Huddersfield Road, Holmfirth, Yorkshire, HD9 3TW.	Manufacturer's instructions reference "A/22160" dated 5th August 1998 as amended by manufacturer's instructions reference "GHD/DUN4B/1" dated 4th October 2004.	Untreated dry wood ⁽¹⁾ ; Peat or peat briquettes with, in either case, less than 25% moisture; Union Coal Briketts, manufactured by Rheinbraun AG of Germany comprising lignite compressed into briquettes of approx. 15cm in length with square ends and with a sulphur content not exceeding 1% of the total weight;
		CPL Wildfire, manufactured by Coal Products Ltd., Immingham, which comprise bituminous coal with a volatile content of 32-36% (as to approx. 96% of the total weight) and a cold cure resin binder (as to the remaining weight) are manufactured from those constituents by a process involving roll pressing, have an average weight of either 80-90 grams or 160-170 grams, and have a sulphur content not exceeding 1.8% of the total weight.
Dunsley Yorkshire Woodburning Stove. Manufactured by Dunsley Heat Ltd., Bridge Mills, Huddersfield Road, Holmfirth, Yorkshire, HD9 3TW.	Manufacturer's instructions reference "D13W" dated 4th December 2004.	Untreated dry wood (1).

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
Class of fireplace	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Dunsley Yorkshire Woodburning Stove and Boiler.	Manufacturer's instructions reference "D13W" dated 4th December 2004 and manufacturer's instructions	Untreated dry wood ⁽¹⁾ .
Manufactured by Dunsley Heat Ltd., Bridge Mills, Huddersfield Road, Holmfirth, Yorkshire, HD9 3TW.	reference "GHD/DUN4B/1" dated 4th October 2004.	
E-Compact 15 wood pellet stove boiler.	Instruction manual reference "E-COMPACT 15 Outdoor Pellet Boiler v1.5" dated May	6mm wood pellets ⁽¹⁾ .
Manufactured by Wood Energy Solutions Ltd., Donaskeigh, Tipperary, Co. Tipperary, Ireland.	2012.	
E-Compact 28 Pellet Boiler.	Instruction manual reference "Installation & Operation	6mm wood pellets ⁽¹⁾ .
Manufactured by Wood Energy Solutions Ltd., Donaskeigh, Tipperary, Co. Tipperary, Ireland.	Manual V.2.1" dated July 2012.	
Earlswood.	Instruction manual reference "EW1MF technical manual"	Wood logs ⁽¹⁾ .
Manufactured by ACR Heat Products Ltd., Unit 1 Weston	dated February 2009.	
Works, Weston Lane, Tyseley, Birmingham, B11 3RP.	When the primary air control is in the closed position, it must remain permanently open by 5mm and be prevented from closing fully by a screw.	
Ecco Stove E580.	Instruction manual reference "Ecco Stove 580 manual"	Wood logs ⁽¹⁾ .
Manufactured by Landy Vent UK Ltd., Foster House,	dated 12th December 2011.	
2 Redditch Road, Studley, Warwickshire, B80 7AX.		
Ecco Stove E678.	Instruction manual reference "01/11/3" dated 28th January	Wood logs ⁽¹⁾ .
Manufactured by Landy Vent UK Ltd., Foster House, 2 Redditch Road, Studley,	2011. The appliance must be fitted	
Warwickshire, B80 7AX.	with a system to fix the	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications: secondary air (airwash) to a 4mm open position.	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Ecco Stove E730. Manufactured by Landy Vent UK Limited, Foster House,	Instruction manual reference "020114/D002" dated 2nd January 2014.	Dry wood logs ⁽¹⁾ .
2 Redditch Road, Studley, Warwickshire B80 7AX.	The appliance must be fitted with a mechanical stop to prevent the secondary air control closing beyond the 4 mm open position. All other air controls must be permanently fixed in position.	
Ecco Stove E850. Manufactured by Landy	Instruction manual reference "02/10" dated 10th October 2010.	Wood logs ⁽¹⁾ .
Vent UK Ltd., Foster House, 2 Redditch Road, Studley, Warwickshire, B80 7AX.	The appliance must be fitted with a system that prevents closure of the secondary air flaps beyond 4mm (3 turns).	
Ecofire Barbara wood pellet stove boiler. Manufactured by Palazzetti Lelio S.p.A, Via Roveredo 103, Porcia (PN), 33080, Italy.	Instruction manual reference "cod. 004770900" dated October 2011 and supplementary information "Clean Air Act 1993 and Smoke Control Areas" reference "004723000" dated January 2012.	Wood pellets ⁽¹⁾ .
Ecofire Giulia Idro, Ecofire Kelly Idro Plus and Ecofire Tania Idro wood pellet stove boilers.	Instruction manual reference "cod. 004770432" dated February 2011 and supplementary information "Clean Air Act 1993 and	Wood pellets ⁽¹⁾ .
Manufactured by Palazzetti Lelio S.p.A, Via Roveredo 103, Porcia (PN), 33080, Italy.	Smoke Control Areas" reference "004723000" dated January 2012.	
Eco-Ideal Eco 1 Stove. Manufactured by Hunter	Instruction manual reference "JINECO01 revC" dated 20th July 2011.	Dry wood logs ⁽¹⁾ .
Stoves Ltd., Trevilla Park, Slaughterbridge, Camelford, Cornwall, PL32 9TT.	The appliance must be fitted with a permanent stop that	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications: prevents closure of the	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
	secondary air slider beyond 30% open.	
Eco-Ideal Eco 2 Stove.	Instruction manual reference "JINECO02 revC" dated 20th	Dry wood logs ⁽¹⁾ .
Manufactured by Hunter Stoves Ltd., Trevilla Park,	July 2011.	
Slaughterbridge, Camelford, Cornwall, PL32 9TT.	The appliance must be fitted with a permanent stop that prevents closure of the secondary air slider beyond 30% open.	
Eco-Ideal Eco 3 multifuel stove.	Installation and operating instructions reference "JINECO03 RevB" dated 17th	Wood logs ⁽¹⁾ .
Manufactured by Hunter Stoves Limited, Unit 6, Old Mill Industrial Estate, Exeter, EX5 4RJ.	July 2014.	
Eco-Ideal Eco 4 Stove.	Instruction manual reference "JINEC004 revC" dated 20th	Dry wood logs ⁽¹⁾ .
Manufactured by Hunter Stoves Ltd., Trevilla Park, Slaughterbridge, Camelford, Cornwall, PL32 9TT.	July 2011.	
ECO-Ideal Eco 5 multifuel stove.	Installation and operating instructions ref. "JINECO05 RevB" dated 20th June 2014.	Wood logs ⁽¹⁾ .
Manufactured by Hunter		
Stoves Limited, Trevilla Park, Slaughterbridge, Camelford,	The appliance must be fitted with a mechanical stop to prevent secondary air control	
Cornwall, PL32 9TT.	closure beyond the 40% open position.	
Eco-Ideal Eco 6 Stove.	Instruction manual reference "JINEC006 revC" dated 20th	Dry wood logs ⁽¹⁾ .
Manufactured by Hunter Stoves Ltd., Trevilla Park, Slaughterbridge, Camelford, Cornwall, PL32 9TT.	July 2011.	
ECO-Ideal Inset Eco 8 multifuel stove.	Installation and operating instructions manual reference	Wood logs ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
Manufactured by Hunter	The fireplace must be installed, maintained and operated in accordance with the following specifications: "JINECI08 Rev B" dated	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Stoves Limited, Trevilla Park, Slaughterbridge, Camelford, Cornwall, PL32 9TT.	14th February 2013 and modification instructions reference "JINEC108 Slider Stop Rev B" dated 25th September 2013.	
	The appliance must be fitted with a mechanical stop to prevent secondary air control closure beyond the 20% open position.	
Ecosy+ Ottawa 5 kW Curve SE01 multi-fuel stove.	Installation and Operating Instructions dated 26/02/2016 reference "se01 Version 5".	Wood logs ⁽¹⁾ .
Manufactured by Stove World UK Limited, Unit 24 Folly Farm, Ramsdell, Tadley, RG26 5RJ	A permanent stop to fix the secondary/tertiary air control slider to 8mm open in its minimum position must be implemented	
Ecosy+ Ottawa 5 kW Curve SE01 with stand multi-fuel stove.	Installation and Operating Instructions dated 26/02/2016 reference "se01 Version 5".	Wood logs ⁽¹⁾ .
Manufactured by Stove World UK Limited, Unit 24 Folly Farm, Ramsdell, Tadley, RG26 5RJ	A permanent stop to fix the secondary/tertiary air control slider to 8mm open in its minimum position must be implemented	
Ecosy+ Ottawa 5 multi-fuel stove.	Installation and Operating Instructions dated 04/06/15 reference "Ottawa 5kw	Wood logs ⁽¹⁾ .
Manufactured by Stove World UK Limited, Unit 24 Folly Farm, Ramsdell, Tadley, RG26	Operating Instructions Version 1"	
5RJ	Fitted with a mechanical stop to prevent secondary air control closure beyond the 31mm open position when sold into smoke control areas.	
Ecosy+ Ottawa 12 multi-fuel stove.	Instruction manual dated 04/06/15 reference "Ottawa	Wood logs ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
Manufactured by Stove World	The fireplace must be installed, maintained and operated in accordance with the following specifications: 12kw Operating Instructions	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
UK Limited, Unit 24 Folly Farm, Ramsdell, Tadley, RG26	Version 1"	
5RJ	Fitted with a mechanical stop to prevent secondary air control closure beyond the 31mm open position when sold into smoke control areas.	
Effecta Komplett 20 boiler.	Instruction manual reference "Rev. EA.013-10-18" dated	Wood pellets (1).
Manufactured by Effecta AB	18th October 2013.	
Västra Rågdalsvägen 21,		
434 96, Kungsbacka, Sweden.		
Effecta Komplett III 20kW and Effecta Komplett III light 20kW pellet boilers.	The EFFECTA KOMPLETT III – Installing, - Maintenance, - Service, - Assembly Instruction dated 29th June	Wood pellets ⁽¹⁾ .
Manufactured by Effecta Energy Solutions AB, Västra Rågdalsvägen 21, 434 99 Kungsbacka, Sweden	2015 reference "Rev. E.A. Ver 02"	
Effecta Komplett III 25kW and Effecta Komplett III light 25kW pellet boilers.	Installing, maintenance, service and assembly instruction manual reference "Rev. EA. 014-02-25" dated 25th	Wood logs ⁽¹⁾ .
Manufactured by	February 2014.	
Effecta Energy Solutions AB, Västra Rågdalsvägen 21, 434 99 Kungsbacka, Sweden.		
Effecta Komplett III 35kW and Effecta Komplett III light 35kW pellet boilers.	Installing, maintenance, service and assembly instruction manual reference "Rev. EA. 014-02-25" dated 25th	Wood logs ⁽¹⁾ .
Manufactured by Effecta Energy Solutions AB, Västra Rågdalsvägen 21, 434 99 Kungsbacka, Sweden.	February 2014.	
Effecta Lambda 25, 35 and 60 boilers.	Instruction manual reference	Wood logs ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Manufactured by Effecta AB	"Rev.EA. 013-10-20" dated 20th October 2013.	
Västra Rågdalsvägen 21,		
434 96, Kungsbacka, Sweden.		
Ekoheat 900 9.4kW,	Installation and operating instructions manual reference	Wood logs ⁽¹⁾ .
Ekoheat 1500 15kW.	"CDOC000682" dated May 2013.	
Ekoheat 2500 24.9kW Ekoheat 4000 42.7kW, pellet boilers.	2013.	
Manufactured by EkpowerAps, Falstervej 285500, Middelfart, Denmark.		
Ekol Clarity 5 wood-burning stove.	Installation and operating instructions manual reference	Wood logs ⁽¹⁾ .
Manufactured by Saltfire	"Ekol Clarity 5 Manual 1.0" dated 4th July 2013.	
Stoves Ltd., Station Works, Johns Road, Wareham, BH20 4BG.	The appliance must be modified to allow an ingress of air through the secondary air control.	
	The appliance must be fitted with a stop in the tertiary air system to maintain a gap of 4mm between the circular plates and the openings at the rear of the appliance measured by the maximum aperture resulting from the opening.	
Ekol Clarity 8 wood-burning stove.	instructions manual reference "Ekol Clarity 8 Manual 1.0"	Wood logs ⁽¹⁾ .
Manufactured by Saltfire Stoves Ltd., Station Works, Johns Road, Wareham, BH20 4BG.	dated 4th July 2013.	
Ekol Clarity 12 wood-burning	Installation and operating	Wood logs ⁽¹⁾ .
Stove. (1) The fuel must not contain helogenet	instructions manual reference	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Manufactured by Saltfire Stoves Ltd., Station Works, Johns Road, Wareham, BH20	"Ekol Clarity 12 Manual 1.0" dated 4th July 2013.	
4BG.	The appliance must be modified to allow an ingress of air through the secondary air control.	
	The appliance must be fitted with a stop in the tertiary air system to maintain a gap of 4mm between the circular plates and the openings at the rear of the appliance measured by the maximum aperture resulting from the opening.	
Ekol Clarity 20 Wood Burning Stove.	Installation and operating instructions reference "Ekol Clarity 20 Boiler Wood	Wood logs ⁽¹⁾ .
Manufactured by Saltfire Stoves Ltd, Station Works, Johns Road, Wareham, BH20	Version, Manual Version 1.1" dated 22nd January 2014.	
4BG.	The appliance must be fitted with a mechanical stop to prevent air wash control closure beyond the 25mm open position and a stop preventing manual primary air control closure beyond the 2mm open position.	
Ekol Clarity 30 Wood Burning Stove.	Installation and operating instructions reference "Ekol Clarity 30 Boiler Wood	Wood logs ⁽¹⁾ .
Manufactured by Saltfire Stoves Ltd, Station Works, Johns Road, Wareham, BH20	Version, Manual Version 1.1" dated 22nd January 2014.	
4BG.	The appliance must be fitted with a mechanical stop to prevent air wash control closure beyond the 30mm open position and a stop preventing manual primary air control closure beyond the 2mm open position.	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Ekol Clarity Double Sided wood-burning stove. Manufactured by Saltfire Stoves Ltd., Station Works, Johns Road, Wareham, BH20	Installation and operating Instructions manual reference "Ekol Clarity Double Sided Manual 1.0" dated 4th July 2013.	Wood logs ⁽¹⁾ .
4BG.	The appliance must be modified so that when the primary and secondary air controls are in the fully closed position they will be fixed at 3.5mm open.	
	The appliance must be fitted with a tertiary air control system comprising two 7mm holes on each side of the appliance and a fixed opening of 4 cm ² on the underside of the stove.	
Ekol Inset 5 wood-burning inset stove. Manufactured by Saltfire Stoves Ltd., Station Works,	Installation and operating instructions manual reference "Ekol Inset 5 Manual 1.0" dated 4th July 2013.	Wood logs ⁽¹⁾ .
Johns Road, Wareham, BH20 4BG.	The appliance must be modified so that when the secondary air supply is in its fully closed position it will be fixed at 4mm open.	
Ekol Inset 8 wood-burning inset stove.	Installation and operating instruction manual reference "Ekol Inset 8 Manual 1.0"	Wood logs ⁽¹⁾ .
Manufactured by Saltfire Stoves Ltd., Station Works, Johns Road, Wareham, BH20 4BG.	dated 4th July 2013.	
Elegance Junior UK and Elegance Junior Wall UK 5kW wood burning stoves.	Instruction manual reference "User's manual Revision 1, dated 28th November 2014.	Wood logs ⁽¹⁾ .
Manufactured by Jydepejsen A/S, Ahornsvinget 3-7, Nr.	The appliance must be modified to fix the secondary	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Felding, DK-7500 Holstebro, Denmark.	air control to 698mm ² in its minimum position.	
Ellipse. Manufactured by LaNordica Spa, Via Summano 104 M. Precalcino, 36030, Vicenza, Italy.	Instruction manual reference "7196901-Rev.09" dated 22nd December 2010. The appliance must be fitted with a mechanical stop to prevent closure of the secondary air control beyond the 40% open position.	Wood logs ⁽¹⁾ .
En-tech model ENP 10, 15, 18, 25 and 35 boilers. Manufactured by En-tech Energietechnikpproduktion, Gesellschaft mit beschränkter Haftung (GmbH), Gewerbezone 3, A-9300 St Veit, Glan-Hunnenbrunn, Austria.	Manufacturer's installation manual reference "IMENP 10-35 11/2009" for the Firefox pellet boiler dated November 2009.	Wood pellets ⁽¹⁾ .
En-tech model PK15 and 25 boilers. Manufactured by En-tech Energietechnikpproduktion, Gesellschaft mit beschränkter Haftung (GmbH), Gewerbezone 3, A-9300 St Veit, Glan-Hunnenbrunn, Austria.	Installation manual reference "IMPK PK 15/25 11/2009 EN" dated November 2009.	Wood pellets ⁽¹⁾ .
En-tech model PK45 boilers. Manufactured by En-tech Energietechnikpproduktion, Gesellschaft mit beschränkter Haftung (GmbH), Gewerbezone 3, A-9300 St Veit, Glan-Hunnenbrunn, Austria.	Installation manual reference "IMPK PK 45 11/2009 EN" dated November 2009.	Wood pellets ⁽¹⁾ .
Endress USF-W 250.	Instruction manual reference "Operating and Maintenance manual Endress USF -	Wood chips and pellets (1).

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
Manufactured by Endress Holzfeuerungsanlagen GmbH, Industriestraße 18, D-91593 Burgbernheim.	The fireplace must be installed, maintained and operated in accordance with the following specifications: W250" reference "EMAN – USFW250" dated March 2010.	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Endress USF-W 350.	Instruction manual "Operating	Wood chips and pellets (1).
Manufactured by Endress Holzfeuerungsanlagen GmbH, Industriestraße 18, D-91593 Burgbernheim.	and Maintenance manual Endress USF –W350" reference "EMAN – USFW350" dated March 2010.	
Endress USF-W 500.	Instruction manual "Operating and Maintenance manual	Wood chips and pellets (1).
Manufactured by Endress Holzfeuerungsanlagen GmbH, Industriestraße 18, D-91593 Burgbernheim.	Endress USF -W500" reference "EMAN – USFW500" dated March 2010.	
Endress USF-W 800.	Instruction manual "Operating and Maintenance manual	Wood chips and pellets (1).
Manufactured by Endress Holzfeuerungsanlagen GmbH, Industriestraße 18, D-91593 Burgbernheim.	Endress USF –W800" reference "EMAN – USFW800" dated March 2010.	
Endress USF-W 1000.	Instruction manual "Operating and Maintenance manual	Wood chips and pellets (1).
Manufactured by Endress Holzfeuerungsanlagen GmbH, Industriestraße 18, D-91593 Burgbernheim.	Endress USF –W1000" reference "EMAN – USFW1000" dated March 2010.	
Endress VR-S 300.	Instruction manual "Operating and Maintenance manual	Wood chips and pellets (1).
Manufactured by Endress Holzfeuerungsanlagen GmbH, Industriestraße 18, D-91593 Burgbernheim.	Endress VR-S300" reference "EMAN – VRS300" dated March 2010.	
Endress VR-W 400.	Instruction manual "Operating and Maintenance manual	Wood chips and pellets (1).
Manufactured by Endress Holzfeuerungsanlagen GmbH, Industriestraße 18, D-91593 Burgbernheim.	Endress VR –W400" reference "EMAN – VRW400" dated March 2010.	
Endress VR-W 600.	Instruction manual "Operating and Maintenance manual	Wood chips and pellets ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
Manufactured by Endress Holzfeuerungsanlagen GmbH, Industriestraße 18, D-91593 Burgbernheim.	The fireplace must be installed, maintained and operated in accordance with the following specifications: Endress VR-W600" reference "EMAN – VRW600" dated March 2010.	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Endress VR-W 900. Manufactured by Endress Holzfeuerungsanlagen GmbH, Industriestraße 18, D-91593 Burgbernheim.	Instruction manual "Operating and Maintenance manual Endress VR-W900" reference "EMAN – VRW900" dated March 2010.	Wood chips and pellets ⁽¹⁾ .
EOS 30 346kW output wood pellet boiler with multicyclone. Manufactured by Uniconfort srl, Via dell'Industria 21, 35018, San Martino Di Lupari (PD) Italy.	Use and maintenance manual reference "Uniconfort EOS30 Manual v1" dated July 2011.	Wood pellets ⁽¹⁾ .
EOS 35 407kW output wood pellet boiler with multicyclone. Manufactured by Uniconfort srl, Via dell'Industria 21, 35018, San Martino Di Lupari (PD) Italy.	Use and maintenance manual reference "Uniconfort EOS35 Manual v1" dated July 2011.	Wood pellets ⁽¹⁾ .
EOS 40 464kW output wood pellet boiler with multicyclone. Manufactured by Uniconfort srl, Via dell'Industria 21, 35018, San Martino Di Lupari (PD) Italy.	Use and maintenance manual reference "Uniconfort EOS40 Manual v1" dated July 2011.	Wood pellets ⁽¹⁾ .
EOS 60 700kW output wood pellet boiler with multicyclone. Manufactured by Uniconfort srl. Via dell'Industria 21, 35018, San Martino Di Lupari, (PD) Italy.	Installation instruction manual reference "K135-07332 Uniconfort MUN v 2" dated September 2010.	6mm diameter wood pellets ⁽¹⁾ .
Esse 1 wood burning stove. Manufactured by Esse Engineering Limited,	Installation and User Instructions reference "ONE-SE-104- 29.10.2014" dated 29 October 2014.	Wood logs (1).

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
Ouzledale Foundry, Long Ing,	The fireplace must be installed, maintained and operated in accordance with the following specifications: The appliance must be fitted	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Barnoldswick, Lancashire, BB18 6BN.	with a mechanical stop to prevent secondary air control closure beyond the 50% open position.	
Esse 100 SE Smoke Exempt woodburning stove. Manufactured by ESSE Engineering Ltd., Ouzledale Foundry, Long Ing, Barnoldswisk, Lancashire, BB18 6BN.	Manufacturer's instruction manual reference "100 SE Issue 1" dated February 2009.	Untreated dry wood with a maximum moisture content of 20% maximum length of 200 mm and maximum width or diameter of 120 mm ⁽¹⁾ .
Esse 100DD SE 5kW stove. Manufactured by ESSE Engineering Ltd., Ouzedale Foundry, Long Ing, Barnoldswick, Lancashire, BB18 6BN.	Instruction manual reference "10/11 (PP) INSTR.ST-100DDSE/u" dated October 2011. The appliance must be fitted with a system to prevent closure of the air controls beyond the 50% open position.	Wood logs ⁽¹⁾ .
Esse 125 SE. Manufactured by ESSE Engineering Ltd., Ouzledale Foundry, Long Ing, Barnoldswick, Lancashire, BB18 6BN.	Instruction manual reference "Esse 125SE Issue 1" dated August 2009. The appliance must be fitted with a mechanical stop to prevent closure beyond the 50% open position.	Wood logs ⁽¹⁾ .
Esse 200XK-SE, DD-SE, Podium-SE & Contemporary- SE Smoke Exempt Wood Burning Stoves. Manufactured by Esse Engineering Ltd, Ouzledale Foundry, Long Ing, Barnoldswick, BB18 6BN.	Instruction manual reference "200-SE-I03-310114" dated 31st January 2014.	Wood logs ⁽¹⁾ .
Esse 301 SE stove. Manufactured by ESSE Engineering Ltd., Ouzledale	Instruction manual reference "v45" dated 9th November 2010.	Wood logs ⁽¹⁾ .

The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives
or coatings.

Class of fireplace	Conditions	
Foundry, Long Ing, Barnoldswick, Lancashire, BB18 6BN.	The fireplace must be installed, maintained and operated in accordance with the following specifications: The primary air control must not be fully air tight when closed.	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Eggs 250 stove	Instruction manyal reference	(1)
Esse 350 stove. Manufactured by ESSE Engineering Ltd., Ouzledale Foundry, Long Ing, Barnoldswick, Lancashire, BB18 6BN.	Instruction manual reference "v45" dated 9th November 2010.	Wood logs ⁽¹⁾ .
Esse 500 SE & 525 SE Wood Burning Stoves.	Installation and user instructions reference "1.01" dated October 2013.	Wood logs ⁽¹⁾ .
Manufactured by Esse Engineering Limited, Long Ing, Barnoldswick		
Lancashire, BB18 6BN.		
Esse 700-SE Smoke Exempt Wood Burning Stove.	Instruction manual reference "700-SE-I03-310114" dated 31st January 2014.	Wood logs ⁽¹⁾ .
Manufactured by Esse Engineering Ltd, Ouzledale Foundry, Long Ing, Barnoldswick, BB18 6BN.	313t Junuary 2014.	
Esse 990N wood burning cooker & Esse 990D wood burning cooker with boiler.	Operating instructions reference "1" dated January 2014.	Wood logs ⁽¹⁾ .
Manufactured by Esse Engineering Limited, Ouzledale Foundry, Long Ing, Barnoldswick, BB18 6BN.		
Esse 1622 inset stove. Manufactured by ESSE Engineering Ltd., Ouzledale Foundry, Long Ing,	Installation and operation manual reference "1622/ Integra INSET revision c" dated July 2010.	Dry wood logs ⁽¹⁾ .
Barnoldswick, Lancashire, BB18 6BN.	The appliance must be fitted with a mechanical stop to fix secondary air control fully open.	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
, , , , , , , , , , , , , , , , , , ,	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Esse Plus 1 wood burning cooker & Esse Plus 1D wood burning cooker with boiler.	Installation commissioning and operating instructions reference "1" dated January 2014.	Wood logs ⁽¹⁾ .
Manufactured by Esse Engineering Limited, Ouzledale Foundry, Long Ing, Barnoldswick, BB18 6BN.		
ETA HACK 20, 25, 35, 50, 70, 90, 130 and 200 woodchip boilers.	Instruction manual reference "HACK20-200_Bedienung_201 dated June 2011.	Wood chips ⁽¹⁾ . 1-06_EN"
Manufactured by ETA Heiztechnik Gesellschaft mit beschrankter Haftung (GmbH), A 4716, Hofkirchen an der Trattnach, Gewerbepark 1, Austria.	The appliance must be fitted with an integrated flue gas recirculation system must be used when using wood chips with a moisture content below 15%.	
ETA HACK 20, 25, 35, 50, 70, 90, 130 and 200 woodchip boilers.	Instruction manual reference "HACK20-200_Bedienun 2011-06_EN" dated June 2011.	Wood pellets ⁽¹⁾ .
Manufactured by ETA Heiztechnik Gesellschaft mit beschrankter Haftung (GmbH), A 4716, Hofkirchen an der Trattnach, Gewerbepark 1, Austria.	An integrated flue gas recirculation system must be used when burning wood pellets.	
ETA Hack 45 woodchip boiler. Manufactured by ETA	Operation manual reference "0000000079 V.003" dated 23rd June 2014.	Wood chips ⁽¹⁾ .
Heiztechnik Gesellschaft mit beschrankter Haftung (GmbH), A4716 Hofkirchen an der Trattnach, Gewerbepark 1, Austria.	Integrated flue gas recirculation system must be used when using wood chips with a moisture content below 15%.	
ETA Hack 45 woodchip boiler Manufactured by ETA Heiztechnik Gesellschaft mit beschrankter Haftung (GmbH), A4716 Hofkirchen an der	Operation manual reference "0000000079 V.003" dated 23rd June 2014.	Wood pellets ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
Trattnach, Gewerbepark 1, Austria.	The fireplace must be installed, maintained and operated in accordance with the following specifications: Integrated flue gas recirculation system must be used when using wood pellets.	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
ETA HACK VR BG 2 333 and ETA HACK VR BG 2 350 moving grate boiler size 2.	Instruction manual dated 12 January 2015 reference "EN00000000039 V.010 X.30.0 3500"	Wood pellets or wood chips ⁽¹⁾ .
Manufactured by ETA Heiztechnik GmbH, Gewerbepark 1, 4716, Austria	3300	
ETA PC 20, 25 and 32 wood pellet boilers.	Instruction manual reference "PC20-32_Bedienung_2011-06 dated June 2011.	Wood pellets (1). EN"
Manufactured by ETA Heiztechnik Gesellschaft mit beschrankter Haftung (GmbH), A 4716, Hofkirchen an der Trattnach, Gewerbepark 1, Austria.	duted Julie 2011.	
ETA PE-K 35, 50, 70 and 90 wood pellet boilers.	Instruction manual reference "PE- K35-90 Bedienung 2011-06 E	Wood pellets ⁽¹⁾ .
Manufactured by ETA Heiztechnik Gesellschaft mit beschrankter Haftung (GmbH), A 4716, Hofkirchen an der Trattnach, Gewerbepark 1, Austria.	dated June 2011.	
ETA PE-K 45 wood pellet boiler.	Operation manual reference "0000000083 V.007" dated 25th June 2014.	Wood pellets ⁽¹⁾ .
Manufactured by ETA Heiztechnik Gesellschaft mit beschrankter Haftung (GmbH), A4716 Hofkirchen an der Trattnach, Gewerbepark 1, Austria.		
ETA PU 7, 11 and 15 wood pellet boilers.	Instruction manual reference "PU7-15_Bedienung_2011-06_I dated June 2011.	Wood pellets ⁽¹⁾ . EN"
Manufactured by ETA Heiztechnik Gesellschaft mit beschrankter Haftung (GmbH),		

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
A 4716, Hofkirchen an der Trattnach, Gewerbepark 1, Austria.		
ETA SH 20, 30, 40, 50 and 60 wood gasification boilers.	Instruction manual reference "SH20-60_Bedienung_2011-06 dated June 2011.	Wood logs ⁽¹⁾ . EN"
Manufactured by ETA Heiztechnik Gesellschaft mit beschrankter Haftung (GmbH), A 4716, Hofkirchen an der Trattnach, Gewerbepark 1, Austria.		
eVolution 4 Inset.	Instruction manual reference "eVo 4&7 Inset MS11-11"	Wood logs ⁽¹⁾ .
Manufactured by Broseley Fires Ltd., Knights Way,	dated 9th November 2011.	
Battlefield Enterprise Park, Shrewsbury, Shropshire, SY1 3AB.	The appliance must be fitted with a system to prevent closure of the secondary air control beyond the 15mm open position.	
eVolution 5 model number M-EVO5.	Instruction manual reference "eVo 5 MS07-11" dated 8th July 2011.	Wood logs ⁽¹⁾ .
Manufactured by Broseley Fires Ltd., Knights Way, Battlefield Enterprise Park, Shrewsbury, Shropshire, SY1 3AB.	The appliance must be fitted with a system that prevents the closure of the air control to less than 70% open.	
Evolution 5 models M-EVO5/MF, EVO5/MF/DLX,	Installation & Operating Instructions manual dated 21st July 2015 reference "Evolution	Wood Logs ⁽¹⁾ .
M-EVO5/MF/LOG & model M-EVO5/MF/LOG/DLX 5kW	5MF Issue 1"	
multi-fuel Stoves.	The appliance must be fitted with a mechanical stop	
Manufactured by Broseley Fires Limited, First Floor, Unit B Knights Court, Archers Way, Battlefield Enterprise Park, Shrewsbury, SY1 3GA	to prevent closure of the secondary air control beyond the 10% open position.	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
eVolution 7 Inset. Manufactured by Broseley	Instruction manual reference "eVo 4&7 Inset MS11-11" dated 9th November 2011.	Wood logs ⁽¹⁾ .
Fires Ltd., Knights Way, Battlefield Enterprise Park, Shrewsbury, Shropshire, SY1 3AB.	The appliance must be fitted with a system to prevent closure of the secondary air control beyond the 8mm open position.	
eVolution 26 boiler stove. Manufactured by Broseley	Instruction manual reference "MS10-11c" dated 9th January 2012.	Wood logs ⁽¹⁾ .
Fires Ltd., Knights Way, Battlefield Enterprise Park, Shrewsbury, Shropshire, SY1 3AB.	The appliance must be fitted with a mechanical stop to prevent closure beyond the 40% open position.	
Evotherm P50, P100, P120, P150, P170, P200 pellet boilers.	Manufacturer's instructions operating manual reference "Version 1/2010/Rev. 4.21".	Wood pellets ⁽¹⁾ .
Manufactured by Evotherm, Heiztechnik Vertriebs Gesellschadft mit beschrankter Haftung (GmbH), Seeleiten 24, AT 5120, St Pantaleon, Austria.		
Evoworld HS50 boiler.	Operation manual reference "OM_HS50_14 Version 1.2"	Wood chips ⁽¹⁾ .
Manufactured by Evoworld	dated January 2014.	
Seeleiten 24, 5120 St. Pantaleon,		
Austria.		
Evoworld HS75 ECO boiler.	Operation manual reference "OM_HS75_14 Version 1.2"	Wood chips (1).
Manufactured by Evoworld	dated January 2014.	
Seeleiten 24, 5120 St. Pantaleon,		
Austria.		

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Evoworld HS100 ECO boiler.	Operation manual reference "OM HS100 14 Version 1.2"	Wood chips ⁽¹⁾ .
Manufactured by Evoworld	dated January 2014	
Seeleiten 24, 5120 St. Pantaleon,		
Austria.		
Evoworld HS120 ECO boiler.	Operation manual reference "OM HS120 14 Version 1.2"	Wood chips ⁽¹⁾ .
Manufactured by Evoworld	dated January 2014.	
Seeleiten 24, 5120 St. Pantaleon,		
Austria.		
Evoworld HS150 ECO boiler.	Operation manual reference "OM HS150 14 Version 1.2"	Wood chips (1).
Manufactured by Evoworld	dated January 2014.	
Seeleiten 24, 5120 St. Pantaleon,		
Austria.		
Evoworld HS170 ECO boiler.	Operation manual reference "OM HS170 14 Version 1.2"	Wood chips ⁽¹⁾ .
Manufactured by Evoworld	dated January 2014.	
Seeleiten 24, 5120 St. Pantaleon,		
Austria.		
Evoworld HS200 ECO boiler.	Operation manual reference "OM HS200 14 Version 1.2"	Wood chips ⁽¹⁾ .
Manufactured by Evoworld	dated January 2014.	
Seeleiten 24, 5120 St. Pantaleon,		
Austria.		
Extraflame:	Manufacturer's instructions reference "004275101 011" dated 5th March 2007.	Wood pellets ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Babyfiamma, Bella and Bella Lux, Clementina Comfort Maxi, Contessa, Divina, Divina Plus and Divina Steel, Duchessa and Duchessa Steel, Ecologica, Esmeralda and Esmeralda Crystal, Falò 1CP, Falò 2CP and Falò 1XP, Isabella, Karolina, Preziosa.		
Manufactured by Extraflame S.p.a in Montecchio Precalcino (Vicenza), Italy.		
Extraflame Comfort Mini.	Manufacturer's instructions reference "004275115 REV	Wood pellets ⁽¹⁾ .
Manufactured by Extraflame S.p.a in Montecchio Precalcino (Vicenza), Italy.	005" dated 2nd October 2006.	
Extraflame Idro. Manufactured by Extraflame	Manufacturer's instructions reference "004275128 REV 002" dated 28th August 2006.	Wood pellets ⁽¹⁾ .
S.p.a in Montecchio Precalcino (Vicenza), Italy.		
Extraflame Lucrezia Idro and Lucrezia Steel.	Manufacturer's instructions reference "004275110 REV 011" dated 12th July 2006.	Wood pellets ⁽¹⁾ .
Manufactured by Extraflame S.p.a in Montecchio Precalcino (Vicenza), Italy.		
Falun Model F9478, Falun II model F9480 I,	Installation and Operation Manual dated 27th July 2015 reference "FALUN – Version	Wood logs ⁽¹⁾ .
Alvesta model F9478 I,	A"	
Alvesta II model F9478 T,	The appliance must be fitted with a modified air regulator	
Landshut model F9478 L,	which has a permanent opening of 388mm2 when in	
Landshut II model F9478 N,	the fully closed position	
Kiruna II model F9478 2,		
Kiruna II box model F9478 4,		

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions
	The fireplace must be No fuel is to be used
	installed, maintained and in the fireplace other than
	operated in accordance with authorised fuels and the
	the following specifications: following fuel or fuels:

Atomic model F9478 G,

Ribe model F9480 E,

Cremona model F9480,

Wikantica model F9480 T and,

Wiesbaden model F9480 2 5kW multifuel stoves

NB: Falun II model number changed from F9478 1 toF9480 1.

Manufactured by THORMA Vyroba k.s., Šavoľská cesta 323/1, 986 01,

Fil'akovo-Priemyselný obvod,

Slovakia

Farringdon 8kW freestanding wood burning stove. Manufactured by Arada Limited, The Fireworks,	Operating & Installation manual dated 01/09/2015 reference "AFS P0134 Rev 04".	Wood logs ⁽¹⁾ .
Weycroft Avenue, Axminster, Devon, EX13 5HU	The appliance must be fitted with a mechanical stop to prevent closure of the air control beyond the 29mm open position	
Fat Penguin, Hungry Penguin and, High and Mighty Penguin 5kW multifuel stoves.	Installation and Operating Instructions manual dated June /2015 reference "CPS 9768"	Wood logs ⁽¹⁾ .
Manufactured by Chilli Penguin Stoves Limited, Castell Bach, Mynydd Nefyn, Pwllheli, LL53 6TL	The appliance must be fitted with a mechanical stop to prevent closure of the secondary air controller beyond 17mm from the closed position	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
Class of fireplace	The fireplace must be	No fuel is to be used
	installed, maintained and operated in accordance with	in the fireplace other than authorised fuels and the
	the following specifications:	following fuel or fuels:
FDC Ariel 5S & 5G 5kW Inset multi-fuel Stoves.	Installation and Operating Instructions dated 04/15	Wood logs ⁽¹⁾ .
	reference "FDC Inserts Issue	
Manufactured by FDC (UK) Ltd	01"	
Unit C4 Dinton Business Park,	Fitted with a mechanical stop to prevent secondary air	
Catherine Ford Road	control closure beyond the	
Dinton, Salisbury, Wiltshire	50% open position	
SP3 5HZ		
FDC TFG 5 5kW Freestanding wood burning Stove.	Installation and Operating Instructions dated 04/15	Wood logs ⁽¹⁾ .
C	reference "TFG Stoves FDC	
Manufactured by FDC (UK) Ltd	Issue 01"	
Unit C4 Dinton Business Park,	Fitted with a mechanical stop to prevent secondary air	
Catherine Ford Road	control closure beyond the	
Dinton, Salisbury, Wiltshire	50% and Primary air control beyond the 10% open positions	
SP3 5HZ		
FDC TFG 8 8kW Freestanding wood burning Stove.	Instructions dated 04/15	Wood logs ⁽¹⁾ .
Manufactured by FDC (UK)	reference "TFG Stoves FDC Issue 01"	
Ltd	Fitted with a mechanical	
Unit C4 Dinton Business Park,	stop to prevent secondary air	
Catherine Ford Road	control closure beyond the 25% open position	
Dinton, Salisbury, Wiltshire		
SP3 5HZ		
FDC Charon 10S & 10G 10kW Inset multi-fuel Stoves.	Installation and Operating Instructions dated 04/15	Wood logs ⁽¹⁾ .
	reference "FDC Inserts Issue	
Manufactured by FDC (UK) Ltd	01"	
Unit C4 Dinton Business Park,	Fitted with a mechanical stop to prevent secondary air	
Catherine Ford Road	stop to prevent becomeny an	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Dinton, Salisbury, Wiltshire	control closure beyond the	
SP3 5HZ	10% open position	
FDC5 Stove. Manufactured by Charlton & Jenrick Ltd., Unit D, Stafford	Instruction manual reference "FDC Issue 02" dated April 2012.	Wood logs ⁽¹⁾ .
Park 2, Telford, Shropshire, TF3 3AR.	The appliance must be fitted with a system that prevents closure of the secondary air control slots beyond the 3.5mm open position.	
FDC5i inset stove. Manufactured by Charlton & Jenrick Ltd., Unit D, Stafford	Instruction manual reference "FDCi Issue 06" dated March 2012.	Wood logs ⁽¹⁾ .
Park 2, Telford, Shropshire, TF3 3AR.	The appliance must be fitted with a system that prevents closure of the secondary air control slots beyond the 3.5mm open position.	
FDC5iT Taper inset stove. Manufactured by Charlton & Jenrick Ltd., Unit D, Stafford	Instruction manual reference "FDCiT Issue 1" dated April 2012.	Wood logs ⁽¹⁾ .
Park 2, Telford, Shropshire, TF3 3AR.	The appliance must be fitted with a system that prevents closure of the secondary air control slots beyond the 5mm open position.	
FDC5iW Wide inset stoves.	Instruction manual reference "FDCi Issue 06" dated March	Wood logs ⁽¹⁾ .
Manufactured by Charlton & Jenrick Ltd., Unit D, Stafford	2012.	
Park 2, Telford, Shropshire, TF3 3AR.	The appliance must be fitted with a system that prevents closure of the secondary air control slots beyond the 9mm open position.	
FDC5W Wide stove. Manufactured by Charlton & Jenrick Ltd., Unit D, Stafford	Instruction manual reference "FDC Issue 02" dated April 2012.	Wood logs ⁽¹⁾ .

The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives
or coatings.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Park 2, Telford, Shropshire, TF3 3AR.	The appliance must be fitted with a system that prevents closure of the secondary air control slots beyond the 7mm open position.	
FDC 8 Freestanding Wood Burning Stove.	Instruction manual reference "FDC issue 03" dated July 2012.	Wood logs ⁽¹⁾ .
Manufactured by Charlton & Jenrick Ltd., Unit D, Stafford Park 2, Telford, Shropshire, TF3 3AR.	The appliance must be fitted with a mechanical stop to prevent secondary air control closure beyond the 5mm open position.	
FDC 8i Inset Wood Burning Stove.	Instruction manual reference "FDCi issue 03" dated July 2012.	Wood logs ⁽¹⁾ .
Manufactured by Charlton & Jenrick Ltd., Unit D, Stafford Park 2, Telford, Shropshire, TF3 3AR.	The appliance must be fitted with a mechanical stop to prevent secondary air control closure beyond the 1mm open position.	
Fireball. Manufactured by LaNordica See Via Symmetry 104 M	Instruction manual reference "7196801-Rev.07" dated 22nd December 2010.	Wood logs ⁽¹⁾ .
Spa, Via Summano 104 M. Precalcino, 36030, Vicenza, Italy.	The appliance must be fitted with a mechanical stop to prevent closure of the secondary air control beyond the 40% open position.	
Firebelly FB 5kW woodburning stove.	Instruction manual reference "EZKA/12 090-3 dated May 2013.	Wood logs ⁽¹⁾ .
Manufactured by Firebelly Stoves Ltd., Unit B, Marshall Hall Mills, Elland, HX5 9DU.		
Firebelly FB2 12Kw wood burning stove.	Instruction manual reference "EZKA/12 090-2" dated May 2013.	Wood logs ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Manufactured by Firebelly Stoves Ltd., Unit B, Marshall Hall Mills, Elland, HX5 9DU.	The appliance must be fitted with a permanent stop to fix the secondary air control to 8mm open when in the closed position.	
Firebird SE 5kW multifuel dry inset room heater.	Instruction manual reference "Print Revision 01: July 2014" dated July 2014.	Wood logs ⁽¹⁾ .
Manufactured by Firebird Heating Solutions Limited, Ballymakeera, Co. Cork, Ireland.	The appliance must be fitted with a mechanical stop to prevent closure of the air control beyond the 32mm open position.	
Firefox 5 Clean Burn II, Gallery Classic 5 Clean Burn, Sirius 405 Clean Burn and Sirius 405 Classic Clean Burn.	Instruction manual reference "FF5CBII REV: A" dated June 2011.	Dry wood logs ⁽¹⁾ .
Manufactured by Percy Doughty & Co Ltd., Imperial Point, Express Trading Estate, Stonehill Road, Farnworth, Bolton, BL4 9TN.	The appliance must be fitted with a mechanical stop to prevent secondary air closure beyond the 50% open position.	
Firefox 5CB (4.9kW); Vega 100CB (4.9kW); Sirius 405CB (4.9kW); Flame 5CB (4.9kW).	Instruction manual reference "FFXCBA" dated January 2010.	Wood logs ⁽¹⁾ .
Manufactured by Percy Doughty & Co Ltd., Imperial Point, Express Trading Estate, Stonehill Road, Farnworth, Bolton, BL4 9TN.		
Firefox 8 Clean Burn, Gallery Classic 8 Clean Burn, Sirius 545 Clean Burn and Sirius 545 Classic Clean Burn.	Instruction manual reference "FF8CB REV: A" dated June 2011.	Dry wood logs ⁽¹⁾ .
Manufactured by Percy Doughty & Co Ltd., Imperial Point, Express Trading Estate, Stonehill Road, Farnworth, Bolton, BL4 9TN.	The appliance must be fitted with a mechanical stop to prevent secondary air closure beyond the 50% open position.	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
Class of Jureplace	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Fireglow ST3, Saltfire ST3 and Ultimo ST3 7.3kW woodburning stoves.	Saltfire ST3, Fireglow ST3 and Ultimo ST3 installation and operation instructions dated 7th July 2015 reference "ST3/	Wood logs ⁽¹⁾ .
Manufactured by Saltfire Stoves Ltd, Station Works, Johns Road, Wareham, BH20 4BG	Version 1.0"	
Fireglow ST4, Saltfire ST4 and Ultimo ST4 7.5kW multifuel stoves.	Saltfire ST3, Fireglow ST3 and Ultimo ST3 installation and operation instructions dated 7th July 2015 reference "ST4/	Wood logs ⁽¹⁾ .
Manufactured by Saltfire Stoves Ltd, Station Works, Johns Road, Wareham, BH20 4BG	Version 1.0"	
Fireline FGi5 stove.	Instruction manual reference "FGi.FPi.FXi Issue 06" dated	Wood logs ⁽¹⁾ .
Manufactured by Charlton & Jenrick Ltd., Unit D, Stafford	March 2012.	
Park 2, Telford, Shropshire, TF3 3AR.	The appliance must be fitted with a system that prevents closure of the secondary air control slots beyond the 3.5mm open position.	
Fireline FGi8, FXi8, & FPi8 Cassette Inset Wood Burning Stoves.	Instruction manual reference "FGi.FPi.FXi issue 07" dated July 2012.	Wood logs ⁽¹⁾ .
Manufactured by Charlton & Jenrick Ltd., Unit D, Stafford Park 2, Telford, Shropshire, TF3 3AR.	The appliance must be fitted with a mechanical stop to prevent secondary air control closure beyond the 1mm open position.	
Fireline FP5W and FX5W Freestanding stove.	Instruction manual reference "FX.FP.Issue 06" dated March 2012.	Wood logs ⁽¹⁾ .
Manufactured by Charlton & Jenrick Ltd., Unit D, Stafford Park 2, Telford, Shropshire, TF3 3AR.	The appliance must be fitted with a system that prevents closure of the secondary air control slots beyond the 7mm open position.	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Fireline FPi5T, FGi5T and FXi5T Taper inset stoves.	Instruction manual reference "FXiT.FPiT.FGiT Issue 01" dated March 2012.	Wood logs ⁽¹⁾ .
Manufactured by Charlton & Jenrick Ltd., Unit D, Stafford Park 2, Telford, Shropshire, TF3 3AR.	The appliance must be fitted with a system that prevents closure of the secondary air control slots beyond the 5mm open position.	
Fireline FPi5W, FGi5W and FXi5W Wide inset stoves.	Instruction manual reference "FGi.FPi.FXi Issue 06" dated March 2012.	Wood logs ⁽¹⁾ .
Manufactured by Charlton & Jenrick Ltd., Unit D, Stafford Park 2, Telford, Shropshire, TF3 3AR.	The appliance must be fitted with a system that prevents closure of the secondary air control slots beyond the 9mm open position.	
Fireline FX8, & FP8 Freestanding Wood Burning Stoves.	Instruction manual reference "FX.FP. Issue 08" dated September 2012.	Wood logs ⁽¹⁾ .
Manufactured by Charlton & Jenrick Ltd., Unit D, Stafford Park 2, Telford, Shropshire, TF3 3AR.	The appliance must be fitted with a mechanical stop to prevent secondary air control closure beyond the 5mm open position.	
Fireline FXi 5kW, Fireline FPi 5kW, Fireline FX5 and Fireline FP5.	Instruction manual reference "Issue 03" dated March 2010.	Wood logs ⁽¹⁾ .
Manufactured by Charlton & Jenrick Ltd., Unit D, Stafford Park 2, Telford, Shropshire, TF3 3AR.	The appliance must be fitted with a system that prevents the closure of the secondary air control beyond the 3.5mm open position.	
Fireline Purevision 5kW Freestanding Wood burning Stove.	Installation and operating instructions manual reference "Purevision Freestanding Issue 02" dated January 2014.	Wood logs ⁽¹⁾ .
Manufactured by Charlton & Jenrick Ltd, Unit D Stafford Park 2, Telford, Shropshire, TF3 3AR.	The appliance must be fitted with a mechanical stop to prevent air supply closure	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications: beyond the 18mm open position.	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Fireline Purevision 5kW i5 Inset Wood burning Stove.	Installation and operating instructions manual reference "Purevision Inset Issue 02" dated January 2014.	Wood logs ⁽¹⁾ .
Manufactured by Charlton & Jenrick Ltd, Unit D Stafford Park 2, Telford, Shropshire, TF3 3AR.	The appliance must be fitted with a mechanical stop to prevent air supply closure beyond the 18mm open position.	
Fireline Purevision 5kW Wide Freestanding Wood burning Stove.	Installation and operating instructions manual reference "Purevision Freestanding Issue 02" dated January 2014.	Wood logs ⁽¹⁾ .
Manufactured by Charlton & Jenrick Ltd, Unit D Stafford Park 2, Telford, Shropshire, TF3 3AR.	The appliance must be fitted with a mechanical stop to prevent air supply closure beyond the 15mm open position.	
Fireline Purevision 5kW i5 Wide Inset Wood burning Stove.	Installation and operating instructions manual reference "Purevision Inset Issue 02" dated January 2014.	Wood logs ⁽¹⁾ .
Manufactured by Charlton & Jenrick Ltd, Unit D Stafford Park 2, Telford, Shropshire, TF3 3AR.	The appliance must be fitted with a mechanical stop to prevent air supply closure beyond the 15mm open position.	
Fireline Purevision 8.5kW Freestanding Wood burning Stove.	Installation and operating instructions manual reference "Purevision Freestanding Issue 02" dated January 2014.	Wood logs ⁽¹⁾ .
Manufactured by Charlton & Jenrick Ltd, Unit D Stafford Park 2, Telford, Shropshire, TF3 3AR.	The appliance must be fitted with a mechanical stop to prevent air supply closure beyond the 22mm open position.	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Fireline Purevision 8.5kW i8.5 Inset Wood burning Stove. Manufactured by Charlton & Jenrick Ltd, Unit D Stafford Park 2, Telford, Shropshire, TF3 3AR.	Installation and operating instructions manual reference "Purevision Inset Issue 02" dated January 2014. The appliance must be fitted with a mechanical stop to prevent air supply closure beyond the 22mm open position.	Wood logs ⁽¹⁾ .
Firematic 25, 50, 90 and 150. Manufactured by HERZ Armaturen Ges.m.b.H, Richard-Strauss-Straße 22,A-1230 Wien, Austria.	Manufacturer's instructions reference "Bedienungsanleitung Firematic V 1.1 ENG doc" dated June 2005.	Chipped wood, wood pellets, or planed wood shavings ⁽¹⁾ .
Firematic 45 and 60. Manufactured by HERZ Armaturen Ges.m.b.H., Richard-Strauss-Straße 22,A-1230 Wien, Austria.	Instruction manual reference "05.007 Operating Instructions – FM (1Ph) 20 35 45 60 v2.3" dated August 2009.	Wood pellets conforming to ÖNORM M7135 with diameter of 6mm or wood chips up to a maximum size of 50mm and maximum water content 35% (1).
Firematic FM 130, FM 151, FM 180 and FM 199. Manufactured by Herz Energietechnik GmbH, Herzstraße 1, 7423 Pinkafeld, Austria.	Instruction manual reference "Operating Instructions Herz firematic 130 – 199 BioControl" version Betriebsanleitung firematic 20-201 BioControl Englisch V 3.1.	Wood chips and wood pellets (1)
Firenzo Aucklander stove. Manufactured by Firenzo Woodfires UK Ltd., 98 Niven Street, Napier 4142, New Zealand.	Instruction manual reference "AL" dated 15th January 2013 and instruction manual reference "AU" dated 1st February 2013. The appliance must be fitted with a mechanical stop to prevent air control slots closure beyond the 6.5mm open	Wood logs ⁽¹⁾ .
Firenzo Bronte stove.	Instruction manual reference "BI" dated 15th January	Wood logs ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

G1 CA 1	G 1: .	
Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Manufactured by Firenzo Woodfires UK Ltd., 98 Niven Street, Napier 4142, New Zealand.	2013 and instruction manual reference "BU" dated 1st February 2013.	
	The appliance must be fitted with a mechanical stop to prevent air control slots closure beyond the 6.5mm open position.	
Firenzo Contessa stove. Manufactured by Firenzo Woodfires UK Ltd., 98 Niven Street, Napier 4142, New Zealand.	Instruction manual reference "CI" dated 15th January 2013 and instruction manual reference "CU" dated 1st February 2013. The appliance must be fitted	Wood logs ⁽¹⁾ .
	with a mechanical stop to prevent air control slots closure beyond the 6mm open position.	
Firenzo Fires Hastings 4.8kW wood burning stove. Manufactured by Firenzo Fires, 98 Niven Street, Napier4142,	User manual reference "HU 2014-10-16" dated 16th October 2014 and installation manual reference "HI 2014-10-16" dated 16th October 2014.	Wood logs ⁽¹⁾ .
New Zealand.	The appliance must be fitted with a mechanical stop to prevent air control closure beyond the 6mm open position.	
Firenzo Lady Kitchener stove. Manufactured by Firenzo Woodfires UK Ltd., 98 Niven Street, Napier 4142, New Zealand.	Instruction manual reference "LKI" dated 15th January 2013 and instruction manual reference "LKU" dated 1st February 2013.	Wood logs ⁽¹⁾ .
	The appliance must be fitted with a mechanical stop to prevent air control slots closure beyond the 6.5mm open position.	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Firenzo Napier 4.8kW free standing wood burning stove. Manufactured by Hewitsons ltd, 98 Niven street, Onekawa, Napier, New Zealand.	Installation manual reference "UKNapierInstall/4.8/v1 dated 24th January 2014 and instruction manual reference "UKNapierUser/4.8/v1 dated 24th January 2014. The appliance must be fitted with a permanent stop to prevent closure of the air slide beyond 7mm.	Dry wood logs ⁽¹⁾ .
Firenzo Wellingtonian stove. Manufactured by Firenzo Woodfires UK Ltd., 98 Niven Street, Napier 4142, New Zealand.	Instruction manual reference "WI" dated 15th January 2013 and instruction manual reference "WU" dated 1st February 2013. The appliance must be fitted with a mechanical stop to prevent air control slots closure	Wood logs ⁽¹⁾ .
	beyond the 6.5mm open position.	
Firestorm 4.5 SE. Manufactured by The Heat	Instruction manual reference "4.5KW SE Issue (6928) 1" dated 28th April 2012.	Wood logs ⁽¹⁾ .
Resistant Glass Company Ltd., Unit 2, Bracewell Avenue, Poulton Industrial Estate, Poulton Le Fylde, FY6 8JF.	The appliance must be fitted with a stop that will only allow a minimum 3mm air gap between the air control plate and the appliance when the secondary air is turned down to its minimum position.	
Firestorm 6.5 SE. Manufactured by The Heat	Instruction manual reference "6.5KW SE Issue (6928) 3" dated 28th April 2012.	Wood logs ⁽¹⁾ .
Resistant Glass Company Ltd., Unit 2, Bracewell Avenue, Poulton Industrial Estate, Poulton Le Fylde, FY6 8JF.	The appliance must be fitted with a stop that will only allow a minimum air gap 6mm between the air control plate and the appliance when the	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications: secondary air is turned down to its minimum position.	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Firestorm 10 SE. Manufactured by The Heat Resistant Glass Company Ltd., Unit 2, Bracewell Avenue, Poulton Industrial Estate, Poulton Le Fylde, FY6 8JF.	Instruction manual reference "10KW SE Issue (6928) 2" dated 28th April 2012. The appliance must be fitted with a stop that will only allow a minimum air gap 6mm between the air control plate and the appliance when the secondary air is turned down to its minimum position.	Wood logs ⁽¹⁾ .
Firewarm 4SE stove. Manufactured by Heat Design, 30 Hawthorn Road, Western Industrial Estate, Naas Road, Dublin 12, Ireland.	Instruction manual reference "FW468SE" dated 25th July 2012. The appliance must be fitted with a system to prevent closure of the secondary air control beyond 5mm open.	Wood logs ⁽¹⁾ .
Firewarm 06C inset stove. Manufactured by Heat Design, 30 Hawthorn Road, Western Industrial Estate, Naas Road, Dublin 12, Ireland.	Instruction manual reference "FW06C" dated 26th July 2012. The appliance must be fitted with a permanent stop to prevent closure of the secondary air control beyond 20% open.	Wood logs ⁽¹⁾ .
Firewarm 6SE stove. Manufactured by Heat Design, 30 Hawthorn Road, Western Industrial Estate, Naas Road, Dublin 12, Ireland.	Instruction manual reference "FW468SE" dated 25th July 2012. The appliance must be fitted with a system to prevent closure of the secondary air control beyond 75% from closed.	Wood logs ⁽¹⁾ .
Firewarm 8SE stove. Manufactured by Heat Design, 30 Hawthorn Road, Western	Instruction manual reference "FW468SE" dated 25th July 2012.	Wood logs ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
Industrial Estate, Naas Road, Dublin 12, Ireland.	The fireplace must be installed, maintained and operated in accordance with the following specifications: The appliance must be fitted with a system to prevent closure of the secondary air control beyond 25% from closed.	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Firewarm 11C Inset stove. Manufactured by Heat Design, 30 Hawthorn Road, Western Industrial Estate, Naas Road, Dublin 12, Ireland.	Instruction manual reference "FW11C" dated 26th July 2012. The appliance must be fitted with a permanent stop to prevent closure of the secondary air control beyond 20% open.	Wood logs ⁽¹⁾ .
Firewarm FW5i Multi-fuel inset stove. Manufactured by Heat Design Ltd., 30 Hawthorn Road, Western Industrial Estate, Naas Road, Dublin 12, Ireland.	Installation and operating instructions reference "FW5i" dated 2nd May 2013. The appliance must be fitted with a mechanical stop to prevent secondary air control closure beyond 3.5mm open.	Wood logs ⁽¹⁾ .
Flatford 5K, Barrington 5K and Hampstead 5K wood burning stoves. Manufactured by Chesneys Ltd., 194-200 Battersea Park Road, London, SW11 4ND.	Instruction manual reference "CH5K – V1" dated 14th March 2012. The appliance must be fitted with a mechanical stop to prevent secondary air control closure beyond the 18mm open position.	Wood logs ⁽¹⁾ .
Flavel Arundel FCMSB 4.9kW Multifuel Stove. Manufactured by BFM Europe Limited, Trentham Lakes North, Stoke-on-Trent, Staffordshire, ST4 4TJ	Manufacturers Installation and Operating Instructions dated 19th November 2014 reference "B-176820" Fitted with the smoke control stop (part number F-176950) to prevent secondary air control closure beyond the 30% open position when sold into smoke control areas	Wood logs ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Flavel Rochester FCSSB 7kW Multifuel Stove.	Installation and Operating Instructions dated 29/02/2016 reference "B-181940 Issue 5".	Wood logs ⁽¹⁾ .
Manufactured by BFM Europe Limited, Trentham Lakes North, Stoke-on-Trent, Staffordshire, ST4 4TJ		
Fogo Montanha Versatile S600SE, Versatile S600 SE Table, Versatile S600 SE	Instruction manual reference "S600 –UK V1" dated 2014.	Wood pellets ⁽¹⁾ .
Spider,	The appliance must be fitted with a permanent stop or other	
Versatile S600 SE Square,	measure to prevent closure of the air control beyond the 40%	
Versatile S600 SE Cube,	open position.	
Versatile S600 SE 2X Cube and Versatile S600 SE Round wood-burning stoves manufactured by		
Fogo Montanha (Solzaima, S.A.)		
Rua dos Outarelos, 111 3750-362 Belazamia do Chao, Portugal.		
Franco Belge Model 134 08 11 Savoy EA (8kW output) wood burning stove.	Instructions manual reference "1290-1" dated 9th July 2009.	Wood logs ⁽¹⁾ .
Manufactured by Franco Belge, Staub Fonderie SA, Rue Orphée Variscotte, 59660, Merville, France.		
Franco Belge Model 134 08 09 Savoy Mk II Elegance multifuel stove with KEA 13408 smoke control kit.	Instructions manual reference "1290-1" dated 9th July 2009.	Wood logs ⁽¹⁾ .
Manufactured by Franco Belge, Staub Fonderie SA,		

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Rue Orphée Variscotte, 59660, Merville, France.		
Franco Belge Montfort MK2 wood burning stove.	Instruction manual reference "1295-3" dated 17th November 2009.	Wood logs ⁽¹⁾ .
Manufactured by Franco Belge, Staub Fonderie SA, Rue Orphée Variscotte, 59660, Merville, France.	The appliance must be fitted with a mechanical stop to prevent closure of the secondary air control beyond the 25% open position.	
Fröling Lambdamat commercial wood chip boiler models 500, 750 and 1000.	Operating and installation manual reference "B 069 01 04" dated February 2004.	Wood chips (1).
Manufactured by Fröling Heizkessel-und Behälterbau Ges.m.b.H., Industriestraße 12, A-4710 Grieskirchen, Austria.		
Froling P1 7, 10, 15 and 20 pellet boilers.	Operating instructions manual reference "B1000013_en Edition 15/07/2014" detail 15th	Wood pellets ⁽¹⁾ .
Manufactured by Froling Heizkessel und Behalterbau GmbH, A-4710 Grieskirchen, Industriestrasse 12, Austria.	Edition 15/07/2014" dated 15th July 2014.	
Froling P4 45 pellet boiler.	Operating instructions manual reference "BO870114 en	Wood pellets ⁽¹⁾ .
Manufactured by Froling Heizkessel und Behalterbau GmbH, A-4710 Grieskirchen, Industriestrasse 12, Austria.	Edition 18/07/2014" dated 18th July 2014.	
Fröling P4 8, 15, 20, 25, 32, 38, 48 and 60 pellet boilers.	Instruction manual reference "BO430408 _en" dated July 2009.	Wood pellets with a diameter of 6mm ⁽¹⁾ .
Manufactured by Fröling Heizkessel-und Behälterbau Ges.m.b.H., Industriestraße 12, A-4710 Grieskirchen, Austria.		
Fröling P4 80 and P4 100 wood pellet boilers.	Instruction manual reference "B043 – Version 8" dated May 2012.	Wood pellets ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Manufactured by Fröling Heizkessel-und Behälterbau Ges.m.b.H., Industriestraße 12, A-4710 Grieskirchen, Austria.		
Froling S4 Turbo 15 15kW; Froling S4 Turbo 22 22kW; Froling S4 Turbo 28 28kW; Froling S4 Turbo 34 34kW; Froling S4 Turbo 40 40kW; Froling S4 Turbo 50 50kW; and Froling S4 Turbo 60 60kW.	Assembly instruction manual reference "M0970208" dated November 2008 and operating instruction manual reference "B0510108" dated November 2008.	Wood logs ⁽¹⁾ .
Manufactured by Fröling Heizkessel-und Behälterbau Ges.m.b.H., Industriestraße 12, A-4710 Grieskirchen, Austria.		
Froling T4 130 and 150 wood chip and pellet boilers.	Operating instructions manual reference "BO830113_en Edition 06/11/2013" dated 6th	Wood pellets or wood chips ⁽¹⁾ .
Manufactured by Froling Heizkessel und Behalterbau GmbH, A-4710 Grieskirchen, Industriestrasse 12, Austria.	November 2013.	
Fröling T4 24, 30, 40, 50, 60, 75, 90, 100 and 110kW boilers.	Instruction manual reference "B071 - Version 05" dated May 2012.	Wood pellets or wood chips ⁽¹⁾ .
Manufactured by Fröling Heizkessel-und Behälterbau Ges.m.b.H., Industriestraße 12, A-4710 Grieskirchen, Austria.	141dy 2012.	
Fröling Turbomatic 28, 35, 48 and 55.	Installation instructions reference "M 060 01 03"	Wood chips with less than 35% moisture content that
Manufactured by Fröling Heizkessel-und Behälterbau Ges.m.b.H., Industriestraße 12, A-4710 Grieskirchen, Austria.	dated November 2003 and operating instructions reference "99229a" dated August 2002.	meet ÖNORM (a) M 7133: 1998 size class G30 or wood pellets of 6mm diameter and a moisture content below 10%
Fröling Turbomatic 85, 100 and 110.	Installation instructions reference "M 060 01 03" dated November 2003	Wood chips with less than 35% moisture content that meet ÖNORM (a) M 7133; 1998
Manufactured by Fröling Heizkessel-und Behälterbau (1) The fiel must not contain beloeget.	and operating instructions	size class G30 or G50, wood pellets of 6mm diameter and a

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Ges.m.b.H., Industriestraße 12, A-4710 Grieskirchen, Austria.	reference "99229a" dated August 2002.	moisture content below 10% (1).
Fröling Turbomat 150 and 220. Manufactured by Fröling Heizkessel-und Behälterbau Ges.m.b.H., Industriestraße 12, A-4710 Grieskirchen, Austria.	Manufacturer's instructions reference "BO310003" dated August 2003.	Wood pellets, or wood chips ⁽¹⁾ .
Fröling Turbomat 320 and 500. Manufactured by Fröling Heizkessel-und Behälterbau Ges.m.b.H., Industriestraße 12, A-4710 Grieskirchen, Austria.	Manufacturer's instructions reference "B0340004" dated November 2004.	Wood pellets, or wood chips (1)
Fröling TX150 150kW boiler with Exhaust Gas Recirculation device. Manufactured by Fröling Heizkessel-und Behälterbau Ges.m.b.H., Industriestraße 12, A-4710 Grieskirchen, Austria.	Installation instruction manual reference "M1130009" dated September 2010 and operating instruction manual reference "B 067 00 09" dated September 2010.	Wood chips with a moisture content $\leq 30\%$ and a maximum cross sectional area of 5cm2 or wood pellets with a moisture content of $\leq 10\%$ and a maximum diameter of 10mm $^{(1)}$.
Fröling TX 200 199kW and TX 250 250kW boilers with Exhaust Gas Recirculation device. Manufactured by Fröling Heizkessel-und Behälterbau Ges.m.b.H., Industriestraße 12, A-4710 Grieskirchen, Austria.	Instruction manual reference "B067 – Version 03" dated May 2012.	Wood pellets or wood chips ⁽¹⁾ .
Fröling:	Operating instructions	Wood logs or wood pellets (1).
SP Dual 15kW boiler;	reference "B0760212_en Edition 09/10/2012" dated 9th October 2012.	
SP Dual 22kW boiler;		
SP Dual 28kW boiler;		
SP Dual 34kW boiler; and		
SP Dual 40kW boiler.		

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Manufactured by Fröling Heizkessel-und Behälterbau Ges.m.b.H., Industriestraße 12, A-4710 Grieskirchen, Austria.		
Future Fires Panoramic FX1. Manufactured by Gen-Fab Ltd., Swinton Bridge Industrial Estate, Whitelee Rd, Swinton, S64 8BH.	Instruction manual reference "PANFXREV2" dated 31st October 2012.	Wood logs ⁽¹⁾ .
Gilles HPK-RA 13kW, 15kW, 20kW, 25kW, 30kW, 35kW, 40kW, 45kW, 49kW, 60kW, 70kW, 75kW, 85kW, 95kW, 100kW, 120kW, and 145kW.	Manufacturer's instructions reference "Gilles/0-145/1" dated January 2007.	Wood pellets, or wood chips (1).
Manufactured by Gilles Energie – und Umwelttechnik Gmbh, Koaserbauer Str. 16A-4810 Gmunden, Austria.		
Gilles HPK-RA 160. Manufactured by Gilles Energie – und Umwelttechnik Gmbh, Koaserbauer Str. 16A-4810 Gmunden, Austria.	Instruction and operating manuals reference "BD-200-01a-01" dated November 2008, "BD-200-01a-02" dated November 2008, "BD-200-01a-03" dated November 2008, "BD-200-01a-04" dated November 2008, "BD-200-01a-06" dated November 2008, "BD-200-03a-07" dated November 2008, and "BD-200-03a-09" dated November 2008.	Wood chips and wood pellets (1).
Gilles HPK USK 150kW, 180kW, 240kW and 300kW. Manufactured by Gilles Energie – und Umwelttechnik Gmbh, Koaserbauer Str. 16A-4810 Gmunden, Austria.	Manufacturer's instructions reference "Gilles/150-300/1" dated January 2007.	Wood pellets, or wood chips

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Gilles HPK USK 360kW. Manufactured by Gilles Energie – und Umwelttechnik Gmbh, Koaserbauer Str. 16A-4810 Gmunden, Austria.	Manufacturer's operating instructions reference "Gilles 360/1" dated January 2008.	Wood pellets or wood chips ⁽¹⁾ .
Gilles HPKI-K 180, 195, 240, 300, 360, 450, 550, 700, 900, 995, 1200 and 1600. Manufactured by Gilles Energie – und Umwelttechnik Gmbh, Koaserbauer Str. 16A-4810 Gmunden, Austria.	Instruction manual reference "Operating Instruction HPKI-K Underfeed Stoking. 1-general-hpki-k underfeed stoking" dated November 2008.	Wood chips and pellets ⁽¹⁾ .
Gilles HPKI-R 999 kW biomass boiler manufactured by Gilles Energie und Umwelttechnik GmbH & Co KG Limited, Koaserbauerstraβe, A-4180 Gmuden, Austria.	Installation, operation and maintenance manual reference "BD-HPKI-R-999-01.1 Version 02/2014" dated 23rd July 2014. The appliance must be fitted with cyclone dust arrestment.	Wood chips ⁽¹⁾ .
Gilles UTSK 450kW, 550kW, 700kW, 900kW, 1200kW, and 1600kW Boilers. Manufactured by Gilles Energie – und Umwelttechnik Gmbh, Koaserbauer Str. 16A-4810 Gmunden, Austria.	Manufacturer's operating instructions reference "Gilles 360/1" dated January 2008.	Wood pellets or wood chips ⁽¹⁾ .
Gozney G1200/W, G1400/W, G1600/W and G1800/W wood-burning pizza ovens. Manufactured by Gozney Ltd., Units 18 & 19, Radar Way, Christchurch Business Park, The Runway, Christchurch, BH23 4JE.	Operational manual reference "Version 1.1" dated July 2013.	Wood logs ⁽¹⁾ .
Grant Spira Condensing Wood Pellet Boiler 6-26kW model	Instruction manual reference "IRL NO.012 Rev; 1" dated April 2012.	6mm wood pellets ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
number WPS626 and 9-36kW model number WPS936.		<u> </u>
Manufactured by Grant UK Ltd., Hopton House, Hopton Industrial Estate, Devizes, Wiltshire, SN10 2EU.		
Grant Vectra 4-16 16kW condensing wood pellet boiler.	Installation & Servicing Instructions manual dated July 2015 reference "Part	Wood Pellets (1).
Manufactured by Grant(UK) Limited,	No. DOC.47 Rev.06 13/07/15"	
Hopton House, Hopton Industrial Estate, Devizes, Wiltshire, SN10 2EU		
Graphite 5 model number GR905 4.9 kW multifuel stove.	Instruction manual reference "GR905/UK/NI/ROI/V3 18-07-14" dated July 2014.	Wood logs ⁽¹⁾ .
Manufactured by Hi-Flame Fireplace UK Limited, Unit 5A, Holmes Chapel Business Park, Manor Lane, Holmes Chapel, Cheshire CW4 8AF.	The appliance must be fitted with a mechanical stop to prevent closure of the main air control beyond the 50% open position.	
Graphite 8 model number GR908 8kW multifuel stove.	Instruction manual reference "GR908/UK/NI/ROI/V4-D 18-07-14" dated July 2014.	Wood logs ⁽¹⁾ .
Manufactured by Hi-Flame Fireplace UK Limited, Unit 5A, Holmes Chapel Business Park, Manor Lane, Holmes Chapel, Cheshire CW4 8AF.	The appliance must be fitted with a mechanical stop to prevent secondary air control closure beyond the 20% open position, and a 70mm opening of the door rope seal.	
Greencast 5MF Traditional, Greencast 5MF Modern, Greencast 8MF Traditional and Greencast 8MF Modern multifuel stoves.	Installation and operating instructions manual reference "Greencast MF&WD Version 1" dated June 2013.	Wood logs ⁽¹⁾ .
Manufactured by Capital Fireplaces Ltd., 12-17 Henlow	The appliance must be fitted with the manufacturer's smoke control kit.	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Trading Estate, Henlow Camp, Hitchin, SG16 6DS.		
Greencast 5WD Traditional and Greencast 5WD Modern woodburning stoves.	Installation and operating instructions manual reference "Greencast MF&WD Version 1" dated June 2013.	Wood logs ⁽¹⁾ .
Manufactured by Capital Fireplaces Ltd., 12-17 Henlow Trading Estate, Henlow Camp, Hitchin, SG16 6DS.		
Greencast 8WD Traditional and Greencast 8WD Modern wood-burning stoves.	Installation and operating instructions manual reference "Greencast MF&WD Version 1" dated June 2013.	Wood logs ⁽¹⁾ .
Manufactured by Capital Fireplaces Ltd., 12-17 Henlow Trading Estate, Henlow Camp, Hitchin, SG16 6DS.	The appliance must be fitted with the manufacturer's smoke control kit.	
Green Energy Engineering PROPEL P70 and P100 Pellet Boilers.	Instruction manual reference "PROPEL Wood Pellet Boiler Models: P70 – P100 Version 2" dated 23rd September 2012.	Wood pellets ⁽¹⁾ .
Manufactured by Kozlusan – Salih Kozlu, Kayalioilu Kasabasi, Akhisar, Manisa, PK 23, Turkey.		
Green Energy Engineering PROPEL P25 and P40 wood pellet boilers.	Instruction manual reference "Owner's Manual PROPEL Wood Pellet Boiler Version 2" dated 23rd September 2012.	Wood pellets ⁽¹⁾ .
Manufactured by Kozlusan – Salih Kozlu, Kayalioilu Kasabasi, Akhisar, Manisa, PK 23, Turkey.		
Green Energy Engineering SLIMPEL S25.	Instruction manual reference "Owner's Manual SLIMPEL Wood Pellet Boiler Version 2"	Wood pellets ⁽¹⁾ .
Manufactured by Kozlusan – Salih Kozlu, Kayalioilu Kasabasi, Akhisar, Manisa, PK 23, Turkey.	dated 23rd September 2013.	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
Class of fireplace	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Greenflame 28 Pellet Boiler. Manufactured by Trianco Ltd., Thorncliffe, Chapletown, Sheffield, S35 2PH.	Instruction manual reference "Installation & Operation Manual V.2.1" dated July 2012.	6mm wood pellets ⁽¹⁾ .
Greenflame Eco 10kW Model Number FG3730, FG3731, FG3790, FG3791 Greenflame Eco 15kW Model Number FG3732, FG3733, FG3792, FG3793 Greenflame Eco 25kW Model Number FG3734, FG3735, FG3794, FG3795 Greenflame Eco 40kW Model Number FG3736, FG3737, FG3796, FG3797	Greenflame Eco Wood Pellet Boiler 10-60 kW Installation, Operation and servicing Instructions manual dated April 2015 reference "400012"	Wood pellets ⁽¹⁾ .
rG3743, FG3798, FG3799 manufactured by T.R. Engineering Ltd, Unit 7 Newton Chambers Way, Thornecliffe, Chapeltown, Sheffield, S35 2PH	Instruction manual reference	Wood pollots with a diameter
Guntamatic Biocom and Powercorn 50 and 75. Manufactured by GUNTAMATIC Heiztechnik GmbH A-4722 PEUERBACH Bruck 7, Austria.	Instruction manual reference "GUN/BIO/OP/ VI/0709" dated 29th July 2009.	Wood pellets with a diameter of 6mm and a length of between 10 and 30 mm ⁽¹⁾ .
Guntamatic Biocom and Powercorn 100. Manufactured by GUNTAMATIC Heiztechnik GmbH A-4722 PEUERBACH Bruck 7, Austria.	Instruction manual reference "GUN/BIO/OP/VI/0709" dated 29th July 2009.	Wood pellets with a diameter of 6mm and a length of between 10 and 30 mm, or wood chip with less than 35% moisture content and meeting

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
		ÖNORM M 7133:1998 size class G30 ⁽¹⁾ .
Guntamatic Powerchip 50 and 75. Manufactured by Guntamatic Heiztechnik GmbH A-4722 PEUERBACH Bruck 7, Austria.	Instruction manual reference "GUN/POW/OP/VI/0709" dated 29th July 2009.	Wood pellets with a diameter of 6mm and a length of between 10 and 30 mm ⁽¹⁾ .
Guntamatic Powerchip 100. Manufactured by GUNTAMATIC Heiztechnik GmbH A-4722 PEUERBACH Bruck 7, Austria.	Instruction manual reference "GUN/POW/OP/VI/0709" dated 29th July 2009.	Wood pellets with a diameter of 6mm and a length of between 10 and 30 mm, or wood chip less with than 35% moisture content and meeting ÖNORM M 7133:1998 size class G30 ⁽¹⁾ .
Guntamatic PRO 175, PRO 199, PRO 250. Manufactured by GUNTAMATIC Heiztechnik GmbH A – 4722 PEUERBACH, Bruck 7, Austria.	Operating instructions and system log book reference "PRO-13-00-00-00-01-BADE" dated October 2013.	Wood chips or wood pellets ⁽¹⁾ .
Guntamatic PRO-Flex 175, PRO-Flex 199, PRO-Flex 250. Manufactured by GUNTAMATIC Heiztechnik GmbH A – 4722 PEUERBACH, Bruck 7, Austria.	Operating instructions and system log book reference "PRO-Flex-A-00-00-01-BADE" dated October 2013.	Wood pellets ⁽¹⁾ .
Hamont CATfire 350 USZI pellet boiler fitted with CATfire 300 cyclone. Manufactured by Hamont Contracting and Trading, spol. s.r.o., Sedlište 227, postal code 739 36, district Frýdek-Mistek, Czech Republic.	Operating instruction reference "Operating Manual for Boilers CATfire 150-500kW" dated 1st January 2008.	Wood pellets with a diameter of 6mm and a maximum length of 30 mm ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Hampstead 8, Hampstead LS 8, Hampstead XLS 8, Belgravia 8, Barrington 8, Petworth 8 and Flatford 8 stoves. Manufactured by Chesneys Ltd., 194-200 Battersea Park Road, London, SW11 4ND.	Instruction manual reference "CH8K - V12" dated 31st October 2011. The appliance must be fitted with a system that prevents closure of the air controls further than 40mm from open and with a permanent stop	Wood logs ⁽¹⁾ .
Road, London, 5 W 11 41VD.	that prevents closure of the secondary air slider beyond 30% open.	
Handöl 31, Handöl 31A, Handöl 32, Handöl 32A, Handöl 33T, Handöl 34T, Handöl 35T,Varde Ovne Look 1, Varde Ovne Look 2, Varde Ovne Look 3.	Installation instructions reference "IAV SE/EX 0811-4 511941" and lighting instructions reference "BAV SE/EX H30 511942".	Untreated dry wood with less than 20% moisture ⁽¹⁾ .
Manufactured by Nibe AB, Box 134, SE-285 23 Markaryd, Sweden.	The appliance must be fitted with a permanent stop on the air inlet to prevent closure beyond the 45% open position.	
Handöl 50, Handöl 51, Handöl 52, Handöl 52T, Handöl 53, Handöl 54, Handöl 54T, Handöl 51L, Varde Ovne S1, Varde Ovne S2, Varde Ovne S3.	Installation instructions reference "IAV SE/EX 0737-4 511866" and lighting instructions reference "BAV SE/EX 0717-1 511865".	Untreated dry wood with less than 20% moisture ⁽¹⁾ .
Manufactured by Nibe AB, Box 134, SE-285 23 Markaryd, Sweden.	The appliance must be fitted with a permanent stop on the air inlet to prevent closure beyond the 45% open position.	
Harrie Leenders Boxer Plus & Boxer Black Wood Burning Stoves.	Instruction manual reference "Boxer Plus manual Issue 1" dated January 2014.	Wood logs ⁽¹⁾ .
Manufactured by Harrie		
Leenders Industrieweg		
25 5688 DP Oirschot Netherlands.		

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Harrie Leenders Cylon; Harrie Leenders Doran 160; Harrie Leenders Doran 190; Harrie Leenders Fuga S; Harrie Leenders Fuga eL; Harrie	Instruction manual reference "Supplementary Instructions Amended June 2010" dated June 2010.	Wood logs ⁽¹⁾ .
Leenders Stor; Harrie Leenders Signa.	The appliance must be fitted with a mechanical stop to prevent closure of the air	
Manufactured by Harrie Leenders, Industrieweg 25, 5688 DP Oirschot, The Netherlands.	slide beyond the 15mm open position.	
HDG Compact models 25/35 (25kW, 35kW) wood chip and pellet boilers.	Operating instructions reference "HDG Compact Version V01" dated April 2009.	Wood chips or wood pellets (1)
Manufactured by HDG Bavaria, Gesellschaft mit beschränkter Haftung (GmbH) Siemensstrasse 22, 84323 Massing, Germany.		
HDG Compact 45 (45 kW) boiler.	Manual reference "9980001529 V 05.1" dated April 2014 and additional	Wood chips or wood pellets (1)
Manufactured by HDG Bavaria Gesellschaft mit beschrankter Haftung (GmbH) Siemensstraße 22 D-84323 Massing, Germany.	supplementary installation instructions reference "IN1295" dated July 2014.	
HDG Compact models 50/65 (50kW, 65kW) wood chip and pellet boilers.	Operating instructions reference "HDG Compact Version V03" dated April 2009.	Wood chips or wood pellets (1)
Manufactured by HDG Bavaria, Gesellschaft mit beschränkter Haftung (GmbH) Siemensstrasse 22, 84323 Massing, Germany.	2007.	
HDG Compact model 80 (80kW) wood chip and pellet boiler.	Operating instructions reference "HDG Compact Version V03" dated April 2009.	Wood chips or wood pellets (1).

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Manufactured by HDG Bavaria, Gesellschaft mit beschränkter Haftung (GmbH) Siemensstrasse 22, 84323 Massing, Germany.		
HDG Compact 99 (99 kW), 194 (194 kW) and Compact 199 (199 kW) boilers with model HDG 3113 cyclone. Manufactured by HDG Bavaria Gesellschaft mit beschrankter Haftung (GmbH) Siemensstraße 22 D-84323 Massing, Germany.	Manual reference "9980001520 V.03.01" dated March 2013 and additional supplementary installation instructions reference "IN1296" dated July 2014.	Wood chips or wood pellets ⁽¹⁾ .
HDG Compact model 100 (100kW) wood chip and pellet boiler; HDG Compact model 150, 200 (150kW, 200kW) wood chip and pellet boiler with model HDG 3113 cyclone.	Operating instructions reference "HDG Compact 100-200 Version V1" dated July 2008.	Wood chips or wood pellets ⁽¹⁾ .
Manufactured by HDG Bavaria, Gesellschaft mit beschränkter Haftung (GmbH) Siemensstrasse 22, 84323 Massing, Germany.		
HDG Euro models 30, 40 and 50 (30kW, 40kW and 50kW) wood log boilers.	Operating instructions reference "HDG Euro V3.0 with HDG Lambda Control 1 Version V1" dated June 2008.	Split wood logs of 500 mm length and maximum edge length of 120 mm and a residual moisture content of
Manufactured by HDG Bavaria, Gesellschaft mit beschränkter Haftung (GmbH) Siemensstrasse 22, 84323 Massing, Germany.	2000.	20% ⁽¹⁾ .
HDG K10, K15, K21 and K26 pellet boilers.	Operation manual reference "Manual ref: 99800001036" dated November 2011 and	Wood pellets ⁽¹⁾ .
Manufactured by	additional supplementary installation instructions K and	
HDG Bavaria GmbH		

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Heating systems for wood	R Series reference "IN2014" dated January 2014.	
Siemensstraße 22	dated January 2014.	
D-84323 Massing, Germany.		
HDG Navaro models 20, 25 and 30 (20kW, 25kW and 30kW) wood log boilers.	Operating instructions reference "HDG Navora 20/25/30 with HDG Lambda Control 1 Version V2" dated	Split wood logs of 500 mm length and maximum edge length of 120 mm and a residual moisture content of
Manufactured by HDG Bavaria, Gesellschaft mit beschränkter Haftung (GmbH) Siemensstrasse 22, 84323 Massing, Germany.	June 2008.	20% ⁽¹⁾ .
HDG Pelletmaster model PM15, 15kW wood pellet boiler.	Operating instructions reference "HDG Pelletmaster Version 1" dated October 2006.	Wood pellets ⁽¹⁾ .
Manufactured by HDG Bavaria Gesellschaft mit beschrankter Haftung (GmbH) Siemensstraße 22 D-84323 Massing, Germany.		
HDG R20, R25 and R30 wood log boilers.	Manual reference "9980000819" dated August 2011 and additional	Wood logs ⁽¹⁾ .
Manufactured by HDG Bavaria GmbH Heating systems for wood, Siemensstraße 22,	supplementary installation instructions K and R Series reference "IN2014" dated January 2014.	
D-84323 Massing, Germany		
Heat Design TR5c inset stove.	Instruction manual reference "TRc Issue 02" dated April	Wood logs ⁽¹⁾ .
Manufactured by Charlton & Jenrick Ltd., Unit D Stafford	2012.	
Park 2, Telford, Shropshire, TF3 3AR.	The appliance must be fitted with a system that prevents closure of the secondary air control slots beyond the 3.5mm open position.	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Conditions	
The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Instruction manual reference "TRiT Issue 01" dated April 2012.	Wood logs ⁽¹⁾ .
The appliance must be fitted with a system that prevents closure of the secondary air control slots beyond the 5mm open position.	
Instruction manual reference "TRc Issue 02" dated April 2012.	Wood logs ⁽¹⁾ .
The appliance must be fitted with a system that prevents closure of the secondary air control slots beyond the 9mm open position.	
Instruction manual reference "HD TR Freestanding. Issue 01" dated January 2013.	Wood logs ⁽¹⁾ .
The appliance must be fitted with a mechanical stop to prevent secondary air control closure beyond the 5mm open position.	
Instruction manual reference "TRc issue 03" dated July 2012.	Wood logs ⁽¹⁾ .
The appliance must be fitted with a mechanical stop to prevent secondary air control closure beyond the 1mm open position.	
Installation and Operating instructions dated 1st January 2016 reference "HELIOS INSTRUCTION - REV D".	Wood logs ⁽¹⁾ .
	The fireplace must be installed, maintained and operated in accordance with the following specifications: Instruction manual reference "TRiT Issue 01" dated April 2012. The appliance must be fitted with a system that prevents closure of the secondary air control slots beyond the 5mm open position. Instruction manual reference "TRc Issue 02" dated April 2012. The appliance must be fitted with a system that prevents closure of the secondary air control slots beyond the 9mm open position. Instruction manual reference "HD TR Freestanding. Issue 01" dated January 2013. The appliance must be fitted with a mechanical stop to prevent secondary air control closure beyond the 5mm open position. Instruction manual reference "TRc issue 03" dated July 2012. The appliance must be fitted with a mechanical stop to prevent secondary air control closure beyond the 5mm open position. Instruction manual reference "TRc issue 03" dated July 2012. The appliance must be fitted with a mechanical stop to prevent secondary air control closure beyond the 1mm open position. Installation and Operating instructions dated 1st January 2016 reference "HELIOS

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Road, Farnworth, Bolton, BL4 9TN		
Henley Achill Wood Burning Stove.	Instruction manual reference "Version 1" dated November 2012.	Wood logs ⁽¹⁾ .
Manufactured by Henley Stoves Ltd., Ard Ri Marble, Curraheen, Tralee, Co. Kerry, Ireland.	The appliance must be fitted with a mechanical stop to prevent closure of the secondary air control slots beyond the 50% open position.	
Henley Druid 5 multifuel stove.	User manual reference "Version 2.0" dated May 2013.	Wood logs ⁽¹⁾ .
Manufactured by Henley Stoves Ltd., Ard Ri Marble, Curraheen, Tralee, Co. Kerry, Ireland.	The appliance must be fitted with a mechanical stop to prevent closure of the secondary air control slot beyond the 30% open position.	
Henley Druid 8 multifuel stove.	User manual reference "Version 2.0" dated June 2013.	Wood logs ⁽¹⁾ .
Manufactured by Henley Stoves Ltd., Ard Ri Marble, Curraheen, Tralee, Co. Kerry, Ireland.	The appliance must be fitted with a mechanical stop to prevent closure of the secondary air control slot beyond the 40% open position.	
Hereford 5 and 7 multifuel stoves. Manufactured by Broseley Fires Limited, First Floor, Unit	Installation & Operating Instructions manual dated 8th July 2015 reference "Mar 14/ GB Issue 5"	Wood logs ⁽¹⁾ .
B Knights Court, Archers Way, Battlefield Enterprise Park, Shrewsbury, SY1 3GA	The appliance must be fitted with a mechanical stop to prevent closure of the secondary air control slide beyond the 10mm open position.	
Hergom E-30 XS 4.9kW multi-fuel stove.	Use and maintenance instructions dated 01/05/2015 reference "C03602 .10.2015 VERSION 4".	Wood logs ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Manufactured by Industrias Hergóm, S.A, Soto de la Marina, Cantabria, Spain	The appliance must be fitted with a mechanical stop to prevent closure of the secondary air control beyond the 65mm open position	
Herz BioFire BF 500, BF 600, BF 800, and BF 1000. Manufactured by Herz Energietechnik GmbH, Herzstrasze 1, 7423 Pinkafeld, Austria.	Instruction manual reference "Betriebsanleitung Biofire 500-1000 Biocontrol Englisch V1.2.doc".	Wood chips and pellets ⁽¹⁾ .
Herz Firematic 201, 249, 251, 299, 301 boilers. Manufactured by Herz Energietechnik GmbH, Herzstrasze 1, 7423 Pinkafeld,	Operating instructions manual reference "Betriebsanleitung_firematic_20 V1 2 (2)" dated May 2013.	Wood pellets and Wood chips (1) 0-301_Touch_Englisch
Austria. Herz Firematic 349 (349kW), 401 (401kW) and 499 (499kW) boilers. Manufactured by Herz Energietechnik GmbH. Herstraße 1, 7423 Pinkafeld	Operating Instructions dated December 2014 reference "Betriebsanleitung_Firematic_2 " and supplementary document dated 28th April 2015 reference "CleanAirAct1993_20150507H	
Austria Herz Firematic FM 80 and Herz Firematic FM 100. Manufactured by Herz Energietechnik GmbH, Herzstrasze 1, 7423 Pinkafeld, Austria.	Assembly and installation instructions "HERZ firematic 20 - 101 BioControl". Reference "04.001", installation instructions "Herz Firematic (1Ph) 20-101" and operating instructions "HERZ firematic 20 - 101 BioControl" reference "Betriebsanleitung firematic 20-101 BioControl Englisch V 2.53.doc".	Wood chips and pellets ⁽¹⁾ .
Heta Inspire 55 and 55H 6.3kW stoves.	Operating Instructions dated July 2015 reference "Pevex1020/AH/ver2."	Wood Logs ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Manufactured by Heta A/S, Jupitervej 22,7620 Lemvig, Denmark	Fitted with a mechanical stop to prevent air control closure beyond the 41% open position	
Hestia 5 EV-A5-CD1 wood burning stove.	Installation and operating instructions manual reference "Hestia EVA5/A7 Issue 1"	Wood logs ⁽¹⁾ .
Manufactured by Broseley Fires Limited, First Floor Unit B, Knights Court, Archers Way, Battlefield Enterprise Park, Shrewsbury, SY1 3GA.	The appliance must be fitted with a permanent stop to fix the secondary air slide at a minimum of 23mm open.	
Hestia 7 EV-A7-CD1 wood burning stove. Manufactured by Broseley	Installation and operating instructions manual reference "Hestia EVA5/A7 Issue 1" dated 30th June 2014.	Wood logs ⁽¹⁾ .
Fires Limited, First Floor Unit B, Knights Court, Archers Way, Battlefield Enterprise Park, Shrewsbury, SY1 3GA.	The appliance must be fitted with a permanent stop to fix the secondary air slide at a minimum of 50mm open.	
Heta Inspire 40 and Heta Inspire 45 stoves. Manufactured by Heta A/S, Jupitervej 22, 7620 Lemvig,	Operating and installation instruction manual reference "Pevex1020/AH/ver1: Jan 2013" dated January 2013.	Wood logs ⁽¹⁾ .
Denmark.	The appliance must be fitted with a permanent stop to fix the air control valve at 41% open when in the fully closed position.	
Heta Scanline 500D, 510D, 520D and 530D wood burning stoves.	Instruction manual reference "Pevex1005/AH/ver2" dated June 2011.	Dry wood logs ⁽¹⁾ .
Manufactured by Heta A/S, Jupitervej 22, 7620 Lemvig, Denmark.	The appliance must be fitted with permanent stops to ensure that the primary and secondary air controls do not close beyond 95% and 50% respectively.	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Heta Scanline 7D, 7AD, 7BD, 7CD and 7DD wood burning stoves.	Instruction manual reference "Pevex1006/AH/ver2" dated June 2011.	Dry wood logs ⁽¹⁾ .
Manufactured by Heta A/S, Jupitervej 22, 7620 Lemvig, Denmark.	The appliance must be fitted with permanent stops to ensure that the primary and secondary air controls do not close beyond 95% and 50% respectively.	
Heta Scanline 800;	Instruction manual reference "Pevex1019/AH/ver1" dated	Wood logs ⁽¹⁾ .
Heta Scanline 810 standard;	January 2013.	
Heta Scanline 810 with high ash door and soapstone;	The appliance must be fitted with a permanent stop to fix the air control at 31%	
Heta Scanline 820 baking oven;	open when in the fully closed position.	
Heta Scanline 820 with soapstone and baking oven;		
Heta Scanline 820 accumulation;		
Heta Scanline 820 soapstone and accumulation;		
Heta Scanline 820 with shelf;		
Heta Scanline 820 soapstone and shelf;		
Heta Scanline 830 extra accumulation;		
Heta Scanline 830 extra accumulation and soapstone;		
Heta Scanline 840 high ash door and shelf;		
Heta Scanline 840 high ash door, shelf and soapstone;		

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions
	The fireplace must be No fuel is to be used
	installed, maintained and in the fireplace other than
	operated in accordance with authorised fuels and the
	the following specifications: following fuel or fuels:

Heta Scanline 840 high ash door and accumulation;

Heta Scanline 840 high ash door, accumulation and soapstone;

Heta Scanline 840 baking oven with high ash door;

Heta Scanline 840 baking oven with high ash door and soapstone;

Heta Scanline 850 on pedestal;

Heta Scanline 850 soapstone on pedestal;

Heta Scanline 80;

Heta Scanline 80 B; and

Heta Scanline 80 BF wood burning stoves.

Manufactured by Heta A/S,

Jupitervej 22, 7620 Lemvig,

Denmark.

ceramic;

Heta Scanline 810 with high ash door and ceramic;	Instruction manual reference "Pevex1019/AH/ver1" dated January 2013.	Wood logs ⁽¹⁾ .
Heta Scanline 820 with baking		
oven and ceramic;	The appliance must be fitted with a permanent stop to	
Heta Scanline 820 with	fix the air control at 31%	
thermastone and ceramic;	open when in the fully closed position.	
Heta Scanline 820 with shelf and top in sandstone;		
Heta Scanline 820 with shelf.		

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Status: This is the original version (as it was originally made). This item of legislation is currently only available in its original format.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Heta Scanline 830 with extra thermastone and top in soapstone;		,
Heta Scanline 830 with extra thermastone and ceramic;		

Heta Scanline 840 high ash door, shelf and ceramic;

Heta Scanline 840 high ash door, thermastone and ceramic;

Heta Scanline 840 high ash door, baking oven and ceramic;

Heta Scanline 850 on column and ceramic; and

Heta Scanline 850 on turntable column and ceramic wood burning stoves.

Manufactured by Heta A/S,

Jupitervej 22, 7620 Lemvig

Denmark.

Heta Scanline 800 Aqua and Heta Scanline 800 Aqua low boiler stoves.	Instruction manual reference "Pevex1018/AH/ver1" dated January 2013.	Wood logs ⁽¹⁾ .
Manufactured by Heta A/S,	The appliance must be fitted with a permanent stop to	
Jupitervej 22, 7620 Lemvig,	fix the air control at 52% open when in the fully closed	
Denmark.	position.	
Hi-Flame Inset Convector model number HF 5902 4.9kW	Instruction manual reference "HF5902/UK-NI-ROI/	Wood logs ⁽¹⁾ .
inset room heater.	V3.18-07-14" dated June 2014.	
Manufactured by Hi-Flame	The appliance must be fitted	
Fireplace UK Limited, Unit	with a mechanical stop to	
5A, Holmes Chapel Business	prevent secondary air control	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Park, Manor Lane, Holmes Chapel, Cheshire CW4 8AF.	closure beyond the 5mm open position.	
Highland Biomass Solutions Bio-Flame 28 Wood Pellet Boiler.	Installation and operation manual reference "Version 2.1" dated July 2013.	Wood pellets ⁽¹⁾ .
Manufactured by Wood Energy Solutions, Donaskeigh, Co. Tipperary, Ireland.		
Highland Biomass Solutions Bio-Flame 55, 85, 100, 125, & 199 Wood Pellet Boilers.	Installation, operation and servicing instructions reference "Manual Edition: Bio-Flame Commercial Series" dated July	Wood pellets ⁽¹⁾ .
Manufactured by Wood Energy Solutions Ltd., Donaskeigh, Tipperary, Co. Tipperary, Ireland.	2013.	
Highlander 3 Enviro-burn smoke exempt multi fuel stove.	Instruction manual reference "ENVIRO 3 DB005" dated 11th February 2013.	Wood logs ⁽¹⁾ .
Manufactured by Dunsley Heat Ltd., Bridge Mills, Huddersfield Road, Holmfirth, Yorkshire, HD9 3TW.	The appliance must be fitted with a system preventing closure of the secondary air control beyond the 3mm open position.	
Highlander 5 Clean Burn. Manufactured by Dunsley Heat Ltd., Bridge Mills, Huddersfield Road, Holmfirth, Yorkshire, HD9 3TW.	Instruction manual reference "Highlander. The Dunsley-Enviroburn-5. Clean Burn Stove Installation and operating instructions, D12-01-09, D060-01-09, D13-01-09, D12-12-08."	Wood logs conforming to BS EN 13240:2001 (1).
Highlander 5 Enviro-burn SOLO Slimline smoke exempt multi fuel stove.	Instruction manual reference "ENVIRO 5 DB002" dated 2nd February 2013.	Wood logs ⁽¹⁾ .
Manufactured by Dunsley Heat Ltd., Bridge Mills, Huddersfield Road, Holmfirth, Yorkshire, HD9 3TW.	The appliance must be fitted with a system preventing closure of the secondary air control beyond the 3mm open position.	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Highlander 7 Enviroburn Solo multi-fuel stove (product codes 00325, 00326 and 00327).	Installation and operating instructions manual reference "ENVIRO 7 DB001" dated 15th June 2012.	Dry wood logs ⁽¹⁾ .
Manufactured by Dunsley Heat Ltd., Bridge Mills, Huddersfield Road, Holmfirth, Yorkshire, HD9 3TW.	The appliance must be fitted with a mechanical stop to prevent closure of the secondary air-wash beyond 2mm. Four fixed 5mm diameter air holes are provided for the tertiary air supply.	
Highlander 8 Enviro-burn Solo 8.1kW multifuel stove. Manufactured by Dunsley Heat Limited Bridge Mills	Installation and operating instructions manual reference "ENVIRO 8 DB010" dated 15th October 2014.	Wood logs ⁽¹⁾ .
Heat Limited, Bridge Mills, Huddersfield Road, Holmfirth, Huddersfield, HD9 3TW.	A mechanical stop to prevent closure beyond the 3mm open position must be implemented.	
Hillandale Silverdale 5SE, Amalia 5 and Oppdal 5 woodburning stoves.	Instruction manual reference "GB12A Version 1" dated February 2013.	Wood logs ⁽¹⁾ .
Manufactured by Broseley Fires Ltd., Knights Way, Battlefield Enterprise Park, Shrewsbury, Shropshire, SY1 3AB.	The appliance must be fitted with a permanent stop to prevent closure of the secondary air slide beyond the 23mm open position.	
Hillandale Silverdale 7SE, Amalia 7 and Oppdal 7 woodburning stoves.	Instruction manual reference "GB12A Version 1" dated February 2013.	Wood logs ⁽¹⁾ .
Manufactured by Broseley Fires Ltd., Knights Way, Battlefield Enterprise Park, Shrewsbury, Shropshire, SY1 3AB.	The appliance must be fitted with a permanent stop to prevent closure of the secondary air slide beyond the 50mm open position.	
Hopwood Multifuel Stove Model HW1MF. Manufactured by ACR Heat Products Ltd., Unit 1, Weston	Instruction manual reference "HW1MF 0101" dated 17th July 2013.	Wood logs ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
Works, Weston Lane, Tyseley, Birmingham, B11 3RP.	The fireplace must be installed, maintained and operated in accordance with the following specifications: The appliance must be fitted with a permanent stop to the secondary air slider to prevent closure beyond the 5mm open position and the tertiary air openings at the rear of the appliance are fixed at 50% open.	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Hörby Model F9473 N,	Installation and Operation Manual dated 27th July 2015	Wood logs ⁽¹⁾ .
Borgholm II model F9473 E,	reference "HORBY – Version A"	
Torino model F9473 I,	The appliance must be fitted	
Loholm model F9473 L,	with a mechanical stop to	
Ulsborg model F9473 2,	•	
Augsburg model F9473 K,	prevent closure of the air control lever beyond the 3mm open position.	
Nancy model F9472 O,	•	
Passau model F9472 R,	NB: correction to 3mm from 30mm – see notification dated 6 August 2015.	
Basel II model F9472 H,	o August 2013.	
Skal II model F9472 P,		
Nancy II model F9472 Y,		
Domino IIFS model F9472 V and Colmar model F9472 X 5kW multifuel stoves		
NB: addition of 'Colmar' model F9472 X further to notification dated 6 August 2015.		
Manufactured by THORMA Vyroba k.s., Šavoľská cesta 323/1, 986 01,		
Fil'akovo-Priemyselný obvod,		

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Slovakia		
Horse Flame Little Artemis model number HF277-SE wood burning stove.	Instruction manual reference "AL905-SE/UK-NI-ROI/V2-D.18-07-12" dated July 2012.	Wood logs ⁽¹⁾ .
Manufactured by Hi-Flame Fireplace UK Ltd., Unit 5A, Holmes Chapel Business Park, Manor Lane, Holmes Chapel, Cheshire, CW4 8AF.	The appliance must be fitted with a mechanical stop to prevent closure of the secondary air control beyond the 3mm open position.	
Horse Flame Precision 1 model number HF905-SE.	Instruction manual reference "HF905/UK-NI-ROI/V2.1-06-11" dated June 2011.	Wood logs ⁽¹⁾ .
Manufactured by Henan Hi-Flame Metal Co. Ltd., Eastside, Yugang Avenue, Airport District, Zheng Zhou 451163, Henan, China.	The appliance must be fitted with a mechanical stop to prevent closure of the main air control beyond the 50% open position.	
Horse Flame Precision II model number HF907-SE wood burning stove.	Instruction manual reference "HF907-SE/UK-NI-ROI/V3-D. 14-07-12" dated July 2012.	Wood logs ⁽¹⁾ .
Manufactured by Hi-Flame Fireplace UK Ltd., Unit 5A, Holmes Chapel Business Park, Manor Lane, Holmes Chapel, Cheshire, CW4 8AF.	The appliance must be fitted with a mechanical stop to prevent secondary air control closure beyond the 20% open position, and a 70mm opening of the door rope seal to allow a constant flow of air.	
Hothouse 4SE stove.	Instruction manual reference "HH468SE" dated 25th July	Wood logs ⁽¹⁾ .
Manufactured by Heat Design, 30 Hawthorn Road, Western Industrial Estate, Naas Road, Dublin 12, Ireland.	The appliance must be fitted with a system to prevent closure of the secondary air control beyond 5mm open.	
Hothouse 06C inset stove. Manufactured by Heat Design,	Instruction manual reference "HH06C" dated 26th July 2012.	Wood logs ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
Industrial Estate, Naas Road,	The fireplace must be installed, maintained and operated in accordance with the following specifications: The appliance must be	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Dublin 12, Ireland.	fitted with a permanent stop to prevent closure of the secondary air control beyond 20% open.	
Hothouse 6SE stove. Manufactured by Heat Design,	Instruction manual reference "HH468SE" dated 25th July 2012.	Wood logs ⁽¹⁾ .
30 Hawthorn Road, Western Industrial Estate, Naas Road, Dublin 12, Ireland.	The appliance must be fitted with a system to prevent closure of the secondary air control beyond 75% from closed.	
Hothouse 8SE stove. Manufactured by Heat Design, 30 Hawthorn Road, Western Industrial Estate, Naas Road, Dublin 12, Ireland.	Instruction manual reference "HH468SE" dated 25th July 2012.	Wood logs ⁽¹⁾ .
	The appliance must be fitted with a system to prevent closure of the secondary air control beyond 25% from closed.	
Hothouse 11C inset stove. Manufactured by Heat Design,	Instruction manual reference "HH11C" dated 26th July 2012.	Wood logs ⁽¹⁾ .
30 Hawthorn Road, Western Industrial Estate, Naas Road, Dublin 12, Ireland.	The appliance must be fitted with a permanent stop to prevent closure of the secondary air control beyond 20% open.	
Hothouse Breeze 4SE Multifuel stove.	Installation and operating instruction manual reference "HHB468SE" dated 2nd May	Wood logs ⁽¹⁾ .
Manufactured by Heat Design Ltd., 30 Hawthorn Road, Western Industrial Estate, Naas Road, Dublin 12, Ireland.	The appliance must be fitted with a mechanical stop to prevent secondary air control closure beyond the 5mm open position.	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

C1 00 1		
Class of fireplace	Conditions	77 01 1
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Hothouse Breeze 5i Multi-fuel inset stove.	Installation and operating instruction manual reference "HHB5i" dated 2nd May 2013.	Wood logs ⁽¹⁾ .
Manufactured by Heat Design Ltd., 30 Hawthorn Road, Western Industrial Estate, Naas Road, Dublin 12, Ireland.	The appliance must be fitted with a mechanical stop to prevent secondary air control closure beyond the 3.5mm open position.	
Hothouse Breeze 6SE Multifuel stove. Manufactured by Heat Design	Installation and operating instruction manual reference "HHB468SE" dated 2nd May 2013.	Wood logs ⁽¹⁾ .
Ltd., 30 Hawthorn Road, Western Industrial Estate, Naas Road, Dublin 12, Ireland.	The appliance must be fitted with a mechanical stop to prevent secondary air control closure beyond the 25% open position.	
Hothouse Breeze 8SE Multifuel stove. Manufactured by Heat Design	Installation and operating instruction manual reference "HHB468SE" dated 2nd May 2013.	Wood logs ⁽¹⁾ .
Ltd., 30 Hawthorn Road, Western Industrial Estate, Naas Road, Dublin 12, Ireland.	The appliance must be fitted with a mechanical stop to prevent secondary air control closure beyond the 75% open position.	
Hothouse HH5i Multi-fuel inset stove.	Installation and operating instruction manual reference "HH5i" dated 2nd May 2013.	Wood logs ⁽¹⁾ .
Manufactured by Heat Design Ltd., 30 Hawthorn Road, Western Industrial Estate, Naas Road, Dublin 12, Ireland.	The appliance must be fitted with a mechanical stop to prevent secondary air control closure beyond the 3.5mm open position.	
Hotpod Unlimited; Hotpod Limited Edition.	Instruction manual reference "Version 3" dated June 2011.	Wood logs ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Manufactured by Hotpod LLP, PO Box 137, St Ives, Cornwall, TR26 2WW.		
Hoval AgroLyt 20, 25, 35, 45 and 50. Manufactured by Hoval AG, Austrasse 70, 9490 Vaduz, Liechtenstein.	Manufacturer's technical information and installation instructions reference "4 205 194/00" dated January 2006 and reference "4 205 193/00" dated June 2006.	Wood logs with less than 20% moisture ⁽¹⁾ .
Hoval BioLyt Wood Pellet Boiler. Manufactured by Hoval UK Ltd., Northgate, Newark, Nottinghamshire, NG24 1JN.	Instruction manual reference "Hoval Operating Instructions, wood pellet heating boiler BioLyt (50,70,120,140,160)" dated 3rd July 2008 and reference "Technical information assembly instructions" dated 3rd October 2009.	Wood pellets ⁽¹⁾ .
Hoval BioLyt 50 Wood Pellet Boiler (49kW thermal output). Manufactured by Hoval AG, Austrasse 70, 9490 Vaduz, Liechtenstein.	Manufacturer's technical information and installation instructions reference "4 204794/00" dated October 2005 and operating instructions reference "4 204 793/01" dated January 2006.	Wood pellets ⁽¹⁾ .
Hoval BioLyt 50 and 70 models. Manufactured by Hoval AG, Austrasse 70, 9490 Vaduz, Liechtenstein.	Manufacturer's technical information and installation instructions references "4 204 794/01" and "4 204 793/02" dated June 2007.	Wood pellets ⁽¹⁾ .
Hoval BioLyt 160 pellet boiler. Manufactured by Hoval UK Ltd., Northgate, Newark, Nottinghamshire, NG24 1JN.	Instruction manual reference "Hoval Operating Instructions, wood pellet heating boiler BioLyt (50,70,120,140,160)" dated 3rd July 2008 and reference "Technical information assembly instructions" dated 3rd October 2009.	Wood pellets ⁽¹⁾ .
Hoval BioLyt 8, 13, 15, 23, 25, 31 & 36 Wood Pellet Boiler.	Operating instructions reference "No: 4 211	Wood pellets ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
Manufactured by Hoval Limited,	The fireplace must be installed, maintained and operated in accordance with the following specifications: 326/01-10/13" dated October 2013.	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Northgate, Newark, Nottinghamshire, NG24 1JN.		
Hoval Forester MGS 150, 180, 240, 300, 360, 450, 550, 700, 900 boilers. Manufactured by Schmid	Instruction manual reference "Hoval Forester MGS_MMXXXv1" (where XXX is the unit size for example 150) dated July 2011.	Wood pellets or wood chips following CEN/TS 14961 ⁽¹⁾ .
AG Woodfiring systems, PO Box 42, CH-8380 Eschikon, Switzerland.		
Hoval Forester UFS 180, 240, 300, 360, 450, 550, 700, 900, 1200, 1600.	Instruction manual reference "Forester UFS" dated November 2009.	Wood pellets or wood chips following CEN/TS 14961 ⁽¹⁾ .
Manufactured by Schmid AG Woodfiring Systems, PO Box 42, CH-8360 Eschlikon, Switzerland.		
Hoval STU 150, 200, 250, 300, 350, 425 and 500. Manufactured by Hoval UK	Manufacturer's technical information and installation instructions reference "STUman/01" dated	Wood pellets ⁽¹⁾ .
Ltd., Northgate, Newark, Nottinghamshire, NG24 1JN.	November 2007 or reference "STU/man/01/1" dated June 2008.	
Hoval STU 600, 800 and 1000.	manual reference "STU/	Wood pellets ⁽¹⁾ .
Manufactured by Hoval UK Ltd., Northgate, Newark, Nottinghamshire, NG24 1JN.	man/01" dated November 2007 or the installation and operation manual reference "STU/man/01/1" dated June 2008.	
HSV 50 + WTH 45, 49 or 55; HSV 80 + WTH 70 or 80; HSV 100 + WTH 100.	Manufacturer's installation manual version 44 reference "BA HSV30-100 RA/RAP V44 0608".	Wood chips or wood pellets ⁽¹⁾ .
Manufactured by Hargassner Gesellschaft mit beschränkter Haftung (GmbH), Gunderding 8, A-4952, Weng, Austria.		

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Hunter Avalon 5 Inset stove. Manufactured by Hunter Stoves Ltd., Trevilla Park, Slaughterbridge, Camelford, Cornwall, PL32 9TT.	Instruction manual reference "JINAVI05 Rev B" dated 10th October 2012. The valve plate adjusted by the secondary air control must contain six 5mm holes.	Wood logs ⁽¹⁾ .
Hunter Hawk 4 multifuel stove. Manufactured by Hunter Stoves Ltd., Unit 6, Old Mill Industrial Estate, Exeter, EX5 4RJ	Installation and operating instructions reference "JINHCR06 RevB" dated 20th June 2014. The appliance must be fitted with a modified top air plate with an additional 9 x 5mm	Wood logs ⁽¹⁾ .
	holes and the tertiary air aperture permanently fixed to the 60% open position.	
Hunter Herald 4. Manufactured by Hunter Stoves Ltd., Trevilla Park, Slaughterbridge, Camelford, Cornwall, PL32 9TT.	Instruction manual reference "JINHH04 revC" dated 22nd September 2011 and "JINHH04&HHC05 Slider Stop revA" dated 22nd July 2011.	Wood logs ⁽¹⁾ .
	The appliance must be fitted with a permanent stop that prevents closure of the secondary air slider beyond 30% open.	
Hunter Herald 5 Compact. Manufactured by Hunter Stoves Ltd., Trevilla Park, Slaughterbridge, Camelford, Cornwall, PL32 9TT.	Instruction manual reference "JINHHC05 revC" dated 22nd September 2011 and "JINHH04&HHC05 Slider Stop revA" dated 22nd July 2011.	Wood logs ⁽¹⁾ .
	The appliance must be fitted with a permanent stop that prevents closure of the secondary air slider beyond 30% open.	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Hunter Herald 5 Slimline. Manufactured by Hunter Stoves Ltd., Trevilla Park, Slaughterbridge, Camelford, Cornwall, PL32 9TT.	Instruction manual reference "JINHHW05 revC" dated 22nd September 2011.	Wood logs ⁽¹⁾ .
Hunter Herald 6. Manufactured by Hunter Stoves Ltd., Trevilla Park, Slaughterbridge, Camelford, Cornwall, PL32 9TT.	Instruction manual reference "JINHH04 revC" dated 22nd September 2011.	Wood logs ⁽¹⁾ .
Hunter Herald 8 slimline CE vII stove. Manufactured by Hunter Stoves Ltd., Trevilla Park, Slaughterbridge, Camelford, Cornwall, PL32 9TT.	Instruction manual reference "JINHHW08 revB" dated 24th January 2013.	Wood logs ⁽¹⁾ .
Hunter Herald i4. Manufactured by Hunter Stoves Ltd., Trevilla Park, Slaughterbridge, Camelford, Cornwall, PL32 9TT.	Instruction manual reference "JINHVR04 Rev E" dated 2nd December 2011 and instruction manual reference "JINHVR04SCK revB" dated 5th December 2011. The appliance must be fitted with smoke control area kit JHVR0401.	Wood logs ⁽¹⁾ .
Hunter Herald Inset 5 CBC 4.7kW wood-burning inset stove. Manufactured by Hunter Stoves Ltd, Trevilla Park, Slaughterbridge, Camelford, Cornwall, PL32 9TT	Installation and Operating Instructions dated 30/06/2015 reference "JINHCB04 RevB"	Wood logs ⁽¹⁾ .
Hunter stoves Inset Avalon 8 multi-fuel inset stove. Manufactured by Hunter	Installation and operating instructions manual reference "JINAVI08 Rev B" dated 14th February 2013 and modification instructions	Wood logs ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
Stoves Limited, Trevilla Park,	The fireplace must be installed, maintained and operated in accordance with the following specifications: reference "JINAV108 Slider	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Slaughterbridge, Camelford,	Stop Rev B" dated 25th September 2013.	
Cornwall, PL32 9TT.	The appliance must be fitted with a mechanical stop to prevent secondary air control closure beyond the 20% open position.	
Hunter stoves Inset Telford 8 multi-fuel inset stove.	Installation and operating instructions manual reference "JINTDI08 Rev B" dated	Wood logs ⁽¹⁾ .
Manufactured by Hunter Stoves Limited, Trevilla Park, Slaughterbridge, Camelford,	5th February 2013 and modification instructions "JINTD108 Slider Stop Rev B" dated 25th September 2013.	
Cornwall, PL32 9TT.	The appliance must be fitted with a mechanical stop to prevent secondary air control closure beyond the 20% open position.	
Hunter Kestrel 5 multifuel stove.	Installation and operating instructions reference "JINHRR05 RevB" dated 20th	Wood logs ⁽¹⁾ .
Manufactured by Hunter Stoves Limited,	June 2014.	
Unit 6,	The appliance must be fitted with a modified top air plate with an additional 8 x 5mm	
Old Mill Industrial Estate,	holes.	
Exeter,		
EX5 4RJ		
Hunter Telford 5 Inset stove.	Instruction manual reference "JINTDI05 rev B" dated 10th	Wood logs ⁽¹⁾ .
Manufactured by Hunter Stoves Ltd., Trevilla Park,	October 2012.	
Slaughterbridge, Camelford, Cornwall, PL32 9TT.	The valve plate adjusted by the secondary air control must contain six 5mm holes.	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Huntingdon 25 clear door (model number 7057) and Huntingdon 25 tracery door	Instruction manual reference "PM 249 Issue 1".	Untreated dry wood ⁽¹⁾ .
(model number 7058). Manufactured by Stovax	The appliance must be fitted with a permanent stop on the secondary air inlet to prevent	
Ltd., Falcon Road, Sowerton Industrial Estate, Exeter, Devon EX2 7LF.	closure beyond the 75% open position.	
Hwam 2610, 2620, 2630 and 2640 3.5kW wood-burning stoves.	Operating and Maintenance Instructions dated July 2015 reference "IN1272 Ed.B"	Wood Logs ⁽¹⁾ .
Manufactured by HWAM Heat Design AS Nydamsvej 53, 8362 Hørning, Denmark		
Hwam 3110, 3120, 3410, 3420, 3440, 3520 and 3530 4.5kW wood-burning stoves.	Operating and Maintenance Instructions dated January 2015 reference "IN1211 Ed B"	Wood Logs ⁽¹⁾ .
Manufactured by HWAM Heat Design AS Nydamsvej 53, 8362 Hørning, Denmark		
Hwam 3610, 3620, 3630, 3640, 3650, 3660 6kW woodburning stoves.	Operating Instructions dated July 2015 reference "IN1244 Ed A"	Wood Logs ⁽¹⁾ .
Manufactured by HWAM Heat Design AS Nydamsvej 53, 8362 Hørning, Denmark	Fitted with a mechanical stop to prevent air control closure beyond the 8mm open position	
Hwam 30/55 7kW inset woodburning stove.	Operating and Maintenance Instructions dated July 2015 reference "IN1262 Ed C"	Wood Logs ⁽¹⁾ .
Manufactured by HWAM Heat Design AS Nydamsvej 53, 8362 Hørning, Denmark	Telefonee II (1202 Ed C	
Hwam Beethoven, Hwam Beethoven H, Hwam Mozart, Hwam Ravel, Hwam Vivaldi, Hwam 30 (4.5kW nominal thermal output).	Euroheat Distributors (HBS) Ltd.'s operational instructions reference "IN1 141 Ed B" dated November 2006.	Untreated dry wood ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
Manufactured by HWAM Heat Design AS Nydamsvej 53, 8362 Hørning, Denmark.	The fireplace must be installed, maintained and operated in accordance with the following specifications: The appliance must be fitted with a mechanism to prevent closure of the air wash/secondary air control.	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Ild 1 and Ild 4 stoves. Manufactured by Color	Instruction manual reference "11.1c" dated February 2012.	Wood logs ⁽¹⁾ .
Emajl d.o.o., Alaginci 87/a, HR-34000 Požega, Croatia.	The appliance must be fitted with a mechanical stop to prevent closure of the secondary air control beyond the 83mm open position.	
Ild 2 and Ild 5 stoves.	Instruction manual reference "11-1d" dated February 2012.	Wood logs ⁽¹⁾ .
Manufactured by Color Emajl d.o.o., Alaginci 87/a, HR-34000 Požega, Croatia.	The appliance must be fitted with a mechanical stop to prevent closure of the secondary air control beyond the 83mm open position.	
Ild 6 Insert stove. Manufactured by Color Emajl d.o.o., Alaginci 87/a,	ILD 6 Insert stove Instruction manual reference "12-1b GB" dated 25th February 2013.	Wood logs ⁽¹⁾ .
HR-34000 Požega, Croatia.	The appliance must be fitted with a permanent stop preventing closure of the secondary air control beyond 18% open.	
Ild 7 and Ild 8 wood-burning stoves.	Instruction manual reference "Manual version. No. 13-1 GB 01.07.13" dated 1st July 2013.	Wood logs ⁽¹⁾ .
Manufactured by Color Emajl d.o.o., Alaginci 87/a, HR-34000 Požega, Croatia.	The appliance must be fitted with a permanent stop to fix the secondary air control at 7.5% open when in the fully closed position.	
Insert 50 Crystal, Insert 70 Crystal and Insert 80 Crystal. Manufactured by LaNordica Spa, Via Summano 104 M.	Instruction manual reference "6096801-Rev.17" dated 22nd December 2010.	Wood logs ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Precalcino, 36030, Vicenza, Italy.	The appliance must be fitted with a mechanical stop to prevent closure of the secondary air control beyond the 40% open position.	
Insert 100 Crystal.	Instruction manual reference "6096801-Rev.17" dated 22nd	Wood logs ⁽¹⁾ .
Manufactured by, LaNordica Spa, Via Summano 104 M. Precalcino, 36030, Vicenza, Italy.	December 2010.	
Instyle 400; Instyle 550.	Instruction manual reference "Instruction manual Instyle 12	Wood logs ⁽¹⁾ . 209 ENG".
Manufactured by Dik Geurts Haardkachels BV; Industrieweg Oost 11, 6662 NE Elst (Gld), The Netherlands.		
Interra 60, 68, 74, 78 stoves.	Instruction manual reference "Interra 60-68-74-78	Wood logs ⁽¹⁾ .
Manufactured by M-Design, M-Design, Torhoutsesteenweg 222A, 8210 Zedelgem, Bruges,	Instruction for Installation and use" dated August 2012.	
Belgium, 8210 Zedelgem.	The units have a permanent stop fitted for use in UK smoke control areas.	
I Series 600 SLF L/M 5kW freestanding wood burning stove.	Operating & Installation manual dated 01/09/2015 reference "AFS P0133 Rev. H".	Wood logs ⁽¹⁾ .
Manufactured by Arada Limited, The Fireworks, Weycroft Avenue, Axminster, Devon, EX13 5HU	The appliance must be fitted with a mechanical stop to prevent closure of the air control beyond the 20mm open position	
Italy Built In.	Instruction manual reference "7095401 Rev.02" dated 13th	Wood logs ⁽¹⁾ .
Manufactured by La Nordica Spa, Via Summano 104 M. Precalcino, 36030, Vicenza, Italy.	December 2010.	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Italy Imported wood burning ovens: Etna, Amiata, Stromboli and Vesuvius.	Installation and operation manual reference "E.A.S.V. ISSUE 1" dated July 2013.	Wood logs ⁽¹⁾ .
Manufactured by Italy Imported Ltd., Avenue House, Southgate, Chichester, PO19 1ES.		
Italy Termo Built-in DSA (back boiler cooker).	Instructions for installation, use and maintenance manual reference "7095703 – IT-EN-	Wood logs ⁽¹⁾ .
Manufactured by La Nordica SPA, Via Summano, 104 Montecchio Precalcino, Vicenza, 36030, Italy.	DE-FR" dated July 2013.	
Italy Termo DSA;	Instruction manual reference "7095802 Rev.06" dated 1st	Wood logs ⁽¹⁾ .
Termosuprema Compact DSA.	February 2011.	
Manufactured by LaNordica Spa, Via Summano 104 M. Precalcino, 36030, Vicenza, Italy.		
Ivanhoe JS5000 multi-fuel.	Instruction manual reference "Ivanhoe multi-fuel stove	Wood logs ⁽¹⁾ .
Manufactured by James Smellie Ltd., Unit N, Leona Industrial Estate, Nimmings Road, Halesowen, West Midlands, B62 9JQ.	instruction manual Issue 1" dated June 2012.	
JC Bordelet EVA 992 Centrale Foyer Fermé (vitrée) enclosed wood-burning stove;	Instruction manual reference "Fireplaces Manual	Wood logs ⁽¹⁾ .
JC Bordelet EVA 992 Murale (vitrée) enclosed wood-burning stove; and	Installation – Use – 1/04/07 Characteristics of the Fireplace" dated 1st April 2007.	
JC Bordelet EVA 992 Angle (vitrée) enclosed wood-burning stove.	2007.	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Manufactured by Groupe Seguin, Cheminees Seguin Duteriez, Zone Industrielle de Lhérat, 63310 France.	7 31 7	, SV ,
JC Bordelet LEA 998 centrale foyer fermé (vitrée) enclosed wood-burning stove; and	Instruction manual reference "Fireplaces Manual	Wood logs ⁽¹⁾ .
	Installation-Use-1/04/07	
JC Bordelet LEA 998 Murale (vitrée) enclosed wood-burning stove.	Characteristics of the Fireplace" dated 1st April 2007.	
Manufactured by Groupe Seguin, Cheminees Seguin Duteriez, Zone Industrielle de Lhérat, 63310 France.		
Jetmaster 18f stove.	Instruction manual reference	Dry wood logs ⁽¹⁾ .
Manufactured by Jetmaster Fires Ltd., Unit 2, Peacock Trading Estate, Goodwood Road, Eastleigh, Hampshire, SO50 4NT.	"106870/18f/60f/Issue No.5" dated June 2011.	
Jetmaster 18i stove. Manufactured by Jetmaster Fires Ltd., Unit 2, Peacock Trading Estate, Goodwood Road, Eastleigh, Hampshire, SO50 4NT.	Installation and use instruction manual reference "Part No 106870 Issue No. 1" dated February 2010 and supplementary instruction manual reference "Part No 106872 Issue No. 1" dated May 2010.	Wood logs ⁽¹⁾ .
	The appliance must be fitted with a mechanical stop to prevent closure of the air control beyond the 40% open position.	
Jetmaster 60i stove.	Installation and use instruction	Wood logs ⁽¹⁾ .
Manufactured by Jetmaster Fires Ltd., Unit 2, Peacock Trading Estate, Goodwood	manual reference "Part No 106870 Issue No. 1" dated February 2010 and supplementary instruction manual reference "Part No	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
Road, Eastleigh, Hampshire, SO50 4NT.	The fireplace must be installed, maintained and operated in accordance with the following specifications: 106872 Issue No. 1" dated May 2010. The appliance must be fitted	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
	with a mechanical stop to prevent closure of the air control beyond the 40% open position.	
Jotul F100 Stove. Manufactured by Jotul UK Ltd., Unit 1, The IO Centre, Nash Road, Park Farm, Redditch, Worcestershire, B98 7AS.	Instruction manual reference "129980" dated September 2002 and smoke control area modification reference "UK F100 SC appendix" dated 2010.	Wood logs ⁽¹⁾ .
7710.	The appliance must be fitted with a permanent stop that prevents the closure of the secondary air control beyond the 50% open position.	
Jotul F162, F163, F262 and F263. Manufactured by Jotul UK Ltd., Unit 1, The IO Centre, Nash Road, Park Farm, Redditch, Worcestershire, B98 7AS.	Instruction manual reference "Jotul F162/F162C/F163 Manual Version Po6" dated January 2011 and supplementary instruction manual reference "Jotul F162/F163/262/263 SMOKE" dated 1st January 2012.	Wood logs ⁽¹⁾ .
,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	The appliance must be fitted with a mechanical stop to prevent secondary air control closure beyond the 20% open position.	
Jotul I520FRL, I520F, I520FR and I520FL 7.8kW inset stoves. Manufactured by Jotul A.S, P.O. Box 1411, N-1602	Instruction manual reference "KIS-580 02 03 Version P02" dated November 2013 and "Jøtul I520 Series SMOKE" dated 3rd June 2014	Wood logs ⁽¹⁾ .
Fredrikstad, Norway	The appliance must be fitted with a permanent stop to fix the secondary air control to	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications: 980mm2 in its minimum position.	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Jydepejsen Country 510 and 760 5kW stoves. Manufactured by Jydepejsen A/S, Ahornsvinget 3-7, Nr.Felding, DK-7500, Holstebro, Denmark.	Instruction manual "Country001" reference "Jydepejsen A/S - June 2011" dated June 2011. The appliance must be fitted with a permanent stop to the secondary air control such that it cannot be closed less than 35%.	Wood logs ⁽¹⁾ .
KARA KW990 woodchip boiler. Manufactured by KARA Energy Systems B.V., P.O. Box 570, 7600 AN Almelo, Plesmanweg 27, 7602 PD Almelo, The Netherlands.	Instruction manual reference "Maintenance and Operation Guide KARA Wood Fired Boiler Version 2012.02" dated 26th July 2012.	Woodchip (1).
Keddy SK1000 5.9kW wood- burning inset roomheater manufactured by Keddy AB, PO Box 542, 441 15 Alingsas, Sweden	Fireplace inserts Installation instructions Care and firing instructions Model SK1000 dated 1st September 2013 reference "Rev 1." Fitted with a mechanical stop to prevent air control closure beyond the 30% open position	Wood Logs ⁽¹⁾ .
Keddy K700 5.9kW wood- burning stove. Manufactured by Keddy AB, PO Box 542, 441 15 Alingsas, Sweden	K700 Installation Instructions Care and Firing Instructions dated 1st May 2015 reference "Rev 1." Fitted with a mechanical stop to prevent air control closure beyond the 30% open position	Wood Logs ⁽¹⁾ .
Keddy K1100 5.6kW wood- burning stove manufactured by Keddy AB, PO Box 542, 441 15 Alingsas, Sweden	K1100 Installation Instructions Care and Firing Instructions dated 1st September 2014 reference "Rev 1."	Wood Logs ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications: Fitted with a mechanical stop	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
	to prevent air control closure beyond the 30% open position	
Keddy K800 6kW woodburning stove Manufactured by Keddy AB, PO Box 542, 441 15 Alingsas,	K800 Installation Instructions Care and Firing Instructions dated 1st September 2013 reference "Rev 1."	Wood Logs ⁽¹⁾ .
Sweden Sweden	Fitted with a mechanical stop to prevent air control closure beyond the 25% open position	
Klover PFP18 and PFP18-B pellet insert appliances. Manufactured by Klover Limited, Klover s.r.l Via A. Volta, 8 - 37047 San Bonifacio (VR), Italy.	Instruction manual reference "Installation. Use and Maintenance. Useful advice. Pellet Fire Place. User Guide" dated February 2009.	Wood pellets ⁽¹⁾ .
Klover PFP22 and PFP22-B pellet insert appliances. Manufactured by Klover Limited, Klover s.r.l Via A. Volta, 8 - 37047 San Bonifacio (VR), Italy.	Instruction manual reference "Klover PFP22 insert Defra manual" dated 31st January 2014.	Wood pellets ⁽¹⁾ .
Klover Smart 80 central heating pellet stove models SM80, SM80-BP, SM80-P. Manufactured by Klover Limited, Klover s.r.l Via A. Volta, 8 - 37047 San Bonifacio (VR), Italy.	Instruction manual reference "Smart Pellet central heating Stove. Use and maintenance, Installation, Useful advice" dated March 2012.	Wood pellets ⁽¹⁾ .
Klover Smart 120 central heating pellet cooker stove models – SM120, SM120-BP, SM120-P. Manufactured by Klover Limited, Klover s.r.l Via A. Volta, 8 - 37047 San Bonifacio (VR), Italy	Instruction manual reference "Klover. Pellet thermo cooker. Smart. Installation. Use and maintenance. Useful advice. User Guide" dated March 2012.	Wood pellets ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
3.0 1	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Klover Star 14 –ST14 pellet stove.	Instruction manual reference "Installation. Use and Maintenance. Useful advice.	Wood pellets ⁽¹⁾ .
Manufactured by Klover Limited, Klover s.r.l Via A. Volta, 8 - 37047 San Bonifacio (VR), Italy.	Star 14. User Guide" dated April 2011.	
Klover Star 18 – ST18 pellet stove.	Instruction manual reference "Star 18 Pellet Boiler Stove. Installation. Use and	Wood pellets ⁽¹⁾ .
Manufactured by Klover Limited, Klover s.r.l Via A. Volta, 8 - 37047 San Bonifacio (VR), Italy.	Maintenance, Useful Tips revision: 1.1" dated September 2013.	
Knightsbridge SE multifuel stove, Knightsbridge SE multifuel stove with stoveasy grate, Highgrove SE multifuel	Instruction manual reference "NS 5-6 Issue 1" dated 8th January 2014.	Wood logs ⁽¹⁾ .
stove, Highgrove SE multifuel stove with stoveasy grate.	The tertiary air control must be fully open when burning wood.	
Manufactured by Newman Fireplaces Limited, Unit 6 & 7 Rawreth Barns, Dollymans Farm, Doublegate Lane, Rawreth, Wickford, Essex, SS11 8UD.		
KÖB Pyromat-DYN (KPM-DYN) 45, 65, 85.	Instruction manual reference "ID 103689-L English" dated 1st January 2005 and	Wood logs (up to 0.5m) and off cuts of natural timber, wood chips and pellets ⁽¹⁾ .
Manufactured by Viessman Ltd., Hortonwood 30, Telford, Shropshire, TF1 7YP.	instruction manual reference "ID: 103708-G English".	emps and penets
KÖB Pyromat-ECO (KPM-ECO) models 35, 45, 55, 65, 75, 85.	Instruction manual reference "ID 104646-D English" dated 1st January 2005 and instruction manual reference	Wood logs (up to 0.5m) and off cuts of natural timber ⁽¹⁾ .
Manufactured by Viessman Ltd., Hortonwood 30, Telford, Shropshire, TF1 7YP.	"ID: 104642-B English".	
KÖB Pyromat-ECO (KPM-ECO) models 61, 81, 101, 151.	Instruction manual reference "ID 104646-D English" dated 1st January 2005 and	Wood logs (up to 1.0m) and off cuts of natural timber ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

61 60 1	G 1:	
Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Manufactured by Viessman Ltd., Hortonwood 30, Telford, Shropshire, TF1 7YP.	instruction manual reference "ID: 104642-B English".	
KÖB Pyrot (KRT) models 100, 150, 220, 300, 400, 540. Manufactured by Viessman Ltd., Hortonwood 30, Telford, Shropshire, TF1 7YP.	Instruction manual reference "ID 104654-H English" dated 1st January 2005 and instruction manual reference "ID: 106811-H English".	Wood chips or wood pellets ⁽¹⁾ .
KÖB Pyrtec (KPT) models 390, 530, 720, 950, 1250. Manufactured by Viessman Ltd., Hortonwood 30, Telford, Shropshire, TF1 7YP.	Instruction manual reference "ID 104661-F English" dated 1st January 2005 and instruction manual reference "ID: 105174-F English". The appliance must be fitted with multi-cyclone dedusters.	Wood chips or wood pellets ⁽¹⁾ .
Kooga Cleanburn Stove. Manufactured by Percy Doughty & Co Ltd., Imperial Point, Express Trading Estate, Stonehill Road, Farnworth, Bolton, BL4 9TN.	Instruction manual reference "KCB 04/10A" dated April 2010.	Wood logs ⁽¹⁾ .
KOZ550, 639kW pellet boiler. Manufactured by Kayalioglu Kasabasi (Izmir-Istanbul Yolu Uzeri), PK23 Akhisar/Manisa, Turkey.	Owner/operator's manual reference "version 1A 2010" dated December 2010 and maintenance and instruction manual for Glosfume BMF Biomass filter units (50 to 1000kW) reference "version AEE001-VER4" dated December 2010. The appliance must be used with a Glosfume model BMF 200	6mm diameter wood pellets ⁽¹⁾ .
KP12, KP22 and KP62 wood pellet boilers. Manufactured by PONAST spol. s r.o., Na Potůčkách 163,	208 ceramic particulate filter. Service manual reference "QPP051-2" dated 25th May 2012 and instructions for operation manual reference "QPP049-3" dated 25th May 2012.	Wood pellets ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
136

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Valašské Meziříčí, 757 01, Czech Republic.		
KWB Easyfire EF2 S/GS/V 8, 12, 15, 22, 25, 30 and 35 wood pellet boilers. Manufactured by KWB	Operation manual reference "B KWB Easyfire EN, 05.2011" dated May 2011 and installation manual reference "M KWB Easyfire, 05.2011" dated May	Wood pellets ⁽¹⁾ .
- Kraft und Wärme aus Biomasse Gesellschaft mit Beschränkter Haftung (GmbH), Industriestrasse 235, A-8321 St. Margarethen an der Raab, Austria.	2011.	
KWB Multifire 15, 25, 30, 40, 50, 60, 80, 99 and 100 woodpellet and wood-chip fired boilers.	Manufacturer's instructions reference "BA-USV 0803" dated August 2003.	Wood chips and wood pellets (1)
Manufactured by KWB – Kraft und Wärme aus Biomasse Gesellschaft mit Beschränkter Haftung (GmbH), Industriestrasse 235, A-8321 St. Margarethen an der Raab, Austria.		
kwb Multifire MF2 D/ZI 20 biomass boiler, Kwb Multifire MF2 D/ZI 30 biomass boiler, Kwb Multifire MF2 D/ZI 40 biomass boiler, Kwb Multifire MF2 D/ZI 45 biomass boiler, Kwb Multifire MF2 D/ZI 45 biomass boiler, Kwb Multifire MF2 D/ZI 60 biomass boiler, Kwb Multifire MF2 D/ZI 65 biomass boiler, Kwb Multifire MF2 D/ZI 65 biomass boiler, Kwb Multifire MF2 D/ZI 70 biomass boiler, Kwb Multifire MF2 D/ZI 80 biomass boiler, Kwb Multifire MF2 D/ZI 99 biomass boiler, Kwb Multifire MF2 D/ZI 100 biomass boiler, Kwb Multifire MF2 D/ZI 101 biomass boiler, Kwb Multifire MF2 D/ZI	Operation Manual KWB Multifire MF2 D/ZI dated July 2015 references "Index 3 EN"	Wood chips and wood pellets ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
108 biomass boiler, and KWB Multifire MF2 D/ZI 120		
manufactured by Kraft und Wärme aus Biomasse GmbH, Industriestraβe 235 A-8321, St Margarethen Straße, Austria		
KWB Multifire USV 49.5kW wood chip and wood pellet boiler.	Instruction manual reference "BA Multifire 06.2010" dated June 2010.	
Manufactured by KWB – Kraft und Wärme aus Biomasse Gesellschaft mit Beschränkter Haftung (GmbH), Industriestrasse 235, A-8321 St. Margarethen an der Raab, Austria.		
KWB Pelletfire Plus MF2 S/GS 45 pellet boiler, KWB Pelletfire Plus MF2 S/GS 50 pellet boiler, KWB Pelletfire Plus MF2 S/GS 55 pellet boiler, KWB Pelletfire Plus MF2 S/GS 65 pellet boiler, KWB Pelletfire Plus MF2 S/ GS 70	Operation Manual KWB Pelletfire Plus MF2 S/GS dated July 2015 references "Index 3 EN"	Wood pellets ⁽¹⁾ .
KWB Pelletfire Plus MF2 S/GS 75 pellet boiler, KWB Pelletfire Plus MF2 S/GS 95 pellet boiler, KWB Pelletfire Plus MF2 S/GS 99 pellet boiler, KWB Pelletfire Plus MF2 S/GS 100 pellet boiler, KWB Pelletfire Plus MF2 S/ GS 101 pellet boiler, KWB Pelletfire Plus MF2 S/GS 108 pellet boiler, KWB Pelletfire Plus MF2 S/GS 115 pellet boiler, KWB Pelletfire Plus MF2 S/GS 135.		

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Manufactured by Kraft und Wärme aus Biomasse GmbH, Industriestraβe 235 A-8321, St Margarethen Straße, Austria		
KWB Powerfire TDS 200 199kW Boiler.	Operation manual reference "B KWB Powerfire 200–300kW, EN, 09.2012" dated April 2013.	Wood pellets or Wood chips ⁽¹⁾ .
Manufactured by KWB — Kraft und Wärme aus Biomasse Gesellschaft mit Beschränkter Haftung (GmbH), Industriestrasse 235, A-8321 St. Margarethen an der Raab, Austria.	EN, 09.2012 dated April 2013.	
KWB TDS Powerfire 130, 240 and 300.	Manufacturer's instructions reference "BA TDS-05.2008" dated 14 May 2008, including	Wood pellets or wood chips ⁽¹⁾ .
Manufactured by KWB – Kraft und Wärme aus Biomasse Gesellschaft mit Beschränkter Haftung (GmbH), Industriestrasse 235, A-8321 St. Margarethen an der Raab, Austria.	specification of recommended fuels.	
KWB TDS Powerfire 150. Manufactured by KWB – Kraft und Wärme aus Biomasse Gesellschaft	Manufacturer's instructions reference "BA TDS – 0805" dated August 2005.	Wood pellets or wood chips ⁽¹⁾ .
mit Beschränkter Haftung (GmbH), Industriestrasse 235, A-8321 St. Margarethen an der Raab, Austria.		
Langdale Smoke Control 7.5kW freestanding multi fuel stove	Installation and User Instructions dated 07/07/2015 reference "Langdale Smoke Control Issue 1".	Wood logs ⁽¹⁾ .
manufactured by Town and Country Fires Limited, Unit 1 Enterprise Way, Thornton Road Industrial Estate, Pickering, North Yorkshire, YO18 7NA		

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Lima B.11 wood burning stove Manufactured by Hase Kaminofenbau GmbH, Niederkircher Strasse 14, D-54294 Trier	Instruction manual reference "Lima_R1" dated November 2014. The appliance must be fitted with a mechanical stop to prevent air control closure beyond the 42mm open position.	Wood logs ⁽¹⁾ .
Lindner & Sommerauer pellet boilers models: SL-P49, SL- P50, SL-P65, SL-P80, SL-P99, SL-P110, SL-P150, SL-P199, SL-P200 and SL-P250 Manufactured by Lindner & Sommerauer, SL-Technik	Operating instructions and technical description – Rotary Grid system SL 25T/2R to SL250 T6R and SL-P30 to SL-P 250, reference "140304 ENG" dated 5th March 2014.	Wood pellets ⁽¹⁾ .
GmbH, Trimmelkram 113 A-5120 St Pantaleon, Austria.		
Lindner & Sommerauer wood chip boilers models: SL49T4R, SL50T4R, SL65T4R, SL80T4R, SL99T4R, SL110T4R, SL150T4R, SL199T6R, SL200T6R and SL250T6R	Operating instructions and technical description – Rotary Grid system SL 25T/2R to SL250 T6R and SL-P30 to SL-P 250, reference "140304 ENG" dated 5th March 2014.	Wood pellets or wood chips ⁽¹⁾ .
Manufactured by Lindner & Sommerauer, SL-Technik GmbH, Trimmelkram 113 A-5120 St Pantaleon, Austria.		
Lin-ka H 1500 Hot Water Boiler fitted with either a mono-cyclone (type LIN-KA 2000) or a multi-cyclone (type LIN-KA 3x2).	Instruction manual reference "LIN-KA H 1500 Hot Water Manual/Ver. 2005/Rev. 1.10" dated 27th January 2010.	Wood pellets of maximum 8mm diameter ⁽¹⁾ .
Manufactured by LIN- KA Maskinfabrik A/S, Nylandsvej 38, DK-6940 Lem St. Denmark.		

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Little Thurlow wood burning stove.	Manufacturer's instructions reference "issue No. 3." dated 30th June 2007.	Seasoned logs of less than 20% moisture and of a maximum
Manufactured by Town and Country Fires Ltd., 1 Enterprise Way, Thornton Road Industrial Estate, Pickering, North Yorkshire, YO18 7NA.	Jour Julie 2007.	length of 350mm ⁽¹⁾ .
Little Wenlock Classic SE Wood Fuel Stove.	Operating instructions reference "N00471AXX Rev 001 DP 081219" dated 19th	Dry and split wood logs of a maximum length of 25cm and a maximum diameter of 10cm
Manufactured by Aga, Station Road, Ketley, Telford, Shropshire, TF1 5AQ.	December 2008.	(1)
LogFire LF6cT Wood Burning Stove.	Instruction manual reference "LF6cT-1" dated 18th December 2012.	Wood logs ⁽¹⁾ .
Manufactured by LogFire Stoves Ltd., Britannia House, Junction Street, Darwen, Lancashire, BB3 2RB.	The appliance must be fitted with a mechanical stop to prevent closure of the air control slots beyond the 21mm open position.	
LogWIN Klassik wood log gasification boilers models: LWK 180, LWK 250 and LWK 300.		Wood logs ⁽¹⁾ .
Manufactured by Windhager Zentralheizung GmbH, Anton- Windhager- Str. 20, A-5201 Seerkirchen bei Salzburg, Austria	Assembly instructions LogWIN Klassik dated July 2015 references "093391/03"	
LogWIN Premium wood log gasification boilers models: LWP 180, LWP 250, LWP 300, LWP 360 and LWP 500.	Operating Manual LogWIN Premium dated July 2015 reference "092412/05"	Wood logs ⁽¹⁾ .
Manufactured by Windhager Zentralheizung GmbH, Anton- Windhager- Str. 20, A-5201	Assembly instructions LogWIN Premium dated July 2015 references "092413/05"	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Seerkirchen bei Salzburg, Austria		
Lotus H370 Petite 6.6kW insert stove.	Instruction manual reference "Fireplace Insert, Lotus H370	Wood logs ⁽¹⁾ .
Manufactured by Lotus Heating Systems A/S;	Petite Version 1" dated 11th October 2012.	
Agertoften 6, 5550 Langeskov, Denmark.	The appliance must be fitted with a mechanical stop to prevent closure of the air damper beyond the 5mm open position.	
Lotus Liva 1, Liva 2, Liva 3 and Liva 4G stoves.	Instruction manual reference "Mounting and User Instructions Lotus-Liva series	Wood logs ⁽¹⁾ .
Manufactured by Lotus Heating Systems A/S;	Stoves Version 4" dated January 2010.	
Agertoften 6, 5550 Langeskov, Denmark.		
Lotus Liva 5, Liva 5S, Liva 5G, Liva 6, Liva 6S and, Liva 6G 5kW wood-burning stoves.	Instruction manual dated July 2015 reference "Mounting and User Instructions Lotus-Liva	Wood Logs ⁽¹⁾ .
Manufactured by Lotus Heating Systems A/S, Agertoften 6, 5550 Langeskov,	(Lotus Liva 5, Liva 6) version 3, 20/7-2015 "	
Denmark		
Lotus Mira 1 and Mira 2 5kW wood-burning.	Instruction manual dated July 2015 reference "Mounting and User Instructions Lotus-Mira	Wood Logs ⁽¹⁾ .
Manufactured by Lotus Heating Systems A/S, Agertoften 6, 5550 Langeskov,	Series Stoves (Lotus Mira 1/2, Mira 3/4) version 4, 20/7-2015	
Denmark		
Lotus Sola, Sola S, Sola M and Sola MST stoves.	Instruction manual reference "Mounting and User Instructions Lotus-Sola series	Wood logs ⁽¹⁾ .
Manufactured by Lotus Heating Systems A/S,	Stoves Version 2" dated January 2010.	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Agertoften 6, 5550 Langeskov, Denmark.		
Løvenholm. Manufactured by Hunter Stoves Ltd., Trevilla Park, Slaughterbridge, Camelford, Cornwall, PL32 9TT.	Manufacturer's installation and operation manual reference "version 07/08" dated July 2008.	Untreated wood with less than 20% moisture content ⁽¹⁾ .
Løvenholm, Løvenholm Traditional, European and Pedestal Stoves. Manufactured by Hunter Stoves Ltd., Trevilla Park, Slaughterbridge, Camelford, Cornwall, PL32 9TT.	Manufacturer's instructions "Løvenholm Multifuel stove installation and operating manual" reference "version 06/09" dated June 2009.	Untreated wood with less than 20% moisture content ⁽¹⁾ .
Loxton 3 stoves. Manufactured by Mendip Stoves Ltd., Unit H1, Mendip Industrial Estate, Mendip Road, Rooksbridge, Somerset, BS26 2UG.	Instruction manual reference "Mendip Stoves Ltd., 2012, ver 3" dated July 2012. The appliance must be fitted with a permanent stop to fix the secondary air control such that it cannot be closed more than 25% open.	Wood logs ⁽¹⁾ .
Loxton 5, Churchill 5 and Sqabox Uno stoves. Manufactured by Mendip Stoves Ltd., Unit H1, Mendip Industrial Estate, Mendip Road, Rooksbridge, Somerset, BS26 2UG.	Instruction manual reference "Mendip Stoves Ltd., 2012, ver 3" dated July 2012. The appliance must be fitted with a permanent stop such that the secondary air 'closed position' results in a 2.5mm gap in the two secondary air openings.	Wood logs ⁽¹⁾ .
Loxton 6, Loxton 8, Churchill 6, Churchill 8 and Sqabox Duo stoves.	Instruction manual reference "Mendip Stoves Ltd., 2012, ver 3" dated July 2012.	Wood logs ⁽¹⁾ .
Manufactured by Mendip Stoves Ltd., Unit H1, Mendip Industrial Estate, Mendip	The appliance must be fitted with a permanent stop on the secondary air control such that	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Road, Rooksbridge, Somerset, BS26 2UG.	it cannot be closed more than 35% open.	
Love 7 5kW, 6kW, and 7kW Freestanding multifuel stoves Manufactured by De and	Installation and User Manual reference "LV567 v.2/10-2014" dated October 2014.	Wood logs ⁽¹⁾ .
Vi Commerce JSC, 3 Asen Zlatarov Str., 7150 Dve Mogili, Bulgaria.	The appliance must be fitted with smoke control kit DV6020400GB to prevent secondary air control closure beyond the 35% open position.	
Ludlow Wood Burning Smoke Exempt Stove (Ludlow Stove SE).	Instruction manual reference "N00529AXX REV:001" dated 13th July 2011.	Dry wood logs ⁽¹⁾ .
Manufactured by Aga, Station Road, Ketley, Telford, Shropshire, TF1 5AQ.		
Lundy, Skye and, Ramsey 5kW pellet stoves.	Owners manual for 5kW pellet stove models ;- Lundy, Skye and Ramsey dated 16th July 2015 reference "5kW Stove"	Wood pellets ⁽¹⁾ .
Manufactured by Island Pellet Stoves Ltd, Tugbury house, Unit 26 main avenue, Treforest Industrial Estate, Pontypridd, CF37 5UR		
Lundy, Skye and, Ramsey 8kW pellet boiler stoves.	Owners manual for 8kW pellet boiler stove models;- Lundy, Skye and Ramsey dated 16th July 2015 reference "8kw boiler stove"	Wood pellets ⁽¹⁾ .
Manufactured by Island Pellet Stoves Ltd, Tugbury house, Unit 26 main avenue, Treforest Industrial Estate, Pontypridd, CF37 5UR		
Luno B.13 wood burning stove Manufactured by Hase	Instruction manual reference "Luno_R1" dated November 2014.	Wood logs ⁽¹⁾ .
Kaminofenbau GmbH, Niederkircher Strasse 14, D-54294 Trier	The appliance must be fitted with a mechanical stop to prevent air control closure	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
	beyond the 33mm open position.	
Malvern Multifuel stove (Model MV1MF).	Technical manual reference "MV1MF 0101" dated 17th October 2013.	Wood logs ⁽¹⁾ .
Manufactured by		
ACR Heat Products Ltd, Unit 1, Weston Works, Weston Lane, Tyseley, Birmingham, West Midlands,	When the primary air control is in the closed position, it remains permanently open by 5mm and is prevented from closing fully by a screw.	
B11 3RP.		
Marvic Multifuel Cassette (inset) roomheater.	Instruction manual reference "INK.00.7927" dated 20th December 2011.	Wood logs ⁽¹⁾ .
Manufactured by Wanders Fires & Stoves, Amtweg 4, Netterden, NL-7077 AL, The Netherlands.	The appliance must be fitted with a modification to the secondary air control to ensure that the air supply holes remain 3mm open when the operator has nominally shut the control.	
Mazona Stoves Portland 5kW multifuel inset roomheater. Manufactured by Micon Distribution Limited, 1a	Portland Stove - Smoke Control Area Exempt Operation and Installation Manual dated 15/03/2016 reference "Version B".	Wood logs ⁽¹⁾ .
Hallstown Road, Ballinderry Upper, Lisburn BT28 2NE	The appliance must be fitted with a mechanical stop to prevent closure of the secondary air control beyond the 2mm open position	
Mazona Stoves Rocky 6kW multifuel stove. Manufactured by Micon Distribution Limited, 1a Hallstown Road, Ballinderry	Mazona Rocky - Smoke Control Area Exempt Operation and Installation Manual dated 16/03/2016 reference "Version B".	Wood logs ⁽¹⁾ .
Upper, Lisburn BT28 2NE	The appliance must be fitted with a mechanical stop to prevent closure of the	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fivenians	Conditions	
Class of fireplace	The fireplace must be installed, maintained and operated in accordance with the following specifications: secondary air control beyond the 3mm open position	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Mazona Stoves Tuscon inset multi fuel stove Manufactured by Micon Distribution Ltd, 1a Hallstown Road, Ballinderry Upper, Lisburn BT28 2NE	Instruction manual reference "Version A (MZSTUSE)" dated 17th December 2014. The appliance must be fitted with a mechanical stop to prevent secondary air control closure beyond the 2mm open position.	Wood logs ⁽¹⁾ .
Meg 4.5 Pod and Meg Sirius 450 Qube 4.5kW multi-fuel stoves. Manufactured by F.E. Robinson (Hooton) Ltd, Station Works, Hooton Road, Hooton, South Wirral, CH66 7NF	Instruction manual dated 10 July 2015 reference "Meg Solid Fuel Stoves Manual Version 1.4. Issued 15/07/2015"	Wood logs ⁽¹⁾ .
Meg 5.0 stove and Sirius 600 Inset stove. Manufactured by F.E Robinson, (Hooton) Ltd., Station Works, Hooton Road, Hooton, South Wirral, CH66 7NF.	Instruction manual reference "Manual Version 1.3" dated 27th July 2012. The appliance must be fitted with a mechanical stop to prevent secondary air control closure beyond the 10mm open position.	Wood logs ⁽¹⁾ .
MEG 7.5/Sirius 750 and MEG 4.5/Sirius 450. Manufactured by Meg Stoves, F.E. Robinson (Hooton) Ltd., Station Works, Hooton Road, Hooton, South Wirral, CH66 7NF.	<u> </u>	Wood logs ⁽¹⁾ .
Mendip Burcott SE 4.1kW multi-fuel inset roomheater model No. M00401-00-00-00 Burcott SE,	Operation and installation manual reference "Mendip Stoves Ltd, 2013, Burcott v4" dated 9th August 2014.	Wood logs ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Manufactured by	The appliance must be fitted with a stop to prevent closure	
Mendip Stoves Limited, Unit H1, Mendip Industrial Estate, Mendip Road, Rooksbridge, Somerset, BS26 2UG	of the secondary air control beyond 25% open.	
Mendip Churchill 5 SE 4.5kW multi-fuel stove.	Operation and Installation Manual dated 1st September 2015 reference "MK3".	Wood logs ⁽¹⁾ .
Manufactured by Mendip Stoves Limited, Unit H1, Mendip Industrial Estate, Mendip Road, Rooksbridge, Somerset, BS26 2UG	The appliance must be fitted with a permanent stop to prevent closure of the secondary air control beyond 25% open.	
Mendip Churchill 5 SE Convection Logstore 4.5kW multi-fuel stove.	Operation and Installation Manual dated 1st September 2015 reference "MK3".	Wood logs ⁽¹⁾ .
Manufactured by Mendip Stoves Limited, Unit H1, Mendip Industrial Estate, Mendip Road, Rooksbridge, Somerset, BS26 2UG	The appliance must be fitted with a permanent stop to prevent closure of the secondary air control beyond 25% open.	
Mendip Loxton 5 SE 4.5kW multi-fuel stove.	Operation and Installation Manual dated 1st September 2015 reference "MK3".	Wood logs ⁽¹⁾ .
Manufactured by Mendip Stoves Limited, Unit H1, Mendip Industrial Estate, Mendip Road, Rooksbridge, Somerset, BS26 2UG	The appliance must be fitted with a permanent stop to prevent closure of the secondary air control beyond 25% open.	
Mendip Loxton 5 Maxi SE 4.5kW multi-fuel stove.	Operation and Installation Manual dated 1st September 2015 reference "MK3".	Wood logs ⁽¹⁾ .
Manufactured by Mendip Stoves Limited, Unit H1, Mendip Industrial Estate, Mendip Road, Rooksbridge, Somerset, BS26 2UG	The appliance must be fitted with a permanent stop to prevent closure of the secondary air control beyond 25% open	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Mendip SE Wood Burning 5kW Space Heating Stove.	Instruction manual reference "700273 Iss. 2 Rev. 1" dated January 2012.	Wood logs ⁽¹⁾ .
Manufactured by TR Engineering Ltd., Unit 7, Newton Chambers Way, Thorncliffe Industrial Estate, Chapeltown, Sheffield, S35 2PH.	January 2012.	
Mendip SE Wood Burning 8kW Space Heating Stove.	Instruction manual reference "700275 Iss. 2 Rev. 1" dated January 2012.	Wood logs ⁽¹⁾ .
Manufactured by TR Engineering Ltd., Unit 7, Newton Chambers Way, Thorncliffe Industrial Estate, Chapeltown, Sheffield, S35 2PH.		
Mendip Sqabox unO SE 4.5kW multi-fuel stove.	Operation and Installation Manual dated 1st September 2015 reference "MK3".	Wood logs ⁽¹⁾ .
Manufactured by Mendip Stoves Limited, Unit H1, Mendip Industrial Estate, Mendip Road, Rooksbridge, Somerset, BS26 2UG	The appliance must be fitted with a permanent stop to prevent closure of the secondary air control beyond 25% open.	
Mendip Stoves Christon Round D600 SE with 3 sided frame and Christon Round D600 SE with 4 sided frame wood-burning inset roomheaters	Instruction manual reference "Mendip Stoves Limited, 2014. Christon Insets v1 06.2014" dated June 2014. The appliance must be fitted with a permanent stop on the results of the permanent stop on the permanent stop of t	Wood logs ⁽¹⁾ .
Manufactured by	with a permanent stop or other measure to prevent closure of the air control beyond the 40%	
Fogo Montanha (Solzaima, S.A.)	open position.	
Rua dos Outarelos, 111		
3750-362 Belazaima do Chão, Portugal		

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Mendip Stoves Somerton 2 Standard SE, Somerton 2 Compact SE, Somerton 2 Pedestal SE 7kW wood burning stoves	Operation and installation manual reference "Mendip Stoves Ltd., Somerton 2. 2013. Ver.2" dated May 2014.	Wood logs ⁽¹⁾ .
Manufactured by Mendip Stoves Ltd., Unit H1, Mendip, Industrial Estate, Rooksbridge, Somerset, BS26 2UG	The appliance must be fitted with a mechanical stop to prevent closure of the secondary air control beyond the 25% open position.	
Merlin Midline ST-C and Merlin Slimline ST-D multifuel stoves.	Installation and operation instruction manual reference "MerlinST-C&D_v1" dated 16th July 2013.	Wood logs ⁽¹⁾ .
Manufactured by Merlin Stoves Ltd., Foregates, Holmer, Hereford, HR4 9RJ.	The appliance must be fitted with a mechanical stop to prevent air control closure beyond the 50mm open position.	
Mescoli PB50, PB35, PB28. Manufactured by MESCOLI CALDAIE S.rl. Caldaie-Termocucine, Via del Commercio, 285 4 1058 Vignola, (MO) Italy.	Instruction and installation manual reference "SY315EVO P,C,B-COMBIFIRE 2 PB28/35/50 BOILERS Edition 1.7" dated January 2006.	Wood pellets following ÖNORM M7 135 or DIN plus (DIN 51731) ⁽¹⁾ .
Micromet MEG 7.5 (also known as the Sirius 750); Micromet MEG 4.5 (also known as the Sirius 450).	Instruction manual reference "Micromet Solid Fuel Stoves Manual (24)" dated 16th June 2010.	Dry wood logs ⁽¹⁾ .
Manufactured by Micromet, 125 Bridge St, Birkenhead, Merseyside, CH41 1BD.		
Mido UK, Mido Soapstone UK 6kW stoves. Manufactured by Jydepejsen A/S, Ahornsvinget 3-7, Nr.	User's manual dated June 2011 reference "Cosmo & Midi. User's manual. Jydepejsen A/S - June 2011"	Wood logs ⁽¹⁾ .
Felding, DK-7500 Holstebro, Denmark	The appliance must be fitted with a mechanical stop to prevent closure of the air	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
	control valve beyond the 16% open position	
Milan Series 4.	Instruction manual reference "CH4K Milan-V2" dated 18th	Wood logs ⁽¹⁾ .
Manufactured by Chesneys Ltd., 194-200 Battersea Park	November 2010.	
Road, London, SW11 4ND.	The appliance must be fitted with a system to prevent closure of the air control beyond the 25mm open position.	
Milan Series 6. Manufactured by Chesneys	Instruction manual reference "CH6K Milan-V2" dated 18th November 2010.	Wood logs ⁽¹⁾ .
Ltd., 194-200 Battersea Park Road, London, SW11 4ND.	The appliance must be fitted with a system to prevent closure of the air control beyond the 40mm open position.	
Mi Stoves Taymin 5 CB 4.9kW multifuel stove. Manufactured by Capital	Installation & Operating Instructions dated 26th June 2015 reference "15JUN09/ TA5/V1.2"	Wood logs ⁽¹⁾ .
Fireplaces Ltd, Units 12-17, Henlow Trading Estate	Fitted with a mechanical stop to prevent secondary air	
Henlow Camp, SG16 6DS	control closure beyond the 50% open position.	
Mi Stoves Taymin 8 CB 8.9kW multifuel stove	Installation & Operating Instructions dated 26th June 2015 reference "15JUN10/	Wood logs ⁽¹⁾ .
Manufactured by Capital Fireplaces Ltd, Units 12-17,	TA8/V1.4"	
Henlow Trading Estate	Fitted with a mechanical	
Henlow Camp, SG16 6DS	stop to prevent secondary air control closure beyond the 50% open position.	
Monaco multifuel Stove, Staub Fonderie-Franco Belge model 1340605.	Instruction manual reference "1303 - 1" dated 4th May 2010.	Wood logs ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Manufactured by Staub Fonderie-Franco Belge, Rue Orphee Variscotte, 59660, Merville, France.	The appliance must be fitted with a mechanical stop to prevent closure of the secondary air control beyond 4mm from closed.	
Mondo 1, Mondo 2 and Mondo Petite stoves. Manufactured by Lotus Heating Systems A/S,	Instruction manual reference "Lotus-Mondo Series Stoves Version 1" dated 15th October 2012.	Wood logs ⁽¹⁾ .
Agertoften 6, 5550 Langeskov, Denmark.	The appliance must be fitted with a mechanical stop to prevent closure of the air dampers beyond the 8mm open position.	
Morsø-Ø4. Manufactured by Morsø Jernstoberi A/S, DK-7900 Nykobing, Mors, Denmark.	Instruction manual reference "Ø- Collection" dated 1st February 2010 and instruction manual reference "72000400" dated 1st February 2010. Applies to units manufactured after 01/02/2010.	Wood logs ⁽¹⁾ .
The Morsø 1400 series consisting of the 1412 and 1442 models.	Manufacturer's instructions	Wood logs with less than 20% moisture (1).
Manufactured by Morsø Jernstøberi A/S DK-7900 Nykøbing, Mors, Denmark.		
Morsø 1416, 1418, 1446 and 1448 4kW stoves.	Instruction manual reference "Morsø 1416, 1418, 1446 & 1448. Instruction for	Wood logs ⁽¹⁾ .
Manufactured by Morsø Jernstøberi A/S DK-7900 Nykøbing, Mors, Denmark.	Installation and use Part No: 72150000" dated 31st January 2012.	
The Morsø 3100 series consisting of the 3112 and 3142 models.	Manufacturer's instructions reference "72311200" dated 4th February 2008.	Wood logs with less than 20% moisture ⁽¹⁾ .
Manufactured by Morsø Jernstøberi A/S DK-7900 Nykøbing, Mors, Denmark.		

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
The Morsø 6140 series consisting of the 6140 and 6148 models.	Manufacturer's instructions reference "72610400" dated 4th September 2007.	Wood logs with less than 20% moisture ⁽¹⁾ .
Manufactured by Morsø Jernstøberi A/S DK-7900 Nykøbing, Mors, Denmark.		
Morsø 7300 series 4.3kW wood burning stoves models 7340, 7342, 7343, 7348 & 7370	Instructions for installation and use reference "72746400" dated August 2014.	Wood logs ⁽¹⁾ .
Manufactured by Morsø Jernstøberi A/S . DK-7900 Nykøbing Mors, Denmark	The appliance must be fitted with a permanent stop to prevent closure of the secondary air control inlet beyond 22mm open.	
Morsø 7400 series 4.3kW wood-burning stoves models 7440, 7442, 7443, 7448 & 7470	Instructions for installation and use reference "72746400" dated August 2014.	Wood logs ⁽¹⁾ .
Manufactured by Morsø Jernstøberi A/S . DK-7900 Nykøbing Mors, Denmark	The appliance must be fitted with a permanent stop to prevent closure of the secondary air control inlet beyond 22mm open.	
Morsø 7600 series including Model 7642, 7644 and 7648.	Instructions for installation and use reference "72762200" dated 14th July 2010.	Wood logs with less than 20% moisture (1).
Manufactured by Morsø Jernstøberi A/S DK-7900 Nykøbing, Mors, Denmark.	The air control been altered such that this equates to an increased minimum open position. Reference drawings Morsø 7600-137, 7600-138, 7600-139, 7600-140 and 7600-141.	
Morsø 7800 series 7.3 kW wood-burning stoves models 7840, 7843, 7848, 7850, 7851, 7870, 7890	Instructions for installation and use reference "72797500" dated August 2014.	Wood logs ⁽¹⁾ .
	The appliance must be fitted with a permanent stop to prevent closure of the	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

The fireplace must be installed, maintained and operated in accordance with the following specifications: Manufactured by Morso Jernstoberi A/S . DK-7900 Nykobing Mors, Denmark	Class of fireplace	Conditions	
Morso 7900 series 7.3 kW wood-burning stoves models 7940, 7943, 7948, 7950, 7970, 7990 M Manufactured by Morso Bernstoberi A/S . DK-7900 Nykobing Mors, Denmark Morso DB15 central heating stove distributed by Solife Expose Advice Sheet no1" dated 22nd January 2014. Morso Jernstoberi A/S DE-7900 Nykobing, Mors, Denmark. Instruction manual reference "Solife Fuel Central Heating Stoves Manual Issued - 22/01/2014 (459)" dated 22nd January 2014 and reference "Solifee Smoke Advice Sheet no1" dated 22nd January 2014. Solifee Smoke Advice Sheet no1" dated 22nd January 2014. Morso Owl 3410, 3420 and Manufacturer's instructions reference "72345600" dated for wood which has been split, stacked and start of the start wood which fast of the fitted with a gramme of instruction and use reference "72797500" and use reference use reference "72797500" and use reference use of the total weight (1).	Jernstøberi A/S . DK-7900	installed, maintained and operated in accordance with the following specifications: secondary air control inlet	in the fireplace other than authorised fuels and the
wood-burning stoves models 7940, 7943, 7948, 7950, 7970, 7990 M Manufactured by Morso Jernstoberi A/S . DK-7900 Nykobing Mors, Denmark Morso DB15 central heating stove distributed by 22/01/2014 (459)" dated 22nd January 2014. Morso Jernstoberi A/S . DK-7900 Nykobing, Mors, Denmark. Morso Owl 3410, 3420 and 3440 for wood burning. Morso Owl 3410, 3420 and 3440 for wood burning.	Nykøbing Mors, Denmark		
Manufactured by Morsø Jernstoberi A/S. DK-7900 Nykøbing Mors, Denmark Morsø DB15 central heating stove distributed by Morsø Jernstøberi A/S DK-7900 Nykøbing, Mors, Denmark. Instruction manual reference "Solid Fuel Central Heating Stoves Manual Issued - 22/01/2014 (459)" dated 22nd January 2014 and reference "Soliftee Smoke Advice Sheet no1" dated 22nd January 2014. "Soliftee Smoke Advice Sheet no1" dated 22nd January 2014. Wildfire, manufactured by Rheinbraun AG of Germany and comprising lignite compressed into briquettes of approximately 15 cm in length with square ends and with a sulphur content not exceeding 1% of the total weight. CPL Wildfire, manufactured by Coal Products Limited, Immingham, which comprise bituminous coal with a volatile content of 32-36 % (as to approximately 96% of the total weight); are manufactured from those constituents by a process involving roll-pressing; have an average weight of either 80-90 grammes; and have a sulphur content not exceeding 1.8% of the total weight (1). Morsø Owl 3410, 3420 and 3440 for wood burning. Manufacturer's instructions reference "72345600" dated Manufacturer's instructions reference "72345600" dated Manufacturer's instructions reference "72345600" dated	wood-burning stoves models 7940, 7943, 7948, 7950, 7970,	and use reference "72797500"	Wood logs ⁽¹⁾ .
Stove distributed by Morsø Jernstøberi A/S DK-7900 Nykøbing, Mors, Denmark. Solid Fuel Central Heating Stoves Manual Issued - 22/01/2014 (459)" dated 22nd January 2014 and reference "Soliftee Smoke Advice Sheet no1" dated 22nd January 2014. Rheinbraun AG of Germany and comprising lignite compressed into briquettes of approximately 15 cm in length with square ends and with a sulphur content not exceeding 1% of the total weight. CPL Wildfire, manufactured by Coal Products Limited, Immingham, which comprise bittuminous coal with a volatile content of 32-36 % (as to approximately 96% of the total weight) and a cold cure resin binder (as to the remaining weight); are manufactured from those constituents by a process involving roll-pressing; have an average weight of either 80-90 grammes or 160-170 grammes; and have a sulphur content not exceeding 1.8% of the total weight (1). Morsø Owl 3410, 3420 and 3440 for wood burning. Manufacturer's instructions reference "72345600" dated	Jernstøberi A/S . DK-7900	fitted with a permanent stop to prevent closure of the secondary air control inlet	
3440 for wood burning. reference "72345600" dated has been split, stacked and	stove distributed by Morsø Jernstøberi A/S DK-7900 Nykøbing, Mors,	"Solid Fuel Central Heating Stoves Manual Issued - 22/01/2014 (459)" dated 22nd January 2014 and reference "Soliftec Smoke Advice Sheet	or peat briquettes with, in either case, less than 25% moisture. Union Coal Brikettes, manufactured by Rheinbraun AG of Germany and comprising lignite compressed into briquettes of approximately 15 cm in length with square ends and with a sulphur content not exceeding 1% of the total weight. CPL Wildfire, manufactured by Coal Products Limited, Immingham, which comprise bituminous coal with a volatile content of 32-36 % (as to approximately 96% of the total weight) and a cold cure resin binder (as to the remaining weight); are manufactured from those constituents by a process involving roll-pressing; have an average weight of either 80-90 grammes or 160-170 grammes; and have a sulphur content not exceeding 1.8% of
15t January 2000.		reference "72345600" dated	Untreated dry wood which

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Manufactured by Morsø Jernstøberi A/S DK-7900 Nykøbing, Mors, Denmark.		air dried; or air dried wood briquettes ⁽¹⁾ .
Morsø S10-40 5kW stove.	Instruction manual reference "Morsø S10. Instruction for	Wood logs ⁽¹⁾ .
Manufactured by Morsø Jernstøberi A/S DK-7900 Nykøbing, Mors, Denmark.	Installation and use. Part No: 72104000" dated 31st January 2012.	
Morsø S10-70 5kW stove. Manufactured by Morsø Jernstøberi A/S DK-7900 Nykøbing, Mors, Denmark.	Instruction manual reference "Morsø S10-70. Instruction for Installation and use. Part No: 72103000" dated 31st January 2012.	Wood logs ⁽¹⁾ .
Morsø S11-40, S11-42, S11-43 and S11-90 4kW stoves. Manufactured by Morsø Jernstøberi A/S DK-7900	Instruction manual reference "Morsø S11. Instruction for Installation and use. Part No: 72114200" dated 31st January 2012.	Wood logs ⁽¹⁾ .
Nykøbing, Mors, Denmark.		
Morsø S81-90 4kW stove. Manufactured by Morsø Jernstøberi A/S DK-7900 Nykøbing, Mors, Denmark.	Instruction manual reference "Morsø S81-90. Instruction for Installation and use" dated 30th January 2012.	Wood logs ⁽¹⁾ .
Multibio 49 pellet boiler. Manufactured by Ekoefekt Inc. Semecska 187, 411 15 Trebivlice, Czech Republic.	Instruction manual reference "MB49/IM/ISSUE 001" dated 4th July 2012.	Wood pellets or olive kernels (1).
Neo models 1C,1P,1W, 3C,3P and 3W 5kW multifuel stoves	Technical manual dated 13th May 2015 reference "Document NEO Version 2"	Wood logs ⁽¹⁾ .
Manufactured by ACR Heat Products Ltd, Unit 1 Weston Works, Weston Lane, Tyseley, Birmingham, B11 3RP	The appliance must be fitted with a mechanical stop to prevent closure of the rotary air control beyond the 27mm open position.	
Nero D IHS, Nero M IHS,	Instruction manual dated November 2014 reference "DSB2-Defra / UK-NI-ROI / V3.01.15	Wood logs ⁽¹⁾ .
(4)		

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Vecto D IHS, Vecto M IHS and, Orbit 6Kw IHS free standing wood-burning stoves	A modification to prevent closure of the air flow control valve below position 2 must be implemented.	
Manufactured by Dan Skan GmbH, Burgwedeler Str. 7-8, D-30657 Hannover, Germany		
Nero D, Nero M, Vecto D, Vecto M and Orbit 6kW free standing wood burning stoves	Instruction manual reference "DSB2-Defra/UK-NI-ROI/ V1.11.14" dated November 2014.	Wood logs ⁽¹⁾ .
Manufactured by Dan Skan GmbH, Burgwedeler Str. 7-8, D-30657 Hannover, Germany.	The appliance must be fitted with a modification to prevent closure of the air flow control valve below position 2.	
Nestor Martin C23 multifuel stove (7.7kW);	Euroheat Distributors (HBS) Ltd.'s operation instructions reference "IN 1213 Edition B"	Untreated dry wood ⁽¹⁾ .
Nestor Martin C33 multifuel stove (9.2kW);	dated June 2010.	
Nestor Martin D33 multifuel stove (8kW).		
Manufactured by Nestor Martin S.A. 11 Rue de Lion, B-5660, Frasnes Lez Couvin, Belgium.		
Nestor Martin 'Harmony' H13 multifuel stove (3.5kW nominal thermal output).	Euroheat Distributors (HBS) Ltd.'s operation instructions reference "IN 1116 Edition D"	Untreated dry wood ⁽¹⁾ .
Manufactured by Nestor Martin S.A. 11 Rue de Lion, B-5660, Frasnes Lez Couvin, Belgium.	dated January 2007.	
Nestor Martin 'Harmony' H13 multifuel stove (5kW);	Euroheat Distributors (HBS) Ltd.'s operation instructions reference "IN 1116 Edition	Untreated dry wood ⁽¹⁾ .
Nestor Martin 'Stanford' S13 multifuel stove (3.5kW).	D5" dated June 2010.	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Manufactured by Nestor Martin S.A. 11 Rue de Lion, B-5660, Frasnes Lez Couvin, Belgium.	The minimum air bleed flap must be set at a minimum of 14.5mm.	
Nestor Martin 'Harmony' H23 (6kW) and H33 (8kW) multifuel stoves;	Euroheat Distributors (HBS) Ltd.'s operation instructions reference "IN 1116 Edition D5" dated June 2010.	Untreated dry wood ⁽¹⁾ .
Nestor Martin 'Stanford' S23 (6kW) SP23 (6kW) S33 (8kW) and SP33 (8kW) multifuel stoves.		
Manufactured by Nestor Martin S.A. 11 Rue de Lion, B-5660, Frasnes Lez Couvin, Belgium.		
Nestor Martin IN13 Insert multifuel stove (5kW).	Euroheat Distributors (HBS) Ltd.'s operation instructions reference "IN 1214 edition B"	Untreated dry wood (1).
Manufactured by Nestor Martin S.A. 11 Rue de Lion,	dated June 2010.	
B-5660, Frasnes Lez Couvin, Belgium.	The minimum air bleed flap must be set at a minimum of 14.5mm.	
Nestor Martin IT 13 multifuel stove (3.5kW).	Euroheat Distributors (HBS) Ltd.'s operation instructions reference "IN 1180 Edition	Untreated dry wood ⁽¹⁾ .
Manufactured by Nestor Martin S.A. 11 Rue de Lion,	D1" dated June 2010.	
B-5660, Frasnes Lez Couvin, Belgium.	The minimum air bleed flap must be set at a minimum of 14.5mm.	
Nestor Martin R23 multifuel stove (6kW).	Euroheat Distributors (HBS) Ltd.'s operation instructions reference "IN 1141 Edition B"	Untreated dry wood ⁽¹⁾ .
Manufactured by Nestor Martin S.A. 11 Rue de Lion, B-5660, Frasnes Lez Couvin, Belgium.	dated November 2006.	
Nestor Martin R33 (8kW) multifuel stove.	Euroheat Distributors (HBS) Ltd.'s operation instructions	Untreated dry wood ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

C1 CC 1	C 1:	
Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Manufactured by Nestor Martin S.A. 11 Rue de Lion, B-5660, Frasnes Lez Couvin, Belgium.	reference "IN 1116 Edition D" dated January 2007.	
Newark EGTL05.	Instruction manual reference "EGTL05 Version 1.4" dated	Wood logs ⁽¹⁾ .
Manufactured by Elite Group Trading Ltd., Room 1208, Kak	5th July 2011.	
Tak Commercial Building, 317-319 Des Voeux Road Central, Hong Kong, 999077.	The appliance must be fitted with a permanent stop to prevent any closure of the tertiary air control.	
Newbourne 35FS, and	Installation and Operating Instructions for Newbourne	Wood Logs ⁽¹⁾ .
Newbourne 35FS Panorama, 3.8kW multifuel stoves	35/40/50/60 FS Multfuel stoves dated June 2015 reference "Pevex1022/AH/	
Manufactured by Pevex Enterprises Ltd, Unit MP7,	ver1"	
Kirrawah Business Park, Newbourne Road,	The appliance must be fitted with a permanent stop that ensures the air control cannot	
Nr Woodbridge, IP12 4PR	close beyond 15% open position.	
Newbourne 40 and Newbourne 50 Freestanding stoves.		Wood logs ⁽¹⁾ .
Manufactured by Pevex Enterprises Ltd., Unit 16,	"Pevex1012/AH/ver1" dated January 2013.	
Seven Acres Business Park, Newbourne Road, Waldringfield, Nr Woodbridge, IP12 4PS.	The appliance must be fitted with a permanent stop ensuring a minimum opening area of 1cm² for the primary air slider when in the fully closed position and a tertiary air inlet area of 4cm².	
Newbourne 40FS and Newbourne 40FS Panorama 4.5kW multifuel stoves.	Installation and Operating Instructions for Newbourne 35/40/50/60 FS Multfuel stoves dated June 2015	Wood Logs ⁽¹⁾ .
Manufactured by Pevex Enterprises Ltd, Unit MP7,	reference "Pevex1022/AH/ver1"	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	1
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Kirrawah Business Park,	A permanent stop must be	
Newbourne Road,	implemented ensuring a minimum opening area of	
Nr Woodbridge, IP12 4PR	1 cm2 for the primary air slider when in the fully closed position and a tertiary air inlet area of 4 cm2.	
Newbourne 40i 4.5kW multifuel inset roomheater. Manufactured by Pevex Enterprises Ltd, Unit MP7,	Installation and Operating Instructions for Newbourne 40 inset multifuel stoves dated June 2015 reference "Pevex 1033/AH/ver1:June2015"	Wood Logs ⁽¹⁾ .
Kirrawah Business Park, Newbourne Road,	The appliance must be fitted	
Nr Woodbridge, IP12 4PR	with permanent stops that ensure the primary and tertiary air controls do not close beyond 0.5cm open and 2 cm open positions respectively.	
Newbourne 40 inset stove.	Instruction manual reference	Wood logs ⁽¹⁾ .
Manufactured by Pevex Enterprises Ltd., Unit 16, Seven Acres Business	"Pevex1015/AH/ver1" dated January 2013.	
Park, Newbourne Road, Waldringfield, Nr Woodbridge, IP12 4PS.	The appliance must be fitted with permanent stops that ensure the secondary and tertiary air controls do not close beyond 1.1cm open and 2cm open positions respectively.	
Newbourne 50FS and Newbourne 50FS Panorama 5kW multifuel stoves.	Installation and Operating Instructions for Newbourne 35/40/50/60 FS Multfuel stoves dated June 2015	Wood Logs ⁽¹⁾ .
Manufactured by Pevex Enterprises Ltd, Unit MP7, Kirrawah Business Park,	reference "Pevex1022/AH/ ver1"	
Newbourne Road,	A permanent stop must be implemented ensuring a	
Nr Woodbridge, IP12 4PR	minimum opening area of 1 cm2 for the primary air slider when in the fully closed	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
158

Class of fireplace	Conditions	
Crass of fireprace	The fireplace must be installed, maintained and operated in accordance with the following specifications: position and a tertiary air inlet area of 4 cm2.	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Newbourne 60FS Panorama and Newbourne 60FS 7kW multifuel stove. Manufactured by Pevex Enterprises Ltd, Unit MP7, Kirrawah Business Park, Newbourne Road, Nr Woodbridge, IP12 4PR	Installation and Operating Instructions for Newbourne 35/40/50/60 FS Multfuel stoves dated June 2015 reference "Pevex1022/AH/ ver1"	Wood Logs ⁽¹⁾ .
Newton SE Wood Burning 5kW Space Heating Stove.	Instruction manual reference "700504 Iss. 2 Rev 1" dated	Wood logs ⁽¹⁾ .
Manufactured by TR Engineering Ltd., Unit 7, Newton Chambers Way, Thorncliffe Industrial Estate, Chapeltown, Sheffield, S35 2PH.	January 2012.	
Newton SE Wood Burning 8kW Space Heating Stove.	Instruction manual reference "700506 Iss. 3 Rev. 2" dated January 2012.	Wood logs ⁽¹⁾ .
Manufactured by TR Engineering Ltd., Unit 7, Newton Chambers Way, Thorncliffe Industrial Estate, Chapeltown, Sheffield, S35 2PH.	<i>unium</i> y 2012.	
Nordic 350.	Instruction manual reference number "1001" dated 20th July	Wood logs ⁽¹⁾ .
Manufactured by C DE A Ingenieria Ltda, Jose Miguel Carrera 6, Colina, Santiago, 9361294, Chile.	2012.	
Nordpeis Bergen (NP- BERGEN) wood burning 5.4kW stove	Installation and user manual reference "PM1081 Issue 1" dated 1st January 2013 and additional installation and user	Wood logs ⁽¹⁾ .
Manufactured by Nordpeis AS, Gjellebekkstubben 11, N-3420 LIERSKOGEN, Norway.		

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
	PM1066 Issue 2" dated July 2014.	
	The appliance must be fitted with a mechanical stop to prevent air vent control closure beyond 7mm open.	
Nordpeis Duo 1 (NP- DUO1STOVE), 2 (NP- DUO2STOVE), 4 (NP- DUO4STOVE), and 5 (NP- DUO5STOVE) wood burning 5kW stoves Manufactured by Nordpeis AS, Gjellebekkstubben 11, N-3420	Installation and user manual reference "PM1083 Issue 1" dated 13th May 2013 and additional installation and user instructions for use in Smoke Control Areas reference "PM1112 Issue 1" dated July 2014.	Wood logs ⁽¹⁾ .
LIERSKOGEN, Norway	The appliance must be fitted with a mechanical stop to prevent closure beyond the 28% open position.	
Nordpeis Quadro 1 (NP-QUAD1P) and 2 (NP-QUAD2B) wood burning 6.2kW stoves Manufactured by Nordpeis AS, Gjellebekkstubben 11, N-3420 LIERSKOGEN, Norway.	User manual reference "PM1084 Issue 1" dated 3rd September 2012 and additional installation and user instructions for use in Smoke Control Areas reference "PM1068 Issue 1" dated July 2014.	Wood logs ⁽¹⁾ .
	The appliance must be fitted with a mechanical stop to prevent air control closure beyond 8mm open.	
Nordpeis S-31A(S31-A) wood burning 6.2kW inset roomheater Manufactured by Nordpeis AS, Gjellebekkstubben 11, N-3420 LIERSKOGEN, Norway.	User manual reference "PM1089 Issue 1" dated 15th January 2013 and additional installation and user instructions for use in Smoke Control Areas reference "PM1068 Issue 1" dated July 2014.	Wood logs ⁽¹⁾ .
	The appliance must be fitted with a mechanical stop to	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
	prevent air control closure beyond 8mm open.	
Nordpeis Uno 1 (NP-UNO1), 2 (NP-UNO2), and 4 (NP- UNO4) wood burning 4.2kW stoves Manufactured by Nordpeis AS, Gjellebekkstubben 11, N-3420 LIERSKOGEN, Norway.	Installation and user manual reference "PM1082 Issue 1" dated 14th May 2013 and additional installation and user instructions for use in Smoke Control Areas reference "PM1111 Issue 1" dated July 2014.	Wood logs ⁽¹⁾ .
	The appliance must be fitted with a mechanical stop to prevent air control closure beyond the 38% open position.	
Nørreskoven MkII. Manufactured by Hunter Stoves Ltd., Trevilla Park, Slaughterbridge, Camelford, Cornwall, PL32 9TT.	Instruction manual reference "Cleanburn, Nørreskoven MkII, Multifuel Stove. Installation and Operating Instructions, v01.11" dated January 2011.	Wood logs ⁽¹⁾ .
	The appliance must have a factory fitted stop to prevent closure of secondary air control beyond 40%.	
Norvik 5. Manufactured by Elite Group Trading Ltd., Room 1208, Kak	Instruction manual reference "EGTL05A Version 1.5" dated 12th September 2011.	Wood logs ⁽¹⁾ .
Tak Commercial Building, 317-319 Des Voeux Road Central, Hong Kong, 999077.	The appliance must be fitted with a permanent stop to prevent any closure of the tertiary air control.	
Oakdale FB1MF 5kW multifuel stove. Manufactured by ACR Heat	Technical manual dated 17th February 2015 reference "Document FB1MF 0101 Version 2"	Wood logs ⁽¹⁾ .
Products Ltd, Unit 1 Weston Works, Weston Lane, Tyseley, Birmingham, B11 3RP	The appliance must be fitted with a mechanical stop to prevent closure of the secondary air slider beyond the	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
	25mm open position and, the tertiary air control will be fixed in the fully open position.	
Octoplus 10 and Octoplus 15 Boiler. Manufactured by Solarfocus Ltd., Werkstrasse 1, 4451 St.Ulrich, Steyr, Austria.	Installation instructions reference "Version 1.1" dated 19th April 2010 and operating manual reference "Version 10.051" dated 10th May 2010.	Wood pellets ⁽¹⁾ .
ÖkoFEN Pellematic PE08, PE12, PE16, PE20, PE25, PE32, PEK12, PEK16, PEK20, PEK25, PEK32, PES12, PES16, PES20, PES25, PES32, PESK12, PESK16, PESK20, PESK25, and PESK32.	Manufacturer's instructions reference "PE/HB/001.E" dated February 2007.	Wood pellets with a maximum diameter of 6mm and a maximum length of 4cm ⁽¹⁾ .
Manufactured by ÖkoFEN Forschungs-und Entwicklungs Ges.m.b.H of Gewerbepark1, 4133 Niederkappel, Austria.		
ÖkoFEN Pellematic PE36, PE48, PE56, PEK36, PEK48, PEK56, PES36, PES48, PES56, PESK36, PESK48, PESK56.	Manufacturer's instructions reference "PBV 2000 CMP 1.4 (V2.31)" dated March 2008.	Wood pellets with a maximum diameter of 6mm and a maximum length of 4cm ⁽¹⁾ .
Manufactured by ÖkoFEN Forschungs-und Entwicklungs Ges.m.b.H of Gewerbepark1, 4133 Niederkappel, Austria.		
Olymberyl Baby Gabriel model number HF217-SE.	Instruction manual reference "HF217-SE/UK-NI-ROI/V2.16-06-11" dated June 2011.	Wood logs ⁽¹⁾ .
Manufactured by Henan Hi-Flame Metal Co. Ltd., Eastside, Yugang Avenue, Airport District, Zheng Zhou 451163, Henan, China.	The appliance must be fitted with a mechanical stop to prevent closure of the secondary air control beyond the 3mm open position.	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions		
	1 *		No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Omega UK, Omega High UK, Omega Chef UK and Omega Core UK.	Installation and Operation manual dated June 2015 reference "Omega, Omega High, .User manual. Revision		Wood logs ⁽¹⁾ .
Manufactured by Jydepejsen A/S, Ahornsvinget 3-7, Nr.	1, 25.03.2015	,	
Felding, DK-7500 Holstebro, Denmark	The appliance with a mechan prevent closure control valve to open position	ical stop to	
Optifire 800 Green, Infire 800 Green, wood burning stoves.	Instruction ma "07DH8000A" November 201	' dated	Wood logs ⁽¹⁾ .
Manufactured by Bodart & Gonay Ltd., Rue De Lambinon, 3 Harze, Belgium, 4920.	The appliance with a "UK kit areas OPTI IF	t for smokeless	
Orchard Ovens models: FVR Speciale 80, 100, 110, 110 x 160 and 120; TOP Superiore	Manufacturer's instructions dated 25th October 2004 references:		Untreated dry wood ⁽¹⁾ .
100 and 120; GR 100, 120, 140, 120 x 160, 140 x 160, 140	Instruction	Model	-
x 180 and 180; OT 100, 120,	OOL inst.1	FVR 80	-
140, 120 x 160, 140 x 160, 140 x 180 and 180; the Valoriani	OOL inst.2	FVR100	_
Piccolo.	OOL inst.3	FVR 110	_
Manufactured by Valoriani of	OOL inst.4	FVR 120	_
Via Caselli alla Fornace, 213 50066 Reggello, Firenze, Italy.	OOL inst.5	FVR 110x160	
50000 Reggeno, I nenze, italy.	OOL inst.6	TOP 100	_
	OOL inst.7	TOP 120	_
	OOL inst.8	GR 100 and	
		OT 100	
	OOL inst.9	GR 120 and	-
		OT 120	_
	OOL inst.10	GR 140 and	
		OT 140	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions		
	The fireplace must be installed, maintained and operated in accordance with the following specifications:		No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
	OOL inst.11	GR 120x160 and OT 120x160	
	OOL inst.12	GR 140x160 and OT 140x160	
	OOL inst.13	GR 140x180 and OT 140x180	
	OOL inst.14	GR 180 and	•
		OT 180	
	OOL inst.15	Valoriani Piccolo	
Oregon EGTL03. Manufactured by Elite Group Trading Ltd., Room 1208, Kak Tak Commercial Building, 317-319 Des Voeux Road Central, Hong Kong, 999077.	Instruction mai "EGTL03 Vers 5th July 2011.		Wood logs ⁽¹⁾ .
Orion UK and Orion Soapstone UK 7kW stoves. Manufactured by Jydepejsen A/S, Ahornsvinget 3-7, Nr.	User's manual 2015 reference Orion & Troja Revision 1, 25	"Sirius & User manual.	Wood logs ⁽¹⁾ .
Felding, DK-7500 Holstebro, Denmark	The appliance with a mechan prevent closure control valve be open position	ical stop to	
Osby Parca P500 Type 30 wood pellet boiler using Bioline 300 pellet burner.	Instruction man "Osby Parca P biomass O & M dated 18th July	500 Type P30 M: Version 1"	Wood pellets ⁽¹⁾ .
Manufactured by Enertech AB, Osby Parca Division, PO Box 93, SE-283 22 Osby, Sweden. The burner is manufactured by Ecotec varmesystem AB	The appliance management system that the boil operate at 100% Continuous Ra	ystem designed er will only % Maximum	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Hedbovagen 42, PO Box 2103, S-511 02 Skene, Sweden.		
Osby Parca PB2 2000kW boiler.	Operating & Maintenance manual, PB2 boiler reference "manual	Wood pellets ⁽¹⁾ .
Manufactured by Enertech AB, Osby Parca Division, PO Box 93, SE-283 22 Osby, Sweden.	PB2_ENG_Rev2_JAN2012" dated January 2012.	
Osby Parca PB2 3000kW boiler.	Operating & Maintenance manual, PB2 boiler reference "manual	Wood pellets, wood chips wood briquettes ⁽¹⁾ .
Manufactured by Enertech AB, Osby Parca Division, PO Box 93, SE-283 22 Osby, Sweden.		
Ottawa B.12 wood burning stove	Instruction manual reference "Ottawa_R1" dated November 2014.	Wood logs ⁽¹⁾ .
Manufactured by Hase Kaminofenbau GmbH, Niederkircher Strasse 14, D-54294 Trier	The appliance must be fitted with a mechanical stop to prevent air control closure beyond the 42mm open position.	
Oxford 4.6kW multi-fuel stove.	Bronpi Installation Instructions. Version 3 Issued 15-12-2014Bronpi	Wood logs ⁽¹⁾ .
Manufactured by Bronpi Calefaccion, Carretera Cordoba-Malaga Km 78.2. Spain	Supplementary Instructions Mod. Oxford. Version 7 Issued 23-01-2015	
•	Appliances must be fitted with a permanent stop to prevent closure of the air control beyond 25% open position	
Parkray Caprice 4.	Instruction manual reference "JINCAP04 Rev E" dated	Wood logs ⁽¹⁾ .
Manufactured by Hunter Stoves Ltd., Trevilla Park, Slaughterbridge, Camelford, Cornwall, PL32 9TT.	2nd December 2011 and instruction manual reference "JINCAP04SCK revB" dated 5th December 2011.	
(4) 771 6 1		

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications: The appliance must be fitted with smoke control area kit	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Parkray Caprice 4 Euro 4.9kW wood-burning stove. Manufactured by Hunter Stoves Ltd, Trevilla Park, Slaughterbridge, Camelford, Cornwall, PL32 9TT	Installation and Operating Instructions dated 29/01/2015 reference "JINCAE04 RevA" and Smoke Control Area Kit Installation Instructions dated 05/12/11 reference "JINCAP04SCK revB" Fitted with "smoke control	Wood logs ⁽¹⁾ .
Parkray Caprice 5 inset stove. Manufactured by Hunter Stoves Ltd., Trevilla Park, Slaughterbridge, Camelford, Cornwall, PL32 9TT.	Instruction manual reference "JINCAP05 Rev B" dated 10th December 2012 and instruction manual reference "JINCAP05SCK Rev A" dated 6th July 2012.	Wood logs ⁽¹⁾ .
	The appliance must be fitted with smoke control area kit JCAP0501.	
Parkray Caprice 6 inset stove. Manufactured by Hunter Stoves Ltd., Trevilla Park, Slaughterbridge, Camelford, Cornwall, PL32 9TT.	Instruction manual reference "JINCAP06 Rev B" dated 10th December 2012 and instruction manual reference "JINCAP05SCK Rev A" dated 6th July 2012. The appliance must be fitted	Wood logs ⁽¹⁾ .
	with smoke control area kit JCAP0501.	
Parkray Chevin 5 Inset stove. Manufactured by Hunter Stoves Ltd., Trevilla Park, Slaughterbridge, Camelford, Cornwall, PL32 9TT.	Instruction manual reference "JINCHI05 Rev B" dated 10th October 2012. The valve plate adjusted by the secondary air control must contain six 5mm holes.	Wood logs ⁽¹⁾ .
Parkray Consort 4 multifuel stove	Installation and operating instructions reference	Wood logs ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Manufactured by Parkray	"JINCNS04 RevB" dated 20th	
Limited,	June 2014.	
Trevilla Park,	The appliance must be fitted with a modified top air plate	
Slaughterbridge,	with an additional 9 x 5mm holes, and the tertiary air	
Camelford,	aperture permanently fixed to the 60% open position.	
Cornwall,		
PL32 9TT		
Parkray Consort 5.	Instruction manual reference "JINCND05 revC" dated	Wood logs ⁽¹⁾ .
Manufactured by Hunter	22nd September 2011 and	
Stoves Ltd., Trevilla Park,	"JINCND05&CNC05 Slider	
Slaughterbridge, Camelford, Cornwall, PL32 9TT.	Stop revA" dated 22nd July 2011.	
	The appliance must be fitted with a permanent stop that prevents closure of the secondary air slider beyond 30% open.	
Parkray Consort 5 Compact.	Instruction manual reference "JINCNC05 revC" dated	Wood logs ⁽¹⁾ .
Manufactured by Hunter Stoves Ltd., Trevilla Park, Slaughterbridge, Camelford, Cornwall, PL32 9TT.	22nd September 2011 and "JINCND05&CNC05 Slider Stop revA" dated 22nd July 2011.	
	The appliance must be fitted with a permanent stop that prevents closure of the secondary air slider beyond 30% open.	
Parkray Consort 5 Slimline.	Instruction manual reference "JINHHW05 revC" dated 22nd	Wood logs (1).
Manufactured by Hunter Stoves Ltd., Trevilla Park, Slaughterbridge, Camelford, Cornwall, PL32 9TT.	September 2011.	
Colliwall, FL32 911.		

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Parkray Consort 7. Manufactured by Hunter Stoves Ltd., Trevilla Park, Slaughterbridge, Camelford, Cornwall, PL32 9TT.	Instruction manual reference "JNCS07 revC" dated 22nd September 2011.	
Parkray Consort Inset 5 CBC 4.7kW wood-burning inset stove.	Installation and Operating Instructions dated 30/06/2015 reference "JINPCB04 RevB"	Wood logs ⁽¹⁾ .
Manufactured by Hunter Stoves Ltd, Trevilla Park, Slaughterbridge, Camelford, Cornwall, PL32 9TT		
Parkray Consort slimline 9.	Instruction manual reference "JINCSS09 revC" dated 14th	Wood logs ⁽¹⁾ .
Manufactured by Hunter Stoves Ltd., Trevilla Park, Slaughterbridge, Camelford, Cornwall, PL32 9TT.	December 2012.	
Parkray Derwent 5 multifuel stove	Installation and operating instructions reference "JINDER05 RevB" dated 20th	Wood logs ⁽¹⁾ .
Manufactured by Parkray Limited,	June 2014.	
Unit 6,	The appliance must be fitted with a modified top air plate with an additional 8 x 5mm	
Old Mill Industrial Estate,	holes.	
Exeter,		
EX5 4RJ		
Parkray Inset Chevin 8 multi- fuel inset stove.	Installation and operating instructions manual reference "JINCHI08 Rev B" dated	Wood logs ⁽¹⁾ .
Manufactured by Hunter Stoves Limited, Trevilla Park, Slaughterbridge, Camelford,	7th February 2013 and modification instructions reference "JINCH108 Slider Stop Rev B" dated 25th	
Cornwall, PL32 9TT.	September 2013.	regult of treatment with wood process tives

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications: The appliance must be fitted with a mechanical stop to prevent secondary air control closure beyond the 20% open position.	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Passat Energy HO180 199kW boiler manufactured by Passat Energy A/S, Vestergade 36, Ørum, 8830 Tjele, Denmark	User's guide dated 11th May 2015 reference "HO User Guide C004_EN Revision date: 14/07/2015". "HO Maintenance Description Automatic Solid Fuel Boiler dated 18th February 2013 Version C002_EN Revision date 14th July 2015	Wood Chip & Wood Pellets ⁽¹⁾ .
Passat Energy HO250 249kW boiler. Manufactured by Passat Energy A/S, Vestergade 36, Ørum, 8830 Tjele, Denmark	User's guide dated 11th May 2015 reference "HO User Guide C004_EN Revision date: 14/07/2015". "HO Maintenance Description Automatic Solid Fuel Boiler dated 18th February 2013 Version C002_EN Revision date 14th July 2015	Wood Pellets ⁽¹⁾ .
Passat Energy HO300 300kW boiler. Manufactured by Passat Energy A/S, Vestergade 36, Ørum, 8830 Tjele, Denmark	User's guide dated 11th May 2015 reference "HO User Guide C004_EN Revision date: 14/07/2015". "HO Maintenance Description Automatic Solid Fuel Boiler dated 18th February 2013 Version C002_EN Revision date 14th July 2015	Wood Pellets ⁽¹⁾ .
Passat Energy HO420 501kW boiler. Manufactured by Passat Energy A/S, Vestergade 36, Ørum, 8830 Tjele, Denmark	User's guide dated 11th May 2015 reference "HO User Guide C004_EN Revision date: 14/07/2015". "HO Maintenance Description Automatic Solid Fuel Boiler dated 18th February 2013 Version C002_EN Revision date 14th July 2015	Wood Pellets ⁽¹⁾ .
Passat Energy HO510 595kW boiler.	User's guide dated 11th May 2015 reference "HO User	Wood Pellets ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
Manufactured by Passat Energy A/S, Vestergade 36, Ørum, 8830 Tjele, Denmark	The fireplace must be installed, maintained and operated in accordance with the following specifications: Guide C004_EN Revision date: 14/07/2015". "HO Maintenance Description Automatic Solid Fuel Boiler dated 18th February 2013 Version C002_EN Revision date 14th July 2015	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Passat Energy HO680 790kW boiler. Manufactured by Passat Energy A/S, Vestergade 36, Ørum, 8830 Tjele, Denmark	User's guide dated 11th May 2015 reference "HO User Guide C004_EN Revision date: 14/07/2015". "HO Maintenance Description Automatic Solid Fuel Boiler dated 18th February 2013 Version C002_EN Revision date 14th July 2015	Wood Pellets ⁽¹⁾ .
Passat Energy HO850 990kW boiler. Manufactured by Passat Energy A/S, Vestergade 36, Ørum, 8830 Tjele, Denmark	User's guide dated 11th May 2015 reference "HO User Guide C004_EN Revision date: 14/07/2015". "HO Maintenance Description Automatic Solid Fuel Boiler dated 18th February 2013 Version C002_EN Revision date 14th July 2015	Wood Pellets ⁽¹⁾ .
PCE 50 500kW wood chip boiler. Manufactured by Groupe Compte, R, Zl de Vaureil, F – 63220 Arlanc, France.	Instruction manual reference "PCE50 rev00" dated 29th January 2013.	Wood chips ⁽¹⁾ .
PCE 70 700kW wood chip boiler. Manufactured by Groupe Compte, R, Zl de Vaureil, F – 63220 Arlanc, France.	Instruction manual reference "PCE70 rev00" dated 29th January 2013.	Wood chips ⁽¹⁾ .
PCE 90 900kW wood chip boiler. Manufactured by Groupe Compte, R, Zl de Vaureil, F – 63220 Arlanc, France.	Instruction manual reference "PCE90 rev00" dated 29th January 2013.	Wood chips ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
PCE 120 1200kW wood chip boiler.	Instruction manual reference "PCE120 rev00" dated 29th January 2013.	Wood chips (1).
Manufactured by Groupe Compte, R, Zl de Vaureil, F – 63220 Arlanc, France.	January 2013.	
PCE 150 1500kW boiler.	Instruction manual reference "PCE150 rev00" dated 29th	Wood chips (1).
Manufactured by Groupe Compte, R, Zl de Vaureil, F – 63220 Arlanc, France.	January 2013.	
Pelle 5kW stove, Vidar Small 5kW stove and Vidar Medium 7.6kW stove.	Instruction manual reference "8900009004" dated July 2011.	Dry wood logs ⁽¹⁾ .
Manufactured by Dik Geurts Haardkachels BV, Industrieweg Oost 11, 6662 NE Elst (Gld), the Netherlands.		
Pelletmaster PM15, 15kW wood pellet boiler.	Manufacturer's operating instructions reference "HDG Pelletmaster Version V1" dated	Wood pellets ⁽¹⁾ .
Manufactured by HDG Bavaria Gesellschaft mit beschränkter Haftung (GmbH), Siemensstrasse 22, 84323 Massing, Germany.	October 2006.	
Pelletstar 10, 20, 30, 45 and 60.	Manufacturer's operating instructions reference "V2.2" dated November 2007.	Wood pellets corresponding to ÖNORM M7135 of 6mm
Manufactured by HERZ Armaturen Ges.m.b.H, Richard-Strauss-Straße 22,	dated November 2007.	diameter ⁽¹⁾ .
A-1230 Wien, Austria.		
PelletTop 15 and PelletTop 25 Boiler.	Installation instructions reference "Version 020905" dated 2nd September 2005 and	Wood pellets ⁽¹⁾ .
Manufactured by Solarfocus Ltd., Werkstrasse 1, 4451 St.Ulrich, Steyr, Austria.	operating manual reference "Version 270906" dated 27th September 2006.	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Pellettop 35, Pellettop 49 and	Operating manual dated August 2012 reference	Wood pellets ⁽¹⁾ .
Pellettop 70 wood pellet boilers.	"pellettop_operating_manual_2	01209v1".
Manufactured by SOLARFOCUS GmbH, Werkstrasse 1, 4451 St.Ulrich, Steyr, Austria.		
Pellux 100/20 20kW wood pellet boiler.	Installation & Operating Manual Dated '2015-02-24' Reference '24148'	wood pellets ⁽¹⁾ .
Manufactured by NIBE Energy System Ltd, Unit 3c, Broom Bank Business Park, Bridge Way, Chesterfield, Chesterfield, S41 9QG		
Pellux 100/30 30kW wood pellet boiler.	Installation & Operating Manual Dated '2015-02-24' Reference '24148'	wood pellets ⁽¹⁾ .
Manufactured by NIBE Energy System Ltd, Unit 3c, Broom Bank Business Park, Bridge Way, Chesterfield, Chesterfield, S41 9QG		
Penman Heritage 100M, Mode 100M, Heritage 200M and Mode 200M multifuel stoves.	Installation and operating instructions manual reference "Her/Mod M&W Version 1" dated May 2013.	Wood logs ⁽¹⁾ .
Manufactured by Capital Fireplaces Ltd., 12-17 Henlow Trading Estate, Henlow Camp, Hitchin, SG16 6DS.	The appliance must be fitted with the manufacturer's smoke control kit.	
Penman Heritage 100W and Mode 100W wood-burning stoves.	Installation and operating instructions manual reference "Her/Mod M&W Version 1" dated May 2013.	Wood logs ⁽¹⁾ .
Manufactured by Capital Fireplaces Ltd., 12-17 Henlow Trading Estate, Henlow Camp, Hitchin, SG16 6DS.	·	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fiventage	Conditions	
Class of fireplace	Conditions The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Penman Heritage 200W and Mode 200W wood-burning stoves.	Installation and operating instructions manual reference "Her/Mod M&W Version 1" dated May 2013.	Wood logs ⁽¹⁾ .
Manufactured by Capital Fireplaces Ltd., 12-17 Henlow Trading Estate, Henlow Camp, Hitchin, SG16 6DS.	The appliance must be fitted with the manufacturer's smoke control kit.	
Percy Doughty Vega 450 Qube 4.5kW multifuel stove. Manufactured by F.E.	Instruction manual dated 28 July 2015 reference "Qube 450/Vega 450 Qube Solid Fuel Stoves Manual Version 1.1	Wood logs ⁽¹⁾ .
Robinson (Hooton) Ltd, Station Works, Hooton Road, Hooton, South Wirral, CH66 7NF	Issued 28/07/2015"	
Pevex 60 convector stove.	Instruction manual reference	Wood logs ⁽¹⁾ .
Manufactured by Pevex Enterprises Ltd., Unit 16, Seven Acres Business	"Pevex1016/AH/ver1" dated January 2013.	
Park, Newbourne Road, Waldringfield, Nr Woodbridge, IP12 4PS.	The appliance must be fitted with a permanent stop to the secondary air supply to prevent the slider from being closed beyond the 40% open position. The tertiary air supply must remain 100% open.	
Pevex Bohemia X30,X40, X40 Cube, X50 and X60 multifuel stoves.	Manufacturer's instruction manual reference "AH/Ver3" dated July 2010.	Dry wood logs ⁽¹⁾ .
Manufactured by Pevex Enterprises Ltd., Unit 16, Seven Acres Business Park, Newbourne Road, Waldringfield, Nr Woodbridge, IP12 4PS.		
Pevex Bohemia X40 Inset multi-fuel appliance. Manufactured by Pevex	Instruction manual reference "Pevex1004/AH/ver2/" dated June 2011.	Dry wood logs ⁽¹⁾ .
Enterprises Ltd., Unit 16,		

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Seven Acres Business Park, Newbourne Road, Waldringfield, Nr Woodbridge, IP12 4PS.	The appliance must be fitted with permanent stops that ensure the primary and tertiary air controls do not close beyond 0.5cm open and 2cm open positions respectively.	
Pevex Serenity 40D inset multi-fuel appliance.	Instruction manual reference "Pevex1003/AH/ver2" dated June 2011.	Dry wood logs ⁽¹⁾ .
Manufactured by Pevex Enterprises Ltd., Unit 16, Seven Acres Business Park, Newbourne Road, Waldringfield, Nr Woodbridge, IP12 4PS.	The appliance must be fitted with permanent stops that ensure the secondary and tertiary air controls do not close beyond 1.1cm open and 2cm open positions respectively.	
Piazzetta MC 65/60 SL 11kW wood-burning inset roomheater with liftable door. Manufactured by Gruppo	Instructions for installation, use and maintenance dated 1st December 2015 reference "H072141UK0 / DT2001679 - Rev. 03_om"	Wood logs ⁽¹⁾ .
Piazzetta S.p.A, Via Montello, 22, 31011 Casella d'Asolo (TV), Italy	The appliance must be fitted with a permanent stop to prevent closure of the secondary air control beyond 10mm open	
Piazzetta MC 65/60 11kW wood-burning inset roomheater. Manufactured by Gruppo	Instructions for installation, use and maintenance dated 1st December 2015 reference "H072140UK0 / DT2002645 - Rev. 04_om"	Wood logs ⁽¹⁾ .
Piazzetta S.p.A, Via Montello, 22, 31011 Casella d'Asolo (TV), Italy	The appliance must be fitted with a permanent stop to prevent closure of the secondary air control beyond 10mm open	
Piazzetta MC 80/64 BL 11kW wood-burning inset roomheater with swivel door.	Instructions for installation, use and maintenance dated 1st December 2015	Wood logs ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
Manufactured by Gruppo	The fireplace must be installed, maintained and operated in accordance with the following specifications: reference "DT2002877/	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Piazzetta S.p.A, Via Montello, 22, 31011 Casella d'Asolo	H072168UK0_01_om"	
(TV), Italy	The appliance must be fitted with a permanent stop to prevent closure of the secondary air control beyond 10mm open	
PONAST KP 12S, KP 22S, KP 52S and KP 62S automatic pellet boilers. Manufactured by PONAST spol. s r. o., Na Potůčkách 163, Valašské Meziříčí, 757 01, Czech Republic.	Automatic boiler service and operation manual reference "Version 1.1" dated 29th July 2013.	Wood pellets ⁽¹⁾ .
Portway 1. Manufactured by BFM Europe	Instruction manual reference "Solid Fuel Stoves Manual issued - 20/08/2009 (291)	Wood logs ⁽¹⁾ .
Ltd., Trentham Lakes, Stoke on Trent, Staffordshire, ST4 4TJ.	2"dated 20th August 2009. The appliance must be used with a modification to the secondary air slide which inhibits closure further than the 25mm from the left position.	
Portway 2; Portway 3. Manufactured by BFM Europe Ltd., Trentham Lakes, Stoke on Trent, Staffordshire, ST4	Instruction manual reference "Solid Fuel Stoves Manual issued - 20/08/2009 (291) 2" dated 20th August 2009.	Wood logs ⁽¹⁾ .
4TJ.	The appliance must be used with a modification to the secondary air slide which inhibits closure further than the 20mm from the left position.	
Portway Deepwood No 2. Manufactured by BFM Europe Limited, Gordon Banks Drive, Trentham Lakes North, Stoke-	Instruction manual reference "Portway solid fuel heating stoves wood burning models. Wood Fuel Stoves Manual v1" and "Soliftec Smoke Advice	Wood logs ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications: All appliances will be fitted	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
	with a mechanical stop to prevent closure beyond the 7mm closed position on the secondary air control.	
Portway Inset. Manufactured by BFM Europe Ltd., Trentham Lakes, Stoke on Trent, Staffordshire, ST4	Instruction manual reference "Solid Fuel Stoves Manual issued - 20/08/2009 (291) 2" dated 20th August 2009.	Wood logs ⁽¹⁾ .
4TJ.	The secondary air control must be modified such that the 20mm from left position is maintained during use. The primary air control must also be modified such that the minimum setting allows a bleed of air to pass through.	
Potterton Commercial BBS 199 199kW wood pellet boiler when fitted with a WVT multi- cyclone MK02.	Instruction manual reference "Rev 1.1" dated July 2013.	Wood pellets ⁽¹⁾ .
Manufactured by WVT - Wirtschaftliche Verbrennungs- Technik GmbH		
Bahnhofstrasse 55-59, D-51491 Overath- Untereschbach, Germany.		
Pyroclassic IV.	Instruction manual reference "PYROS 04" dated August	Wood logs ⁽¹⁾ .
Manufactured by Pyroclassic Fires Ltd., PO Box 28150, Havelock North 4157,	2011.	
Hawke Bay, New Zealand.		
PZ 65 RL and PZ 100 RL pellet boilers.	Instruction manual reference "Assembly instruction — Instruction manual – servicing	Wood pellets ⁽¹⁾ .
Manufactured by Biotech Energietechnik GmbH, Furtmühlstrasse 32, A-5101,	& cleaning PZ65RL/PZ100RL/PZ101RL" reference	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
Bergheim bei Salzburg,	The fireplace must be installed, maintained and operated in accordance with the following specifications: "BTMoBeWe ENG" dated July	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Austria.	2012.	
Quadra-Fire 2100 Millennium Freestanding Wood Burning Stove.	Manufacturer's instructions reference "250-6931B" dated 9th October 2003.	Dry cured untreated wood of maximum size 38.1 cm x 10.16 cm x 5.08 cm ⁽¹⁾ .
Manufactured by Hearth & Home Technologies, 1445 North Highway, Colville, WA 99114, USA.		
Quadra-Fire Cumberland Gap Freestanding Wood Burning Stove.	Manufacturer's instructions reference "7006-186" dated 8th July 2003.	Dry cured untreated wood of maximum size 43.18 cm x 10.16 cm x 5.08 cm ⁽¹⁾ .
Manufactured by Hearth & Home Technologies, 1445 North Highway, Colville, WA 99114, USA.		
Quadra-Fire Yosemite Freestanding Wood Burning Stove.	Manufacturer's instructions reference "7004-187" dated 4th June 2003.	Dry cured untreated wood of maximum size 38.1 cm x 10.16 cm x 5.08 cm ⁽¹⁾ .
Manufactured by Hearth & Home Technologies, 1445 North Highway, Colville, WA 99114, USA.		
Rais 2:1 inset stove.	Instruction manual reference "USER MANUAL Rais 2:1	Wood logs ⁽¹⁾ .
Manufactured by Rais A/S, Industrivej 20, 9900, Frederikshavn, Denmark.	Revision 2" dated December 2009. Part number 9106510.	
Rais 500, 500-1G, 500-1SG, 500-2G, 500-2SG, 500-3G, & 500-3SG Woodburning stove.	Instruction manual references "Instructions for installation, use and maintenance Rais 500 Revision 5" dated January	Wood logs ⁽¹⁾ .
Manufactured by Rais A/S, Industrivej 20, 9900,	2014.	
Frederikshavn, Denmark.	The appliance must be fitted with a mechanical stop to prevent secondary air control closure beyond the 15% open position.	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
Class of fireplace	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Rais 700 inset stove. Manufactured by Rais A/ S, Industrivej 20, 9900, Frederikshavn, Denmark.	Instruction manual reference "USER MANUAL Rais 700 Revision 0" dated 2010.	Wood logs ⁽¹⁾ .
Rais 900 woodburning stove. Manufactured by Rais A/ S, Industrivej 20, 9900, Frederikshavn, Denmark.	Instruction manual reference "Instructions for installation, use and maintenance Rais 900 Revision 1" dated January 2014. The appliance must be fitted with a mechanical stop to prevent secondary air control closure beyond the 5% open position.	Wood logs ⁽¹⁾ .
Rais Bionic woodburning stove. Manufactured by Rais A/ S, Industrivej 20, 9900, Frederikshavn, Denmark.	Instruction manual references "Instructions for installation, use and maintenance Rais Bionic Fire Revision 1" dated January 2014.	Wood logs ⁽¹⁾ .
Rais Epoca, Rais Poleo 95 and Rais Poleo 106 stoves. Manufactured by Rais A/ S, Industrivej 20, 9900, Frederikshavn, Denmark.	Instruction manual reference "User Manual Rais Poleo 95 & Rais Poleo 106 Rais Epoca Revision 1" dated December 2009. Part number 2106510.	Wood logs ⁽¹⁾ .
Rais Epoca II, Rais Poleo II 106 SST & Rais Poleo II 128 SST woodburning stoves. Manufactured by Rais A/ S, Industrivej 20, 9900, Frederikshavn, Denmark.	Instruction manual reference "Instructions for installation, use and maintenance Rais Poleo 2 & Rais Epoca 2 Revision 1" dated January 2014. The appliance must be fitted with a mechanical stop to	Wood logs ⁽¹⁾ .
Rais Juno & Rais Juno G Woodburning stoves.	prevent secondary air control closure beyond the 30% open position. Instruction manual reference "Instructions for installation, use and maintenance Rais	Wood logs ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
Manufactured by Rais A/S, Industrivej 20, 9900, Frederikshavn, Denmark.	The fireplace must be installed, maintained and operated in accordance with the following specifications: Rina, Rais Viva & Rais Juno Rev 6" dated January 2014. The appliance must be fitted with a mechanical stop to prevent closure of the air damper beyond the 8.5 mm open position.	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Rais Pilar 13L & 13H Wood Burning Stoves. Manufactured by Rais A/ S, Industrivej 20, 9900, Frederikshavn, Denmark.	Instruction manual reference "Instructions for installation, use and maintenance Rais Pilar 13 L & Pilar 13 H Revision 2" dated January 2014.	Wood logs ⁽¹⁾ .
Rais Q-Be 5.9kW wood- burning stove Manufactured by Rais A/ S Industrivej 20, 9900, Frederikshavn, Denmark	Instruction for installation use and maintenance Rais Q-Be dated April 2015 reference "Revision 1". The appliances must be modified to provide a minimum open area of 554mm² in the secondary air control and 143mm2 in the tertiary air control.	Wood logs ⁽¹⁾ .
Rais Q-Tee II woodburning stove. Manufactured by Rais A/S, Industrivej 20, 9900, Frederikshavn, Denmark.	Instruction manual reference "Instructions for installation, use and maintenance Rais Q-Tee 2 Revision 1" dated January 2014. The appliance must be fitted with a mechanical stop to prevent secondary air control closure beyond the 48% open position.	Wood logs ⁽¹⁾ .
Rais Q-Tee 57, 65 and 85. Manufactured by Rais A/ S Industrivej 20, 9900, Frederikshavn, Denmark.	Instruction manual reference "Manual for Rais Q-Tee Revision 1" dated 28th June 2011 and supplementary instructions reference "Rais Q-Tee" dated 7th July 2011.	Dry wood logs ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
	The appliance must be fitted with a mechanical stop to prevent air control closure beyond the 11.7mm open position.	
Rais Q-Tee Wall 57, Rais Q-Tee Wall 65 and Rais Q-Tee Inset. Manufactured by Rais A/S, Industrivej 20, 9900, Frederikshavn, Denmark.	Instruction manual reference "Manual for Rais Q-Tee Revision 2" dated 7th December 2012 and supplementary instructions reference "Supplementary Instructions Rais Rev.3" dated 31st January 2013.	Dry wood logs ⁽¹⁾ .
	The appliance must be fitted with a mechanical stop to prevent air control closure beyond the 11.7mm open position.	
Rais Rondo 92 and Rais Rondo 120 stoves. Manufactured by Rais A/ S, Industrivej 20, 9900, Frederikshavn, Denmark.	Instruction manual reference "User Manual Rais Rondo 92 & Rais Rondo 120 revision 2" dated December 2009. Part number 4076510.	Wood logs ⁽¹⁾ .
Rais Rondo Classic and Rais Mino II stoves. Manufactured by Rais A/	Instruction manual reference "User Manual Rais Rondo & Rais Mino II revision 2" dated March 2008. Part number	Wood logs ⁽¹⁾ .
S, Industrivej 20, 9900, Frederikshavn, Denmark.	5056510.	
Rais Visio 2 wood-burning stove and Rais Visio 3 7kW wood-burning stoves.	Instruction for installation use and maintenance Visio 2 & Visio 3 dated June 2015 reference "Rev 2a".	Wood logs ⁽¹⁾ .
Manufactured by Rais A/S Industrivej 20, 9900, Frederikshavn, Denmark	The appliances must be modified to provide a minimum open area of 300mm ² in the secondary air control and 93mm ² in the tertiary air control.	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Rais Viva 4.6 kW wood- burning stoves models 98, 98G, 120, 120G, 98 Classic, 98G Classic, 120 Classic and 120G Classic.	Instruction for installation use and maintenance Rais Rina, Rais Viva & Rais Juno including Classic Models dated June 2015 reference "Issue 7a"	Wood logs ⁽¹⁾ .
Rais Rina 4.6 kW wood-burning stove.	The appliances must be fitted with a mechanical stop to	
Rais Rina 4.6 kW wood- burning stoves models 90, 90 Classic, SST, SST Classic	prevent closure of the air damper beyond the 8.5 mm open position.	
Rais Juno 4.6 kW woodburning stove.		
Rais Juno 4.6 kW wood- burning stoves models G, 120 Classic, G 120 Classic, 1560 Classic, G 1560 Classic, 1930 Classic, G 1930 Classic.		
Manufactured by Rais A/ S Industrivej 20, 9900, Frederikshavn, Denmark		
Rais Viva 98, Rais Viva 98G, Rais Viva 120, Rais Viva 120G and Rais Rina 90 wood burning stoves. Manufactured by Rais A/ S, Industrivej 20, 9900, Frederikshavn, Denmark.	Instruction manual reference "Manual for Rais Rina, Rais Viva" dated 29th August 2011 and instruction manual reference "Supplementary Instructions Rais" dated 27th September 2011.	Wood logs ⁽¹⁾ .
i reactivistavii, Defiliativ.	The appliance must be fitted with a mechanical stop to prevent closure of the air damper beyond the 8.5mm open position.	
Red Compact 14 wood pellet boiler.	Instruction manual reference "8901310800 Revision 0" dated 19th December 2013.	Wood pellets (1).
Manufactured by MCZ GROUP SpA, Via La Croce,		

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
8 Vigonovo di Fontanafredda (PN) Italy, 33074.		
Red Compact 18 and Red Compact 24 wood pellet boilers.	Instruction manual reference "8901232500 Revision 2" dated 8th January 2014.	Wood pellets ⁽¹⁾ .
Manufactured by MCZ GROUP SpA, Via La Croce, 8 Vigonovo di Fontanafredda (PN) Italy, 33074.		
Red Compact 35 wood pellet boiler.	Instruction manual reference "8901238400 Revision 1" dated 8th January 2014.	Wood pellets ⁽¹⁾ .
Manufactured by MCZ GROUP SpA, Via La Croce, 8 Vigonovo di Fontanafredda (PN) Italy, 33074.	dated offi January 2014.	
Redfyre Kensal 20 flat top (product code RF-EN20M), Redfyre Kensal 33 flat top (product code RF-KEN33M and RF-KEN33W).	Manufacturer's instruction manual reference "PM247 issue 1" dated July 2008 and instruction manual reference "PM280 issue 1" dated January 2009.	Untreated dry wood ⁽¹⁾ .
Manufactured by Redfyre Cookers, Osprey Road, Sowton Industrial Estate, Exeter, Devon, EX2 7JG.	The appliance must be fitted with a permanent stop on the secondary air inlet to prevent closure beyond the 50% open position.	
Rika Como pellet stove.	Instruction manual reference "IN1226 Edition 1" dated June	6 mm wood pellets ⁽¹⁾ .
Manufactured by RIKA Innovative Ofentechnik GmbH Müllerviertel 20 AT - 4563 Micheldorf, Austria.	2011.	
Rika Evo Aqua 9 and 15.	Instruction manual reference "J18/HB" dated 27th February	6mm wood pellets ⁽¹⁾ .
Manufactured by SHT Heiztechnik aus Salzburg GmbH, Rechtes Salzachufer 40 A-5101, Salzburg-Bergheim, Austria.	2009.	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Rika Memo pellet stove.	Instruction manual reference "IN1228 Edition 1" dated June	6 mm wood pellets ⁽¹⁾ .
Manufactured by RIKA Innovative Ofentechnik GmbH Müllerviertel 20 AT - 4563 Micheldorf, Austria.	2011.	
Rika Pico pellet stove.	Instruction manual reference "IN1230 Edition 1" dated June	6 mm wood pellets ⁽¹⁾ .
Manufactured by RIKA Innovative Ofentechnik GmbH Müllerviertel 20 AT - 4563 Micheldorf, Austria.	2011.	
Rika Revo pellet stove.	Instruction manual reference "IN1229 Edition 1" dated June	6 mm wood pellets ⁽¹⁾ .
Manufactured by RIKA Innovative Ofentechnik GmbH Müllerviertel 20 AT - 4563 Micheldorf, Austria.	2011.	
Rika Tema 6kW stove.	Instruction manual reference "IN1218 Edition 2" dated	Wood logs ⁽¹⁾ .
Manufactured by RIKA Innovative Ofentechnik GmbH, Müllerviertel 20, AT - 4563 Micheldorf, Austria.	January 2012.	
Rika Topo pellet stove.	Instruction manual reference "IN1227 Edition 1" dated June	6 mm wood pellets ⁽¹⁾ .
Manufactured by RIKA Innovative Ofentechnik GmbH Müllerviertel 20 AT - 4563 Micheldorf, Austria.	2011.	
Riva 40 Cassette 4.9kW stoves.	Instruction manual reference "PM235 Issue 2" dated August 2009 and smoke control kit	Wood logs ⁽¹⁾ .
Manufactured by Stovax Ltd., Falcon Road, Sowton Industrial Estate, Exeter, Devon, EX2 7LF.	instruction manual reference "PM375 Issue 2" dated January 2010.	
	The appliance must be fitted with a permanent stop to prevent closure of the secondary air control below the 50% open position.	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Riva 40 Freestanding, Riva 40 Avanti, Riva 40 Avanti Midi, And Riva 40 Avanti Highline 4.9kW stoves. Manufactured by Stovax Ltd., Falcon Road, Sowton Industrial Estate, Exeter, Devon, EX2 7LF.	Instruction manual reference "PM226 Issue 2" dated August 2009 and smoke control kit instruction manual reference "PM375 Issue 2" dated January 2010. The appliance must be fitted with a permanent stop to prevent closure of the secondary air control below the 50% open position.	Wood logs ⁽¹⁾ .
Riva 45 Cassette (model numbers RV45 & RV45B) wood burning stoves. Manufactured by Stovax Ltd., Falcon Road, Sowton Industrial Estate, Exeter, Devon, EX2 7LF.	Instruction manual reference "PM375 Issue 5" dated June 2012 and instruction manual reference "PM235 Issue 5" dated June 2012. The appliance must be fitted with a permanent stop	Wood logs ⁽¹⁾ .
20,011, 212, 721.	to prevent closure of the secondary air control below the 50% open position.	
Riva 50 Cassette (model numbers RV50 & RV50B) wood burning stoves. Manufactured by Stovax Ltd.,	Instruction manual reference "PM375 Issue 5" dated June 2012 and instruction manual reference "PM235 Issue 5" dated June 2012.	Wood logs ⁽¹⁾ .
Falcon Road, Sowton Industrial Estate, Exeter, Devon, EX2 7LF.	The appliance must be fitted with a permanent stop to prevent closure of the secondary air control below the 50% open position and the primary air control fixed to allow a bleed of air to enter the firebox from underneath the grate.	
Riva 55 Cassette, Riva 66 Cassette, and Riva 66 Avanti Cassette stoves. Manufactured by Stovax	Instruction manual reference "PM235 Issue 2" dated August 2009 and smoke control kit instruction manual reference "PM375 Issue 2" dated	Wood logs ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
Industrial Estate, Exeter, Devon, EX2 7LF.	The fireplace must be installed, maintained and operated in accordance with the following specifications: The appliance must be fitted with a permanent stop	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
	to prevent closure of the secondary air control below the 50% open position and the primary air control fixed to allow a bleed of air to enter the firebox from underneath the grate.	
Riva 55 Avanti Midi and Riva 66 Freestanding 8kW stoves. Manufactured by Stovax Ltd; Falcon Road, Sowton Industrial Estate, Exeter,	Instruction manual reference "PM226 Issue 2" dated August 2009 and smoke control kit instruction manual reference "PM375 Issue 2" dated January 2010.	Wood logs ⁽¹⁾ .
Devon, EX2 7LF.	The appliance must be fitted with a permanent stop to prevent closure of the secondary air control below the 50% open position and the primary air control fixed to allow a bleed of air to enter the firebox from underneath the grate.	
Riva Plus Small (5kW), Riva Plus Midi (6.5kW) and Riva Plus Medium (8kW) stoves. Manufactured by Stovax Ltd., Falcon Road, Sowton Industrial Estate, Exeter,	Instruction manual reference "PM231 Issue 3" dated June 2009 and smoke control kit instruction manual reference "PM402 Issue 1" dated November 2009.	Wood logs ⁽¹⁾ .
Devon, EX2 7LF.	The appliance must be fitted with a permanent stop to prevent closure of the secondary air control below the 25% open position.	
Riva Studio 1 (5kW) freestanding wood stove. Manufactured by Stovax Ltd., Falcon Road, Sowton Industrial Estate, Exeter, Devon, EX2 7LF.	Instruction manual reference "PM452 Issue 1" dated June 2010 and smoke control kit instruction manual reference "PM400 Issue 3" dated June 2010.	Wood logs ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

G1 00 1	~	
Class of fireplace	The fireplace must be installed, maintained and operated in accordance with the following specifications: The appliance must be fitted with a permanent stop to prevent closure of the secondary air control below the 45% open position and the primary air control fixed to prevent full closure to allow a bleed of air to enter the firebox at the base of the fuel bed.	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Riva Studio 2 (8kW) freestanding wood stove. Manufactured by Stovax Ltd., Falcon Road, Sowton Industrial Estate, Exeter, Devon, EX2 7LF.	Instruction manual reference "PM452 Issue 1" dated June 2010 and smoke control kit instruction manual reference "PM400 Issue 3" dated June 2010. The appliance must be fitted with a permanent stop to prevent closure of the secondary air control below the 25% open position and the primary air control fixed to prevent full closure to allow a bleed of air to enter the firebox at the base of the fuel bed.	Wood logs ⁽¹⁾ .
Riva Studio 1 Cassette (5kW). Manufactured by Stovax Ltd., Falcon Road, Sowton Industrial Estate, Exeter, Devon, EX2 7LF.	Instruction manual reference "PM274 Issue 2" dated October 2009 and smoke control kit instruction manual reference "PM400 Issue 1" dated November 2009. The appliance must be fitted with a permanent stop to prevent closure of the secondary air control below the 45% open position and the primary air control fixed to prevent full closure to allow a bleed of air to enter the firebox at the base of the fuel bed.	Wood logs ⁽¹⁾ .
Riva Studio 2 Cassette (8kW).	Instruction manual reference "PM274 Issue 2" dated October 2009 and smoke	Wood logs ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
Manufactured by Stovax Ltd., Falcon Road, Sowton Industrial Estate, Exeter, Devon, EX2 7LF.	The fireplace must be installed, maintained and operated in accordance with the following specifications: control kit instruction manual reference "PM400 Issue 1" dated November 2009.	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
	The appliance must be fitted with a permanent stop to prevent closure of the secondary air control below the 25% open position and the primary air control fixed to prevent full closure to allow a bleed of air to enter the firebox at the base of the fuel bed.	
Riva Studio Cassette 500 RVS-500 Wood Burning Stove. Manufactured by Stovax Ltd.,	Instruction manual reference "PM400 Issue 4" dated October 2012 and instruction manual reference "PM274 Issue 9" dated August 2012.	Wood logs ⁽¹⁾ .
Falcon Road, Sowton Industrial Estate, Exeter, Devon, EX2 7LF.	The appliance must be fitted with Smoke Control Kit RVS500SCKIT to prevent secondary air closure beyond the 50% open position.	
Riva Studio Duplex RVS-2DS Wood Burning Stove. Manufactured by Stovax Ltd., Falcon Road, Sowton Industrial Estate, Exeter, Devon, EX2 7LF.	Instruction manual reference "PM935 Issue 1" dated October 2012 and instruction manual reference "PM904 – Issue 1" dated August 2012. The appliance must be fitted with Smoke Control Kit RVS-2DSSCKIT to prevent secondary air closure beyond the 91mm open position.	Wood logs ⁽¹⁾ .
Riva Studio Freestanding 500 RVFS-500 Wood Burning Stove. Manufactured by Stovax Ltd., Falcon Road, Sowton Industrial Estate, Exeter, Devon, EX2 7LF.	Instruction manual reference "PM400 Issue 4" dated October 2012 and instruction manual reference "PM452 Issue 3" dated August 2012. The appliance must be fitted with Smoke Control Kit RVS500SCKIT to prevent	Wood logs ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

	T ~ 1.	
Class of fireplace	Conditions The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
	secondary air closure beyond the 50% open position.	, J
Riva Vision Small (5kW) – Multifuel; Riva Vision Midi (6.5kW) - Multifuel. Manufactured by Stovax Ltd., Falcon Road, Sowton Industrial Estate, Exeter,	Instruction manual reference "PM278 Issue 2a" dated October 2009 and smoke control kit instruction manual reference "PM401 Issue 1" dated January 2010.	Wood logs ⁽¹⁾ .
Devon, EX2 7LF.	The appliance must be fitted with a permanent stop to prevent closure of the secondary air control below the 50% open position.	
Riva Vision Medium (8kW) – Multifuel.	Instruction manual reference "PM278 Issue 2a" dated October 2009 and smoke	Wood logs ⁽¹⁾ .
Manufactured by Stovax Ltd., Falcon Road, Sowton Industrial Estate, Exeter, Devon, EX2 7LF.	control kit instruction manual reference "PM401 Issue 1" dated January 2010.	
	The appliance must be fitted with a permanent stop to prevent closure of the secondary air control below the 25% open position.	
Robus Black Star 10, 14, 24 and 45 comfort wood pellet boilers.	Instruction manual reference "MCS 0001RE Issue 1" dated May 2013.	Wood pellets ⁽¹⁾ .
Manufactured by OPOP spol s.r.o, Zašovská 750, Valašské Meziříčí, Czech Republic and the pellet burners by NBE Productions A/S, Kjeldgaardsvej 2, 9300 Saeby, Denmark.		
Robus Black Star BS100 105kW and Robus Black Star BS200 196kW wood pellet boilers.	Instruction manual reference "Robus Black Star 100 and 200: Version 1.0" dated September 2014.	Wood pellets ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Conditions	
The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Instruction manual reference "Ready to Burn: Version 1.1: Version 1.0" dated November 2014.	Wood pellets ⁽¹⁾ .
Instruction manual reference "Issue No. 04" dated 11th January 2012	Wood logs ⁽¹⁾ .
The appliance must be fitted with a mechanical stop to	
closure beyond the 30% open position.	
"Rosedale Smoke Control Stove Installation and User Instructions Issue 1" dated 01/05/2010.	Wood logs with a maximum of 20% moisture ⁽¹⁾ .
The appliance must be fitted with a mechanical stop to prevent closure of the secondary air control beyond the 50% open position.	
Technical manual dated 17th February 2015 reference "Document FB3MF 0101 Version 2"	Wood logs ⁽¹⁾ .
	Instruction manual reference "Ready to Burn: Version 1.1: Version 1.0" dated November 2014. Instruction manual reference "Ready to Burn: Version 1.1: Version 1.0" dated November 2014. Instruction manual reference "Issue No. 04" dated 11th January 2012. The appliance must be fitted with a mechanical stop to prevent secondary air control closure beyond the 30% open position. "Rosedale Smoke Control Stove Installation and User Instructions Issue 1" dated 01/05/2010. The appliance must be fitted with a mechanical stop to prevent closure of the secondary air control beyond the 50% open position. Technical manual dated 17th February 2015 reference "Document FB3MF 0101

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
Class of Jureplace	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Works, Weston Lane, Tyseley, Birmingham, B11 3RP	The appliance must be fitted with a mechanical stop to prevent secondary air slider closure beyond the 25mm open position, and the tertiary air control will be fixed in the 50% open position.	
Royal Klima 18 Idro wood pellet stove boiler. Manufactured by Palazzetti Lelio S.p.A, Via Roveredo 103, Porcia (PN), 33080, Italy.	Instruction manual reference "cod. 0047700880" dated September 2011 and supplementary information "Clean Air Act 1993 and Smoke Control Areas" reference "004723000" dated	Wood pellets ⁽¹⁾ .
	January 2012.	
S5i 5kW multifuel inset stove	Operating and Installation Instructions manual dated	Wood logs ⁽¹⁾ .
S5f 5kW multifuel stove	17 July 2015 reference "ST Version 1.0"	
S5l 5kW multifuel stove	, 0.0.0	
G5i 5kW multifuel inset stove		
G5f 5kW multifuel stove		
G5l 5kW multifuel stove		
S9i 9kW multifuel inset stove		
S9f 9kW multifuel stove		
S9l 9kW multifuel stove		
G9i 9kW multifuel inset stove		
G9f 9kW multifuel stove		
G9l 9kW multifuel stove.		
Manufactured by Stovey Limited, Site 1, Cotwall Lane, High Ercall, Telford, Shropshire, TF6 6JD		

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Salamander Hobbit SE stove Model 0901.	Instruction manual reference "Ref 0901SE" dated March 2013.	Wood logs ⁽¹⁾ .
Manufactured by Salamander Stoves Ltd., Cosemount Cottage, Canada Hill, East Ogwell, Newton Abbot, Devon, TQ12 6AF.	The secondary air rotating plate must be modified such that it cannot be closed further than 4mm open.	
	The primary air spin wheel must be modified such that it is fixed at a minimum of 1 half turn open.	
Saltfire Aquaburn 20 Wood Burning Stove. Manufactured by Saltfire Stoves Ltd, Station Works,	Installation and operating instructions reference "Saltfire Aquaburn 20 Boiler Wood Version, Manual Version 1.1" dated 22nd January 2014.	Wood logs ⁽¹⁾ .
Johns Road, Wareham, BH20 4BG.	The appliance must be fitted with a mechanical stop to prevent air wash control closure beyond the 25mm open position and a stop preventing manual primary air control closure beyond the 2mm open position.	
Saltfire Aquaburn 30 Wood Burning Stove. Manufactured by Saltfire Stoves Ltd, Station Works, Johns Road, Wareham, BH20	Installation and operating instructions reference "Saltfire Aquaburn 30 Boiler Wood Version, Manual Version 1.1" dated 22nd January 2014.	Wood logs ⁽¹⁾ .
4BG.	The appliance must be fitted with a mechanical stop to prevent air wash control closure beyond the 30mm open position and a stop preventing manual primary air control closure beyond the 2mm open position.	
Saltfire Double Sided DS1 wood-burning stove.	Installation and operating instructions manual reference "Saltfire Double Sided DS1	Wood logs ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Manufactured by Saltfire Stoves Ltd., Station Works, Johns Road, Wareham, BH20 4BG.	Manual 1.0" dated 4th July 2013. The appliance must be modified so that when the primary and secondary air controls are in the fully closed position they will be fixed at 3.5mm open. A tertiary air control system comprising two 7mm holes on each side of the appliance and a fixed opening of 4 cm ² on the underside of the stove must be implemented.	
Saltfire Ecoview 5, Fireglow Eco 5, and Ecowarm Crystal 5 stoves.	Instruction manual reference "Evoview5 Manual 1.0" dated 15th December 2011.	Wood logs ⁽¹⁾ .
Manufactured by Saltfire Stoves Ltd., Station Works, Johns Road, Wareham, BH20 4BG.	The appliance must be fitted with a mechanical stop to prevent closure of the tertiary air beyond the 4mm open position.	
Saltfire Ecoview 12, Fireglow Eco 12, and Ecowarm Crystal 12 stoves.	Instruction manual reference "Evoview12 Manual 1.0" dated 15th December 2011.	Wood logs ⁽¹⁾ .
Manufactured by Saltfire Stoves Ltd., Station Works, Johns Road, Wareham, BH20 4BG.	The appliance must be fitted with a mechanical stop to prevent closure of the tertiary air beyond the 4mm open position.	
Saltfire Oslo-Eco, Fireglow Eco 7 and Ecowarm Crystal 6. Manufactured by Saltfire Stoves Ltd., Station Works, Johns Road, Wareham, BH20 4BG.	Instruction manual reference "ECO7operation-Revision 2A" dated 24th January 2011.	Wood logs ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Saltfire ST1, Fireglow ST1, & Ultimo ST1 Wood Burning Stove.	Installation and Operating Instructions reference "Saltfire ST1, A.K.A Fireglow ST1, A.K.A. Ultimo ST1, Manual	Wood logs ⁽¹⁾ .
Manufactured by Saltfire Stoves Ltd, Station Works, Johns Road, Wareham, BH20	Version 1.1" dated 22nd January 2014.	
4BG.	The appliance must be fitted with mechanical stop to prevent air wash control closure beyond the 22mm open position and a stop to prevent secondary air control closure beyond the 50% open position.	
Saltfire ST2, Fireglow ST2, & Ultimo ST2 Wood Burning Stove.	Installation and Operating Instructions reference "Saltfire ST2, A.K.A Fireglow ST2, A.K.A. Ultimo ST2, Manual	Wood logs ⁽¹⁾ .
Manufactured by Saltfire Stoves Ltd, Station Works, Johns Road, Wareham, BH20	Version 1.1" dated 22nd January 2014.	
4BG.	The appliance must be fitted with a mechanical stop to prevent air wash control closure beyond the 7mm open position and a stop to prevent tertiary air control closure beyond the 20% open position.	
Saltfire Sturminster Inset wood-burning stove.	Installation and Operating Instruction manual reference "Saltfire Sturminster Manual	Wood logs ⁽¹⁾ .
Manufactured by Saltfire Stoves Ltd., Station Works, Johns Road, Wareham, BH20 4BG.	1.0" dated 4th July 2013.	
San Remo 4SE stove. Manufactured by Heat Design,	Instruction manual reference "SR468SE" dated 25th July 2012.	Wood logs ⁽¹⁾ .
30 Hawthorn Road, Western Industrial Estate, Naas Road, Dublin 12, Ireland.	The appliance must be fitted with a system to prevent closure of the secondary air control beyond 5mm open.	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
San Remo 6SE stove. Manufactured by Heat Design, 30 Hawthorn Road, Western	Instruction manual reference "SR468SE" dated 25th July 2012.	Wood logs ⁽¹⁾ .
Industrial Estate, Naas Road, Dublin 12, Ireland.	The appliance must be fitted with a system to prevent closure of the secondary air control beyond 75% from closed.	
San Remo 8SE stove. Manufactured by Heat Design, 30 Hawthorn Road, Western	Instruction manual reference "SR468SE" dated 25th July 2012.	Wood logs ⁽¹⁾ .
Industrial Estate, Naas Road, Dublin 12, Ireland.	The appliance must be fitted with a system to prevent closure of the secondary air control beyond 25% from closed.	
San Remo SR5i Multi-fuel	Installation and Operating	Wood logs ⁽¹⁾ .
inset stove.	Instruction manual reference "SR5i" dated 2nd May 2013.	
Manufactured by Heat Design Ltd., 30 Hawthorn Road, Western Industrial Estate, Naas Road, Dublin 12, Ireland.	The appliance must be fitted with a mechanical stop to prevent secondary air control closure beyond the 3.5mm open position.	
SASP 1000 675 kW Biomass Boiler when fitted with a multi-cyclone	Instruction manual assembly and operation manual reference "Version TOP/SASP/V.1.1" dated 12th December 2013.	
Manufactured by Topling d.o.o. Magistraini put BB, 78430 Prnjavor. The Republic of Srpska, Bosnia and Herzegovina.		
Scan Anderson 4-5.	Manufacturer's instructions entitled "Scan Andersen 4-5"	Untreated dry wood (1).
	reference "09/05-GB" dated	
Manufactured by Krog Iversen 7 Co., A/S DK-5492 Vissenbjerg, Denmark.	15th November 2007.	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications: secondary air inlet to prevent closure beyond 20mm.	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Scan Andersen 8-2 woodburning 7 kW stove Manufactured by Jøtul A.S, P.O. Box 1411, N-1602 Fredrikstad, Norway.	Installation and operating instructions manual reference "10026402 -P01" dated October 2012 and addendum to installation and operating instructions manual reference "SMOKEA8-2" dated 5th June 2014.	Wood logs ⁽¹⁾ .
	The appliance must be fitted with Smoke control kit SMOKEA8-2 to prevent closure of the air control beyond 25% open.	
Scan 58-1, Scan 58-1 Wall;	Instruction manual reference "GB 90358500-5" dated	Wood logs ⁽¹⁾ .
Scan 58-2, Scan 58-2 Wall;	24th March 2011 and	
Scan 58-3, Scan 58-3 Wall;	supplementary instructions for UK Smoke Control Areas reference "SCAN58SCA"	
Scan 58-4, Scan 58-4 Wall;	dated 1st March 2013.	
Scan 58-5, Scan 58-5 Wall;	The appliance must be fitted with a mechanical stop	
Scan 58-6, Scan 58-6 Wall;	to prevent closure of the	
Scan 58-7, Scan 58-7 High Top;	secondary air control beyond the 1/3rd open position.	
Scan 58-8, Scan 58-8 High Top;		
Scan 58-9, Scan 58-9 High Top;		
Scan 58-10, Scan 58-10 High Top.		
Manufactured by Scan A/S, Glasvænget 3-9, 5492 Vissenbjerg, Denmark.		

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Scan 64-1 - with steel sides, Scan 64-2 - with steel sides and side windows, Scan 64-3 - with sides of natural stones/tiles, Scan 64-4 - with sides of natural stone/tile and side windows, Scan 64-7 - with stainless steel sides, Scan 64-8 - with stainless steel sides and side windows wood burning 6 kW Stoves.	Assembly and Instructions manual dated 24.03.2015 reference "GB 90064500" Fitted with a mechanical stop to prevent secondary air control closure beyond the 59% open position.	Wood logs ⁽¹⁾ .
Manufactured by Scan A/S Glasvænget 3-9 5492 Vissenbjerg,		
Denmark		
Scan 65-1 6kW wood-burning stove with sheet steel panels and top plate	Assembly and Instructions manual dated 21/08/2015 reference "GB 90065500".	Wood logs ⁽¹⁾ .
Scan 65-2 6kW wood-burning stove with side windows Scan 65-3 6kW wood-burning	The appliance must be fitted with a mechanical stop to prevent closure of the secondary air control beyond	
stove Clad with stone slabs Scan 65-4 - 6kW wood- burning stove clad with stone slabs and side windows	the 59% open position	
Scan 65-5 – 6kW wood- burning stove with extended top and baking compartment		

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

83-8 Maxi stove.

Status: This is the original version (as it was originally made). This item of legislation is currently only available in its original format.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Scan 65-6 - 6kW wood- burning stove with extended top and baking compartment and side windows		
Scan 65-7 – 6kW wood- burning stove with high stone clad and extended top		
Scan 65-8 - 6kW wood- burning stove with high stone clad and extended top and side windows		
Scan 65-9 - 6kW wood- burning stove with high sheet steel and extended top		
Scan 65-10 - 6kW wood- burning stove with high sheet steel and extended top and side windows.		
Manufactured by Scan A/ S Glasvænget 3-9 5492 Vissenbjerg, Denmark		
Scan 66-1, 66-3, 66-4 stoves Manufactured by Scan A/ S, Glasvaenget 3-9, 5492 Vissenbjerg, Denmark.	Assembly and instructions manual reference "GB 90066500" dated 27th October 2014.	Wood logs ⁽¹⁾ .
	The appliance must be fitted with a mechanical stop to prevent secondary air control closure beyond the 35mm open position.	
Scan 83-1 stove, Scan 83-2 stove, Scan 83-3 Maxi stove, Scan 83-4 Maxi stove, Scan 83-5 stove, Scan 83-6 stove, Scan 83-7 Maxi stove, Scan	Instruction manual reference "UK 90583500" dated 15th January 2014.	Wood logs ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Manufactured by Scan A/S, Glasvaenget 3-9, 5492 Vissenbjerg, Denmark.		
Scan DSA 7-5 wood-burning Inset roomheater. Manufactured by Scan A/ S, Glasvænget 3-9, 5492 Vissenbjerg, Denmark.	Instruction manual "Instructions for installation and use: SCAN DSA 6 & DSA 7-5" reference "Edition 17.09.2010 – GB", supplement "DSA 7-5 – UK smoke control areas" reference "DSA 7-5 SMOKE" dated 1st January 2012 and instructions for installation (including directions for use and stoking) reference "Edition 05.10.2010 – GB" dated 5th October 2010. The appliance must be fitted with a mechanical stop to prevent closure of the air wash control lever beyond the 50% open position.	Wood logs ⁽¹⁾ .
Scan ILD 7 and ILD 8 wood- burning stoves Manufactured by Color	Instruction manual reference "Manual version. No. 13-1 GB 01.07.13" dated 1st July 2013.	Wood logs ⁽¹⁾ .
Emajl d.o.o. Alaginci 87/a, HR-34000 Pozega, Croatia.	The appliance must be fitted with a permanent stop to fix the secondary air control 7.5% open in the fully closed position.	
Scandian 5MF Traditional, Scandian 5MF Modern, Scandian 8MF Traditional and Scandian 8MF Modern multifuel stoves.	Installation and operating instructions manual reference "Scandian MF&WD Version 1" dated June 2013.	Wood logs ⁽¹⁾ .
Manufactured by Capital Fireplaces Ltd., 12-17 Henlow Trading Estate, Henlow Camp, Hitchin, SG16 6DS.	The appliance must be fitted with the manufacturer's smoke control kit.	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
Class of fireplace	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Scandian 5WD Traditional and Scandian 5WD Modern woodburning stoves.	Installation and operating instructions manual reference "Scandian MF&WD Version 1" dated June 2013.	Wood logs ⁽¹⁾ .
Manufactured by Capital Fireplaces Ltd., 12-17 Henlow Trading Estate, Henlow Camp, Hitchin, SG16 6DS.		
Scandian 8WD Traditional and Scandian 8WD Modern woodburning stoves.	Installation and operating instructions manual reference "Scandian MF&WD Version 1" dated June 2013.	Wood logs ⁽¹⁾ .
Manufactured by Capital Fireplaces Ltd., 12-17 Henlow Trading Estate, Henlow Camp, Hitchin, SG16 6DS.	The appliance must be fitted with the manufacturer's smoke control kit.	
Schmid UTSK 180, 240, 300, 360, 450, 550, 700, 900, 1200, 1600kW.	Manufacturer's instruction manual reference "UTSK- ABC.22-AME-S-PPU" dated 25/09/2008 (where ABC is	Wood pellets or wood chips following CEN/TS 14961:2005 ⁽¹⁾ .
Manufactured by Schmid AG Woodfiring Systems, PO Box 42, CH-8380 Eschikon, Switzerland.	model number i.e. 180, 240, 300, 360, 450, 550, 700, 900, 1200, 1600).	
Schmid UTSL 30, 40, 50, 65, 80, 110, 150kW.	Manufacturer's instruction manual reference "Operating Manual Wooden Chips and	Wood pellets or wood chips following CEN/TS 14961:2005 ⁽¹⁾ .
Manufactured by Schmid AG Woodfiring Systems, PO Box 42, CH-8380 Eschikon, Switzerland.	Pellets Plant. Lignumat UTSL" dated 23rd December 2004.	14901.2003**.
Schmid UTSP 180, 240, 300kW.	Manufacturer's instruction manual reference "UTSK – ABC22-AME-S-PPU" (where	Wood pellets following CEN/ TS 14961:2005 ⁽¹⁾ .
Manufactured by Schmid AG Woodfiring Systems, PO Box 42, CH-8380 Eschikon, Switzerland.	ABC is model number i.e. 180, 240, 300) dated 25th September 2008.	
Schmid UTSR 150, 180, 240, 300, 360, 450, 550, 700, 900kW.	Manufacturer's instruction manual reference "UTSR – ABC22-AME-S-PPV" (where ABC is model number i.e. 150, 180, 240, 300, 360, 450,	Wood pellets or wood chips following CEN/TS 14961:2005 ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Manufactured by Schmid AG Woodfiring Systems, PO Box 42, CH-8380 Eschikon, Switzerland.	550, 700, 900) dated 25th September 2008.	
Schmid UTSR 1200.	Instruction manual reference "60110797.doc" dated 24th	Wood chips and wood pellets
Manufactured by Schmid AG Energy Solutions, PO Box 42, CH-8380 Eschikon, Switzerland.	April 2012.	(b).
Schmid UTSW 900.32.	Instruction manual reference	Wood chips and wood pellets
Manufactured by Schmid AG Woodfiring Systems, PO Box 42, CH-8380 Eschikon, Switzerland.	"Instruction manual. Wood chip furnace with boiler type Schmid Pyrotroine Modular issue 1" dated 7th January 2013 and instruction manual reference "PersonalTouch Version 2010 EVO10 V531\PT_2010_C3." dated 2010.	(1)
Seguin Jade wood-burning stove.	Instruction manual reference "Wood Stoves Manual	Wood logs ⁽¹⁾ .
Manufactured by Groupe Seguin, Cheminees Seguin	Installation – Use 1/1/2013	
Duteriez, Zone Industrielle de Lhérat, 63310 France.	Characteristics of the Stove' dated 1st January 2013.	
	The appliance must be fitted with a permanent stop to prevent closure of the secondary air control beyond the 40% open position.	
Seguin Saphir wood-burning stove.	Instruction manual reference "Wood Stoves Manual	Wood logs ⁽¹⁾ .
Manufactured by Groupe Seguin, Cheminees Seguin	Installation – Use 1/1/2013	
Duteriez, Zone Industrielle de Lhérat, 63310 France.	Characteristics of the Stove" dated 1st January 2013.	
	The appliance must be fitted with a permanent stop	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications: to prevent closure of the	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
	secondary air control beyond the 15mm open position.	
Senza UK w/o sideglass and Senza UK w/ sideglass 5kW wood burning stoves	Instruction manual reference "User's manual Revision 1, 27.11.2014" dated 27th November 2014.	Wood logs ⁽¹⁾ .
Manufactured by Jydepejsen A/S, Ahornsvinget 3-7, Nr. Felding, DK-7500 Holstebro, Denmark.	The appliance must be fitted with a modification to fix the secondary air control to 1300mm ² in its minimum position.	
Serenity 40 FS, Serenity 40 LS and Serenity 40 FW stoves.	Instruction manual reference "Pevex1014/AH/ver1" dated January 2013.	Wood logs ⁽¹⁾ .
Manufactured by Pevex Enterprises Ltd., Unit 16, Seven Acres Business Park, Newbourne Road, Waldringfield, Nr Woodbridge, IP12 4PS.	The appliance must be fitted with permanent stops that ensure the secondary and tertiary air controls do not close beyond 1.1cm open and 2cm open positions respectively.	
Serenity 45, 5.5kW multifuel inset roomheater. Manufactured by Pevex Enterprises Ltd, Unit MP7,	Installation and Operating Instructions for Serenity 45 inset dated June 2015 reference "Pevex1030/AH/ver1"	Wood Logs ⁽¹⁾ .
Kirrawah Business Park, Newbourne Road,	The appliance must be fitted with a permanent stop that ensures the air control cannot	
Nr Woodbridge, IP12 4PR	close beyond 19mm open (position 2).	
Serenity 50FS, Serenity 50LS, Serenity 50FW, Serenity 50 Ped and Serenity 50 Inset stoves.	Instruction manual reference "Pevex1014/AH/ver1" dated January 2013.	Wood logs ⁽¹⁾ .
Manufactured by Pevex Enterprises Ltd., Unit 16, Seven Acres Business Park, Newbourne Road,	The secondary air slider must have a built in stop to prevent the slider from being shut off completely and remains open by 40% of its full travel.	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
Waldringfield, Nr Woodbridge,	The fireplace must be installed, maintained and operated in accordance with the following specifications: The tertiary air control must	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
IP12 4PS.	not have a slider and it must be factory designed with a 2cm open slot that remains 100% open.	
Serrano 5, York Midi; Monterrey 6 Stoves.	Instruction manual reference "09TJD" dated January 2010.	Wood logs ⁽¹⁾ .
Manufactured by Broseley Ltd., Knights Way, Battlefield Enterprise Park, Shrewsbury, Shropshire, SY1 3AB.	The appliance must be fitted with a system that prevents the closure of the secondary air flaps to less than 8mm open position.	
Serrano 5 Multi Fuel and Monterrey 6 Multi Fuel Stoves.	Instruction manual reference "TJ09C" dated 21st December 2009.	Wood logs ⁽¹⁾ .
Manufactured by Broseley Fires Ltd., Knights Way, Battlefield Enterprise Park, Shrewsbury, Shropshire, SY1 3AB.	The appliance must be fitted with a system that prevents the closure of the secondary air flaps to less than 8mm open position.	
Serrano 7 Multi Fuel stove. Manufactured by Broseley	Instruction manual reference "TJ09C" dated 21st December 2009.	Wood logs ⁽¹⁾ .
Fires Ltd., Knights Way, Battlefield Enterprise Park, Shrewsbury, Shropshire, SY1 3AB.	The appliance must be fitted with a system that prevents the closure of the secondary air flaps to less than 10mm open position.	
Sherborne SE NS-3C,	Installation and user instruction manual dated 4th	Wood logs ⁽¹⁾ .
Chesham SE NS-3B,	June 2014, reference "NS-3A - NS-3B - NS-3C"	
Burford SE NS-3A 4.9kW multi-fuel stoves.	The appliance must be fitted with mechanical stops	
Manufactured by Newman Fireplaces Ltd	to prevent closure of the secondary air control beyond the 30% open position	
Units 6 & 7 Rawreth Barns, Dollymans Farm, Doublegate		

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Lane, Rawreth, Wickford, Essex, SS11 8UD		30 0
Short Penguin and Penguin 8 multifuel stoves. Manufactured by Chilli	Instruction manual reference "Penguin Manual Version 1 Issue 1" dated 17th December 2013.	Wood logs ⁽¹⁾ .
Penguin Stoves Limited, Castell Bach, Mynydd Nefyn, Pwllheli, LL53 6TL.	The appliance must be fitted with a modification to fix the secondary air control to 1cm open in the fully closed position.	
SHT TDA Thermodual 15 and 25 log and pellet burning boilers.	Installation servicing instructions reference "In1233 Edition 1a" dated January	Wood logs or wood pellets ⁽¹⁾ .
Manufactured by Lohberger Heiztechnik GmbH,	2014, operating instructions reference "M21/HB M27/GB" dated 28th January 2014 and supplementary installation	
Rechtes Salzachufer 40,	instructions reference "IN1241 Edition 1a" dated January 2014.	
A-5020 Salzburg, Austria.		
SHT TDA Thermodual 30 and 40 log and pellet burning boilers.	Installation servicing instructions reference "In2015 Edition 1" dated January	Wood logs or wood pellets ⁽¹⁾ .
Manufactured by Lohberger Heiztechnik GmbH,	2014, operating instructions reference "M21/HB M27/GB dated 28th January 2014 and supplementary installation	
Rechtes Salzachufer 40,	instructions reference "IN1241 Edition 1a" dated January	
A-5020 Salzburg, Austria.	2014.	
Sigma UK 7kW inset roomheater.	User's manual dated March 2015 reference "Sigma & Sigma Titan. User's manual.	Wood logs ⁽¹⁾ .
Manufactured by Jydepejsen A/S, Ahornsvinget 3-7, Nr.	Revision 1, 25.03.2015"	
Felding, DK-7500 Holstebro, Denmark	The appliance must be fitted with a mechanical stop to prevent closure of the air control valve beyond the 28% open position	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
Citias syjn opiuos	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Silverdale 5SE, Amalia 5, Oppdal 5 and Hestia 5 multifuel stoves	Instruction manual reference "GB14A-issue 5" dated December 2014.	Wood logs ⁽¹⁾ .
Manufactured by Broseley Fires, Knights Way, Battlefield Enterprise Park, Shrewsbury, SY1 3AB.	The appliance must be fitted with a permanent stop to fix the secondary air slide at a minimum of 23mm open.	
NB: these are the same as the wood burning versions, with an alternative grate to allow use of other authorised fuels.		
Silverdale 7SE, Amalia 7, Oppdal 7 and Hestia 7 multifuel stoves	Instruction manual reference "GB14A-issue 5" dated December 2014.	Wood logs ⁽¹⁾ .
Manufactured by Broseley Fires, Knights Way, Battlefield Enterprise Park, Shrewsbury, SY1 3AB.	The appliance must be fitted with a permanent stop to fix the secondary air slide at a minimum of 50mm open.	
NB: these are the same as the wood burning versions, with an alternative grate to allow use of other authorised fuels.		
Sirius 490 Sigma MF, Sirius 490 Scene MF, Sirius 790 Sigma MF and Sirius 790 Scene MF multifuel stoves.	Installation and Operating Instructions manual reference "Sirius MF&WD Version 1" dated May 2013.	Wood logs ⁽¹⁾ .
Manufactured by Capital Fireplaces Ltd., 12-17 Henlow Trading Estate, Henlow Camp, Hitchin, SG16 6DS.	The appliance must be fitted with the manufacturer's smoke control kit.	
Sirius 490 Sigma WD and Sirius 490 Scene WD wood- burning stoves.	Installation and operating Instructions manual reference "Sirius MF&WD Version 1" dated May 2013.	Wood logs ⁽¹⁾ .
Manufactured by Capital Fireplaces Ltd., 12-17 Henlow Trading Estate, Henlow Camp, Hitchin, SG16 6DS.		

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
		No. Cost in the land
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Sirius 790 Sigma WD and Sirius 790 Scene WD woodburning stoves.	Installation and operating instructions manual reference "Sirius MF&WD Version 1" dated May 2013.	Wood logs ⁽¹⁾ .
Manufactured by Capital Fireplaces Ltd., 12-17 Henlow Trading Estate, Henlow Camp, Hitchin, SG16 6DS.	The appliance must be fitted with the manufacturer's smoke control kit.	
Sirius Imperial, Principal, Qadrical,& Essence 4.9kW multifuel stoves.	Installation & Operating Instructions dated 26th June 2015 reference "15JUN08/ EQIP/V1.3"	Wood logs ⁽¹⁾ .
Manufactured by Capital Fireplaces Ltd,	Fitted with a mechanical stop to prevent secondary air	
Units 12-17, Henlow Trading Estate, Henlow Camp, SG16 6DS	control closure beyond the 50% open position.	
Sirius Traditional Stove.	Instruction and operating	Wood logs ⁽¹⁾ .
Manufactured by Tianjin Focus Arts & Crafts Co, Industrial Area Gao Zhuangzi Village, Xin Zhuang Town, Jin Nan District, Tianjin, P.R. China 300350.	instruction manual reference "v173 of 09/11/2010" dated 9th November 2010.	
Smart 150, Smart 199, Smart 250, Smart 300, Smart 350, Smart 400, Smart 450 and Smart 500 boilers all fitted with cyclones.	Operation manual reference "BO4CD35 Issue No: 02" dated January 2014.	6mm wood pellets or 30mm wood chips at maximum 30% moisture ⁽¹⁾ .
Manufactured by Smart Heating Technology s.r.o, U Statku 653/24, 717 00 Ostrava- Bartovice, Czech Republic.		
Spartherm Arte U-50h – P3, U-90h – P3 and U-70h – P3 insert stoves	Instruction manual reference "Version 06/2014" dated June 2014.	Wood logs ⁽¹⁾ .
Manufactured by Spartherm		

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Maschweg 38, Melle, Germany.		
Spartherm Linear Cassette XS500-P3 insert stove	Instruction manual reference "Version 06/2014" dated June 2014.	Wood logs ⁽¹⁾ .
Manufactured by Spartherm Feuerungstechnik GmbH Maschweg 38, Melle, Germany.		
Spartherm Linear cassette model S 600 P3 inset stove.	Installation and operating instructions reference "Spatherm AA BA Kaminkass	Dry wood logs ⁽¹⁾ .
Manufactured by	01-2014" dated January 2014.	sette_Elifett_GB_Stand
Spartherm Feuerungstechnik GmbH, Maschweg 38,Melle, Germany.	The appliance must be fitted with a mechanical stop to prevent secondary air control closure beyond the 25% open position.	
Spartherm Mini 2LRh-4S P3, Mini 2L-4S P3 and Mini 2R-4S P3 wood-burning inset roomheaters	Instruction manual reference "Instruction Manual Fireplace Inserts Version 06/2014" dated June 2014.	Wood logs ⁽¹⁾ .
Manufactured by Spartherm Feuerungstechnik GmbH Maschweg 38, Melle, 49324, Germany.	The appliance must be fitted with a system to prevent closure of the air controls beyond the 3mm open position.	
Spartherm Passo S-P3, Spartherm Passo M-P3 and Spartherm Passo L-P3 10kW wood-burning stoves.	Installation and Operating instructions for Stoves Selection manual dated July 2015 reference "Version 07/2015"	Wood logs ⁽¹⁾ .
Manufactured by Spartherm Feuerungstechnik GmbH, Maschweg 38, D-49324 Melle, Germany	A permanent stop must be in place on the secondary air inlet to prevent closure beyond the 3mm open position	
Spartherm Stovo S, M, & L Wood burning stoves.	Installation and operating instructions reference "Version 07/2013" dated July 2013.	Wood logs ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Manufactured by Spartherm, Feuerungstechnik GmbH, Maschweg 38, Melle, Germany.	The appliance must be fitted with a mechanical stop to prevent secondary air control closure beyond the 13% open position.	
Spatherm Varia ASh2L – P3, Varia ASh2R – p3, Varia ASh2LX – P3, Varia Ash2R X – P3 wood burning inset roomheaters.	Instruction manual reference 'Instruction Manual Fireplace Inserts Version 06/2014' dated June 2014.	Wood logs ⁽¹⁾ .
Manufactured by Spatherm Feuerungstechnik GmbH, Maschweg 38, D-49324 Melle, Germany.	A system to prevent closure of the air controls beyond the 7mm open position must be implemented.	
Stockton 3 flat top (product code 7118), Stockton 4 flat top (product code 7101 and 7102), Stockton 5 flat top (product code 7127), Stockton 5 midline (product code 7130), Stockton 6 flat top (product codes 7100 and 7162), Stockton 6 Highline (product code 7117), and Stockton 7 flat top (product codes 7120 and 7163).	Instruction manual reference "PM227 ENG Issue 2" dated July 2008 and instruction manual reference "PM271 Issue 2" dated January 2009. The appliance must be fitted with a permanent stop on the secondary air inlet to prevent closure beyond the 50% open position.	Untreated dry wood ⁽¹⁾ .
Manufactured by Stovax Ltd., Falcon Road, Sowton Industrial Estate, Exeter, Devon, EX2 7LF.		
Stockton 5 flat top (model number 7119), Stockton 5 Canopy (model number 7160), and Stockton 5 Midline (model number 7133).	Manufacturer's instructions reference "PM176 – issue 4". The appliance must be fitted with a permanent stop on the secondary air inlet to prevent	Untreated dry wood ⁽¹⁾ .
Manufactured by Stovax Ltd., Falcon Road, Sowton Industrial Estate, Exeter, Devon, EX2 7LF.	closure beyond the 50% open position.	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Stockton 7 Inset Convector (product codes 7125F and 7125C). Manufactured by Stovax Ltd., Falcon Road, Sowton Industrial Estate, Exeter, Devon, EX2 7LF.	Manufacturer's instruction manual reference "PM230 Issue 1" dated May 2008 and instruction manual reference "PM281 Issue 1" dated January 2009. The appliance must be fitted with a permanent stop on the secondary air inlet to prevent closure beyond the 50% open position.	Untreated dry wood ⁽¹⁾ .
Stockton Milner (4.6kW) inset stove – smoke control version. Manufactured by Stovax Ltd., Falcon Road, Sowton Industrial Estate, Exeter, Devon, EX2 7LF.	Instruction manual reference "PM416 Issue 1" dated June 2010 and smoke control kit instruction manual reference "PM501 Issue 1" dated June 2010. The appliance must be fitted with a permanent stop to prevent closure of the secondary air control below the 50% open position.	Wood logs ⁽¹⁾ .
The Stone Bake Oven Company Mezzo 76 Go and Mezzo 76 Kit wood-burning pizza ovens. Manufactured by Gozney Ltd, Units 18 & 19, Radar Way, Christchurch Business Park, The Runway, Christchurch, BH23 4JE.	Oven Assembly and Operation Manual dated May 2015 reference "Mezzo_Oven_Manual/ Version 1.1"	Wood logs ⁽¹⁾ .
The Stone Bake Oven Company Vento 100 wood- burning pizza ovens. Manufactured by Gozney Ltd, Units 18 & 19, Radar Way, Christchurch Business Park, The Runway, Christchurch, BH23 4JE.	Vento 100 Oven Assembly and Operation Manual dated May 2015 reference "Vento_Oven_Manual/Version 1.1"	Wood logs ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
Class of fireplace	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
The Stone Bake Oven Company Gusto 120 wood- burning pizza ovens.	Gusto 120 Oven Assembly and Operation Manual dated May 2015 reference "Gusto Oven Manual/Version	Wood logs ⁽¹⁾ .
Manufactured by Gozney Ltd, Units 18 & 19, Radar Way, Christchurch Business Park, The Runway, Christchurch, BH23 4JE.	1.1"	
Stoven Mayfair SE & Stoven Kensington SE 5kW Wood Burning Stoves.	Instruction manual reference "3-4" dated 27th November 2011.	Wood logs ⁽¹⁾ .
Manufactured by Ciang Stoves Ltd., South Chuangye Road, (Hanling Industrial Estate), Beiguan Section, Anyang City, Henan Provence, China 455000.	The appliance must be fitted with mechanical stops to prevent closure of the secondary air control beyond the 25% open position and the tertiary air beyond the 1mm open position.	
Stovo S-plus – P3 and Stovo L-plus – P3 4.7kW wood burning stoves. Manufactured by Spartherm	Installation and Operating instructions for Stoves Selection manual dated July 2015 reference "Version 07/2015"	Wood Logs ⁽¹⁾ .
Feuerungstechnik GmbH Maschweg 38, 49324 Melle	The appliance must be fitted with a mechanical stop to	
Germany	prevent closure of the air control beyond the 5mm open position	
Strebel Biotec 25 and 40 boilers	Instruction manual reference "Version BIOTEC 122013" dated December 2013.	Wood pellets ⁽¹⁾ .
Manufactured by Topling d.o.o. Magistralni put BB, 78430 Prnjavor, The Republic of Srpska, Bosnia and Herzegovina.	dated December 2015.	
Strebel SRP TR 90, 90kW output pellet boiler.	Installation manual reference "Installation and operation instructions for special pellet-furnace version 09:2010".	6mm diameter wood pellets ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Manufactured by Strebel Ltd., 1F Albany Park Industrial Estate, Frimley Road, Camberley, Surrey, GU15 7P.		
Strebel Taurus XL 145, Strebel Taurus XL 190,	Instruction manual reference "Manual Version XL145 to 290" dated December 2013.	
Strebel Taurus XL 240 and		
Strebel Taurus XL 290 boilers.		
Manufactured by KSM Stoker, Naessundvej 440, 7960 Karby, Denmark.		
Stretton Insert Smoke Exempt Wood Fuel Stove (Stretton Stove SE).	Instruction manual reference "N00530AXX REV:001" dated 12th July 2011.	Dry wood logs ⁽¹⁾ .
Manufacture 11 Acc		
Manufactured by Aga, Station Road, Ketley Telford, Shropshire, TF1 5AQ.		
Station Road, Ketley Telford,	Instruction manual reference "Installation, Operation and Maintenance Instructions. STU wood-pellet fired hot water boiler skid assembly STUman CAA (SM)" dated May 2011.	Wood pellets ⁽¹⁾ .
Station Road, Ketley Telford, Shropshire, TF1 5AQ. STU 195 and STU 975. Manufactured by Hoval Ltd., Northgate, Newark,	"Installation, Operation and Maintenance Instructions. STU wood-pellet fired hot water boiler skid assembly STUman	Wood pellets ⁽¹⁾ . Wood Logs ⁽¹⁾ .
Station Road, Ketley Telford, Shropshire, TF1 5AQ. STU 195 and STU 975. Manufactured by Hoval Ltd., Northgate, Newark, Nottinghamshire, NG24 1JN. Stûv Micromega 11kW Wood-	"Installation, Operation and Maintenance Instructions. STU wood-pellet fired hot water boiler skid assembly STUman CAA (SM)" dated May 2011. Directions for use Stûv µM manual dated September 2015	
Station Road, Ketley Telford, Shropshire, TF1 5AQ. STU 195 and STU 975. Manufactured by Hoval Ltd., Northgate, Newark, Nottinghamshire, NG24 1JN. Stûv Micromega 11kW Wood-Burning Stove. Manufactured by Stûv SA Rue Jules Borbouse 4, 5170 Bois-	"Installation, Operation and Maintenance Instructions. STU wood-pellet fired hot water boiler skid assembly STUman CAA (SM)" dated May 2011. Directions for use Stûv µM manual dated September 2015 reference "SN 122141" Fitted with a mechanical stop to prevent air control closure	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications: The appliance must be fitted with a mechanical stop to prevent air control closure beyond the positions between settings 3 and 4.	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Stuv 30 Compact IN and Stuv 30 Compact R. Manufactured by Stuv Sa, Rue Jules Borbouse 4, B-5170 Bois-de-Villers, Belgium.	Instruction manual reference "SN 112787" dated January 2013 and installation instruction manual reference "112787" dated January 2013. The appliance must be fitted with a mechanical stop to prevent air control closure beyond the positions between settings 3 and 4.	Wood logs ⁽¹⁾ .
Stuv 30 Compact.	Instruction manual reference	Wood logs ⁽¹⁾ .
Manufactured by Stuv Sa, Rue Jules Borbouse 4, B-5170 Bois-de-Villers, Belgium.	"SN 94770" dated January 2013 and installation instruction manual reference "SN 94770" dated January 2013. The appliance must be fitted with a mechanical stop to prevent air control closure	
	beyond the positions between settings 3 and 4.	
Suprema, Mamy and Italy Hard Top.	Instruction manual reference "7095701 Rev.09" dated 13th December 2010.	Wood logs ⁽¹⁾ .
Manufactured by La Nordica Spa, Via Summano 104 M. Precalcino, 36030, Vicenza, Italy.		
Talbott 150-CMH 150kW output Biomass Air Heater. Manufactured by Talbott's Biomass Energy Systems	Instruction manual reference "OM-150-CMH version.1" dated January 2011.	Softwood, hardwood, medium density fibreboard (MDF) or chipboard offcuts ⁽¹⁾ .
Ltd., Tollgate Drive, Tollgate		result of treatment with wood precervatives

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of Guardina	Conditions	
Class of fireplace	Conditions The Guardage must be	No fiel is to be seed
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Industrial Estate, Stafford, ST16 3HS.		
Talbott's Automatic Biomass Air Heaters, models T1.5/A, T3/A, T5/A and TM/A.	Manufacturer's instructions reference "T/A JANUARY 1990".	Hardwood or softwood shavings or sawdust ⁽¹⁾ .
Formerly manufactured by Talbott's Heating Ltd., and now manufactured by Talbott's Biomass Energy Systems Ltd., Tollgate Drive, Tollgate Industrial Estate, Stafford, ST16 3HS.		
Talbott's Biomass Energy Models C1, C2, C3 and C4.	Manufacturer's instructions reference "Issue C1000/C/ Range" dated August 1995.	Chipboard or wood shavings, forestry chips ⁽¹⁾ .
Formerly manufactured by Talbott's Heating Ltd., and now manufactured by Talbott's Biomass Energy Systems Ltd., Tollgate Drive, Tollgate Industrial Estate, Stafford, ST16 3HS.		
Talbott's model T75, T150, T300 Biomass Air Heaters.	Manufacturer's instructions reference "models T75, T150 and T300: "gen/sttech" dated	Wood offcuts, wood-waste, pellets, chipboard ⁽¹⁾ .
Formerly manufactured by Talbott's Heating Ltd., and now manufactured by Talbott's Biomass Energy Systems Ltd., Tollgate Drive, Tollgate Industrial Estate, Stafford, ST16 3HS.	1st January 1995.	
Talbott's T500 Biomass Air heater (afterburn model).	Manufacturer's instructions reference "A10000" dated 1st January 1983.	Wood offcuts, wood-waste, pellets, chipboard ⁽¹⁾ .
Formerly manufactured by Talbott's Heating Ltd., and now manufactured by Talbott's Biomass Energy Systems Ltd., Tollgate Drive, Tollgate Industrial Estate, Stafford, ST16 3HS.	The afterburn cycle must last not less than 25 minutes and must come into operation each time the loading door is opened.	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

	T	
Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Termatech TT20, TT20Bazic, TT20R, TT20S, TT20RS and TT20SA woodburning stoves	User and mounting manual reference "99-275 UK version" dated July 2014.	Wood logs ⁽¹⁾ .
Manufactured by TermaTech A/S, Jegstrupvej 60, DK-8361 Hasselager, Denmark	The appliance must be fitted with the damper control unit referenced in the manufacturer's manual.	
Termatech TT22 and TT22S convection wood-burning stoves	User and mounting manual reference "99-234 UK version" dated July 2014.	Wood logs ⁽¹⁾ .
Manufactured by TermaTech A/S, Jegstrupvej 60, DK-8361 Hasselager, Denmark	The appliance must be fitted with a smoke control kit to ensure the primary and secondary air controls are 25% open in their minimum position.	
Therminator II 22 and Therminator II 30 Boiler. Manufactured by Solarfocus Ltd., Werkstrasse 1, 4451 St.Ulrich, Steyr, Austria.	Installation instructions reference "Version: 11/08/06" dated July 2006, operating manual reference "V8.051" dated September 2009 and maintenance instructions reference "Ver.:01/09/06" dated 2006.	Wood pellets ⁽¹⁾ .
Therminator II 27 and Therminator II 36 Boiler. Manufactured by Solarfocus Ltd., Werkstrasse 1, 4451 St.Ulrich, Steyr, Austria.	Installation instructions reference "Version:11/08/06" dated July 2006, operating manual reference "V8.051" dated September 2009 and maintenance instructions reference "Ver.:01/09/06" dated 2006.	Wood logs ⁽¹⁾ .
Therminator II 40 Boiler. Manufactured by Solarfocus Ltd., Werkstrasse 1, 4451 St.Ulrich, Steyr, Austria.	Installation instructions reference "Version: 11/08/06" dated July 2006, operating manual reference "V8.051" dated September 2009 and maintenance instructions reference "Ver.:01/09/06" dated 2006.	Wood pellets or wood chips ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
Class of Jureplace	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Therminator II 49 and Therminator II 60 Boiler. Manufactured by Solarfocus	Installation instructions reference "Version: 11/08/06" dated July 2006, operating manual reference "V8.051"	Wood logs or wood pellets or wood chips ⁽¹⁾ .
Ltd., Werkstrasse 1, 4451 St.Ulrich, Steyr, Austria.	dated September 2009 and maintenance instructions reference "Ver.:01/09/06" dated 2006.	
Thornhill T3 small. Manufactured by Thornhill Fac Design Ltd. 58 60	Instruction manual reference "ED/11/05" dated January 2011.	Wood logs ⁽¹⁾ .
Eco Design Ltd., 58-60 Wincheap, Canterbury, Kent, CT1 3RS.	The appliance must be fitted with an air plate that prevents the tertiary air controller from closing more than 17mm and opening more than 45mm.	
Tiger GH-T Insert Stove. Manufactured by Hughes Design Limited, Denver House, Winster, Derbyshire, DE4 2DH.	Instruction manual reference "Tiger solid fuel heating stoves inset multi-fuel models incorporating GH-T Firebox. Solid Fuel Stoves Manual v12" dated 22nd January 2014 and "Soliftec Smoke Advice Sheet no1" dated 22nd January 2014.	Wood logs ⁽¹⁾ .
	The appliance must be fitted with a mechanical stop to prevent closure beyond the 5mm closed position on the secondary air control.	
Tiger SuperClean.	Instruction manual reference "Installation and Operating	Wood logs ⁽¹⁾ .
Manufactured by Tiger stoves, Focus Arts & Crafts Co., Industrial Area Gao Zhuangzi Village, Xin Zhuang Town, Jin Nan District, Tainjin, P. R. China 300350.	Instructions document v.148" dated April 2010.	
Tile Tec Fireplaces Bliss 5 CB 4.9kW multifuel stove.	Installation & Operating Instructions dated 26th June 2015 reference "15JUN09/ BL5/V1.2"	Wood logs ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
Manufactured by Capital Fireplaces Ltd, Units 12-17,	The fireplace must be installed, maintained and operated in accordance with the following specifications: Fitted with a mechanical stop to prevent secondary air	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Henlow Trading Estate	control closure beyond the 50% open position.	
Henlow Camp, SG16 6DS	• •	
Tile Tec Fireplaces Bliss 8 CB 8.9kW multifuel stove. Manufactured by Capital	Installation & Operating Instructions dated 26th June 2015 reference "15JUN09/ BL8/V1.4"	Wood logs ⁽¹⁾ .
Fireplaces Ltd, Units 12-17, Henlow Trading Estate	Fitted with a mechanical	
Henlow Camp, SG16 6DS	stop to prevent secondary air control closure beyond the 50% open position.	
Trianco Greenflame 15 wood pellet boiler.	Instruction manual reference "Item No. 400001 Iss. 2" dated 25th June 2012.	6mm wood pellets ⁽¹⁾ .
Manufactured by T.R Engineering Ltd., Unit 7, Newton Chambers Way, Thorncliffe Industrial Estate, Chapeltown, Sheffield, S35 2PH.	Zour valle 2012.	
Trianco Greenflame 18 Slim Wood Pellet Boiler	Installation and operating manual reference "V.1.1" dated June 2014.	Wood pellets ⁽¹⁾ .
Manufactured by T.R Engineering Ltd., Unit 7, Newton Chambers Way, Thorncliffe Industrial Estate, Chapeltown, Sheffield, S35 2PH.	June 2014.	
Trianco Greenflame 55, 85, 100, 125, & 199 Wood Pellet Boilers.	Installation, operation and servicing instructions reference "Manual Edition: Greenflame	Wood pellets ⁽¹⁾ .
Manufactured by Wood Energy Solutions Ltd., Donaskeigh, Tipperary, Co. Tipperary, Ireland.	Commercial Series" dated May 2012.	
Tripp TR5i Multi-fuel inset stove.	Installation and operating instruction manual reference "TR5i" dated 2nd May 2013.	Wood logs ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
Class of Jireplace	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Manufactured by Heat Design Ltd., 30 Hawthorn Road, Western Industrial Estate, Naas Road, Dublin 12, Ireland.	The appliance must be fitted with a mechanical stop to prevent secondary air control closure beyond the 3.5mm open position.	
Triton 450 Glass and Vega 450 4.5kW multifuel stoves. Manufactured by F.E.Robinson(Hooton)Limited, Station Works, Hooton Road,	Instruction manual dated 28th July 2015, reference: "Triton 450 / Vega 450 / Volan 750 / Vega 750 Solid Fuel Stoves Manual Version 1.1 Issued 28/07/2015"	Wood Logs ⁽¹⁾ .
Hooton, South Wirral, CH66 7NF		
Troja 44 UK, Troja 45 UK and, Troja 46 UK 7kW stoves. Manufactured by Jydepejsen A/S, Ahornsvinget 3-7, Nr.	User's manual dated March 2015 reference "Sirius & Orion & Troja. User manual. Revision 1, 25.03.2015"	Wood logs ⁽¹⁾ .
Felding, DK-7500 Holstebro, Denmark	The appliance must be fitted with a mechanical stop to prevent closure of the air control valve beyond the 27% open position	
Tucana 600, Vega 600 6kW multifuel inset stoves. Manufactured by	Instruction manual dated 28th July 2015, reference: "Tucana 600 / Vega 600 Solid Fuel Stoves Manual Version 1.1	Wood Logs ⁽¹⁾ .
F.E.Robinson(Hooton)Limited, Station Works, Hooton Road, Hooton, South Wirral,	Issued 28/07/2015" The appliance must be fitted with a mechanical stop to prevent secondary air control closure beyond the 10 mm	
CH66 7NF Turbhogar Alfa 80T and	open position Manual of assembly and use	Wood logs ⁽¹⁾ .
65T, Turbhogar Beta 80T, Turbhogar Delta 80T and 65T, Turbhogar Lambda 80T and 65T, Turbhogar Sigma 80T and 65T, Turbhogar Omega 80T	reference "RR100920" dated 20th September 2010 and supplementary instruction manual reference "UK100920" dated 20th September 2010.	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
and Turbhogar Tau 80T and 65T fireplace inserts.	The appliance must be fitted with a system that prevents	
Manufactured by Rofer & Rodi UK Ltd., Rofer & Rodi UK Ltd., Unit 10, Millennium Road, Airedale Business Centre, Skipton, North Yorkshire, BD23 2TZ.	the full closure of the air control opening so that the air openings remain 3mm (30%) open at the minimum setting.	
Turco Woodsman 18 Slim Wood Pellet Boiler	Installation and operation manual reference "V.1.1" dated June 2014.	Wood pellets ⁽¹⁾ .
Manufactured by Wood Energy Solutions Limited, Donaskeigh, Tipperary, Co. Tipperary, Ireland.		
Turkington Engineering Woodlander 28 Wood Pellet Boiler; and	Installation and operation manual reference "Version 2.1" dated July 2013.	Wood pellets ⁽¹⁾ .
Highland Biomass Solutions Bio-Flame 28 Wood Pellet Boiler.		
Manufactured by Wood Energy Solutions Ltd., Donaskeigh, Tipperary, Co. Tipperary, Ireland.		
Turkington Engineering Woodlander 55, 85, 100, 125, & 199 Wood Pellet Boilers.	Installation, operation and servicing instructions reference "Manual Edition: Woodlander	Wood pellets ⁽¹⁾ .
Manufactured by Wood Energy Solutions Ltd., Donaskeigh, Tipperary, Co. Tipperary, Ireland.	Commercial Series" dated July 2013.	
Twin Heat Cpi12 boiler	Users manual dated January	Wood pellets or wood chips ⁽¹⁾ .
manufactured by Twin Heat A/S, Nørrevangen 7,	2015 reference "Users manual Compact Stoker Cpi12 Version 3.1 – Jan. 2015"	
DK-9631, Gedsted, Denmark		

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Twin Heat CS120i, CS150i and CS250i boilers.	Users manual dated January 2015 reference "Users manual Stoker Plants CS120i, CS150i,	Wood pellets or wood chips ⁽¹⁾ .
Manufactured by Twin Heat A/S, Nørrevangen 7, DK-9631, Gedsted, Denmark	CS200i, CS250i Version 7.1 – Jan. 2015"	
Twin Heat CS 150i.	Manufacturer's operating instructions reference "version	Wood pellets of a maximum length of 30mm and diameter
Manufactured by TWIN HEAT A/S, Nørrevangen 7, DK-9631 Gedsted, Denmark.		of 6mm and conforming to CEN/TS 14961:2005 ⁽¹⁾ .
Twin Heat CS200i boiler.	Users manual dated January 2015 reference "Users manual	Wood chips ⁽¹⁾ .
Manufactured by Twin Heat A/S, Nørrevangen 7, DK-9631, Gedsted, Denmark	Stoker Plants CS120i, CS150i, CS200i, CS250i Version 7.1 – Jan. 2015"	
Twin Heat M20i, M40i and M80i boilers.	Users manual dated January 2015 reference "Users manual Stoker Plants M20i, M40i,	Wood pellets or wood chips ⁽¹⁾ .
Manufactured by Twin Heat A/S, Nørrevangen 7, DK-9631, Gedsted, Denmark		
Twin Heat MCS20i, MCS40i and MCS80i boilers.	Users manual dated January 2015 reference "Users manual Stoker Plants MCS20i,	Wood pellets or wood chips ⁽¹⁾ .
Manufactured by Twin Heat A/S, Nørrevangen 7,	· · · · · · · · · · · · · · · · · · ·	
DK-9631, Gedsted, Denmark		
Type USV wood pellet and wood chip fired boilers, model numbers USV-15, 25, 30, 40, 50, 60, 80 and 100.	Manufacturer's instructions reference "BA-USV 0803" dated August 2003.	Wood pellets or wood chips ⁽¹⁾ .
Manufactured by KWB – Kraft und Wärme aus Biomasse Gesellschaft mit beschränkter Haftung (GmbH) of Industriestrasse 235, A-8321 St. Margarethen an der		

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Type USP wood pellet fired boilers, model numbers USP-10, 15, 20, 25 and 30.	Manufacturer's instructions reference "BA-USP 0703" dated 28th July 2003.	Wood pellets ⁽¹⁾ .
Manufactured by KWB – Kraft und Wärme aus Biomasse Gesellschaft mit beschränkter Haftung (GmbH) of Industriestrasse 235, A-8321 St. Margarethen an der Raab, Austria.		
ULTIME C MF 600-75 WHE 1S – DEFRA 19.4kW woodburning inset appliance. Manufactured by MetalFire nv,	Instruction manual dated May 2015 reference "Instructions for use Ultime C range – Smoke Control Areas (UK) "V1 – DEFRA/ May 2015"	Wood Logs ⁽¹⁾ .
Noorwegenstraat 28, B-9940, Evergem, Belgium	The appliances must be fitted with a mechanical stop to the air control to prevent closure beyond the 50% open position.	
ULTIME C MF 800-50 WHE 1S – DEFRA (20kW) and ULTIME C 1050-75 WHE 1S – DEFRA (27.5kW) wood- burning inset appliances.	Instruction manual dated May 2015 reference "Instructions for use Ultime C range – Smoke Control Areas (UK) "V1 – DEFRA/ May 2015"	Wood Logs ⁽¹⁾ .
Manufactured by MetalFire nv, Noorwegenstraat 28, B-9940, Evergem, Belgium	The appliances must be fitted with a mechanical stop to the air control to prevent closure beyond the 11mm open position.	
ULTIME C MF 800-75 WHE 1S – DEFRA 23.4kW woodburning inset appliance. Manufactured by MetalFire nv	Instruction manual dated May 2015 reference "Instructions for use Ultime C range – Smoke Control Areas (UK) "V1 – DEFRA/ May 2015"	Wood Logs ⁽¹⁾ .
Noorwegenstraat 28, B-9940, Evergem, Belgium	The appliances must be fitted with a mechanical stop to the air control to prevent closure beyond the 11mm open position.	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
ULTIME C MF 1050-50 WHE 1S – DEFRA (21.6kW) and ULTIME C 1300-50 WHE 1S – DEFRA (27kW),wood- burning inset appliances.	Instruction manual dated May 2015 reference "Instructions for use Ultime C range – Smoke Control Areas (UK) " V1 – DEFRA/ May 2015"	Wood Logs ⁽¹⁾ .
Manufactured by MetalFire nv, Noorwegenstraat 28, B-9940, Evergem, Belgium		
ULTIME D MF 600-50 WHE 1S – DEFRA 13.8kW inset roomheater. Manufactured by MetalFire nv, Noorwegenstraat 28, B-9940 Evergem, Belgium	Instructions for use Ultime D range – Smoke Control Areas (UK) dated May 2015 reference "V1 – DEFRA/ May 2015" and Installation Instructions Ultime D range – Smoke Control Areas (UK) dated May 2015 reference "V1 – DEFRA/ May 2015"	Wood Logs ⁽¹⁾ .
	The appliance must be fitted with a permanent stop to prevent closure of the air control lever beyond the 7 mm open position.	
ULTIME D MF 600-75 WHE 1S – DEFRA 18.8kW inset roomheater. Manufactured by MetalFire nv, Noorwegenstraat 28, B-9940 Evergem, Belgium	Instructions for use Ultime D range – Smoke Control Areas (UK) dated May 2015 reference "V1 – DEFRA/ May 2015" and Installation Instructions Ultime D range – Smoke Control Areas (UK) dated May 2015 reference "V1 – DEFRA/ May 2015"	Wood Logs ⁽¹⁾ .
	The appliance must be fitted with a permanent stop to prevent closure of the air control lever beyond the 15 mm open position.	
ULTIME D MF 1050-50 WHE 1S – DEFRA 19.4kW inset roomheater.	Instructions for use Ultime D range – Smoke Control Areas (UK) dated May 2015 reference "V1 – DEFRA/ May 2015" and Installation	Wood Logs ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Manufactured by MetalFire nv, Noorwegenstraat 28, B-9940 Evergem, Belgium	Instructions Ultime D range - Smoke Control Areas (UK) dated May 2015 reference "V1 - DEFRA/ May 2015"	
	The appliance must be fitted with a permanent stop to prevent closure of the air control lever beyond the 9 mm open position.	
ULTIME D inset roomheaters models :	Instructions for use Ultime D range – Smoke Control Areas (UK) dated May 2015	Wood Logs ⁽¹⁾ .
MF 800-50 WHE 1S – DEFRA 16.6kW,	reference "V1 – DEFRA/ May 2015" and Installation Instructions Ultime D range	
MF 800-75 WHE 1S – DEFRA 21.2kW,	- Smoke Control Areas (UK) dated May 2015 reference "V1 - DEFRA/ May 2015"	
MF 1050-75 WHE 1S - DEFRA 23.5kW.	The appliance must be fitted with a permanent stop to	
Manufactured by MetalFire nv,	prevent closure of the air control lever beyond the 11	
Noorwegenstraat 28, B-9940 Evergem, Belgium	mm open position.	
Uniconfort EOS 45, EOS 50, EOS 55, EOS 65, EOS 70, EOS 75, EOS 80, EOS 85 fitted with a multi-cyclone.	Instruction manual reference "Uniconfort EOS MANUAL: R1" dated May 2012.	Wood pellets ⁽¹⁾ .
Manufactured by Uniconfort srl, Via dell'Industria, 21, 35018 San Martino di Lupari, PD, Italy.		
Uniconfort EOS 90 fitted with a multi-cyclone.	Instruction manual reference "Uniconfort EOS MANUAL: R1" dated May 2012.	Wood pellets or wood chips ⁽¹⁾ .
Manufactured by Uniconfort srl, Via dell'Industria, 21, 35018 San Martino di Lupari, PD, Italy.	,	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Varde Aura Ovne 1 (VD-AURA1), 2 (VD-AURA2), 3 (VD-AURA3), and 11 (VD-AURA11) wood burning 5kW stoves Manufactured by Varde Ovne A/S, Kongevej 246, DK-6510 Gram, Denmark.	Installation and user guide reference "FOR-177 GB2 edition" dated 26th July 2010 and additional installation and user instructions for use in Smoke Control Areas reference "Varde Aura 2. Edition FOR-177 GB PM1053 Issue 2" dated July 2014. The appliance must be fitted with a mechanical stop to prevent closure of the secondary air control beyond	Wood logs ⁽¹⁾ .
	the 50% open position.	
Varde Ovne Fuego 1 (VD-FUEGO1) and 2 (VD-FUEGO2) wood burning 5kW stoves Manufactured by Varde Ovne A/S, Kongevej 246, DK-6510 Gram, Denmark.	Installation and user guide reference "Varde Fuego Revision 2" dated 15th May 2013 and additional installation and user instructions for use in Smoke Control Areas reference "Varde Fuego – Revision 02 Installation and User Guide PM1062 Issue 2" dated July 2014.	Wood logs ⁽¹⁾ .
	The appliance must be fitted with a mechanical stop to prevent closure of the secondary air control beyond the 50% open position.	
Varde Ovne Samsø (VD-SAMSO) 5 kW wood burning stove. Manufactured by Varde Ovne A/S, Kongevej 246, DK-6510 Gram, Denmark	Smoke Control Kit Additional Installation and User Instructions for use in Smoke Control Areas dated 01/09/2015 reference "PM1258 Issue 1", and Installation and User Guide dated 01/09/2015 reference "PM1257 Issue 2".	Wood logs ⁽¹⁾ .
	The appliance must be fitted with a mechanical stop	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications: to prevent closure of the secondary air control beyond the 50% open position.	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Varde Ovne Shape 1 (VD-SHAPE1B) and 2 (VD-SHAPE2B) wood burning 5kW stoves Manufactured by Varde Ovne A/S, Kongevej 246, DK-6510 Gram, Denmark.	Installation and user guide reference "FOR – 176 GB1 edition" dated 18th June 2009 and additional installation and user instructions for use in Smoke Control Areas reference "Varde Shape 1. Edition FOR-176 GB PM 1054 Issue 2" dated July 2014.	Wood logs ⁽¹⁾ .
	The appliance must be fitted with a mechanical stop to prevent closure of the secondary air control beyond the 37.5% open position.	
Varde Ovne Uniq 1 (VD-UNIQ1) wood burning 5.4kW stove Manufactured by Varde Ovne A/S, Kongevej 246, DK-6510 Gram, Denmark.	Installation and user guide reference "Revision 6" dated 3rd June2014 and additional installation and user instructions for use in Smoke Control Areas reference "Varde Uniq –Revision 4 Installation and User Guide PM1055 Issue 2" dated July 2014.	Wood logs ⁽¹⁾ .
	The appliance must be fitted with a mechanical stop to prevent closure of the secondary air control beyond the 30% open position.	
Varia AS 11kW wood-burning inset appliances models: Varia AS-A-P3, Varia ASh-A-P3, Varia AS X-A-P3, Varia ASh X-A-P3, Varia AS-A1-P3,	Instruction manual dated September 2015 reference "Instruction manual Fireplace Inserts version 09/2014"	Wood Logs ⁽¹⁾ .
Varia ASh-A1-P3, Varia AS X-A1-P3 and, Varia ASh X-A1-P3.	The appliances must be fitted with a mechanical stop to the air control to prevent closure beyond the 10 mm open position.	
(1) The fuel must not contain halogenate	ed organic compounds or heavy metals as a r	regult of treatment with wood pregamentings

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Manufactured by Spartherm Feuerungstechnik GmbH,		
Maschweg 38, D-49324 Melle, Germany		
VarioWIN VA 120 12kW wood pellet boiler.	Installation instruction manual reference "092947/00" dated	Wood pellets, 6mm diameter, length 80% between 15-30mm
Manufactured by Windhager Zentralheizung GmbH, Anton- Windhager-Str.20, A-5201 Seerkirchen bei Salzburg, Austria.	January 2010 and operating instruction manual reference "092945/00" dated January 2010.	and a density of at least 1.1kg/dm ³⁽¹⁾ .
Vega 100 Clean Burn II.	Instruction manual reference "Vega 100 Clean Burn II	Wood logs ⁽¹⁾ .
Manufactured by Percy Doughty & Co Ltd., Imperial Point, Express Trading Estate, Stonehill Road, Farnworth	Installation and Operation Instructions REV: D" dated January 2013.	
Bolton, BLA 9TN.	The appliance must be fitted with a mechanical stop to prevent secondary air control closure beyond the 50% open position.	
Vega 200 Clean Burn.	Instruction manual reference "Vega 200 Clean Burn	Wood logs ⁽¹⁾ .
Manufactured by Percy Doughty & Co Ltd., Imperial Point, Express Trading Estate, Stonehill Road, Farnworth	Installation and Operation Instructions REV: D" dated January 2013.	
Bolton, BLA 9TN.	The appliance must be fitted with a mechanical stop to prevent secondary air control closure beyond the 50% open position.	
Vega Amor 100 4.9kW multi- fuel stove	Instruction manual reference "AMOR 100 REV:B" dated December 2014.	Wood logs ⁽¹⁾ .
Manufactured by Percy Doughty & Co. Limited, Imperial Point, Express Trading Estate, Stone Hill	The appliance must be fitted with a mechanical stop to prevent secondary air closure beyond the 50% open position.	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Road, Farnworth, Bolton BL4 9TN		
Vega Edge 100 4.9kW multi- fuel stove	Instruction manual reference "VEGA EDGE 100 INSTRUCTION – REV. B"	Wood logs ⁽¹⁾ .
Manufactured by Percy Doughty & Co. Limited,	dated December 2014.	
Imperial Point, Express Trading Estate, Stone Hill Road, Farnworth, Bolton BL4 9TN	The appliance must be fitted with a permanent stop to modify the secondary air control closure to a minimum	
	of 7mm open.	
Vega Edge 200SL 5kW multifuel stove.	Installation and Operating instructions dated 1st February 2016 reference "VEGA EDGE"	Wood logs ⁽¹⁾ .
Manufactured by Percy Doughty & Co Limited, Imperial Point, Express Trading Estate, Stone Hill Road, Farnworth, Bolton, BL4 9TN	SERIES INSTRUCTION - REV.C".	
Vega Edge 200 8kW multi-fuel stove.	Installation and Operating instructions dated 1st February 2016 reference "VEGA EDGE	Wood logs ⁽¹⁾ .
Manufactured by Percy Doughty & Co Limited, Imperial Point, Express Trading Estate, Stone Hill Road, Farnworth, Bolton, BL4 9TN	SERIES INSTRUCTION - REV.C".	
Vermont Castings Defiant model 1975 catalytic woodburning stove.	Homeowner's installation and operating manual reference "30005554 7/13 Rev. 10"	Wood logs ⁽¹⁾ .
canning store.	dated July 2013.	
Manufactured by Vermont Castings Group, 62 Vermont Castings Road, Bethel, Vermont, 05032, USA.	The appliance must be operated with the catalyst and fitted with a system that prevents closure of the air control lever beyond the 25mm (5 o'clock) open position.	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Vermont Castings Encore model 2040 catalytic woodburning stove.	Homeowner's installation and operating manual reference "30005552 7/13 Rev. 9" dated July 2013.	Wood logs ⁽¹⁾ .
Manufactured by Vermont Castings Group, 62 Vermont Castings Road, Bethel, Vermont, 05032, USA.	The appliance must be operated with the catalyst.	
Vesuvio 400kW automatic pizza oven. Manufactured by CLM srl,	CLM Vesuvio oven instruction manual reference "Instruction and maintenance manual ENGLISH version Review	'CalorPan' 100% beech briquette, octagonal section, length 260-300mm, width and height 75-90mm manufactured
Via I Maggio 35, 31043, Fontanelle (Treviso), Italy.	0.1" dated 29th November 2011.	from dried beech sawdust (1).
View 3 (3.8kW) and View 5 (4.9kW) multifuel stoves; View 5 (4.9kW) wood stove. Manufactured by Stovax Ltd., Falcon Road, Sowton	Instruction manual reference "PM485 Issue 1" dated June 2010 and smoke control kit instruction manual reference "PM490 Issue 1" dated June 2010.	Wood logs ⁽¹⁾ .
Industrial Estate, Exeter, Devon, EX2 7LF.	The appliance must be fitted with a permanent stop to prevent closure of the secondary air control below the 50% open position.	
View 7 (7kW) inset appliance Product code VW-7NMF. Manufactured by Stovax Ltd.,	Instruction manual reference "PM552 - Issue 1" dated June 2011 and smoke control kit instruction manual reference	Wood logs ⁽¹⁾ .
Falcon Road, Sowton Industrial Estate, Exeter,	"PM490 Issue 2" dated July 2011.	
Devon, EX2 7LF.	The appliance must be fitted with a permanent stop on the secondary air inlet to prevent closure beyond the 50% open position.	
Vista Magnifico SE & Vista Perfetto SE 4.9kW wood burning stoves.	Newman Fireplaces Ltd.'s Instruction manual reference "1-2" dated 24th October 2011.	Wood logs ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Manufactured by Ciang Stoves Ltd., South Chuangye Road, (Hanling Industrial Estate), Beiguan Section, Anyang City, Henan Provence, China 455000.	The appliance must be fitted with mechanical stops to prevent closure of the secondary air control beyond the 30% open position and the tertiary air beyond the 50% open position.	
Vista Magnifico SE NS-1 and Vista Perfetto SE NS-2	Installation and user instruction manual dated 3rd June 2014, reference "NS-1, NS-2 Edition: 2"	Wood logs (1)
4.9kW multi-fuel stoves. Manufactured by Newman Fireplaces Ltd Units 6 & 7 Rawreth Barns, Dollymans Farm, Doublegate Lane, Rawreth, Wickford, Essex, SS11 8UD	The appliance must be fitted with mechanical stops to prevent closure of the secondary air control beyond the 30% open position	
Vitae 06C inset stove. Manufactured by Heat Design, 30 Hawthorn Road, Western Industrial Estate, Naas Road, Dublin 12, Ireland.	Instruction manual reference "VIT06C" dated 26th July 2012. The appliance must be fitted with a permanent stop to prevent closure of the secondary air control beyond 20% open.	Wood logs ⁽¹⁾ .
Vitae 11C inset stove. Manufactured by Heat Design, 30 Hawthorn Road, Western Industrial Estate, Naas Road, Dublin 12, Ireland.	Instruction manual reference "VIT11C" dated 26th July 2012. The appliance must be fitted with a permanent stop to prevent closure of the secondary air control beyond 20% open.	Wood logs ⁽¹⁾ .
Vitoligno 300-P models 12, 18, 24, 32, 40 and 48 pellet boilers.	Operating instructions reference "5592 617 GB" dated January 2014 and Vitoligno 300-P Technical	Wood pellets ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Manufactured by Viessmann Limited, Hortonwood 30, Telford, TF1 7YP.	guide reference "5414 644 GB" dated January 2014.	
Volan 750 Glass and Vega 75-Glass 7.5kW multifuel stove.	Instruction manual dated 28th July 2015, reference: "Triton 450 / Vega 450 / Volan 750 /	Wood Logs ⁽¹⁾ .
Manufactured by F.E.Robinson(Hooton)Limited,	Vega 750 Solid Fuel Stoves Manual Version 1.1 Issued 28/07/2015	
Station Works, Hooton Road,		
Hooton, South Wirral,		
CH66 7NF		
Warm 1 and 4 stoves.	Instruction manual reference "11-1a" dated February 2012.	Wood logs ⁽¹⁾ .
Manufactured by Color Emajl d.o.o., Alaginci 87/a, HR-34000 Požega, Croatia.	The appliance must be fitted with a mechanical stop to prevent closure of the secondary air control beyond the 83mm open position.	
Warm 2 and 5 stoves.	Instruction manual reference "11-1b" dated February 2012.	Wood logs ⁽¹⁾ .
Manufactured by Color Emajl d.o.o., Alaginci 87/a, HR-34000 Požega, Croatia.	The appliance must be fitted with a mechanical stop to prevent closure of the secondary air control beyond the 83mm open position.	
Warmflow WS18 and WP 18 Pellet Boilers	Boiler Manual for Wood Pellet Boiler WS18/WP18 reference "CODE 4220 Issue 1." dated	Wood pellets ⁽¹⁾ .
Manufactured by Warmflow Engineering Co Limited, Lissue Industrial Estate, Moira Road, Lisburn, Northern Ireland, BT28 2RF.	May 2014.	
Warmington SE multi-fuel stove	Instruction manual reference "NS-10 Edition 1" dated 17th September 2014.	Wood logs ⁽¹⁾ .
Manufactured by Newman Fireplaces Ltd, Units 6&7,	-	regult of treatment with wood presentatives

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Rawreth Barns, Dollyman's Farm, Doublegate Lane, Rawreth, Wickford, Essex, SS11 8UD.	The appliance must be fitted with the manufacturer's smoke control kit (Newman fireplaces part number 59) to prevent closure of the secondary air control beyond the 30% open position.	
Westcott 5SE. Manufactured by Dimplex, GDC Group Ltd., Millbrook House, Grange Drive, Hedge End Southampton, SO30 2DF.	The instruction manual reference "08/51351/0 - Issue 0" dated 7th September 2010.	Wood logs ⁽¹⁾ .
Westfire Series One stove and Westfire Series Two stove. Manufactured by Westfire Tømrervej 3 DK-6800 Varde, Denmark.	Installation manual and operating instructions and supplementary instruction manual reference "Westfire supplementary instructions June 2011/Version 1" dated 1st June 2011.	Wood logs ⁽¹⁾ .
	The appliance must be fitted with a permanent stop to prevent closure of the secondary air control less than 50% open.	
Westfire Uniq 15, 16 and 20 (also known as WF UNIQ 15, 16 and 20). Manufactured by Westfire Tømrervej 3 DK-6800 Varde, Denmark.	Manufacturer's instructions reference "WF15 – WF16 – WF20" dated 2007 and supplementary instructions reference "01 wfuk.2207" dated 2007.	Untreated dry wood ⁽¹⁾ .
	The appliance must be fitted with a permanent stop on the secondary air inlet to prevent closure beyond 50mm.	
Westfire Uniq 17, Westfire Uniq 18, Westfire Uniq 19, Westfire Uniq 23, Westfire Uniq 23 side Glass and Westfire Uniq 23 Inset.	Instruction manual reference "Westfire Supplementary Instructions June 2010" dated June 2010.	Wood logs ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
Manufactured by Westfire APS, Tømrervej 3, DK-6800 Varde, Denmark.	The fireplace must be installed, maintained and operated in accordance with the following specifications: The appliance must be fitted with a mechanical stop to prevent closure of the air slide beyond the 30mm open position.	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Westfire Uniq 21 stove, Westfire Uniq 21 pedestal stove and Westfire Uniq 21 wall hung stove. Manufactured by Westfire APS, Tømrervej 3, DK-6800 Varde, Denmark.	Installation manual and operating instructions and supplementary instruction manual reference "Westfire supplementary instructions June 2011/Version 1" dated 1st June 2011. The appliance must be fitted with a permanent stop to prevent closure of the secondary air control less than 60% open.	Wood logs ⁽¹⁾ .
Westfire Uniq 26 stove, Westfire Uniq 27 stove and Westfire Uniq 28 stove. Manufactured by Westfire APS, Tømrervej 3, DK-6800 Varde, Denmark.	Installation manual and operating instructions and supplementary instruction manual reference "Westfire supplementary instructions June 2011/Version 1" dated 1st June 2011. The appliance must be fitted with a permanent stop to the secondary air slider control to prevent closure more than 20mm from the fully closed position.	Wood logs ⁽¹⁾ .
Westfire Uniq 32 Inset stove and Westfire Uniq 32 Freestanding stove. Manufactured by Westfire APS, Tømrervej 3, DK-6800 Varde, Denmark.	Installation manual and operating instructions and supplementary instruction manual reference "Westfire supplementary instructions June 2011/Version 1" dated 1st June 2011. The appliance must be fitted with a permanent stop to prevent closure of the	Wood logs ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications: secondary air control less than 50% open.	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Westfire Uniq 33 SE Westfire Uniq 33 side glass SE Westfire Uniq 34 SE	Installation manual and operating instructions reference "UNIQ33/34V1" dated 2012.	Wood logs ⁽¹⁾ .
Westfire Uniq 34 side glass SE multi-fuel 6.1 kW stoves Manufactured by Westfire ApS, Tømrervej 3, VARDE, DK-6800, Denmark.		
Westfire Uniq 35 SE Freestanding multi-fuel 4.3 kW stove, Westfire Uniq 35 SE Pedestal multi-fuel 4.3kW stove, Westfire Uniq 35 SE Inset with 3 sided frame multi- fuel 4.3kW stove and Westfire Uniq 35 SE Inset with 4 sided frame multi-fuel 4.3kW stove. Manufactured by Westfire	Installation manual and operating instructions reference "WF35" dated 2013. The appliance must be fitted with the manufacturer's smoke reduction kit to prevent closure of the secondary air control beyond 25% open.	Wood logs ⁽¹⁾ .
ApS, Tomrervej 3, VARDE, DK-6800, Denmark.		
Wiking Miro 1,2,3,4,5 and 6 4.9kW wood-burning stoves. Manufactured by HWAM Heat Design AS Nydamsvej 53, 8362 Hørning, Denmark	Operating and Maintenance Instructions dated January 2013 reference "IN1274 Ed A" Fitted with a mechanical stop to prevent air control closure beyond the 12mm open position	Wood Logs ⁽¹⁾ .
Windhager BioWin 90 and 120. Manufactured by Windhager Zentralheizung GmbH, Anton-Windhager-Str. 20, A-5201 Seekirchen bei Salzburg, Austria.	Manufacturer's instructions reference "092125/00" dated August 2008.	Wood pellets ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Windhager BioWin 100, 150, 210 and 260.	Manufacturer's instruction manual reference "0916197/00" dated May	Wood pellets ⁽¹⁾ .
Manufactured by Windhager Zentralheizung GmbH, Anton- Windhager-Str. 20, A-5201 Seerkirchen bei Salzburg, Austria.	2008.	
Windhager Bio Win 350, 450 and 600 35, 45 and 60kW pellet boilers.	Operating manual reference "093209/02" dated July 2013 and installation instructions manual reference "093212/04"	Wood pellets ⁽¹⁾ .
Manufactured by Windhager Zentralheizung GmbH, Anton- Windhager-Str. 20, A-5201 Seerkirchen bei Salzburg, Austria.	dated July 2013.	
Windhager FireWyn 90 and 120.	Instruction manual reference "092125/00" dated August 2007.	Wood pellets ⁽¹⁾ .
Manufactured by Windhager Zentralheizung GmbH, Anton- Windhager-Str.20, A-5201 Seekirchen bei Salzburg, Austria.		
Wood Energy Solutions E- Compact 15 Slim and 18 Slim Wood Pellet Boilers.	Installation and operation manual reference "V.1.1" dated June 2014.	Wood pellets ⁽¹⁾ .
Manufactured by Wood Energy Solutions Limited, Donaskeigh, Tipperary, Co. Tipperary, Ireland.		
Wood Energy Solutions E- Compact 55 Wood Pellet Boiler.	Installation and operating manual reference "Manual Edition: E-COMPACT	Wood pellets ⁽¹⁾ .
Manufactured by Wood Energy Solutions Ltd., Donaskeigh, Tipperary, Co. Tipperary, Ireland.	55_December 2012 Issue 1" dated December 2012.	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Wood Energy Solutions E-Compact 85, 100, & 125 Wood Pellet Boilers. Manufactured by Wood Energy Solutions Ltd., Donaskeigh, Tipperary, Co. Tipperary,	Installation and operating manual reference "Manual Edition: E-COMPACT Commercial Series_85-125" dated May 2012.	Wood pellets ⁽¹⁾ .
Wood Energy Solutions E- Compact 199 Wood Pellet Boiler.	Installation and operating manual reference "Manual Edition: E-COMPACT Commercial Series_199" dated	Wood pellets ⁽¹⁾ .
Manufactured by Wood Energy Solutions Ltd., Donaskeigh, Tipperary, Co. Tipperary, Ireland.	May 2012.	
Wood Fired Ovens by Jamie Oliver Ltd.'s GR Valoriani Ristorante 100; Wood Fired Ovens by Jamie Oliver Ltd.'s OT Valoriani Ristorante 100.	Instruction manual reference "OOLinst.8 GR 100 and OT 100 v2" dated January 2011.	Untreated wood of less than 20% moisture ⁽¹⁾ .
Manufactured by Valoriani of Via Caselli alla Fornace, 213, 50066 Reggello, Firenze, Italy.		
Wood Fired Ovens by Jamie Oliver Ltd.'s GR Valoriani Ristorante 120; Wood Fired Ovens by Jamie Oliver Ltd.'s OT Valoriani Ristorante 120.	Instruction manual reference "OOLinst.9 GR 120 and OT 120 v2" dated January 2011.	Untreated wood of less than 20% moisture ⁽¹⁾ .
Manufactured by Valoriani of Via Caselli alla Fornace, 213, 50066 Reggello, Firenze, Italy.		
Wood Fired Ovens by Jamie Oliver Ltd.'s GR Valoriani Ristorante 140; Wood Fired Ovens by Jamie Oliver Ltd.'s OT Valoriani Ristorante 140.	Instruction manual reference "OOLinst.10 GR 140 and OT 140 v2" dated January 2011.	Untreated wood of less than 20% moisture ⁽¹⁾ .
Manufactured by Valoriani of Via Caselli alla Fornace, 213, 50066 Reggello, Firenze, Italy.		

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Wood Fired Ovens by Jamie Oliver Ltd.'s GR Valoriani Ristorante 120x160; Wood Fired Ovens by Jamie Oliver Ltd.'s OT Valoriani Ristorante 120x160.	Instruction manual reference "OOLinst.11 GR 120x160 and OT 120x160 v2" dated January 2011.	Untreated wood of less than 20% moisture ⁽¹⁾ .
Manufactured by Valoriani of Via Caselli alla Fornace, 213, 50066 Reggello, Firenze, Italy.		
Wood Fired Ovens by Jamie Oliver Ltd.'s GR Valoriani Ristorante 140x160; Wood Fired Ovens by Jamie Oliver Ltd.'s OT Valoriani Ristorante 140x160.	Instruction manual reference "OOLinst.12 GR 140x160 and OT 140x160 v2" dated January 2011.	Untreated wood of less than 20% moisture ⁽¹⁾ .
Manufactured by Valoriani of Via Caselli alla Fornace, 213, 50066 Reggello, Firenze, Italy.		
Wood Fired Ovens by Jamie Oliver Ltd.'s GR Valoriani Ristorante 140x180; Wood Fired Ovens by Jamie Oliver Ltd.'s OT Valoriani Ristorante 140x180.	Instruction manual reference "OOLinst.13 GR 140x180 and OT 140x180 v2" dated January 2011.	Untreated wood of less than 20% moisture ⁽¹⁾ .
Manufactured by Valoriani of Via Caselli alla Fornace, 213, 50066 Reggello, Firenze, Italy.		
Wood Fired Ovens by Jamie Oliver Ltd.'s GR Valoriani Ristorante 180; Wood Fired Ovens by Jamie Oliver Ltd.'s OT Valoriani Ristorante 180.	Instruction manual reference "OOLinst.14 GR 180 and OT 180 v2" dated January 2011.	Untreated wood of less than 20% moisture ⁽¹⁾ .
Manufactured by Valoriani of Via Caselli alla Fornace, 213, 50066 Reggello, Firenze, Italy.		
Wood Fired Ovens by Jamie Oliver Ltd.'s Valoriani Casa 80.	Instruction manual reference "OOLinst.1 FVR 80 v2" dated January 2011.	Untreated wood of less than 20% moisture ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Manufactured by Valoriani of Via Caselli alla Fornace, 213, 50066 Reggello, Firenze, Italy.		
Wood Fired Ovens by Jamie Oliver Ltd.'s Valoriani Casa 100.	Instruction manual reference "OOLinst.2 FVR 100 v2" dated January 2011.	Untreated wood of less than 20% moisture ⁽¹⁾ .
Manufactured by Valoriani of Via Caselli alla Fornace, 213, 50066 Reggello, Firenze, Italy.		
Wood Fired Ovens by Jamie Oliver Ltd.'s Valoriani Casa 110.	Instruction manual reference "OOLinst.3 FVR 110 v2" dated January 2011.	Untreated wood of less than 20% moisture ⁽¹⁾ .
Manufactured by Valoriani of Via Caselli alla Fornace, 213, 50066 Reggello, Firenze, Italy.		
Wood Fired Ovens by Jamie Oliver Ltd.'s Valoriani Casa 110x160.	Instruction manual reference "OOLinst.5 FVR 110x160 v2" dated January 2011.	Untreated wood of less than 20% moisture ⁽¹⁾ .
Manufactured by Valoriani of Via Caselli alla Fornace, 213, 50066 Reggello, Firenze, Italy.		
Wood Fired Ovens by Jamie Oliver Ltd.'s Valoriani Casa 120.	Instruction manual reference "OOLinst.4 FVR120 v2" dated January 2011.	Untreated wood of less than 20% moisture ⁽¹⁾ .
Manufactured by Valoriani of Via Caselli alla Fornace, 213, 50066 Reggello, Firenze, Italy.		
Wood Fired Ovens by Jamie Oliver Ltd.'s Valoriani Piccolo.	Instruction manual reference "OOLinst.15 Valoriani Piccolo v2" dated January 2011.	Untreated wood of less than 20% moisture ⁽¹⁾ .
Manufactured by Valoriani of Via Caselli alla Fornace, 213, 50066 Reggello, Firenze, Italy.		
Wood Fired Ovens by Jamie Oliver Ltd.'s Valoriani Villa 100.	Instruction manual reference "OOLinst.6 TOP 100 v2" dated January 2011.	Untreated wood of less than 20% moisture ⁽¹⁾ .
(4) 771 0 1		1. 0

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Manufactured by Valoriani of Via Caselli alla Fornace, 213, 50066 Reggello, Firenze, Italy.		
Wood Fired Ovens by Jamie Oliver Ltd.'s Valoriani Villa 120.	Instruction manual reference "OOLinst.7 TOP 120 v2" dated January 2011.	Untreated wood of less than 20% moisture ⁽¹⁾ .
Manufactured by Valoriani of Via Caselli alla Fornace, 213, 50066 Reggello, Firenze, Italy.		
Woodpecker 15, 25 and 45 wood pellet boilers.	Installation and operating manual reference "Issue 6" dated May 2012.	Wood pellets conforming to CEN TS 14961 ⁽¹⁾ .
Formerly manufactured by Garranlea Renewables Ltd., and now manufactured by Woodpecker Energy UK, Abbey Manor Business Centre, Preston Road, Yeovil, BA20 2EN.		
Woodpecker 50kW wood pellet boilers.	Instruction manual reference "Installation and Operating Manual Woodpecker 50 Model	Wood pellets conforming to CEN TS 14961 (a) (1).
Manufactured by Woodpecker Energy UK, Abbey Manor Business Centre, Preston Road, Yeovil, BA20 2EN.	Wood Pellet Boiler System Version 2" dated May 2012.	
Woodpecker Thermon 150 boiler.	Instruction manual reference "Installation and Operating manual Issue 2" dated	6mm wood pellets ⁽¹⁾ .
Manufactured by Woodpecker Energy UK, Abbey Manor Business Centre, Preston Road, Yeovil, BA20 2EN.	February 2012.	
Woodpecker Thermon 199kW pellet boiler.	Instruction manual reference "Issue 2.0" dated February 2012.	6mm wood pellets ⁽¹⁾ .
Manufactured by Woodpecker Energy UK, Abbey Manor Business Centre, Preston Road, Yeovil, BA20 2EN.		

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Woodpecker Thermon 200 boiler.	Instruction manual reference "Installation and Operating manual Issue 2" dated	6mm wood pellets ⁽¹⁾ .
Manufactured by Woodpecker Energy UK, Abbey Manor Business Centre, Preston Road, Yeovil, BA20 2EN.	February 2012.	
Woodpecker Thermon 250 boiler.	Instruction manual reference "Installation and Operating	6mm wood pellets ⁽¹⁾ .
Manufactured by Woodpecker Energy UK, Abbey Manor Business Centre, Preston Road, Yeovil, BA20 2EN.	manual Issue 2" dated February 2012.	
Woodpecker Thermon 300 boiler.	Instruction manual reference "Installation and Operating manual Issue 2" dated	6mm wood pellets ⁽¹⁾ .
Manufactured by Woodpecker Energy UK, Abbey Manor Business Centre, Preston Road, Yeovil, BA20 2EN.	February 2012.	
Woodwarm stoves Firebright SE multifuel insert stove.	Installation and operating instructions manual reference "Version INSSE" dated 1st	Wood logs ⁽¹⁾ .
Manufactured by Metal Developments Ltd., The	June 2013.	
Workshop, Wheatcroft Farm, Cullompton, Devon, EX15 1RA.	The appliance must be modified to prevent closure of the existing secondary air slide plate, located beneath the appliance, beyond the 3mm open position.	
Woodwarm stoves Firegem, Firewren and Fireblaze SE.	Installation and operating instructions manual reference "Version FSSE" dated 1st June	Wood logs ⁽¹⁾ .
Manufactured by Metal Developments Ltd., The	2013.	
Workshop, Wheatcroft Farm, Cullompton, Devon, EX15 1RA.	The appliance must be fitted with a system that prevents closure of the secondary air control beyond the 5mm open position.	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
33 1	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Woodwarm stoves Foxfire SE woodburning stove. Manufactured by Metal	Installation and operating instructions manual reference "Version FFSE" dated 1st June 2013.	Wood logs ⁽¹⁾ .
Developments Ltd., The Workshop, Wheatcroft Farm, Cullompton, Devon, EX15 1RA.	The appliance must be modified to fix the secondary bleed hole at a minimum of 75% open.	
Wood Waste Technology Ltd. WT5.	Manufacturer's instructions reference "WT5_v2" dated 16th February 2009.	Medium density fibreboard, chipboard, hardwood or softwood offcuts ⁽¹⁾ .
Manufactured by Wood Waste Technology Ltd., Units 1 and 2, Drummond Road, Astonfields Industrial Estate, Stafford, Staffordshire, ST16 3HJ.		softwood offedis .
Wood Waste Technology Heater, models WT10 and WT15.	Manufacturer's instructions reference "WT10" and "WT15" dated 19th January 2005.	Medium density fibreboard, chipboard, hardwood or softwood offcuts ⁽¹⁾ .
Manufactured by Wood Waste Technology Ltd., Units 1 and 2, Drummond Road, Astonfields Industrial Estate, Stafford, Staffordshire, ST16 3HJ.	2003.	
Wood Waste Technology WW199 (199kW output) biomass boiler and cyclone	Heating O&M Manual	Chipboard, medium density fibreboard, softwood and hardwood. All fuels to be chipped to a maximum size
Manufactured by Wood Waste Technology Limited, Units 1,2 and 3 Drummond Road, Astonfields Industrial Estate, Stafford, ST16 3HJ	2014.	of 15mm with a maximum moisture content of 30% Maximum fines (sawdust) content 50% (1).
Woody 5kW multifuel stove.	Installation and Operating Instructions manual dated June	Wood logs ⁽¹⁾ .
Manufactured by Chilli Penguin Stoves Limited, Castell Bach, Mynydd Nefyn,	2015 reference "CPS 9768" The appliance must be	
Pwllheli, LL53 6TL	fitted with a mechanical	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
	stop to prevent closure of the secondary air controller beyond 18mm from the closed position	
Worcester Greenstyle Bewdley 3 3.9kW wood burning stove. Manufactured by Bosch Thermotechnology Limited, Cotswold Way, Worcester, WR4 9SW, United Kingdom	Bewdley 3 Owner's Manual dated 01/02/2016 reference "852477-4201E", and Installation Manual Bewdley 3 dated 01/02/2016 reference "852470-4104E".	Wood logs ⁽¹⁾ .
With 75 W, Omice Peniguoni	The appliance must be fitted with a modification that prevents closure of the secondary air control beyond 34 mm open position.	
Worcester Greenstyle Bewdley 5 5kW wood burning stove.	Bewdley 5 Owner's Manual dated 01/02/2016 reference "852478-4201E", and	Wood logs ⁽¹⁾ .
Manufactured by Bosch Thermotechnology Limited, Cotswold Way, Worcester, WR4 9SW, United Kingdom	Installation Manual Bewdley 5 dated 01/02/2016 reference "852471-4105E".	
	The appliance must be fitted with a modification that prevents closure of the secondary air control beyond 35 mm open position.	
Worcester Greenstyle Bewdley 8 8kW wood burning stove.	Bewdley 8 Owner's Manual dated 01/02/2016 reference "852479-4201E", and	Wood logs ⁽¹⁾ .
Manufactured by Bosch Thermotechnology Limited, Cotswold Way, Worcester, WR4 9SW, United Kingdom	Installation Manual Bewdley 8 dated 01/02/2016 reference "852472-4004E".	
	The appliance must be fitted with a modification that prevents closure of the secondary air control beyond 10 mm open position.	
Worcester Greenstyle Hanbury 4 4.2kW wood burning stove.	Hanbury 4 Owner's Manual dated 01/02/2016 reference "852480-4201E", and	Wood logs ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fivonless	Conditions	
Class of fireplace		No fuel is to be used
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Manufactured by Bosch Thermotechnology Limited, Cotswold Way, Worcester, WR4 9SW, United Kingdom	Installation Manual Hanbury 4 dated 01/02/2016 reference "852473-4201E".	Tourney were or years.
	The appliance must be fitted with a modification that prevents closure of the secondary air control beyond 3.5 mm open position.	
Worcester Greenstyle Hanbury 5 5.5kW wood burning stove. Manufactured by Bosch Thermotechnology Limited, Cotswold Way, Worcester,	Hanbury 5 Owner's Manual dated 01/02/2016 reference "852481-4201E", and Installation Manual Hanbury 5 dated 01/02/2016 reference "852474-4201E".	Wood logs ⁽¹⁾ .
WR4 9SW, United Kingdom	The appliance must be fitted with a modification that prevents closure of the secondary air control beyond 3 mm open position.	
Worcester Greenstyle Hanbury 8 7.7kW wood burning stove. Manufactured by Bosch Thermotechnology Limited, Cotswold Way, Worcester,	Hanbury 8 Owner's Manual dated 01/02/2016 reference "852482-4201E", and Installation Manual Hanbury 8 dated 01/02/2016 reference "852475-4201E".	Wood logs ⁽¹⁾ .
WR4 9SW, United Kingdom	The appliance must be fitted with a modification that prevents closure of the secondary air control beyond 3mm open position.	
WTA WT Auto 200kW Airheater. Manufactured by Wood Waste Technology Ltd., Units 1 and 2, Drummond Road, Astonfields Industrial Estate, Stafford, Staffordshire, ST16 3HJ.	Instruction manual reference "WTA Installation Operation & Maintenance Instructions WTA v1 Issue A" dated April 2011.	Chipboard, medium density fibreboard, softwood, hardwood. All fuels to be chipped to a maximum size of 25mm and a maximum moisture content of 20%. Maximum fines (sawdust) content 5%. (1).

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
WTH 150 and WTH 200 boilers.	Installation manual "version 91 for Large Capacity Boiler WTH 150-200" reference "BA	Wood chips or wood pellets ⁽¹⁾ .
Manufactured by Hargassner Gesellschaft mit beschränkter Haftung (GmbH), Gunderding 8, A-4952, Weng, Austria.	GK V90b 0309".	
Xeoos 5kW stove Versions: Natur, Style, Harmony, Pur, Classic, Elegance and Stone;	Operating and installation instructions reference "Revisions – Index 01/08	Wood logs conforming to DIN 51731 ⁽¹⁾ .
Xeoos 8kW stove Versions: Basic, Pur, Classic, Elegance Stone and Air.	Fassung Januar 2008" dated January 2008.	
Manufactured by Specht Modulare Ofensysteme GmbH & Co, KG i.V. DiplIng. Frank Werner Projektmanagement Bahnhofstr, 2 D 35116 Hatzfeld.		
Yeoman CL3 (3.8kW) and CL5 (4.9kW) multifuel stoves; Yeoman CL5 (4.9kW) wood Stove.	Instruction manual reference "PM489 Issue 1" dated June 2010 and smoke control kit instruction manual "PM491 Issue 1" dated 5th April 2010.	Wood logs ⁽¹⁾ .
Manufactured by Stovax Ltd., Falcon Road, Sowton Industrial Estate, Exeter, Devon, EX2 7LF.	The appliance must be fitted with a permanent stop to prevent closure of the secondary air control below the 50% open position.	
Yeoman CL 7 (7kW) inset appliance Product code YM-CL7NMF.	Instruction manual reference "PM553 - Issue 1" dated June 2011 and smoke control kit instruction manual reference	Wood logs ⁽¹⁾ .
Manufactured by Stovax Ltd., Falcon Road, Sowton Industrial Estate, Exeter,	"PM491 Issue 2" dated June 2011.	
Devon, EX2 7LF.	The appliance must be fitted with a permanent stop on the secondary air inlet to prevent	esult of treatment with wood-preservatives

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
Course of firefrance	The fireplace must be installed, maintained and operated in accordance with the following specifications: closure beyond the 50% open position.	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Yeoman CL Milner Stove Product code YM-CLMB. Manufactured by Stovax Ltd., Falcon Road, Sowton Industrial Estate, Exeter, Devon, EX2 7LF.	Instruction manual reference "PM559 - Issue 1" dated June 2011 and smoke control kit instruction manual reference "PM491 Issue 2" dated June 2011. The appliance must be fitted with a permanent stop to prevent closure of the secondary air control below the 50% open position.	Wood logs ⁽¹⁾ .
Yeoman Devon - Multifuel, flat top, 1 door (9kW); Yeoman Devon - Multifuel, flat top, 2 door (9kW); Yeoman Devon - Multifuel, low canopy, 1 door (9kW); Yeoman Devon - Multifuel, low canopy, 2 door (9kW); Yeoman Devon - Multifuel, high canopy, 1 door (9kW); Yeoman Devon - Multifuel, high canopy, 2 door (9kW). Manufactured by Stovax Ltd., Falcon Road, Sowton Industrial Estate, Exeter, Devon, EX2 7LF.	Instruction manual reference "PM184 Issue 3" dated February 2008 and smoke control kit instruction manual "PM403 Issue 1" dated January 2010. The appliance must be fitted with a permanent stop to prevent closure of the secondary air control below the 50% open position and a system must be fitted that ensures a gap of 1mm for bleed of primary air when the spin wheels are rotated to their closed positions must be fitted.	Wood logs ⁽¹⁾ .
Yeoman Exmoor - Multifuel, flat top (4.9kW); Yeoman Exmoor - Multifuel, low canopy (4.9kW); Yeoman Exe - Multifuel, flat top, 1 door (4.9kW); Yeoman Exe - Multifuel, flat top, 2 door (4.9kW); Yeoman Exe - Multifuel, low canopy, 1 door (4.9kW); Yeoman Exe - Multifuel, low canopy, 2 door (4.9kW);	Instruction manual reference "PM184 Issue 3" dated February 2008 and smoke control kit instruction manual "PM403 Issue 1" dated January 2010. The appliance must be fitted with a permanent stop to prevent closure of the secondary air control below the 60% open position and a system that prevents full	Wood logs ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
	closure of the primary air controls must be fitted.	
Monterrey 7SE and Monroe	Instruction manual reference "GB12A Version 1" dated February 2013.	Wood logs ⁽¹⁾ .
Fires Ltd., Knights Way, Battlefield Enterprise Park, Shrewsbury, Shropshire, SY1	The appliance must be fitted with a system that prevents the closure of the secondary air slider beyond the 10mm open position.	
Monterrey 5 SE and Monroe 5	Instruction manual reference "GB12A Version 1" dated February 2013.	Wood logs ⁽¹⁾ .
Fires Ltd., Knights Way, Battlefield Enterprise Park, Shrewsbury, Shropshire, SY1	The appliance must be fitted with a system that prevents the closure of the secondary air slider beyond the 8mm open position.	
Granada model F9437 G,	Installation and Operation Manual dated 27th July 2015 reference "ZARAGOZA – Version A"	Wood logs ⁽¹⁾ .
F9437 P,	The appliance must be fitted with a modified air regulator which has a permanent	
,	opening of 388mm2 when in the fully closed position	
Zaragoza Box model F9437 B,		
Caen ceramic model F9437 C and, Caen soapstone model F9437 S 5kW multifuel stoves.		
Manufactured by THORMA Vyroba k.s., Šavoľská cesta 323/1, 986 01,		
Fil'akovo-Priemyselný obvod,		

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Class of fireplace	Conditions
	The fireplace must be No fuel is to be used
	installed, maintained and in the fireplace other than
	operated in accordance with authorised fuels and the
	the following specifications: following fuel or fuels:
Slovakia	

The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives
or coatings.

EXPLANATORY NOTE

(This note is not part of the Order)

This Order revokes and replaces with amendments the Smoke Control Areas (Exempted Fireplaces) (Wales) Order 2015 (S.I. 2015/1513) (W. 175).

Section 20 of the Clean Air Act 1993 ("the 1993 Act") places a general prohibition on the emission of smoke in smoke control areas.

The Welsh Ministers may, by order made under section 21(5) of the 1993 Act, exempt, in relation to Wales, specified classes of fireplace from the provisions of section 20, if they are satisfied that such fireplaces can be used for burning fuel other than authorised fuels without producing any smoke or a substantial quantity of smoke.

Article 2 of this Order exempts the classes of fireplace listed in the first column of the Schedule to this Order from the provisions of section 20 of the 1993 Act, subject to the conditions in the second and third columns of that Schedule in relation to that class of fireplace.

The Welsh Ministers' Code of Practice on the carrying out of Regulatory Impact Assessments was considered in relation to this Order. As a result, it was not considered necessary to carry out a regulatory impact assessment as to the likely costs and benefits of complying with this Order.