

ANNEX

3. SPECIAL PROVISIONS FOR METAL AEROSOL DISPENSERS

3.1. Capacity

The total capacity of these containers may not exceed 1 000 ml.

3.1.1. Test pressure of the container

- (a) For containers filled at a pressure of less than 6·7 bars at 50° C, the test pressure must be equal to at least 10 bars.
- (b) For containers filled at a pressure equal to or greater than 6·7 bars at 50° C, the test pressure must be 50 % higher than the internal pressure at 50° C.

[^{F1}3.1.2. The pressure at 50 °C in the aerosol dispenser must not exceed the values provided for in the following table, depending upon the content of gases in the aerosol dispenser:

Content of gases	Pressure at 50 °C
Liquefied gas or mixture of gases having a flammable range with air at 20 °C and a standard pressure of 1,013 bar	12 bar
Liquefied gas or mixture of gases not having a flammable range with air at 20 °C and a standard pressure of 1,013 bar	13,2 bar
Compressed gases or gases dissolved under pressure not having a flammable range with air at 20 °C and a standard pressure of 1,013 bar	15 bar]

.....

Textual Amendments

- F1** Substituted by [Commission Directive \(EU\) 2016/2037](#) of 21 November 2016 amending [Council Directive 75/324/EEC](#) as regards the maximum allowable pressure of aerosol dispensers and to adapt its labelling provisions to [Regulation \(EC\) No 1272/2008](#) of the European Parliament and of the Council on classification, labelling and packaging of substances and mixtures (Text with EEA relevance).

.....

^{F2}3.1.3. Volume of the liquid phase

.....

.....

Textual Amendments

- F2** Deleted by [Commission Directive 2008/47/EC](#) of 8 April 2008 amending, for the purposes of adapting to technical progress, [Council Directive 75/324/EEC](#) on the approximation of the laws of the Member States relating to aerosol dispensers (Text with EEA relevance).