

Council Directive of 26 May 1986 on the approximation of the laws of the Member States relating to tyre pressure gauges for motor vehicles (86/217/EEC) (repealed)

Article 1
Article 2
Article 3
Article 4
Article 5
Signature

ANNEX

1. Scope
2. Metrological requirements
 - 2.1. Maximum permissible errors
 - 2.2. Variation due to temperature
 - 2.3. Hysteresis error
 - 2.4. Return of the instrument's index to a predetermined mark
3. Technical requirements
 - 3.1. Construction
 - 3.2. Indicating device
 - 3.2.1.
 - 3.2.2.
 - 3.2.3. The scale intervals must be equal over the entire scale...
4. Inscriptions and marks
 - 4.1. Inscriptions
 - 4.1.1. Compulsory inscriptions
 - 4.1.2. Optional inscriptions
 - 4.2. Verification and sealing marks
5. EEC pattern approval
 - 5.1. Verification of compliance with technical and metrological requirements
 - 5.1.1. Determination of instrument error
 - 5.1.2. Determination of hysteresis error
 - 5.1.3. Examination of the stability of the properties of pressure gauges...
 - 5.1.4. Variation due to temperature
6. EEC initial verification
 - 6.1. Examination of conformity
 - 6.2. Verification tests
 - 6.2.1. Determination of errors
 - 6.2.2. Determination of hysteresis error