

Directive 2009/76/EC of the European Parliament and of the Council of 13 July 2009 relating to the driver-perceived noise level of wheeled agricultural or forestry tractors (Codified version) (Text with EEA relevance) (repealed)

Article 1
Article 2
Article 3
Article 4
Article 5
Article 6
Article 7
Article 8
Article 9
Signature	

ANNEX I

APPARATUS, CONDITIONS AND METHOD OF MEASUREMENT

1. UNIT OF MEASUREMENT AND MEASURING APPARATUS
 - 1.1. Unit of measurement
 - 1.2. Measuring apparatus
2. CONDITIONS OF MEASUREMENT
3. METHOD OF MEASUREMENT
 - 3.1. The microphone must be located 250 mm to the side...
 - 3.2. The maximum noise level in dB(A) shall be determined as...
 - 3.3. The test report shall include noise-level measurements carried out under...
4. ASSESSMENT CRITERIA

ANNEX II

APPARATUS, CONDITIONS AND METHOD OF MEASUREMENT

1. UNIT OF MEASUREMENT AND MEASURING APPARATUS
 - 1.1. Unit of measurement
 - 1.2. Measuring apparatus
2. CONDITIONS OF MEASUREMENT
3. METHOD OF MEASUREMENT
 - 3.1. The microphone must be located 250 mm to the side...
 - 3.2. Noise level shall be determined as follows:
4. ASSESSMENT CRITERIA

ANNEX III

DETERMINATION OF SEAT REFERENCE POINT

- 1. DEFINITION
 - 1.1.
- 2. DETERMINATION OF SEAT REFERENCE POINT
 - 2.1.
 - 2.2.
- 3. DESCRIPTION OF THE DEVICE
 - 3.1.
 - 3.2.
- 4. SETTING UP THE DEVICE

Appendix

ANNEX IV

PART A

PART B

ANNEX V

.....