

## 1986 No. 115

## ROAD AND RAILWAY TRANSPORT

## Level Crossing (Lurgan (Bells Row)) Order (Northern Ireland) 1986

Made . . . . . 29th April 1986

Coming into operation . . . . . 29th July 1986

The Department of the Environment(a) in exercise of the powers conferred on it by section 66 of the Transport Act (Northern Ireland) 1967(b) and of all other powers enabling it in that behalf, having received from the railway undertaking an application under the said section 66, makes the following Order:

*Citation, commencement and interpretation*

1.—(1) This Order may be cited as the Level Crossing (Lurgan (Bells Row)) Order (Northern Ireland) 1986 and shall come into operation on 29th July 1986.

(2) In this Order “the crossing” means the Lurgan (Bells Row) Level Crossing in the townland of Drumnamoe and County of Armagh whereby the road known as Bells Row is crossed by the railway between Lisburn and Portadown stations.

*Suspension of statutory provisions*

2. While this Order remains in force—

- (a) section 47 of the Railways Clauses Consolidation Act 1845(c) (requirements as to gates);
- (b) section 6 of the Railways Clauses Act 1863(d) (requirements as to lodges, etc.);
- (c) any other statutory provision imposing requirements to the same or similar effect as those contained in the enactments mentioned in paragraphs (a) and (b);

shall not apply in relation to the crossing.

*Provision of automatic equipment*

3. The railway undertaking shall at the crossing—

- (a) provide, maintain and operate the barriers, lights and automatic and other devices, excluding traffic signs, specified in Schedules 1 and 2 and shall give notice in writing to the Department of the Environment as soon as the provision thereof is complete;
- (b) secure the provision, maintenance and operation of the traffic signs specified in Schedule 1;
- (c) comply with the conditions and requirements specified in Schedule 2.

---

(a) The functions of the Ministry of Development under the Transport Act (Northern Ireland) 1967 transferred to the Department of the Environment by S.R. & O. (N.I.) 1973 No. 504 Art. 4  
 (b) 1967 c. 37 (N.I.) as amended by S.I. 1984/1986 (N.I. 15) Art. 15  
 (c) 1845 c. 20  
 (d) 1863 c. 92

Sealed with the Official Seal of the Department of the Environment on 29th April 1986.

(L.S.)

*J. M. Irvine*

Assistant Secretary

## SCHEDULE 1

## PARTICULARS OF BARRIERS, LIGHTS, TRAFFIC SIGNS AND OTHER DEVICES AND APPLIANCES

1. A barrier shall be pivoted as close to the railway as practicable on the nearside of the road on each side of the railway.

2. It shall be possible to raise and lower the barriers. When lowered the barriers shall be as nearly horizontal as possible, and as nearly as possible at right angles to the centre line of the carriageway and shall extend across the nearside of the carriageway. The tip of each barrier shall extend to a point between 150mm and 450mm from the centre of the carriageway and a clear exit of at least 3 metres of carriageway width shall be left to the offside edge of the carriageway.

3. When the barriers are fully lowered their uppermost surfaces shall be not less than 900mm above the road surface at the centre of the carriageway and the underclearance between the barriers and the road surface shall not exceed 1000mm.

4. When in the fully raised position the barriers shall be inclined towards the carriageway at an angle of between 5 and 10 degrees from the vertical. No part of either barrier or of any attachment thereto which is less than 5 metres above the level of the carriageway shall be horizontally displaced from the nearer edge of the carriageway by less than 450mm. No part of any barrier or of any attachment thereto which is less than 2 metres above the level of either footway shall be horizontally displaced from that edge of the footway further from the carriageway by less than 150mm.

5. The barriers shall be as light as possible but shall also be strong enough to prevent distortion or fracture likely to be caused by wind pressure. It shall be possible to raise them by hand.

6. Two electric lamps, each of not less than 5 watts nominal rating and with lenses of not less than 50mm diameter, shall be fitted to each barrier, one within 150mm of its tip and the other near its centre. When illuminated the lamps shall show a red light in each direction along the carriageway.

7. The barriers shall display on both front and rear faces alternate red and white bands each approximately 600mm long and to the full depth of the barriers. A band of red retro-reflecting material not less than 50mm deep shall be provided along the full length of each red band.

8. Suitable screening shall be provided for each barrier machine to guard against danger to persons from the operating mechanism and moving parts of the machine.

9. A traffic light signal as prescribed by regulation 13(4) of the Regulations shall be provided adjacent to each barrier pivot post not more than 1 metre before the barrier. There shall be an additional traffic light signal of the same type on the offside of the road on each side of the railway so located as to be either in line with or on the railway side of the stop line mentioned in paragraph (11). The traffic light signals on each side of the railway shall be so positioned as to face outwards from the crossing towards approaching road traffic. All the signals shall be capable of directional adjustment.

10. An audible warning device shall be provided on or adjacent to each barrier pivot post.

11. A light signal for pedestrians, having a lens with an effective diameter of not less than 195mm or not more than 220mm and which, when illuminated, shows a symbol of the size, colour and type shown in Department of Transport Drawing WBM 248, shall be provided below or adjacent to each road traffic light signal, shall be so positioned as to face outwards towards pedestrians approaching the crossing and shall be capable of directional adjustment.

12. A reflectorised stop line of the size and type shown in Diagram 1001 in the Regulations shall be provided across the nearside of the carriageway on each side of the railway not more than 1 metre before the nearside traffic light signal.

13. A reflectorised pedestrian stop line of the size and type shown in Diagram 1003.2 in the Regulations shall be provided across the offside of the carriageway and any made-up ground on both sides of the carriageway on both sides of the railway. The line shall be not less than 1 metre before the traffic light signal on the same side of the carriageway and not nearer than 2 metres to the running edge of the nearest rail and shall be as nearly as possible at right angles to the centre line of the carriageway.

14. Where the road passes over the crossing, reflectorised edge of carriageway road markings of the size and type shown in Diagram 1011 in the Regulations shall be provided along each edge of the made-up ground along each edge of the carriageway.

15. The centre line of the carriageway shall be marked on the crossing between the stop lines mentioned above and for a distance of 12 metres on each side of the railway measured along the centre of the carriageway from the stop lines with a reflectorised double continuous line road marking of the size and type shown in Diagram 1013.1 in the Regulations. The centre line shall be continued for a distance of 13 metres on each side of the railway measured along the centre of the carriageway from the ends of the double continuous line with a reflectorised double line of the size and type also shown in Diagram 1013.1 in the Regulations wherein the continuous line is on the nearside of the broken line.

16. A traffic sign of the size, colour and type shown in Diagram 863 in the Regulations shall be provided below or adjacent to each traffic light signal and shall face outwards from the crossing towards approaching road traffic.

17. A traffic sign of the size, colour and type shown in Diagram 828.2 in the Regulations shall be provided on or adjacent to the offside traffic light signal post on each side of the railway angled to face drivers of vehicles halted at the stop line.

18. A traffic sign of the size, colour and type shown in Diagram 649.1 in the Regulations shall be provided on each road approach to the crossing facing traffic approaching the crossing.

19. A telephone mounted in a cabinet and connected to Portadown Signal Box shall be provided on or adjacent to each offside traffic light signal post. A traffic sign of the size, colour and type shown in Diagram 854 in the Regulations shall be provided on the door and on at least two of the other faces of the cabinet. Suitable illuminated notices giving instructions to users shall be provided and maintained in each cabinet.

20. Two independent power supplies shall be provided at the crossing, one of which may consist of standby batteries of sufficient capacity to operate the whole installation for 12 hours.

21. In this Schedule—

“nearside” means the left-hand side of the road or carriageway in relation to a person approaching the crossing along the road or carriageway;

“offside” means the right-hand side of the road or carriageway in relation to any such person;

“the Regulations” means the Traffic Signs Regulations (Northern Ireland) 1979(a).

## SCHEDULE 2

## CONDITIONS AND REQUIREMENTS TO BE COMPLIED WITH BY THE RAILWAY UNDERTAKING

1. The carriageway shall be approximately 7.0 metres wide at the crossing.
2. The ground at the two edges of the carriageway over the crossing shall be made-up to the level of the carriageway for a distance of not less than 1 metre beyond each edge.
3. A footway shall be retained on the made-up ground.
4. The surface of the carriageway over the crossing shall be maintained in good and even condition.
5. Cattle-cum-trespass guards of standard railway design shall be provided adjacent to the ground which is made-up to the level of each carriageway. The guards shall extend the full distance between the fences on each side of the railway.
6. The barriers shall be kept in the fully raised position except during the time when engines, carriages or other vehicles passing along the railway have occasion to cross the road.
7. The electric lamps on each barrier mentioned in Schedule 1 shall be lit at all times except when the barriers are in the fully raised position.
8. If the road approaches to the crossing are lit the crossing shall be lit to at least the same standard.
9. Visual indicators and an audible alarm shall be provided in Portadown Signal Box. The indicators shall show when the barriers are raised and when the main power supply is available and the alarm shall sound if a period of approximately 3 minutes elapses and there is no indication that the barriers are raised.
10. The barriers, the audible warning devices and the traffic light signals mentioned in Schedule 1 shall be activated automatically, as described in paragraph (11) by the approach of a train but means shall also be provided at the crossing for their manual operation and control.
11. When the train either occupies a track circuit or operates a treadle the audible warning devices and the pedestrian and traffic light signals shall begin to operate and the barriers shall be lowered in accordance with the following sequence:—
  - (a) The amber lights shall show and the audible warning shall begin. The lights shall show for approximately 3 seconds.
  - (b) Immediately the amber lights are extinguished the intermittent red lights and the pedestrian signals shall begin to show.
  - (c) 4 to 8 seconds later the barriers shall begin to descend and shall take a further 6 to 8 seconds to reach the lowered position.
  - (d) Not less than 27 seconds shall elapse between the time when the amber lights first show and the time when the train reaches the crossing.
  - (e) The intermittent red lights and pedestrian signals shall continue to show and the audible warning devices shall continue to sound until the barriers have begun to rise and all shall be switched off before the barriers have risen to an angle of 45 degrees above the horizontal.
12. The barriers shall both rise as soon as the train has passed the crossing, provided that if another train is approaching the crossing, they shall only be raised if a minimum of 10 seconds, reckoned from the time they begin to lower, can elapse before the arrangements detailed in paragraph (11) are due to recommence.
13. In the event of failure of all the intermittent red lights facing in one direction or of a total power failure both barriers shall descend under gravity or remain lowered as the case may be. If, after the barriers have begun to lower, one barrier fails to reach the lowered position neither barrier shall rise until both have been fully lowered. If either barrier fails to rise from the lowered position the road traffic light signals shall continue to show.

## EXPLANATORY NOTE

*(This note is not part of the Order.)*

This Order requires the provision and maintenance of an automatic half barrier crossing at the Lurgan (Bells Row) railway level crossing in place of manually operated crossing gates. Section 47 of the Railways Clauses Consolidation Act 1845 (which requires the railway undertaking to provide gates and gate-keepers), section 6 of the Railways Clauses Act 1863 (which requires the railway undertaking to erect a lodge) and any other statutory provision imposing requirements to the same or similar effect, shall not apply to the crossing whilst this Order remains in force.