SCHEDULE 21

Regulations 21 and 23

Part I

Requirements Relating to Obligatory Front Retro Reflectors and to Optional Front Retro Reflectors to the Extent Specified in Part II

1. Number:	Two
2. Position—	
(a) Longitudinal:	No requirement
(b) Lateral—	
(i) (i) Maximum distance from the side of the trailer:	150 mm
(ii) (ii) Minimum separation distance between a pair of front reflectors:	600 mm or, if the overall width of the trailer is less than 1400 mm, 400 mm
(c) Vertical—	
(i) (i) Maximum height above the ground:	900 mm or, if the structure of the trailer makes this impracticable, 1500 mm
(ii) (ii) Minimum height above the ground:	350 mm
3. Angles of visibility—	
(a) Horizontal:	30° outwards and 5° inwards
(b) Vertical—	
(i) (i) Any case not covered by sub- paragraph (ii):	15° above and below the horizontal
(ii) (ii) Where the highest point of the reflecting area is less than 750 mm above the ground:	15° above and 5° below the horizontal
4. Alignment:	To the front
5. Markings:	An approval mark
6. Size of reflecting area:	No requirement
7. Colour:	White

- 8. Other requirements—
 - (a) Where two front reflectors are required to be fitted they shall form a pair.
 - (b) Triangular shaped retro reflectors shall not be fitted to the front of any trailer.
- 9. Definitions—

In this Schedule—

Status: This is the original version (as it was originally made). This item of legislation is currently only available in its original format.

"approval mark" means either—

- (a) a marking designated as an approval mark by regulation 4 of the Designation of Approval Marks Regulations and shown at item 3 or 3A or 3B of Schedule 2 to those Regulations; or
- (b) a marking designated as an approval mark by regulation 5 of the Designation of Approval Marks Regulation and shown at item 4 of Schedule 4 to those Regulations.