**Status:** This is the original version (as it was originally made). This item of legislation is currently only available in its original format.

#### SCHEDULE 1

## ACCURACY CLASSIFICATION OF NON-AUTOMATIC WEIGHING MACHINES

# PART III

## MACHINES DESIGNATED CLASS II

12. A machine which is:

II

(a) made in accordance with an approved pattern and which is or could be marked

, or

(b) first stamped before 1st November 1991 and marked "Class B" in accordance with the provisions for beam scales in the Weights and Measures Regulations (Northern Ireland) 1967,

is a Class II machine.

13. The specifications for non-graduated and graduated Class II machines are given in Table 2.

| <i>Maximum</i><br><i>capacity</i> "Max"     | Lower limit of<br>the minimum<br>load"Min" | Scale<br>interval"d" | Number of scale intervals "n" | Verification<br>scale<br>interval"e" |
|---|--|----------------------|-------------------------------|--------------------------------------|
| Non-graduated<br>machines                   |  |                      |                               |                                      |
| $1 \text{ g} \leq \text{Max} < 5 \text{ g}$ | 10 e                                       |                      |                               | Max                                  |
|   |  |                      |                               |                                      |
|   |  |                      |                               | 1 000                                |
| 5 g $\leq$ Max                              | 10 e                                       |                      |                               | 5 mg                                 |
| <100 g                                      |  |                      |                               |                                      |
| $100 \text{ g} \leq \text{Max}$             | 10 e                                       |                      |                               | Max                                  |
| <200 g                                      |  |                      |                               |                                      |
|   |  |                      |                               | 20 000                               |
| $200 \text{ g} \leq \text{Max}$             | 50 e                                       |                      |                               | Max                                  |
|   |  |                      |                               |                                      |
|   |  |                      |                               | 20 000                               |
| Graduated<br>machines                       |  |                      |                               |                                      |
| Non-self                                    |  |                      |                               |                                      |

#### Table 2

Non-self indicating machines **Status:** This is the original version (as it was originally made). This item of legislation is currently only available in its original format.

| <i>Maximum</i><br><i>capacity</i> "Max "                                  | Lower limit of<br>the minimum<br>load "Min" | Scale<br>interval "d"  | Number of scale<br>intervals "n"                              | <i>Verification</i><br>scale<br>interval"e" |
|---|---|--|---|---|
| $1 \text{ g} \le \text{Max} < 50 \text{ g}$                               | 10 d  | $1 \text{ mg} \le d \le 5 \text{ mg}$                                    | $200 \le n < 50\ 000$   | d   |
| 10 g ≤ Max <50 g  | 50 d  | $\begin{array}{l} 10 \text{ mg} \leq d \leq 50 \\ \text{mg} \end{array}$ | $1\ 000 \le n < 5\ 000$                                       | 5 mg  |
| $50 g \le Max \le 500 g$  | 10 d  | $1 \text{ mg} \le d \le 5 \text{ mg}$                                    | $\begin{array}{c} 10  000 \leq n \leq 100 \\ 000 \end{array}$ | d   |
| 50 g $\leq$ Max $<$ 5 kg  | 50 d  | $\begin{array}{l} 10 \ mg \leq d \leq 500 \\ mg \end{array}$             | $\begin{array}{c} 1 \ 000 \leq n < 10 \\ 000 \end{array}$     | Max   |
|   |   |  |   |   |
|   |   |  |   | 10 000                                      |
| $\begin{array}{l} 100 \ g \leq Max \leq 50 \\ kg \end{array}$             | 50 d  | $\begin{array}{l} 10 \ mg \leq d \leq 500 \\ mg \end{array}$             | $\begin{array}{c} 10  000 \leq n \leq 100 \\ 000 \end{array}$ | d   |
| 5 kg $\leq$ Max   | 50 d  | $1 g \leq d$   | $\begin{array}{c} 5  000 \leq n < \!\! 10 \\ 000 \end{array}$ | Max   |
|   |   |  |   |   |
|   |   |  |   | 10 000                                      |
| $10 \text{ kg} \le \text{Max}$  | 50 d  | $1 g \leq d$   | $\begin{array}{c} 10  000 \leq n \leq 100 \\ 000 \end{array}$ | d   |
| Self and semi-<br>self indicating<br>machines                             |   |  |   |   |
| $\begin{array}{l} 1 \hspace{0.1cm} g \leq Max \leq 500 \\ g \end{array}$  | 10 d  | $1 \text{ mg} \le d \le 5 \text{ mg}$                                    | $\begin{array}{c} 200 \leq n \leq 100 \\ 000 \end{array}$     | d   |
| $\begin{array}{l} 10 \hspace{0.1cm} g \leq Max \leq 50 \\ kg \end{array}$ | 50 d  | $\begin{array}{l} 10 \ mg \leq d \leq 500 \\ mg \end{array}$             | $\begin{array}{c} 1 \ 000 \leq n \leq 100 \\ 000 \end{array}$ | d   |
| $5 \text{ kg} \le \text{Max}$   | 50 d  | $1 g \leq d$   | $\begin{array}{c} 5 \ 000 \leq n \leq 100 \\ 000 \end{array}$ | d   |

### Notes

1. When a machine is provided with a rider its verification scale interval shall be the smaller of the following—

(i) the verification scale interval of the machine not taking into account the rider, or

(ii) the scale interval of the rider device.

2. When graduated self or semi-self indicating machines are provided with a device for interpolation of reading, this shall not be taken into account when determining the verification scale interval of the machine.

3. When graduated self or semi-self indicating machines are provided with an indicating device on which the last figure is clearly differentiated from the other figures, the verification scale interval shall correspond to the last but one figure of the indication. **Status:** This is the original version (as it was originally made). This item of legislation is currently only available in its original format.

4. Machines of a maximum capacity equal to or greater than 1 kg of an actual scale interval of 100 mg and of a verification scale interval of 1 g may belong to this class of machine, provided that the last figure is clearly differentiated from the other figures.

5. In the case of machines where the weight indicating or printing is in carat (metric) units or ounces troy the relevant capacity and verification scale interval shall be the amounts in carat (metric) or ounces troy respectively which are equivalent to those specified in the Table in terms of mg, g and kg.

6. Where the equivalent metric value for an ounce troy scale interval falls between ranges then the value shall be considered as belonging to the lower range.