STATUTORY RULES OF NORTHERN IRELAND

2016 No. 404

ROAD AND RAIL TRANSPORT

The Level Crossing (Coleraine (Bushmills Road)) Order (Northern Ireland) 2016

Made--17th November 2016Coming into operation-15th December 2016

THE LEVEL CROSSING (COLERAINE (BUSHMILLS ROAD)) ORDER (NORTHERN IRELAND) 2016

- 1. Citation, commencement and interpretation
- 2. Suspension of statutory provisions
- 3. Provision of equipment
- 4. Revocation
 - Signature

SCHEDULE PARTICULARS OF THE BARRIERS, LIGHTS, TRAFFIC SIGNS 1 AND OTHER DEVICES

- 1. Cattle-cum-trespass guards of standard railway design shall be provided adjacent...
- 2. A barrier shall be pivoted as close to the railway...
- 3. It shall be possible to raise and lower the barriers....
- 4. When the barriers are fully lowered, their uppermost surfaces shall...
- 5. When in the fully raised position, the barriers shall be...
- 6. The barriers shall be as light as possible but shall...
- 7. The barriers shall be fitted with skirts so arranged that...
- 8. Three electric lamps, or equivalent (light emitting diodes) each of...
- 9. The barriers shall display on both front and rear faces...
- 10. Suitable screening shall be provided for each barrier machine to...
- 11. A traffic light signal of the size, colour and type...
- 12. An audible warning device shall be provided on or adjacent...
- 13. A reflectorised stop line of the size and type shown...
- 14. Where Bushmills Road passes over the crossing, reflectorised edge of...
- 15. The centre line of the carriageway shall be marked on...

- 16. A traffic sign of the size, colour and type shown...
- 17. There shall be a signalling control centre at Coleraine. A...
- 18. The control point shall have push-buttons to:
- 19. Facilities shall be provided at the crossing to operate the...
- 20. The crossing shall be illuminated during the hours of darkness...
- 21. Protecting railway signals shall be provided and these shall be...
- 22. In this Schedule 'the Regulations' means the Traffic Signs...

SCHEDULE

- E CONDITIONS AND REQUIREMENTS TO BE COMPLIED2 WITH BY THE RAILWAY UNDERTAKING
- 1. The carriageway shall be approximately 9 metres wide at the...
- 2. The ground at the two edges of the carriageway over...
- 3. The surface of the carriageway and footways over the crossing...
- 4. The barriers shall be kept in the fully raised position...
- 5. The electric lamps or equivalent (light emitting diodes) on each...
- 6. If the road approaches to the crossing are lit the...
- 7. The protecting signals shall be controlled from the signalling control...
- 8. The picture of the crossing shall be exhibited on the...
- 9. Visual indicators and an audible alarm shall be provided at...
- 10. The audible alarm shall sound if: (a) any barrier is...
- 11. When the 'lower' push button is pressed the sequence of...
- 12. The arrangements shall be such that the protecting railway signals...
- 13. If a train overruns a protecting signal the arrangements shall...
- 14. The intermittent red lights shall continue to show until the...
- 15. If any barrier fails to rise from the lowered position,...

Explanatory Note