

## SCHEDULE 5

Regulation 9(4), (6), (7), (9), (11)

CRITERIA FOR DETERMINING MINIMUM NUMBERS OF SAMPLING  
POINTS FOR FIXED MEASUREMENTS OF CONCENTRATIONS  
OF RELEVANT POLLUTANTS AND OZONE IN AMBIENT AIR

## PART I

RELEVANT POLLUTANTS: MINIMUM NUMBER OF SAMPLING  
POINTS FOR FIXED MEASUREMENT TO ASSESS COMPLIANCE  
WITH LIMIT VALUES FOR THE PROTECTION OF HUMAN  
HEALTH AND ALERT THRESHOLDS IN ZONES WHERE FIXED  
MEASUREMENT IS THE SOLE SOURCE OF INFORMATION

**Diffuse sources**

<i>Population of zone (thousands)</i>	<i>If concentrations exceed the upper assessment threshold</i>	<i>If maximum concentrations are between the upper and lower assessment thresholds</i>	<i>For SO<sub>2</sub> and NO<sub>2</sub> in agglomerations where maximum concentrations are below the lower assessment thresholds</i>
0 –250	1	1	not applicable
250 –499	2	1	1
500 –749	2	1	1
750 –999	3	1	1
1,000 –1,499	4	2	1
1,500 –1,999	5	2	1
2,000 –2,749	6	3	2
2,750 –3,749	7	3	2
3,750 –4,749	8	4	2
4,750 –5,999	9	4	2
>6,000	10	5	3

For NO<sub>2</sub> and  
particulate matter: to  
include at least one  
urban-background  
station and one traffic-  
orientated station  
– this requirement  
shall also apply to  
benzene and carbon  
MONOXIDE provided  
that it does not

---

*Status: This is the original version (as it was originally made). This item of legislation is currently only available in its original format.*

---

<i>Population of zone (thousands)</i>	<i>If concentrations exceed the upper assessment threshold</i>	<i>If maximum concentrations are between the upper and lower assessment thresholds</i>	<i>For SO<sub>2</sub> and NO<sub>2</sub> in agglomerations where maximum concentrations are below the lower assessment thresholds</i>
	increase the number of sampling points.		

### Point sources

1.2. For the assessment of pollution in the vicinity of point sources, the number of sampling points for fixed measurement should be calculated taking into account emission densities, the likely distribution patterns of ambient-air pollution and the potential exposure of the population.

## PART II

### RELEVANT POLLUTANTS: MINIMUM NUMBER OF SAMPLING POINTS FOR FIXED MEASUREMENTS TO ASSESS COMPLIANCE WITH LIMIT VALUES FOR THE PROTECTION OF ECOSYSTEMS OR VEGETATION IN ZONES OTHER THAN AGGLOMERATIONS

<i>If maximum concentrations exceed the upper assessment threshold</i>	<i>If maximum concentrations are between the upper and lower assessment thresholds</i>
1 station every 20,000 km <sup>2</sup>	1 station every 40,000 km <sup>2</sup>
In island zones the number of sampling points for fixed measurement should be calculated taking into account the likely distribution patterns of ambient-air pollution and the potential exposure of ecosystems or vegetation.	

## PART III

### OZONE: MINIMUM NUMBER: OF SAMPLING POINTS FOR FIXED CONTINUOUS MEASUREMENT TO ASSESS AIR QUALITY IN VIEW OF COMPLIANCE WITH THE TARGET VALUES, LONG-TERM

## OBJECTIVES AND INFORMATION AND ALERT THRESHOLDS WHERE CONTINUOUS MEASUREMENT IS THE SOLE SOURCE OF INFORMATION

<i>Population (<math>\times 1,000</math>)</i>	<i>Agglomerations (urban and suburban) <sup>(a)</sup></i>	<i>Other zones (suburban and rural) <sup>(b)</sup></i>	<i>Rural background</i>
0–250		1	1 station/50,000 km <sup>2</sup> as an average density over all zones
251–500	1	2	“
501–1,000	2	2	“
1,001–1,500	3	3	“
1,501–2,000	3	4	“
2,001–2,750	4	5	“
2,751–3,750	5	6	“
> 3,750	1 additional station per 2 million inhabitants	1 additional station per 2 million inhabitants	

(a) At least 1 station in suburban areas, where the highest exposure of the population is likely to occur. In agglomerations at least 50% of the stations should be located in suburban areas.

(b) One station per 25,000 km<sup>2</sup> for complex terrain is recommended.

---

## PART IV

### OZONE: MINIMUM NUMBER OF SAMPLING POINTS FOR FIXED MEASUREMENTS FOR ZONES ATTAINING THE LONG-TERM OBJECTIVES

**4.1.** The number of sampling points for ozone must, in combination with other means of supplementary assessment such as air quality modelling and co-located nitrogen dioxide measurements, be sufficient to examine the trend of ozone pollution and check compliance with the long-term objectives. The number of stations located in agglomerations and other zones may be reduced to one-third of the number specified in Part III. Where information from fixed measurement stations is the sole source of information, at least one monitoring station should be kept. If, in zones where there is supplementary assessment, the result of this is that a zone has no remaining station, co-ordination with the number of stations in neighbouring zones must ensure adequate assessment of ozone concentrations against long-term objectives. The number of rural background stations should be 1 per 100,000 km<sup>2</sup>.