SCHEDULE Article 2

Exempted fireplaces

Fireplace	Conditions The fireplace must be installed, maintained and operated in accordance with the following specifications	Permitted fuel
Wood Fired Boiler models RRK 22– 49 (49 kW output)	The manufacturer's and Wood Energy Limited's instructions 'Binder Equipment Installation, Commissioning and Maintenance' dated 17th May 2005, reference WELBinderManualrev0.doc, revision 0.	Wood pellets or wood chips ^(a) .
Wood Fired Boiler models RRK 80– 175 (75–149 kW	The manufacturer's and Wood Energy Limited's instructions 'Binder Equipment Installation, Commissioning and Maintenance' dated 17th May 2005, reference WELBinderManualrev0.doc, revision 0.	Wood pellets or wood chips ^(a) .
Wood Fired Boiler models RRK 130-250 (185-230 kW output),	The manufacturer's and Wood Energy Limited's instructions 'Binder Equipment Installation, Commissioning and Maintenance' dated 17th May 2005, reference WELBinderManualrev0.doc, revision 0.	Wood pellets or wood chips ^(a) .
Wood Fired Boiler model RRK 1000 (1200 kW output) with	The manufacturer's and Wood Energy Limited's instructions 'Binder Equipment Installation, Commissioning and Maintenance' dated 17th May 2005, reference WELBinderManualrev0.doc, revision 0.	Wood pellets or wood chips ^(a) .

⁽a) The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions The fireplace must be installed, maintained and operated in accordance with the following specifications	Permitted fuel
MZA manufactured by Binder Gesellschaft mit beschränkter Haftung (GmbH) of Austria.		
Pioneer 400, Solution 400 and Pioneer	The manufacturer's instructions 'Operating Instructions Clearview Vision/Vision Inset/ Pioneer & Solution' dated 1st July 2006, reference V1/42, stamped and signed "Smoke Control".	Air-dried wood logs ^(a) .
6. The Dunsley Yorkshire Woodburning Stove manufactured by Dunsley Heat Limited.	The manufacturer's instructions dated 4th December 2004, reference D13W.	Untreated dry wood.
Yorkshire Woodburning Stove	The manufacturer's instructions dated 4th December 2004, reference D13W together with the manufacturer's instructions dated 4th October 2004 reference GHD/DUN4B/1.	Untreated dry wood.
	Euroheat Distributors (HBS) Limited's operation Instructions Reference: "IN1141 Ed B" and dated November 2006.	Untreated dry wood.
(a) The fuel must not contain preservatives or coatings.	halogenated organic compounds or heavy metals as a result of t	reatment with wood-

Status: This is the original version (as it was originally made). This item of legislation is currently only available in its original format.

Fireplace	Conditions The fireplace must be installed, maintained and operated in accordance with the following specifications	Permitted fuel
(4.5kW Nominal	Euroheat Distributors (HBS) Limited's operation Instructions Reference: "IN1141 Ed B" and dated November 2006.	Untreated dry wood.
(4.5kW Nominal	Euroheat Distributors (HBS) Limited's operation Instructions Reference: "IN1141 Ed B" and dated November 2006.	Untreated dry wood.
(4.5kW Nominal	Euroheat Distributors (HBS) Limited's operation Instructions Reference: "IN1141 Ed B" and dated November 2006.	Untreated dry wood.
(4.5kW Nominal Thermal Output) fitted	Euroheat Distributors (HBS) Limited's operation Instructions Reference: "IN1141 Ed B" and dated November 2006.	Untreated dry wood.
(a) The fuel must not contain preservatives or coatings.	halogenated organic compounds or heavy metals as a result of t	reatment with wood-

preservatives or coatings.

Status: This is the original version (as it was originally made). This item of legislation is currently only available in its original format.

Fireplace	Conditions The fireplace must be installed, maintained and operated in accordance with the following specifications	Permitted fuel
with mechanism to prevent closure of the air wash/secondary air control, manufactured by HWAM Heat Design AS Nydamsvej 53 8362 Hørning Denmark.		
Harmony H23 Multi-	Euroheat Distributors (HBS) Limited's operation Instructions Reference: "IN1143 Ed B" and dated November 2006.	Untreated dry wood.
Stanford S23 Multi-	Euroheat Distributors (HBS) Limited's operation Instructions Reference: "IN1143 Ed B" and dated November 2006.	Untreated dry wood.
Stanford SP23 Multi- fuel Stove (6kW Nominal Thermal Output), manufactured by Nestor Martin S A Finuick Nv Voie Axiale 5 B-5660 Couvin Belgium	Euroheat Distributors (HBS) Limited's operation Instructions Reference: "IN1143 Ed B" and dated November 2006.	Untreated dry wood.
(a) The fuel must not contain preservatives or coatings	halogenated organic compounds or heavy metals as a result of t	reatment with wood-

preservatives or coatings.

	Conditions		
Fireplace	The fireplace must be installed, maintained		Permitted fuel
	and operated in accordance with the		
16. Nestor Martin	following specification Euroheat Distributors (1)		Untreated dry wood.
	operation Instructions F		Ontreated dry wood.
	B" and dated Novembe	r 2006.	
Output), manufactured by			
Nestor Martin			
S A Finuick Nv			
Voie Axiale 5 B-5660 Couvin			
Belgium			
	The manufacturer's inst		Untreated dry wood.
Speciale 80, 100, 110,	October 2004, reference	es:	
$110 \times 160 \text{ and } 120;$			
TOP Superiore 100 and 120; GR 100, 120,			
$140, 120 \times 160, 140$			
× 160, 140 × 180 and 180; OT 100, 120,			
140, 120 × 160, 140			
× 160, 140 × 180			
and 180; the Valoriani Piccolo, all of which			
are manufactured by			
Valoriani of Via Caselli alla Fornace,			
213, 50066 Reggello,			
Firenze, Italy.			
	Instruction	Model	
	OOLinst.1	FVR 80	
	OOLinst.2	FVR 100	
	OOLinst.3	FVR 110	
	OOLinst.4	FVR 120	
	OOLinst.5	FVR 110 × 160	
	OOLinst.6	TOP 100	
	OOLinst.7	TOP 120	
	OOLinst.8	GR 100 and OT 100	
	OOLinst.9	GR 120 and OT 120	
() 771 0.1	OOLinst.10	GR 140 and OT 140	

⁽a) The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions The fireplace must be installed, maintained and operated in accordance with the following specifications		Permitted fuel
	OOLinst.11	GR 120 × 160 and OT 120 × 160	
	OOLinst.12	GR 140 × 160 and OT 140 × 160	
	OOLinst.13	GR 140 × 180 and OT 140 × 180	
	OOLinst.14	GR 180 and OT 180	
	OOLinst.15	Valoriani Piccolo.	
	The manufacturer's instructions dated 9th October 2003, reference 250–6931B.		Dry cured untreated wood of maximum size 38.1 cm × 10.16 cm × 5.08 cm.
-	The manufacturer's instructions dated 4th June 2003, reference 7004–187.		Dry cured untreated wood of maximum size 38.1 cm × 10.16 cm × 5.08 cm.
	The manufacturer's instructions dated 8th July 2003, reference 7006–186.		Dry cured untreated wood of maximum size 43.18 cm × 10.16 cm × 10.16 cm.
wood pellet-fired boilers, model numbers USP-10, 15, 20, 25	2003, reference BA-US	P 0703.	

⁽a) The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

preservatives or coatings.

Fireplace	Conditions The fireplace must be installed, maintained and operated in accordance with the following specifications	Permitted fuel
and 30, manufactured by KWB – Kraft und Wärme aus Biomasse Gesellschaft mit beschränkter Haftung (GmbH) of Industriestrasse 235, A- 8321 St. Margarethen an der Raab, Austria.		
	The manufacturer's instructions dated August 2003, reference BA-USV 0803.	Wood pellets or wood chips ^(a) .
	The manufacturer's instructions dated 19th January 2005, reference WT10 and WT15.	Hardwood and softwood offcuts ^(a) .
BioLyt 50 wood pellet fired boiler	The manufacturers technical information and installation instructions dated 10/05 reference 4 204 794/00 and operating instructions dated 01/06 reference 4 204 793/01	Wood pellets ^(a)
(a) The fuel must not contain	halogenated organic compounds or heavy metals as a result of t	reatment with wood-