

Status: This is the original version (as it was originally made). This item of legislation is currently only available in its original format.

SCHEDULE

Class of fireplace	Conditions
The Babcock Worsley Fluidised Bed Combuster manufactured by Babcock Robey Limited.	<ol style="list-style-type: none">1. The fireplace shall be installed, maintained and operated so as to minimise the emission of smoke at all times, and in accordance with the manufacturer’s instructions dated 30th April 1986 and which bear the reference “No. C06/0016”.2. No fuel shall be used other than the waste derived fuel recommended in the manufacturer’s instructions.3. The fireplace shall be operated as a single unit with—<ol style="list-style-type: none">(a) the Tollemache Drier manufactured by Newell Dunford Limited; and(b) the Venturi Scrubber manufactured by Air Pollution Control Limited.
The CBR Flexifuel Heater, models 300, 400 and 600 manufactured by CBR Fabrications Limited.	<ol style="list-style-type: none">1. The fireplaces shall be installed, maintained and operated so as to minimise the emission of smoke at all times, and in accordance with the manufacturer’s instructions, which bear the reference FF/CBR Flexifuel 87.2. No fuel shall be used other than hard or soft wood off-cuts, chipboard or plastic coated chipboard.3. The fireplace shall not be used to burn sawdust in bulk or plastic materials other than plastic coated chipboard.
The CBR Turbo Heat, models 200, 300, 400, 500, 600 and 800 manufactured by CBR Fabrications Limited.	<ol style="list-style-type: none">1. The fireplaces shall be installed, maintained and operated so as to minimise the emission of smoke at all times, and in accordance with the manufacturer’s instructions, which bear the reference FF/CBR Turbo Heat 88.2. No fuel shall be used other than hard or soft wood off-cuts, chipboard or plastic coated chipboard.3. The fireplace shall not be used to burn sawdust in bulk or plastic materials other than plastic coated chipboard.
The Eclipse Junior, Standard, Senior, Jumbo 30 and Jumbo 50 incinerators, manufactured by Northern Incinerators Limited.	<ol style="list-style-type: none">1. The fireplaces shall be installed, maintained and operated so as to minimise the emission of smoke at all times, and in accordance with the manufacturer’s instructions dated 21st June 1988 and which bear the reference “NORCIN/TECH/88”.2. No fuel shall be used, other than fuel consisting of paper, cardboard cartons, scrap wood, foliage, combustible floor sweepings and

Status: This is the original version (as it was originally made). This item of legislation is currently only available in its original format.

Class of fireplace	Conditions
The Haat LD, MD and HD Incinerators manufactured by Haat Incineration Limited.	<p>other waste from domestic, commercial and industrial activities containing no more than 20 per cent of restaurant and cafeteria waste, and containing less than 5 per cent by weight of coated papers, plastic or rubber waste.</p> <p>1. The fireplaces shall be installed, maintained and operated so as to minimise the emission of smoke at all times, and in accordance with the manufacturer’s instructions dated March 1988 and which bear the reference“HAAT/I/CAA”.</p> <p>2. No fuel shall be used, other than fuel consisting of paper, cardboard cartons, scrap wood, foliage, combustible floor sweepings and other waste from domestic, commercial and industrial activities containing no more than 20 per cent of restaurant and cafeteria waste, and containing less than 5 per cent by weight of coated papers, plastic or rubber waste.</p>
The Holden Heat House 29.3 kw and 45.4 kw underfeed bituminous coal burning boilers manufactured by Holden Heat plc.	<p>1. The fireplaces shall be installed, maintained and operated so as to minimise the emission of smoke at all times, and in accordance with the manufacturer’s instructions which—</p> <p>(a) in the case of the installation instructions bear the reference“HH861B”; and</p> <p>(b) in the case of the user instructions bear the reference“HH861A”.</p> <p>2. No fuel shall be used other than the washed coals recommended in the manufacturer’s user instructions.</p>
The RanHeat Boiler Type RHA20, manufactured by RanHeat, Energy A/S.	<p>1. The fireplace shall be installed, maintained and operated so as to minimise the emission of smoke at all times, and in accordance with the manufacturer’s instructions dated 30th March 1988 and which bear the reference“RHGBEA 30388”.</p> <p>2. No fuel shall be used other than hard and soft wood shavings.</p>
The Talbott Pirojet P150 Heater manufactured by Talbott’s Heating Limited.	<p>1. The fireplace shall be installed, maintained and operated so as to minimise the emission of smoke at all times, and in accordance with the manufacturer’s instructions dated February 1987 and which bear the reference“<i>No. P150-2-87</i>”.</p> <p>2. No fuel shall be used other than hard or soft wood off-cuts, chipboard or plastic coated chipboard.</p>

Status: This is the original version (as it was originally made). This item of legislation is currently only available in its original format.

Class of fireplace	Conditions
The Talbott Pirojet P300 Heater manufactured by Talbott's Heating Limited.	<p>3. When the fireplace is used to burn chipboard and plastic coated chipboard, an afterburner which is supplied with the fireplace and which must be capable of continuously producing 20 megajoules of heat per hour, shall be used.</p> <p>4. The fireplace shall not be used to burn sawdust in bulk or plastic materials other than plastic coated chipboard.</p> <p>1. The fireplace shall be installed, maintained and operated so as to minimise the emission of smoke at all times, and in accordance with the manufacturer's instructions dated February 1987 and which bear the reference "No. P300-2-87".</p> <p>2. No fuel shall be used other than hard or soft wood off-cuts, chipboard or plastic coated chipboard.</p> <p>3. When the fireplace is used to burn chipboard and plastic coated chipboard an afterburner which is supplied with the fireplace and which must be capable of continuously producing 40 megajoules of heat per hour, shall be used.</p> <p>4. The fireplace shall not be used to burn sawdust in bulk or plastic materials other than plastic coated chipboard.</p>
The Talbott Pirojet P600 Heater manufactured by Talbott's Heating Limited.	<p>1. The fireplace shall be installed, maintained and operated so as to minimise the emission of smoke at all times, and in accordance with the manufacturer's instructions dated December 1986 and which bear the reference "P600-12-86".</p> <p>2. No fuel shall be used other than hard or soft wood off-cuts, or chipboard or plastic coated chipboard.</p> <p>3. When the fireplace is used to burn chipboard, and plastic coated chipboard an afterburner which is supplied with the fireplace and which must be capable of continuously producing 75 megajoules of heat per hour, shall be used.</p> <p>4. The fireplace shall not be used to burn sawdust in bulk or plastic materials other than plastic coated chipboard.</p>
The Triancomatic 90 boiler manufactured by Trianco Redfyre Limited.	<p>1. The fireplace shall be installed, maintained and operated so as to minimise the emission of smoke at all times, and in accordance with the</p>

Status: This is the original version (as it was originally made). This item of legislation is currently only available in its original format.

Class of fireplace	Conditions
The Triancomatic 140 boiler manufactured by Trianco Redfyre Limited.	<p>manufacturer's instructions dated July 1987 and which—</p> <ul style="list-style-type: none"><li data-bbox="868 461 1241 555">(a) in the case of the installation instructions bear the reference "No. 46576"; and<li data-bbox="868 566 1302 629">(b) in the case of the user instructions bear the reference "No. 46574". <p>2. No fuel shall be used other than the washed coals recommended in the manufacturer's user instructions.</p> <p>1. The fireplace shall be installed, maintained and operated so as to minimise the emission of smoke at all times, and in accordance with the manufacturer's instructions dated November 1986 and which—</p> <ul style="list-style-type: none"><li data-bbox="868 927 1241 1021">(a) in the case of the installation instructions bear the reference "No. 48375"; and<li data-bbox="868 1032 1302 1095">(b) in the case of the user instructions bear the reference "No. 48374". <p>2. No fuel shall be used other than the washed coals recommended in the manufacturer's user instructions.</p>