PROSPECTIVE

SCHEDULE 1

Regulations 5(1) and 6(1)

TRAFFIC SIGNS AND ROAD MARKINGS TO INDICATE ZEBRA CROSSINGS AND ZEBRA CONTROLLED AREAS

PART I

TRAFFIC SIGNS

1.—(1) Subject to the following provisions of this Part of this Schedule the traffic signs which are to be placed at or near a Zebra crossing for the purpose of indicating it shall consist of globes each of which is—

- (a) coloured yellow or fluorescent yellow;
- (b) not less than 275 nor more than 335 mm in diameter;
- (c) illuminated by a flashing light or, where the Secretary of State so authorises in writing in relation to a particular crossing a constant steady light; and
- (d) mounted on a post or bracket so that the lowest part of a globe is not less than 2.1 metres nor more than 3.1 metres above the surface of the ground immediately beneath it.

(2) One globe shall be placed at each end of the crossing and, if there is a refuge for pedestrians or central reservation on the crossing, one or more globes may, if the traffic authority thinks fit, be placed on the refuge or central reservation.

Commencement Information

II Sch. 1 para. 1 in force at 15.12.1997, see reg. 1(b)

2. Where a globe is mounted on or attached to a post, whether or not specially provided for the purpose—

- (a) the post shall be coloured in alternate black and white bands, the lowest band being coloured black;
- (b) the bands shall be not less than 275 mm nor more than 335 mm wide except that the lowest band may be up to 1 metre wide; and
- (c) the post may be internally illuminated.

Commencement Information

I2 Sch. 1 para. 2 in force at 15.12.1997, see reg. 1(b)

- 3. A globe or the post on which it is mounted may be fitted with all or any of the following—
 - (a) a backing board or other device designed to improve the conspicuousness of the globe;
 - (b) a shield or other device designed to prevent or reduce light shining into adjacent premises;
 - (c) a light to illuminate the crossing.

Commencement Information

I3 Sch. 1 para. 3 in force at 15.12.1997, see reg. 1(b)

4. A crossing shall not be taken to have ceased to be indicated in accordance with this Part of this Schedule by reason only of—

- (a) the imperfection, disfigurement or discolouration of any globe or post, or
- (b) the failure of illumination of any of the globes.

Commencement Information

I4 Sch. 1 Pt. I para. 4 in force at 15.12.1997, see reg. 1(b)

5. Nothing in this Part of this Schedule shall be taken to restrict regulation 8 or 9.

Commencement Information I5 Sch. 1 para. 5 in force at 15.12.1997, see reg. 1(b)

PART II

ROAD MARKINGS

Road markings

- 6. Subject to the following provisions of this Part of this Schedule—
 - (a) within the limits of a Zebra crossing the carriageway shall be marked with a series of alternate black and white stripes;
 - (b) the Zebra controlled areas shall be marked with give-way lines, a line of studs and zigzag lines,

of the size and type, and generally in the manner, shown in the diagram at the end of this Part of this Schedule.

Commencement Information

I6 Sch. 1 para. 6 in force at 15.12.1997, see reg. 1(b)

Number of studs and stripes

7. The number of studs and stripes may be varied.

Commencement Information

I7 Sch. 1 para. 7 in force at 15.12.1997, see reg. 1(b)

Document Generated: 2024-04-04

Status: This version of this schedule contains provisions that are prospective. Changes to legislation: There are outstanding changes not yet made by the legislation.gov.uk editorial team to The Zebra, Pelican and Puffin Pedestrian Crossings Regulations and General Directions 1997. Any changes that have already been made by the team appear in the content and are referenced with annotations. (See end of Document for details) View outstanding changes

Limits of the crossing

8.—(1) If it provides a reasonable contrast with the white stripes, the colour of the surface of the carriageway may be used to indicate the stripes shown coloured black in the diagram.

(2) The white stripes may be illuminated by retroreflecting material.

(3) Subject to paragraph (4) each black and each white stripe shall be of the same size and not less than 500 mm nor more than 715 mm wide as measured across the carriageway.

(4) The first stripe at each end may be up to 1300 mm wide and, if the traffic authority consider it appropriate in relation to a particular crossing having regard to the layout of the carriageway or other special circumstances, the other stripes may be not less than 380 mm nor more than 840 mm wide as measured across the carriageway.

Commencement Information

18 Sch. 1 para. 8 in force at 15.12.1997, see reg. 1(b)

Studs

- 9.—(1) The studs may be omitted altogether.
- (2) If studs are provided—
 - (a) they shall be coloured white, silver or light grey;
 - (b) they shall be either—
 - (i) circular in shape with a diameter of not less than 95 mm nor more than 110 mm; or
 - (ii) square in shape with each side not less than 95 mm nor more than 110 mm long;
 - (c) they may illuminated by retroreflecting material;
 - (d) if they consist of a device fixed to the carriageway, they shall—
 - (i) not be fitted with reflecting lenses;
 - (ii) be so fixed that they do not project more than 20 mm above the adjacent surface of the carriageway at their highest points nor more than 6 mm at their edges;
 - (e) the distance from the centre of any stud to the centre of the next stud in the same line shall not be less than 250 mm nor more than 715 mm and the distance between the edge of the carriageway at each end of a line of studs and the centre of the nearest stud shall be not more than 1.3 metres; and
 - (f) the two lines of studs need not be at right angles to the edge of the carriageway, but shall form straight lines and, so far as is reasonably practicable, shall be parallel to each other.

Commencement Information

I9 Sch. 1 para. 9 in force at 15.12.1997, see reg. 1(b)

Zig-zag lines

10.—(1) The pattern of the central zig-zag lines may be reversed or, on a road having a carriageway not more than 6 metres wide, those lines may be omitted altogether so long as they are replaced by the road marking shown in diagram 1004 in Schedule 6 to the 1994 Regulations.

(2) Subject to sub-paragraph (4) the number of marks in a zig-zag line shall not be less than 8 nor more than 18 and a zig-zag line need not contain the same number of marks as any other zig-zag line.

(3) Each mark in a zig-zag line shall be coloured white and may be illuminated by retroreflecting material.

Commencement Information

I10 Sch. 1 para. 10 in force at 15.12.1997, see reg. 1(b)

4) Where the traffic authority is satisfied that, by reason of the layout or character of any roads in the vicinity of a Zebra crossing, it would be impracticable to lay out a Zebra controlled area in accordance with this Schedule—

- (a) the number of marks in any zig-zag line in that area may be reduced to not less than 2; and
- (b) the length of any of the marks may be varied to not less than 1 metre.

Commencement Information

II1 Sch. 1 Pt. IIn1 para. 4 in force at 15.12.1997, see reg. 1(b)

Commencement Information

- **I10** Sch. 1 para. 10 in force at 15.12.1997, see reg. 1(b)
- III Sch. 1 Pt. IIn1 para. 4 in force at 15.12.1997, see reg. 1(b)

Give-way line

11.—(1) The give-way line shall be coloured white and may be illuminated by retroreflecting material.

(2) The angle of the give-way line in relation to, and its distance from, the edge of the crossing may be varied, if the traffic authority is satisfied that the variation is necessary having regard to the angle of the crossing in relation to the edge of the carriageway.

(3) The maximum distance of 3 metres between the give-way line and the limits of the crossing shown in the diagram in this Part of this Schedule may, if the traffic authority think fit having regard to the layout or character of the road in the vicinity of the crossing, be increased to not more than 10 metres.

Commencement Information

I12 Sch. 1 para. 11 in force at 15.12.1997, see reg. 1(b)

Discolouration or partial displacement of markings

12. A Zebra crossing or a Zebra controlled area shall not be deemed to have ceased to be indicated in accordance with this Schedule by reason only of the discolouration or partial displacement of any of the road markings prescribed by this Schedule, so long as the general appearance of the pattern of the lines is not impaired.

Document Generated: 2024-04-04


Status: This version of this schedule contains provisions that are prospective. Changes to legislation: There are outstanding changes not yet made by the legislation.gov.uk editorial team to The Zebra, Pelican and Puffin Pedestrian Crossings Regulations and General Directions 1997. Any changes that have already been made by the team appear in the content and are referenced with annotations. (See end of Document for details) View outstanding changes

Commencement Information I13 Sch. 1 para. 12 in force at 15.12.1997, see reg. 1(b)

PART II

DIAGRAM

Commencement Information I14 Sch. 1 Pt. IIn2 in force at 15.12.1997, see reg. 1(b)



Status:

This version of this schedule contains provisions that are prospective.

Changes to legislation:

There are outstanding changes not yet made by the legislation.gov.uk editorial team to The Zebra, Pelican and Puffin Pedestrian Crossings Regulations and General Directions 1997. Any changes that have already been made by the team appear in the content and are referenced with annotations.

View outstanding changes

Changes and effects yet to be applied to :

- Sch. 1 para. 1 coming into force by S.I. 1997/2400 reg. 1(b)
- Sch. 1 para. 2 coming into force by S.I. 1997/2400 reg. 1(b)
- Sch. 1 para. 3 coming into force by S.I. 1997/2400 reg. 1(b)
- Sch. 1 para. 5 coming into force by S.I. 1997/2400 reg. 1(b)
- Sch. 1 para. 6 coming into force by S.I. 1997/2400 reg. 1(b)
- Sch. 1 para. 7 coming into force by S.I. 1997/2400 reg. 1(b)
- Sch. 1 para. 8 coming into force by S.I. 1997/2400 reg. 1(b)
- Sch. 1 para. 9 coming into force by S.I. 1997/2400 reg. 1(b)
- Sch. 1 para. 10 coming into force by S.I. 1997/2400 reg. 1(b)
- Sch. 1 para. 11 coming into force by S.I. 1997/2400 reg. 1(b)
- Sch. 1 para. 12 coming into force by S.I. 1997/2400 reg. 1(b)
- Sch. 1 Pt. IIn2 coming into force by S.I. 1997/2400 reg. 1(b)
- Sch. 1 para. 1(1)(c) words substituted by 2016 c. 11 Sch. 2 para. 24(3)
- Sch. 1 Pt. I para. 4 coming into force by S.I. 1997/2400 reg. 1(b)
- Sch. 1 Pt. IIn1 para. 4 coming into force by S.I. 1997/2400 reg. 1(b)
- direction 8(3) word inserted by S.I. 1998/901 direction 2

Changes and effects yet to be applied to the whole Instrument associated Parts and Chapters:

Whole provisions yet to be inserted into this Instrument (including any effects on those provisions):

- Pt. 2 revoked by S.I. 2016/362 Sch. 19 Pt. 2
- Pt. 2 direction 10 words omitted by 2016 c. 11 Sch. 2 para. 25(3)(a)
- Pt. 2 direction 9 words substituted by 2016 c. 11 Sch. 2 para. 25(2)
- Pt. 2 direction 10 words substituted by 2016 c. 11 Sch. 2 para. 25(3)(b)
- reg. 12(1)(e)(ea)(eb) words omitted by S.I. 2011/935 reg. 6(b)(ii)
- reg. 12(1)(eza) inserted by 2015 c. 20 Sch. 9 para. 17(3)
- reg. 12(1)(ea) inserted by S.I. 2006/594 Sch. para. 15(2)(b)
- reg. 12(1)(eb) inserted by S.S.I. 2006/129 sch. para. 5(2)(b)
- reg. 12(1)(ec) inserted by S.I. 2011/935 reg. 6(b)(iii)
- reg. 13(1)(g) inserted by S.I. 2006/594 Sch. para. 15(3)(b)
- reg. 13(1)(h) inserted by S.S.I. 2006/129 sch. para. 5(3)(b)
- reg. 13(1)(i) and word inserted by S.I. 2011/935 reg. 6(c)(ii)
- reg. 13(1)(fa) inserted by 2015 c. 20 Sch. 9 para. 18(3)
- reg. 21(d) and word inserted by S.I. 2006/594 Sch. para. 15(4)
- reg. 21(e) and word inserted by S.S.I. 2006/129 sch. para. 5(4)
- reg. 21(ca) inserted by 2015 c. 20 Sch. 9 para. 19(3)