

SCHEDULE 8

MARKING OF PROJECTIONS

PART 2

FORWARD AND REARWARD PROJECTIONS

Markers for the side of a forward or rearward projection

- 6.—(1) This paragraph applies where any relevant vehicle is carrying a load and—
- (a) the length of any forward projection of the load exceeds 4.5 metres; or
 - (b) the length of any rearward projection of the load exceeds 5 metres.
- (2) Additional side markers must be fitted to the right hand side and the left hand side of a forward or rearward projection so that the horizontal distance between the extreme projecting points of the relevant vehicle and the nearest points of any adjacent side markers does not exceed—
- (a) 2.5 metres in the case of a forward projection;
 - (b) 3.5 metres in the case of a rearward projection.
- (3) The additional side markers also must be fitted to the projection so that—
- (a) each additional side marker is, as near as is practicable, in a longitudinal plane;
 - (b) the vertical distance between the lowest part of each additional side marker and the surface of the road is not more than 2.5 metres; and
 - (c) each additional side marker is clearly visible, within a reasonable distance, to a person using the road on that side of the projection.
- (4) In determining the extreme projecting points of a relevant vehicle for the purposes of subparagraph (2), any part of a crane or other special appliance or apparatus, which is treated as a forward projection or a rearward projection by virtue of article 6(3), is to be disregarded.