

SCHEDULE 2

Regulations 4 and 5

A. MAXIMUM VOC CONTENT LIMIT
VALUES FOR PAINTS AND VARNISHES

	<i>Product Subcategory</i>	<i>Type (*)</i>	<i>Phase I (g/l (**))(from 1.1.2007)</i>	<i>Phase II (g/l (**))(from 1.1.2010)</i>
a	Interior matt walls and ceilings (Gloss $\leq 25@60^\circ$)	WB	75	30
		SB	400	30
b	Interior glossy walls and ceilings (Gloss $>25@60^\circ$)	WB	150	100
		SB	400	100
c	Exterior walls of mineral substrate	WB	75	40
		SB	450	430
d	Interior/exterior trim and cladding paints for wood and metal	WB	150	130
		SB	400	300
e	Interior/exterior trim varnishes and woodstains, including opaque woodstains	WB	150	130
		SB	500	400
f	Interior and exterior minimal build woodstains	WB	150	130
		SB	700	700
g	Primers	WB	50	30
		SB	450	350
h	Binding primers	WB	50	30
		SB	750	750
i	One-pack performance coatings	WB	140	140
		SB	600	500
j	Two-pack reactive performance coatings for	WB	140	140
		SB	550	500
(*)	"solvent-borne coatings (SB)" means coatings the viscosity of which is adjusted by the use of organic solvent; and "water-borne coatings (WB)" means coatings the viscosity of which is adjusted by the use of water; where "coatings" has the meaning defined in paragraph 3 of Schedule 1.			
(**)	g/l ready to use			

Status: This is the original version (as it was originally made).

	<i>Product Subcategory</i>	<i>Type (*)</i>	<i>Phase I (g/l (**))(from 1.1.2007)</i>	<i>Phase II (g/l (**))(from 1.1.2010)</i>
	specific end use such as floors			
k	Multi-coloured coatings	WB	150	100
		SB	400	100
l	Decorative effect coatings	WB	300	200
		SB	500	200

(*) “solvent-borne coatings (SB)” means coatings the viscosity of which is adjusted by the use of organic solvent; and “water-borne coatings (WB)” means coatings the viscosity of which is adjusted by the use of water; where “coatings” has the meaning defined in paragraph 3 of Schedule 1.

(**) g/l ready to use

B. MAXIMUM VOC CONTENT LIMIT VALUES FOR VEHICLE REFINISHING PRODUCTS

	<i>Product Subcategory</i>	<i>Coatings</i>	<i>VOC g/l (*) (1.1.2007)</i>
a	Preparatory and cleaning	Preparatory	850
		Pre-cleaner	200
b	Bodyfiller/stopper	All types	250
c	Primer	Surfacer/filler and general (metal) primer	540
		Wash primer	780
d	Topcoat	All types	420
e	Special finishes	All types	840

(*) g/l of ready for use product. Except for subcategory (a) any water content of the product ready for use should be discounted.