SCHEDULE 2

DIAGRAMS

(Note - diagrams are not to scale and measurements are given in millimetres)

Diagram A (reference wheelchair)

(Regulation 2(1))




Diagram B (wheelchair sign)

(Schedule 1, paragraphs 6(3) and (4), 16(1) (a) and 20(7))




Diagram C1 (priority seat)

(Schedule 1, paragraph 13(3) and (7) (d))




Diagram C2 (facing seats without table)

(Schedule 1, paragraph 13(3) and (7) (d))




Diagram C3 (non facing seats)

(Schedule 1, paragraph 13(3) and (7) (d))





Diagram C4 (facing seats with table)

(Schedule 1, paragraph 13(3) and (7) (d))



(Note: Minimum clearance of 230 mm required between edge of seat and edge of table to ensure passengers can access and exit seat space standing upright without having to bend their knees).

Diagram D1 (hinged handrail – plan view)

(Schedule 1, paragraph 16(1) (f) (iii))




Diagram D2 (hinged handrail - elevation)

(Schedule 1, paragraph 16(1) (f) (iv))




Diagram E (alternative wheelchair space sign)

(Schedule 1, paragraph 20(7) and (8))



Changes to legislation:

There are outstanding changes not yet made by the legislation.gov.uk editorial team to The Rail Vehicle Accessibility (Non-Interoperable Rail System) Regulations 2010. Any changes that have already been made by the team appear in the content and are referenced with annotations. View outstanding changes

Changes and effects yet to be applied to:

 Regulations continued under new enabling powers in 2010 c. 15 by S.I. 2010/2317 art. 21Sch. 7