Changes to legislation: There are outstanding changes not yet made by the legislation.gov.uk editorial team to The Smoke Control Areas (Exempted Fireplaces) (England) (No. 2) Order 2011. Any changes that have already been made by the team appear in the content and are referenced with annotations. (See end of Document for details)

STATUTORY INSTRUMENTS

2011 No. 2106

CLEAN AIR, ENGLAND

The Smoke Control Areas (Exempted Fireplaces) (England) (No. 2) Order 2011

Made - - - - 22nd August 2011
Laid before Parliament 31st August 2011
Coming into force - - 1st October 2011

The Secretary of State makes the following Order in exercise of the powers conferred by section 21 of the Clean Air Act 1993(1).

The Secretary of State is satisfied that the fireplaces exempted by this Order can be used for burning fuel other than authorised fuels(2) without producing any smoke or a substantial quantity of smoke.

Citation, application and commencement

- 1. This Order—
 - (a) may be cited as the Smoke Control Areas (Exempted Fireplaces) (England) (No. 2) Order 2011;
 - (b) applies in England; and
 - (c) comes into force on 1st October 2011.

Fireplaces exempted from the provisions of section 20 of the Clean Air Act 1993

2. The fireplaces listed in the Schedule are exempt from the provisions of section 20 of the Clean Air Act 1993 (prohibition on emission of smoke in smoke control area), subject to the conditions listed in the Schedule.

Revocation

3. The Smoke Control Areas (Exempted Fireplaces) (England) Order 2011(3) is revoked.

^{(1) 1993} c. 11.

⁽²⁾ Fuels declared by the Secretary of State to be authorised fuels for the purposes of Part III of the Clean Air Act 1993 under section 20(6) of that Act are specified in S.I. 2008/514 as amended by S.I. 2008/2342, S.I. 2009/2191, S.I. 2010/576, S.I. 2011/715 and SI 2011/2105.

⁽³⁾ SI 2011/714.

Changes to legislation: There are outstanding changes not yet made by the legislation.gov.uk editorial team to The Smoke Control Areas (Exempted Fireplaces) (England) (No. 2) Order 2011. Any changes that have already been made by the team appear in the content and are referenced with annotations. (See end of Document for details)

Henley
Parliamentary Under Secretary of State
Department for Environment, Food and Rural
Affairs

22nd August 2011

Changes to legislation: There are outstanding changes not yet made by the legislation.gov.uk editorial team to The Smoke Control Areas (Exempted Fireplaces) (England) (No. 2) Order 2011. Any changes that have already been made by the team appear in the content and are referenced with annotations. (See end of Document for details)

SCHEDULE

Article 2

Exempted Fireplaces

Fireplace	Conditi	ions
	The fireplace must be installed maintained and operated in accordance with the following specifications:	Permitted fuels (other than authorised fuels):
18i and 60i stoves manufactured by Jetmaster Fires Limited, Unit 2 Peacock Trading Estate, Goodwood Road, Eastleigh, Hampshire, SO50 4NT	Installation and use instruction manual reference: "Part No 106870 Issue No. 1" dated February 2010 and supplementary instruction manual reference: "Part No 106872 Issue No. 1" dated May 2010. The appliance must be fitted with a mechanical stop to prevent closure of the air control beyond the 40% open position.	Wood logs ⁽¹⁾
Aarrow Signature 5 SC, Aarrow Ecoburn 5 SC, Hamlet Solution 5 SC and Villager Espirit 5 SC Stoves manufactured by Arada Limited, The Fire Works, Millwey Industrial Estate, Axminster, Devon, EX13 5HU	Instruction manual references "Rev 02" dated April 2010. The appliance must be fitted with a mechanical stop to prevent closure of the air control beyond 20mm from the closed position and 50 mm beyond the fully open position.	Wood logs ⁽¹⁾
Aduro 3D, 8D, 10D, 11D and Asgård 1D, 2D and 7D wood burning stoves distributed in the UK by Pevex Enterprises Limited, Unit 16 Seven Acres Business Park, Newbourne Road, Waldringfield, Nr Woodbridge. IP12 4PS	Instruction manual references "Pevex1001/AH/ver1" and dated June 2011. The appliance must be fitted with permanent stops to ensure that the primary and secondary air controls do not close beyond 95% and 50% respectively	Dry wood logs ⁽¹⁾
	Instruction manual references "Pevex1002/AH/ver1" and dated June 2011. The appliance must be fitted with permanent stops to ensure that the primary and secondary air controls do not close beyond 95% and 50% respectively	Dry wood logs ⁽¹⁾
Arimax Bio 300Kw	Instruction manual reference "INSTALLATION AND	6-8mm Wood Pellets with a Moisture content less than
Arimax Bio 400Kw	OPERATION MANUAl Arimax	10%(1)

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditi	ons
	The fireplace must be installed maintained and operated in accordance with the following specifications:	Permitted fuels (other than authorised fuels):
Arimax Bio 500Kw Boilers Manufactured by Artierm Oy PO Box 59 Fin – 43101 Saarijarvi, Finland	Bio 120-3000 kW" dated 30/03/2010	
Ashwell Green-Tec 150 boiler manufactured by Ashwell Biomass Limited, Unit 12, 35 Pinfold Road, Thurmaston, Leicester, LE4 8AT	Instruction manual reference "ASH-gt150/101 Version 1.2" dated 06/2009	Wood pellets ⁽¹⁾
Ashwell Green-Tec 195 boiler, manufactured by Ashwell Biomass Limited, Unit 12, 35 Pinfold Road, Thurmaston, Leicester, LE4 8AT		Wood pellets ⁽¹⁾
Ashwell Green-Tec 300 boiler manufactured by Ashwell Biomass Limited, Unit 12, 35 Pinfold Road, Thurmaston, Leicester, LE4 8AT	Instruction manual reference "ASH-gt300/103 Version 1.2" dated 06/2009	Wood pellets ⁽¹⁾
Barbas ECO 52 Stove manufactured by Interfocos, Hallenstraat 17, 5531 AB Bladel, The Netherlands.	Instruction manual references '02 -327332' dated March 2010	Wood logs ⁽¹⁾
Barbas Unilux 3 -52 Stove manufactured by Interfocos, Hallenstraat 17, 5531 AB Bladel, The Netherlands.	Instruction manual references '03 -326587' dated March 2010	Wood logs ⁽¹⁾
Barbas Unilux 3 -40, 5 kW wood burning insert and Barbas ECO 40, 5 kW wood burning roomheater manufactured by Interfocos BV, Hallenstraat 17, NL-5531, AB, BLADEL, Netherlands	The Unilux-3 40 Instruction Manual, document Version 01-326587 dated August 2009. The ECO 40 Instruction Manual, document Version 01-327332 dated October 2009.	Wood logs ⁽¹⁾
Baxi Bioflo manufactured by Windhager Zentralheizung GmbH, Anton-Windhager-Str. 20, A-5201 Seekirchen bei, Salzburg, Austria.	Operating instruction manual references "720574401" dated 2010 and installation and servicing instruction manual "720574501" dated 2010	Wood pellets ⁽¹⁾

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditi	ons
	The fireplace must be installed maintained and operated in accordance with the following specifications:	Permitted fuels (other than authorised fuels):
Be Modern Monroe 5, Monroe 5, Be Modern Monterrey 5, Monterrey 5 and York Midi Multi Fuel Stoves manufactured by Broseley Fires Ltd, Knights Way Battlefield Enterprise Park, Shrewsbury, Shropshire SY1 3AB	2010. The appliance must be fitted with a system that prevents the closure of the secondary air	Wood logs ⁽¹⁾
Monterrey 7, Be Modern Monroe 7 and Monroe 7 Multi	fitted with a system that prevents	Wood logs ⁽¹⁾
The Binder Wood Fired Boiler models RRK 22-49 (49 kW output) manufactured by Binder Gesellschaft mit beschränkter Haftung (GmbH) of Austria	Wood Energy Limited's instructions 'Binder Equipment Installation, Commissioning	Wood pellets or wood chips ⁽¹⁾
cyclone models ZA 80-175 manufactured by Binder	Wood Energy Limited's instructions 'Binder Equipment Installation, Commissioning	Wood pellets or wood chips ⁽¹⁾
The Binder Wood Fired Boiler model RRK 130-250 (185-230 kW output), RRK 200-350 (250-300 kW output), RRK 400-600 (350-500 kW output) and RRK 640-850 (650-840 kW output) with cyclone model type ZA manufactured by Binder Gesellschaft mit	The manufacturer's and Wood Energy Limited's instructions 'Binder Equipment Installation, Commissioning and Maintenance' dated 17 th May 2005, reference WELBinderManualrev0.doc, revision 0	Wood pellets or wood chips ⁽¹⁾

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditi	ons
	The fireplace must be installed maintained and operated in accordance with the following specifications:	Permitted fuels (other than authorised fuels):
beschränkter Haftung (GmbH) of Austria		
The Binder Wood Fired Boiler model RRK 1000 (1200 kW output) with multi-cyclone model MZA manufactured by Binder Gesellschaft mit beschränkter Haftung (GmbH) of Austria	,	Wood pellets or wood chips ⁽¹⁾
model RRK 1200- 1650 with Binder model MZA multicyclone and automatic ignition manufactured by	referenced: 2009 July Binder O&M revision8.doc Operation	Wood pellets or wood chips ⁽¹⁾
Boiler model RRK 1800- 2300 Binder model MZA multicyclone and automatic ignition manufactured by	referenced: 2009 July Binder	Wood pellets or wood chips ⁽¹⁾
model RRK 2500- 3000 with Binder model MZA	referenced: 2009 July Binder O&M revision8.doc Operation and Maintenance Manual,	Wood pellets or wood chips ⁽¹⁾
Biomatic 220 and 250 fitted with Zyklovent 220–250 cyclone separator manufactured by HERZ Armaturen Ges.m.b.H, Geschäftsbereich HERZ, Feuerungstechnik, A–8272 Sebersdorf 138, Austria	The manufacturer's instructions dated April 2005, reference Bedienungsanleitung Englisch v2.0 doc	Chipped wood, wood pellets or planed wood shavings ⁽¹⁾

The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives
or coatings.

Fireplace	Conditions	
	The fireplace must be installed maintained and operated in accordance with the following specifications:	Permitted fuels (other than authorised fuels):
Biomatic 300, 350, 400 and 500 fitted with Zyklovent 300-500 cyclone separator manufactured by HERZ Armaturen Ges.m.b.H, Geschäftsbereich HERZ, Feuerungstechnik, A-8272 Sebersdorf 138, Austria	dated April 2005, reference Bedienungsanleitung Englisch	Chipped wood, wood pellets or planed wood shavings ⁽¹⁾
Boru 4.9 kW Stove manufactured by Righpur Limited, T/A Boru Stoves, the Hive, Ballydine, Gooldscross, Ireland	Instruction manual reference 'BFF010' dated 26th January 2011. The air controls must be fixed such that they cannot be closed more than: Primary air slide 2mm, Secondary air slide 2mm, Tertiary air slide 30%	Wood logs ⁽¹⁾
Burley Hollywell SE manufactured by Burley Appliances Ltd, Lands End Way, Oakham, Rutland LE15 6RB	Instruction manual reference 'BUR/11/05' dated January 2011. The appliance must be fitted with an air plate that prevents the tertiary air controller from closing more than 17mm and opening more than 45mm	Wood logs ⁽¹⁾
Bushman Large Commercial Pizza Oven manufactured by Dingley Dell Enterprises Ltd, PO Box 3534, Kidderminster, Worcestershire, DY14 9ZE	Instruction manual references 'LCOINST' dated January 2011	Wood logs ⁽¹⁾
	Instruction manual references 'LDOINST' dated January 2011	Wood logs ⁽¹⁾
Bushman Medium Commercial Pizza Oven manufactured by Dingley Dell Enterprises Ltd, PO Box 3534, Kidderminster, Worcestershire, DY14 9ZE	Instruction manual references 'MCOINST' dated January 2011	Wood logs ⁽¹⁾
Bushman Medium Domestic Pizza Oven manufactured by Dingley Dell Enterprises Ltd, PO Box 3534, Kidderminster, Worcestershire, DY14 9ZE	Instruction manual references 'MDOINST' dated January 2011	Wood logs ⁽¹⁾

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed maintained and operated in accordance with the following specifications:	Permitted fuels (other than authorised fuels):
Bushman Small Commercial Pizza Oven manufactured by Dingley Dell Enterprises Ltd, PO Box 3534, Kidderminster, Worcestershire, DY14 9ZE	Instruction manual references 'SCOINST' dated January 2011	Wood logs ⁽¹⁾
Bushman Small Domestic Pizza Oven manufactured by Dingley Dell Enterprises Ltd, PO Box 3534, Kidderminster, Worcestershire, DY14 9ZE	Instruction manual references 'SDOINST' dated January 2011	Wood logs ⁽¹⁾
Carillon 16:9 Crystal manufactured by La Nordica Spa, Via Summano 104 M.Precalcino, 36030 Vicenza, Italy	Instruction manual references '7196755-Rev 09' dated 22nd December 2010. The appliance must be fitted with a mechanical stop to prevent closure of the secondary air control beyond the 40% open position.	Wood logs ⁽¹⁾
Carillon 4:3 manufactured by La Nordica Spa, Via Summano 104 M.Precalcino, 36030 Vicenza, Italy	Instruction manual references '7196755-Rev 09' dated 22nd December 2010. The appliance must be fitted with a mechanical stop to prevent closure of the secondary air control beyond the 40% open position.	Wood logs ⁽¹⁾
Carron Dante SE manufactured by Jig UK Limited Hurlingham Business Park, Fulbeck Heath, Grantham, Lincolnshire NG32 3HL	Instruction manual references 'BHC401-406' dated 12th January 2011. The appliance must be fitted with a system preventing the closure of the secondary air control openings beyond 14mm.	Wood logs ⁽¹⁾
Carron Stove SE manufactured by Jig UK Limited Hurlingham Business Park, Fulbeck Heath, Grantham, Lincolnshire NG32 3HL	Instruction manual references 'BHC501-506' dated 12th January 2011. The appliance must be fitted with a system preventing the closure of the secondary air control openings beyond 3mm.	Wood logs ⁽¹⁾
Carron Stove manufactured by Jig UK Limited Hurlingham Business Park, Fulbeck Heath, Grantham, Lincolnshire NG32 3HL	Instruction manual references "91- 62351" dated July 2009	Dry and split wood logs of a maximum length of 23 cm ⁽¹⁾

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings

Fireplace	Conditions	
	The fireplace must be installed maintained and operated in accordance with the following specifications:	Permitted fuels (other than authorised fuels):
Charnwood Country 4 wood burning stove manufactured by AJ Wells and Sons, Bishops Way, Newport, Isle of Wight, PO30 5WS	Modification instruction manual references 'TIS.95' dated January 2011 and instruction manual 'Country 4 MKII' dated January 2011.	Wood logs ⁽¹⁾
	The appliance must be fitted with the manufacturer's smoke reduction kit when used within a smoke control area to fix the minimum aperture of the secondary air inlets to a minimum of 21mm open.	
Charnwood Island 1 manufactured by AJ Wells and Sons, Bishops Way, Newport, Isle of Wight, PO30 5WS	Instruction manual references 'Island I.II.III 12.10 IssueB' dated December 2010.	Wood logs ⁽¹⁾
	The appliance must be fitted with a stop bracket (kit no. 010/AY83/S) to prevent the airwash flaps at the back of the stove from being closed beyond 2mm.	
Charnwood Island 2 manufactured by AJ Wells and Sons, Bishops Way, Newport, Isle of Wight, PO30 5WS	Instruction manual references 'Island I.II.III 12.10 IssueB' dated December 2010.	Wood logs ⁽¹⁾
5 /	The appliance must be fitted with a stop bracket (kit no. 010/BY83/S) to prevent the airwash flaps at the back of the stove from being closed beyond 2mm.	
Charnwood Island 3 manufactured by AJ Wells and Sons, Bishops Way, Newport, Isle of Wight, PO30 5WS	Instruction manual references 'Island I.II.III 12.10 IssueB' dated December 2010.	Wood logs ⁽¹⁾
isle of might, 1 000 5 mb	The appliance must be fitted with a stop bracket (kit no. 010/CY83/S) to prevent the airwash flaps at the back of the stove from being closed beyond 2mm.	
Charnwood Cove 1SR stove manufactured by A.J Wells and Sons Ltd, Bishops Way,	Installation and Use Instruction manual references "COVE1SR01.10 Issue A".	Wood logs ⁽¹⁾

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditi	ons
Newport, Isle of Wight, PO30 5WS	The fireplace must be installed maintained and operated in accordance with the following specifications: An adjustment of the air control such that the minimum closure of the air control is equivalent to that found with the control pushed in 15mm from the fully open position	Permitted fuels (other than authorised fuels):
Charnwood Tor Pico manufactured by AJ Wells and Son Ltd, Bishops Way, Newport, Isle of Wight, PO30 5WS	Instruction manual references 'Tor and Tor Pico 12.10 Issue B' dated December 2010	Wood logs ⁽¹⁾
Charnwood Tor stove manufactured by A.J Wells and Sons Ltd, Bishops Way, Newport, Isle of Wight, PO30 5WS	Installation and Use Instruction manual references "Tor 02.10 Issue A"	Wood logs ⁽¹⁾
Chesneys 4 Series (4.6 kW) Stoves: Flatford 4, Hampstead 4, Alpine 4 also sold as: Sunbeam 4, Dakota 4, Providence 4. Pacific 4 also sold as: Murano 4, Apollo 4. Chelsea 4 also sold as: Wellington 4, Guernsey 4, Belgravia 4 Manufactured by Chesneys, 194-200 Battersea Park Road, London, SW11 4ND	_	Wood logs ⁽¹⁾
Chesneys 6 Series (7 kW) Stoves: Flatford 6, Barrington 6, Petworth 6, Hampstead 6, Alpine 6 also sold as: Sunbeam 6, Dakota 6, Providence 6 and the Chelsea 6 also sold as: Wellington 6, Guernsey 6, Belgravia 6 Manufactured by Chesneys, 194-200 Battersea Park Road, London, SW11 4ND	Chesneys 6 series Instruction manual references "CH6K-V4" dated 7th December 2009. The appliance must be fitted with a mechanical stop to prevent closure of the air control beyond the 10mm open position	Wood logs ⁽¹⁾
The Classic model 25, 35, 40, 49, and 60 wood pellet boilers	The manufacturer's installation manual for the Classic Pellet	Wood pellets ⁽¹⁾

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings. 10

Fireplace	Conditions	
	The fireplace must be installed maintained and operated in accordance with the following specifications:	Permitted fuels (other than authorised fuels):
manufactured by Hargassner Gesellschaft mit beschränkter Haftung (GmbH), Gunderding 8, A-4952, Weng, Austria	Boilers reference No. 22, Pellet Boilers, Type Classic 25, 31, 35, 40, 49, 60, reference BA Classic 25L-60L Nr 21 0508.	
Clean Air Systems CAS 200, 400 and 600 handfed airheaters manufactured by Inventair Ltd, Lancaster Road, Carnaby Industrial Estate, Bridlington, East Yorkshire, YO15 3QY	To be operated in accordance with the Handbook for CAS hand fired airheater range reference 24600H version 1 dated January 2011	Softwood, hardwood, medium density fibreboard (MDF) or chipboard offcuts ⁽¹⁾
Clean Air Systems CAS 300 Max airheater and cyclone manufactured by Inventair Ltd, Lancaster Road, Carnaby Industrial Estate, Bridlington, East Yorkshire, YO15 3QY	To be operated in accordance with the Handbook for CAS 300 Max airheater range reference 300A version 1 dated January 2011	Softwood, hardwood, medium density fibreboard (MDF) or chipboard offcuts ⁽¹⁾
The Clearview Pioneer 400, Solution 400 and Pioneer Oven wood burning stoves manufactured by Clearview Stoves of More Works, Bishops Castle, Shropshire, SY9 5HH	The manufacturer's instructions 'Operating Instructions Clearview Vision/Vision Inset/ Pioneer & Solution' dated 1st July 2006, reference V1/42, stamped and signed "Smoke Control". The appliance must be fitted with a tamperproof mechanical	Air-dried wood logs ⁽¹⁾
	stop on the air slide/damper.	
Contura 510, Contura 520T, Contura 550, Contura 550A, Contura 550W, Contura 560T, Contura 560K, Contura 570, Contura 580, Contura 585, Contura 590, Contura T, all manufactured by NIBE AB Box 134, 285 23 Markaryd, Sweden		Untreated dry wood with less than 20% moisture ⁽¹⁾
Contura 580W manufactured by NIBE AB Box 134, 285 23 Markaryd, Sweden	Installation instruction IAV SE/EX 0740-1 511911. A permanent stop must be in place on the air inlet to prevent closure beyond the 20% open position.	Untreated dry wood with less than 20% moisture ⁽¹⁾

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed maintained and operated in accordance with the following specifications:	Permitted fuels (other than authorised fuels):
Contura 750 manufactured by Nibe, Box 134, S-285 23 Markaryd. Sweden	Instruction manual references "811064 BAV SE-EX C750/780-1". The appliance must be fitted with a mechanical stop to prevent closure beyond the 28% open position	Wood Logs ⁽¹⁾
Contura 750A manufactured by Nibe, Box 134, S-285 23 Markaryd, Sweden	Instruction manual references "811064 BAV SE-EX C750/780-1". The appliance must be fitted with a mechanical stop to prevent closure beyond the 28% open position.	Wood Logs ⁽¹⁾
Contura 780 manufactured by Nibe, Box 134, S-285 23 Markaryd, Sweden	Instruction manual references "811064 BAV SE-EX C750/780-1". The appliance must be fitted with a mechanical stop to prevent closure beyond the 28% open position.	Wood Logs ⁽¹⁾
Contura i4 Modern and Contura i4 Classic manufactured by Nibe Stoves, Box 134, S-285 23 Markaryd. Sweden	Instruction manual references "811136 BAV C i4 GB-1" dated 04-07-2011 and Supplementary operating instructions "811142 BAV GB-2" dated June 2011. Fitted with a mechanical stop to prevent closure beyond the 28% open position	Dry wood logs ⁽¹⁾
Cove 2 SR manufactured by A.J.Wells & Sons Ltd of Bishops Way, Newport, Isle of Wight, PO30 5WS	"Cove2SR 07.09 IssB" dated	Dry and split wood logs of a maximum length of 23 cm ⁽¹⁾
	A permanent stop must be in place on air control to prevent closure beyond 14mm from the fully closed position	
CTC Ecoflex 15 and 20 manufactured by Enertech AB, Box 313, S-341 26 Ljungby, Sweden	The manufacturer's instructions dated 20th February 2007, reference 161 505 27 06/1	Wood pellets ⁽¹⁾
Dimplex SE Selborne 5 stove manufactured by ESSE Engineering Ltd, Ouzledale Foundry Long	Instruction manual references "SE Selborne 5 Issue 1" dated 08 2009.	Wood logs ⁽¹⁾

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
Ing Barnoldswick Lancashire BB18 6BN	The fireplace must be installed maintained and operated in accordance with the following specifications: The appliance must be fitted with a mechanical stop to prevent closure beyond the 50% open position.	Permitted fuels (other than authorised fuels):
Dovre 250 (model DV-250) manufactured by Dovre NV, Nijverheidsstraat 18, BE-2381 Weelde, Belgium	The manufacturer's instructions, reference PM 250 Issue 1 A permanent stop must be in place on the secondary air inlet to prevent closure beyond the 75% open position	Untreated dry wood ⁽¹⁾
The Dunsley Yorkshire Stove, manufactured by Dunsley Heat Limited	The manufacturer's instructions dated 5th August 1998, reference A/22160 as amended by those dated 4th December 2004, reference D13	Union Coal Briketts, manufactured by Rheinbraur content not exceeding 1% of the total weight CPL Wildfire, manufactured by Coal Products Limited, Immingham, which—comprise bituminous coal with a volatile content of 32-36% (as to approximately 96% of the total weight) and a cold cure resin binder (as to the remaining weight); are manufactured from those constituents by a process involving roll-pressing; have an average weight of either 80-90 grams or 160-170 grams; and have a sulphur

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditi	ions
-	The fireplace must be installed maintained and operated in accordance with the following specifications:	Permitted fuels (other than authorised fuels):
		content not exceeding 1.8% of the total weight
The Dunsley Yorkshire Multifuel Stove manufactured by Dunsley Heat Limited	The manufacturer's instructions dated 5th August 1998, reference A/22160 as amended by those dated 4th December 2004, reference D13	Untreated dry wood ⁽¹⁾ Peat or peat briquettes with, in either case, less than 25% moisture
		Union Coal Briketts, manufactured by Rheinbraun AG of Germany comprising lignite compressed into briquettes of approximately 15 cm in length with square ends and with a sulphur content not exceeding 1% of the total weight
		CPL Wildfire, manufactured by Coal Products Limited, Immingham, which—comprise bituminous coal with a volatile content of 32-36% (as to approximately 96% of the total weight) and a cold cure resin binder (as to the remaining weight); are manufactured from those constituents by a process involving roll-pressing; have an average weight of either 80-90 grams or 160-170 grams; and have a sulphur content not exceeding 1.8% of the total weight
The Dunsley Yorkshire Multifuel Stove and Boiler manufactured by Dunsley Heat Limited	The manufacturer's instructions dated 5th August 1998, reference A/22160, as amended by those dated 4th October 2004, reference GHD/DUN4B/1	Untreated dry wood ⁽¹⁾ Peat or peat briquettes with, in either case, less than 25% moisture

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed maintained and operated in accordance with the following specifications:	Permitted fuels (other than authorised fuels):
		Union Coal Briketts, manufactured by Rheinbraun AG of Germany and comprising lignite compressed into briquettes of approximately 15 cm in length with square ends and with a sulphur content not exceeding 1% of the total weight
		CPL Wildfire, manufactured by Coal Products Limited, Immingham, which comprise bituminous coal with a volatile content of 32-36% (as to approximately 96% of the total weight) and a cold cure resin binder (as to the remaining weight); are manufactured from those constituents by a process involving roll-pressing; have an average weight of between 80-90 grams or between 160-170 grams; and have a sulphur content not exceeding 1.8% of the total weight
The Dunsley Yorkshire Woodburning Stove manufactured by Dunsley Heat Limited	The manufacturer's instructions dated 4th December 2004, reference D13W	Untreated dry wood ⁽¹⁾
The Dunsley Yorkshire Woodburning Stove and Boiler manufactured by Dunsley Heat Limited	The manufacturer's instructions dated 4th December 2004, reference D13W together with the manufacturer's instructions dated 4th October 2004 reference GHD/DUN4B/1	Untreated dry wood ⁽¹⁾

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed maintained and operated in accordance with the following specifications:	Permitted fuels (other than authorised fuels):
Earlswood manufactured by ACR Heat Products Limited, Unit One Weston Works, Weston Lane, Tyseley, Birmingham B11 3RP	Instruction manual reference "EW1MF technical manual" dated 02 2009. When the primary air control is in the closed position, it remains permanently open by 5mm and is prevented from closing fully by a screw.	Wood logs ⁽¹⁾
Eco-Ideal Eco 1 Stove manufactured by Hunter Stoves Limited, unit 6, Old Mill Industrial Estate, Stoke Canon, Exeter. Devon EX5 4RJ	Instruction manual references "JINECO01 revC" dated "20/07/11". The appliance must be fitted with a permanent stop that prevents closure of the secondary air slider beyond 30% open	Dry wood logs ⁽¹⁾
Eco-Ideal Eco 2 Stove manufactured by Hunter Stoves Limited, unit 6, Old Mill Industrial Estate, Stoke Canon, Exeter. Devon EX5 4RJ	Instruction manual references "JINECO02 revC" dated "20/07/11". The appliance must be fitted with a permanent stop that prevents closure of the secondary air slider beyond 30% open	Dry wood logs ⁽¹⁾
Eco-Ideal Eco 4 Stove manufactured by Hunter Stoves Limited, unit 6, Old Mill Industrial Estate, Stoke Canon, Exeter. Devon EX5 4RJ	Instruction manual references "JINECO04 revC" dated "20/07/11"	Dry wood logs ⁽¹⁾
Eco-Ideal Eco 6 Stove manufactured by Hunter Stoves Limited, unit 6, Old Mill Industrial Estate, Stoke Canon, Exeter. Devon EX5 4RJ	" JINECO06 revC" dated	Dry wood logs ⁽¹⁾
Ecco Stove E678 manufactured by Landy Vent UK Ltd, Foster House, 2 Redditch Road, Studley, Warwickshire B80 7AX	Instruction manual references '01/11/3' dated 28th January 2011. The appliance must be fitted with a system to fix the secondary air (airwash) to a 4mm open position	Wood logs ⁽¹⁾
Ecco Stove E850 manufactured by Landy Vent UK Ltd, Foster House, 2 Redditch		Wood logs ⁽¹⁾

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditi	ons
	The fireplace must be installed maintained and operated in accordance with the following specifications:	Permitted fuels (other than authorised fuels):
Road, Studley, Warwickshire B80 7AX	a system that prevents the closure of the secondary air flaps beyond 4mm (3 turns)	
Ecowarm Crystal 6 manufactured by Saltfire Stoves Ltd, Units 1 and 2, The Omega Centre, Sandford Lane, Wareham BH20 4DY	Instruction manual refrences 'ECO7operation-Revision 2A' dated 24th January 2011	Wood logs ⁽¹⁾
Ellipse manufactured by La Nordica Spa, Via Summano 104, M. Precalcino, 36030 Vicenza, Italy		Wood logs ⁽¹⁾
The En-tech model ENP 10, 15, 18, 25 and 35 boilers manufactured by Entech Energietechnikproduktion Gesellschaft mit beschränkter Haftung (GmbH), Gewerbezone 3, A-9300 St Veit, Glan-Hunnenbrunn, Austria	manual dated 11/2009, reference IMENP 10-35 11/2009 for the	Wood logs ⁽¹⁾
The En-tech model PK 15 and 25 boilers manufactured by Entech Energietechnikproduktion Gesellschaft mit beschränkter Haftung (GmbH), Gewerbezone 3, A-9300 St Veit, Glan-Hunnenbrunn, Austria	manual dated 11/2009, reference	Wood pellets ⁽¹⁾
The En-tech model PK 45 boilers manufactured by Entech Energietechnikproduktion Gesellschaft mit beschränkter Haftung (GmbH), Gewerbezone 3, A-9300 St Veit, Glan-Hunnenbrunn, Austria	The manufacturer's installation manual dated 11/2009, reference IMPK PK45 11/2009 EN for the Firefox pellet boiler.	Wood pellets ⁽¹⁾
Endress USF-W 1000 manufactured by Endress		Wood Chips and pellets ⁽¹⁾

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditi	ons
Holzfeuerungsanlagen GmbH,	The fireplace must be installed maintained and operated in accordance with the following specifications: manual Endress USF –W1000"	Permitted fuels (other than authorised fuels):
Industriestraße 18, D-91593 Burgbernheim.	dated 03/2010 Reference EMAN – USFW1000	
Endress USF-W 250 manufactured by Endress Holzfeuerungsanlagen GmbH, Industriestraße 18, D-91593 Burgbernheim.	Instruction manual references "Operating and Maintenance manual Endress USF -W250" dated 03/2010. Reference EMAN – USFW250	Wood Chips and pellets ⁽¹⁾
Endress USF-W 350 manufactured by Endress Holzfeuerungsanlagen GmbH, Industriestraße 18, D-91593 Burgbernheim.	Instruction manual references "Operating and Maintenance manual Endress USF –W350" dated 03/2010 Reference EMAN – USFW350	Wood Chips and pellets ⁽¹⁾
Endress USF-W 500 manufactured by Endress Holzfeuerungsanlagen GmbH, Industriestraße 18, D-91593 Burgbernheim.	Instruction manual references "Operating and Maintenance manual Endress USF -W500" dated 03/2010 Reference EMAN – USFW500	Wood Chips and pellets ⁽¹⁾
Endress USF-W 800 manufactured by Endress Holzfeuerungsanlagen GmbH, Industriestraße 18, D-91593 Burgbernheim.	Instruction manual references "Operating and Maintenance manual Endress USF –W800" dated 03/2010 Reference EMAN – USFW800	Wood Chips and pellets ⁽¹⁾
Endress VR-S 300 manufactured by Endress Holzfeuerungsanlagen GmbH, Industriestraße 18, D-91593 Burgbernheim.	Instruction manual references "Operating and Maintenance manual Endress VR-S300" dated 03/2010 Reference EMAN – VRS300	Wood Chips and pellets ⁽¹⁾
Endress VR-W 400 manufactured by Endress Holzfeuerungsanlagen GmbH, Industriestraße 18, D-91593 Burgbernheim.	Instruction manual references "Operating and Maintenance manual Endress VR –W400" dated 03/2010 Reference EMAN – VRW400	Wood Chips and pellets ⁽¹⁾
Endress VR-W 600 manufactured by Endress Holzfeuerungsanlagen GmbH, Industriestraße 18, D-91593 Burgbernheim.	Instruction manual references "Operating and Maintenance manual Endress VR-W600" dated 03/2010 Reference EMAN – VRW600	Wood Chips and pellets ⁽¹⁾
Endress VR-W 900 manufactured by Endress Holzfeuerungsanlagen GmbH,	Instruction manual references "Operating and Maintenance manual Endress VR-W900"	Wood Chips and pellets ⁽¹⁾

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditi	ons
Industriestraße 18, D-91593 Burgbernheim.	The fireplace must be installed maintained and operated in accordance with the following specifications: dated 03/2010 Reference EMAN – VRW900	Permitted fuels (other than authorised fuels):
	The manufacturer's instruction manual dated February 2009, reference 100SE Issue 1. A permanent stop must be in place on the secondary air inlet to prevent closure beyond the 50% open position	Untreated dry wood with a maximum moisture content of 20%, maximum length of 200 mm and maximum width or diameter of 120 mm ⁽¹⁾
EOS 30 346kW output wood pellet boiler with multicyclone manufactured by: Uniconfort srl, Via dell'Industria 21, 35018, San Martino Di Lupari (PD) Italy	reference "Uniconfort EOS30	Wood pellets ⁽¹⁾
EOS 35 407kW output wood pellet boiler with multicyclone manufactured by: Uniconfort srl, Via dell'Industria 21, 35018, San Martino Di Lupari (PD) Italy		Wood pellets ⁽¹⁾
EOS 40 464kW output wood pellet boiler with multicyclone manufactured by: Uniconfort srl, Via dell'Industria 21, 35018, San Martino Di Lupari (PD) Italy		Wood pellets ⁽¹⁾
EOS 60 700 kW output wood pellet boiler with multicyclone manufactured by Uniconfort sri, Via dell'Industria 21, 35018 San Martino Di Lupari (PD) Italy	Installation Instruction manual references 'K135-07332 Uniconfort MUN v 2' dated September 2010	6mm diameter wood pellets ⁽¹⁾
Esse 125 SE Stove manufactured by ESSE Engineering Ltd, Ouzledale Foundry, Long Ing, Barnoldswick, Lancashire, BB18 6BN	Instruction manual references "Esse 125SE Issue 1" dated August 2009. The appliance must be fitted with a mechanical stop to prevent closure beyond the 50% open position.	Wood logs ⁽¹⁾
Esse 301 SE Stove manufactured by ESSE	Instruction manual references "v45" dated 9th November 2010.	Wood logs ⁽¹⁾

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditi	ions
	The fireplace must be installed maintained and operated in accordance with the following specifications:	Permitted fuels (other than authorised fuels):
Engineering Ltd, Ouzledale Foundry, Long Ing, Barnoldswick, Lancashire, BB18 6BN	The primary air control must not be fully air tight when closed.	
Esse 350 SE Stove manufactured by ESSE Engineering Ltd, Ouzledale Foundry, Long Ing, Barnoldswick, Lancashire, BB18 6BN	Instruction manual references 'v45' dated 9th November 2010	Wood logs ⁽¹⁾
Esse 1622 inset stove manufactured by Esse Engineering Limited, Long Ing, Barnoldswick Lancashire BB18 6BN	2010.	Wood logs ⁽¹⁾
	The appliance must be fitted with a mechanical stop to fix secondary air control fully open.	
ETA HACK 20, 25, 35, 50, 70, 90, 130 and 200 woodchip boilers Manufactured by ETA Heiztechnik Gesellschaft mit beschrankter Haftung (GmbH), A 4716, Hofkirchen an der Trattnach, Gewerbepark 1, Austria	Instruction manual reference "HACK20-200_Bedienung_2011-dated 06/2011. Integrated flue gas recirculation system must be used when using wood chips with a moisture content below 15%	Wood chips ⁽¹⁾ 06_EN"
ETA HACK 20, 25, 35, 50, 70, 90, 130 and 200 woodchip boilers Manufactured by ETA Heiztechnik Gesellschaft mit beschrankter Haftung (GmbH), A 4716, Hofkirchen an der Trattnach, Gewerbepark 1, Austria	Instruction manual reference "HACK20-200_Bedienung_2011-dated 06/2011. Integrated flue gas recirculation system must be used when burning wood pellets	Wood pellets ⁽¹⁾ 06_EN"
ETA PC 20, 25 and 32 wood pellet boilers Manufactured by ETA Heiztechnik Gesellschaft mit beschrankter Haftung (GmbH), A 4716, Hofkirchen an der Trattnach, Gewerbepark 1, Austria	Instruction manual reference "PC20-32_Bedienung_2011-06_E dated 06/2011	Wood pellets ⁽¹⁾ N''

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditi	ons
	The fireplace must be installed maintained and operated in accordance with the following specifications:	Permitted fuels (other than authorised fuels):
ETA PE-K 35, 50, 70 and 90 wood pellet boilers Manufactured by ETA Heiztechnik Gesellschaft mit beschrankter Haftung (GmbH), A 4716, Hofkirchen an der Trattnach, Gewerbepark 1, Austria	K35-90_Bedienung_2011-06_EN	_
ETA PU 7, 11 and 15 wood pellet boilers Manufactured by ETA Heiztechnik Gesellschaft mit beschrankter Haftung (GmbH), A 4716, Hofkirchen an der Trattnach, Gewerbepark 1, Austria	"PU7-15_Bedienung_2011-06_EN	
ETA SH 20, 30, 40, 50 and 60 wood gasification boilers Manufactured by ETA Heiztechnik Gesellschaft mit beschrankter Haftung (GmbH), A 4716, Hofkirchen an der Trattnach, Gewerbepark 1, Austria	Instruction manual reference "SH20-60_Bedienung_2011-06_E dated June 2011	
M-EVO5 manufactured by Broseley Fires Limited,	Instruction manual references "eVo 5 MS07-11" dated 8th July 2011. The appliance must be fitted with a system that prevents the closure of the air control to less than 70% open	Wood Logs ⁽¹⁾
Evotherm P50, P100, P120, P150, P170, P200 pellet boilers manufactured by Evotherm, Heiztechnik Vertriebs Gesellschaft mit beschrankter Haftung (GmbH), Seeleiten 24, AT 5120, St Pantaleon, Austria	1 2	Wood pellets ⁽¹⁾
The Extraflame: Babyfiamma, Bella and Bella Lux, Clementina, Comfort Maxi, Contessa, Divina, Divina Plus and Divina Steel, Duchessa and Duchessa Steel, Ecologica,	The manufacturer's operating instructions dated 5th March 2007, reference 004275101 011	Wood pellets ⁽¹⁾

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditi	ons
	The fireplace must be installed maintained and operated in accordance with the following specifications:	Permitted fuels (other than authorised fuels):
Esmeralda and Esmeralda Crystal, Falò 1CP, Falò 2CP and Falò 1XP, Isabella, Karolina and Preziosa, all of which are manufactured by Extraflame S.p.a in Montecchio Precalcino (Vicenza), Italy		
The Extraflame Comfort Mini manufactured by Extraflame S.p.a in Montecchio Precalcino (Vicenza), Italy	The manufacturer's operating instructions dated 2nd October 2006, reference 004275115 REV 005	Wood pellets ⁽¹⁾
The Extraflame Idro manufactured by Extraflame S.p.a in Montecchio Precalcino (Vicenza), Italy	The manufacturer's operating instructions dated 28th August 2006, reference 004275128 REV 002	Wood pellets ⁽¹⁾
The Extraflame Lucrezia Idro and Lucrezia Steel manufactured by Extraflame S.p.a in Montecchio Precalcino (Vicenza), Italy	The manufacturer's operating instructions dated 12th July 2006, reference 004275110 REV 011	Wood pellets ⁽¹⁾
Fireball manufactured by La Nordica Spa, Via Summano 104, M. Precalcino 36030, Vicenza, Italy	Instruction manual references '7196801-Rev 07' dated 22nd December 2010. The appliance must be fitted with a mechanical stop to prevent closure of the secondary air control beyond the 40% open position.	Wood logs ⁽¹⁾
Firefox 5CB, Vega 100CB, Sirius 405CB and Flame 5CB (4.9kW) stoves manufactured by Percy Doughty & Co, Imperial Point, Express Trading Estate, Stonehill Road, Farnworth, Bolton, BL4 9TN	Instruction manual references "FFXCBA" dated January 2010	Wood logs ⁽¹⁾
Firefox 5 Clean Burn II, Gallery Classic 5 Clean Burn, Sirius 405 Clean Burn and Sirius 405 Classic Clean Burn manufactured by Percy Doughty & Co Limited, Imperial Point, Express Trading	Instruction manual references "FF5CBII REV:A" dated June 2011. The appliance must be fitted with a mechanical stop to prevent secondary air closure beyond the 50% open position	Dry wood logs ⁽¹⁾

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditi	ons
	The fireplace must be installed maintained and operated in accordance with the following specifications:	Permitted fuels (other than authorised fuels):
Estate, Stone Hill Road, Farnworth, Bolton. BL4 9TN		
Gallery Classic 8 Clean Burn,	2011. The appliance must be	Dry wood logs ⁽¹⁾
Fireglow Eco 7 manufactured by Saltfire Stoves Ltd, Units 1 and 2, The Omega Centre, Sandford Lane, Wareham BH20 4DY	Instruction manual references 'ECO7 operation-Revision 2A' dated 24th January 2011	Wood logs ⁽¹⁾
Charlton and Jenrick G1-	"Issue 03" dated 03/10. The appliance must be fitted with a system that prevents the closure	Wood logs ⁽¹⁾
and 150 manufactured	Bedienungsanleitung Firematic V	Chipped wood, wood pellets or planed wood shavings ⁽¹⁾
Firematic 45 and 60 manufactured by HERZ Armaturen Ges.m.b.H, Geschäftsbereich HERZ Feuerungstechnik, A-8272 Sebersdorf 138, Austria	Instruction manual references "05.007 .Operating instructions - FM (1Ph) 20 35 45 60 v2.3" dated "08/2009"	Wood pellets conforming to ÖNORM M7135 with diameter of 6 mm or Wood chips up to a maximum size of 50mm and maximum water content 35% ⁽¹⁾
Franco Belge Model 134 08 11 Savoy EA 8kW output wood burning stove manufactured by : Franco Belge, Staub Fonderie SARL, Rue Orphée	The Savoy EA Technical Manual, document reference 1290-1, reviewed 9 July 2009.	Wood logs ⁽¹⁾

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditi	ons
	The fireplace must be installed maintained and operated in accordance with the following specifications:	Permitted fuels (other than authorised fuels):
Variscotte, 59660, Merville, France		
Fröling Lambdamat Commercial wood chip boiler models 500, 750 and 1000 manufactured by Fröling Heizkessel und Behälterbau Gesellschaft mit beschränkter Haftung (GmbH), A-4710 Grieskirchen, Industriestrasse 12, Austria	Lambdamat Communal Operating and Installation Manual reference B 069 01 04 of February 2004	Wood chips ⁽¹⁾
Fröling S4 Turbo 15 15kW, Fröling S4 Turbo 22 22kW, Fröling S4 Turbo 28 28kW, Fröling S4 Turbo 34 34kW, Fröling S4 Turbo 40 40kW, Fröling S4 Turbo 50 50kW, Fröling S4 Turbo 60 60kW manufactured by Fröling Heizkessel und Behälterbau Gesellschaft mit beschränkter Haftung (GmbH), A-4710 Grieskirchen, Industriestrasse 12, Austria	Assembly instruction manual 'M0970208' dated November 2008 and Operating instruction manual 'B0510108' dated November 2008	Wood logs ⁽¹⁾
Fröling Turbomatic 28, 35, 48 and 55 manufactured by Fröling Heizkessel- und Behälterbau Ges.m.b.H, Industriestraße 12, A-4710 Grieskirchen, Austria	The manufacturer's installation manual dated November 2003, reference M 060 01 03	Wood chip less than 35% moisture content and meeting ÖNORM M 7133: 1998 size class G30 ⁽¹⁾
	The manufacturer's operating manual dated August 2002, reference 99229a	Wood pellets of 6 mm diameter and a moisture content below 10% ⁽¹⁾
Fröling Turbomatic 85, 100 and 110 manufactured by Fröling Heizkessel- und Behälterbau Ges.m.b.H, Industriestraße 12,	The manufacturer's instruction manual dated November 2003, reference M 060 01 03	Wood chip less than 35% moisture content and meeting ÖNORM M 7133: 1998 of either size class G30 or G50 ⁽¹⁾
A-4710 Grieskirchen, Austria	The manufacturer's operating manual dated August 2002, reference 99229a	Wood pellets of 6 mm diameter and a moisture content below 10% ⁽¹⁾
	The manufacturer's operating instructions dated August 2003, reference B0310003	Wood pellets or wood chips ⁽¹⁾

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed maintained and operated in accordance with the following specifications:	Permitted fuels (other than authorised fuels):
Ges.m.b.H, Industriestraße 12, A-4710 Grieskirchen, Austria		
Fröling Turbomat 320 and 500 manufactured by Fröling Heizkessel- und Behälterbau Ges.m.b.H, Industriestraße 12, A-4710 Grieskirchen, Austria	The manufacturer's operating instructions dated November 2004, reference B0340004	Wood pellets or wood chips(1)
Fröling P4 8, 15, 20, 25, 32, 38, 48 and 60 Pellet Boilers manufactured by Fröling Heizkessel- und Behälterbau Ges.m.b.H, Industriestrasse 12, A-4710 Grieskirchen	Instruction manual reference "B0430408_en" dated July 2009	Wood pellets with a diameter of 6mm ⁽¹⁾
Fröling TX150 150kW boiler with Exhaust Gas Recirculation device manufactured by Fröling Heizkessel- und Behälterbau Ges.m.b.H. Industriestraße 12, Austria	Installation Instruction manual references "M1130009" dated 09/2010 and operating instruction manual "B 067 00 09" dated 09/2010	Wood chips with a moisture content $\leq 30\%$ and a maximum cross sectional area of 5cm^2 or wood pellets with a moisture content of $\leq 10\%$ and a maximum diameter of $10\text{mm}^{(1)}$
Gilles HPK-RA 13 kW, 15 kW, 20 kW, 25 kW, 30 kW, 35 kW, 40 kW, 45 kW, 49 kW, 60 kW, 70 kW, 75 kW, 85 kW, 95 kW, 100 kW, 120 kW and 145 kW manufactured by GILLES Energie- und Umwelttechnik GmbH, Koaserbauer Str. 16 A-4810 Gmunden, Austria	Operating instructions dated January 2007, reference Gilles/0–145/1	Wood pellets or wood chips ⁽¹⁾
Gilles HPK-RA 160 Manufactured by Gilles Energie – und Umwelttechnik Gmbh, Koaserbauer Str. 16A-4810 Gmunden, Austria		Wood Chips and pellets ⁽¹⁾

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditi	ions
	The fireplace must be installed maintained and operated in accordance with the following specifications:	Permitted fuels (other than authorised fuels):
Gilles HPK USK 150 kW, 180 kW, 240 kW and 300 kW manufactured by GILLES Energie- und Umwelttechnik GmbH, Koaserbauer Str. 16 A-4810 Gmunden, Austria	Operating instructions dated January 2007, reference Gilles/150–300/1	Wood pellets or wood chips ⁽¹⁾
Gilles HPK USK 360 kW manufactured by GILLES Energie- und Umwelttechnik GmbH, Koaserbauer Str. 16 A-4810 Gmunden, Austria	Operating instructions dated January 2008, reference Gilles/360/1	Wood pellets or wood chips ⁽¹⁾
240, 300, 360, 450, 550,	, <u>,</u>	Wood Chips and pellets ⁽¹⁾
Gilles UTSK 450 kW, 550 kW boilers manufactured by GILLES Energie-und Umwelttechnik GmbH, Koaserbauer Str. 16 A-4810 Gmunden, Austria	Operating instructions dated January 2008, reference Gilles/360/1	Wood pellets or wood chips ⁽¹⁾
Gilles UTSK 700 kW, 900 kW boilers manufactured by GILLES Energie-und Umwelttechnik GmbH, Koaserbauer Str. 16 A-4810 Gmunden, Austria	Operating instructions dated January 2008, reference Gilles/360/1	Wood pellets or wood chips ⁽¹⁾
Gilles UTSK 1200 kW, 1600 kW boilers manufactured by GILLES Energie- und Umwelttechnik GmbH, Koaserbauer Str. 16 A-4810 Gmunden, Austria	Operating instructions dated January 2008, reference Gilles/360/1	Wood pellets or wood chips ⁽¹⁾
Guntamatic Biocom and Powercorn 50 and 75 manufactured by GUNTAMATIC Heiztechnik GmbH A – 4722 PEUERBACH, Bruck 7	Instruction manual references "GUN/BIO/OP/V1/0709" dated 29/07/09	Wood pellets with a diameter of 6mm and a length of between 10 and 30 mm ⁽¹⁾

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed maintained and operated in accordance with the following specifications:	Permitted fuels (other than authorised fuels):
Guntamatic Powerchip 50 and 75 manufactured by GUNTAMATIC Heiztechnik GmbH A – 4722 PEUERBACH, Bruck 7	Instruction manual references "GUN/POW/OP/V1/0709" dated 29/07/09	Wood pellets with a diameter of 6mm and a length of between 10 and 30 mm ⁽¹⁾
Guntamatic Biocom and Powercorn 100 manufactured by GUNTAMATIC Heiztechnik GmbH A – 4722 PEUERBACH, Bruck 7	Instruction manual references "GUN/BIO/OP/V1/0709" dated 29/07/09.	Wood pellets with a diameter of 6 mm and a length of between 10 and 30 mm or Wood chip less than 35% moisture content and meeting ÖNORM M 7133: 1998 size class G30 ⁽¹⁾
Guntamatic Powerchip 100 manufactured by GUNTAMATIC Heiztechnik GmbH A – 4722 PEUERBACH, Bruck 7		Wood pellets with a diameter of 6 mm and a length of between 10 and 30 mm or Wood chip less than 35% moisture content and meeting ÖNORM M 7133: 1998 size class G30 ⁽¹⁾
The HSV 50 + WTH 45, 49 or 55 boilers manufactured by Hargassner Gesellschaft mit beschränkter Haftung (GmbH), Gunderding 8, A-4952, Weng, Austria		Wood chip or wood pellets ⁽¹⁾
beschränkter Haftung (GmbH),	manual version 44 for Wood Chip and Pellet Stoves, Type	Wood chip or wood pellets ⁽¹⁾
100 boiler manufactured by	The manufacturer's installation manual version 44 for Wood Chip and Pellet Stoves, Type HSV 30-100. Reference BA HSV30-100 RA/RAP V44 0608.	Wood chip or wood pellets ⁽¹⁾
Hamont CATfire 350 USZI pellet boiler fitted with CATfirte 300 cyclone, manufactured by Hamont Contracting and Trading, spol.	"Operating Manual for Boilers CATfire 150-500kW" effective	Wood pellets with a 6mm diameter and a maximum length of 30mm ⁽¹⁾

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions		
	The fireplace must be installed maintained and operated in accordance with the following specifications:	Permitted fuels (other than authorised fuels):	
s.r.o., Sedlište 227, postal code 739 36, district Frýdek-Mistek Czech Republic.			
Handöl 31, Handöl 31A, Handöl 32, Handöl 32A, Handöl 33T, Handöl 34T, Handöl 35T, Varde Ovne Look 1, Varde Ovne Look 2, Varde	Installation instructions IAV SE/EX 0811-4 511941 Lighting instructions BAV SE/EX H30 511942.	Untreated dry wood with less than 20% moisture ⁽¹⁾	
Ovne Look 3, all manufactured by NIBE AB Box 134, 285 23 Markaryd, Sweden	A permanent stop must be in place on the air inlet to prevent closure beyond the 45% open position.		
Handöl 50, Handöl 51, Handöl 52, Handöl 52T, Handöl 53, Handöl 54, Handöl 54T, Handöl 51L, Varde Ovne S1, Varde Ovne S2, Varde Ovne S3, all	Installation instruction IAV SE/EX 0737-4 511866 Lighting instruction BAV SE/EX 0717-1 511865.	Untreated dry wood with less than 20% moisture ⁽¹⁾	
manufactured by NIBE AB Box 134 285 23 Markaryd, Sweden	A permanent stop must be in place on the air inlet to prevent closure beyond the 45% open position.		
Harrie Leenders Cylon	Instruction manual references	Wood logs ⁽¹⁾	
Harrie Leenders Doran 160	"Supplementary Instructions Amended June 2010"		
Harrie Leenders Doran 190	The appliance must be fitted with a mechanical stop to		
Harrie Leenders Fuga S	prevent closure of the air slide		
Harrie Leenders Fuga eL	beyond the 15mm open position		
Harrie Leenders Stor			
Harrie Leenders Signa			
Stoves manufactured by Harrie Leenders Industrieweg 255688 DP Oirschot Netherlands			
HDG Compact models 25/35 (25 kW, 35 kW) wood chip and pellet boilers manufactured by HDG Bavaria Gesellschaft mit beschrankter Haftung (GmbH),	The manufacturer's operating instructions for the HDG Compact 25/35 with HDG Hydronic reference "HDG	Wood chip or wood pellets ⁽¹⁾	

The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives
or coatings.

Fireplace	Conditi	ions
	The fireplace must be installed maintained and operated in accordance with the following specifications:	Permitted fuels (other than authorised fuels):
Siemensstrasse 22, 84323 Massing, Germany	Compact Version V01" of April 2009	
HDG Compact models 50/65 (50 kW, 65 kW) wood chip and pellet boilers manufactured by HDG Bavaria Gesellschaft mit beschrankter Haftung (GmbH), Siemensstrasse 22, 84323 Massing, Germany	Compact 50/65 with HDG Hydronic reference "HDG	Wood chip or wood pellets ⁽¹⁾
(80 kW) wood chip and	1	Wood chip or wood pellets ⁽¹⁾
(100 kW) wood chip and pellet boiler manufactured by	Compact 100/150/200 reference "HDG Compact 100-200 Version	Wood chip or wood pellets ⁽¹⁾
200 (150 kW, 200 kW)	1	Wood chip or wood pellets ⁽¹⁾
HDG Euro models 30, 40 and 50 (30 kW, 40 kW and 50 kW) wood log boilers manufactured by HDG Bavaria Gesellschaft mit beschrankter Haftung (GmbH), Siemensstrasse 22, 84323 Massing, Germany	The manufacturer's operating instructions for the HDG Euro 30/40/50 with Lambda Control 1 reference "HDG Euro V3.0 with HDG Lambda Control 1 Version V1" of June 2008	Split wood logs of 500 mm length and maximum edge length of 120 mm and a residual moisture content of 20% ⁽¹⁾
HDG Navaro models 20, 25 and 30 (20 kW, 25 kW and 30 kW) wood log boilers manufactured	The manufacturer's operating instructions for the HDG Navora 20/25/30 with Lambda Control 1	Split wood logs of 500 mm length and maximum edge length of 120 mm and a

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed maintained and operated in accordance with the following specifications:	Permitted fuels (other than authorised fuels):
by HDG Bavaria Gesellschaft mit beschrankter Haftung (GmbH), Siemensstrasse 22, 84323 Massing, Germany	reference "HDG Navora 20/25/30 with HDG Lambda Control 1 Version V2" of June 2008	residual moisture content of 20% ⁽¹⁾
PM15, 15 kW wood pellet boiler manufactured by HDG	Pelletmaster 15/25 reference "HDG Pelletmaster Version V1"	Wood pellets ⁽¹⁾
Herz BioFire BF 1000 manufactured by Herz Engietechnik GmbH. Herstraße 1, 7423 Pinkafeld Österreich/ Austria	Instruction manual references "Operating instructions HERZ BioFire 500 – 1000 Biocontrol" Reference "Betriebsanleitung Biofire 500-1000 Biocontrol Englisch V1.2.doc"	Wood Chips and pellets ⁽¹⁾
Herz BioFire BF 500 manufactured by Herz Engietechnik GmbH. Herstraße 1, 7423 Pinkafeld Österreich/ Austria	Instruction manual references "Operating instructions HERZ BioFire 500 – 1000 Biocontrol" Reference "Betriebsanleitung Biofire 500-1000 Biocontrol Englisch V1.2.doc"	Wood Chips and pellets ⁽¹⁾
Herz BioFire BF 600 manufactured by Herz Engietechnik GmbH. Herstraße 1, 7423 Pinkafeld Österreich/ Austria	Instruction manual references "Operating instructions HERZ BioFire 500 – 1000 Biocontrol" Reference "Betriebsanleitung Biofire 500-1000 Biocontrol Englisch V1.2.doc"	Wood Chips and pellets ⁽¹⁾
Herz BioFire BF 800 manufactured by Herz Engietechnik GmbH. Herstraße 1, 7423 Pinkafeld Österreich/ Austria	Instruction manual references "Operating instructions HERZ BioFire 500 – 1000 Biocontrol" Reference "Betriebsanleitung Biofire 500-1000 Biocontrol Englisch V1.2.doc"	Wood Chips and pellets ⁽¹⁾
Herz Firematic FM 100 manufactured by Herz Engietechnik GmbH. Herstraße 1, 7423 Pinkafeld Österreich/ Austria	Assembly and installation Instructions "HERZ firematic 20 – 101 BioControl" Reference "04.001" Installation Instructions – "Herz Firematic (1Ph) 20-101" Operating instructions "HERZ firematic 20 - 101 BioControl"	Wood Chips and pellets ⁽¹⁾

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditi	ons
	The fireplace must be installed maintained and operated in accordance with the following specifications: Reference "Betriebsanleitung firematic 20-101 BioControl Englisch V 2.53.doc"	Permitted fuels (other than authorised fuels):
Heta Scanline 500D, 510D, 520D and 530D wood burning stoves distributed in the UK by Pevex Enterprises Limited, Unit 16 Seven Acres Business Park, Newbourne Road, Waldringfield Nr Woodbridge. IP12 4PS		Dry wood logs ⁽¹⁾
7BD, 7CD and 7DD wood burning stoves distributed in the UK by Pevex Enterprises Limited, Unit 16 Seven Acres Business Park, Newbourne		Dry wood logs ⁽¹⁾
Highlander 5 Clean Burn Manufactured by Dunsley Heat Limited, Bridge Mills, Huddersfield, Holmfirth, West Yorkshire, HD9 3TW		Wood logs ⁽¹⁾ conforming to BS EN 13240:2001
model number HF905-SE. UK Distribution Hi-Flame Limited,	Instruction manual references "HF905/UK-NI-ROI/V2.1-06-11" Dated June 2011 Fitted with a mechanical stop to prevent closure of the main air control beyond the 50% open position	Wood Logs ⁽¹⁾
Hotpod Limited Edition manufactured by Hotpod LLP, PO Box 137, St Ives Cornwall TR26 2WW	Instruction manual reference "Version 3" dated June 2011	Wood Logs ⁽¹⁾
Hotpod Unlimited manufactured by Hotpod LLP, PO Box 137, St Ives Cornwall TR26 2WW	Instruction manual reference "Version 3" dated June 2011	Wood Logs ⁽¹⁾

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditi	ons
	The fireplace must be installed maintained and operated in accordance with the following specifications:	Permitted fuels (other than authorised fuels):
The Hoval AgroLyt 20, 25, 35, 45 and 50 manufactured by Hoval AG, Austrasse 70, 9490 Vaduz, Liechtenstein	Installation and operation manuals dated January 2006, reference 4 205/194/00, and June 2006, reference 205 193/00	Wood logs with less than 20% moisture ⁽¹⁾
Hoval BioLyt 160 pellet boiler manufactured by Hoval Limited, Hoval Limited,Northgate, Newark, Nottinghamshire NG24 1JN	wood pellet heating boiler	Wood Pellets ⁽¹⁾
Hoval BioLyt 50 and 70 manufactured by Hoval AG, Austrasse 70, 9490 Vaduz, Liechtenstein	Installation and operating manuals referenced 4 204 794/01 and 4 204 793/2 dated 06/07	Wood Pellets ⁽¹⁾
Hoval Forester UFS 180, 240, 300, 360, 450, 550, 700, 900, 1200, 1600 manufactured by Schmid AG, Wood firing Systems PO Box 42, CH-8360 Eschlikon, Switzerland		Wood Pellets or Wood Chips ⁽¹⁾ following CEN/TS 14961
Hoval Forester MGS 150, 180, 240, 300, 360, 450, 550, 700, 900 boilers manufactured by Schmid AG, Wood firing systems PO Box 42, CH-8380 Eschikon Switzerland.	MGS_MMXXXv1" (Where	Wood Pellets or Wood Chips following CEN/TS 14961 ⁽¹⁾
	Installation and operation manual referenced STU man/01 dated 11/07 or the installation and operation manual referenced STU/man/01/1 dated 06/08.	Wood Pellets ⁽¹⁾
Hoval STU 600, 800 and 1000 manufactured by Hoval Limited, Hoval Limited, Northgate, Newark, Nottinghamshire. NG24 1JN		Wood Pellets ⁽¹⁾
Huntingdon 25 clear door (model number 7057) and Huntingdon 25 tracery	l	Untreated dry wood ⁽¹⁾

The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives
or coatings.

Fireplace	Conditions	
	The fireplace must be installed maintained and operated in accordance with the following specifications:	Permitted fuels (other than authorised fuels):
door (model number 7058) manufactured by Stovax Limited, Falcon Road, Sowton Industrial Estate, Exeter, Devon, EX2 7LF	place on the secondary air inlet to prevent closure beyond the 75% open position	
The Hwam Beethoven and Hwam Beethoven H (4.5 kW nominal thermal output manufactured by HWAM Heat Design AS Nydamsvej 53, 8362 Hørning, Denmark	(HBS) Limited's operational	Untreated dry wood ⁽¹⁾
The Hwam Mozart (4.5 kW nominal thermal output) manufactured by HWAM Heat Design AS Nydamsvej 53, 8362 Hørning, Denmark	Euroheat Distributors (HBS) Limited's operational instructions dated November 2006, reference IN1141 Ed B The appliance must be fitted with a mechanism to prevent closure of the air wash/ secondary air control.	Untreated dry wood ⁽¹⁾
The Hwam Ravel (4.5 kW nominal thermal output) manufactured by HWAM Heat Design AS Nydamsvej 53, 8362 Hørning, Denmark	(HBS) Limited's operational	Untreated dry wood ⁽¹⁾
The Hwam Vivaldi (4.5 kW nominal thermal output) manufactured by HWAM Heat Design AS Nydamsvej 53, 8362 Hørning, Denmark	Euroheat Distributors (HBS) Limited's operational instructions dated November 2006, reference IN1141 Ed B The appliance must be fitted with a mechanism to prevent closure of the air wash/ secondary air control.	Untreated dry wood ⁽¹⁾
The Hwam 30 (4.5 kW nominal thermal output) manufactured	(HBS) Limited's operational	Untreated dry wood preservatives

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditi	ions
	The fireplace must be installed maintained and operated in accordance with the following specifications:	Permitted fuels (other than authorised fuels):
by HWAM Heat Design AS Nydamsvej 53, 8362 Hørning, Denmark	instructions dated November 2006, reference IN1141 Ed B	
Delimark	The appliance must be fitted with a mechanism to prevent closure of the air wash/ secondary air control.	
Insert 100 Crystal manufactured by La Nordica Spa, Via Summany 104 M. Precalcino 36030, Vicenza, Italy		Wood logs ⁽¹⁾
Insert 50 Crystal manufactured by La Nordica Spa, Via Summany 104 M. Precalcino 36030, Vicenza, Italy	Instruction manual references '6096801-Rev. 17' dated 22nd December 2010. A mechanical stop to prevent closure of the secondary air control beyond the 40% open position must be fitted.	Wood logs ⁽¹⁾
Insert 70 Crystal manufactured by La Nordica Spa, Via Summany 104 M. Precalcino 36030, Vicenza, Italy	Instruction manual references '6096801-Rev. 17' dated 22nd December 2010. A mechanical stop to prevent closure of the secondary air control beyond the 40% open position must be fitted.	Wood logs ⁽¹⁾
Insert 80 Crystal manufactured by La Nordica Spa, Via Summany 104 M. Precalcino 36030, Vicenza, Italy	Instruction manual references '6096801-Rev. 17' dated 22nd December 2010. A mechanical stop to prevent closure of the secondary air control beyond the 40% open position must be fitted	Wood logs ⁽¹⁾
Italy Built In manufactured by La Nordica Spa, Via Summany 104 M. Precalcino 36030, Vicenza, Italy	Instruction manual references '7095401' Rev.02' dated 13th December 2010	Wood logs ⁽¹⁾
Italy Termo DSA manufactured by La Nordica Spa, Via Summany 104 M. Precalcino 36030, Vicenza, Italy	Instruction manual references '7095802 Rev. 06' dated 1st February 2011	Wood logs ⁽¹⁾
Instyle 400 and 550 stoves manufactured by Dik Geurts Haardkachels BV, Industrieweg	Instruction manual referenced "Instruction_manual_Instyle_1209	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions		
	The fireplace must be installed maintained and operated in accordance with the following specifications:	Permitted fuels (other than authorised fuels):	
Oost 11, 6662 NE Elst (Gld), The Netherlands			
Jetmaster 18f stove manufactured by Jetmaster Fires Limited, Unit 2, Peacock Trading Estate, Goodwood Road, Eastleigh, Hampshire SO50 4NT	Instruction manual references "106870/18f/60f/Issue No.5" dated "June 2011"	Dry wood logs ⁽¹⁾	
Jotul F100 manufactured by Jotul UK Ltd, Unit 1, The IO Centre, Nash Road, Park Farm, Redditch, Worcestershire, B98 7AS	Instruction manual reference '129980' dated September 2002 and smoke control area modification reference 'UK F100 SC appendix' dated 2010. The appliance must be fitted with a permanent stop that prevents the closure of the secondary air control beyond the 50% open position	Wood logs ⁽¹⁾	
Jydepejsen Country 510 and 760 5kW stoves manufactured by Jydepejsen A/S, Ahornsvinget 3-7, Nr.Felding, DK-7500, Holstebro, Denmark	Instruction user manual "Country001" reference "Jydepejsen A/S - June 2011" dated June 2011. A permanent stop must be fitted to the secondary air control such that it cannot be closed less than 35%.	Wood logs ⁽¹⁾	
KÖB Pyromat-DYN (KPM-DYN) Models 45, 65 and 85 manufactured by Viessmann Ltd, Hortonwood 30,Telford, Shropshire, TF1 7YP	Instruction manual references "ID 103689-L English" dated 01.01.2005 and instruction manual "ID: 103708-G English"	Wood logs (up to 0.5m) and off cuts of natural timber, wood chips and pellets ⁽¹⁾	
KÖB Pyromat-ECO (KPM-ECO) Models 35, 45, 55, 65, 75, 85,manufactured by Viessmann Ltd, Hortonwood 30,Telford, Shropshire, TF1 7YP	Instruction manual references "ID 104646-D English" dated 01.01.2005 and instruction manual "ID: 104642-B English"	Wood logs (up to 0.5m) and off cuts of natural timber ⁽¹⁾	
KÖB Pyromat-ECO (KPM-ECO) Models 61, 81, 101 and 151 manufactured by Viessmann Ltd, Hortonwood 30,Telford, Shropshire, TF1 7YP	Instruction manual references "ID 104646-D English" dated 01.01.2005 and instruction manual "ID: 104642-B English"	Wood logs (up to 1.0m) and off cuts of natural timber ⁽¹⁾	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed maintained and operated in accordance with the following specifications:	Permitted fuels (other than authorised fuels):
KÖB Pyrot (KRT) Models 100, 150, 220, 300, 400 and 540 manufactured by Viessmann Ltd, Hortonwood 30,Telford, Shropshire, TF1 7YP	Instruction manual references "ID 104654-H English" dated 01.01.2005 and instruction manual "ID: 106811-H English"	Wood chips or pellets ⁽¹⁾
KÖB Pyrtec (KPT) Models 390, 530, 720, 950 and 1250 and manufactured by Viessmann Ltd, Hortonwood 30,Telford, Shropshire, TF1 7YP	"ID 104661-F English" dated 01.01.2005 and instruction	Wood chips or pellets ⁽¹⁾
Kooga Cleanburn Stove manufactured by Percy Doughty & Co, Imperial Point, Express Trading Estate, Stone Hill Road, Farnworth, Bolton, BL4 9TN	Instruction manual references "KCB 04/10A" dated April 2010	Wood logs ⁽¹⁾
KOZ550, 639 kW output pellet boiler manufactured by Kaylioglu Kasabasi (Izmir- Istanbul Yolu Uzeri) P.K 23 Akhisar/Manisa Turkey	Only when used with a Glosfume model BMF 208 ceramic particulate filter. The Green energy engineering Ltd (GEE) KOZ550 pellet boiler owner/operator's manual reference version 1A 2010 dated December 2010. The Glosfume Ltd maintenance and instruction manual for Glosfume BMF Biomass Fiilter units (50 – 100kW) version AEE001-VER 4 dated December 2010	6mm diameter wood pellets ⁽¹⁾
KWB TDS Powerfire 130, 240 and 300 manufactured by KWB – Kraft und Wärme aus Biomasse Gesellschaft mit beschränkter Haftung (GmbH) of Industriestrasse 235, A-8321 St. Margarethen an der Raab	The manufacturer's instructions dated 14th May 2008, reference BA TDS-05.2008, including specification of recommended fuels	Wood pellets or wood chips ⁽¹⁾
KWB TDS Powerfire 150 manufactured by KWB – Kraft und Wärme aus Biomasse Gesellschaft mit beschränkter Haftung (GmbH)	The manufacturer's instructions dated August 2005, reference BA TDS-0805	Wood pellets or wood chips ⁽¹⁾

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditi	ions
	The fireplace must be installed maintained and operated in accordance with the following specifications:	Permitted fuels (other than authorised fuels):
of Industriestrasse 235, A-8321 St. Margarethen an der Raab		
Lin-ka H1500 Hot Water Boiler fitted with either a monocyclone (type LIN-KA 2000) or a multi-cyclone (type LIN-KA 3x2) manufactured by LIN-KA Maskinfabrik A/S, Nylandsvej 38 DK-6940 Lem St. Denmark	Instruction manual reference "LIN-KA H 1500 Hot Water Manual/Ver. 2005/Rev. 1.10" dated 27/01/2010	Wood Pellets of maximum diameter 8mm ⁽¹⁾
The Little Thurlow Smoke Control Wood Burning Stove manufactured by Town & Country Fires Limited, 1 Enterprise Way, Thornton Road Industrial Estate, Pickering, North Yorkshire, YO18 7NA	Town and Country Fires' operating instructions dated 30 June 2007, issue No. 3	Seasoned logs of less than 20 per cent moisture and of a maximum length of 350mm ⁽¹⁾
Little Wenlock Classic Wood Fuel Stove manufactured by Aga, Station Road, Ketley, Telford, Shropshire, TF1 5AQ	Operating instructions dated 19th December 2008, reference N00471AXX Rev 001 DP081219	Dry and split wood logs of a maximum length of 25 cm and a maximum diameter of 10 cm ⁽¹⁾
Lotus Liva 1, Liva 2, Liva 3 and Liva 4G Stoves manufactured by Lotus Heating Systems A/S, Agertoften 6, 5550 Langeskov, Denmark	Instruction manual "Mounting and User Instructions Lotus-Liva series Stoves" Version 4 dated January 2010	Wood logs ⁽¹⁾
Lotus Sola, Sola S, Sola M and Sola MST Stoves manufactured by Lotus Heating Systems A/S Agertoften 6, 5550 Langeskov, Denmark	Instruction manual "Mounting and User Instructions Lotus-Sola series Stoves" Version 2 dated January 2010.	Wood logs ⁽¹⁾
The Løvenholm manufactured by Hunter Stoves Limited, Unit 6, Old Mill Industrial Estate, Stoke Canon, Exeter, Devon, EX5 4RJ		Untreated wood with a moisture content below 20% ⁽¹⁾
The Løvenholm, Løvenholm Traditional, Løvenholm European, Løvenholm Pedestal stoves manufactured by Hunter Stoves Limited, Unit 6, Old Mill Industrial Estate, Stoke	Løvenholm Multifuel stove installation and operation manual version 06/09	Untreated wood with a moisture content below 20% ⁽¹⁾

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed maintained and operated in accordance with the following specifications:	Permitted fuels (other than authorised fuels):
Canon, Exeter, Devon, UK EX5 4RJ		
Ludlow Wood Burning Smoke Exempt Stove (Ludlow Stove SE) manufactured by Aga Station Road, Ketley Telford Shropshire. TF1 5AQ	Instruction manual references "N00529AXX REV:001" dated 13 th July 2011	Dry wood Logs ⁽¹⁾
MEG 4.5 (also known as the Sirius 450) manufactured by Meg Stoves, FE Robinson (Hooton) Ltd, Station Works, Hooton Road, Hooton South Wirral CH66 7NF	Instruction manual references 'Meg Solid Fuel Stoves manual (107)' dated 28 th January 2011	Wood logs ⁽¹⁾
MEG 7.5 (also known as the Sirius 750) manufactured by Meg Stoves, FE Robinson (Hooton) Ltd, Station Works, Hooton Road, Hooton South Wirral CH66 7NF	Instruction manual references 'Meg Solid Fuel Stoves manual (107)' dated 28 th January 2011	Wood logs ⁽¹⁾
Mescoli PB50	Instruction and Installation	Wood Pellets ⁽¹⁾ following
Mescoli PB35 Mescoli PB28	manual reference "SY315EVO P,C,B – COMBIFIRE 2 PB28/35/50 BOILERS" Edition 1.7 dated 1/2006	ÖNORM M7 135 or DIN plus (DIN 51731)
Manufactured by MESCOLI CALDAIE S.rI. Caldaie – Termocucine Via del Commercio, 285 4 1058 Vignola (MO) Italy.	- 17 	
Micromet MEG 4.5 stove (also known as the Sirius 450) manufactured by Micromet 125 Bridge St Birkenhead Merseyside CH41 1BD		Dry Wood logs ⁽¹⁾
Micromet MEG 7.5 stove (also known as the Sirius 750) manufactured by Micromet 125 Bridge St Birkenhead Merseyside CH41 1BD	Instruction manual references "Micromet Solid Fuel Stoves Manual (24)" dated 16/06/2010	Dry Wood logs ⁽¹⁾
by Chesney's Ltd, 194-200	Instruction manual references 'CH4K Milan-V2' dated 18 th	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditi	ions
Battersea Park Road, London SW11 4ND	The fireplace must be installed maintained and operated in accordance with the following specifications: November 2010. Fitted with a system to prevent closure of the air control beyond the 25mm open position	Permitted fuels (other than authorised fuels):
Milan Series 6 manufactured by Chesney's Ltd, 194-200 Battersea Park Road, London SW11 4ND	Instruction manual references 'CH6K Milan-V2' dated 18 th November 2010. Fitted with a system to prevent closure of the air control beyond the 40mm open position	Wood logs ⁽¹⁾
Monaco multifuel Stove, Staub Fonderie-Franco Belge model 1340605 manufactured by Staub Fonderie-Franco Belge, Rue Orphee Variscotte, BP73 59660 Merville, France	Instruction manual references '1303 -1' dated 4 th May 2010. Appliances must be fitted with a mechanical stop to prevent closure of the secondary air control beyond 4mm from closed	Wood logs ⁽¹⁾
Monfort MK2 Stove manufactured by Franco Belge Staub, Staub Fonderie, Rue Orphee Variscotte, BP73, 59660 Merville, France	Instruction manual reference "1295-3" dated 17th November 2009. The appliance must be fitted with a mechanical stop to prevent closure of the secondary air control beyond the 25% open position	Wood logs ⁽¹⁾
Monterrey 6 , York Midi Serrano 5 manufactured by Broseley Fires Ltd, Knights Way, Battlefield Enterprise Park, Shrewsbury, Shropshire, SY1 3AB		Wood logs ⁽¹⁾
MORSØ-Ø4 manufactured by MORSØ Limited, Unit 7- io centre Valley Drive, Swift Valley, Rugby, Warwickshire, CV21 1TW	Instruction manual references "Ø- Collection" dated 01.02.2010 and instruction manual "72000400" dated 01.02.2010. Applies to units manufactured after 01 February 2010	Wood logs ⁽¹⁾
The Morsø 1400 series consisting of the 1412 and 1442 manufactured by Morsø	Installation and operation manual dated 10th January 2008, reference 72146800	Wood logs with less than 20% moisture ⁽¹⁾

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed maintained and operated in accordance with the following specifications:	Permitted fuels (other than authorised fuels):
Jernstøberi A/S DK-7900 Nykøbing, Mors, Denmark		
The Morsø 3100 series consisting of the 3112 and 3142 models manufactured by Morsø Jernstøberi A/S DK-7900 Nykøbing, Mors, Denmark		Wood logs with less than 20% moisture ⁽¹⁾
The Morsø 6140 and 6148 manufactured by Morsø Jernstøberi A/S DK-7900 Nykøbing, Mors, Denmark	Installation and operation manual dated 4th September 2007, reference 72610400	Wood logs with less than 20% moisture ⁽¹⁾
Morsø Model 7600 including Model 7642, 7644 and 7648 stoves manufactured by Morsø Limited, UK distribution by Morsø UK limited, Unit 7, The io Centre, Valley Drive, Swift Valley, CV21 1TW		Wood logs with less than 20% moisture ⁽¹⁾
The Morsø Owl 3410, 3420 and 3440 for wood burning manufactured by manufactured by Morsø Jernstøberi A/S DK-7900 Nykøbing, Mors, Denmark	dated 1st January 2000, reference	Untreated dry wood which has been split, stacked and air dried, or air dried wood briquettes ⁽¹⁾
Nestor Martin C23 multifuel stove (7.7 kW) manufactured by Nestor Martin S.A., 11 Rue De Lion, B-5660, Frasnes Les Couvin, Belgium.	Euroheat Distributors (HBS) Limited's operation Instructions Reference: "IN1213 Edition B" and dated June 2010.	Untreated dry wood ⁽¹⁾
Nestor Martin C33 multifuel stove (9.2 kW) manufactured by Nestor Martin S.A., 11 Rue De Lion, B-5660, Frasnes Les Couvin, Belgium.	Euroheat Distributors (HBS) Limited's operation Instructions Reference: "IN1213 Edition B" and dated June 2010.	Untreated dry wood ⁽¹⁾
Nestor Martin D33 multifuel stove (8 kW) manufactured by Nestor Martin S.A., 11 Rue	Euroheat Distributors (HBS) Limited's operation Instructions Reference: "IN1213 Edition B" and dated June 2010.	Untreated dry wood ⁽¹⁾

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditi	ons
	The fireplace must be installed maintained and operated in accordance with the following specifications:	Permitted fuels (other than authorised fuels):
De Lion, B-5660, Frasnes Les Couvin, Belgium.		
Nestor Martin 'Harmony' H13 multifuel stove (5 kW) manufactured by Nestor Martin S.A., 11 Rue De Lion, B-5660, Frasnes Les Couvin, Belgium.	Euroheat Distributors (HBS) Limited's operation Instructions Reference: "IN1116 Edition D5" and dated June 2010. The minimum air bleed flap must be set at a minimum of 14.5mm	Untreated dry wood ⁽¹⁾
Nestor Martin 'Harmony' H23 (6 kW) and H33 (8 kW) multifuel stoves manufactured by Nestor Martin S.A., 11 Rue De Lion, B-5660, Frasnes Les Couvin, Belgium.	Euroheat Distributors (HBS) Limited's operation Instructions Reference: "IN1116 Edition D5" and dated June 2010.	Untreated dry wood ⁽¹⁾
Nestor Martin IN13 Insert multifuel stove (5 kW) manufactured by Nestor Martin S.A., 11 Rue De Lion, B-5660, Frasnes Les Couvin, Belgium.	Euroheat Distributors (HBS) Limited's operation Instructions Reference: "IN1214 Edition B" and dated June 2010. The minimum air bleed flap must be set at a minimum of 14.5mm	Untreated dry wood ⁽¹⁾
Nestor Martin 'Stanford' S13 multifuel stove (3.5 kW) manufactured by Nestor Martin S.A., 11 Rue De Lion, B-5660, Frasnes Les Couvin, Belgium.	Euroheat Distributors (HBS) Limited's operation Instructions Reference: "IN1116 Edition D5" and dated June 2010. The minimum air bleed flap must be set at a minimum of 14.5mm	Untreated dry wood ⁽¹⁾
Nestor Martin 'Stanford' S23 (6 kW), SP23 (6 kW), S33 (8 kW) and SP33 (8 kW) multifuel stoves manufactured by Nestor Martin S.A., 11 Rue De Lion, B-5660, Frasnes Les Couvin, Belgium.		Untreated dry wood ⁽¹⁾
The Nestor Martin R23 multifuel Stove (6 kW) manufactured by Nestor	Euroheat Distributors (HBS) Limited's operational	Untreated dry wood ⁽¹⁾

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed maintained and operated in accordance with the following specifications:	Permitted fuels (other than authorised fuels):
Martin, S A 11 Rue De Lion, B-5660, Frasnes Les Couvin, Belgium.	instructions. Reference: "IN1141 Edition B" and November 2006.	
Nestor Martin IT13 multifuel stove (3.5 kW) manufactured by Nestor Martin S.A., 11 Rue De Lion, B-5660, Frasnes Les Couvin, Belgium.	Euroheat Distributors (HBS) Limited's operation Instructions Reference: "IN1180 Edition D1" and dated June 2010. The minimum air bleed flap must be set at a minimum of 14.5mm	Untreated dry wood ⁽¹⁾
Nestor Martin R33 (8 kW) multifuel stove manufactured by Nestor Martin S.A., 11 Rue De Lion, B-5660, Frasnes Les Couvin, Belgium.	Euroheat Distributors (HBS) Limited's operation Instructions Reference: "IN1116 Edition D" and dated January 2007.	Untreated dry wood ⁽¹⁾
Newark EGTL05 manufactured by Elite Group Trading Limited, Room 1208 Kak Tak, Commercial Building 317-319 Des Voeux Road,Central Hong Kong 999077	Instruction manual references "EGTL05 Version 1.4" dated 5 th July 2011. The appliance must be fitted with a permanent stop to prevent any closure of the tertiary air control	Wood Logs (1)
Nørreskoven MkII manufactured for Hunter Stoves Ltd, Unit 6, Old Mill Industrial Estate, Stoke Canon, Devon EX5 4RJ	Instruction manual references 'Cleanburn, Nørreskoven MkII multifuel stove installation and operating instructions, v01.11' dated January 2011. The appliance must be fitted with stop to prevent closure of secondary air control beyond 40%	Wood logs ⁽¹⁾
Octoplus 10 and Octoplus 15 Boiler manufactured by Solarfocus, Werkstrasse 1 4451 St. Ulrich, Steyr, Austria	Installation instructions version 1.1 dated 19 th April 2010. Operating manual version 10.051 dated 10 th May 2010	Wood logs ⁽¹⁾
ÖkoFEN Pellematic PE08, PE12, PE16, PE20, PE25, PE32, PEK12, PEK16, PEK20, PEK25, PEK32, PES12, PES16, PES20, PES25, PES32, PESK12, PESK16, PESK20, PESK25 and PESK32 manufactured by ÖkoFEN	ÖkoFEN operation instructions dated February 2007, reference PE/HB/001.E	Wood pellets of maximum diameter 6 mm and maximum length 4 cm ⁽¹⁾

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditi	ons
	The fireplace must be installed maintained and operated in accordance with the following specifications:	Permitted fuels (other than authorised fuels):
Forschungs- und Entwicklungs Ges.m.b.H of Gewerbepark 1, 4133 Niederkappel, Austria		
ÖkoFEN Pellematic PE36, PE48, PE56, PESK36, PESK48, PESK56, PEK36, PEK48, PEK56, PES36, PES48 and PES56 manufactured by ÖkoFEN Forschungs- und Entwicklungs Ges.m.b.H of Gewerbepark 1, 4133 Niederkappel, Austria	ÖkoFEN operation instructions reference PBV 2000 CMP 1.4 (V2.31) and with revision dated March 2008	Wood pellets of maximum diameter 6 mm and maximum length 4 cm ⁽¹⁾
Olymberyl Baby Gabriel model number HF217-SE. UK Distribution by Hi-Flame Limited, Unit 7B Holmes Chapel Business Park Manor Lane Holmes Chapel Cheshire CW4 8AF	Instruction manual references "HF217-SE/UK-NI-ROI/V2.16-06-11" Dated June 2011. The appliance must be fitted with a mechanical stop to prevent closure of the secondary air control beyond the 3mm open position	Wood Logs ⁽¹⁾
The Orchard Ovens models: FVR Speciale 80, 100, 110, 110 x 160 and 120; TOP Superiore 100 and 120; GR 100, 120, 140, 120 x 160, 140 x 160, 140 x 180 and 180; OT 100, 120, 140, 120 x 160, 140 x 160, 140 x 180 and 180; the Valoriani Piccolo, all of which are manufactured by Valoriani of Via Caselli alla Fornace, 213, 50066 Reggello, Firenze, Italy	The manufacturer's instructions dated 25 th October 2004, references: Instruction Model OOLinst. 1 FVR 80 OOLinst. 2 FVR 100 OOLinst. 3 FVR 110 OOLinst. 4 FVR 120 OOLinst. 5 FVR 110 x 160 OOLinst. 6 TOP 100 OOLinst. 7 TOP 120 OOLinst. 8 GR 100 and OT 100 OOLinst. 9 GR 120 and OT 120 OOLinst. 10 GR 140 and OT 140	Untreated dry wood ⁽¹⁾
	OOLinst. 11 GR 120 x 160 and OT 120 x 160	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditi	ons
	The fireplace must be installed maintained and operated in accordance with the following specifications: OOLinst. 12 GR 140 x 160 and OT 140 x 160 OOLinst. 13 GR 140 x 180 and OT 140 x 180 OOLinst. 14 GR 180 and OT 180 OOLinst. 15 Valoriani Piccolo	Permitted fuels (other than authorised fuels):
Oregon EGTL03 manufactured by Elite Group Trading Limited, Room 1208 Kak Tak Commercial Building 317-319 Des Voeux Road, Central Hong Kong 999077	Instruction manual references "EGTL03 Version 1.3" dated 5 th July 2011	Wood Logs ⁽¹⁾
Pelle 5kW stove, Vidar Small 5kW stove and Vidar Medium 7.6kW stove manufactured by Dik Geurts Haardkachels BV, Industrieweg Oost 11, 6662 NE Elst (Gld), The Netherlands	Instruction manual reference "8900009004" dated July 2011	Dry wood logs ⁽¹⁾
Pelle 5kW stove, Vidar Small 5kW stove and Vidar Medium 7.6kW stove manufactured by Dik Geurts Haardkachels BV, Industrieweg Oost 11, 6662 NE Elst (Gld), The Netherlands	Instruction manual reference "8900009004" dated July 2011	Dry wood logs ⁽¹⁾
	Operating instructions dated November 2007, reference V2.2	Wood pellets corresponding to ÖNORM M7135 of 6 mm diameter ⁽¹⁾
PelletTop 15 and PelletTop 25 Boiler manufactured by Solarfocus, Werkstrasse 1 4451 St.Ulrich, Steyr, Austria	Installation instructions version 020905 dated 2 nd September 2005. Operating manual version 270906 dated 27 th September 2006	Wood pellets ⁽¹⁾
Pevex Bohemia X 30, X 40, X40 Cube, X 50 and X 60	Instruction manual references 'AH/Ver3' dated July 2010	Dry wood logs ⁽¹⁾

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed maintained and operated in accordance with the following specifications:	Permitted fuels (other than authorised fuels):
multi-fuel stoves manufactured by Pevex Enterprises Limited, Unit 16 Seven Acres Business Park, Newbourne Road, Waldringfield Nr Woodbridge, IP12 4PS		
Inset multi-fuel appliance manufactured by Pevex	be fitted with permanent stops	Dry wood logs ⁽¹⁾
Pevex Serenity 40D inset multi- fuel appliance manufactured by Pevex Enterprises Limited, Unit 16 Seven Acres Business Park, Newbourne Road, Waldringfield, Nr Woodbridge, IP12 4PS	Instruction manual references "Pevex1003/AH/ver2" and dated June 2011. The appliance must be fitted with permanent stops that ensure the secondary and tertiary air controls do not close beyond 1.1cm open and 2cm open positions respectively.	Dry wood logs ⁽¹⁾
Portway 1 Stove manufactured by BFM Europe Limited, Trentham Lakes, Stoke on Trent, Staffordshire, ST4 4TJ	Instruction manual referenced: 'Solid Fuel Stoves Manual issued - 20/08/2009 (291) 2' The appliance must be used with a modification to the secondary air slide which inhibits closure further than the 25mm from the left position.	Wood logs ⁽¹⁾
Portway 2 and 3 Stoves manufactured by BFM Europe Limited, Trentham Lakes, Stoke on Trent, Staffordshire, ST4 4TJ	Instruction manual referenced: 'Solid Fuel Stoves Manual issued - 20/08/2009 (291) 2'. The appliance must be used with a modification to the secondary air slide which inhibits closure further than the 20mm from the left position.	Wood logs ⁽¹⁾
Portway Inset Stove manufactured by BFM Europe Limited, Trentham Lakes,	Instruction manual referenced: 'Solid Fuel Stoves Manual issued - 20/08/2009 (291) 2'.	Wood logs ⁽¹⁾

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditi	ions
Stoke on Trent, Staffordshire, ST4 4TJ	The fireplace must be installed maintained and operated in accordance with the following specifications: A modification of the secondary air control must be implemented such that the 20mm from left position is maintained during use. In addition the primary air control must be modified such that the minimum setting allows a bleed of air to pass through	Permitted fuels (other than authorised fuels):
The Quadra-Fire 2100 Millennium Freestanding Wood Burning Stove manufactured by Hearth & Home Technologies 1445 North Highway, Colville, WA 99114, USA	The manufacturer's instructions dated 9th October 2003, reference 250–6931B	Dry cured untreated wood of maximum size 38.1 cm x 10.16 cm x 5.08 cm ⁽¹⁾
The Quadra-Fire Cumberland Gap Freestanding Wood Burning Stove manufactured by Hearth & Home Technologies 1445 North Highway, Colville, WA 99114, USA	The manufacturer's instructions dated 8th July 2003, reference 7006–186	Dry cured untreated wood of maximum size 43.18 cm x 10.16 cm x 10.16 cm ⁽¹⁾
The Quadra-Fire Yosemite Freestanding Wood Burning Stove manufactured by Hearth & Home Technologies 1445 North Highway, Colville, WA 99114, USA	The manufacturer's instructions dated 4th June 2003, reference 7004–187	Dry cured untreated wood of maximum size 38.1 cm x 10.16 cm x 5.08 cm ⁽¹⁾
manufactured by Rais A/	Instruction manual reference "USER MANUAL Rais 2:1 Revision 2". Dated December 2009. Part number 9106510	Wood Logs ⁽¹⁾
Rais 700 inset stove manufactured by Rais A/ S Industrivej 20, 9900, Frederikshavn, Denmark	Instruction manual reference "USER MANUAL Rais 700 Revision 0". Dated 2010	Wood Logs ⁽¹⁾
Rais Epoca, Rais Poleo 95 and Rais Poleo 106 stoves manufactured by Rais A/S Industrivej 20, 9900, Frederikshavn, Denmark	& Rais Poleo 106 Rais Epoca	Wood Logs ⁽¹⁾
	Instruction manual reference "USER MANUAL Rais Rondo	Wood Logs ⁽¹⁾

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditi	ons
	The fireplace must be installed maintained and operated in accordance with the following specifications:	Permitted fuels (other than authorised fuels):
Rais A/S Industrivej 20, 9900, Frederikshavn, Denmark	& Rais Mino II revision 2". Dated March 2008. Part number 5056510	
Rais Rondo 92 and Rais Rondo 120 stoves manufactured by Rais A/S Industrivej 20, 9900, Frederikshavn, Denmark	Instruction manual reference "USER MANUAL Rais Rondo 92 & Rais Rondo 120 revision 2". Dated December 2009. Part number 4076510	Wood Logs ⁽¹⁾
RAIS Q-Tee 57 manufactured by Rais A/S Industrivej 20, 9900, Frederikshavn, Denmark	Instruction manual references "Manual for RAIS Q-Tee Revision 1" dated 28 th June 2011 and Supplementary instructions Rais Q-Tee dated 7 th July 2011. The appliance must be fitted with a mechanical stop to prevent air control closure beyond the 11.7mm open position	Dry wood Logs ⁽¹⁾
RAIS Q-Tee 65 manufactured by Rais A/S Industrivej 20, 9900, Frederikshavn, Denmark	Instruction manual references "Manual for RAIS Q-Tee Revision 1" dated 28 th June 2011 and Supplementary instructions Rais Q-Tee dated 7 th July 2011. The appliance must be fitted with a mechanical stop to prevent air control closure beyond the 11.7mm open position	Dry wood Logs ⁽¹⁾
RAIS Q-Tee 85 manufactured by Rais A/S Industrivej 20, 9900, Frederikshavn, Denmark	Instruction manual references "Manual for RAIS Q-Tee Revision 1" dated 28 th June 2011 and Supplementary instructions Rais Q-Tee dated 7 th July 2011. The appliance must be fitted with a mechanical stop to prevent air control closure beyond the 11.7mm open position	Dry wood Logs ⁽¹⁾
Redfyre Kensal 20 Flat top (product code RF- EN20M), Redfyre Kensal 33 Flat top (product code RF- KEN33M and RF-KEN33W) manufactured by Redfyre Cookers, Osprey Road, Sowton	The manufacturer's instruction manual dated July 2008, reference PM 247 Issue 1, and instruction manual dated January 2009, reference PM280 Issue 1	Untreated dry wood ⁽¹⁾

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditi	ons
	The fireplace must be installed maintained and operated in accordance with the following specifications:	Permitted fuels (other than authorised fuels):
Industrial Estate, Exeter, Devon, EX2 7JG	A permanent stop must be in place on the secondary air inlet to prevent closure beyond the 50% open position	
Rika Como pellet stove manufactured by RIKA Innovative Ofentechnik GmbH, Müllerviertel 20, AT - 4563 Micheldorf. Austria.	Instruction manual references "IN1226 Edition 1" dated June 2011	6mm wood pellets ⁽¹⁾
Rika Evo Aqua 9 and 15 manufactured by SHT Heiztechik aus Salzburg GmbH, Rechtes Salzachufer 40, A-5101, Salzburg- Bergheim, Austria	Instruction manual references 'J18/HB' dated 27 th February 2009	6mm wood pellets ⁽¹⁾
Rika Memo pellet stove manufactured by RIKA Innovative Ofentechnik GmbH, Müllerviertel 20, AT - 4563 Micheldorf. Austria.	Instruction manual references "IN1228 Edition 1" dated June 2011	6mm wood pellets ⁽¹⁾
Rika Pico pellet stove manufactured by RIKA Innovative Ofentechnik GmbH, Müllerviertel 20, AT - 4563 Micheldorf. Austria.		6mm wood pellets ⁽¹⁾
	Instruction manual references "IN1229 Edition 1" dated June 2011	6mm wood pellets ⁽¹⁾
Rika Topo pellet stove manufactured by RIKA Innovative Ofentechnik GmbH Müllerviertel 20, AT - 4563 Micheldorf. Austria.	Instruction manual references "IN1227 Edition 1" dated June 2011	6mm wood pellets ⁽¹⁾
Riva 40 Cassette 4.9kW stoves manufactured by Stovax Limited, Falcon Road, Sowton Industrial Estate, Exeter, Devon, EX2 7LF	Instruction manual references PM235 Issue 2 dated August 2009 and smoke control kit instruction manual PM375 Issue 2 dated January 2010.	Wood logs ⁽¹⁾

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditi	ons
	The fireplace must be installed maintained and operated in accordance with the following specifications:	Permitted fuels (other than authorised fuels):
	A permanent stop must be positioned to prevent closure of the secondary air control below the 50% open position	
Riva 40 Freestanding, Riva 40 Avanti, Riva 40 Avanti Midi and Riva 40 Avanti Highline 4.9kW stoves manufactured by Stovax Limited, Falcon Road, Sowton Industrial Estate, Exeter, Devon, EX2 7LF	Instruction manual references PM226 Issue 2 dated August 2009 and smoke control kit instruction manual PM375 Issue 2 dated January 2010. A permanent stop must be positioned to prevent closure of the secondary air control below the 50% open position	Wood logs ⁽¹⁾
Riva 55 Cassette, Riva 66 cassette, Riva 66 Avanti cassette stoves manufactured by Stovax Limited, Falcon Road, Sowton Industrial Estate, Exeter, Devon, EX2 7LF		Wood logs ⁽¹⁾
Riva 55 Avanti Midi and Riva 66 Freestanding 8 kW stoves manufactured by Stovax Limited, Falcon Road, Sowton Industrial Estate, Exeter, Devon, EX2 7LF	Instruction manual references PM226 Issue 2 dated August 2009 and smoke control kit instruction manual PM375 Issue 2 dated January 2010. A permanent stop must be positioned to prevent closure of the secondary air control below the 50% open position and the primary air control fixed to allow a bleed of air to enter the firebox from underneath the grate	Wood logs ⁽¹⁾
Riva Plus Small (5 kW), Midi (6.5kW) and Medium (8 kW) Stoves manufactured	Instruction manual references PM231 Issue 3 dated June 2009 and smoke control kit instruction	Wood logs ⁽¹⁾

The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives
or coatings.

Fireplace	Conditi	ons
by Stovax Limited, Falcon Road, Sowton Industrial Estate, Exeter, Devon, EX2 7LF	The fireplace must be installed maintained and operated in accordance with the following specifications: manual PM402 Issue 1 dated November 2009. A permanent stop must be positioned to prevent closure of the secondary air control below the 25% open position	Permitted fuels (other than authorised fuels):
Riva Studio 1 (5kW) freestanding wood stove manufactured by Stovax Limited, Falcon Road, Sowton Industrial Estate, Exeter, Devon, EX2 7LF	Instruction manual references PM452 Issue 1 dated June 2010 and smoke control kit instruction manual PM400 Issue 3 dated June 2010. A permanent stop must be positioned to prevent closure of the secondary air control below the 45% open position and the primary air control fixed to prevent full closure to allow a bleed of air to enter the firebox at the base of the fuel bed	Wood logs ⁽¹⁾
Riva Studio 2 (8kW) freestanding wood stove manufactured by Stovax Limited, Falcon Road, Sowton Industrial Estate, Exeter, Devon, EX2 7LF	Instruction manual references PM452 Issue 1 dated June 2010 and smoke control kit instruction manual PM400 Issue 3 dated June 2010. A permanent stop must be positioned to prevent closure of the secondary air control below the 25% open position and the primary air control fixed to prevent full closure to allow a bleed of air to enter the firebox at the base of the fuel bed	Wood logs ⁽¹⁾
Riva Studio 1 Cassette (5 kW) Stove manufactured by Stovax Limited, Falcon Road, Sowton Industrial Estate, Exeter, Devon, EX2 7LF	Instruction manual references PM274 Issue 2 dated October 2009 and smoke control kit instruction manual PM400 Issue 1 dated November 2009. A permanent stop must be positioned to prevent closure of the secondary air control below the 45% open position and the primary air control fixed to prevent full closure to allow a bleed of air to enter the firebox at the base of the fuel bed	Wood logs ⁽¹⁾

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditi	ons
	The fireplace must be installed maintained and operated in accordance with the following specifications:	Permitted fuels (other than authorised fuels):
Riva Studio 2 Cassette (8 kW) Stove manufactured by Stovax Limited, Falcon Road, Sowton Industrial Estate, Exeter, Devon, EX2 7LF	Instruction manual references PM274 Issue 2 dated October 2009 and smoke control kit instruction manual PM400 Issue 1 dated November 2009. A permanent stop must be positioned to prevent closure of the secondary air control	Wood logs ⁽¹⁾
	below the 25% open position and the primary air control fixed to prevent full closure to allow a bleed of air to enter the firebox at the base of the fuel bed	
Riva Vision Medium (8 kW) Multifuel Stove manufactured by Stovax Limited, Falcon Road, Sowton Industrial Estate, Exeter, Devon, EX2 7LF	Instruction manual references PM278 Issue 2a dated October 2009 and smoke control kit instruction manual PM401 Issue 1 dated January 2010. A permanent stop must be positioned to prevent closure of the secondary air control below the 25% open position	Wood logs ⁽¹⁾
Riva Vision Small (5 kW) and Riva Vision Midi (6.5 kW) Multifuel Stoves manufactured by Stovax Limited, Falcon Road, Sowton Industrial Estate, Exeter, Devon, EX2 7LF	Instruction manual references PM278 Issue 2a dated October 2009 and smoke control kit instruction manual PM401 Issue 1 dated January 2010. A permanent stop must be positioned to prevent closure of the secondary air control below the 50% open position	Wood logs ⁽¹⁾
Rosedale SC Multifuel Stove manufactured by Town & Country Fires Limited, 1 Enterprise Way, Thornton Road Industrial Estate, Pickering, North Yorkshire, YO18 7NA	Rosedale Smoke Control Stove Installation and User Instructions "Issue 1" dated 1 st May 2010. The appliance must be fitted with a mechanical stop to prevent closure of the secondary air control beyond the 50% open position when sold into smoke control areas.	Wood logs with a maximum of 20% moisture ⁽¹⁾

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditi	ions
	The fireplace must be installed maintained and operated in accordance with the following specifications:	Permitted fuels (other than authorised fuels):
Saltfire Oslo-Eco manufactured by Saltfire Stoves Ltd, Units 1 and 2, The Omega Centre, Sandford Lane, Wareham BH20 4DY	Instruction manual references 'ECO7 operation-Revision 2A' dated 24 th January 2011	Wood logs ⁽¹⁾
Scan Andersen 4-5 manufactured by Krog Iversen & Co. A/S DK-5492 Vissenbjerg, Denmark	The manufacturer's Instruction manual dated 15 th November 2007 entitled "Scan Andersen 4-5", reference Edition 09/05-GB A permanent stop must be in place on the secondary air inlet to prevent closure beyond 20mm	Untreated dry wood ⁽¹⁾
Schmid UTSK 180, 240, 300, 360, 450, 550, 700, 900, 1200, 1600kw manufactured by Schmid AG Wood Firing Systems PO Box 42 CH-8380 Eschikon	"Instruction manual UTSK – ABC.22 – AME – S- PPU" Dated 25.09.2008 Where ABC is Model Number i.e. 180, 240, 300, 360, 450, 550, 700, 900, 1200, 1600	Wood Pellets or Wood Chips following CEN/TS 14961:2005 ⁽¹⁾
Schmid UTSL 30, 40, 50, 65, 80, 110, 150, kw Manufactured by Schmid AG Wood Firing Systems, PO Box 42, CH-8380 Eschikon	Instruction manual references "Operating Manual Wooden Chips and Pellets Plant. Lignumat UTSL" dated 23.12.2004	Wood Pellets or Wood Chips following CEN/TS 14961:2005 ⁽¹⁾
Schmid UTSP 180, 240, 300kw Manufactured by Schmid AG, Wood Firing Systems, PO Box 42, CH-8380 Eschikon	"Instruction manual UTSK – ABC.22 – AME – S- PPU" Dated 25.09.2008 Where ABC is Model Number i.e. 180, 240, 300.	Wood Pellets following CEN/ TS 14961:2005 ⁽¹⁾
Schmid UTSR, 150, 180, 240, 300, 360, 450, 550, 700, 900, kw Manufactured by Schmid AG, Wood Firing Systems, PO Box 42, CH-8380 Eschikon	"Instruction manual UTSR – ABC.22 – AME – S-PPV" Dated 25.09.2008 where ABC is Model Number i.e. 150, 180, 240, 300, 360, 450, 550, 700, 900	
Serrano 5 and Monterrey 6 Multi Fuel Stoves manufactured by Broseley fires Ltd, Knights Way, Battlefield Enterprise Park, Shrewsbury, Shropshire SY1 3AB	Instruction manual references 'TJ09C' dated 21st December 2009. The appliance must be fitted with a system that prevents the closure of the secondary air flaps to less than 8mm open position.	Wood logs ⁽¹⁾
Serrano 7 Multi Fuel Stove manufactured by Broseley fires	Instruction manual references 'TJ09C' dated 21st December	Wood logs ⁽¹⁾

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditi	ons
Ltd, Knights Way, Battlefield Enterprise Park, Shrewsbury, Shropshire SY1 3AB	The fireplace must be installed maintained and operated in accordance with the following specifications: 2009. The appliance must be fitted with a system that prevents the closure of the secondary air flaps to less than 10mm open position.	Permitted fuels (other than authorised fuels):
Sirius 450 – see Micromet MEG 4.5 and MEG 4.5 stove		
Sirius 750 – see Micromet MEG 7.5 and MEG 7.5 stove		
Stockton 3 Flat top (product code 7118), Stockton 4 Flat top (product code 7101 and 7102), Stockton 5 Flat top (product code 7127) Stockton 5 midline (product code 7130), Stockton 6 Flat top (product codes 7100 and 7162), Stockton 6 Highline (product code 7117) and Stockton 7 Flat top (product codes 7120 and 7163) manufactured by Stovax Limited, Falcon Road, Sowton Industrial Estate, Exeter, Devon, EX2 7LF	manual dated July 2008, reference PM227 ENG Issue 2, and instruction manual dated January 2009, reference PM271 Issue 2.	Untreated dry wood ⁽¹⁾
Stockton 5 Flat top (model number 7119), Stockton 5 Canopy (model number 7160) and Stockton 5 Midline (model number 7133) manufactured by Stovax Limited, Falcon Road, Sowton Industrial Estate, Exeter, Devon, EX2 7LF	manual reference PM 176 – Issue 4.	Untreated dry wood ⁽¹⁾
Stockton 7 Inset Convector (product codes 7125F and 7125C) manufactured by Stovax Limited, Falcon Road, Sowton Industrial Estate, Exeter, Devon, EX2 7LF	manual dated May 2008,	Untreated dry wood ⁽¹⁾

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditi	ions
	The fireplace must be installed maintained and operated in accordance with the following specifications:	Permitted fuels (other than authorised fuels):
Stockton Milner (4.6 kW) inset stove – smoke control version - manufactured by Stovax Limited, Falcon Road, Sowton Industrial Estate, Exeter, Devon, EX2 7LF	Instruction manual reference PM416 Issue 1 (June 2010) and smoke control kit instruction manual PM501 Issue 1 (June 2010).	Wood logs ⁽¹⁾
	A permanent stop must be positioned to prevent closure of the secondary air control below the 50% open position	
Strebel SRP TR 90, 90kW output pellet boiler manufactured by Strebel Ltd, 1f Albany Park, Camberley, Surrey GU16 7PB	The Strebel SRP TR 90 pellet boiler installation manual reference 'Installation and operation instructions for special pellet furnace' version 09:2010	6mm diameter wood pellets ⁽¹⁾
Stretton Insert Smoke Exempt Wood Fuel Stove (Stretton Stove SE) manufactured by Aga Station Road, Ketley Telford Shropshire. TF1 5AQ	Instruction manual references "N00530AXX REV:001" dated 12 th July 2011	Dry wood Logs ⁽¹⁾
Suprema, Mamy and Italy Hard Top manufactured by La Nordica Spa, Via Summano 104 M. Precalcino, 36030 Vicenza, Italy	Instruction manual references '7095701 Rev.09' dated 13 th December 2010	Wood logs ⁽¹⁾
Talbott 150-CMH 150kW output Biomass Air Heater manufactured by Talbott's Biomass Energy Systems Ltd, Tollgate Drive, Tollgate Industrial Estate, Stafford ST16 3HS	Talbott 150-CMH hand-fed Biomass Air Heater operating package reference 'OM-150-	
The Talbott's Automatic Biomass Air Heaters models T1.5/A, T3/A, T5/A and TM/A formerly manufactured by Talbott's Heating Ltd and now manufactured by Talbott's Biomass Energy Systems Ltd, Tollgate Drive, Tollgate Industrial Estate, Stafford ST16 3HS	Manufacturer's Instructions reference 'T/A JANUARY 1990'	Hardwood or softwood shavings or sawdust ⁽¹⁾

The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives
or coatings.

Fireplace	Conditi	ons
	The fireplace must be installed maintained and operated in accordance with the following specifications:	Permitted fuels (other than authorised fuels):
The Talbott's Biomass Energy Models C1, C2, C3 and C4 formerly manufactured by Talbott's Heating Ltd and now manufactured by Talbott's Biomass Energy Systems Ltd, Tollgate Drive, Tollgate Industrial Estate, Stafford ST16 3HS	Manufacturer's Instructions dated August 1995 reference 'Issue C1000/C/Range'	Chipboard, wood shavings or forestry chips ⁽¹⁾
The Talbott's model T75, T150, T300 Biomass Air Heaters formerly manufactured by Talbott's Heating Ltd and now manufactured by Talbott's Biomass Energy Systems Ltd, Tollgate Drive, Tollgate Industrial Estate, Stafford ST16 3HS	Manufacturer's Instructions dated 1 st January 1995 reference models T75, T150 and T300 'gen/sttech'	Wood offcuts, wood waste, pellets or chipboard ⁽¹⁾
The Talbott's T500 Biomass Air Heater (afterburn model) formerly manufactured by Talbott's Heating Ltd and now manufactured by Talbott's Biomass Energy Systems Ltd, Tollgate Drive, Tollgate Industrial Estate, Stafford ST16 3HS	Manufacturer's instructions dated 1 st January 1983 reference A10000. The afterburn cycle shall last not less than 25 minutes and must come into operation each time the loading door is opened.	Wood offcuts, wood waste, pellets or chipboard ⁽¹⁾
Termosuprema Compact DSA manufactured by La Nordica Spa, Via Summano 104 M. Precalcino, 36030, Vicenza, Italy	Instruction manual references '7095802 Rev. 06' dated 1st January 2011	
Therminator II 22 and Therminator II 30 Boiler manufactured by Solarfocus, Werkstrasse 1, 4451 St.Ulrich, Steyr, Austria	Installation Instructions 'Version 11/08/06' dated July 2006. Operating Manual 'V8.051' dated September 2009. Maintenance Instructions 'Ver 1st September 2006 dated 2006	Wood pellets ⁽¹⁾
Therminator II 27 and Therminator II 36 Boiler manufactured by Solarfocus,	Installation Instructions 'Version 11/08/06' dated July 2006. Operating Manual 'V8.051' dated September 2009. Maintenance	Wood logs ⁽¹⁾

The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives
or coatings.

Fireplace	Conditi	ons
	The fireplace must be installed maintained and operated in accordance with the following specifications:	Permitted fuels (other than authorised fuels):
Werkstrasse 1, 4451 St.Ulrich, Steyr, Austria	Instructions 'Ver 1 st September 2006 dated 2006	
Therminator II 40 Boiler manufactured by Solarfocus, Werkstrasse 1, 4451 St.Ulrich, Steyr, Austria	Installation Instructions 'Version 11/08/06' dated July 2006. Operating Manual 'V8.051' dated September 2009. Maintenance Instructions 'Ver 1st September 2006 dated 2006	Wood pellets or wood chips ⁽¹⁾
Therminator II 49 and Therminator II 60 Boiler manufactured by Solarfocus, Werkstrasse 1, 4451 St.Ulrich, Steyr, Austria	Installation Instructions 'Version 11/08/06' dated July 2006. Operating Manual 'V8.051' dated September 2009. Maintenance Instructions 'Ver 1st September 2006 dated 2006	Wood logs or wood pellets or wood chips ⁽¹⁾
Thornhill T3 small manufactured by Thornhill Eco Design Ltd 58/60 Winsheap, Canterbury, Kent CT1 3RS	Instruction manual references 'ED/11/05' dated January 2011. The appliance must be fitted with an air plate that prevents the teriary air controller from closing more than 17mm and opening more than 45mm	Wood logs ⁽¹⁾
Tiger SuperClean stove manufactured by Tiger stoves, Focus Arts & Crafts Co, Industrial Area Gao Zhuangzi Village, Xin Zhuang Town, Jin Nan District, Tianjin, P.R.China 300350	Instruction manual references "INSTALLATION AND OPERATING INSTRUCTIONS document v. 148" dated April 2010.	Wood logs ⁽¹⁾
Turbhogar Alfa 80T and 65T, Turbhogar Beta 80T, Turbhogar Delta 80T and 65T, Turbhogar Lamda 80T and 65T, Turbhogar Sigma 80T and 65T, Turbhogar Omega 80T and Turbhogar Tau 80T and 65T fireplace inserts manufactured by Rofer and Rodi UK Ltd, Unit 10, Millennium Road, Airedale Business Centre, Skipton, North Yorkshire BD23 2TZ	Manual of assembly and use referenced 'RR 100920' dated 20 th September 2010 and supplementary instruction manual 'UK 100920' of the same date. Appliances must be fitted with a system that prevents the full closure of the air control opening so that the air openings remain 3mm (30%) open at the minimum setting.	Wood logs ⁽¹⁾

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditi	ions
	The fireplace must be installed maintained and operated in accordance with the following specifications:	Permitted fuels (other than authorised fuels):
Twin Heat CS150i manufactured by TWIN HEAT A/S, Nørrevangen 7, DK-9631 Gedsted, Denmark	Operating instructions dated 17th December 2008, reference Version 6.0.03	Wood pellets of a maximum length of 30 mm and diameter of 6 mm and conforming to CEN/TS 14961:2005 ⁽¹⁾
The Type USP wood pellet-fired boilers, model numbers USP-10, 15, 20, 25 and 30, manufactured by KWB – Kraft und Wärme aus Biomasse Gesellschaft mit beschränkter Haftung (GmbH) of Industriestrasse 235, A-8321 St. Margarethen an der Raab, Austria	dated 28th July 2003, reference	Wood pellets ⁽¹⁾
The Type USV wood pellet- and wood chipfired boilers, model numbers USV-15, 25, 30, 40, 50, 60, 80 and 100, manufactured by KWB – Kraft und Wärme aus Biomasse Gesellschaft mit beschränkter Haftung (GmbH) of Industriestrasse 235, A-8321 St Margarethen an der Raab, Austria	dated August 2003, reference	Wood pellets or wood chips(1)
pellet boiler manufactured by Windhager Zentralheizung	January 2010 and operating instruction manual '092945/00'	Wood pellets ⁽¹⁾ , 6mm diameter, length 80% between 15-30mm and a density of at least 1.1kg.dm3
View 3 (3.8 kW) and View 5 (4.9kW) multifuel stoves manufactured by Stovax Limited, Falcon Road, Sowton Industrial Estate, Exeter, Devon, EX2 7LF	and smoke control kit instruction manual PM490 Issue 1 dated June 2010. A permanent stop must be positioned to prevent closure of	Wood logs ⁽¹⁾
	the secondary air control below the 50% open position	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditi	ions
	The fireplace must be installed maintained and operated in accordance with the following specifications:	Permitted fuels (other than authorised fuels):
View 5 (4.9kW) wood stove manufactured by Stovax Limited, Falcon Road, Sowton Industrial Estate, Exeter, Devon, EX2 7LF	Instruction manual references PM485 Issue 1 dated June 2010 and smoke control kit instruction manual PM490 Issue 1 dated June 2010.	Wood logs ⁽¹⁾
	A permanent stop must be positioned to prevent closure of the secondary air control below the 50% open position	
View 7 (7 kW) inset appliance Product code VW-7NMF manufactured by Stovax Limited, Falcon Road, Sowton Industrial Estate, Exeter, Devon, EX2 7LF	Instruction manual reference "PM552 - Issue 1" dated June 2011 and smoke control kit instruction manual reference "PM490 Issue 2" dated July 2011.	Wood logs ⁽¹⁾
	A permanent stop must be in place on the secondary air inlet to prevent closure beyond the 50% open position.	
The WTH 150 and WTH 200 boilers manufactured by Hargassner Gesellschaft mit beschränkter Haftung (GmbH), Gunderding 8, A-4952, Weng, Austria	The manufacturer's installation manual version 91 for Large Capacity Boiler WTH 150-200. Reference BA GK V90b 0309.	Wood chip or wood pellets ⁽¹⁾
Westcott 5SE manufactured by Dimplex, GDC Group Ltd, Millbrook House, Grange Drive, Hedge End, Southampton SO30 2DF	Instruction manual references 08/51351/0 – Issue 0 dated 7th September 2010	Wood logs ⁽¹⁾
Westfire Series One stove and Westfire Series Two stove manufactured by Westfire, Tømrervej 3, DK-6800 Varde, Denmark	Westfire WF One and Two series installation manual and operating instructions and supplementary Instruction manual reference "Westfire supplementary instructions June 2011/Version 1" dated 1 st June 2011. The appliance must be fitted with a permanent stop to prevent closure of the secondary air control less than 50% open	Wood logs ⁽¹⁾

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditi	ons
	The fireplace must be installed maintained and operated in accordance with the following specifications:	Permitted fuels (other than authorised fuels):
Westfire Uniq 15, 16 and 20 (also known as WF UNIQ 15, 16 and 20) manufactured by Westfire Tømrervej 3 DK-6800 Varde, Denmark	Installation and operating instructions dated 2007, reference WF15–WF16–WF20, together with supplementary instructions dated 2007, reference 01wfuk.2007.	Untreated dry wood ⁽¹⁾
	A permanent stop must be in place on the secondary air inlet to prevent closure beyond 50mm	
Westfire Uniq 18 Westfire Uniq 17	Instruction manual references "WESTFIRE SUPPLEMENTARY	Wood logs ⁽¹⁾
Westfire Uniq 19	INSTRUCTIONS JUNE 2010" All appliances will be fitted with	
Westfire Uniq 23	a mechanical stop to prevent closure of the secondary air slide beyond the 30mm open position	
Westfire Uniq 23 side Glass Westfire Uniq 23 Inset stoves manufactured by Westfire APS Tømrervej 3 DK-6800 Varde Denmark	when sold into smoke control areas.	
Westfire Uniq 21 stove, Westfire Uniq 21 pedestal stove and Westfire Uniq 21 wall hung stove manufactured by Westfire, Tømrervej 3, DK-6800 Varde, Denmark	Westfire WF21 installation manual and operating instructions and supplementary Instruction manual reference "Westfire supplementary instructions June 2011/Version 1" dated 1 st June 2011. The appliance must be fitted with a permanent stop to prevent closure of the secondary air control less than 60% open	Wood logs ⁽¹⁾
Westfire Uniq 26 stove, Westfire Uniq 27 stove and Westfire Uniq 28 stove manufactured by Westfire, Tømrervej 3, DK-6800 Varde, Denmark	Westfire WF26, WF27, WF28 installation manual and operating instructions and supplementary Instruction manual reference "Westfire supplementary instructions June 2011/Version 1" dated 1st June 2011. The appliance must be fitted with a permanent stop to the secondary air slider control to	Wood logs ⁽¹⁾

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditi	ons
	The fireplace must be installed maintained and operated in accordance with the following specifications:	Permitted fuels (other than authorised fuels):
	prevent closure more than 20mm from the fully closed position	
Westfire Uniq 32 Inset stove and Westfire Uniq 32 Freestanding stove manufactured by Westfire, Tømrervej 3, DK-6800 Varde, Denmark	Westfire WF23/Uniq23, WF32/ Uniq 32 inset stove installation manual and operating instructions and supplementary Instruction manual reference "Westfire supplementary instructions June 2011/Version 1" dated 1 st June 2011. The appliance must be fitted with a permanent stop to prevent closure of the secondary air control less than 50% open	Wood logs ⁽¹⁾
Windhager BioWin 100, 150, 210 and 260 manufactured by Windhager Zentralheizung GmbH, Anton-Windhager- Str. 20, A-5201 Seerkirchen bei Salzburg, Austria	The manufacturer's instruction manual dated May 2008, reference 0916197/00	Wood pellets ⁽¹⁾
Windhager FireWin 90 and 120 manufactured by Windhager Zentralheizung GmbH, Anton-Windhager- Str. 20, A-5201 Seerkirchen bei Salzburg, Austria	The manufacturer's instruction manual dated August 2008, reference 092125/00	Wood pellets ⁽¹⁾
Wood Fired Ovens by Jamie Oliver Ltd's GR Valoriani Ristorante 100 and OT Valoriani Ristorante 100 manufactured by Valoriani of Via Caselli alla Fornace 213, 50066 Reggello, Firenze, Italy	v2' dated January 2011	Untreated wood ⁽¹⁾ of less than 20% moisture
Wood Fired Ovens by Jamie Oliver Ltd's GR Valoriani Ristorante 120 and OT Valoriani Ristorante 120 manufactured by Valoriani of Via Caselli alla Fornace 213, 50066 Reggello, Firenze, Italy	Instruction manual reference 'OOLinst.9 GR 120 and OT 120 v2' dated January 2011	Untreated wood ⁽¹⁾ of less than 20% moisture
Wood Fired Ovens by Jamie Oliver Ltd's GR Valoriani Ristorante 120x160 and OT	Instruction manual reference 'OOLinst.11 GR 120x160 and	Untreated wood ⁽¹⁾ of less than 20% moisture

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed maintained and operated in accordance with the following specifications:	Permitted fuels (other than authorised fuels):
Valoriani Ristorante 120x160 manufactured by Valoriani of Via Caselli alla Fornace 213, 50066 Reggello, Firenze, Italy	OT 120x160 v2' dated January 2011	
Wood Fired Ovens by Jamie Oliver Ltd's GR Valoriani Ristorante 140 and OT Valoriani Ristorante 140 manufactured by Valoriani of Via Caselli alla Fornace 213, 50066 Reggello, Firenze, Italy	Instruction manual reference 'OOLinst.10 GR 140 and OT 140 v2' dated January 2011	Untreated wood ⁽¹⁾ of less than 20% moisture
Wood Fired Ovens by Jamie Oliver Ltd's GR Valoriani Ristorante 140x180 and OT Valoriani Ristorante 140x180 manufactured by Valoriani of Via Caselli alla Fornace 213, 50066 Reggello, Firenze, Italy	Instruction manual reference 'OOLinst.13 GR 140x180 and OT 140x180 v2' dated January 2011	Untreated wood ⁽¹⁾ of less than 20% moisture
Wood Fired Ovens by Jamie Oliver Ltd's GR Valoriani Ristorante 180 and OT Valoriani Ristorante 180 manufactured by Valoriani of Via Caselli alla Fornace 213, 50066 Reggello, Firenze, Italy	Instruction manual reference 'OOLinst.14 GR 180 and OT 180 v2' dated January 2011	Untreated wood ⁽¹⁾ of less than 20% moisture
Wood Fired Ovens by Jamie Oliver Ltd's GR Valoriani Ristorante 140x160 and OT Valoriani Ristorante 140x160 manufactured by Valoriani of Via Caselli alla Fornace 213, 50066 Reggello, Firenze, Italy	Instruction manual reference 'OOLinst.12 GR 140x160 and OT 140x160 v2' dated January 2011	Untreated wood ⁽¹⁾ of less than 20% moisture
Wood Fired Ovens by Jamie Oliver Ltd's Valoriani Casa 100 manufactured by Valoriani of Via Caselli alla Fornace 213, 50066 Reggello, Firenze, Italy	Instruction manual reference 'OOLinst.2 FVR 100 v2' dated January 2011	Untreated wood ⁽¹⁾ of less than 20% moisture
Wood Fired Ovens by Jamie Oliver Ltd's Valoriani Casa 110 manufactured by Valoriani of Via Caselli alla Fornace 213, 50066 Reggello, Firenze, Italy	Instruction manual reference 'OOLinst.3 FVR 110 v2' dated January 2011	Untreated wood ⁽¹⁾ of less than 20% moisture

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed maintained and operated in accordance with the following specifications:	Permitted fuels (other than authorised fuels):
Wood Fired Ovens by Jamie Oliver Ltd's Valoriani Casa 110x160 manufactured by Valoriani of Via Caselli alla Fornace 213, 50066 Reggello, Firenze, Italy	Instruction manual reference 'OOLinst.5 FVR 110x160 v2' dated January 2011	Untreated wood ⁽¹⁾ of less than 20% moisture
Wood Fired Ovens by Jamie Oliver Ltd's Valoriani Casa 120 manufactured by Valoriani of Via Caselli alla Fornace 213, 50066 Reggello, Firenze, Italy	Instruction manual reference 'OOLinst.4 FVR 120 v2' dated January 2011	Untreated wood ⁽¹⁾ of less than 20% moisture
Wood Fired Ovens by Jamie Oliver Ltd's Valoriani Casa 80 manufactured by Valoriani of Via Caselli alla Fornace 213, 50066 Reggello, Firenze, Italy	Instruction manual reference 'OOLinst.1 FVR 80 v2' dated January 2011	Untreated wood ⁽¹⁾ of less than 20% moisture
Wood Fired Ovens by Jamie Oliver Ltd's Valoriani Piccolo manufactured by Valoriani of Via Caselli alla Fornace 213, 50066 Reggello, Firenze, Italy	Instruction manual reference 'OOLinst.15 Valoriani Piccolo v2' dated January 2011	Untreated wood ⁽¹⁾ of less than 20% moisture
Wood Fired Ovens by Jamie Oliver Ltd's Valoriani Villa 100 manufactured by Valoriani of Via Caselli alla Fornace 213, 50066 Reggello, Firenze, Italy	Instruction manual reference 'OOLinst.6 TOP 100 v2' dated January 2011	Untreated wood ⁽¹⁾ of less than 20% moisture
Wood Fired Ovens by Jamie Oliver Ltd's Valoriani Villa 120 manufactured by Valoriani of Via Caselli alla Fornace 213, 50066 Reggello, Firenze, Italy	'OOLinst.7 TOP 120 v2' dated	Untreated wood ⁽¹⁾ of less than 20% moisture
Woodpecker 15, 25 and 45 wood pellet boilers manufactured by Woodpecker Energy UK, Abbey Manor Business Centre Preston Road. Yeovil. BA20 2FJ. Previously manufactured by Garranlea Renewables Ltd of Barnard, Garranlea, New Inn, Cashel, Co. Tipperary, Ireland	Instruction manual references " Europe Issue 4" dated July 2010	Wood pellets conforming to CEN TS 14961 ⁽¹⁾

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings

Fireplace	Conditions	
	The fireplace must be installed maintained and operated in accordance with the following specifications:	Permitted fuels (other than authorised fuels):
Woodpecker Thermon 150 boiler manufactured by Woodpecker Energy UK, Abbey Manor Business Centre Preston Road. Yeovil. BA20 2FJ	Instruction manual references "Thermon Europe Issue 1" dated January 2011	6mm Wood Pellets ⁽¹⁾
Woodpecker Thermon 200 boiler manufactured by Woodpecker Energy UK, Abbey Manor Business Centre Preston Road. Yeovil. BA20 2FJ	Instruction manual references "Thermon Europe Issue 1" dated January 2011	6mm Wood Pellets ⁽¹⁾
Woodpecker Thermon 250 boiler manufactured by Woodpecker Energy UK, Abbey Manor Business Centre, Preston Road. Yeovil. BA20 2FJ	Instruction manual references "Thermon Europe Issue 1" dated January 2011	6mm Wood Pellets ⁽¹⁾
Woodpecker Thermon 300 boiler manufactured by Woodpecker Energy UK, Abbey Manor Business Centre, Preston Road. Yeovil. BA20 2FJ	Instruction manual references "Thermon Europe Issue 1" dated January 2011	6mm Wood Pellets ⁽¹⁾
The Wood Waste Technology Ltd WT5 manufactured by Wood Waste Technology Limited, Units 1 & 2, Drummond Road, Astonfields Industrial Estate, Stafford, Staffordshire ST16 3HJ	The manufacturer's instructions dated 16th February 2009, reference WT5_v2	Medium density fibreboard, chipboard and hard and softwood offcuts ⁽¹⁾
The Wood Waste Technology Heater, models WT10 and WT15, manufactured by Wood Waste Technology Limited, Units 1 & 2, Drummond Road, Astonfields Industrial Estate, Stafford, Staffordshire ST16 3HJ	The manufacturer's instructions dated 19th January 2005, reference WT10 and WT15	Medium density fibreboard, chipboard and hard and softwood offcuts ⁽¹⁾
WTA WT Auto 200 kW Airheater manufactured by Wood Waste Technology	Instruction manual references "WTA Installation Operation &	Chipboard, Medium Density Fibreboard, Softwood, Hardwood. All fuels to be

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed maintained and operated in accordance with the following specifications:	Permitted fuels (other than authorised fuels):
Limited, Units 1, 2 & 3 Drummond Road, Astonfields Industrial Estate, Stafford. ST16 3HJ	Maintenance Instructions" WTA v1 Issue A dated April 2011.	chipped to a maximum size of 25mm and a maximum moisture content of 20%. Maximum fines (sawdust) content 5% ⁽¹⁾
Xeoos 5 kW stove Versions - Natur, Style, Harmony, Pur, Classic, Elegance and Stone Xeoos 8kW stove Versions - Basic, Pur, Classic, Elegance Stone and Air Instruction manual references Manufactured by Specht Modulare Ofensysteme GmbH & Co, KG i.V. DiplIng. Frank Werner Projektmanagement Bahnhofstr. 2 D 35116 Hatzfeld	Instructions Xeoos 5kW/	Wood logs ⁽¹⁾ Conforming to DIN 51731
Yeoman CL3 (3.8 kW) and CL5 (4.9 kW) multifuel stoves manufactured by Stovax Limited, Falcon Road, Sowton Industrial Estate, Exeter, Devon, EX2 7LF	PM489 Issue 1 dated June 2010 and smoke control kit instruction	Wood logs ⁽¹⁾
	Instruction manual references PM489 Issue 1 dated June 2010 and smoke control kit instruction manual PM491 Issue 1 dated 5 April 2010. A permanent stop must be positioned to prevent closure of the secondary air control below the 50% open position	Wood logs ⁽¹⁾
Yeoman CL 7 (7 kW) inset appliance Product code YM-CL7NMF manufactured by Stovax Limited, Falcon Road, Sowton Industrial Estate, Exeter, Devon, EX2 7LF	Instruction manual reference "PM553 - Issue 1" dated June 2011 and smoke control kit instruction manual reference "PM491 Issue 2" dated June 2011.	Wood logs ⁽¹⁾

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed maintained and operated in accordance with the following specifications:	Permitted fuels (other than authorised fuels):
	A permanent stop must be in place on the secondary air inlet to prevent closure beyond the 50% open position.	
Yeoman CL Milner Stove Product code YM-CLMB manufactured by Stovax Limited, Falcon Road, Sowton Industrial Estate, Exeter, Devon, EX2 7LF	Instruction manual reference "PM559 - Issue 1" dated June 2011 and smoke control kit instruction manual reference "PM491 Issue 2" dated June 2011.	Wood logs ⁽¹⁾
	A permanent stop must be positioned to prevent closure of the secondary air control below the 50% open position.	
Yeoman Devon Multifuel Flat Top 1 Door, Flat Top 2 Door, Low Canopy 1 Door, Low Canopy 2 Door, High Canopy 1 Door and High Canopy 2 Door (9kW) Stoves manufactured by Stovax Limited, Falcon Road, Sowton Industrial Estate, Exeter, Devon, EX2 7LF	Instruction manual references PM184 Issue 3 dated February 2008 and smoke control kit instruction manual PM403 Issue 1 dated January 2010. A permanent stop must be positioned to prevent closure of the secondary air control below the 50% open position and a system that ensures a gap of 1mm for bleed of primary air when the spin wheels are rotated to their fully closed positions	Wood logs ⁽¹⁾
Yeoman Exe Multifuel Flat Top 1 Door, Flat Top 2 Door, Low Canopy 1 Door and Low Canopy 2 Door (4.9kW) Stoves manufactured by Stovax Limited, Falcon Road, Sowton Industrial Estate, Exeter, Devon, EX2 7LF	Instruction manual references PM184 Issue 3 dated February 2008 and smoke control kit instruction manual PM403 Issue 1 dated January 2010. A permanent stop must be positioned to prevent closure of the secondary air control below the 60% open position and a system that prevents full closure of the primary air controls	Wood logs ⁽¹⁾
Yeoman Exmoor Multifuel Flat Top and Multifuel		Wood logs ⁽¹⁾

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Changes to legislation: There are outstanding changes not yet made by the legislation.gov.uk editorial team to The Smoke Control Areas (Exempted Fireplaces) (England) (No. 2) Order 2011. Any changes that have already been made by the team appear in the content and are referenced with annotations. (See end of Document for details)

Fireplace	Conditions	
	The fireplace must be installed	Permitted fuels (other than
	maintained and operated in	authorised fuels):
	accordance with the following	
	specifications:	
Low Canopy(4.9 kW) Stoves	2008 and smoke control kit	
manufactured by Stovax	instruction manual PM403 Issue	
Limited, Falcon Road, Sowton	1 dated January 2010	
Industrial Estate, Exeter,		
Devon, EX2 7LF	A permanent stop must be	
	positioned to prevent closure of	
	the secondary air control below	
	the 60% open position and a	
	system that prevents full closure	
	of the primary air controls	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

EXPLANATORY NOTE

(This note is not part of the Order)

This Order revokes and replaces with amendments the Smoke Control Areas (Exempted Fireplaces) (England) Order 2011 (S.I. 2011/714).

It exempts the fireplaces listed in the Schedule from the provisions of section 20 of the Clean Air Act 1993 (prohibition of smoke emissions in smoke control areas), subject to the conditions set out in the Schedule. Several additional fireplaces have been exempted.

No impact assessment has been produced for this instrument as no impact on business, the private or voluntary sectors is foreseen.

Status:

Point in time view as at 01/10/2011.

Changes to legislation: