## **SCHEDULE 2**

Signs that warn of hazards and signs for bridges and other structures

## PART 5

## Associated plates and structure warning markings for signs in Part 4

- 1.—(1) A warning or information of a description specified in column 2 of an item in the sign table in this Part must be conveyed by a plate or structure warning marking which is of the size, colour and type provided for—
  - (a) in the diagram in column 3 of the item; or
  - (b) in that diagram varied in accordance with column 4.
- **2.** A provision of Part 7 mentioned (by reference to paragraph number) in column 5 of the sign table applies to the structure warning marking provided for at the item number in question.

Sign table — Schedule 2, Part 5

(1)	(2)	(3)	(4)	(5)
Ite	mDescription	Diagram	Variants	Applicable provisions in Part 7
1	Diagram 530.1 Reduced headroom over part of road due to overhanging building or structure	Overhanging building	150he legend may include— 75 (a) a distance, with or without an arrow pointing to the left or to the right; (b) an arrow pointing to the left or to the right 2. "building" may be varied to "buildings" or "structure"	
2	Diagram 531.2 High vehicles to use middle of road at	ARCH BRIDGE High vehicles use middle of road	The legend may include an arrow pointing to the left or to the right	

(1)	(2)	(3)	(4)	(5)
Ite	mDescription	Diagram	Variants	Applicable provisions in Part 7
	arch bridge ahead,			
3	Diagram 532.4 Upper: Extent of headroom available at the side of and in the centre of a road at an arch bridge. Lower:	\$300 min  \$\frac{1}{3000}\$ min  \$\frac{1}{3000}\$ min  \$\frac{1}{300}\$ mi	1. The position and number of chord markings in the upper part of the diagram may be varied as appropriate  2. The black and yellow marking may be omitted	7, 9
	Marking highlighting reduced headroom at an arch bridge.			
4	Diagram 530.2 Reduced headroom at a hazard (Alternative types)	300 min 300 min 1560 max	equal equal	7, 9

**Status:** This is the original version (as it was originally made). This item of legislation is currently only available in its original format.

(1)	(2)	(3)	(4)	(5)
Ite	mDescription	Diagram	Variants	Applicable provisions in Part 7
5	Diagram 572 Distance ahead to hazard	<sup>50</sup> 62.5 75 100 125 150	<ol> <li>The distance may be varied to another distance</li> <li>The legend may include an arrow pointing to the left or to the right</li> </ol>	