
WELSH STATUTORY INSTRUMENTS

2009 No. 3225

**The Smoke Control Areas (Authorised Fuels)
(Wales) (Amendment) Regulations 2009**

Amendments

2.—(1) In the Schedule (Authorised Fuels) to the Smoke Control Areas (Authorised Fuels) (Wales) Regulations 2008 (1), after paragraph 8, insert—

“**8A.** Briteheat briquettes, manufactured by Coal Products Limited at Immingham Briquetting Works, North East Lincolnshire, which—

- (a) comprise anthracite (as to approximately 60 to 85% of the total weight), petroleum coke (up to approximately 30% of the total weight), bituminous coal (up to approximately 15% of the total weight), and a molasses and phosphoric acid binder (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving roll-pressing and heat treatment at about 300°C;
- (c) are cushion-shaped briquettes with an indented line running longitudinally around the briquette and have an average weight of 30 grams per briquette; and
- (d) have a sulphur content not exceeding 2% of the total weight.”

(2) After paragraph 41 of the Schedule, insert—

“**41A.** Therma Briquettes, manufactured by Maxibrite Limited at Llantrisant, Rhondda Cynon Taff, which—

- (a) comprise anthracite fines (as to approximately 84% of the total weight) petroleum coke (as to approximately 12% of the total weight) and starch binder (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving roll-pressing and heat treatment at 250°C;
- (c) are oval/tear shaped briquettes with a line through the centre and have an average weight of 26 grams per briquette; and
- (d) have a sulphur content not exceeding 2% of the total weight.”

(3) After paragraph 42 of the Schedule, insert—

“**42A.** Tiger Tim Firelogs, manufactured by De Lange B V., Rustenburgerweg 3, 1646 WJ Ursem, the Netherlands, which—

- (a) comprise slackwax (as to approximately 50% of the total weight) and sawdust (as to approximately 50% of the total weight);
- (b) were manufactured from those constituents by a process of heat treatment and extrusion;

Status: This is the original version (as it was originally made). This item of legislation is currently only available in its original format.

- (c) are firelogs approximately 280 millimetres in length and 75 millimetres x 75 millimetres x 75 millimetres with a single groove running along each of the four 280 millimetre length faces and have an average weight of 1.1 kilograms per firelog; and
- (d) have a sulphur content not exceeding 0.2% of the total weight.”.