
STATUTORY RULES OF NORTHERN IRELAND

2010 No. 419

ROAD AND RAILWAY TRANSPORT

Level Crossing (Lissue) Order (Northern Ireland) 2010

Made - - - - 13th December 2010

Coming into operation 28th January 2011

LEVEL CROSSING (LISSUE) ORDER (NORTHERN IRELAND) 2010

1. Citation, commencement and interpretation
 2. Suspension of statutory provisions
 3. Provision of automatic equipment
 4. Revocation
- Signature

SCHEDULE PARTICULARS OF THE BARRIERS, LIGHTS, TRAFFIC SIGNS
AND OTHER DEVICES

1. Cattle-cum-trespass guards of standard railway design shall be provided adjacent...
2. A barrier shall be pivoted as close to the railway...
3. It shall be possible to raise and lower the barriers...
4. When barriers are fully lowered their uppermost surfaces shall be...
5. When in the fully raised position the barriers shall be...
6. The barriers shall be as light as possible but shall...
7. Two electric lamps, or equivalent (light emitting diodes) each of...
8. The barriers shall display on both front and rear faces...
9. Suitable screening shall be provided for each barrier machine to...
10. A traffic light signal of the size, colour and type...
11. An audible warning device shall be provided on or adjacent...
12. A reflectorised stop line of the size and type shown...
13. A reflectorised pedestrian stop line of the size and type...
14. Where the road passes over the crossing, reflectorised edge of...
15. The centre line of the carriageway shall be marked on...
16. A traffic sign of the size, colour and type shown...
17. A traffic sign of the size, colour and type shown...
18. A traffic sign of the size, colour and type shown...
19. A traffic sign of the size, colour and type shown...

Status: This is the original version (as it was originally made). This item of legislation is currently only available in its original format.

20. A traffic sign of the size, colour and type shown...
21. A telephone mounted in a weather-proof box connected to the...
22. Two independent power supplies shall be provided at the crossing,...
23. In this Schedule “the Regulations” means the Traffic Signs Regulations...

SCHEDULE CONDITIONS AND REQUIREMENTS TO BE COMPLIED WITH BY THE RAILWAY UNDERTAKING

1. The carriageway shall be approximately 6.7 metres wide at the...
 2. The ground shall be made-up to the level of the...
 3. The surface of the carriageway over the crossing shall be...
 4. The barriers shall be kept in the fully raised position...
 5. The electric lamps or equivalent (light emitting diodes) on each...
 6. If the road approaches to the crossing are lit the...
 7. Visual indicators and an audible alarm shall be provided in...
 8. The barriers, the audible warning devices and the traffic light...
 9. When the train either occupies a track circuit or operates...
 10. Should the barriers and other protective equipment at the crossing...
 11. In the event of the failure of both intermittent red...
 12. Should a total power failure occur both barriers shall descend...
 13. If either barrier fails to rise from the lowered position...
- Explanatory Note