#### STATUTORY INSTRUMENTS

#### 1989 No. 1796

### The Road Vehicles Lighting Regulations 1989

#### **PART II**

## REGULATIONS GOVERNING THE FITTING OF LAMPS, REFLECTORS, REAR MARKINGS AND DEVICES

#### Colour of light shown by lamps and reflectors

- 11.—(1) No vehicle shall be fitted with a lamp [F1 or retro reflective material] which is capable of showing a red light to the front, except—
  - (a) a red and white chequered domed lamp, or a red and white segmented mast-mounted warning beacon, fitted to a fire service control vehicle and intended for use at the scene of an emergency;
  - (b) a side marker lamp or a side retro reflector;
  - (c) retro reflective material or a retro reflector designed primarily to reflect light to one or both sides of the vehicle and attached to or incorporated in any wheel or tyre of—
    - [F2(i) a pedal cycle;
      - (ii) a trailer drawn by, or a sidecar attached to, a pedal cycle;
    - (iii) a solo motor bicycle or motor bicycle combination; or
    - (iv) an invalid carriage; or
  - (d) a traffic sign.
- (2) No vehicle shall be fitted with a lamp [F3 or retro reflective material] which is capable of showing any light to the rear, other than a red light, except—
  - (a) amber light from a direction indicator or side marker lamp;
  - (b) white light from a reversing lamp;
  - (c) white light from a work lamp;
  - (d) light to illuminate the interior of a vehicle;
  - (e) light from an illuminated rear registration plate;
  - (f) light for the purposes of illuminating a taxi meter;
  - (g) in the case of a bus, light for the purposes of illuminating a route indicator;
  - (h) blue light and white light from a chequered domed lamp fitted to a police control vehicle and intended for use at the scene of an emergency;
  - (i) white light from a red and white chequered domed lamp, or a red and white segmented mast-mounted warning beacon, fitted to a fire service control vehicle and intended for use at the scene of an emergency;
  - (j) green light and white light from a chequered domed lamp fitted to an ambulance control vehicle and intended for use at the scene of an emergency;

- (k) blue light from a warning beacon or rear special warning lamp fitted to an emergency vehicle [F4 or to a vehicle used for special forces purposes], or from any device fitted to a vehicle used for police purposes;
- (1) amber light from a warning beacon fitted to-
  - (i) a road clearance vehicle;
  - (ii) a vehicle constructed or adapted for the purpose of collecting refuse;
  - (iii) a breakdown vehicle;
  - (iv) a vehicle having a maximum speed not exceeding 25 mph or any trailer drawn by such a vehicle;
  - (v) a vehicle having an overall width (including any load) exceeding 2.9 m;
  - (vi) a vehicle used for the purposes of testing, maintaining, improving, cleansing or watering roads or for any purpose incidental to any such use;
  - (vii) a vehicle used for the purpose of inspecting, cleansing, maintaining, adjusting, renewing or installing any apparatus which is in, on, under or over a road, or for any purpose incidental to any such use;
  - (viii) a vehicle used for or in connection with any purpose for which it is authorised to be used on roads by an order under section 44 of the Act;
  - [F5(ix) a vehicle used for escort purposes;]
    - (x) a vehicle used by the Commissioners of Customs and Excise for the purpose of testing fuels;
    - (xi) a vehicle used for the purpose of surveying;
    - (xii) a vehicle used for the removal or immobilisation of vehicles in exercise of a statutory power or duty;
- (m) green light from a warning beacon fitted to a vehicle used by a medical practitioner registered by the General Medical Council (whether with [F6full or provisional] registration);
- (n) yellow light from a warning beacon fitted to a vehicle for use at airports;
- (o) light of any colour from a traffic sign which is attached to a vehicle;
- [F7(0a) amber light from a lamp attached to or incorporated in a pedal of a pedal cycle;
  - (ob) white light or amber light from a lamp which is designed to emit light primarily to one or both sides of the vehicle, and is attached to or incorporated in any wheel or tyre of—
    - (i) a pedal cycle or;
    - (ii) a trailer drawn by, or a sidecar attached to, a pedal cycle;
    - (p) reflected light from amber pedal retro reflectors;
    - (q) reflected light of any colour from retro reflective material or a retro reflector designed primarily to reflect light to one or both sides of the vehicle and attached to or incorporated in any wheel or tyre of—
      - [F8(i) a pedal cycle;
        - (ii) a trailer drawn by, or a sidecar attached to, a pedal cycle;
      - (iii) a solo motor bicycle or motor bicycle combination; or
      - (iv) an invalid carriage;]
    - (r) reflected light from amber retro reflective material on a road clearance vehicle;
    - (s) reflected light from yellow retro reflective registration plates;

- [F9(sa) reflected blue, yellow and white light from a retro reflective plate displaying a distinguishing sign in accordance with Council Regulation (EC) No. 2411/98;]
- [F10(sb)] reflected light from a registration plate fixed to the rear of a trailer displaying a registration mark assigned to that trailer in accordance with regulations made under section 15 of the Haulage Permits and Trailer Registration Act 2018 (c. 19);]
  - (t) reflected light from yellow retro reflective material incorporated in a [FII] prescribed rear marking fitted in the appropriate manner to]—
    - (i) a motor vehicle having a maximum gross weight exceeding 7500 kg;
    - (ii) a motor vehicle first used before 1st August 1982 having an unladen weight exceeding 3000 kg;
    - (iii) a trailer having a maximum gross weight exceeding 3500 kg;
    - (iv) a trailer manufactured before 1st August 1982 having an unladen weight exceeding 1000 kg;
    - (v) a trailer which forms part of a combination of vehicles one of which is of a type mentioned in a previous item of this sub-paragraph;
    - (vi) a load carried by any vehicle; F12...
  - (u) reflected light from orange retro reflective material incorporated in a sign fitted to the rear of a vehicle carrying a dangerous substance within the meaning of the Dangerous Substances (Conveyance by Road in Road Tankers and Tank Containers) Regulations 1981(1) or the Road Traffic (Carriage of Dangerous Substances in Packages etc) Regulations 1986(2)
- $[^{F13}(v)]$  reflected light from yellow retro reflective material incorporated in a prescribed sign and fitted to the rear of a bus;  $^{F14}$ ...
  - (w) reflected light from yellow retro reflective material incorporated in a sign fitted to the rear of a bus in accordance with paragraph (4)|<sup>F15</sup>;
  - (x) reflected light from a yellow conspicuity marking where the fitting of that marking complies with the mandatory or optional ECE conspicuity requirements; or
  - (y) reflected light from yellow or orange retro reflective material fitted to the rear of a vehicle used for—
    - (i) police,
    - (ii) [F16Scottish Fire and Rescue Service] or, in England and Wales, fire and rescue authority,
    - - (iv) [F18Driver and Vehicle Standards Agency], or
      - (v) traffic officer,

purposes

- [ reflected light from yellow or orange retro reflective material fitted to the rear of a  $^{\text{F19}}(z)$  vehicle—
  - (i) used for ambulance purposes, or
  - (ii) used for the purpose of providing a response to an emergency at the request of an NHS ambulance service.]

<sup>(1)</sup> S.I.1981/1059, to which there is no relevant amendment.

<sup>(2)</sup> S.I. 1986/1951.

- (3) For the purposes of paragraph (2)(t), a rear marking fitted to a vehicle is a prescribed rear marking fitted in the appropriate manner if the rear marking—
  - (a) is a rear marking of a description specified in the entry applicable to that vehicle in the right hand column of paragraph 1 of Part I of Schedule 19, and
  - (b) complies with paragraphs 2 to 7 of that Part of that Schedule.
- (4) For the purposes of paragraph (2)(w), a sign ("the secondary sign") is fitted to the rear of a bus in accordance with this paragraph if—
  - (a) a prescribed sign is also fitted to the rear of a bus;
  - (b) the total area of the retro reflective material incorporated in the secondary sign is no greater than the area of the prescribed sign; and
  - (c) the secondary sign satisfies the requirements specified—
    - (i) in the case of a bus which is owned or hired by a [F20] local authority (within the meaning of the Education Act 1996) in connection with the exercise of its functions relating to education] or any person managing an education establishment attended by children under the age of 16 years, in paragraph (5) or (6); or
    - (ii) in any other case, in paragraph (6).
- (5) The requirements referred to in paragraph (4)(c)(i) are that the secondary sign contains no words or other markings apart from words or markings identifying the [F21]local authority] or the educational establishment (as the case may be).
- (6) The requirements referred to in paragraph (4)(c)(ii) are that the secondary sign contains no words or other markings apart from words or other markings which—
  - (a) indicate that children are on board the bus when it is in motion or likely to be on board the bus or in its vicinity when it is stationary, and
  - (b) are calculated to reduce the risk of road accidents involving such children.]

- F1 Words in reg. 11(1) added (1.10.1994) by The Road Vehicles Lighting (Amendment) Regulations 1994 (S.I. 1994/2280), regs. 1(2), 5(2)
- F2 Reg. 11(1)(c)(i)-(iv) substituted for reg. 11(1)(c)(i)-(iii) (21.10.2005) by The Road Vehicles Lighting (Amendment) Regulations 2005 (S.I. 2005/2559), regs. 1, 4(2)
- **F3** Words in reg. 11(2) added (1.10.1994) by The Road Vehicles Lighting (Amendment) Regulations 1994 (S.I. 1994/2280), regs. 1(2), **5(2)**
- **F4** Words in reg. 11(2)(k) inserted (15.4.2011) by The Road Traffic Exemptions (Special Forces) (Variation and Amendment) Regulations 2011 (S.I. 2011/935), regs. 1(1), **4(b)**
- F5 Reg. 11(2)(l)(ix) substituted (21.10.2005) by The Road Vehicles Lighting (Amendment) Regulations 2005 (S.I. 2005/2559), regs. 1, 4(3)
- F6 Words in reg. 11(2)(m) substituted (19.7.2006 for specified purposes in accordance with art. 1(2)(b) of the amending S.I. as notified in the London Gazette dated 20.7.2007) by The Medical Act 1983 (Amendment) and Miscellaneous Amendments Order 2006 (S.I. 2006/1914), arts. 1(2)(b)(c)(3), 76(a)
- F7 Reg. 11(2)(oa)(ob) inserted (21.10.2005) by The Road Vehicles Lighting (Amendment) Regulations 2005 (S.I. 2005/2559), regs. 1, 4(4)
- F8 Reg. 11(2)(q)(i)-(iv) substituted for reg. 11(2)(q)(i)-(iii) (21.10.2005) by The Road Vehicles Lighting (Amendment) Regulations 2005 (S.I. 2005/2559), regs. 1, 4(5)
- F9 Reg. 11(2)(sa) inserted (21.3.2001) by The Road Vehicles Lighting (Amendment) Regulations 2001 (S.I. 2001/560), regs. 1, 2
- **F10** Reg. 11(2)(sb) inserted (21.11.2018) by The Trailer Registration Regulations 2018 (S.I. 2018/1203), reg. 1(2), **Sch. 3 para. 1(2)**

- **F11** Words in reg. 11(2)(t) substituted (1.10.1994) by The Road Vehicles Lighting (Amendment) Regulations 1994 (S.I. 1994/2280), regs. 1(2), **5(3)**
- F12 Word in reg. 11(2) omitted (1.10.1994) by virtue of The Road Vehicles Lighting (Amendment) Regulations 1994 (S.I. 1994/2280), regs. 1(2), 5(4)
- F13 Reg. 11(2)(v)(w), (3)-(6) added (1.10.1994) by The Road Vehicles Lighting (Amendment) Regulations 1994 (S.I. 1994/2280), regs. 1(2), 5(4)
- F14 Word in reg. 11(2)(v) omitted (4.1.2010) by virtue of The Road Vehicles Lighting and Goods Vehicles (Plating and Testing) (Amendment) Regulations 2009 (S.I. 2009/3220), regs. 1, 5(2)(a)
- F15 Reg. 11(2)(x)(y) and semicolon added (4.1.2010) by The Road Vehicles Lighting and Goods Vehicles (Plating and Testing) (Amendment) Regulations 2009 (S.I. 2009/3220), regs. 1, 5(2)(b)
- F16 Words in reg. 11(2)(y)(ii) substituted (S.) (1.4.2013) by The Police and Fire Reform (Scotland) Act 2012 (Consequential Modifications and Savings) Order 2013 (S.S.I. 2013/119), art. 1, sch. 2 para. 7(3)
- F17 Reg. 11(2)(y)(iii) omitted (26.5.2015) by virtue of Deregulation Act 2015 (c. 20), s. 115(3)(d), Sch. 9 para. 12(2)
- **F18** Words in reg. 11(2)(y)(iv) substituted (1.4.2014) by The Driving Standards Agency and the Vehicle and Operator Services Agency (Merger) (Consequential Amendments) Regulations 2014 (S.I. 2014/480), regs. 1, **5(2)**
- F19 Reg. 11(2)(z) inserted (26.5.2015) by Deregulation Act 2015 (c. 20), s. 115(3)(d), Sch. 9 para. 12(3)
- **F20** Words in reg. 11(4)(c)(i) substituted (5.5.2010) by The Local Education Authorities and Children's Services Authorities (Integration of Functions) (Local and Subordinate Legislation) Order 2010 (S.I. 2010/1172), art. 1(1), **Sch. 3 para. 16(2)**
- **F21** Words in reg. 11(5) substituted (5.5.2010) by The Local Education Authorities and Children's Services Authorities (Integration of Functions) (Local and Subordinate Legislation) Order 2010 (S.I. 2010/1172), art. 1(1), **Sch. 3 para. 16(3)**

#### **Commencement Information**

II Reg. 11 in force at 1.11.1989, see reg. 1(1)

#### Movement of lamps and reflectors

- 12.—(1) Save as provided in paragraph (2), no person shall use, or cause or permit to be used, on a road any vehicle to which, or to any load or equipment of which, there is fitted a lamp, reflector or marking which is capable of being moved by swivelling, deflecting or otherwise while the vehicle is in motion.
  - (2) Paragraph (1) does not apply in respect of-
    - (a) a headlamp which can be dipped only by the movement of the headlamp or its reflector;
    - (b) a headlamp which is capable of adjustment so as to compensate for the effect of the load carried by the vehicle;
    - (c) a lamp or reflector which can be deflected to the side by the movement of, although not necessarily through the same angle as, the front wheel or wheels of the vehicle when turned for the purpose of steering the vehicle;
    - (d) a headlamp or front fog lamp which can be wholly or partially retracted or concealed;
    - (e) a direction indicator fitted to a motor vehicle first used before 1st April 1986;
    - (f) a work lamp;
    - (g) a warning beacon;
    - (h) an amber pedal retro reflector; F22...

- (i) retro reflective material or a retro reflector of any colour which is fitted so as to reflect light primarily to one or both sides of the vehicle and is attached to or incorporated in any wheel or tyre of—
  - [F23(i) a pedal cycle;
    - (ii) a trailer drawn by, or a sidecar attached to, a pedal cycle;
    - (iii) a solo motor bicycle or motor bicycle combination, or
    - (iv) an invalid carriage;]
- [F24(j)] a lamp which is designed to emit light primarily to one or both sides of the vehicle, and is attached to or incorporated in any wheel or tyre of—
  - (i) a pedal cycle;
  - (ii) a trailer drawn by, or a sidecar attached to, a pedal cycle; or
  - (k) a lamp attached to or incorporated in a pedal of a pedal cycle.]

- F22 Word in reg. 12(2)(h) omitted (21.10.2005) by virtue of The Road Vehicles Lighting (Amendment) Regulations 2005 (S.I. 2005/2559), regs. 1, 5(a)
- **F23** Reg. 12(2)(i)(i)-(iv) substituted for reg. 12(2)(i)(i)-(iii) (21.10.2005) by The Road Vehicles Lighting (Amendment) Regulations 2005 (S.I. 2005/2559), regs. 1, **5(b)**
- **F24** Reg. 12(2)(j)(k) added (21.10.2005) by The Road Vehicles Lighting (Amendment) Regulations 2005 (S.I. 2005/2559), regs. 1, **5(c)**

#### **Commencement Information**

**I2** Reg. 12 in force at 1.11.1989, see reg. 1(1)

#### Lamps to show a steady light

- **13.**—(1) Save as provided in paragraph (2), no vehicle shall be fitted with a lamp which automatically emits a flashing light.
  - (2) Paragraph (1) does not apply in respect of-
    - (a) a direction indicator;
    - (b) a headlamp fitted to an emergency vehicle [F25 or a vehicle used for special forces purposes];
    - (c) a warning beacon or special warning lamp;
    - (d) a lamp or illuminated sign fitted to a vehicle used for police purposes;
    - (e) a green warning lamp used as an anti-lock brake indicator; F26...
    - (f) lamps forming part of a traffic sign;
  - $I^{\text{F27}}(g)$  a front position lamp capable of emitting a flashing light (whether or not it is also capable of emitting a steady light) which is fitted to—
    - (i) a pedal cycle; or
    - (ii) a trailer drawn by, or a sidecar attached to, a pedal cycle;

and which, if it is a lamp which is required to be fitted pursuant to regulation 18, is capable, when emitting a flashing light, of emitting light to the front of the pedal cycle, trailer or sidecar (as the case may be) of an intensity of not less than 4 candelas; or

- (h) a rear position lamp capable of emitting a flashing light (whether or not it is also capable of emitting a steady light) which is fitted to—
  - (i) a pedal cycle; or
  - (ii) a trailer drawn by, or a sidecar attached to, a pedal cycle;

and which, if it is a lamp which is required to be fitted pursuant to regulation 18, is capable, when emitting a flashing light, of emitting light to the rear of the pedal cycle, trailer or sidecar (as the case may be) of an intensity of not less than 4 candelas.]

#### **Textual Amendments**

- F25 Words in reg. 13(2)(b) added (15.4.2011) by The Road Traffic Exemptions (Special Forces) (Variation and Amendment) Regulations 2011 (S.I. 2011/935), regs. 1(1), 4(c)
- **F26** Word in reg. 13(2) omitted (21.10.2005) by virtue of The Road Vehicles Lighting (Amendment) Regulations 2005 (S.I. 2005/2559), regs. 1, 6(a)
- **F27** Reg. 13(2)(g)(h) added (21.10.2005) by The Road Vehicles Lighting (Amendment) Regulations 2005 (S.I. 2005/2559), regs. 1, **6(b)**

#### **Commencement Information**

I3 Reg. 13 in force at 1.11.1989, see reg. 1(1)

#### Filament lamps

- 14.—(1) Where a motor vehicle first used on or after 1st April 1986 or any trailer manufactured on or after 1st October 1985 is equipped with any lamp of a type that is required by any Schedule to these Regulations to be marked with an approval mark, no filament lamp other than a filament lamp referred to in the Designation of Approval Marks Regulations in—
  - (a) regulation 4 and Schedule 2, items 2 or 2A, 8, 20, 37 or 37A; or
  - (b) regulation 5 and Schedule 4, item 18,

shall be fitted to any such lamp.

F28	2	١						

#### **Textual Amendments**

**F28** Reg. 14(2) omitted (1.10.1994) by virtue of The Road Vehicles Lighting (Amendment) Regulations 1994 (S.I. 1994/2280), regs. 1(2), **8** 

#### **Commencement Information**

**I4** Reg. 14 in force at 1.11.1989, see **reg. 1(1)** 

#### General requirements for electrical connections

- 15.—(1) Every motor vehicle first used on or after 1st April 1991 shall be so constructed that every position lamp, side marker lamp, end-outline marker lamp and rear registration plate lamp with which the vehicle is fitted is capable of being switched on and off by the operation of one switch and, save as provided in paragraph (2), not otherwise.
- (2) Sub-paragraph (a) of paragraph (1) shall not prevent one or more position lamps from being capable of being switched on and off independently of any other lamp referred to in that subparagraph.

#### **Commencement Information**

I5 Reg. 15 in force at 1.11.1989, see reg. 1(1)

#### Restrictions on fitting blue warning beacons, special warning lamps and similar devices

- **16.** No vehicle, other than an emergency vehicle [F29 or a vehicle used for special forces purposes], shall be fitted with—
  - (a) a blue warning beacon or special warning lamp, or
  - (b) a device which resembles a blue warning beacon or a special warning lamp, whether the same is in working order or not.

#### **Textual Amendments**

**F29** Words in reg. 16 inserted (15.4.2011) by The Road Traffic Exemptions (Special Forces) (Variation and Amendment) Regulations 2011 (S.I. 2011/935), regs. 1(1), 4(d)

#### **Commencement Information**

**I6** Reg. 16 in force at 1.11.1989, see reg. 1(1)

#### **Obligatory warning beacons**

- 17.—(1) Subject to paragraph (2), no person shall use, or cause or permit to be used, on an unrestricted dual-carriageway road any motor vehicle with four or more wheels having a maximum speed not exceeding 25 mph unless it or any trailer drawn by it is fitted with at least one warning beacon which—
  - (a) complies with Schedule 16, and
  - (b) is showing an amber light.
  - (2) Paragraph (1) shall not apply in relation to—
    - (a) any motor vehicle first used before 1st January 1947; and
    - (b) any motor vehicle, or any trailer being drawn by it, to which paragraph (1) would otherwise apply, when that vehicle or trailer is on any carriageway of an unrestricted dual-carriageway road for the purpose only of crossing that carriageway in the quickest manner practicable in the circumstances.

#### **Commencement Information**

I7 Reg. 17 in force at 1.11.1989, see reg. 1(1)

#### [F30Signs on buses carrying children

- **17A.**—(1) Subject to paragraph (2), no person shall use or cause or permit to be used on a road a bus when it is carrying a child to or from his school unless—
  - (a) a prescribed sign is fitted to the front of the bus and is plainly visible to road users ahead of the bus, and
  - (b) a prescribed sign is fitted to the rear of the bus and is plainly visible to road users behind the bus.

- (2) Paragraph (1) does not apply where a bus is on a bus service of a description specified in paragraph 2 of the Schedule to the Fuel Duty Grant (Eligible Bus Services) Regulations 1985.
  - (3) For the purposes of this regulation—
    - (a) a reference to a bus carrying a child to or from his school is a reference to a bus carrying a child—
      - (i) to, or to a place within the vicinity of, his school on a day during term time before he has attended the school on that day; or
      - (ii) from, or from a place within the vicinity of, his school on a day during term time after he has finished attending the school on that day;
    - (b) "school" has the meaning given by section 114 of the Education Act 1944; and
    - (c) a reference to a child is a reference to a child under the age of 16 years.]

F30 Reg. 17A inserted (1.4.1995) by The Road Vehicles Lighting (Amendment) Regulations 1994 (S.I. 1994/2280), regs. 1(2), 6

#### Obligatory lamps, reflectors, rear markings and devices

- **18.**—(1) Save as provided in the foregoing provisions of these Regulations [F31, in regulation 20A(9)] and in [F32 paragraphs (2), [F33(2ZA),] (2A) and (2B)], every vehicle of a class specified in a Table in Schedule 1 shall be fitted with lamps, reflectors, rear markings and devices which—
  - (a) are of a type specified in column 1 of that Table, and
  - (b) comply with the relevant installation, alignment and performance requirements set out in the Schedule or Part of a Schedule shown against that type in column 2 of that Table.
- (2) The requirements specified in paragraph (1) do not apply in respect of a lamp, reflector, rear marking or device of a type specified in column 1 of a Table in the case of a vehicle shown against it in column 3 of that Table.
- [F34(2ZA) The requirements specified in paragraph (1) do not apply in the case of a headlamp cleaning device fitted to a lamp, other than a gas discharge headlamp or an adaptive front lighting system.]
- [F35(2A)] The requirements specified in paragraph 5(c) and (ca) of Schedule 2 shall not apply in the case of a front position lamp capable of emitting a flashing light which is fitted to—
  - (i) a pedal cycle; or
- (ii) a trailer drawn by, or a sidecar attached to, a pedal cycle, unless the lamp is also capable of emitting a steady light.
- (2B) The requirements specified in paragraph 5(d) and (e) of Schedule 10 shall not apply in the case of a rear position lamp capable of emitting a flashing light which is fitted to—
  - (i) a pedal cycle; or
- (ii) a trailer drawn by, or a sidecar attached to, a pedal cycle, unless the lamp is also capable of emitting a steady light.]
- (3) The requirements specified in paragraph (1) apply without prejudice to any additional requirements specified in regulations 20 [F36, 20A] and 21.
  - (4) The Schedules referred to in the Tables in Schedule 1 are Schedules 2 to 21 [F37, and 24].

- **F31** Words in reg. 18(1) inserted (4.1.2010) by The Road Vehicles Lighting and Goods Vehicles (Plating and Testing) (Amendment) Regulations 2009 (S.I. 2009/3220), regs. 1, 6(2)
- F32 Words in reg. 18(1) substituted (21.10.2005) by The Road Vehicles Lighting (Amendment) Regulations 2005 (S.I. 2005/2559), regs. 1, 7(2)
- **F33** Word in reg. 18(1) inserted (20.5.2018) by The Road Vehicles Lighting (Amendment) Regulations 2017 (S.I. 2017/852), regs. 1, 4(a)
- F34 Reg. 18(2ZA) inserted (20.5.2018) by The Road Vehicles Lighting (Amendment) Regulations 2017 (S.I. 2017/852), regs. 1, 4(b)
- F35 Reg. 18(2A)(2B) inserted (21.10.2005) by The Road Vehicles Lighting (Amendment) Regulations 2005 (S.I. 2005/2559), regs. 1, 7(3)
- **F36** Word in reg. 18(3) inserted (4.1.2010) by The Road Vehicles Lighting and Goods Vehicles (Plating and Testing) (Amendment) Regulations 2009 (S.I. 2009/3220), regs. 1, **6(3)**
- **F37** Words in reg. 18(4) inserted (20.5.2018) by The Road Vehicles Lighting (Amendment) Regulations 2017 (S.I. 2017/852), regs. 1, 4(c)

#### **Commencement Information**

**I8** Reg. 18 in force at 1.11.1989, see reg. 1(1)

#### Restrictions on the obscuration of certain obligatory lamps and reflectors

- 19. Every vehicle shall be so constructed that at least part of the apparent surface of any—
  - (a) front and rear position lamp,
  - (b) front and rear direction indicator, and
  - (c) rear retro reflector,

which is required by these Regulations to be fitted to a vehicle is visible when the vehicle is viewed from any point directly in front of or behind the lamp or reflector, as appropriate, when every door, tailgate, boot lid, engine cover, cab or other movable part of the vehicle is in a fixed open position.

# Commencement Information 19 Reg. 19 in force at 1.11.1989, see reg. 1(1)

#### Optional lamps, reflectors, rear markings and devices

**20.** [F38Subject to regulation 20A(9), every optional lamp], reflector, rear marking or device fitted to a vehicle, being of a type specified in an item in column 2 of the Table below, shall comply with the provisions shown in column 3 of that Table.

#### **TABLE**

(1)	(2)	(3)	
Item No.	Type of lamp, reflector, rear marking or device	Provisions with which	ch compliance is required
1	Front position lamp	Schedule 2, Part II	and Parts I of Schedules 2 to 5, 7, 9

(1) Item No.	(2) Type of lamp, reflector, rear marking or device	(3) Provisions with which	h compliance is required
			to 13 and 17 to 21 to the extent specified in Parts II of those Schedules.
2	Dim-dip device and running lamp	Schedule 3, Part II	and Parts I of Schedules 2 to 5, 7, 9 to 13 and 17 to 21 to the extent specified in Parts II of those Schedules.
3	Dipped-beam headlamp	Schedule 4, Part II	and Parts I of Schedules 2 to 5, 7, 9 to 13 and 17 to 21 to the extent specified in Parts II of those Schedules.
4	Main-beam headlamp	Schedule 5, Part II	and Parts I of Schedules 2 to 5, 7, 9 to 13 and 17 to 21 to the extent specified in Parts II of those Schedules.
5	Front fog lamp	Schedule 6	and Parts I of Schedules 2 to 5, 7, 9 to 13 and 17 to 21 to the extent specified in Parts II of those Schedules.
7	Direction indicator	Schedule 7, Part II	and Parts I of Schedules 2 to 5, 7, 9 to 13 and 17 to 21 to the extent specified in Parts II of those Schedules.
8	Hazard warning signal device	Schedule 8	and Parts I of Schedules 2 to 5, 7, 9 to 13 and 17 to 21 to the extent specified in Parts II of those Schedules.
9	Side marker lamp	Schedule 9, Part II	and Parts I of Schedules 2 to 5, 7, 9 to 13 and 17 to 21 to the extent specified

(1) Item No.	(2) Type of lamp, reflector, rear marking or device	(3) Provisions with which	compliance is required
			in Parts II of those Schedules.
10	Rear position lamp	Schedule 10, Part II	and Parts I of Schedules 2 to 5, 7, 9 to 13 and 17 to 21 to the extent specified in Parts II of those Schedules.
11	Rear fog lamp	Schedule 11, Part II	and Parts I of Schedules 2 to 5, 7, 9 to 13 and 17 to 21 to the extent specified in Parts II of those Schedules.
12	Stop lamp	Schedule 12, Part II	and Parts I of Schedules 2 to 5, 7, 9 to 13 and 17 to 21 to the extent specified in Parts II of those Schedules.
13	End-outline marker lamp	Schedule 13, Part II	and Parts I of Schedules 2 to 5, 7, 9 to 13 and 17 to 21 to the extent specified in Parts II of those Schedules.
14	Reversing lamp	Schedule 14 [ <sup>F39</sup> , Part II]	and Parts I of Schedules 2 to 5, 7, 9 to 13 and 17 to 21 to the extent specified in Parts II of those Schedules.
15	Warning beacon	Schedule 16	and Parts I of Schedules 2 to 5, 7, 9 to 13 and 17 to 21 to the extent specified in Parts II of those Schedules.
16	Side retro reflector	Schedule 17, Part II	and Parts I of Schedules 2 to 5, 7, 9 to 13 and 17 to 21 to the extent specified in Parts II of those Schedules.

(1)	(2)	(3)	
Item No.	Type of lamp, reflector, rear marking or device	Provisions with which	h compliance is required
17	Rear retro reflector	Schedule 18, Part II	and Parts I of Schedules 2 to 5, 7, 9 to 13 and 17 to 21 to the extent specified in Parts II of those Schedules.
18	Rear marking	Schedule 19, Part II	and Parts I of Schedules 2 to 5, 7, 9 to 13 and 17 to 21 to the extent specified in Parts II of those Schedules.
19	Pedal retro reflector	Schedule 20, Part II	and Parts I of Schedules 2 to 5, 7, 9 to 13 and 17 to 21 to the extent specified in Parts II of those Schedules.
20	Front retro reflector	Schedule 21, Part II	and Parts I of Schedules 2 to 5, 7, 9 to 13 and 17 to 21 to the extent specified in Parts II of those Schedules.
[ <sup>F40</sup> 21	Daytime running lamps fitted on or after 20th May 2018	Schedule 24]	

- **F38** Words in reg. 20 substituted (4.1.2010) by The Road Vehicles Lighting and Goods Vehicles (Plating and Testing) (Amendment) Regulations 2009 (S.I. 2009/3220), regs. 1, 7
- **F39** Words in reg. 20 inserted (20.5.2018) by The Road Vehicles Lighting (Amendment) Regulations 2017 (S.I. 2017/852), regs. 1, **5(a)**
- **F40** Words in reg. 20 inserted (20.5.2018) by The Road Vehicles Lighting (Amendment) Regulations 2017 (S.I. 2017/852), regs. 1, **5(b)**

#### **Commencement Information**

**I10** Reg. 20 in force at 1.11.1989, see reg. 1(1)

#### [F41Application of the ECE conspicuity requirements

- **20A.**—(1) Subject to paragraphs (2), (4) and (5), a goods vehicle which is—
  - (a) a motor vehicle first used on or after 10th July 2011, or

- (b) a trailer manufactured on or after 10th July 2011, shall be fitted with conspicuity markings which comply with the mandatory ECE conspicuity requirements.
  - (2) Paragraph (1) does not apply in respect of a goods vehicle which is—
    - (a) a motor vehicle with a maximum gross weight not exceeding 7500 kg;
    - (b) a trailer with a maximum gross weight not exceeding 3500 kg;
    - (c) an incomplete vehicle proceeding to a works for completion or to a place where it is to be stored or displayed for sale; or
    - (d) a motor car or heavy motor car intended to form part of an articulated vehicle.
- (3) A goods vehicle to which paragraph (1) applies is referred to in this regulation as a "relevant goods vehicle".
- (4) If the overall length of a relevant goods vehicle does not exceed 6 m, conspicuity markings that comply with the mandatory ECE conspicuity requirements need not be fitted to the side of that vehicle.
- (5) If the overall width of a relevant goods vehicle does not exceed 2.1 m, conspicuity markings that comply with the mandatory ECE conspicuity requirements need not be fitted to the rear of that vehicle.
- (6) To the extent that, pursuant to paragraph (4) or (5), a relevant goods vehicle is not required to be fitted with conspicuity markings to the side or rear that comply with the mandatory ECE conspicuity requirements, conspicuity markings which comply with the optional ECE conspicuity requirements may be fitted to the side or rear (as the case may be).
- (7) Subject to paragraph (8), a vehicle which is not a relevant goods vehicle may be fitted with conspicuity markings which comply with the optional ECE conspicuity requirements.
  - (8) Paragraph (7) does not apply in respect of—
    - (a) a passenger vehicle (other than a bus); or
    - (b) a trailer with a maximum gross weight not exceeding 750 kg.
- (9) A requirement imposed under regulation 18 or 20 is to be disregarded to the extent it is incompatible with paragraph (1), (6) or (7).
- (10) In this regulation "motor car" and "heavy motor car" have the same meaning as in the Construction and Use Regulations.]

**F41** Reg. 20A inserted (4.1.2010) by The Road Vehicles Lighting and Goods Vehicles (Plating and Testing) (Amendment) Regulations 2009 (S.I. 2009/3220), regs. 1, **8** 

#### Projecting trailers and vehicles carrying overhanging or projecting loads or equipment

- **21.**—(1) No person shall use, or cause or permit to be used, on a road in the circumstances mentioned in paragraph (2)—
  - (a) any trailer which forms part of a combination of vehicles which projects laterally beyond any preceding vehicle in the combination; or
- (b) any vehicle [F42 or] combination of vehicles which carries a load or equipment in either case under the conditions specified in an item in column 2 of the Table below, unless the vehicle or combination of vehicles complies with the requirements specified in that item in column 3 of that Table.

#### TABLE

(1)	(2)	(3)
Item No.	Conditions	Requirements
1	A trailer which is not fitted with front position lamps and which projects laterally on any side so that the distance from the outermost part of the projection to the outermost part of the illuminated area of the obligatory front position lamp on that side fitted to any preceding vehicle in the combination exceeds 400 mm.	A lamp showing white light to the front shall be fitted to the trailer so that the outermost part of the illuminated area is not more than 400 mm from the outermost projection of the trailer. The installation and performance requirements relating to front position lamps do not apply to any such lamp.
2	A trailer which is not fitted with front position lamps and which carries a load or equipment which projects laterally on any side of the trailer so that the distance from the outermost projection of the load or equipment to the outermost part of the illuminated area of the obligatory front position lamp on that side fitted to any preceding vehicle in the combination exceeds 400 mm.	A lamp showing white light to the front shall be fitted to the trailer or the load or equipment so that the outermost part of the illuminated area is not more than 400 mm from the outermost projection of the load or equipment. The installation and performance requirements relating to front position lamps do not apply to any such lamp.
3	A vehicle which carries a load or equipment which projects laterally on any side of the vehicle so that the distance from the outermost part of the load or equipment to the outermost part of the illuminated area of the obligatory front or rear position lamp on that side exceeds 400 mm.	Either—  (a) the obligatory front or rear position lamp shall be transferred from the vehicle to the load or equipment to which must also be attached a white front or a red rear reflecting device; or  (b) an additional front or rear position lamp and a white front or a red rear reflecting device shall be fitted to the vehicle, load or equipment.  All the installation, performance and maintenance requirements relating to front
		or rear position lamps shall in either case be complied with except that for the purpose of

(1)	(2)	(3)
Item No.	Conditions	Requirements  determining the lateral position of such lamps and reflecting devices any reference to the vehicle shall be taken to include the load or equipment except special equipment on a vehicle fitted with a movable platform or the jib of any crane.
4	A vehicle which carries a load or equipment which projects beyond the rear of the vehicle or, in the case of a combination of vehicles, beyond the rear of the rearmost vehicle in the combination, more than—  (a) 2 m in the case of an agricultural vehicle or a vehicle carrying a fire escape; or  (b) 1 m in the case of any other vehicle.	An additional rear lamp capable of showing red light to the rear and a red reflecting device, both of which are visible from a reasonable distance, shall be fitted to the vehicle or the load in such a position that the distance between the lamp and the reflecting device, and the rearmost projection of the load or equipment does not exceed 2m in the case mentioned in sub-paragraph (a) in column 2 of this item or 1 m in any other case. The installation and performance requirements relating to rear position [F43] lamps and rear retro reflectors do not apply to any such additional lamp and reflecting device].
5	A vehicle which carries a load or equipment which projects beyond the front of the vehicle more than—  (a) 2 m in the case of an agricultural vehicle or a vehicle carrying a fire escape; or  (b) 1 m in the case of any other vehicle.	An additional front lamp capable of showing white light to the front and a white reflecting device, both visible from a reasonable distance, shall be fitted to the vehicle or the load in such a position that the distance between the lamp and the reflecting device, and the foremost projection of the load or equipment, does not exceed 2 m in the case mentioned in sub-paragraph (a) in column 2 of this item or 1 m in any other case. The intallation and performance requirements relating to front position lamps and front retro

(1)	(2)	(3)
Item No.	Conditions	Requirements
		reflectors do not apply to any such additional lamp and reflecting device.
6	A vehicle which carries a load or equipment which obscures any obligatory lamp, reflector or rear marking.	Either— a) the obligatory lamp, reflector or rear marking shall be transferred to a position on the vehicle, load or equipment where it is not obscured; or b) an additional lamp, reflector or rear marking shall be fitted to the vehicle, load or equipment.
		All the installation, performance and maintenance requirements relating to obligatory lamps, reflectors or rear markings shall in either case be complied with.

- (2) The circumstances referred to in paragraph (1) are-
  - (a) as regards item 6 in the Table, in so far as it relates to obligatory stop lamps and direction indicators, all circumstances; and
  - (b) as regards items 1 to 5 in the Table and item 6 in the Table, except in so far as it relates to obligatory stop lamps and direction indicators, the time between sunset and sunrise or, except in so far as it relates to obligatory reflectors, when visibility is seriously reduced between sunrise and sunset.

- **F42** Word in reg. 21(1)(b) substituted (1.10.1994) by The Road Vehicles Lighting (Amendment) Regulations 1994 (S.I. 1994/2280), regs. 1(2), **17(1)**
- **F43** Words in reg. 21(1) Table Item 4 substituted (1.10.1994) by The Road Vehicles Lighting (Amendment) Regulations 1994 (S.I. 1994/2280), regs. 1(2), **17(2)**

#### **Commencement Information**

III Reg. 21 in force at 1.11.1989, see reg. 1(1)

#### Additional side marker lamps

**22.**—(1) Save as provided in paragraph (2), no person shall use, or cause or permit to be used, on a road between sunset and sunrise, or in seriously reduced visibility between sunrise and sunset, any vehicle or combination of vehicles of a type specified in an item in column 2 of the Table below unless each side of the vehicle or combination of vehicles is fitted with the side marker lamps specified in that item in column 3 and those lamps are kept lit.

#### TABLE

(1) Item No.	(2) Vehicle or combination of vehicles	(3) Side marker lamps
1	A vehicle or a combination of vehicles the overall length of which (including any load) exceeds 18.3 m.	There shall be fitted—  (a) one lamp no part of the light-emitting surface of which is more than 9.15 m from the foremost part of the vehicle or vehicles (in either case inclusive of any load);  (b) one lamp no part of the
		light-emitting surface of which is more than 3.05 m from the rearmost part of the vehicle or vehicles (in either case inclusive of any load); and
		(c) such other lamps as are required to ensure that not more than 3.05 m separates any part of the light-emitting surface of one lamp and any part of the light-emitting surface of the next lamp.
2	A combination of vehicles the overall length of which (including any load) exceeds 12.2 m but does not exceed 18.3 m and carrying a load supported by any two of the vehicles but not including a	There shall be fitted—  (a) one lamp no part of the light-emitting surface of which is forward of, or more than 1530 mm rearward of, the rearmost part of the drawing
	load carried by an articulated vehicle.	vehicle; and if the supported load extends more than 9.15 m rearward of the rearmost part of the drawing vehicle, one lamp no part of the light- emitting surface of which is forward of, or more than 1530 mm rearward of, the centre of the length of the load.

- (2) The requirements specified in paragraph (1) do not apply to-
  - (a) a combination of vehicles where any vehicle being drawn in that combination has broken down; or

- (b) a vehicle (not being a combination of vehicles) having an appliance or apparatus or carrying a load of a kind specified in the Table to regulation 82(7) or in regulation 82(8) of the Construction and Use Regulations, if the conditions specified in paragraphs 3 and 4 (which provide for the special marking of projections from vehicles) of Schedule 12 to those Regulations are complied with in relation to the special appliance or apparatus or load as if the said conditions had been expressed in the said regulation 82 to apply in the case of every special appliance or apparatus or load of a kind specified in that regulation.
- (3) Every side marker lamp fitted in accordance with this regulation shall comply with Part I of Schedule 9.

#### **Commencement Information**

I12 Reg. 22 in force at 1.11.1989, see reg. 1(1)

**Changes to legislation:**There are currently no known outstanding effects for the The Road Vehicles Lighting Regulations 1989, PART II.