

ANNEX I

MINIMUM SAFETY AND HEALTH REQUIREMENTS FOR WORKPLACES USED FOR THE FIRST TIME, AS REFERRED TO IN ARTICLE 3 OF THE DIRECTIVE

12. Traffic routes — danger areas
 - 12.1. Traffic routes, including stairs, fixed ladders and loading bays and ramps, must be located and dimensioned to ensure easy, safe and appropriate access for pedestrians or vehicles in such a way as not to endanger workers employed in the vicinity of these traffic routes.
 - 12.2. Routes used for pedestrian traffic and/or goods traffic must be dimensioned in accordance with the number of potential users and the type of undertaking.

If means of transport are used on traffic routes, a sufficient safety clearance must be provided for pedestrians.

- 12.3. Sufficient clearance must be allowed between vehicle traffic routes and doors, gates, passages for pedestrians, corridors and staircases.
- 12.4. Where the use and equipment of rooms so requires for the protection of workers, traffic routes must be clearly identified.
- 12.5. If the workplaces contain danger areas in which, owing to the nature of the work, there is a risk of the worker or objects falling, the places must be equipped, as far as possible, with devices preventing unauthorized workers from entering those areas.

Appropriate measures must be taken to protect workers authorized to enter danger areas.

Danger areas must be clearly indicated.