Status: EU Directives are being published on this site to aid cross referencing from UK legislation. After IP completion day (31 December 2020 11pm) no further amendments will be applied to this version.

#### ANNEX II

#### Health and safety and environmental requirements relating to the inspection of pesticide application equipment

The inspection of pesticide application equipment shall cover all aspects important to achieve a high level of safety and protection of human health and the environment. Full effectiveness of the application operation should be ensured by proper performance of devices and functions of the equipment to guarantee the following objectives are met.

The pesticide application equipment must function reliably and be used properly for its intended purpose ensuring that pesticides can be accurately dosed and distributed. The equipment must be in such a condition as to be filled and emptied safely, easily and completely and prevent leakage of pesticides. It must permit easy and thorough cleaning. It must also ensure safe operations, and be controlled and capable of being immediately stopped from the operator's seat. Where necessary, adjustments must be simple, accurate and capable of being reproduced.

Particular attention should be paid to:

# 1. Power transmission parts

The power take-off driveshaft guard and the guard of the power input connection shall be fitted and in good condition and the protective devices and any moving or rotating power transmission parts shall not be affected in their function so as to ensure protection of the operator.

### 2. Pump

The pump capacity shall be suited to the needs of the equipment and the pump must function properly in order to ensure a stable and reliable application rate. There shall be no leakages from the pump.

# 3. Agitation

Agitation devices must ensure a proper recirculation in order to achieve an even concentration of the whole volume of the liquid spray mixture in the tank.

# 4. Spray liquid tank

Spray tanks including indicator of tank content, filling devices, strainers and filters, emptying and rinsing systems, and mixing devices shall operate in such a way as to minimise accidental spillage, uneven concentration distribution, operator exposure and residual content.

## 5. Measuring systems, control and regulation systems

All devices for measuring, switching on and off and adjusting pressure and/or flow rate shall be properly calibrated and work correctly and there shall be no leakages. Control of pressure and operation of pressure adjustment devices shall be easily possible during application. Pressure adjustment devices shall maintain a constant working pressure at constant revolutions of the pump, in order to ensure that a stable volume application rate is applied.

#### 6. Pipes and hoses

Pipes and hoses shall be in proper condition to avoid disturbance of liquid flow or accidental spillage in case of failure. There shall be no leakages from pipes or hoses when run with the maximum obtainable pressure for the system.

#### 7. Filtering

Document Generated: 2023-08-23

Status: EU Directives are being published on this site to aid cross referencing from UK legislation. After IP completion day (31 December 2020 11pm) no further amendments will be applied to this version.

In order to avoid turbulence and heterogeneity in spray patterns, filters shall be in good condition and the mesh size of the filters shall correspond to the size of nozzles fitted on the sprayer. Where applicable the filter blockage indication system shall operate correctly.

8. Spray boom (for equipment spraying pesticides by means of a horizontally positioned boom, located close to the crop or the material to be treated).

The spray boom must be in good condition and stable in all directions. The fixation and adjustment systems and the devices for damping unintended movements and slope compensation must work correctly.

#### 9. Nozzles

Nozzles must work properly to control dripping when spraying stops. To ensure homogeneity of the spray pattern, the flow rate of each individual nozzle shall not deviate significantly from the data of the flow rate tables provided by the manufacturer.

#### 10. Distribution

The transverse and vertical (in case of applications in vertical crops) distribution of the spray mixture in the target area must be even, where relevant.

11. Blower (for equipment distributing pesticides by air assistance)

The blower must be in good condition and must ensure a stable and reliable air stream.