
Changes to legislation: There are currently no known outstanding effects for the Council Regulation (EU) 2020/2230, ANNEX. (See end of Document for details)

ANNEX

ANNEX However, the suspension of tariff duties does not apply where the processing is carried out by retail or catering undertakings. Suspension of duties is subject to end-use customs supervision in accordance with Article 254 of Regulation (EU) No 952/2013 of the European Parliament and of the Council of 9 October 2013 laying down the Union Customs Code (OJ L 269, 10.10.2013, p. 1). Only the ad valorem duty is suspended. The specific duty shall continue to apply. Order number CN code TARIC Description Quota period Quota volume Quota duty (%) 09.2637ex 0710 40 00ex 2005 80 002030 Corn cobs (*Zea mays* var. *saccharata*) whether or not cut, with a diameter of 10 mm or more, but not more than 20 mm, for use in the manufacture of products of the food industry for treatment other than simple repacking 1.1.-31.12.550 tonnes 0 % 09.2849ex 0710 80 6910 Mushrooms of the species *Auricularia polytricha* (uncooked or cooked by steaming or boiling), frozen, for the manufacture of prepared meals 1.1.-31.12.700 tonnes 0 % 09.2664ex 2008 60 3930 Sweet cherries containing added spirit, with a sugar content of not more than 9 % by weight, of a diameter of not more than 19,9 mm, with stones, for use in chocolate products 1.1.-31.12.1 000 tonnes 10 % 09.2740ex 2309 90 3187 Soya bean protein concentrate containing by weight: 60 % (± 10 %) of crude protein, 5 % (± 3 %) of crude fibre, 5 % (± 3 %) of crude ash, and 3 % or more but not more than 6,9 % of starch, for use in the manufacture of animal feed products 1.1.-31.12.30 000 tonnes 0 % 09.2913ex 2401 10 35ex 2401 10 70ex 2401 10 95ex 2401 10 95ex 2401 10 95ex 2401 20 35ex 2401 20 70ex 2401 20 95ex 2401 20 95ex 2401 20 9591101121919110112191 Natural unmanufactured tobacco, whether or not cut in regular size, having a custom value of not less than EUR 450 per 100 kg net weight, for use as binder or wrapper for the manufacture of goods falling within subheading 2402 10 00 1.1.-31.12.6 000 tonnes 0 % 09.2586ex 2710 19 81ex 2710 19 992040 Catalytically hydroisomerized and dewaxed base oil of hydrogenated, highly isoparaffinic hydrocarbons, containing: 90 % or more by weight of saturates, and not more than 0,03 % by weight of sulphur, and with a viscosity index of 80 or more, but less than 120, and a kinematic viscosity of 5,0 cSt at 100 °C or more, but not more than 13,0 cSt at 100 °C 1.1.-30.6.200 000 tonnes 0 % 09.28282712 20 90 Paraffin wax containing by weight less than 0,75 % of oil 1.4.-31.10.60 000 tonnes 0 % 09.2600ex 2712 90 3910 Slack wax (CAS RN 64742-61-6) 1.1.-31.12.100 000 tonnes 0 % 09.2578ex 2811 19 8050 Sulphamidic acid (CAS RN 5329-14-6) with a purity by weight of 95 % or more, whether or not with not more than 5 % addition of the anti-caking agent silicon dioxide (CAS RN 112926-00-8) 1.1.-31.12.27 000 tonnes 0 % 09.2928ex 2811 22 0040 Silica filler in the form of granules, with a purity by weight of 97 % or more of silicon dioxide 1.1.-31.12.1 700 tonnes 0 % 09.2806ex 2825 90 4030 Tungsten trioxide, including blue tungsten oxide (CAS RN 1314-35-8 or CAS RN 39318-18-8) 1.1.-31.12.12 000 tonnes 0 % 09.2872ex 2833 29 8040 Caesium sulphate (CAS RN 10294-54-9) in solid form or as aqueous solution containing by weight 48 % or more but not more than 52 % of caesium sulphate 1.1.-31.12.200 tonnes 0 % 09.2837ex 2903 79 3020 Bromochloromethane (CAS RN 74-97-5) 1.1.-31.12.600 tonnes 0 % 09.2933ex 2903 99 8030 1,3-Dichlorobenzene (CAS RN 541-73-1) 1.1.-31.12.2 600 tonnes 0 % 09.2700ex 2905 12 0010 Propan-1-ol (propyl alcohol) (CAS RN 71-23-8) 1.1.-31.12.15 000 tonnes 0 % 09.2830ex 2906 19 0040 Cyclopropylmethanol (CAS RN 2516-33-8) 1.1.-31.12.20 tonnes 0 % 09.2851ex 2907 12 0010 O-cresol (CAS RN 95-48-7) having a purity of not less than 98,5 % by weight 1.1.-31.12.20 000 tonnes 0 % 09.2704ex 2909 49 8020 2,2',2'-Tetrakis(hydroxymethyl)-3,3'-oxydipropan-1-ol (CAS RN 126-58-9) 1.1.-31.12.500 tonnes 0 % 09.26242912 42 00 Ethylvanillin (3-ethoxy-4-hydroxybenzaldehyde) (CAS RN 121-32-4) 1.1.-31.12.1 950 tonnes 0 % 09.2683ex

Changes to legislation: There are currently no known outstanding effects for the Council Regulation (EU) 2020/2230, ANNEX. (See end of Document for details)

2914 19 9050 Calcium acetylacetonate (CAS RN 19372-44-2) for use in the manufacture of stabilisator systems in tablet form 1.1.-31.12.200 tonnes 0 % 09.2852ex

2914 29 0060 Cyclopropyl methyl ketone (CAS RN 765-43-5) 1.1.-31.12.300 tonnes 0 % 09.2638ex

2915 21 0010 Acetic acid (CAS RN 64-19-7) of a purity by weight of 99 % or more 1.1.-31.12.1 000 000 tonnes 0 % 09.2679

2915 32 00 Vinyl acetate (CAS RN 108-05-4) 1.1.-31.12.400 000 tonnes 0 % 09.2728ex

2915 90 7085 Ethyl trifluoroacetate (CAS RN 383-63-1) 1.1.-31.12.400 tonnes 0 % 09.2665ex

2916 19 9530 Potassium (E,E)-hexa-2,4-dienoate (CAS RN 24634-61-5) 1.1.-31.12.8 250 tonnes 0 % 09.2684ex

2916 39 9028 2,5-dimethylphenylacetyl chloride (CAS RN 55312-97-5) 1.1.-31.12.700 tonnes 0 % 09.2599ex

2917 11 0040 Diethyl oxalate (CAS RN 95-92-1) 1.1.-31.12.500 tonnes 0 % 09.2769ex

2917 13 9010 Dimethyl sebacate (CAS RN 106-79-6) 1.1.-31.12.1 000 tonnes 0 % 09.2634ex

2917 19 8040 Dodecanedioic acid (CAS RN 693-23-2), of a purity by weight of more than 98,5 % 1.1.-31.12.8 000 tonnes 0 % 09.2808ex

2918 22 0010 O-acetylsalicylic acid (CAS RN 50-78-2) 1.1.-31.12.120 tonnes 0 % 09.2646ex

2918 29 0075 Octadecyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate (CAS RN 2082-79-3) with: a sieve passing fraction at a mesh width of 500 µm of more than 99 % by weight, and a melting point of 49 °C or more, but not more than 54 °C, for use in the manufacture of PVC processing stabilizer-one packs based on powder mixtures (powders or press granulates) 1.1.-31.12.380 tonnes 0 % 09.2647ex

2918 29 0080 Pentaerythritol tetrakis(3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate) (CAS RN 6683-19-8) with: a sieve passing fraction at a mesh width of 250 µm of more than 75 % by weight and at a mesh width of 500 µm of more than 99 % by weight, and a melting point of 110 °C or more, but not more than 125 °C, for use in the manufacture of PVC processing stabilizer-one packs based on powder mixtures (powders or press granulates) 1.1.-31.12.140 tonnes 0 % 09.2975ex

2918 30 0010 Benzophenone-3,3',4,4'-tetracarboxylic dianhydride (CAS RN 2421-28-5) 1.1.-31.12.1 000 tonnes 0 % 09.2688ex

2920 29 0070 Tris (2,4-di-tert-butylphenyl)phosphite (CAS RN 31570-04-4) 1.1.-31.12.6 000 tonnes 0 % 09.2648ex

2920 90 1075 Dimethyl Sulphate (CAS RN 77-78-1) with a purity of at least 99 % 1.1.-31.12.18 000 tonnes 2 % 09.2598ex

2921 19 9975 Octadecylamine (CAS RN 124-30-1) 1.1.-31.12.400 tonnes 0 % 09.2649ex

2921 29 0060 Bis(2-dimethylaminoethyl)(methyl)amine (CAS RN 3030-47-5) 1.1.-31.12.1 700 tonnes 0 % 09.2682ex

2921 41 0010 Aniline (CAS RN 62-53-3) with a purity by weight of 99 % or more 1.1.-31.12.150 000 tonnes 0 % 09.2617ex

2921 42 0089 4-Fluoro-N-(1-methylethyl)benzeneamine (CAS RN 70441-63-3) 1.1.-31.12.500 tonnes 0 % 09.2582ex

2921 43 0080 2-Methylaniline (CAS RN 95-53-4) with a purity by weight of at least 99 % 1.1.-31.12.2 000 tonnes 2 % 09.2602ex

2921 51 1910 o-phenylenediamine (CAS RN 95-54-5) 1.1.-31.12.1 800 tonnes 0 % 09.2730ex

2921 59 9085 4,4'-Methanediyl dianiline (CAS RN 101-77-9) with a purity by weight of at least 97 %, in the form of granules, for use in the manufacture of prepolymers 1.1.-31.12.200 tonnes 2 % 09.2591ex

2922 41 0010 L-Lysine hydrochloride (CAS RN 657-27-2) 1.1.-31.12.245 000 tonnes 0 % 09.2592ex

2922 50 0025 L-Threonine (CAS RN 72-19-5) 1.1.-31.12.166 000 tonnes 0 % 09.2575ex

2923 90 0087 3-Chloro-2-hydroxypropyl)trimethylammonium chloride (CAS RN 3327-22-8), in the form of an aqueous solution containing by weight 65 % or more but not more than 71 % 3-chloro-2-hydroxypropyl)trimethylammonium chloride 1.1.-31.12.19 000 tonnes 0 % 09.2854ex

2924 19 0085 3-iodoprop-2-yn-1-yl butylcarbamate (CAS RN 55406-53-6) 1.1.-31.12.400 tonnes 0 % 09.2874ex

2924 29 7087 Paracetamol (INN) (CAS RN 103-90-2) 1.1.-31.12.20 000 tonnes 0 % 09.2742ex

2926 10 0010 Acrylonitrile (CAS RN 107-13-1), for use in the manufacture of goods of chapter 55 and heading 6815 1.1.-31.12.60 000 tonnes 0 % 09.2583ex

2926 10 0020 Acrylonitrile (CAS RN 107-13-1), for use in the manufacture of goods of headings 2921, 2924, 3906 and 4002 1.1.-31.12.40 000

Changes to legislation: There are currently no known outstanding effects for the Council Regulation (EU) 2020/2230, ANNEX. (See end of Document for details)

tonnes0 %09.2856ex 2926 90 70842-Nitro-4(trifluoromethyl)benzotrile (CAS RN 778-94-9)1.1.-31.12.900 tonnes0 %09.2708ex 2928 00 9015Monomethylhydrazine (CAS RN 60-34-4) in the form of an aqueous solution with a content by weight of monomethylhydrazine of 40 (\pm 5) %1.1.-31.12.900 tonnes0 %09.2581ex 2929 10 00251,5-Naphthylene diisocyanate (CAS RN 3173-72-6) with a purity by weight of 90 % or more1.1.-30.6205 tonnes0 %09.2685ex 2929 90 0030Nitroguanidine (CAS RN 556-88-7)1.1.-31.12.6 500 tonnes0 %09.2597ex 2930 90 9894Bis[3-(triethoxysilyl)propyl]disulphide (CAS RN 56706-10-6)1.1.-31.12.6 000 tonnes0 %09.2596ex 2930 90 98962-Chloro-4-(methylsulphonyl)-3-((2,2,2-trifluoroethoxy)methyl) benzoic acid (CAS RN 120100-77-8)1.1.-31.12.300 tonnes0 %09.2580ex 2931 90 0075Hexadecyltrimethoxysilane (CAS RN 16415-12-6) with a purity by weight of at least 95 %, for use in the manufacture of polyethylenel.1.-31.12.165 tonnes0 %09.28422932 12 002-Furaldehyde (furfuraldehyde)1.1.-31.12.10 000 tonnes0 %09.2696ex 2932 20 9025Decan-5-olide (CAS RN 705-86-2)1.1.-31.12.6 000 kilograms0 %09.2697ex 2932 20 9030Dodecan-5-olide (CAS RN 713-95-1)1.1.-31.12.6 000 kilograms0 %09.2812ex 2932 20 9077Hexan-6-olide (CAS RN 502-44-3)1.1.-31.12.4 000 tonnes0 %09.28582932 93 00Piperonal (CAS RN 120-57-0)1.1.-31.12.220 tonnes0 %09.2673ex 2933 39 99432,2,6,6-Tetramethylpiperidin-4-ol (CAS RN 2403-88-5)1.1.-31.12.1 000 tonnes0 %09.2880ex 2933 59 9539Ibrutinib (INN) (CAS RN 936563-96-1)1.1.-31.12.5 tonnes0 %09.2860ex 2933 69 80301,3,5-Tris[3-(dimethylamino)propyl]hexahydro-1,3,5-triazine (CAS RN 15875-13-5)1.1.-31.12.600 tonnes0 %09.2595ex 2933 99 80491,4,7,10-Tetraazacyclododecane (CAS RN 294-90-6)1.1.-31.12.40 tonnes0 %09.2658ex 2933 99 80735-(Acetoacetyl amino)benzimidazolone (CAS RN 26576-46-5)1.1.-31.12.400 tonnes0 %09.2593ex 2934 99 90675-Chlorothiophene-2-carboxylic acid (CAS RN 24065-33-6)1.1.-31.12.45 000 kilograms0 %09.2675ex 2935 90 90794-[[2-Methoxybenzoyl]amino]sulfonyl]benzoyl chloride (CAS RN 816431-72-8)1.1.-31.12.1 000 tonnes0 %09.2710ex 2935 90 90912,4,4-trimethylpentan-2-aminium (3R,5S,6E)-7-{2-[(ethylsulfonyl)amino]-4-(4-fluorophenyl)-6-(propan-2-yl)pyrimidin-5-yl}-3,5-dihydroxyhept-6- enoate (CAS RN 917805-85-7)1.1.-31.12.5 000 kilograms0 %09.2945ex 2940 00 0020D-Xylose (CAS RN 58-86-6)1.1.-31.12.400 tonnes0 %09.2686ex 3204 11 0075Colourant C.I. Disperse Yellow 54 (CAS RN 7576-65-0) and preparations based thereon with a colourant C.I. Disperse Yellow 54 content of 99 % or more by weight1.1.-31.12.250 tonnes0 %09.2676ex 3204 17 0014Preparations based on Colourant C.I. Pigment Red 48:2 (CAS RN 7023-61-2) with a content thereof of 60 % or more but less than 85 % by weight1.1.-31.12.50 tonnes0 %09.2698ex 3204 17 0030Colourant C.I. Pigment Red 4 (CAS RN 2814-77-9) and preparations based thereon with a colourant C.I. Pigment Red 4 content of 60 % or more by weight1.1.-31.12.150 tonnes0 %09.2659ex 3802 90 0019Soda flux calcinated diatomaceous earth1.1.-31.12.35 000 tonnes0 %09.2908ex 3804 00 0010Sodium lignosulphonate (CAS RN 8061-51-6)1.1.-31.12.40 000 tonnes0 %09.28893805 10 90Sulphate turpentine1.1.-31.12.25 000 tonnes0 %09.2935ex 3806 10 0010Rosin and resin acids obtained from fresh oleoresins1.1.-31.12.280 000 tonnes0 %09.2832ex 3808 92 9040Preparation containing 38 % or more but not more than 50 % by weight of pyrithione zinc (INN) (CAS RN 13463-41-7) in an aqueous dispersion1.1.-31.12.500 tonnes0 %09.2876ex 3811 29 0055Additives consisting of reaction products of diphenylamine and branched nonenes containing by weight:28 % or more, but not more than 55 % of 4-monononyldiphenylamine,45 % or more but not more than 65 % of 4,4'-dinonyldiphenylamine, andnot more than 5 % of 2, 4-dinonyldiphenylamine and 2,4'-dinonyldiphenylamine,used for the manufacture of lubricating oils1.1.-31.12.900 tonnes0 %09.2814ex 3815 90 9076Catalyst consisting of titanium dioxide and tungsten trioxide1.1.-31.12.3 000

Changes to legislation: There are currently no known outstanding effects for the
Council Regulation (EU) 2020/2230, ANNEX. (See end of Document for details)

tonnes0 %09.2820ex 3824 79 0010Mixtures containing by weight:60 % or more but not more than 90 % of 2-chloropropene (CAS RN 557-98-2),8 % or more but not more than 14 % of (Z)-1-chloropropene (CAS RN 16136-84-8),5 % or more but not more than 23 % of 2-chloropropane (CAS RN 75-29-6),not more than 6 % of 3-chloropropene (CAS RN 107-05-1), andnot more than 1 % of ethyl chloride (CAS RN 75-00-3)1.1.-31.12.6 000 tonnes0 %09.2644ex 3824 99 9277Preparation containing by weight:55 % or more but not more than 78 % of dimethyl glutarate (CAS RN 1119-40-0),10 % or more but not more than 30 % of dimethyl adipate (CAS RN 627-93-0), andnot more than 35 % of dimethyl succinate (CAS RN 106-65-0)1.1.-31.12.10 000 tonnes0 %09.2681ex 3824 99 9285Mixture of bis [3-(triethoxysilyl)propyl]sulphides (CAS RN 211519-85-6)1.1.-31.12.9 000 tonnes0 %09.2650ex 3824 99 9287Acetophenone (CAS RN 98-86-2), with a purity by weight of 60 % or more but not more than 90 %1.1.-31.12.2 000 tonnes0 %09.2888ex 3824 99 9289Mixture of tertiary alkyl dimethyl amines containing by weight:60 % or more but not more than 80 % of dodecyl dimethylamine (CAS RN 112-18-5), and20 % or more but not more than 30 % of dimethyl(tetradecyl)amine (CAS RN 112-75-4)1.1.-31.12.20 000 tonnes0 %09.2829ex 3824 99 9343Solid extract of the residual, insoluble in aliphatic solvents, obtained during the extraction of rosin from wood, having the following characteristics:a resin acid content not exceeding 30 % by weight,an acid number not exceeding 110, anda melting point of 100 °C or more1.1.-31.12.1 600 tonnes0 %09.2907ex 3824 99 9367Mixture of phytosterols, in the form of powder, containing by weight:75 % or more of sterols,not more than 25 % of stanols,for use in the manufacture of stanols/sterols or stanol/sterol esters1.1.-31.12.2 500 tonnes0 %09.26393905 30 00Poly(vinyl alcohol), whether or not containing unhydrolysed acetate groups1.1.-31.12.15 000 tonnes0 %09.2671ex 3905 99 9081Poly(vinyl butyral)(CAS RN 63148-65-2):containing by weight 17,5 % or more, but not more than 20 % of hydroxyl groups, andwith a median particle size (D50) of more than 0,6 mm1.1.-31.12.12 500 tonnes0 %09.2846ex 3907 40 0025Polymer blend of polycarbonate and poly(methyl methacrylate) with a polycarbonate content of not less than 98,5 % by weight, in the form of pellets or granules, with a luminous transmittance of not less than 88,5 %, measured using a test sample with a thickness of 4 mm at a wavelength of $\lambda = 400$ nm (according to ISO 13468-2)1.1.-31.12.2 000 tonnes0 %09.2585ex 3907 99 8070Copolymer of poly(ethylene terephthalate) and cyclohexane dimethanol, containing more than 10 % by weight of cyclohexane dimethanol1.1.-31.12.60 000 tonnes2 %09.2723ex 3911 90 1910Poly(oxy-1,4-phenylenesulphonyl-1,4-phenyleneoxy-4,4'-biphenylene)1.1.-31.12.5 000 tonnes0 %09.2816ex 3912 11 0020Cellulose acetate flakes1.1.-31.12.75 000 tonnes0 %09.2864ex 3913 10 0010Sodium alginate, extracted from brown seaweed (CAS RN 9005-38-3)1.1.-31.12.10 000 tonnes0 %09.2641ex 3913 90 0087Sodium hyaluronate, non sterile, with:a weight average molecular weight (Mw) of not more than 900 000,an endotoxin level of not more than 0,008 Endotoxin units (EU)/mg,an ethanol content of not more than 1 % by weight,an isopropanol content of not more than 0,5 % by weight1.1.-31.12.200 kilograms0 %09.2661ex 3920 51 0050Sheets of polymethylmethacrylate conforming to standards:EN 4364 (MIL-P-5425E) and DTD5592A, orEN 4365 (MIL-P-8184) and DTD5592A1.1.-31.12.100 tonnes0 %09.2645ex 3921 14 0020Cellular block of regenerated cellulose, impregnated with water containing magnesium chloride and quaternary ammonium compounds, measuring 100 cm (± 10 cm) x 100 cm (± 10 cm) x 40 cm (± 5 cm)1.1.-31.12.1 700 tonnes0 %09.2576ex 5208 12 1620Unbleached woven fabric in plain weave, with:a width of not more than 145 cm,a weight of 120 g/m² or more, but not more than 130 g/m²,30 or more, but not more than 45 wefts per cm,a tuck-in selvedge on both sides,where from the inside out, the 15 mm (± 2 mm) wide tuck-in selvedge consists of a 6 mm or more but not more

Changes to legislation: There are currently no known outstanding effects for the Council Regulation (EU) 2020/2230, ANNEX. (See end of Document for details)

than 9 mm wide strip of plain weave and a 6 mm or more but not more than 9 mm wide strip of panama weave1.1.-31.12.1 500 000 square meters0 %09.2577ex 5208 12 9620Unbleached woven fabric in plain weave, with:a width of not more than 145 cm,a weight of more than 130 g/m², but not more than 145 g/m²30 or more, but not more than 45 wefts per cm,a tuck-in selvedge on both sides,where from the inside out, the 15mm (± 2mm wide) tuck-in selvedge consists of a 6 mm or more but not more than 9 mm wide strip of plain weave and a 6 mm or more but not more than 9 mm wide strip of panama weave1.1.-31.12.2 300 000 square meters0 %09.2848ex 5505 10 1010Waste of synthetic fibres (including noils, yarn waste, and garnetted stock) of nylon or other polyamides (PA6 and PA66)1.1.-31.12.10 000 tonnes0 %09.2721ex 5906 99 9020Woven and laminated rubberised textile fabric with the following characteristics:with three layers,one outer layer consists of acrylic fabric,the other outer layer consists of polyester fabric,the middle layer consists of chlorobutyl rubber,the middle layer has a weight of 452 g/m² or more but not more than 569 g/m²,the textile fabric has a total weight of 952 g/m² or more but not more than 1159 g/m², andthe textile fabric has a total thickness of 0,8 mm or more but not more than 4 mm,used for the manufacture of the retractable roof of motor vehicles1.1.-31.12.375 000 square meters0 %09.2866ex 7019 12 00ex 7019 12 000626S glass stratifils (rovings):composed of continuous glass filaments of 9 µm (±0,5 µm),measuring 200 tex or more but not more than 680 tex,not containing any calcium oxide, andwith a breaking strength of more than 3 550 MPa determined by ASTM D2343-09,for use in the manufacture of aeronautics1.1.-31.12.1 000 tonnes0 %09.2628ex 7019 52 0010Glass web woven from glass fibre coated in plastic, of a weight of 120 g/m²(± 10 g/m²), of a type used in rolling insect screens with fixed frames1.1.-31.12.3 000 000 square meters0 %09.2799ex 7202 49 9010Ferro-chromium containing 1,5 % or more but not more than 4 % by weight of carbon and not more than 70 % of chromium1.1.-31.12.50 000 tonnes0 %09.2652ex 7409 11 00ex 7410 11 003040Refined copper foil and strips, electrolytically manufactured, with a thickness of 0,015 mm or more1.1.-31.12.1 020 tonnes0 %09.2734ex 7409 19 0020Plates or sheets consisting of:a layer of a silicon nitride ceramic with a thickness of 0,32 mm (± 0,1 mm) or more but not more than 1,0 mm (± 0,1 mm),covered on both sides with a foil of refined copper with a thickness of 0,8 mm (± 0,1 mm), andon one side partially covered with a coating of silver1.1.-31.12.7 000 000 pieces0 %09.2662ex 7410 21 0055Plates:consisting of at least one layer of fibreglass fabric impregnated with epoxide resin,covered on one or both sides with copper foil with a thickness of not more than 0,15 mm,with a dielectric constant (DK) of less than 5,4 at 1 MHz, as measured according to IPC-TM-650 2.5.5.2,with a loss tangent of less than 0,035 at 1 MHz, as measured according to IPC-TM-650 2.5.5.2,with a comparative tracking index (CTI) of 600 or more1.1.-31.12.80 000 square meters0 %09.2835ex 7604 29 1030Aluminium alloy rods with a diameter of 300,1 mm or more, but not more than 533,4 mm1.1.-31.12.1 000 tonnes0 %09.2736ex 7607 11 90ex 7607 11 907577Aluminium and magnesium alloy strip or foil:of an alloy conforming to standards 5182-H19 or 5052-H19,in rolls with an outside diameter of minimum 1 250 mm but not more than 1 350 mm,of a thickness (tolerance - 0,006 mm) of 0,15 mm, 0,16 mm, 0,18 mm or 0,20 mm,of a width (tolerance ± 0,3 mm) of 12,5 mm, 15,0 mm, 16,0 mm, 25,0 mm, 35,0 mm, 50,0 mm or 356 mm,having a camber tolerance of not more than 0,4 mm/750 mm,of a flatness measurement: I-unit ±4,having a tensile strength of more than (5182-H19) 365 MPa or (5052-H19) 320 MPa, andof an elongation A50 of more than (5182-H19) 3 % or (5052-H19) 2,5 %,for use in the manufacture of slats for blinds1.1.-31.12.600 tonnes0 %09.27228104 11 00Unwrought magnesium, containing at least 99,8 % by weight of magnesium1.1.-31.12.120 000 tonnes0 %09.2840ex 8104 30 0020Magnesium powder:of purity by weight of 98 % or more,

Changes to legislation: There are currently no known outstanding effects for the Council Regulation (EU) 2020/2230, ANNEX. (See end of Document for details)

but not more than 99,5 %, and with a particle size of 0,2 mm or more but not more than 0,8 mm

1.1.-31.12.2 000 tonnes 0 %09.2629ex 8302 49 0091 Aluminium telescopic handle for use in the manufacture of luggage

1.1.-31.12.1 500 000 pieces 0 %09.2720ex 8413 91 0050 Pump head for two cylinder high pressure pump made of forged steel, with: milled threaded fittings with a diameter of 10 mm or more but not more than 36,8 mm, and drilled fuel channels with a diameter of 3,5 mm or more but not more than 10 mm, of a kind used in diesel injection systems

1.1.-31.12.65 000 pieces 0 %09.2738ex 8482 99 0030 Brass cages with the following characteristics: continuously or centrifugally cast, turned, containing by weight 35 % or more, but not more than 38 % of zinc, containing by weight 0,75 % or more, but not more than 1,25 % of lead, containing by weight 1,0 % or more, but not more than 1,4 % of aluminium, and with a tensile strength of 415 Pa or more, of a kind used for the manufacture of ball bearings

1.1.-31.12.50 000 pieces 0 %09.2763ex 8501 40 20ex 8501 40 804030 Electric AC commutator motor, single-phase, with an output of 250 W or more, an input power of 700 W or more but not more than 2 700 W, an external diameter of more than 120 mm (\pm 0,2 mm) but not more than 135 mm (\pm 0,2 mm), a rated speed of more than 30 000 rpm but not more than 50 000 rpm, equipped with air-inducting ventilator, for use in the manufacture of vacuum cleaners

1.1.-31.12.2 000 000 pieces 0 %09.2584ex 8528 59 0040 Electronic device with LCD touch screen display powered by a voltage of 12 V or more but not more than 14,4 V: with LCD control processor, with GPS module, with Bluetooth module, with USB port, with radio signal tuner, with functions for cooperation with E-CALL, with connectors, without integrated control panel, for use in the manufacture of goods of Chapter 871.1-30.660

000 pieces 0 %09.2672ex 8529 90 92ex 9405 40 397570 Printed circuit board with LED diodes: whether or not equipped with prisms/lens, and whether or not fitted with connector(s) for the manufacture of backlight units for goods of heading 85281.1.-31.12.115 000 000 pieces 0 %09.2574ex 8537 10 9173 Multifunctional device (instrument cluster) with: curved TFT-LCD display (radius 750 mm) with touch-sensitive surfaces, microprocessors and memory chips, acoustic module and loudspeaker, connections for CAN, 3 x LIN bus, LVDS and Ethernet, for operating various functions (e.g. chassis, lighting) and for situation-related display of vehicle and navigation data (e.g. speed, odometer, charge level of the drive battery), for use in the manufacture of passenger cars powered solely by an electric motor covered by HS subheading 8703 801.1.-31.12.66 900 pieces 0 %09.2003ex 8543 70 9063 Voltage controlled frequency generator, consisting of active and passive elements mounted on a printed circuit, contained in a housing with dimensions of not more than 30 mm x 30 mm

1.1.-31.12.1 400 000 pieces 0 %09.2910ex 8708 99 9775 Aluminium alloy support bracket, with mounting holes, whether or not with fixation nuts, for indirect connection of the gearbox to the car body for use in the manufacture of goods of Chapter 871.1.-31.12.200 000 pieces 0 %09.2694ex 8714 10 9030 Axle clamps, housings, fork bridges and clamping pieces, of aluminium alloy of a kind used for motor bikes

1.1.-31.12.1 000 000 pieces 0 %09.2668ex 8714 91 10ex 8714 91 10ex 8714 91 10213175 Bicycle frame, constructed from carbon fibres and artificial resin, for use in the manufacture of bicycles (including electric bicycles)

1.1.-31.12.500 000 pieces 0 %09.2589ex 8714 91 10ex 8714 91 10ex 8714 91 10233370 Frame, constructed from aluminium or aluminium and carbon fibres, for the use in the manufacture of bicycles (including electric bicycles)

1.1.-31.12.8 000 000 pieces 0 %09.2631ex 9001 90 0080 Unmounted glass lenses, prisms and cemented elements for use in the manufacture or repair of goods of CN codes 9002, 9005, 9013 10 and 90151.1.-31.12.5 000 000 pieces 0 %09.2579ex 9029 20 31ex 9029 90 004040 Clustered instrument panel with: stepping motors, analog pointers and dials, or without microprocessor control board, or without LED indicators or LCD display, showing at least: speed, engine revolutions, engine temperature, the fuel level, communicating via CAN-BUS and/or

Changes to legislation: There are currently no known outstanding effects for the
Council Regulation (EU) 2020/2230, ANNEX. (See end of Document for details)

K-LINE protocols,for use in the manufacture of goods of Chapter 871.1.-31.12.160
000 pieces0 %

Changes to legislation:

There are currently no known outstanding effects for the Council Regulation (EU) 2020/2230, ANNEX.