
STATUTORY RULES OF NORTHERN IRELAND

2000 No. 309

ROAD AND RAILWAY TRANSPORT

Level Crossing (Kilmakee) Order (Northern Ireland) 2000

Made - - - - 19th October 2000

Coming into operation 12th November 2000

**LEVEL CROSSING (KILMAKEE)
ORDER (NORTHERN IRELAND) 2000**

1. Citation, commencement and interpretation
 2. Suspension of statutory provisions
 3. Provision of automatic equipment
 4. Revocation
- Signature

SCHEDULE	PARTICULARS OF THE BARRIERS, LIGHTS, TRAFFIC SIGNS AND OTHER DEVICES
1	AND OTHER DEVICES
1.	Cattle-cum-trespass guards of standard railway design shall be provided adjacent...
2.	A barrier shall be pivoted as close to the railway...
3.	It shall be possible to raise and lower the barriers....
4.	When the barriers are fully lowered their uppermost surfaces shall...
5.	When in the fully raised position the barriers shall be...
6.	The barriers shall be as light as possible but shall...
7.	Three electric lamps, or equivalent (light emitting diodes) each of...
8.	The barriers shall display on both front and rear faces...
9.	Suitable screening shall be provided for each barrier machine to...
10.	A traffic light signal of the size, colour and type...
11.	An audible warning device shall be provided on or adjacent...
12.	A reflectorised stop line of the size and type shown...
13.	A reflectorised pedestrian stop line of the size and type...
14.	Where the road passes over the crossing, reflectorised edge of...
15.	A pedestrian traffic light signal of the size, colour and...
16.	A traffic sign of the size, colour and type shown...
17.	A traffic sign of the size, colour and type shown...
18.	A traffic sign of the size, colour and type shown...

Status: This is the original version (as it was originally made). This item of legislation is currently only available in its original format.

19. A traffic sign of the size, colour and type shown...
20. A telephone mounted in a weatherproof box connected to the...
21. Two independent power supplies shall be provided at the crossing,...
22. “the Regulations” means the Traffic Signs Regulations (Northern Ireland) 1997....

SCHEDULE

CONDITIONS AND REQUIREMENTS TO BE COMPLIED WITH BY THE RAILWAY UNDERTAKING

1. The carriageway shall be at least 14.5 metres wide at...
2. The ground at the two edges of the carriageway over...
3. The surface of the carriageway over the crossing shall be...
4. The barriers shall be kept in the fully raised position...
5. The electric lamps or equivalent (light emitting diodes) on each...
6. If the road approaches to the crossing are lit the...
7. Visual indicators and an audible alarm shall be provided in...
8. The barriers, the audible warning devices and the traffic light...
9. When the train either occupies a track circuit or operates...
10. In the event of the failure of both intermittent red...
11. Should a total power failure occur both barriers shall descend...
12. If either barrier fails to rise from the lowered position...
13. When the crossing sequence is initiated as described in paragraph...
Explanatory Note