SCHEDULES

SCHEDULE 1

ACTIVITIES, INSTALLATIONS AND MOBILE PLANT

PART 1 ACTIVITIES CHAPTER 3 MINERAL INDUSTRIES

SECTION 3.1 PRODUCTION OF CEMENT AND LIME

Part A

- (a) Producing cement clinker in rotary kilns with a production capacity exceeding 500 tonnes per day or in other kilns with a production capacity exceeding 50 tonnes per day.
- (b) Producing lime or magnesium oxide in kilns with a production capacity of more than 50 tonnes per day.

Part B

- (a) Blending cement in bulk or using cement in bulk other than at a construction site, including the bagging of cement and cement mixtures, the batching of ready-mixed concrete and the manufacture of concrete blocks and other cement products where the activity is not related to an activity described in paragraph (a) of Part A of this section and is carried on at the same location as an activity described in paragraph (a) of Part B of section 3.5.
- (b) Producing lime where the activity is not likely to involve the heating in any period of 12 months of 5,000 tonnes or more of calcium carbonate or calcium magnesium carbonate or, in aggregate, of both.
- (c) Slaking lime for the purpose of making calcium hydroxide or calcium magnesium hydroxide when related to an activity described in paragraph (b) above.
- (d) Grinding cement clinker not associated with production of cement clinker.
- (e) Unless falling within Part A of section 2.1 or 2.2, grinding metallurgical slag in plant with a grinding capacity of more than 250,000 tonnes in any period of 12 months.

Part C

- (a) Storing, loading or unloading cement or cement clinker in bulk prior to further transportation in bulk.
- (b) Blending cement in bulk or using cement in bulk other than at a construction site, including the bagging of cement and cement mixtures, the batching of ready-mixed concrete and the manufacture of concrete blocks and other cement products where the activity is not related to an activity described in paragraph (a) of Part A of this section and is not described in paragraph (a) of Part B of this section.

(c) Slaking lime for the purpose of making calcium hydroxide or calcium magnesium hydroxide unless related to an activity described in another Part of this Schedule.

SECTION 3.2

ACTIVITIES INVOLVING ASBESTOS

Part A

- (a) Producing asbestos or manufacturing products based on or containing asbestos.
- (b) Stripping asbestos from railway vehicles except—
 - (i) in the course of the repair or maintenance of the vehicle;
 - (ii) in the course of recovery operations following an accident; or
 - (iii) where the asbestos is permanently bonded in cement or in any other material (including plastic, rubber or resin).

Part B

- (a) The industrial finishing of any of the following products where not related to an activity falling within Part A of this section—
 - (i) asbestos cement;
 - (ii) asbestos cement products;
 - (iii) asbestos fillers;
 - (iv) asbestos filters;
 - (v) asbestos floor coverings;
 - (vi) asbestos friction products;
 - (vii) asbestos insulating board;
 - (viii) asbestos jointing, packaging and reinforcement material;
 - (ix) asbestos packing;
 - (x) asbestos paper or card; or
 - (xi) asbestos textiles.

Part C

Nil

Interpretation of section 3.2

1. In this section "asbestos" includes any of the following fibrous silicates: actinolite, amosite, anthophyllite, chrysotile, crocidolite and tremolite.

SECTION 3.3

MANUFACTURING GLASS AND GLASS FIBRE

Part A

(a) Manufacturing glass or glass fibre where the melting capacity of the plant is more than 20 tonnes a day.

Part B

Unless falling within Part A of this section—

Status: This is the original version (as it was originally made).

- (a) Manufacturing glass at any location where the person concerned has the capacity to make 5,000 tonnes or more of glass in any period of 12 months, and any activity involving the use of glass which is carried out at any such location in conjunction with its manufacture.
- (b) Manufacturing glass where the use of lead or any lead compound is involved.
- (c) Manufacturing any glass product where lead or any lead compound has been used in the manufacture of the glass except—
 - (i) making products from lead glass blanks; or
 - (ii) melting, or mixing with another substance, glass manufactured elsewhere to produce articles such as ornaments or road paint.
- (d) Polishing or etching glass or glass products in the course of any manufacturing activity if—
 - (i) hydrofluoric acid is used; or
 - (ii) hydrogen fluoride may be released into the air.
- (e) Manufacturing glass frit or enamel frit and its use in any activity where that activity is related to its manufacture.

Part C

Nil

SECTION 3.4

PRODUCTION OF OTHER MINERAL FIBRES

Part A

(a) Unless falling within Part A of section 3.3, melting mineral substances including the production of mineral fibres with a melting capacity exceeding 20 tonnes per day.

Part B

Nil.

Part C

Nil.

SECTION 3.5

OTHER MINERAL ACTIVITIES

Part A

(a) Manufacturing cellulose fibre reinforced calcium silicate board using unbleached pulp.

Part B

- (a) Unless falling within Part A of any section in this Schedule, the crushing, grinding or other size reduction, other than the cutting of stone, or the grading, screening or heating of any designated mineral or mineral product except where the operation of the activity is unlikely to result in the release into the air of particulate matter.
- (b) Coating road stone with tar or bitumen.
- (c) The fusion of calcined bauxite for the production of artificial corundum.

Part C

- (a) Any of the following activities unless carried on at an exempt location—
 - (i) crushing, grinding or otherwise breaking up coal, coke or any other coal product;
 - (ii) screening, grading or mixing coal, coke or any other coal product;

- (iii) loading or unloading petroleum coke, coal, coke or any other coal product except unloading on retail sale.
- (b) The crushing, grinding or other size reduction, with machinery designed for that purpose, of bricks, tiles or concrete.
- (c) Screening the product of any activity described in paragraph (b).
- (d) Loading, unloading or storing pulverised fuel ash in bulk prior to further transportation in bulk.

Interpretation of Parts B and C

1. In Parts B and C—

"coal" includes lignite;

"designated mineral or mineral product" means—

- (i) clay, sand and any other naturally occurring mineral other than coal or lignite;
- (ii) metallurgical slag;
- (iii) boiler or furnace ash produced from the burning of coal, coke or any other coal product;
- (iv) gypsum which is a by-product of any activity;

"exempt location" means—

- (i) any premises used for the sale of petroleum coke, coal, coke or any coal product where the throughput of such substances at those premises in any period of 12 months is in aggregate likely to be less than 10,000 tonnes; or
- (ii) any premises to which petroleum coke, coal, coke or any coal product is supplied only for use there;

"retail sale" means sale to the final customer.

2. Nothing in this Part applies to any activity carried out underground.

SECTION 3.6 CERAMIC PRODUCTION

Part A

- (a) Manufacturing ceramic products (including roofing tiles, bricks, refractory bricks, tiles, stoneware or porcelain) by firing in kilns, where—
 - (i) the kiln production capacity is more than 75 tonnes per day; or
 - (ii) the kiln capacity is more than 4m³ and the setting density is more than 300 kg/m³.

Part B

- (a) Unless falling within Part A of this section, firing heavy clay goods or refractory materials (other than heavy clay goods) in a kiln where a reducing atmosphere is essential or with a production capacity exceeding 50 tonnes per day.
- (b) Vapour glazing earthenware or clay with salts.

Part C

(a) Unless falling within Part A or Part B of this section, firing heavy clay goods or refractory materials (other than heavy clay goods) in a kiln.

Interpretation of Parts B and C

1. In these Parts—

Status: This is the original version (as it was originally made).

"clay" includes a blend of clay with ash, sand or other materials;

"refractory material" means material (such as fireclay, silica, magnesite, chrome-magnesite, sillimanite, sintered alumina, beryllia and boron nitride) which is able to withstand high temperatures and to function as a furnace lining or in other similar high temperature applications.