STATUTORY RULES OF NORTHERN IRELAND

2013 No. 205

CLEAN AIR

The Smoke Control Areas (Authorised Fuels) Regulations (Northern Ireland) 2013

Made - - - - 31st July 2013

Coming into operation 31st August 2013

The Department of the Environment makes the following Regulations in exercise of the powers conferred by Article 2(2) of the Clean Air (Northern Ireland) Order 1981(1).

In accordance with that Article, the Department of the Environment has had regard, amongst other things, to the sulphur content of the fuels described in regulation 2.

Citation and commencement N.I.

1. These Regulations may be cited as the Smoke Control Areas (Authorised Fuels) Regulations (Northern Ireland) 2013 and shall come into operation on 31st August 2013.

Commencement Information

II Reg. 1 in operation at 31.8.2013, see reg. 1

Authorised fuels N.I.

- **2.** For the purposes of Article 2(2) of the Clean Air (Northern Ireland) Order 1981, the following are authorised fuels—
 - (a) anthracite;
 - (b) semi-anthracite;
 - (c) electricity;
 - (d) gas;
 - (e) low volatile steam coals; and
 - (f) the fuels described in the Schedule.

Commencement Information

I2 Reg. 2 in operation at 31.8.2013, see **reg. 1**

Revocations and savings N.I.

- **3.**—(1) The Smoke Control Areas (Authorised Fuels) Regulations (Northern Ireland) 2012(2) are revoked.
- (2) Any fuel manufactured before the coming into operation of these Regulations which was an authorised fuel continues to be an authorised fuel, notwithstanding the revocation of the Regulations specified in paragraph (1).

Commencement Information

I3 Reg. 3 in operation at 31.8.2013, see **reg. 1**

Sealed with the Official Seal of the Department of the Environment on 31st July 2013.



Wesley Shannon
A senior officer of the
Department of the Environment

SCHEDULE N.I.

Regulation 2

Authorised fuels

- 1. Aimcor Excel briquettes, manufactured by Applied Industrial Materials UK Limited at Newfield, County Durham, or manufactured by Oxbow Carbon & Minerals UK Limited, Windsor House, Cornwall Road, Harrogate, North Yorkshire, which—
 - (a) comprise petroleum coke (as to 60 to 75% of the total weight), low volatile coal and reactive coke (as to 20 to 25% of the total weight) and cold-setting resin binder (as to the remaining weight);
 - (b) were manufactured from those constituents by a process involving roll-pressing;
 - (c) are unmarked pillow-shaped briquettes;
 - (d) have an average weight of 73g per briquette; and
 - (e) have a sulphur content not exceeding 2% of the total weight.

Commencement Information

I4 Sch. para. 1 in operation at 31.8.2013, see reg. 1

- 2. Aimcor Pureheat briquettes, manufactured by Applied Industrial Materials UK Limited at Immingham, North East Lincolnshire, or manufactured by Oxbow Carbon & Minerals UK Limited, Windsor House, Cornwall Road, Harrogate, North Yorkshire, which—
 - (a) comprise anthracite (as to approximately 60% of the total weight), petroleum coke (as to approximately 25% of the total weight), and binder (as to the remaining weight);
 - (b) were manufactured from those constituents by a process involving roll-pressing and heat treatment at about 250°C;
 - (c) are pillow-shaped briquettes with a single line indentation on one side and a double line indentation on the reverse side;
 - (d) have an average weight of 75g per briquette; and
 - (e) have a sulphur content not exceeding 2% of the total weight.

Commencement Information

I5 Sch. para. 2 in operation at 31.8.2013, see reg. 1

- 3. Ancit briquettes, manufactured by Coal Products Limited at Immingham Briquetting Works, Immingham, North East Lincolnshire, which—
 - (a) comprise anthracite (as to approximately 60 to 95% of the total weight), petroleum coke (up to approximately 30% of the total weight), bituminous coal (up to approximately 15% of the total weight), and a molasses and phosphoric acid binder or an organic binder (as to the remaining weight);
 - (b) were manufactured from those constituents by a process involving roll-pressing and heat treatment at about 300°C;
 - (c) are unmarked cushion-shaped briquettes;
 - (d) have an average weight of 48g per briquette; and
 - (e) have a sulphur content not exceeding 2% of the total weight.

Commencement Information

I6 Sch. para. 3 in operation at 31.8.2013, see reg. 1

- 4. Big K Instant Lighting Fire Logs, manufactured by Allspan B.V. at Macroweg 4, 5804 CL Venray, the Netherlands, which—
 - (a) comprise slack wax (as to approximately 58 to 59% of the total weight) and hardwood sawdust (as to approximately 41 to 42% of the total weight);
 - (b) were manufactured from those constituents by a process of heat treatment and extrusion;
 - (c) are firelogs approximately 235mm in length and 80mm in depth, with grooves along their faces;
 - (d) have an average weight of 1.1kg per firelog; and
 - (e) have a sulphur content not exceeding 0.1% of the total weight.

Commencement Information

I7 Sch. para. 4 in operation at 31.8.2013, see reg. 1

- 5. Big K Restaurant Grade Charcoal, manufactured by Big K Products UK Limited at Parque Industrial Alvear, 2126 Alvear, Provincia de Santa Fe, Argentina, which—
 - (a) comprise pyrolised white quebracho wood;
 - (b) were manufactured using a kiln pyrolysis process at approximately 450°C;
 - (c) are unmarked charcoal pieces of between 30mm and 150mm; and
 - (d) have a sulphur content not exceeding 2% of the total weight.

Commencement Information

I8 Sch. para. 5 in operation at 31.8.2013, see **reg. 1**

- 6. Black Diamond Gem briquettes, manufactured by Coal Products Limited at Immingham Briquetting Works, Immingham, North East Lincolnshire, which—
 - (a) comprise anthracite duff (as to 20 to 30% of the total weight), petroleum coke (as to 40 to 45% of the total weight), bituminous coal (as to 12 to 22% of the total weight), and molasses and phosphoric acid binder (as to the remaining weight);
 - (b) were manufactured from those constituents by a process involving roll-pressing and heat treatment at about 300°C;
 - (c) are pillow-shaped briquettes marked with two parallel indented lines running latitudinally around the briquette;
 - (d) have an average weight of 160g per briquette; and
 - (e) have a sulphur content not exceeding 1.5% of the total weight.

Commencement Information

I9 Sch. para. 6 in operation at 31.8.2013, see reg. 1

Changes to legislation: The Smoke Control Areas (Authorised Fuels) Regulations (Northern Ireland) 2013 is up to date with all changes known to be in force on or before 30 August 2023. There are changes that may be brought into force at a future date. Changes that have been made appear in the content and are referenced with annotations. (See end of Document for details) View outstanding changes

- 7. Bord na Móna Firelogs, manufactured by Bord na Móna Fuels Limited, Newbridge, County Kildare, Republic of Ireland, which—
 - (a) comprise slack wax (as to approximately 55% of the total weight), and hardwood sawdust (as to approximately 45% of the total weight);
 - (b) were manufactured from those constituents by a process of heat treatment and extrusion;
 - (c) are firelogs approximately 255mm in length and 75mm in diameter, with grooves along one longitudinal face;
 - (d) have an average weight of 1.3kg per firelog; and
 - (e) have a sulphur content not exceeding 0.1% of the total weight.

Commencement Information

I10 Sch. para. 7 in operation at 31.8.2013, see reg. 1

- 8. Bord na Móna Firepak (also marketed as Arigna Special coal briquettes), manufactured by Bord na Móna Fuels Limited, Newbridge, County Kildare, Republic of Ireland, which—
 - (a) comprise anthracite (as to approximately 50% of the total weight), petroleum coke (as to approximately 20 to 40% of the total weight), bituminous coal (as to approximately 10 to 30% of the total weight), and starch based binder (as to the remaining weight);
 - (b) were manufactured from those constituents by a process involving roll-pressing and heat treatment;
 - (c) are unmarked pillow-shaped briquettes;
 - (d) have an average weight of 50g per briquette;
 - (e) have a sulphur content not exceeding 1.5% of the total weight.

Commencement Information

III Sch. para. 8 in operation at 31.8.2013, see reg. 1

[F18A. Brazier briquettes, manufactured by Coal Products Limited at Immingham Briquetting Works, Immingham, North East Lincolnshire, which—

- (a) comprise anthracite (as to approximately 60 to 80 % of the total weight), petroleum coke (as to approximately 10 to 30% of the total weight), and a molasses and phosphoric acid binder (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving roll-pressing and heat treatment at about 300°C;
- (c) are either unmarked pillow-shaped briquettes, or pillow-shaped briquettes marked with a single indented line running longitudinally along each face, off-set from its counterpart by 10mm;
- (d) have an average weight of either 55g or 80g per briquette; and
- (e) have a sulphur content not exceeding 2% of the total weight on a dry basis.]
- F1 Sch. para. 8A inserted (3.11.2014) by The Smoke Control Areas (Authorised Fuels) (Amendment) Regulations (Northern Ireland) 2014 (S.R. 2014/249), regs. 1, 3(a)
- 9. Briteflame briquettes, manufactured by Maxibrite Limited, Mwyndy Industrial Estate, Llantrisant, Mid Glamorgan, which—

- (a) comprise 10 to 15% bituminous coal, 10 to 15% petroleum coke, 70 to 80% anthracite duff and starch binder (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving roll-pressing and heat treatment at about 260°C;
- (c) are unmarked pillow-shaped briquettes;
- (d) have an average weight of 140g per briquette; and
- (e) have a sulphur content not exceeding 1.9% sulphur on a dry basis.

Commencement Information

I12 Sch. para. 9 in operation at 31.8.2013, see reg. 1

- 10. Briteheat briquettes (otherwise known as Stoveheat Premium briquettes), manufactured by Coal Products Limited at Immingham Briquetting Works, North East Lincolnshire, which—
 - (a) comprise anthracite (as to approximately 60 to 85% of the total weight), petroleum coke (up to approximately 30% of the total weight), bituminous coal (up to approximately 15% of the total weight), and a molasses and phosphoric acid binder (as to the remaining weight);
 - (b) were manufactured from those constituents by a process involving roll-pressing and heat treatment at about 300°C;
 - (c) are cushion-shaped briquettes with an indented line running longitudinally around the briquette;
 - (d) have a average weight of 30g per briquette; and
 - (e) have a sulphur content not exceeding 2% of the total weight.

Commencement Information

I13 Sch. para. 10 in operation at 31.8.2013, see reg. 1

- 11. Briteheat Plus briquettes, manufactured by Coal Products Limited at Immingham Briquetting Works, Immingham, North East Lincolnshire, which—
 - (a) comprise anthracite duff (as to approximately 75 to 95% of the total weight), petroleum coke (up to approximately 20% of the total weight), and a organic binder (as to the remaining weight);
 - (b) were manufactured from those constituents by a process involving roll-pressing;
 - (c) are unmarked pillow-shaped briquettes;
 - (d) have an average weight of 80g per briquette; and
 - (e) have a sulphur content not exceeding 2% of the total weight.

Commencement Information

I14 Sch. para. 11 in operation at 31.8.2013, see reg. 1

- 12. Bryant and May Firelogs, manufactured by Swedish Match at Kostenetz, Bulgaria, which-
 - (a) comprise paraffin wax (as to approximately 50% of the total weight), ground poplar wood (as to approximately 25% of the total weight), wheatflour (as to approximately 15% of the

Changes to legislation: The Smoke Control Areas (Authorised Fuels) Regulations (Northern Ireland) 2013 is up to date with all changes known to be in force on or before 30 August 2023. There are changes that may be brought into force at a future date. Changes that have been made appear in the content and are referenced with annotations. (See end of Document for details) View outstanding changes

total weight), ignitable solids dispersed in gelled paraffin wax (as to approximately 1% of the total weight) and water, swelling agents and preservative (as to the remaining weight);

- (b) were manufactured from those constituents by a process involving extrusion;
- (c) have a quadrant shaped cross section with a radius of approximately 80mm, a length of approximately 265mm, and an ignition strip across one edge;
- (d) have an approximate weight of 1.15kg per firelog; and
- (e) have a sulphur content not exceeding 0.1% of the total weight.

Commencement Information

I15 Sch. para. 12 in operation at 31.8.2013, see reg. 1

- 13. Charglow briquettes, manufactured by Polchar Spolka z ograniczona odpowiedzialnościa, Ulica Kuznicka 1, Police, Zachodniepomorskie, Poland, which—
 - (a) comprise bituminous coal char (as to approximately 45 to 95% of the total weight), anthracite (as to approximately 0 to 20% of the total weight), petroleum coke (as to approximately 0 to 20% of the total weight), bituminous coal (as to approximately 0 to 10% of the total weight) and an organic binder (as to the remaining weight);
 - (b) were manufactured from those constituents by a process involving roll-pressing and heat treatment at about 110°C;
 - (c) are unmarked pillow-shaped briquettes;
 - (d) have an average weight of 100g per briquette; and
 - (e) have a sulphur content not exceeding 1.5% of the total weight.

Commencement Information

I16 Sch. para. 13 in operation at 31.8.2013, see reg. 1

14. Coalite manufactured by Coalite Products Limited at Bolsover, near Chesterfield, Derbyshire, and at Grimethorpe, South Yorkshire, using a low temperature carbonisation process.

Commencement Information

II7 Sch. para. 14 in operation at 31.8.2013, see reg. 1

- 15. Coalite Ovals Briquettes manufactured by Maxibrite Ltd, at Mwyndy Industrial Estate, Llantrisant, Mid Glamorgan, which—
 - (a) comprise 10-15% bituminous coal, 10-15% petroleum coke, 70-80% anthracite duff, and starch binder (as to the remaining weight);
 - (b) were manufactured from those constituents by a process involving roll-pressing and heat treatment at about 260°C;
 - (c) are unmarked pillow-shaped briquettes with approximate dimensions 84.2mm, 61.5mm, and 37.8mm;
 - (d) have an average weight of 118g per briquette; and
 - (e) have a sulphur content not exceeding 1.9% sulphur on a dry basis.

Commencement Information

I18 Sch. para. 15 in operation at 31.8.2013, see reg. 1

- 16. Coke manufactured by—
 - (a) Coal Products Limited at Cwm Coking Works, Llantwit Fardre, Pontypridd, Rhondda Cynon Taff, and sold as "Sunbrite";
 - (b) Monckton Coke & Chemical Company Limited at Royston, near Barnsley, South Yorkshire, and sold as "Sunbrite" or "Monckton Boiler Beans";
 - (c) Corus UK Limited at Teesside Works, Redcar, and sold as "Redcar Coke Nuts (Doubles)"; and
 - (d) Coal Products Limited at Cwm Coking Works, Llantwit Fardre, Pontypridd, Rhondda Cynon Taff, and sold as "Cwm Coke Doubles".

Commencement Information

I19 Sch. para. 16 in operation at 31.8.2013, see reg. 1

- 17. Cosycoke (also marketed as Lionheart Crusader or Sunbrite Plus), manufactured by Monckton Coke & Chemical Company Limited at Royston, near Barnsley, South Yorkshire, and Aimcor Supercoke (also marketed as Supercoke), manufactured by M & G Fuels Limited at Hartlepool Docks, Hartlepool, which in each case—
 - (a) comprise sized hard coke (as to approximately 45 to 65% of the total weight) and sized petroleum coke (as to the remaining weight);
 - (b) were manufactured from those constituents by blending;
 - (c) are unmarked random shapes; and
 - (d) have a sulphur content not exceeding 2% of the total weight.

Commencement Information

I20 Sch. para. 17 in operation at 31.8.2013, see reg. 1

- [F217A. Direct Charcoal Blue Bag Premium Grade Restaurant Charcoal manufactured by Direct Charcoal at Ekamanzi Road, Dalton, KwaZulu Natal, Republic of South Africa, which—
 - (a) comprises pyrolised Acacia Mercii wood;
 - (b) was manufactured using a kiln pyrolysis process at approximately 420 to 480°C;
 - (c) are unmarked charcoal pieces of between 30mm to 150mm; and
 - (d) has a sulphur content not exceeding 2 per cent of the total weight.
 - F2 Sch. paras. 17A, 17B inserted (3.11.2014) by The Smoke Control Areas (Authorised Fuels) (Amendment) Regulations (Northern Ireland) 2014 (S.R. 2014/249), regs. 1, **3(b)**
- 17B. Direct Charcoal Blue Bag Restaurant Charcoal manufactured by Direct Charcoal Limited at Ruta 25, km. 9,5 Pilar (cp. 1629) Buenos Aires, Argentina, which—
 - (a) comprises pyrolised white Quebracho and Guayacan wood;
 - (b) was manufactured using a kiln pyrolysis process at approximately 420 to 480°C;

Changes to legislation: The Smoke Control Areas (Authorised Fuels) Regulations (Northern Ireland) 2013 is up to date with all changes known to be in force on or before 30 August 2023. There are changes that may be brought into force at a future date. Changes that have been made appear in the content and are referenced with annotations. (See end of Document for details) View outstanding changes

- (c) are unmarked charcoal pieces of between 30mm to 150mm; and
- (d) has a sulphur content not exceeding 2 per cent of the total weight.]
- F2 Sch. paras. 17A, 17B inserted (3.11.2014) by The Smoke Control Areas (Authorised Fuels) (Amendment) Regulations (Northern Ireland) 2014 (S.R. 2014/249), regs. 1, 3(b)
- [F317C. CPL Restaurant Grade Charcoal manufactured by Kunfayakun Global Treasures Limited (KGT) at Kunfayakun Stores, No. 1, Aranse Street, Station, Sagamu, Orgub State E17, Shagamu International Market, Nigeria, which—
 - (a) comprises pyrolised Anogeissus Leiocarpus, Burkea Africana, Distemonanthus Benthamianus and Viteloria Paracloxum;
 - (b) was manufactured using a kiln pyrolysis process at approximately 450°C to 550°C;
 - (c) are unmarked charcoal pieces of between 50mm and 180mm; and
 - (d) have a sulphur content not exceeding 1.9% of the total weight on a dry basis.]
 - F3 Sch. para. 17C inserted (10.12.2015) by The Smoke Control Areas (Authorised Fuels) (Amendment) Regulations (Northern Ireland) 2015 (S.R. 2015/367), regs. 1, 2(2)
- 18. Dragonglow briquettes, manufactured by Tower Colliery Limited at Aberdare, Mid Glamorgan, South Wales, which—
 - (a) comprise tower duff (as to approximately 95% of the total weight) and a resin based binder (as to the remaining weight);
 - (b) were manufactured from those constituents by a process involving cold cure roll pressing;
 - (c) are unmarked pillow-shaped briquettes;
 - (d) have an average weight of 100g per briquette; and
 - (e) have a sulphur content not exceeding 1% of the total weight.

Commencement Information

- **I21** Sch. para. 18 in operation at 31.8.2013, see reg. 1
- 19. Dragonbrite briquettes, manufactured by Tower Colliery Limited at Aberdare, Mid Glamorgan, South Wales, which—
 - (a) comprise tower duff (as to approximately 95% of the total weight) and a resin based binder (as to the remaining weight);
 - (b) were manufactured from those constituents by a process involving cold cure roll pressing;
 - (c) are pillow-shaped briquettes marked with the letter "T" on one side;
 - (d) have an average weight of 50g per briquette; and
 - (e) have a sulphur content not exceeding 1% of the total weight.

Commencement Information

- I22 Sch. para. 19 in operation at 31.8.2013, see reg. 1
- 20. Duraflame Firelogs, manufactured by Paramelt B.V., Costerstraat 18, PO Box 86, 1700 AB Heerhugowaard, the Netherlands, which—

- (a) comprise mineral-based petroleum wax (as to approximately 55% of the total weight), and ground hardwood fibre (as to approximately 45% of the total weight);
- (b) were manufactured from those constituents by a process of heat treatment and extrusion;
- (c) are firelogs approximately 320mm in length, 90mm high, and 85 mm wide;
- (d) have an average weight of 1.45kg per firelog; and
- (e) have a sulphur content not exceeding 0.1% of the total weight.

Commencement Information

I23 Sch. para. 20 in operation at 31.8.2013, see reg. 1

- [^{F4}21. Ecoal briquettes (also marketed as Homefire Ecoal briquettes and Supertherm 30), manufactured by Coal Products Limited at Immingham Briquetting Works, Immingham, North East Lincolnshire, which—
 - (a) comprise anthracite fines (as to approximately 40 to 65% of the total weight), petroleum coke (as to approximately 20 to 40% of the total weight), bituminous coal (as to approximately 0 to 20% of the total weight), biomass (as to approximately 5 to 20% of the total weight), biomass char (as to approximately 0 to 10% of the total weight) and molasses and phosphoric acid as binder (as to a maximum of 20% of the total weight);
 - (b) were manufactured from those constituents by a process involving roll-pressing and heat treatment at approximately 300°C;
 - (c) are unmarked pillow shaped briquettes that are typically 72mm in length, 58mm in width and 42mm in height or are unmarked hexagonal briquettes that are typically 70mm in length, 73mm in width and 39 mm in height;
 - (d) have an average weight of 125g per briquette; and
 - (e) have a sulphur content not exceeding 2% of the total weight.]
 - F4 Sch. para. 21 substituted (10.12.2015) by The Smoke Control Areas (Authorised Fuels) (Amendment) Regulations (Northern Ireland) 2015 (S.R. 2015/367), regs. 1, 2(3)
- 22. Ecoal 50 briquettes, manufactured by Coal Products Limited at Immingham Briquetting Works, Immingham, North East Lincolnshire, which—
 - (a) comprise anthracite fines (as to approximately 30 to 55% of the total weight), biomass (as to approximately 25 to 35% of the total weight), petroleum coke (as to approximately 10 to 40% of the total weight), bituminous coal (as to approximately 0 to 5% of the total weight), and natural organic binder (as to the remaining weight);
 - (b) were manufactured from those constituents by a process involving roll pressing, followed by heat treatment at a temperature of approximately 300°C in a controlled, reduced oxygen environment;
 - (c) are hexagonal-shaped briquettes with a single stripe on one side across the flats;
 - (d) have an average weight of 135g per briquette; and
 - (e) have a sulphur content not exceeding 2% of the total weight.

Commencement Information

I24 Sch. para. 22 in operation at 31.8.2013, see reg. 1

- 23. Ecobrite briquettes, manufactured by Arigna Fuels Limited at Arigna, Carrick-on-Shannon, County Roscommon, Republic of Ireland, which—
 - (a) comprise anthracite fines (as to approximately 96% of the total weight) and starch as binder (as to the remaining weight);
 - (b) were manufactured from those constituents by a process involving roll-pressing and heat treatment at 250°C;
 - (c) are unmarked pillow-shaped briquettes in two sizes;
 - (d) have an average weight per briquette of 37g in the case of the smaller size and 48g in the case of the larger size; and
 - (e) have a sulphur content not exceeding 1.5% of the total weight.

Commencement Information

I25 Sch. para. 23 in operation at 31.8.2013, see reg. 1

- 24. EDF Fuel briquettes, manufactured by TheGreenFactory at the Laboratoire de Chimie Agroindustrielle, UMR 1010 INRA/INP-ENSIACET AGROMAT, Site de l'ENIT 47, Avenue d'Azereix, BP 1629 65016 Tarbes Cedex, France, which—
 - (a) comprise approximately 100g of unprocessed Miscanthus (as to approximately 45% of the total weight), approximately 95g of Copra ester (as to approximately 43% of the total weight), and approximately 25g of a binder produced from Miscanthus (processed with calcium oxide as to approximately 0.5% of the total weight) as to the remaining weight;
 - (b) are manufactured from those constituents by a process involving Miscanthus processing, mixing, hot pressing and soaking in an ester bath;
 - (c) are unmarked cylinder-shaped briquettes of 120mm height and 60mm diameter with a star-shaped hole running centrally through the longer length of the briquette;
 - (d) have an average weight of 220g per briquette; and
 - (e) have a sulphur content not exceeding 2% of the total weight.

Commencement Information

I26 Sch. para. 24 in operation at 31.8.2013, see reg. 1

- 25. Excel + briquettes, manufactured for Oxbow Coal B.V. at Newfield Works, Bishop Auckland, County Durham, which—
 - (a) comprise of 65 70% of petroleum coke and 25% anthracite (both by weight), together with a cold setting resin binder, hardener, and low temperature stabiliser as the remaining weight;
 - (b) are produced at ambient temperature by a process involving roll-pressing, the briquettes are 'cold cured';
 - (c) are unmarked pillow shaped briquettes, square in appearance;
 - (d) weigh circa 100 grams +/- 5%; and
 - (e) have a sulphur content not exceeding 1.9% of the total weight.

Commencement Information

I27 Sch. para. 25 in operation at 31.8.2013, see reg. 1

- 26. Extracite briquettes, manufactured by Sophia-Jacoba Handelsgesellschaft mbH at Hückelhoven, Germany, which—
 - (a) comprise anthracite duff (as to approximately 95.5% of the total weight) and ammonium lignosulphonate lye as binder (as to the remaining weight);
 - (b) were manufactured from those constituents by a process involving roll-pressing and heat treatment at about 260°C;
 - (c) are cushion-shaped briquettes with a silvery appearance and are marked with the letters "S" and "J";
 - (d) have an average weight of 40g per briquette; and
 - (e) have a sulphur content of approximately 1.2% of the total weight.

Commencement Information

I28 Sch. para. 26 in operation at 31.8.2013, see reg. 1

- 27. Fireglo briquettes, manufactured by Les Combustibles de Normandie at Caen, France, and by la Société Rouennaise de Defumage at Rouen, France, which—
 - (a) comprise washed Welsh duffs (as to approximately 92% of the total weight) and coal pitch binder (as to the remaining weight);
 - (b) were manufactured from those constituents by a process involving roll-pressing and heat treatment at about 330°C;
 - (c) are ovoids which have three lines on one side and are smooth on the other side;
 - (d) have an average weight of 30g per briquette; and
 - (e) have a sulphur content not exceeding 0.8% of the total weight.

Commencement Information

I29 Sch. para. 27 in operation at 31.8.2013, see reg. 1

- [F527A. G N Grosvenor (Fuel Express) Restaurant Charcoal manufactured by Pabensa S.A. Aviadores del Chaco Asunción Paraguay which—
 - (a) comprises pyrolised Prosopis Nigra, Cordia Alliodora, Centrolobium, Prosopis kuntzei, Caesalpinia, Gonçalo alves and Tabebuia hardwoods;
 - (b) was manufactured using a kiln pyrolysis process at approximately 800°C;
 - (c) are unmarked charcoal pieces of between 20mm and 120mm; and
 - (d) has a sulphur content not exceeding 2% of the total weight on a dry basis.]
 - F5 Sch. para. 27A inserted (3.11.2014) by The Smoke Control Areas (Authorised Fuels) (Amendment) Regulations (Northern Ireland) 2014 (S.R. 2014/249), regs. 1, 3(c)
- [^{F6}27B. Firegold briquettes, manufactured by Coal Products Limited at Immingham Briquetting Works, Immingham, North East Lincolnshire, which—

Changes to legislation: The Smoke Control Areas (Authorised Fuels) Regulations (Northern Ireland) 2013 is up to date with all changes known to be in force on or before 30 August 2023. There are changes that may be brought into force at a future date. Changes that have been made appear in the content and are referenced with annotations. (See end of Document for details) View outstanding changes

- (a) comprise anthracite (as to approximately 36 to 51% of the total weight), petroleum coke (as to approximately 40 to 55% of the total weight) and an organic binder or a molasses and phosphoric acid binder (as to a maximum of 20% of the total weight);
- (b) were manufactured from those constituents by a process involving roll-pressing;
- (c) are unmarked pillow shaped briquettes that are typically 54mm in length, 58mm in width and 34mm in height;
- (d) have an average weight of 87g per briquette; and
- (e) have a sulphur content not exceeding 2% of the total weight on a dry basis.]
- F6 Sch. para. 27B inserted (10.12.2015) by The Smoke Control Areas (Authorised Fuels) (Amendment) Regulations (Northern Ireland) 2015 (S.R. 2015/367), regs. 1, 2(4)
- 28. Homefire briquettes, manufactured by Coal Products Limited at Immingham Briquetting Works, Immingham, North East Lincolnshire, which—
 - (a) comprise anthracite fines (as to approximately 40 to 70% of the total weight), petroleum coke (as to approximately 20 to 45% of the total weight), char (as to approximately 0 to 10% of the total weight), bituminous coal (as to approximately 5 to 30% of the total weight), and an organic binder or a molasses and phosphoric acid binder (as to the remaining weight);
 - (b) were manufactured from those constituents by a process involving roll-pressing;
 - (c) have a volatile matter content in the finished briquette of neither less than 9 nor more than 15% of the total weight on a dry basis;
 - (d) are unmarked hexagonal briquettes;
 - (e) have an average weight of 140g per briquette; and
 - (f) have a sulphur content not exceeding 2% of the total weight.

Commencement Information

I30 Sch. para. 28 in operation at 31.8.2013, see **reg. 1**

- 29. Homefire Fire Logs, manufactured by De Lange B.V., Rustenburgerweg 3, 1646 WJ Ursem, the Netherlands, which—
 - (a) comprise slack wax (as to approximately 50% of the total weight) and sawdust (as to approximately 50% of the total weight);
 - (b) were manufactured from those constituents by a process of heat treatment and extrusion;
 - (c) are firelogs approximately 280mm in length and 75mm x 75mm with a groove running along each of the four 280mm faces;
 - (d) have an average weight of 1.1kg per firelog; and
 - (e) have a sulphur content not exceeding 0.2% of the total weight.

Commencement Information

I31 Sch. para. 29 in operation at 31.8.2013, see reg. 1

30. Homefire ovals, manufactured by Coal Products Limited at Immingham Briquetting Works, Immingham, North East Lincolnshire, which—

- (a) comprise anthracite duff (as to approximately 57% of the total weight), petroleum coke (as to approximately 17% of the total weight), bituminous coal (as to approximately 13% of the total weight), and molasses and phosphoric acid as binder (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving roll-pressing and heat treatment at about 300°C;
- (c) are pillow-shaped briquettes with two parallel indented lines running latitudinally around the briquette;
- (d) have an average weight of 135g per briquette; and
- (e) have a sulphur content not exceeding 2% of the total weight.

Commencement Information

I32 Sch. para. 30 in operation at 31.8.2013, see reg. 1

- 31. Homefire Ovals (R), manufactured by Coal Products Limited at Immingham Briquetting Works, Immingham, North East Lincolnshire, which—
 - (a) comprise anthracite fines (as to approximately 50 to 75% of the total weight), petroleum coke (as to approximately 20 to 45% of the total weight), bituminous coal (as to approximately 5 to 17% of the total weight), and an organic binder (as to the remaining weight);
 - (b) were manufactured from those constituents by a process involving roll-pressing;
 - (c) are pillow-shaped briquettes with two parallel indented lines running latitudinally around the briquette;
 - (d) have an average weight of 130g per briquette; and
 - (e) have a sulphur content not exceeding 2% of the total weight.

Commencement Information

I33 Sch. para. 31 in operation at 31.8.2013, see reg. 1

- 32. Hot Drops, manufactured by EU Zeme Limited at Riga, Eksporta Street 15, LV-1045, which—
 - (a) comprise crushed anthracite (as to approximately 73% of the total weight), bituminous coal (as to approximately 18% of the total weight), and a molasses and orthophosphoric acid binder (as to the remaining weight);
 - (b) were manufactured from those constituents by a process involving roll pressing followed by heat treatment at a temperature of approximately 250-280°C;
 - (c) are almost round pillow-shaped briquettes that are 40mm in diameter and about 21mm thick at the centre of the briquette;
 - (d) have an average weight of 23g per briquette; and
 - (e) have a sulphur content not exceeding 0.5% of the total weight.

Commencement Information

I34 Sch. para. 32 in operation at 31.8.2013, see reg. 1

- [^{F7}32A. HouseFuel Smokeless Ovals, manufactured by Maxibrite Limited at Llantrisant, Rhondda Cynon Taf, which—
 - (a) comprise anthracite fines (as to approximately 84% of the total weight), petroleum coke (as to approximately 12% of the total weight) and starch as binder (as to the remaining weight);
 - (b) were manufactured from those constituents by a process involving roll-pressing and heat treatment at about 260°C;
 - (c) are unmarked pillow-shaped briquettes;
 - (d) have an average weight of 78g per briquette; and
 - (e) have a sulphur content not exceeding 2% of the total weight.
 - F7 Sch. paras. 32A, 32B inserted (3.11.2014) by The Smoke Control Areas (Authorised Fuels) (Amendment) Regulations (Northern Ireland) 2014 (S.R. 2014/249), regs. 1, **3(d)**
- 32B. HouseFuel Smokeless Ovals, manufactured by Maxibrite Limited at Mwyndy Industrial Estate, Llantrisant, Mid Glamorgan, which—
 - (a) comprise bituminous coal and petroleum coke (each as to approximately 10 to 15% of the total weight) and anthracite duff and starch binder (as to the remaining weight);
 - (b) were manufactured from those constituents by a process involving a roll-pressing and heat treatment at about 260°C;
 - (c) are unmarked pillow-shaped briquettes with approximate maximum dimensions of 68mm x 63mm x 38mm;
 - (d) have an average weight of 110g per briquette; and
 - (e) have a sulphur content not exceeding 1.9% on a dry basis.]
 - F7 Sch. paras. 32A, 32B inserted (3.11.2014) by The Smoke Control Areas (Authorised Fuels) (Amendment) Regulations (Northern Ireland) 2014 (S.R. 2014/249), regs. 1, **3(d)**
- 33. Island Lump and Island Nuts, manufactured by Unocal Refinery, California, the United States of America, which—
 - (a) comprise petroleum coke;
 - (b) were manufactured from the petroleum coke by a process involving heat treatment and steam injection;
 - (c) are unmarked random shapes;
 - (d) have an average weight of 80g (per briquette of Island Lump) or 30g (per briquette of Island Nuts); and
 - (e) have a sulphur content not exceeding 2% of the total weight.

Commencement Information

I35 Sch. para. 33 in operation at 31.8.2013, see reg. 1

34. Jewel briquettes, manufactured by Eldon Colliery Limited at Newfield Works, Bishop Auckland, County Durham, which—

- (a) comprise anthracite (as to approximately 30 to 50% of the total weight), Long Beach petroleum coke (as to approximately 50 to 70% of the total weight), and a carbohydrate binder (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving roll-pressing and heat treatment at about 150°C;
- (c) are unmarked pillow-shaped briquettes;
- (d) have an average weight of 33g per briquette; and
- (e) have a sulphur content not exceeding 1.5% of the total weight.

Commencement Information

I36 Sch. para. 34 in operation at 31.8.2013, see reg. 1

35. La Hacienda Easy Logs, manufactured by Allspan B.V. at Macroweg 4, 5804 CL Venray, the Netherlands, which meet the conditions specified for Big K Instant Lighting Fire Logs at paragraph 4.

Commencement Information

I37 Sch. para. 35 in operation at 31.8.2013, see reg. 1

- 36. Long Beach Lump nuts (otherwise known as LBL nuts), manufactured by Aimcor Carbon Corporation at Long Beach, California, the United States of America, or manufactured by Oxbow Carbon & Minerals LLC, 330 Golden Shore, Suite 210, Long Beach, California 90802, the United States of America, which—
 - (a) comprise petroleum coke (as to approximately 85 to 100% of the total weight), limestone (as to approximately 0 to 10% of the total weight), and coal tar pitch (as to the remaining weight);
 - (b) were manufactured from those constituents by a process involving heat treatment and steam injection;
 - (c) are unmarked random shapes; and
 - (d) have a sulphur content not exceeding 2% of the total weight.

Commencement Information

I38 Sch. para. 36 in operation at 31.8.2013, see **reg. 1**

- 37. Maxibrite briquettes, manufactured by Maxibrite Limited at Llantrisant, Rhondda Cynon Taff, which—
 - (a) comprise anthracite fines (as to approximately 84% of the total weight), petroleum coke (as to approximately 12% of the total weight), and starch as binder (as to the remaining weight);
 - (b) were manufactured from those constituents by a process involving roll-pressing and heat treatment at 250°C;
 - (c) are cushion-shaped briquettes marked with the letter "M";
 - (d) have an average weight of 35g per briquette; and
 - (e) have a sulphur content not exceeding 2% of the total weight.

Changes to legislation: The Smoke Control Areas (Authorised Fuels) Regulations (Northern Ireland) 2013 is up to date with all changes known to be in force on or before 30 August 2023. There are changes that may be brought into force at a future date. Changes that have been made appear in the content and are referenced with annotations. (See end of Document for details) View outstanding changes

Commencement Information

I39 Sch. para. 37 in operation at 31.8.2013, see reg. 1

- 38. Multiheat briquettes, manufactured by Coal Products Limited at Immingham Briquetting Works, Immingham, North East Lincolnshire, which—
 - (a) comprise anthracite (as to approximately 60 to 80% of the total weight), petroleum coke (as to approximately 10 to 30% of the total weight), and a molasses and phosphoric acid binder (as to the remaining weight);
 - (b) were manufactured from those constituents by a process involving roll-pressing and heat treatment at about 300°C;
 - (c) are unmarked pillow-shaped briquettes;
 - (d) have average weights per briquette of either 55 or 80g; and
 - (e) have a sulphur content not exceeding 2% of the total weight.

Commencement Information

I40 Sch. para. 38 in operation at 31.8.2013, see reg. 1

- 39. Newburn briquettes, manufactured by ECL Mineral Processing Limited of Newfield Works, Newfield, Bishop Auckland, County Durham, which—
 - (a) comprise petroleum coke (as to approximately 56 to 57% of the total weight), anthracite (as to approximately 37 to 38% of the total weight), and a dry powder binder (as to the remaining weight);
 - (b) were manufactured from those constituents by a cold cure process using roller press;
 - (c) are unmarked pillow shaped briquettes 70mm x 62mm x 42mm;
 - (d) have an average weight of 110g per briquette; and
 - (e) have a sulphur content not exceeding 2% of the total weight.

Commencement Information

I41 Sch. para. 39 in operation at 31.8.2013, see reg. 1

[F839A. Newburn briquettes (also marketed as HouseFuel Burnrite), manufactured by M&G Solid Fuels LLP, Wilton International, Wilton, Middlesbrough, TS90 8WS, which—

- (a) comprise petroleum coke (as to approximately 56 to 57 per cent of the total weight), anthracite (as to approximately 37 to 38 per cent of the total weight), and a dry powder binder (as to the remaining weight);
- (b) were manufactured from those constituents by a cold cure process using roller press;
- (c) are unmarked pillow shaped briquettes 70mm x 62mm x 42mm;
- (d) have an average weight of 110g per briquette; and
- (e) have a sulphur content not exceeding 2 per cent of the total weight.]
- F8 Sch. para. 39A inserted (3.11.2014) by The Smoke Control Areas (Authorised Fuels) (Amendment) Regulations (Northern Ireland) 2014 (S.R. 2014/249), regs. 1, 3(e)

- 40. Newflame briquettes, manufactured by Maxibrite Limited at Llantrisant, Rhondda Cynon Taff, which—
 - (a) comprise anthracite fines (as to approximately 84% of the total weight), petroleum coke (as to approximately 12% of the total weight), and starch as binder (as to the remaining weight);
 - (b) were manufactured from those constituents by a process involving roll-pressing and heat treatment at about 260°C;
 - (c) are unmarked pillow-shaped briquettes;
 - (d) have an average weight of 78g per briquette; and
 - (e) have a sulphur content not exceeding 2% of the total weight.

Commencement Information

I42 Sch. para. 40 in operation at 31.8.2013, see reg. 1

- 41. Newflame Plus briquettes, manufactured by Maxibrite Limited at Mwyndy Industrial Estate, Llantrisant, Mid Glamorgan, which—
 - (a) comprise 10 to 15% bituminous coal, 10 to 15% petroleum coke, 70 to 80% anthracite duff and starch binder (as to the remaining weight);
 - (b) were manufactured from those constituents by a process involving roll-pressing and heat treatment at about 260°C;
 - (c) are unmarked pillow-shaped briquettes with approximate maximum dimensions of 67.6mm, 62.6mm, and 37.5mm;
 - (d) have an average weight of 110g per briquette; and
 - (e) have a sulphur content not exceeding 1.9% sulphur on a dry basis.

Commencement Information

I43 Sch. para. 41 in operation at 31.8.2013, see reg. 1

- 42. Newheat briquettes, manufactured for Oxbow Coal B.V. at Newfield Works, Bishop Auckland, County Durham, which—
 - (a) comprise of circa 60 65% of petroleum coke and 30 35% anthracite (both by weight) together with a cold setting resin binder, hardener and low temperature stabiliser as the remaining weight;
 - (b) are produced at ambient temperature by a process involving roll-pressing, the briquettes are "cold-cured";
 - (c) are unmarked pillow-shaped briquettes, oval in appearance;
 - (d) weigh circa 100 grams, +/- 5%; and
 - (e) have a sulphur content not exceeding 1.9% of the total weight.

Commencement Information

I44 Sch. para. 42 in operation at 31.8.2013, see reg. 1

43. Optima Fire Logs, manufactured by Allspan B.V. at Macroweg 4, 5804 CL Venray, the Netherlands, which meet the conditions specified for Big K Instant Lighting Fire Logs at paragraph 4.

Changes to legislation: The Smoke Control Areas (Authorised Fuels) Regulations (Northern Ireland) 2013 is up to date with all changes known to be in force on or before 30 August 2023. There are changes that may be brought into force at a future date. Changes that have been made appear in the content and are referenced with annotations. (See end of Document for details) View outstanding changes

Commencement Information

I45 Sch. para. 43 in operation at 31.8.2013, see reg. 1

[^{F9}43A. Pagan Fuel's Restaurant Charcoal manufactured by Pabensa S.A. Aviadores del Chaco Asunción Paraguay which—

- (a) comprises pyrolised Prosopis Nigra, Cordia Alliodora, Centrolobium, Prosopis kuntzei, Caesalpinia, Gonçalo alves and Tabebuia hardwoods;
- (b) was manufactured using a kiln pyrolysis process at approximately 800°C;
- (c) are unmarked charcoal pieces of between 20 and 120mm; and
- (d) has a sulphur content not exceeding 2% of the total weight on a dry basis.]
- F9 Sch. para. 43A inserted (3.11.2014) by The Smoke Control Areas (Authorised Fuels) (Amendment) Regulations (Northern Ireland) 2014 (S.R. 2014/249), regs. 1, 3(f)
- 44. Phurnacite briquettes, manufactured by Coal Products Limited at Immingham Briquetting Works, Immingham, North East Lincolnshire, which—
 - (a) comprise anthracite duff (as to approximately 65 to 85% of the total weight), petroleum coke (as to approximately 20% of the total weight), and a molasses and phosphoric acid binder (as to the remaining weight);
 - (b) were manufactured from those constituents by a process involving roll-pressing and heat treatment at about 300°C;
 - (c) are ovoid-shaped briquettes with two parallel indented lines running longitudinally around the briquette;
 - (d) have an average weight of 40g per briquette; and
 - (e) have a sulphur content not exceeding 2% of the total weight.

Commencement Information

I46 Sch. para. 44 in operation at 31.8.2013, see reg. 1

- 45. Pyrobloc Fire Logs, manufactured by Allspan B.V. at Macroweg 4, 5804 CL Venray, the Netherlands, which—
 - (a) comprise slack wax (as to approximately 58 to 59% of the total weight) and hardwood sawdust (as to approximately 41 to 42% of the total weight);
 - (b) were manufactured from those constituents by a process of heat treatment and extrusion;
 - (c) are firelogs approximately 265mm in length and 80mm in depth, with grooves along their faces:
 - (d) have an average weight of 1.3kg per firelog; and
 - (e) have a sulphur content not exceeding 0.1% of the total weight.

Commencement Information

I47 Sch. para. 45 in operation at 31.8.2013, see reg. 1

- 46. Safelight Firelogs, manufactured by Advanced Natural Fuels Limited, at Pocklington, East Riding of Yorkshire, which—
 - (a) comprise woodchip (as to approximately 40 to 55% of the total weight) and Palm Wax binder (as to approximately 45 to 60% of the total weight);
 - (b) were manufactured from those constituents by a process involving pressing of the mixed ingredients at about 40°C to 50°C;
 - (c) are rectangular hard finish firelogs with two deep overlapping slots in the top surface and a single continuous slot in the base surface;
 - (d) have an average weight of 1.8kg per firelog; and
 - (e) have a sulphur content not exceeding 2% of the total weight.

Commencement Information

I48 Sch. para. 46 in operation at 31.8.2013, see reg. 1

- 47. Sovereign briquettes, manufactured by Monckton Coke & Chemical Company Limited at Royston, near Barnsley, South Yorkshire, which—
 - (a) comprise anthracite (as to approximately 75% of the total weight), coal and reactive coke (as to approximately 21% of the total weight), and cold-setting resin binder (as to the remaining weight);
 - (b) were manufactured from those constituents by a process involving extrusion;
 - (c) are unmarked hexagonal briquettes;
 - (d) have an average weight of 130g per briquette; and
 - (e) have a sulphur content not exceeding 2% of the total weight.

Commencement Information

I49 Sch. para. 47 in operation at 31.8.2013, see reg. 1

- 48. Supabrite Coke Doubles, manufactured by H.J. Banks and Company Limited at Inkerman Road Depot, Tow Law, County Durham, which—
 - (a) comprise metallurgical coke (as to approximately 40 to 60% of the total weight), and petroleum coke (as to the remaining weight);
 - (b) were manufactured from those constituents by a process involving blending and screening;
 - (c) are unmarked random shapes; and
 - (d) have a sulphur content not exceeding 1.95% of the total weight.

Commencement Information

I50 Sch. para. 48 in operation at 31.8.2013, see reg. 1

- 49. Supacite briquettes, manufactured by Maxibrite Limited at Llantrisant, Rhondda Cynon Taff, which—
 - (a) comprise anthracite fines (as to approximately 84% of the total weight), petroleum coke (as to approximately 12% of the total weight), and starch as binder (as to the remaining weight);

Changes to legislation: The Smoke Control Areas (Authorised Fuels) Regulations (Northern Ireland) 2013 is up to date with all changes known to be in force on or before 30 August 2023. There are changes that may be brought into force at a future date. Changes that have been made appear in the content and are referenced with annotations. (See end of Document for details) View outstanding changes

- (b) were manufactured from those constituents by a process involving roll-pressing and heat treatment at about 240°C;
- (c) are unmarked ovoids;
- (d) have an average weight of 45g per briquette; and
- (e) have a sulphur content not exceeding 2% of the total weight.

Commencement Information

I51 Sch. para. 49 in operation at 31.8.2013, see reg. 1

- 50. Supertherm briquettes, manufactured by Coal Products Limited at Immingham Briquetting Works, Immingham, North East Lincolnshire, which—
 - (a) comprise a blend (in the proportion of 19:1 by weight) of anthracite and medium volatile coal (as to approximately 93% of the total weight), and cold-setting organic binder or a molasses and phosphoric acid binder (as to the remaining weight);
 - (b) were manufactured from those constituents by a process involving roll-pressing;
 - (c) are unmarked ovoids;
 - (d) have an average weight of 160g per briquette; and
 - (e) have a sulphur content not exceeding 1.5% of the total weight.

Commencement Information

I52 Sch. para. 50 in operation at 31.8.2013, see **reg. 1**

- [F1051. Supertherm II briquettes, manufactured by Coal Products Limited at Immingham Briquetting Works, Immingham, North East Lincolnshire, which—
 - (a) comprise anthracite (as to approximately 36 to 51% of the total weight), petroleum coke (as to approximately 40 to 55% of the total weight) and an organic binder or a molasses and phosphoric acid binder (as to the remaining weight);
 - (b) were manufactured from those constituents by a process involving roll-pressing;
 - (c) are either unmarked ovoids or are ovoids marked with a single latitudinal line running across one face of each briquette;
 - (d) have an average weight of 140g per briquette; and
 - (e) have a sulphur content not exceeding 2% of the total weight on a dry basis.]
 - **F10** Sch. para. 51 substituted (3.11.2014) by The Smoke Control Areas (Authorised Fuels) (Amendment) Regulations (Northern Ireland) 2014 (S.R. 2014/249), regs. 1, **3(g)**
- 52. Taybrite briquettes (otherwise known as Surefire briquettes), manufactured by Coal Products Limited at Immingham Briquetting Works, Immingham, North East Lincolnshire, which—
 - (a) comprise anthracite (as to approximately 60 to 80% of the total weight), petroleum coke (as to approximately 10 to 30% of the total weight), and a molasses and phosphoric acid binder (as to the remaining weight);
 - (b) were manufactured from those constituents by a process involving roll-pressing and heat treatment at about 300°C;

- (c) are pillow-shaped briquettes marked with as single indented line running longitudinally along each face, off-set from its counterpart by 10mm or unmarked;
- (d) have an average weight of 80g per briquette; and
- (e) have a sulphur content not exceeding 2% of the total weight.

Commencement Information

I53 Sch. para. 52 in operation at 31.8.2013, see reg. 1

- 53. Therma briquettes, manufactured by Maxibrite Limited at Llantrisant, Rhondda Cynon Taff, which—
 - (a) comprise anthracite fines (as to approximately 84% of the total weight), petroleum coke (as to approximately 12% of the total weight), and starch as binder (as to the remaining weight);
 - (b) were manufactured from those constituents by a process involving roll-pressing and heat treatment at 250°C;
 - (c) are oval/tear shaped briquettes with a line through the centre;
 - (d) have an average weight of 26g per briquette; and
 - (e) have a sulphur content not exceeding 2% of the total weight.

Commencement Information

I54 Sch. para. 53 in operation at 31.8.2013, see reg. 1

- 54. Thermac briquettes, manufactured by Coal Products Limited at Immingham Briquetting Works, Immingham, North East Lincolnshire, which—
 - (a) comprise anthracite (as to approximately 90% of the total weight) and cold-setting organic binder (as to the remaining weight);
 - (b) were manufactured from those constituents by a process involving roll-pressing;
 - (c) are unmarked pillow-shaped briquettes;
 - (d) have an average weight of 48g per briquette; and
 - (e) have a sulphur content not exceeding 1.5% of the total weight.

Commencement Information

I55 Sch. para. 54 in operation at 31.8.2013, see reg. 1

- 55. Tiger Tim Firelogs, manufactured by De Lange B.V., Rustenburgerweg 3, 1646 WJ Ursem, the Netherlands, which—
 - (a) comprise slack wax (as to approximately 50% of the total weight) and sawdust (as to approximately 50% of the total weight);
 - (b) were manufactured from those constituents by a process of heat treatment and extrusion;
 - (c) are firelogs approximately 280mm in length and 75mm x 75mm with a single groove running along each of the four 280mm length faces;
 - (d) have an average weight of 1.1kg per firelog; and
 - (e) have a sulphur content not exceeding 0.2% of the total weight.

Changes to legislation: The Smoke Control Areas (Authorised Fuels) Regulations (Northern Ireland) 2013 is up to date with all changes known to be in force on or before 30 August 2023. There are changes that may be brought into force at a future date. Changes that have been made appear in the content and are referenced with annotations. (See end of Document for details) View outstanding changes

Commencement Information

I56 Sch. para. 55 in operation at 31.8.2013, see reg. 1

- 56. Unicite, manufactured by D.J. Davies Fuels Limited at Blaenau Fuel Depot, Ammanford, Carmarthenshire, or manufactured by A.I. Simson at Cabby Latch, Logie by Kirriemuir, Angus, which—
 - (a) is a mixture of the following separate fuels—
 - (i) anthracite large nuts, and;
 - (ii) Union briquettes of the description in sub-paragraph (c) manufactured by RWE Power A.G. at Cologne, Germany (as to no more than approximately 40 to 42% of Unicite's total weight);
 - (b) has an overall sulphur content not exceeding 0.5% of the total weight; and
 - (c) in so far as it is constituted by the Union briquettes referred to in sub-paragraph (a)(ii), must consist of compressed lignite with each briquette measuring approximately 75mm wide, 60mm high, and 55mm thick.

Commencement Information

I57 Sch. para. 56 in operation at 31.8.2013, see **reg. 1**

- 57. Zip 100% Natural Firelog, manufactured by Standard Brands (Trading) Ireland Ltd., Castlebellingham, County Louth, Ireland, which—
 - (a) comprise naturally derived hydrogenated triglyceride waxes (as to approximately 53 to 57% of the total weight), willow fibre (as to approximately 23 to 27% of the total weight), and natural molasses based binder (as to the remaining weight);
 - (b) were manufactured from those constituents by a process of heat treatment and extrusion;
 - (c) are firelogs approximately 210mm in length, 80 mm in width and 75mm in height;
 - (d) have an average weight of between 1.085 and 1.115kg per firelog; and
 - (e) have a sulphur content not exceeding 0.2% of the total weight.

Commencement Information

I58 Sch. para. 57 in operation at 31.8.2013, see **reg. 1**

- 58. Zip 100% Natural Firelog, manufactured by Standard Brands (Trading) Ireland Ltd., Castlebellingham, County Louth, Ireland, which—
 - (a) comprise naturally derived hydrogenated triglyceride waxes (as to approximately 53 to 57% of the total weight), willow fibre (as to approximately 23 to 27% of the total weight), and natural molasses based binder (as to the remaining weight);
 - (b) were manufactured from those constituents by a process of heat treatment and extrusion;
 - (c) are firelogs approximately 245mm in length, 75mm in width and 68mm in height;
 - (d) have an average weight of between 0.985 and 1.015kg per firelog; and
 - (e) have a sulphur content not exceeding 0.2% of the total weight.

Commencement Information

I59 Sch. para. 58 in operation at 31.8.2013, see reg. 1

- 59. Zip 100% Natural Stove Log, manufactured by Standard Brands (Trading) Ireland Ltd at Castlebellingham, County Louth, Ireland, which—
 - (a) comprise naturally derived hydrogenated triglyceride waxes (as to approximately 53 to 57% of the total weight), willow fibre (as to approximately 23 to 27% of the total weight) and natural molasses-based binder (as to the remaining weight);
 - (b) were manufactured from those constituents by a process of heat treatment and extrusion;
 - (c) are firelogs approximately 165mm in length, 80mm in width, and 75mm in height;
 - (d) have an average weight of between 0.835 and 0.865kg per firelog; and
 - (e) have a sulphur content not exceeding 0.2% of the total weight.

Commencement Information

I60 Sch. para. 59 in operation at 31.8.2013, see reg. 1

- 60. ZIP Cracklelog Firelogs, ZIP Cracklelog firelogs, and ZIP Crackling Log firelogs, manufactured by Allspan B.V., Macroweg 4, 5804 CL Venray, the Netherlands, which—
 - (a) comprise slack wax (as to approximately 55% of the total weight), hardwood sawdust (as to approximately 42% of the total weight), and crackle seeds (as to approximately 3.2% of the total weight);
 - (b) were manufactured from those constituents by a process of heat treatment and extrusion;
 - (c) are firelogs approximately 235mm in length and 80 mm in diameter, with grooves along the faces;
 - (d) have an average weight of 1.1kg per firelog; and
 - (e) have a sulphur content not exceeding 0.1% of the total weight.

Commencement Information

I61 Sch. para. 60 in operation at 31.8.2013, see reg. 1

- 61. ZIP Firelogs, manufactured by Allspan B.V., Macroweg 4, 5804 CL Venray, the Netherlands, which—
 - (a) comprise slack wax (as to approximately 58 to 59% of the total weight) and hardwood sawdust (as to approximately 41 to 42% of the total weight);
 - (b) were manufactured from those constituents by a process of heat treatment and extrusion;
 - (c) are firelogs approximately 265mm in length and 80mm in depth, with grooves along the faces;
 - (d) have an average weight of 1.3kg per firelog; and
 - (e) have a sulphur content not exceeding 0.1% of the total weight.

Commencement Information

I62 Sch. para. 61 in operation at 31.8.2013, see reg. 1

Changes to legislation: The Smoke Control Areas (Authorised Fuels) Regulations (Northern Ireland) 2013 is up to date with all changes known to be in force on or before 30 August 2023. There are changes that may be brought into force at a future date. Changes that have been made appear in the content and are referenced with annotations. (See end of Document for details) View outstanding changes

- 62. ZIP Firelogs, manufactured by Woodflame Moerdijk B.V., Appolloweg 4, Harbour No: M189A, 4782 SB Moerdijk, the Netherlands, which—
 - (a) comprise slack wax (as to approximately 55 to 60% of the total weight) and hardwood sawdust (as to approximately 40 to 45% of the total weight);
 - (b) were manufactured from those constituents by a process of heat treatment and extrusion;
 - (c) are firelogs approximately 255mm in length and 75mm in diameter, with grooves along one longitudinal face;
 - (d) have an average weight of 1.3kg per firelog; and
 - (e) have a sulphur content not exceeding 0.1% of the total weight.

Commencement Information

I63 Sch. para. 62 in operation at 31.8.2013, see reg. 1

63. ZIP Firelogs, manufactured by Allspan B.V. at Macroweg 4, 5804 CL Venray, the Netherlands, which meet the conditions specified for Big K Instant Lighting Fire Logs at paragraph 4.

Commencement Information

I64 Sch. para. 63 in operation at 31.8.2013, see reg. 1

EXPLANATORY NOTE

(This note is not part of the Regulations)

These Regulations revoke and replace with amendments the Smoke Control Areas (Authorised Fuels) Regulations (Northern Ireland) 2012. The Regulations list fuels to be authorised fuels for the purposes of Article 2(2) of the Clean Air (Northern Ireland) Order 1981.

Three additional fuels are authorised (Schedule, paragraphs 57 to 59).

The Regulations contain a savings provision to provide that stocks of authorised fuels manufactured before these Regulations came into operation remain as authorised fuels (regulation 3(2)).

Changes to legislation:

The Smoke Control Areas (Authorised Fuels) Regulations (Northern Ireland) 2013 is up to date with all changes known to be in force on or before 30 August 2023. There are changes that may be brought into force at a future date. Changes that have been made appear in the content and are referenced with annotations.

View outstanding changes

Changes and effects yet to be applied to:

Regulations repealed by 2016 c. 13 (N.I.) Sch. 3

Commencement Orders yet to be applied to the The Smoke Control Areas (Authorised Fuels) Regulations (Northern Ireland) 2013

Commencement Orders bringing legislation that affects this Rule into force:

S.R. 2016/332 art. 2 commences (2016 c. 13 (N.I.))