

## FIRST SCHEDULE

### THE MISCELLANEOUS MINES (GENERAL) REGULATIONS, 1956, HAVING EFFECT AS IF MADE UNDER SECTION ONE HUNDRED AND FORTY-ONE OF THE MINES AND QUARRIES ACT, 1954

## PART IX

### Machinery and ropes

#### *Maintenance of winding and haulage apparatus*

**40.**—(1) At every mine a competent person appointed for the purpose by the manager shall at intervals not exceeding six months thoroughly examine all apparatus (including any detaching hook) provided for attaching to the rope any cage, carriage or kibble ordinarily used in a shaft, staple-pit or unwalkable outlet.

(2) The manager of every mine shall make and secure the efficient carrying out of arrangements whereby any such apparatus so used is at intervals not exceeding six months annealed or subjected to other appropriate heat treatment:

Provided that in relation to any apparatus made of any steel which does not require heat treatment an inspector may by notice served on the manager of the mine exempt such apparatus from the application of this paragraph.

(3) The manager of every mine shall make and secure the efficient carrying out of arrangements whereby every detaching hook is dismantled, cleaned and refitted at intervals not exceeding three months.

(4) Where the efficient operation of any detaching hook would be affected by wear of any ancillary plate or bell a competent person appointed for the purpose by the manager shall at intervals not exceeding thirty days measure the relevant dimensions by means of calipers or gauges.