**Status:** This is the original version (as it was originally made). This item of legislation is currently only available in its original format.

## SCHEDULE 1

## CLASSIFICATION AND ASCERTAINMENT OF OTHER PARTICULARS OF DANGEROUS GOODS

## PART II

## SPECIFICATION OF DANGER SIGNS

1. The danger signs to be used shall be those shown in column 6 of Part I of this Schedule for the classification of the goods shown in the corresponding entry in column 1 of that Part and the signs shall conform in form and colour to those shown in the said column 6, except that in the case of the signs for the classifications "non-flammable non-toxic gas", "flammable gas", "flammable liquid" and "substance which in contact with water emits flammable gas", the symbol may be in white;

**2.** The words in column 7 of Part I of this Schedule may be included in the lower half of the relevant sign shown in the corresponding entry in column 6 of that Part and where included shall conform in form and colour to those shown in the said column 7, except that—

- (a) in the case of the signs for the classifications "non-flammable non-toxic gas", "flammable gas", "flammable liquid", "spontaneously combustible substance" and "substance which in contact with water emits flammable gas" any lettering may be in white;
- (b) in place of the word "toxic", the word "poison" may be used wherever it occurs; and
- (c) in place of the word "flammable", the word "inflammable" may be used wherever it occurs.

**3.** Each danger sign shall be in the form of a square set with its sides at an angle of 45° to the vertical.

**4.** Danger signs shall have a line of the same colour as the symbol, 5 millimetres inside the edge and running parallel to it. (The broken line which surrounds each sign as depicted in column 6 of Part I of this Schedule delineates the edge of that sign and need not be shown.)