
STATUTORY INSTRUMENTS

1997 No. 3053

ROAD TRAFFIC

The Traffic Signs (Temporary Obstructions) Regulations 1997

Made - - - - - 18th December 1997

Laid before Parliament 8th January 1998

Coming into force 1st March 1998

**THE TRAFFIC SIGNS (TEMPORARY
OBSTRUCTIONS) REGULATIONS 1997**

PART I

PRELIMINARY

1. Citation and commencement
2. Revocation
3. Interpretation

PART II

SIGNIFICANCE OF TRAFFIC SIGNS

4. Keep right sign
5. Flat traffic delineator and traffic cone
6. Road vehicle sign
7. Traffic pyramid, traffic triangle and warning lamp

PART III

SIZE, COLOUR AND TYPE OF TRAFFIC SIGNS

8. Keep right sign
9. Flat traffic delineator
10. Road vehicle sign
11. Traffic cone
12. Traffic pyramid
13. Traffic triangle
14. Warning lamp

Status: This is the original version (as it was originally made). This item of legislation is currently only available in its original format.

PART IV

PLACING OF TRAFFIC SIGNS

15. Authorisation to place traffic signs
16. Conditions of authorisation

PART V

SAVINGS

17. Saving for the 1994 Regulations
18. The Motorways Traffic (England and Wales) Regulations 1982 and the Motorways Traffic (Scotland) Regulations 1995
Signature

SCHEDULE 1 — THE ROAD VEHICLE SIGN

1. A road vehicle sign shall be a flexible sheet on...
2. The triangle shall be equilateral. The area marked A in...
3. The area marked B in the diagram may be coloured...
4. The background shall be coloured yellow which shall be fluorescent...
5. The total area of the sheet, including the red triangle,...

SCHEDULE 2 —

— THE TRAFFIC PYRAMID—FIRST DIAGRAM

1. The areas marked A B and C in the diagram...
2. The pyramid shall not be directly illuminated either internally or...
3. The base may be of any colour or it may...

— THE TRAFFIC PYRAMID—SECOND DIAGRAM

1. The areas marked A and B in the diagram indicate...
2. Each outer edge of the triangular face shall be the...
3. The pyramid shall not be directly illuminated either internally or...

SCHEDULE 3 —

— THE TRAFFIC TRIANGLE—FIRST DIAGRAM

1. The areas marked A B and C in the diagram...
2. The corners shall be radiused.
3. All sides shall be the same length.
4. The reflectorised areas of the surface may be internally illuminated...

— THE TRAFFIC TRIANGLE—SECOND DIAGRAM

1. The areas marked A B and C in the diagram...
2. The corners shall be radiused.
3. All sides shall be the same length.
4. The reflectorised areas of the surface may be internally illuminated...

Explanatory Note