#### STATUTORY INSTRUMENTS

## 2002 No. 3113

### The Traffic Signs Regulations and General Directions 2002

#### PART I

#### THE TRAFFIC SIGNS REGULATIONS 2002

#### SECTION 5

#### LIGHT SIGNALS AND WARNING LIGHTS

# Light signals for the control of vehicular traffic on motorways and all-purpose dual carriageway roads

**37.**—(1) Subject to paragraph (4), light signals for the control of vehicular traffic entering or proceeding along a motorway, shall be—

- (a) of the size, colour and type shown in diagram 6031.1 or 6032.1; and
- (b) operated in accordance with the requirements specified in paragraph (2).
- (2) The requirements are that—
  - (a) each lamp shall show an intermittent red light at a rate of flashing of not less than 60 nor more than 90 flashes per minute, and in such a manner that the lights of one vertical pair are always shown when the lights of the other vertical pair are not shown; and
  - (b) the red cross or the white symbol shown in diagram 6031.1 or 6032.1 shall be illuminated by a steady light when the red lights are flashing.

(3) Light signals for the control of vehicular traffic entering or proceeding along an all-purpose dual carriageway road may also be the size, colour and type prescribed by paragraph (1) and operated in accordance with the requirements specified in paragraph (2).

- (4) Light signals for the control of vehicular traffic—
  - (a) entering a motorway by means of a slip road; or
  - (b) entering a motorway which is a roundabout may, instead of complying with paragraphs (1) and (2), be of the size, colour and type prescribed by regulation 33 or 34.