2003 No. 2553

The Electronic Communications Code (Conditions and Restrictions) Regulations 2003

Lines

4.—(1) A code operator shall install all lines underground unless—

- (a) the line is flown from a pole in an area where service lines are already flown from poles;
- (b) the line is—
 - (i) affixed to and lying on the exterior surface of a building or other permanent structure and is either used as a service line or terminates at a service line distribution point;
 - (ii) a service line flown from the eaves of one building or other permanent structure to those of another where the distance between them is less than 8 metres; or
 - (iii) a feeder cable connecting equipment for the provision of services by wireless telegraphy;

and is neither affixed to a building shown as grade 1 or category A in the statutory list of buildings nor located in a conservation area;

- (c) the line is attached to or supported by poles or pylons which are used in connection with the transport of electricity at a nominal voltage of at least 6000 volts;
- (d) the line is installed for the purpose of providing a temporary electronic communications network under regulation 15; or
- (e) it is not in all the circumstances reasonably practicable to do so.
- (2) A code operator shall ensure that any lines installed over the carriageway of-
 - (a) a maintainable highway or, in Scotland, a public road are placed at least 5.5 metres above the surface of the highway or road; and
 - (b) a maintainable highway or, in Scotland, a public road which is a high load grid route are placed at least 6.5 metres above the surface of the highway or road.

(3) If requested by any person to relocate a line which is already installed above the ground, a code operator must relocate that line unless—

- (a) he determines either that the request is unreasonable or that the person making the request will not pay the costs of the relocation; and
- (b) he notifies that person of that determination within 56 days of the receipt of the request.