#### STATUTORY INSTRUMENTS

# 2004 No. 623

# **ROAD TRAFFIC**

The Motor Vehicles (Approval) (Amendment) Regulations 2004

Made - - - - 8th March 2004
Laid before Parliament 9th March 2004
Coming into force - - 1st April 2004

The Secretary of State for Transport, in exercise of the powers conferred by sections 54, 61, 63 and 66 of the Road Traffic Act 1988(1) and of all other powers enabling him in that behalf, and after consultation with representative organisations in accordance with section 195(2) of that Act, hereby makes the following Regulations:

# Citation and commencement

1. These Regulations may be cited as the Motor Vehicles (Approval)(Amendment) Regulations 2004 and shall come into force on 1st April 2004.

# **Commencement Information**

II Reg. 1 in force at 1.4.2004, see reg. 1

## **Preliminary**

**2.** The Motor Vehicles (Approval) Regulations(2) shall have effect with the following amendments.

#### **Commencement Information**

I2 Reg. 2 in force at 1.4.2004, see reg. 1

## **Amendment of Regulation 3 (Interpretation)**

**3.**—(1) Regulation 3(1) shall be amended as follows.

<sup>(1) 1988</sup> c. 52; section 61 was amended by the Road Traffic Act 1991 (c. 40), section 63 was amended by S.I. 1992/3107.

<sup>(2)</sup> S.I. 2001/25.

(2) In the appropriate alphabetical position insert the following definitions—

""category" has the same meaning as in Annex IIA of the 1970 Directive;

"disabled person" means a person who has a disability (as defined in section 1 of the Disability Discrimination Act 1995(3));

"disabled person's vehicle" means a vehicle which is adapted or constructed so as to enable a disabled person to travel in it, whether as the driver or as a passenger, in safety and reasonable comfort;".

#### **Commencement Information**

**I3** Reg. 3 in force at 1.4.2004, see **reg. 1** 

### **Amendment of Regulation 5 (Approval requirements for relevant vehicles)**

- **4.**—(1) Regulation 5 shall be amended as follows.
- (2) For paragraph (2) there shall be substituted the following paragraph—
  - "(2) The items in Schedule 3 numbered 3, 4, 10 and 13 shall not apply to relevant vehicles which are not Schedule 2 vehicles, except that item 10 shall apply to disabled person's vehicles and vehicles that have been adapted to category M1.".
- (3) For paragraph (8) there shall be substituted the following paragraph—
  - "(8) A relevant vehicle shall be regarded as complying with all the requirements prescribed under section 54 of the 1988 Act if at least one of the following three conditions are satisfied in relation to each applicable subject matter mentioned in Schedule 3 or 4—
    - (a) the vehicle complies with the requirements set out in paragraph (1);
    - (b) the requirements applicable to the vehicle are prescribed by regulation 4 of the 1984 Regulations or by regulation 4 of the 1982 Regulations in relation to the subject matter and the vehicle complies with those requirements;
    - (c) the vehicle has been issued with a Department's approval certificate issued in accordance with Article 31A (4) or (5) of the Road Traffic (Northern Ireland) Order 1981(4).".
- (4) After paragraph (8) there shall be inserted the following paragraph—
  - "(8A) A relevant vehicle which meets the technical requirements for permanent registration in another EEA State shall be treated as complying with all the requirements prescribed under section 54 of the 1988 Act, except to the extent that following an assessment of documentation where such is provided, the Secretary of State is unable to establish that the vehicle satisfies standards equivalent to those prescribed in relation to each applicable subject matter mentioned in Schedule 3 or 4."

#### **Commencement Information**

**I4** Reg. 4 in force at 1.4.2004, see reg. 1

# Amendment of Regulation 6 (Application for Minister's approval certificate)

**5.**—(1) Regulation 6 shall be amended as follows.

<sup>(3) 1995</sup> c. 50.

<sup>(4)</sup> S.I. 1981/154 (N.I.1).

- (2) In paragraph (1) for the second word "for" there shall be substituted the word "of".
- (3) For sub-paragraph 6 (b)(ii) there shall be substituted the following sub-paragraph—
- "(ii) in the case of a Schedule 2 vehicle (other than a left hand drive vehicle or a personally imported vehicle) and a disabled person's vehicle, at the place where the examination took place for the purposes of the original application.".

## **Commencement Information**

**I5** Reg. 5 in force at 1.4.2004, see **reg. 1** 

# Amendment of Regulation 11 (form of certificate)

**6.** For the Table in regulation 11, there shall be substituted the following Table.

#### **TABLE**

(1)	(2)	(3)
Item	Class of vehicle	Letter
1.	Left hand drive vehicle	N
2.	Personally imported vehicle	P
3.	Amateur built vehicle	A
4.	Vehicle manufactured in very low volume	L
5.	Vehicle manufactured using parts from a registered vehicle	С
6.	Rebuilt vehicle	S
7.	Motor caravan, ambulance or hearse	M
8.	Armoured vehicle	T
9.	Vehicle not falling within any of the preceding classes specified in this Table	R
10.	Disabled person's vehicle	D
11.	Vehicle which meets the condition set out in regulation 5(8)(c)	E

#### **Commencement Information**

**I6** Reg. 6 in force at 1.4.2004, see reg. 1

# **Amendment of Schedule 2**

7.—(1) Schedule 2 shall be amended as follows.

- (2) Sub-paragraph 1(f) shall be deleted.
- (3) After sub-paragraph 2(1) there shall be inserted the following sub-paragraph—
  - "(1A) A vehicle may also be treated for the purposes of these regulations as a personally imported vehicle if—
    - (a) a person, who is a serving member of the Armed Forces, intends to import it into the United Kingdom within 12 months of the date of application for a Minister's approval certificate;
    - (b) that person, at the time of that application, has been normally resident in a country other than the United Kingdom for a continuous period of at least 12 months; and
    - (c) paragraphs (c) to (e) of sub-paragraph 2(1) apply to that person.".
- (4) After sub-paragraph 2(5) there shall be inserted the following definition—
  - "(6) In this paragraph—

"serving member of the Armed Forces" means a person who is employed by Her Majesty's air forces, Her Majesty's military forces or Her Majesty's naval forces; except that a serving member of any of the reserve forces shall not be included within this definition."

(5) Paragraph 6 shall be deleted.

#### **Commencement Information**

I7 Reg. 7 in force at 1.4.2004, see reg. 1

#### **Amendment of Schedule 3**

**8.** For the Table in Schedule 3, there shall be substituted the Table set out in Schedule 1 of these Regulations.

## **Commencement Information**

**I8** Reg. 8 in force at 1.4.2004, see reg. 1

#### **Amendment of Schedule 4**

**9.** For the Table in Schedule 4, there shall be substituted the Table set out in Schedule 2 of these Regulations.

#### **Commencement Information**

**19** Reg. 9 in force at 1.4.2004, see **reg. 1** 

#### **Amendment of Schedule 5**

**10.** For the certificate in Schedule 5, there shall be substituted the certificate set out in Schedule 3 of these Regulations.

#### **Commencement Information**

**I10** Reg. 10 in force at 1.4.2004, see reg. 1

#### **Amendment of Schedule 6**

- 11.—(1) In part II of Schedule 6, in the third and fourth columns of the Table, for the references to Community Directives in Schedule 3 shall be inserted the entries specified below.
  - (a) In the reference to Seat belts in column (1), after the last entry—

2000/03/EC\* L53, 25.2.00, p.1

(b) In the reference to Tyres in column (1), after the entry of the Principal Directive—

2001/43/EC+ L211, 4.8.01, p.25

(c) In the reference to Interior fittings in column (1), after the last entry—

2000/04/EC+ L87, 8.4.00, p.22

- (2) In Part II of Schedule 6, in the third and fourth columns of the Table, for the references to Community Directives in Schedule 4 shall be inserted the entries specified below.
  - (a) In the reference to Exhaust emissions in column (1), after the last entry—

1999/102/EC*	L334, 28.12.99, p. 43
2001/01/EC+	L35, 6.2.01, p.34
2001/100/EC+	L16, 18.1.02, p. 32

(b) In the reference to Seat belts in column (1), after the last entry—

2000/03/EC\* L53, 25.2.00, p.1

(c) In the reference to Noise and silencers in column (1), after the last entry—

1999/101/EC\* L334, 28.12.99, p.41

(d) In the reference to Carbon dioxide emissions and fuel consumption in column (1), after the last entry—

1999/100/EC\* L334, 28.12.99, p.36

(e) In the reference to Frontal impact in column (1), after the entry of the Principal Directive—

1999/98/EC\* L9, 13.1.00, p.14

- (3) In Part III of Schedule 6, in the third and fourth columns of the Table, for the references to ECE regulation in Schedule 4, shall be inserted the entry specified below.
  - (a) In the reference to Exhaust emissions, after the last entry—

83.05 29 March 2001

# **Commencement Information**

III Reg. 11 in force at 1.4.2004, see reg. 1

Signed by authority of the Secretary of State

David Jamieson
Parliamentary Under Secretary of State,
Department for Transport

8th March 2004

# SCHEDULE 1

Regulation 5(1)(a)

# APPROVAL REQUIREMENTS FOR RELEVANT VEHICLES (REPLACING SCHEDULE 3)

Com	nencement Information
I12	Sch. 1 in force at 1.4.2004, see <b>reg. 1</b>

1	2	3	4	5
Item	Subject matter	Requirement	Definitions and supplementary provisions	Exemptions and modifications
1	Doors, their latches and hinges			Paragraph 3 shall not apply to door which do not give direct access to a seat designed for normal use while a vehicle is travelling on a road. This includes any door, for which the longitudinal plane passing through the extreme inboard projecting point of such a door is more than 300mr distant from the longitudinal plane passing through the nearest edge of such a seat.
		2. Where hinges are used on doors fitted to the side of a vehicle, other than folding doors, the hinges shall be fitted at the front edge of the door. However,		The latching requirements in paragraphs 1 and 3 shall not apply to any power-operated door if the force applied by the power actuator is sufficient to

1	2	3	4	5
Item	Subject matter	Requirement	Definitions and supplementary provisions	Exemptions and modifications
		they may be fitted at the top or rear edge if either—	Freezeens	keep the door completely closed even when any
		(a) a device is fitted which automatic closes the door at least to the intermedilatched position if it is unlatched when the vehicle	iate	load is applied as described in paragraph 3.
		is moving in the forward		
		direction; or	;	
		(b) a safety-bolt is fitted to prevent such unlatchin and an audible warning	g	
		device is provided which activates an		
		audible warning if the vehicle is driven		

without

I Item	2 Subject matter	3 Requirement	4 Definitions and supplementary	5 Exemptions and modifications
		the bolt in place.	provisions	
		3. On hinged doors, the latch and striker assembly shall be capable of withstanding any load which is likely to be applied in the course of normal driving (ie excluding crash impacts) in both the intermediate and fully latched positions. However if a safety-bolt with an audible warning device is provided as specified in paragraph 2(b) above, the requirement need be met only with the bolt in place.		
2	Radio- interference suppression	The vehicle shall comply with the requirements of paragraph 6.1 of Annex 1 to Directive 72/245/EEC as amended by Directive 89/491/EEC, or of paragraph 6.1 of ECE Regulation 10.01.		This item shall only apply to vehicles propelled by a spark ignition engine.
3	Protective Steering	_	For the purposes of this item— "driver's air bag" means a flexible bag	This item shall not apply to— (a) vehicles manufactured before 1 October

had been

1	2	3	4	5
Item	Subject matter	Requirement	Definitions and supplementary provisions	Exemptions and modifications
		by a sphere of 165mm in diameter shall present any roughness or sharp edges with a radius of curvature of less than 2.5mm.  2. The steering control shall be designed, constructed and fitted so as not to embody components or accessories, including the horn control and other assemblies, capable of catching in the driver's clothing or jewellery in normal driving movements.  3. The steering control and column assembly as fitted to the vehicle or the steering control itself shall offer a degree of protection to the driver in the event of a frontal impact by absorbing energy. This requirement shall be treated as met if either—  (a) the vehicle complies with the	fitted to a vehicle and designed to be filled with gas under pressure in order to protect the driver in the event of a collision involving the front end of the vehicle. "steering control" has the same meaning as in Directive 74/297/ EEC.	1997 in which the centre of the steering control is in the forward quarter of the total length of the vehicle, including any bumpers and overriders; (b) ambulances, motor caravans and hearses (in each case) having a maximum gross weight of more than 2,500 kg if the vehicle has been derived from a goods vehicle either having a maximum gross weight of not less than 1,500 kg or manufacture before 1st October 1997; and (c) armoured vehicles.
		requireme	ents	person's vehicle had been

1	2	3	4	5	
Item	Subject matter	Requirement	Definitions and supplementary provisions		nptions and lifications
		of	*	adap	ted, then the
		paragraj	ph		rements of
		5.2 of			tem shall
		Annex			pply to the
		1 of			ele insofar
		Directiv	re		e adaptation
		74/297/			ents the
		EEC; or	<u>.</u>		cle from
		(b) the			olying
		steering			any of the
		control		this i	rements of
		complie		uiis i	tC111.
		with the		Para	graph 1 shall
		requirer	nents	-	pply to any
		of	.1		ele if:
		paragraj	ons	(a)	it is fitted
		5.2, 5.4.3,			with a
		5.4.4 5.4.4			driver's air
		and			bag;
		5.4.5 of		(b)	the driver's
		Directiv			air bag was
		74/297/	•		fitted at the
		EEC			time the
		as last			vehicle was
		amende	d		manufactured
		by		( )	and
		Directiv	re e	(c)	all parts of
		91/662/			the steering
		EEC.			control are
		<b>4.</b> The vehicle	<b>.</b>	AV CAI	blunted, pt that this
		shall comply with			pt mat uns ption shall
		the requirements			pply to:
		of paragraph 5.1		(i)	an amateur
		of Annex 1 of		(1)	built
		Directive 74/297	/		vehicle;
		EEC.		(ii)	a vehicle
				. ,	manufactured
					in very low
					volume;
				(iii)	a vehicle
					manufactured using
					parts of a
					registered
					vehicle;
				and	

Item Subject matter Requirement Definitions and Exemptions and supplementary modifications provisions	1	2	3	4	5
	Item	Subject matter	Requirement	supplementary	Exemptions and modifications

(iv) a rebuilt vehicle.

Paragraph 1 shall not apply to any switch fitted to the **steering control** of any vehicle if:

- (a) the switch is an integral part of the steering control as originally fitted to the vehicle by its manufacturer and it can be depressed into the steering control by finger pressure; and
- (b) the switch is blunted; except that this exemption shall not apply to
- (i) an amateurbuilt vehicle;
- (ii) a vehicle manufactured in very low volume;
- (iii) a vehicle manufactured using parts of a registered vehicle; and
- (iv) a rebuilt vehicle.

1	2	3	4	5
Item	Subject matter	Requirement	Definitions and supplementary provisions	Exemptions and modifications
4	Exhaust emissions	1. The vehicle shall not emit any avoidable smoke or avoidable visible vapour.  2. When the engine by which the vehicle is propelled is running without load at a normal idling speed, the carbon monoxide content of the exhaust emissions from the engine shall not exceed—  (a) if the vehicle has an effective date before 1st August 1986, 4.5%; or  (b) if the vehicle has an effective date on or after 1st August 1986 and not being a vehicle to which subparagrapior (d) below applies,	"effective date" means the date of manufacture of the vehicle, except that in the case of a vehicle which for the time being meets the requirements of paragraph 3, 5, or 7 of Schedule 2 to these Regulations, it shall mean the 1st January immediately preceding the date of manufacture of the engine by which it is propelled, if that date is earlier; "the emissions publication" means the emission publication as defined in sub-paragraph	purposes only, and (ii) the petrol tank cannot contain more than 15 litres of petrol.  This item shall not apply to vehicles with an internal combustion engine, if the internal combustion engine is used to generate electricity to propel the vehicle.  Paragraphs 2, 3 and 4 shall not apply to— (a) vehicles not propelled by a spark ignition engine;

!	2	3	4			5	
Item	Subject matter	Requirement	-		is and ntary		mptions and lifications
				ision	-		J
		3.5%;		and 1	Use	(b)	vehicles
		or		Regu	ılations;		having an
		(c) if the		"a fa			effective
		vehicle	e	idlin			date before
		is of a		spee	ď"		1st August
		descri		meai	ns—		1975; and
		mentio		(a)	in the	(c)	vehicles
		in the			case		having an
		Annex			of a		effective
		to <b>the</b>			vehicle		date before
		emissi	ons		of a		1st August
		public			descrip		1987 and
		and is			mention	ned	propelled
		either-			in the		by a <b>rotary</b>
					Annex		piston
		(i) a			to		engine.
		_	oassenge	I	[the]		
			car				graphs 2(a)
			naving		publica		(b) and shall
			n .cc		a	not a	ipply to
			effective			alehi	cles propelle
			late		speed	by a	2-stroke
			on		between	nengi	ne.
			or . c		the		
			ıfter		minimu		graph 2(c)
			lst A		and	shall	not apply to
			August		maxim	u <b>(ni</b> )	a passenge
			1992;		limits		car having
		(	or		shown		an effectiv
		(ii) a	ıny		against		date on or
		•	other		that		after 1st
		7	ehicle		descrip	tion	August
		ł	naving		of		1992 and
		f	our		vehicle		before 1st
		(	or		in		August
		r	nore		column	S	1995;
			wheels		3(e)	(ii)	any other
		8	ınd		and (f)		vehicle
			ın		respect	ively	having fou
			effective		of that		or more
		(	late		Annex;		wheels and
		(	on		or		an effectiv
			or	(b)	in any		date on or
		8	ıfter		other		after 1st
		1	lst		case, a		August
			August		rotation	ıal	1994 and
			1994,		speed		before 1st
		-					
			he		of		August

1	2	3	4		5
Item	Subject matter	Requirement	supp	nitions and plementary visions	Exemptions and modifications
			relevant	2,500	if the passenger
			percenta		car or other
			or	3,000	vehicle was not
		(d) if the		revoluti	ions the effective
		vehic	le	per	date, equipped
		is not			with a catalyst
		of a			exhaust emission
		descr	iption	value"	system, in which
		ment	ioned	means the	case paragraph
		in the		ratio by mass of air	2(b) will apply.
		Anne			Paragraphs 2(a)
		to the		to petrol vapour in	Paragraphs 2(c) and 2(d) shall
		emiss		the mixture	not apply to
		<b>publ</b> i and is	cation	entering the	vehicles having
		eithei		combustion	an effective date
				chambers	before 1st Januar
		(i)		divided by	1999 which are
			passenge		either—
			car having	"a normal	(i) fuelled
			an	idling	solely by
			effective	speed"	either liquid
			date	ilicalis III	petroleum
			on	the case of a vehicle of a	gas or natural gas
			or	description	or
			after	mentioned	(ii) bi-fuelled
			1st	in the	vehicles
			August	Annex	when
			1995;	to the	controlled
			or	emissions	to operate
		(ii)	any	publication,	on either of
			other	a rotational	those gases
			vehicle	speed	D 1 2
			having	between the	Paragraphs 3 and
			four	minimum	4(b) shall not
			or more	and maximum	apply to vehicles fuelled solely
			wheels	limits	by natural gas
			and	shown	or to bi-fuelled
			an	against that	vehicles when
				description	controlled to
			date	of vehicle	operate on natura
			on	in columns	gas.
			or	2(b)	
			after	and 2(c)	Paragraph 4(c)
			1st	respectively	shall not apply
			August	of that	to vehicles
		15	1997,	Annex;	fuelled by liquid

1	2	3	4	5
Item	Subject matter	Requirement	Definitions and	-
			supplementary	modifications
			provisions	
		0.5% of	"passenge	
		the total	car" mean	ıs natural gas.
		exhaust	a motor	
		emissions	s vehicle	
		from	which—	
		the	(a) is	
		engine	cons	structed
		by	or	
		volume.	adap	
		<b>3.</b> If the engine	for u	
		by which the	for t	
		vehicle is	carr	iage
		propelled is run	of	
		without a load at a		engers
		rotational speed of	and	
		2,000 revolutions	not a	
		per minute, the	good	
		hydrocarbon	vehi	
		content of the	(b) has	no
		exhaust emission	mor	
		from the engine	than	
		shall not exceed	five	
		0.12% if the	seat	S
		vehicle either—	in	
			addi	
		(a) has not	to th	
		more	driv	
		than	seat	
		three wheels;	(c) has	
		,	weig	ght
		or	not	1'
		(b) is a		eeding
		vehicle	2,50	JU
		to	kg	imum
		which		imum
		paragrapl	n gros and	55,
		2(a)		
		or (b)	(d) has four	or
		applies;	mor	
		<b>4.</b> If the	whe	
		vehicle is one to	"the	C15,
		which paragraph	relevant	
		2(c) or (d) applies	limits"	
		and the engine	means—	
		by which it is	(a) in the	ne.
		propelled is run	(a) III u	
		without a load	of a	
		at a fast idling	vehi	
		speed— <sub>16</sub>	VCIII	.010
		- 10		

l Item	2 Subject matter	3 Requirement	4 Definitions of supplements	-
			provisions	
		(a) the		fa
		carbor		escription
		mono		nentioned
		conter		n the
		of the		nnex
		exhau		the [the
		emissi		missions
		from	-	ublication,]
		the		ne
		engine		ninimum
		shall		nd
		not		naximum
		exceed		mits
		0.3%		hown
		the tot		gainst
		exhau		nat
		emissi		escription
		from	0	
		the	V	ehicle
		engine		
		by		olumns
		volum	ie; 3	(c)
		(b) the	a	nd
			carbon 3	(d)
		conter	12/	espectively
		of the	0	f that
		exhau	st A	nnex;
		emissi	_	r
		from	(b) in	n any
		the	0	ther
		engine	c	ase,
		shall	0	.97
		not	a	nd
		exceed		.03;
		0.02%	6641	
		of the	relevan	nt
		total	percent	tage"
		exhau	st means	in
		emissi		e of a
		from	vehicle	e of a
		the	descrip	tion
		engine	ma amti a	
		by	in the	
		volum	Annex	
		and	to <b>the</b>	
			emissio	ons
		(c) the	public	
		lambo	la the	,
		value	percent	

1	2	3	4	5
Item	Subject matter	Requirement	Definitions and supplementary provisions	Exemptions and modifications
		shall be between the relevant limits.	shown against that description of vehicle in column 2(a) of that Annex; and "rotary piston engine" means an engine in which the torque is provided by means of one or more rotary pistons and not by any reciprocating piston; and any rotary piston engine shall be deemed to be a four-stroke engine.	
5	Smoke Emissions	If the vehicle has an effective date on or after 1 August 1979, when the engine by which it is propelled is subject to the free- acceleration test, the coefficient of absorption of the exhaust emissions from the engine immediately after leaving the exhaust shall not exceed—	For the purposes of this item—  "co- efficient of absorption" shall be construed in accordance with paragraph 3.5 of Annex VII to Directive 72/306; "effective date" has the same meaning as	This item shall only apply to vehicles propelled by a compression ignition engine.

1	2	3	4	4	5
Item	Subject matter	Requirem	si p	Definitions and supplementary provisions	Exemptions and modifications
		of the vehicle is tuenth or charmon (b) in an	cle rbo- ged, 3.0 metre, ny other , 2.5 per	in item 4; and "free acceleration" has the same meaning as in Annex II to Directive 77/143/ EEC as last amended by Directive 92/55/EEC.	
6	Lamps, reflectors and devices	not constitute to the contravent failure to	ment of icle the icle that Roar a road shounset as e would redute a dation or a a road should be in the icle of th	reference of the date of nanufacture of ne vehicle.  For the purposes of this item—  "coefficient of luminous intensity" has the same meaning as in ECE Regulation 3.01; "special purpose" means, in relation to a vehicle,	This item, in so far as it requires any lamp (not being a filament lamp), reflector or device to bear a particular standard mark (or one of two or more standard marks), shall not apply to a vehicle if—  (a) in the case of a lamp or device, it meets the requirements as to intensity; and  (b) in the case of a reflector, it meets the standards as to coefficient of luminous intensity, of the instrument to which the standard

1	2	3		4		5
Item	Subject matter	Requirem	ent	supp	initions and plementary visions	Exemptions and modifications
		(ii)	those Regulati and to be fitted with a dim- dip device or running lamp.		body arrangements or equipment by virtue of which the vehicle is a special purpose vehicle for the purposes of Annex IIA of the 1970 Directive; "standard mark" means a mark which, when applied to a lamp, reflector or device, indicates compliance with the	mark (or as the case may be one of those standard marks) relates.  This item, in so far as it requires compliance with regulation 14 of the Lighting Regulations (filament lamps), shall not apply to a lamp, if by virtue of the preceding paragraphs, it could comply with this item without bearing any standard mark.  This item, in so far as it requires the headlamps (including a filament lamp fitted to a headlamp) fitted to a vehicle to bear a particular standard mark (or one of two or more standard marks), shall not apply to headlamps that emit sufficient light to illuminate the road in front of the vehicle on both main and dipped beam.

1	2	3		5
I Item	Subject matter	3 Requirement	4 Definitions and supplementary provisions	Exemptions and modifications
				In the case of a rear direction indicator which is one of a number of lamps having a common housing and fitted to a left-hand drive vehicle, paragraph 2(b) (I) in Part 1 of Schedule 7 of the Lighting Regulations shall apply as if for "400 mm" there were substituted "480 mm".
				In the case of an ambulance, motor caravan, hearse or armoured vehicle, exemptions shall be permitted in so far as the <b>special purpose</b> of the vehicle makes it impossible fully to comply, provided that all obligatory lamps, reflectors and devices are installed and the angles of visibility are not affected.
7	Rear-view mirrors	1. The vehicle shall be fitted with at least one offside exterior mirror which meets—  (a) if the vehicle is right hand	For the purposes of this item—  "extreme outer edge" has the meaning given by regulation 3 of the	This item shall not apply to vehicles having not more than three wheels, if they comply with the requirements (2) for motortricycles in Annex

hand drive

1	2	3		4		5	
Item	Subject matter	Requiren	,	supp	nitions and elementary isions		mptions and lifications
			or has a		Lighting	III to	Directive
			central		Regulations;	97/2	4/EC.
			driving		"floor		
			position,		marking	The	requirements
			the		A", "floor	of pa	aragraph 2
			adjustmer	ıt,	marking B"	shall	not apply to
			rear		and "floor	moto	or caravans,
			view,		marking		ulances,
			and		C" mean		ses or
			vibration		the lines		oured
			requireme	ents;			cles (in each
			or		such in the		) having a
		(b)	if the		Appendices		imum gross
			vehicle		1 and 2		tht exceeding
			is left		to this		0 kg if the
			hand		Schedule; "longitudinal		cle has been
			drive,		plane" has		nicle of
			the rear				gory M2, M3,
			view,		given in		or N3.
			and		regulation 3(2		n 113.
			vibration		of the		graph 4(b)
			requireme	ents.	Construction		
		<b>2.</b> The	e vehicle		and Use	appl	
		shall a	lso be		Regulations;		to any
		fitted with	h at least		"longitudinal	()	mirror,
		one interi	or mirror		plane a",		no part of
		which	meets		"longitudinal		which is
		the adju	ustment,		plane b" and		less than
		rear vi			"longitudinal		2,000 mm
		vibration			plane c"		above the
		requirem			mean the		ground, or
		unless no			vertical	(b)	to any
		mirror	could		planes "a",		mirror
		provide a			"b" and		which does
		to the rea	Γ.		"c" in the		not protrude
		<b>3.</b> If n	o interior		Appendices		beyond an
		mirror i			1 and 2		extreme
		or if no	interior		to this		outer edge
		mirror	meets		Schedule;		of the
		the rea			"pole A", "pole B"	(c)	vehicle, or any left
		requirem			and "pole	(0)	hand drive
		nearside			C" mean		vehicle.
			shall be		the vertical		veniere.
		fitted	which		lines		
		meets—			projecting		
					upwards		
					from the		
		2/	2				

1	2	3		4			5
Item	Subject matter	Requiren	nent I	Defini			Exemptions and
				supple		-	modifications
		(.)		provisi			
		(a)	if the vehicle		orız urfa	ontal	
			is right			r) at the	
			hand			ions	
			drive		how		
			or has a		the		
			central			ndices	
			driving		and		
			position,		thi		
			the rear			dule, to	
			view			eight	
			and		f—	C	
			vibration	(a	a)	in the	
			requireme			case	
			or			of	
		(b)	if the			pole	
		( )	vehicle			A, the	
			is left			highest	
			hand			point	
			drive,			of the	
			the			reflecting	g
			adjustmen	ıt,		surface of the	
			rear			offside	
			view,			exterior	
			and			mirror;	
			vibration	a O	2)	in the	
			requireme	ents. 🔨	,	case	
		<b>4.</b> Eac	h rear			of	
		view mir				pole	
		to the veh	icle shall			<b>B</b> , the	
		either—				highest	
		(a)	comply			point	
			with the			of the	
			requiremen	nts		reflecting	g
			(including			surface	
			marking			of the	
			requiremen	nts)		interior	
			of			mirror;	
			Annex	(-	c)	and in the	
			II to	((	-)	case	
			Directive			of	
			71/127/			pole	
			EEC as last			C, the	
			as iast amended			highest	
						point	
			by Directive			of the	
			88/321/			reflecting	g
		23					_

1	2	3		4	5
Item	Subject matter	Require	ment	Definitions and supplementary	Exemptions and modifications
			FEC	provisions	
			EEC or	surface	2
			of Part I	of the	la.
			of ECE	nearsid	
			Regulatio 46.01		
			46.01 for a	mirror;	
			Class I	"transverse	
			mirror	eye plane" means the	
			in the	vertical	
			case of an	plane	
			interior	passing through	
			mirror	the line	
			and a	shown as	
			Class	such in the	
			III or a	Appendices	
			Class II	1 and 2	
			mirror	to this	
			in the	Schedule;	
			case	"transverse	
			of an	plane"	
			exterior	means a	
			mirror;	vertical	
			or	plane	
		(b)	comply	normal to a	
		(0)	with the	longitudinal	
			dimensio	mlama	
			requirem		
			and the	"the adjustment	
			following	requirements"	
			requireme	ents—	
				In order to meet	
			(1) tile	the adjustment	
			of	requirements—	
			the	an interior	
			refle	mirror shall	
			surf	ective be capable	
			shal	1 Of Ochig	
			be	adjusted by the driver	
				1	
			with	. WHEH III	
			a	nosition:	
			prot	position; ective <sub>and</sub>	
			hou	sing; an exterior	
			(ii) all	mirror	
			(II) all part		
			of	(a) be	
			the	capable	<u>a</u>
		2	4	Capaul	

1	2	3	4		5
Item	Subject matter	Requirement	Definitio suppleme		Exemptions and modifications
			provision		mounteunons
			external	of	
			surface	being	
			of	adjusted	1
			the	by the	
			mirror	driver	
			which	when	
			are,	in his	
			in	driving	
			the	position	
			case	the	,
			of	door	
			an	being	
			interior	closed;	
			mirror,	or	
			contactable)	be so	
			by	constru	cted
			a	that,	
			sphere	when	
			of	knocked	d
			165	out of	
			mm	alignme	ent,
			diameter,	it can	
			and	be	
			in	returned	d
			the	to its	
			case	former	
			of	position	1
			an	without	
			exterior	need	
			mirror,	of	
			by	adjustm	ient.
			a		
			sphe <b>Pe</b> ovided		
			of a mirror s		
			100 be regard		
			mmas meetin		
			diametprireme		
			shalkub-parag		
			haveabove wh	ether or	
			a not—		
			radi(s) it ca		
				t those	
			curvature requ		
				with	
				window	
			less in th		
				er's	
				r being	
			mm, open	n; or	

1	2	3	4	5
Item	Subject matter	Requirement	Definitions and supplementary	Exemptions and modifications
			provisions with(b) the mirror	
			the is capable	
			exception of being	
			of locked in	
			fixing position	
			holes from the	
			or outside of	
			recesses the vehicle.	
			less	
			than"The dimension	
			12 requirements"	
			mm widen order for	
			if an exterior	
			thes <b>e</b> nirror to meet	
			are the dimension	
			bluntequirements, the	
		(iii	exterior exterior	
		(III)	reflecting surface	
			shalmust be such that	
			be an orthogonal	
			capable: 100 capable in the capable	
			of vertical surface	
			rotating accommodates a	
			inwards inwards towards towards	
			the and a rectangle	
			vehicles vertical sides	
			when 40 mm and	
			a horizontal sides	
			force 70 mm.	
			of	
			10 In order for	
			kg an interior	
			is mirror to meet	
			applied dimension	
			horizontally at dimensions of the	
			the reflecting surface	
			extreme be such that	
			outer orthogonal	
			adaprojection onto a	
			in vertical surface	
			<sub>a</sub> accommodates	
			ion a regtangle with	
			nlarvertical sides	
			from of 40 mm and	
			both horizontal sides the of 80 mm.	

1	2	3	4	5
Item	Subject matter	Requirement	Definitions and supplementary provisions	Exemptions and modifications
			front'The rear view	
			and requirements" (see	
			the the Appendices	
			rear.1 and 2 to this	
			The Schedule)	
			axis	
			of In order for a	
			rotation ror to meet	
			shalthe rear view	
			lie requirements, it withinust be such that	
			50 when the vehicle	
			mmis positioned	
			of such that its	
			the longitudinal axis	
			surfaceparallel to the	
			at longitudinal	
			whi <b>qdanes a, b</b>	
			the and c, with the	
			mirroriver seated	
			is in his normal	
			attachpedght driving	
			to position such that	
			the his eyes lie in	
			vehithe transverse	
			bodyewoplane	
			and with the	
			mirror correctly	
			adjusted, he shall be able to see in	
			that mirror—	
			(a) in the case	
			of an offside	
			exterior	
			mirror, with	
			the offside	
			extreme	
			outer	
			edge of	
			the vehicle	
			positioned	
			so that it is	
			tangential	
			to the	
			longitudinal	
			plane a,	
			the whole	
			of <b>floor</b>	

1	2	3	4	5
Item	Subject matter	Requirement	Definitions and supplementary	
			and pole A and  (b) in the case of an interior mirror, wi the central longitudin axis of the vehicle positioned so that it lies on the longitudin plane b, the whole of floor marking and pole I or  (c) in the case of a nearside exterior mirror, wi the nearside exterior mirror, wi the nearside extreme outer edge of the vehicle positioned so that it is tangential to the longitudin plane c, the whole of floor marking and pole (c)	th l l l l l l l l l l l l l l l l l l l
			"The vibration requirements"	

In order to comply with the vibration requirements, a mirror shall

1	2	3	4	5
Item	Subject matter	Requirement	Definitions and supplementary provisions	Exemptions and modifications
			be fixed to the vehicle in such a way that under normal driving conditions, it neither moves so as to change the field of vision, nor vibrate to an extent which would cause the driver to misinterpret the nature of the image received.	
8	Anti-theft devices	1. The vehicle shall be fitted with some form of anti-theft device, that is to say, a mechanical, electrical or electronic immobiliser or a combination of these (in addition to any key operated switch normally used to start the engine) that prevents the vehicle being driven or moved under its own power.		This item shall not apply to a relevant vehicle which is not a Schedule 2 vehicle, if it was manufactured after 30th September 1998.
		<b>2.</b> No antitheft device shall operate on the braking system.		
		3. If any anti- theft device is, or incorporates, any mechanical device that acts upon a system that affects the control of the vehicle (eg the		

1	2	3	4	5
Item	Subject matter	Requirement	Definitions and supplementary provisions	Exemptions and modifications

steering control)

\_\_\_

- (a) it shall not be possible to start the engine in the normal way until every such mechanical device has been deactivated,
- (b) it shall
  not be
  possible
  to
  activate
  any
  such
  mechanical
  device
  while
  the
  engine
  is
  running,
  and
- (c) the action of activating any such mechanical device shall be distinct and separate from that of

1	2	3	4		5
Item	Subject matter	Requirem	sup	finitions and oplementary ovisions	Exemptions and modifications
			stopping the engine.		
9	Seat belts	belt fitted vehicle, in a harness passive be comply in requirement regulation of Constand Regulation extent (if a it would were the paragraph apply to a vehicles.  2. he will fitted will or more would belt seem to be the seem to be	belt or a elt, shall with the ents of 47(7) struction Use ns to the any) that l apply e said 7 to all motor  rehicle is eth one we belts, shall— bear a mark as described in regulation 47(c)(i) of the Construction and Use Regulations; or meet the requirements referred to in regulation 47(c)(iii) of those Regulations.	his item—  "adult belt" means a seat belt for an adult not being a disabled person's belt; "disabled person's belt", "lap belt" and "seat belt" have the same meanings as in regulation 47 of the Construction and Use Regulations; "harness belt"  (4) means an adult belt which is a harness belt comprising a lap belt and shoulder straps; "passive belt" means an	This item shall not apply to any non-bodied three wheeled vehicle.  This item shall not apply to a vehicle which is not a Schedule 2 vehicle, if it was manufactured after 30th June 1997.  This item shall not apply to an adult belt fitted to a vehicle, if the belt provides (8) level of safety equivalent to that provided by an adult belt which complies with the requirements of this item as they would otherwise apply to the belt but disregarding paragraph 2(b) and 3(b).
		<b>3.</b> If	the		

vehicle is fitted

are so located that

when used with

an adult belt of

Changes to legislation: There are outstanding changes not yet made by the legislation.gov.uk editorial team to The Motor Vehicles (Approval) (Amendment) Regulations 2004. Any changes that have already been made by the team appear in the content and are referenced with annotations. (See end of Document for details) View outstanding changes

1	2	3	4	5
Item	Subject matter	Requirement	Definitions and supplementary provisions	Exemptions and modifications
		with one or more harness belts, every such belt shall—	•	
		(a) bear a mark as described in regulatio (c)(ii) of the Construct and Use Regulation or	n 47(4) tion	
		(b) meet the requirem referred to in regulatio (c)(iv) of those Regulatio	n 47(4)	
10	Seat belt anchorages	1. The vehicle shall comply with the requirements of paragraph 4.3 of Annex I to Directive 76/115/EEC. For outboard seating positions other than in the front, two lower anchorages are allowed.  2. Without prejudice to paragraph 1, the vehicle shall be fitted with an	"adult belt", has the same meanings as in item 9; "disabled person's belt", has the same meanings as in regulation 47 of the Construction and Use	This item shall not apply to any non-bodied three wheeled vehicle.  This item shall not apply to a disabled person's vehicle which is not a Schedule 2 vehicle, except for those anchorages (8) ted after the manufacture of the vehicle.  Paragraph 3

required to hold

every

belt,

securely

adult

1	2	3	4	5
Item	Subject matter	Requirement	Definitions and supplementary provisions	Exemptions and modifications
		disabled person's belt or any part of an adult belt or a disabled person's belt fitted to the vehicle.  3. Every anchorage intended for an adult belt shall comply with the requirements of paragraphs 4.2,		a type for which they are intended to be used, if they provide a level of safety equivalent to that provided by anchorages that meet the requirements of that paragraph when used with an <b>adult belt</b> of a type for which they are intended.
		4.4 and 4.5 of Annex I to Directive 76/115/EEC, provided that for paragraph 4.4.1 there shall be substituted  "4.4.1. belt anchorage shall comply with the following		For motor caravans, ambulances and hearses, paragraph 1 shall apply only to seating positions where there is a seat intended for use while the vehicle is travelling on a road.
		requirements 4. The vehicle shall meet strength characteristics equivalent to those needed to satisfy the requirements of paragraph 5 of Annex I to Directive 76/115/EEC, as last amended by Directive 82/318.	itts	An armoured vehicle shall be exempted from any requirement of paragraph 1 if it can be demonstrated to the satisfaction of the Secretary of State that it is impossible for the vehicle to comply due to its special purpose.
11	Installation of seat belts		For the purposes of this item— "adult belt", "harness belt" and	This item shall not apply to any non-bodied three- wheeled vehicle.

1	2	3	4	5
Item	Subject matter	Requirement	Definitions and	Exemptions and
			supplementary	modifications
			provisions	
		<b>point belt</b> for	"passive	This item shall
		the driver's seat	belt" have	not apply to a
		and the specified	the same	relevant vehicle
		passenger seat (if	meanings as	which is not
		any).	in item 9;	a Schedule 2
		<b>2.</b> If the	"appropriate	vehicle, if it was
		vehicle has an	belt", in	manufactured
		effective date on	relation to	after 30th June
		or after 1st	a seat in	1997, except that
		April 1987, in	a vehicle,	this exemption
		addition to the	means—	shall not apply to a seat belt which
		seat belts required	(a) in a	has been fitted
		by paragraph 1	case where	to an anchorage
		above, it shall	the	during the course
		be fitted with		ræfna vehicle
		an <b>appropriate</b>	is	being adapted
		<b>belt</b> for every		to become a
		other forward-	as	disabled person's
		facing seat in the		newthicle.
		front alongside the	in	
		driver's seat, not	paragra	phe requirements
		being a specified	3.1.7	of paragraphs
		passenger's seat.	of	1, 2 and 3 shall
		<b>3.</b> If the	Annex	not apply in
		vehicle has an	1 to	relation to a
		effective date on		veeat fitted to a
		or after 1st		disabled person's
		April 1987, in	EEC	vehicle if the
		addition to the		vehicle is fitted
		seat belts required		edwith a disabled
		by paragraph 1	by	person's belt for
		and 2 above, it	90/628/	vehat seat.
		shall be fitted with a <b>harness</b>		Paragraph 2
		with a harness belt, a lap belt,	a	shall have effect
		a passive belt		sin relation to
		or a three-point	belt,	motor caravans,
		belt for every	a lap	ambulances and
		other <b>forward</b> -		hearses as if
		facing seat.		for "1st April
		<u> </u>	belt,	1987" there were
		4. Every adult	or a	substituted "1st
		belt and every	three-	October 1988".
		disabled person's	point	
		<b>belt</b> fitted to the	belt;	Paragraph 3
		vehicle shall be	and	shall have effect
		properly secured	(b) in any	in relation to
		to anchorages	other	motor caravans,

1	2	3	4	5
Item	Subject matter	Requirement	Definitions and supplementary provisions	Exemptions and modifications
		provided for it and installed so that it can be used properly to restrain an occupant (eg in the case of a lap belt by passing over the pelvic region and in the case of a harness belt, a passive belt or a three-point belt by also restraining the upper torso and not being liable to slip off the shoulder). Also, there shall be no sharp edges liable to cause abrasion or damage to the belts in normal use. In the case of every lap belt, passive belt and three-point belt, provision shall be made for their safe and convenient storage.	case, a harness belt, a passive belt or a three- point belt. "child restraint", "disabled person's belt", "forward- facing seat", "lap belt", "seat belt", "specified passenger's seat", and "three-point belt" have the same meanings as in regulation 47 of the Construction and Use	April 1987 there were substituted "1st April 1997"; and (b) there were added at the end the words "intended for use while the vehicle is travelling on a road".  An armoured vehicle shall be exempted from any requirement of paragraphs 1, 2 or 3 if it can be demonstrated to (8) e satisfaction of the Secretary of State that it is impossible for the vehicle to comply on account of its special purpose.

Regulations—

1	2	3	4	5
Item	Subject matter	Requirement	Definitions and supplementary provisions	Exemptions and modifications
			(i)	if
				the
				vehicle
				does
				not
				have
				a separate
				chassis,
				the
				date
				of
				manufacture
				of
				the
				integral
				chassis-
				body,
			(ii)	or if
			(11)	the
				vehicle
				has
				a
				separate
				chassis,
				the
				date
				of
				manufacture of
				the
				body
				or
				the
				chassis,
				whichever
				is
				the
				earlier;
			<i>a</i> × · · ·	or
			(b) in the	
			case	<b>X</b> 7
			of an other	
			vehic	
			the	,,,
			date	of
			aute (	~-

1	2	3	4	5
Item	Subject matter	Requirement	Definitions and supplementary provisions	Exemptions and modifications
			of the vehicle "Special purpose" has the same meaning as in item 6.	÷;
12	Brakes	shall comply wi the requiremen of paragraph 2 and 2.2 of Anna 1 of Directive 71/320/EEC last amended b Directive 85/64 EEC; but the application	device"—  (a) except in as relatio by to a 7/ vehicle in having of not as more for than three wheels the same aph 2.4 Direct 71/320 EEC as last amend 4.2 by Direct 88/194 in EEC; n and (b) in relatio to a vehicle having not e g than three	This item shall not apply to a relevant vehicle which is not a schedule 2 vehicle, if it was manufactured after 31st March 1995, except that this exemption shall not apply to the braking system of a disabled person's vehicle if it has been adapted.  The requirements rigin paragraph 1 for the driver to be ivable to operate by the service braking system while keeping edooth hands on the steering control, ivand the secondary braking system while keeping at least one hand on the steering in control, shall not apply to a disabled person's vehicle, so long as the vehicle is adapted for a disabled driver to enable him is, to control the

1	2	3	4		5
Item	Subject matter	Requirement	Def sup <sub>l</sub>	initions and plementary visions	Exemptions and modifications
			nsmission	has	steering at all
		whi		the	times while
			bles	same	operating either
			king		gbraking system.
		of n		as in	150
		less			liRaragraphs 1
		thai		2 to	to 4 shall not
		one		the	apply to vehicles
		whe		Annex	
			each	of Direction	more than three
		side of t		93/14/	wwwheels, if they
			ne icle,	93/14/ EEC;	comply with the requirements for
		in t		"brake	motor-tricycles
			nt of	efficiency"	in the following
		fail		means	provisions of
			part	maximum	Directive 93/14/
		of t	-	total brake	EEC—
			nsmission	force	(a) paragraph
		of t		expressed as	2.1 of the
		ser		a percentage	Annex;
			king;	of the	(b) paragraphs
		and	<u> </u>	maximum	2.2.4 to
		(c) para	aoranh	gross	2.2.8 of the
			1.5.1	weight;	Annex; and
		sha		"braking	(c) in the case
		app		device",	of vehicles
			f for	"control",	equipped
		the		"transmission	
		sen	tence	"service	lock
		ther	re	braking",	devices,
		wer		"secondary	Appendix
		sub	stituted	braking"	2 to the
		the		and "parking	Annex.
		Woi		braking",	In relation to
		"Th		have the	vehicles having
			dition	same	more than 3
			st be	meaning as	wheels, paragraph
		met		in Directive	5 (b) shall
			omatic	71/320/	have effect (in
		mea	ıns".	EEC as last	the case of a
		<b>2.</b> If	the	amended by	vehicle having a
		vehicle	is	Directive	secondary brake
		equipped wit	h an	85/647/	operated by a
		anti-lock de		EEC;	means other than
			nply	"in running	a foot control)
		with parag	-	order"	as if for "50kg"
		2.2.1.23	of	means—	and "70kg"
		20			=

1	2	3	4	5
Item	Subject matter	Requirement	Definitions and supplementary	
			provisions	
		71/320/EEC as	(a) with	1
		last amended by	all	were substituted
		Directive 88/194/	fluid	_
		EEC.	(suc	
		<b>3.</b> The vehicle	as oi	
		shall comply with	and .	In relation to
		the requirements	_	ne vehicles having
		of paragraphs		ant)not more than
		2.2.1.11.1 and		ssarthree wheels,
		2.2.1.11.2 of		he paragraph 5 shall cle have effect as if
		Directive 71/320/	to be	
		EEC as last	drive	
		amended by	with	,
		Directive 91/422/	the	and "25%"
		EEC.	fuel	respectively, for
		<b>4.</b> The	tank	
		secondary	full,	kg" there were
		<b>braking</b> and	and	substituted "40"
		service braking	havi	ng kg, if a control
		shall have the	a	other than a
		same control.	spare	e foot <b>control</b> is
		5. The brake	whee	el used to apply
		efficiency shall be	and	•
		not less than—	tool-	braking.
			kit;	
		(a) for the service		ringParagraph 7 shall
		braking	a	not apply to a
		8	drive	
		(i) in	weig 68kg	thing rakes acting on the city its rear wheels
		the	14	are fitted with an
		case	(c) not	anti-lock device
		of a		rwisænd were so fitted
				ringat the time of
			icle, any	its manufacture
		60%		
		or	or	exemption shall
		(ii) in		engerest apply to:
		the	"lateral	(i) an amateur-
		case	brake	built vehicle,
		of	distributio	n", (ii) a vehicle
		a	in relation	
		goo	ds to an axle,	
			icle means	registered vehicle,
		50%	the ratio	and (iii) a rebuilt
		(b) for the	(expressed	l vehicle.
		secondar	as a	.)
		seconuar	y percentage	<i>:)</i>

Item		3	4	5
	Subject matter	Requirement	Definitions and supplementary provisions	Exemptions and modifications
	Subject matter	brakin in the case when the servo- assista provide for the service braking (if any) fails and a force is applied to the control  (i) ir th ca o a pi ve 3 w th fa fa a is 5 o (ii) ir th ca a g	supplementary provisions  g of the lower to the higher of the braking forces transmitted nce by the tyres ed to the road surface for two wheels, on opposite sides of the vehicle on the same axle; "longitudinal brake distribution" means the ratio of the braking forces transmitted assenger by the tyres chicle, oby the tyres to the road surface then the braking forces transmitted assenger by the tyres chicle, oby the tyres to the road surface through the front and rear wheels respectively when the vehicle is in running order and being braked asse on a level	•

Document Generated: 2023-06-19

Changes to legislation: There are outstanding changes not yet made by the legislation.gov.uk editorial team to The Motor Vehicles (Approval) (Amendment) Regulations 2004. Any changes that have already been made by the team appear in the content and are referenced with annotations. (See end of Document for details) View outstanding changes

1	2	3	4		5
Item	Subject matter	Requirement	supp	nitions and plementary visions	Exemptions and modifications
		(c)	18%	"servo-	
			for	assistance"	
			the	means an	
			parking	energy	
			braking.	supply	
				which	
				supplements	
				the	
				muscular	
				energy of	
				the driver;	
				"total braking	
				force"	
				means the	
				total of the	
				braking	
				forces	
				transmitted	
				by the tyres	
				to the road	
				surface	
				when the	
				brakes are	
				applied.	
		6. The late	ral		
		brake	C		
		distribution the serv	for		
		braking shall—			
		(a) in			
		relati			
		to eac			
		steeri axle;			
		and			
		(b) for al			
		value			
		of to	tai		

breaking force and vehicle speed, be not less

1	2	3	4	5
Item	Subject matter	Requirement	Definitions and supplementary provisions	Exemptions and modifications

than 70%.

**7.** The longitudinal brake distribution for the service braking shall, for all values of total braking force, vehicle speed adjustment and settings (if any), greater than the ratio of the vertical forces transmitted to the road through the and rear front wheels respectively when the vehicle is in running order and being braked on a level surface.

**8.** The capacity of the braking device absorb and dissipate energy shall be sufficient ensure that all the required aspects of braking performance can maintained be under all normal operating conditions of the vehicle, including long hill descents, taking account of the vehicle's speed capability, weight and weight distribution.

1	2	3	4	5
Item	Subject matter	Requirement	Definitions and supplementary provisions	Exemptions and modifications
13	Noise and silencers		means the rotational speed at which maximum power is produced.	Paragraph 1 shall only apply to vehicles propelled by an internal combustion engine.
		(a) the		
		vehicle is held stationar on a level surface such that there is an unobstru area not less than 3 metres wide all around the vehicle; and		
		(b) the engine by which the vehicle is propelled	d	
		is run at a constant rotationa speed		

2 Suhiect matter	3 Requirement	4 Definitions and	5 Exemptions and
Subject mutter	пецинени	supplementary provisions	modifications
	of 3/4 S,	•	
	the noise measured at 0.5 metres from the exhaust outlet at 45 degrees to the axis of the outlet pipe in a horizontal plane, shall not exceed 101db(A).		
Glass in windscreens and other windows outside	The windows of the vehicle shall be fitted with glazing which complies with the requirements of regulations 31 and 32 of the Construction and Use Regulations to the extent (if any) that they apply to the vehicle. However, side screens may be constructed of safety glazing.	and (10) of the Construction and Use Regulations, the date of	The requirements of regulation 32(2) and (7) of the Construction and Use Regulations shall not apply to the glazing fitted to any window, if that glazing provides a level of safety equivalent to glazing which complies with the requirements set out in column 3 of this item.  (P) relation to a vehicle fitted with a near-side exterior mirror (in addition to the obligatory off-side exterior mirror) which meets the requirements of item 7 (rear-view mirrors), the requirements of regulation 32(10) of those
		(b) for all other purposes,	Regulations shall not apply to the
	Glass in windscreens and other windows	of 3/4 S, the noise measured at 0.5 metres from the exhaust outlet at 45 degrees to the axis of the outlet pipe in a horizontal plane, shall not exceed 101db(A).  Glass in windscreens and other windows outside  The windows of the vehicle shall be fitted with glazing which complies with the requirements of regulations 31 and 32 of the Construction and Use Regulations to the extent (if any) that they apply to the vehicle. However, side screens may be constructed of	Subject matter  Requirement  of 3/4 S, the noise measured at 0.5 metres from the exhaust outlet at 45 degrees to the axis of the outlet pipe in a horizontal plane, shall not exceed 101db(A).  Glass in windscreens and other windows outside  The windows of the vehicle shall be fitted with glazing which complies with the requirements of regulations 31 and 32 of the Construction and Use Regulations to the extent (if any) that they apply to the vehicle. However, side screens may be constructed of safety glazing.  For the purposes of this item, the Construction and Use Regulations to the extent (if any) that they apply to the vehicle. However, side screens may be constructed of safety glazing.  For the purposes of this item date on which a vehicle is first used were a reference to the date of which a vehicle is first used were a reference to its effective date.  For the purposes of this item defective date  "effective date "effective date" means—  (a) for the purposes of regulations, the date of manufacture of the vehicle or 31st March 1985, whichever is the earlier; (b) for all other

1	2	3	4	5
Item	Subject matter	Requirement	Definitions and supplementary provisions	Exemptions and modifications
			the date of manufacture of the vehicle; "safety glazing" has the same meaning as in regulation 32 of the	glazing fitted to any window every part of which is behind the driver.  In relation to any glass fitted in a window of (and armoured vehicle, the requirements of regulation 32(10) of those Regulations shall apply as if the values in column 4 of Table II of that regulation (minimum light transmission) were all 60%.
15	Seats and their anchorages	1. Every seat and seat back adjustment and displacement system provided shall incorporate a locking system which operates		This item does not apply to seats not intended for normal use while the vehicle is travelling on a road (including seats exempt

1	2	3	4	5
Item	Subject matter	Requirement	Definitions and supplementary provisions	Exemptions and modifications
		automatically in all positions provided for normal use and all seats, including those which can be tipped forward or have fold-down backs, shall lock automatically in their normal upright position.  2. The unlocking controls for displacement systems which facilitate access by passengers shall be accessible from outside the vehicle when the door is open. They shall be easily accessible, even to the occupant of the seat immediately behind the seat concerned if such a seat is designated as suitable for an adult.		from Directive 74/408/EEC as last amended by Directive 81/577/EEC).  This item does not apply to any seat designed for a disabled person, so long as such a seat is securely attached to the vehicle.
		3. Seats shall be constructed and firmly attached to the vehicle such that they and their anchorages comply with the design, construction and fitting requirements of paragraph 6.2 to Annex I of		

	<u> </u>	2		<i>-</i>
I Item	2 Subject matter	3 Requirement	4 Definitions and supplementary	5 Exemptions and modifications
			provisions	modifications
		Directive 74/408/ EEC.		
16	Tyres		Vehicles Tyres (Safety) Regulations 1994(5); "corresponding standard" shall be construed in accordance with regulation 13	Paragraph 1 shall not apply to a tyre fitted to a vehicle, if the tyre provides a level of safety equivalent to a tyre that meets the requirements of that paragraph.  Paragraph 2 shall not apply to a myre fitted to a vehicle, if the tyre provides a level of safety equivalent to that provided by a tyre that complies with the requirements of that paragraph so far as it relates to BS AU 144e-1988.  Paragraph 3(c) and (d) shall not apply to a tyre fitted to a vehicle for which information on the load capacity and speed capability have been separately provided.

size;

1	2	3	4	5
Item	Subject matter	Requirement	Definitions and supplementary provisions	Exemptions and modifications

- (b) construction type (eg radial ply);
- (c) load capacity; and
- (d) speed capability.
- **4.** Each tyre fitted to the vehicle shall be of a nominal size appropriate to the wheel to which it is fitted.
- 5. Tyres on the same axle shall be of the same nominal size and the same construction type. If radial tyres are fitted to the front axle, they shall also be fitted to the rear and if biasbelted tyres are fitted to the front axle, radial or bias-belted tyres shall be fitted to the rear.
- 6. Each wheel on each axle shall be equipped with a tyre which has a load capacity such that when the axle is loaded to its maximum permitted axle weight, the weight transmitted to the road surface by that tyre does not

1	2	3	4	5
Item	Subject matter	Requirement	Definitions and supplementary provisions	Exemptions and modifications
		exceed that load capacity.  7. The speed capability of all tyres fitted shall be not less than the maximum design speed of the vehicle.		
17	Interior fittings		the purposes of this item—  "air bag" means a flexible bag fitted to a vehicle and designed to be filled with gas under pressure in order to protect the driver or a front seat passenger in the event of a collision involving the front of the vehicle; "designated seating position" means a position where there is a seat designed for normal use while the vehicle is travelling	This item shall not apply to a goods vehicle.  This item shall not apply to any area inside a motor caravan, an ambulance or a hearse which is not inside the head impact zone for any designated seating position.  An armoured vehicle shall be exempted from any requirement of this item if it can be demonstrated to the satisfaction of the Secretary of State that it is impossible for the vehicle to comply due to its special purpose.  Paragraph 1 shall not apply to:  (a) the edges of any interior fitting (if there is a gap of less than 20

1	2	3	4	5
Item	Subject matter	Requirement	Definitions and supplementary provisions	Exemptions and modifications
		retract into the surface of the panel or become detached from the panel when a horizontal force of 40kg is applied to them.  3. The lower edge of the instrument panel which is within the specified zone shall be rounded to a radius of curvature of not less than 19mm, or if it is covered with non-rigid material, not less than 5mm.  4. The rearward and upward-facing parts of seat frames behind which there is a designated seating position, and which are within the head impact zone shall be both covered with non-rigid material and have a radius of curvature of not less than 5mm.  5. The handbrake control in the fully released position and the gear-lever control in any forward gear		modifications  mm wide between the edges); (b) any heating or ventilation grill element; or (c) any control mounted on the heating or ventilation grill element area; so long as they are blunted.  Paragraph 1 shall not apply to foot pedal controls.  Paragraphs 1 and 2 shall not apply to any switches, controls or associated equipment designed for the use by a disabled person and fitted in a disabled person's vehicle so long as any edges are blunted.  Paragraph 4 shall not apply to any seat designed for a disabled person and fitted in a disabled person's vehicle.
		position shall not have any radius of curvature of	height of the projection	(a) any floor- mounted

7			1	
1	2	3	4	5
Item	Subject matter	Requirement	Definitions and	Exemptions and
			supplementary	modifications
			provisions	
		less than 3.2mm	is not more	hand-brake
		on surfaces which	than half its	control if,
		can be contacted	width and	in the fully
		by a sphere of	its edges are	released
		165mm diameter.	blunted;	position,
		<b>6.</b> Shelves and	"special	no part of
		other similar items	purpose"	the control
		fitted below the	has the	is in the
		level of the	same	specified
		highest part of	meaning as	zone; or
		the instrument	in item 6;	(b) any hand-
		panel shall be	"specified	brake
			zone"	control
		that their supports	means	mounted on
		1	the zone	or under the
		have no protruding edges	which—	instrument
		and that all parts	(a) is	panel, if in
		facing into the	forward	l the fully
			of the	released
		vehicle present a surface not	transver	rse position,
		less than 25mm	plane	there is no
		high with edges	of the	possibility
		rounded to a	torso	of the
		radius of	referenc	ce occupants
		curvature of not	line	of the
		less than 3.2mm.	of the	vehicle
		This surface shall	manikir	n contacting it
		also be covered	as	in the event
		with <b>non-rigid</b>	defined	of a frontal
		material.	in	impact.
			paragra	ph
		7. On that part	2.5	Paragraph 7
		of the inner	and	shall not apply
		surface of the		ixo parts covered
		roof which is	1 of	with a <b>non-rigid</b>
		situated above or	Annex	material and
		forward of the	3 to	the hood-frames
		occupants and can		of convertible
		be contacted by		vehicles. For
		a sphere of 165mm	EEC	opening roofs,
		diameter, the		the requirements
		width of	amende	shall apply to
		projecting parts	by	parts, including
		made of <b>rigid</b>		devices for
		material, shall	90/630/	opening, closing
		not be less than	EEC	and adjusting the
		the length of their	with	roof, with the
		projection from	the	roof in the closed
		the surface and	manileir	nagition

manikinposition.

1	2	3	4	5	
Item	Subject matter	Requirement	Definition suppleme provision.	ntary mo	emptions and odifications
		their edges shall have a radius of curvature of not less than 5mm. Roof sticks or ribs made of rigid material with the exception of the header rail of the glazed surfaces and door frames, shall not project downwards by more than 19mm.	(b)	position@ar in the far rearmosthe designated seating and positionsha	agraph 1 (in so as it relates to surface of an rument panel) paragraph 2 Il not apply to vehicle if: it is fitted with air bags for the protection of the driver and the front seat passenger; and those air bags were fitted at the time the vehicle was manufacture except that this exemption shall not apply to: (i) an amateur- built vehicle, (ii) a vehicle manufacture in very low volume, (iii a vehicle manufacture using parts of a registered vehicle, and (iv) a rebuil vehicle.

1	2	3	4	5
Item	Subject matter	Requirement	Definitions and supplementary provisions	Exemptions and modifications
			78/632/ EEC.	/
18	External projections	shall not be fitted with any mascot, emblem or other ornamental object unless it complies with the requirements of regulation 53 of the Construction and Use Regulations.  2. The radius of curvature of all hard parts on or protruding from the external surface of the vehicle and which can be contacted by a sphere of 100 mm diameter, shall be not less than 2.5 mm.  3. Headlamp visors and rims shall not project more than 30 mm beyond the lens surface.  4. The ends of bumpers shall be turned inwards, or be recessed, or be integrated within the bodywork.  5. Handles, hinges, push	For the purposes of this item—  "extreme outer edge" has the meaning given by regulation 3 (2) of the Lighting Regulations modified so as to disregard the projection of handles, hinges, push buttons, fuel tank filler caps and windows; "external surface" of the vehicle means the outward facing surface at any height from the floor line up to a height of 2 metres from the horizontal surface on which the vehicle is	This item shall not apply to a goods vehicle.  Those parts of a motor caravan, ambulance or hearse other than the driver's cabin shall be exempted from any requirement of this item if it can be demonstrated to the satisfaction of the Secretary of State that it is impossible for the vehicle to comply due to its special purpose.  An armoured vehicle shall be exempted from any requirement of this item if it can be demonstrated to the satisfaction of the Secretary of State that it is impossible for the vehicle to comply due to its special purpose.  Paragraph 2 shall not apply to—
		buttons and fuel tank filler caps shall not project	standing; "floor line" has	(a) hard parts of a vehicle which are
		more than 40 mm from the external	the same meaning as	manufacture of plastic

unless

surface

in Directive

or rubber,

1	2	3	4	5	
Item	Subject matter	Requirement	Definitions and supplementary provisions		mptions and lifications
		they cannot under any circumstance project beyond the <b>extreme outer edge</b> of the vehicle, in which case they may project by up to 50 mm from the <b>external surface</b> . All handles shall be enclosed in a	74/483/ EEC. "hard parts" means those made of a material of hardness exceeding 60 shore A; "special purpose" has the	(b)	provided that they are flexible and are blunted; parts which protrude by less than 5.0 mm but by not less than 1.5 mm, if the outward facing
		protective surround or be recessed, unless they cannot in any circumstances project beyond the extreme outer edge of the vehicle.	same meaning as in item 6; "vehicle body plan- form" means the area resulting from a	(c)	angles of such parts are blunted and any parts which protrude by less than 1.5 mm; grills such as air
		6. The open ends of door handles which rotate parallel to the plane of the door shall be turned back towards the plane of the door. Such open ends shall be directed rearwards unless the handles cannot under	vertical projection of the complete body onto a horizontal surface; and, for the purposes of this definition- "complete		intakes, having gaps of not more than 40 mm but more than 25 mm, if they have radii of curvature of not less than 1 mm; and those
		any circumstances project beyond the <b>extreme outer edge</b> of the vehicle and at least one of the following requirements is met—  (a) the	body" means all parts of the bodywork and chassis, including any separate wheel- guards, but does not include		having gaps of not more than 25 mm but more than 10 mm, if they have radii o curvature of not less than 0.5 mm; and those
		open end of the handle	running gear, such as wheels,		having gaps of not more than 10 mm

handle

axles,

1	2	3	4	5	
Item	Subject matter	Requirement	Definitions and supplementary provisions		emptions and difications
		is shielded to the front by a protective surround	steering.	(d)	if they are blunted; wind screen, head lamp and rear window wiper
		or (b) the open end of the			blades and supports, provided that they are blunted;
		handle is recessed into the vehicle bodywor		(e)	fixing holes or recesses of less than 12mm diameter, provided that they are
		(c) the gap measure laterally between the open end of the handle and the vehicle body is no more than 2 mm when the		(f)	blunted; wheels, so long as: (i) there are no pointed or sharp features which project beyond the external plane of the wheel rim;
		handle is in its normal position with the door latched.			(ii) no wing nuts are fitted; and (iii) there
		7. The open ends of handles, which pivot outwards in any			are no projection above the horizontal

l Item	2 Subject matter	3 Requirement	4 Definitions and	5 Exemptions and
	V	•	supplementary provisions	modifications
		direction, shall		plane
		face either		passing
		rearwards or		through
		downwards,		the
		unless they have		axis of
		an independent		rotation
		return mechanism		of the
		and cannot project		wheels,
		more than 15 mm		and
		from the external		beyond
		surface should the		the
		return mechanism		vehicle
		fail.		body
		8. Windows,		plan
		which open		form,
		outwards from the		apart
		external surface		from
		of the vehicle,		tyres
		shall have no		and
		forward facing		wheel
		C		discs,
		exposed edge and shall not		(includ
				central
		project beyond		wheel
		the extreme outer		securin
		edge of the vehicle.		nuts)
		venicie.		if the
		<b>9.</b> No jacking		latter
		bracket shall		have a
		project by more		radius
		than 10 mm		of
		beyond the		curvatu
		vertical projection		of not
		of the <b>floor</b>		less
		line lying directly		than
		above it.		30
		10 N. 1.		mm
		10. No exhaust		and
		pipe shall project		do not
		by more than 10		project
		mm beyond the		by
		vertical projection		more
		of the <b>floor</b>		than
		line lying directly		30
		above it, unless		mm
		it terminates in		beyond
		a rounded edge		the
		having a radius		vehicle
				VEIIII

1	2	3	4	5	
Item	Subject matter	Requirement	Definitions and supplementary provisions		emptions and difications
		of curvature of no less than 2.5 mm.			plan- form;
				(g)	sheet metal edges if they are folded back by about 180 degrees;
				(h)	folds in body
				(i)	panels; lateral air or rain deflectors, if their edges which are capable of being directed outwards have a radius of curvature of not less than
				(j)	1 mm; radio aerial shafts; provided that they are fitted with a fixed end capping of not less than 2.5mm radius; and
				(k)	in the case of any other vehicle any part of the external surface (including without prejudice to the generality of this

paragraph

1	2	3	4	5
Item	Subject matter	Requirement	Definitions and supplementary provisions	Exemptions and modifications
			provisions	cosmetic features such as trim and badges) of the vehicle as originally manufactured or as subsequently altered in amanner approved by the manufacturer, which are blunted and which it is not reasonably practicable
				to remove, except that this
				exemption shall
				not apply to:
				(i) an amateur- built vehicle,
				(ii) a vehicle manufactured in very low volume,
				(iii) a vehicle manufactured using parts of a registered vehicle, and
				(iv) a rebuilt vehicle.
19	Speed-ometers	shall be fitted with a speedomete capable capable indicating speed	er speed" has the of meaning given in regulation 3(2) of at the Construction	This item shall not apply to vehicles having a <b>maximum speed</b> of less than 25 mph.

not exceeding 20 Regulations.

1	2	3	4	5
Item	Subject matter	Requirement	Definitions and supplementary provisions	Exemptions and modifications
		mph at all speeds up to the maximum speed of the vehicle and capable of being read by the driver at all times of the day or night.		
		2. For all true speeds up to the design speed of the vehicle, the true speed shall not exceed the indicated speed.		
		3. For all true speeds of between 25 mph and 70 mph (or the maximum speed if lower), the difference between the indicated speed and the true speed shall not exceed—		
		V/10 + 6.25 mph where $V =$ the true speed of the vehicle in mph.		
20	Wiper and washer system	1. The vehicle shall be fitted with one or more wipers which when switched on, operate automatically to clear the windscreen of water, so that the driver has an adequate view of the road ahead, both directly in front of the vehicle and in front of both sides		This item shall not apply to a goods vehicle.  This item shall not apply to vehicles not equipped with a windscreen through which the driver must look to obtain an adequate view of the road ahead, both directly in front of the vehicle and in

1	2	3	4	5
Item	Subject matter	Requirement	Definitions and supplementary provisions	Exemptions and modifications
		of the vehicle, in wet weather.  3. The wiper or wipers shall		front of both sides of the vehicle, from all normal seating positions.
		have at least one operating frequency at which it or they shall operate continuously at no		
		less than 45 cycles per minute.		
		3. The wiper blade or blades shall return automatically to a position of rest which shall be		
		at or beyond the outer edge of the area swept by the wiper and shall be capable		
		of being displaced from this position on the windscreen to allow for windscreen cleaning.		
		4. The vehicle shall be fitted with a windscreen washer system capable of cleaning, in conjunction with		
		the wiper or wipers, the area of windscreen swept by the wiper or wipers.		
		<b>5.</b> When this system is actuated with the nozzles plugged, it shall		

be capable of

I Item	2 Subject matter	3 Requirement	4 Definitions and supplementary provisions	5 Exemptions and modifications
		pressures produced.  6. The capacity of the liquid reservoir for this system shall not be less than 1 litre.		
21	Defrosting and demisting system	1. The vehicle shall be equipped with a system for removing frost and ice from the glazed surfaces of the windscreen. This system shall be effective enough to ensure that the driver has an adequate view of the road ahead, both directly in front of the vehicle and in front of both sides of the vehicle, in cold weather.  2. The vehicle shall be equipped with a system for removing mist from the interior glazed surface of the windscreen. This system shall be effective enough to ensure that the driver has an adequate view of the road ahead, both directly in front of the vehicle and in front of both sides of the vehicle, in		This item shall not apply to a goods vehicle.  This item shall not apply to vehicles not equipped with a windscreen through which the driver must look to obtain an adequate view of the road ahead, both directly in front of the vehicle and in front of both sides of the vehicle, from all normal seating positions.

1	2	3	4	5
Item	Subject matter	Requirement	Definitions and supplementary provisions	Exemptions and modifications
		wet and humid weather.		
22	Fuel input	The vehicle shall be fitted with a fuel tank so constructed that it cannot readily be filled from a petrol pump delivery nozzle which has an external diameter of not less than 23.6mm without the aid of a device (such as a funnel) not fitted to the vehicle.		This item shall not apply to vehicles to which paragraph 2(c) or (d) in column 3 of item 4 (exhaust emissions) do not apply.
23	Design weights	1. The maximum gross weight of the vehicle shall be no less than the sum of the kerbside weight, and—  (a) in the case of a vehicle other than a motor caravan, 75kg for each seat, and  (b) in the case of a motor caravan, 85kg for each seat and 10kg for each	For the purposes of this item— "seat" means any seat, including the driver's seat, designed for use while the vehicle is travelling on the road.	This item shall not apply to a goods vehicle.

Document Generated: 2023-06-19

Changes to legislation: There are outstanding changes not yet made by the legislation.gov.uk editorial team to The Motor Vehicles (Approval) (Amendment) Regulations 2004. Any changes that have already been made by the team appear in the content and are referenced with annotations. (See end of Document for details) View outstanding changes

1	2	3	4	5
Item	Subject matter	Requirement	Definitions and supplementary provisions	Exemptions and modifications
		metre of the total lengtl of the vehic	1	
		<b>2.</b> For vehicles—	all	
		(a) the su of the maxin permit axle weigh must not be less than t maxin gross weigh of the vehic	mum itted  its  e  he mum it	
		(b) when the vehic is loade to its maxin gross weigh by placir a weigh of 68l in each seat and b distril the remain weigh	le d mum nt ng nt kg ch y puting ning	

areas

1	2	3	4	5
Item	Subject matter	Requirement	Definitions and supplementary provisions	Exemptions and modifications
		design	ed	
		to		
		accom	modate	
		luggag	ge	
		(all in		
		accord	ance	
		with		
		paragr		
		2 of th		
		Appen	dix	
		to		
		Direct		
		92/21/		
		EEC		
		as last		
		amend		
		by		
		Direct		
		95/48/		
		EC),		
		the axl		
		weight	_	
		of eacl axle	1	
		shall		
		not		
		exceed	1	
		the	ı	
		maxim	nıım	
		permit		
		axle	tea	
		weight	:	
		and	,	
		(c) when the		
		vehicle		
		is	5	
		loaded		
		to its		
		to its		

maximum gross weight, and at the same time, its rear axle is

1	2	3	4	5
Item	Subject matter	Requirement	Definitions and supplementary provisions	Exemptions and modifications
		loaded		
		to its		
		maxim		
		permit	ted	
		axle		
		weight	,	
		the		
		front		
		axle		
		weight		
		shall		
		not be		
		less		
		than		
		30%		
		of the		
		maxim	um	
		gross		
		weight	•	
24	General vehicle construction	<b>1.</b> All aspec of the design an		

construction of the vehicle and its equipment which are not covered by other subject matters in this Schedule, shall be such that danger is caused or likely to be caused to any person in the vehicle or on a road.

2. In particular, under all normal conditions likely to be encountered while the vehicle is being driven on a road, including when the vehicle is loaded to its maximum gross weight and the axle weight of any

1	2	3	4	5
Item	Subject matter	Requirement	Definitions and supplementary provisions	Exemptions and modifications
		one axle equals its maximum permitted axle weight—		
		(a) it shall be possible to control the		

account
of the
vehicle's
speed
and
acceleration
capabilities;

vehicle safely, taking

- (b) it shall at all times be possible for the driver, while controlling the vehicle, to have a full view of the road and traffic ahead of the vehicle;
- (c) the clearance between any of the following parts of the

Document Generated: 2023-06-19

Changes to legislation: There are outstanding changes not yet made by the legislation.gov.uk editorial team to The Motor Vehicles (Approval) (Amendment) Regulations 2004. Any changes that have already been made by the team appear in the content and are referenced with annotations. (See end of Document for details) View outstanding changes

1	2	3	4	5
Item	Subject matter	Requireme		nd Exemptions and
		V	ehicle,	
			amely	
		th	ne	
			yres,	
			heels,	
			ther	
			otating	
			omponents	
			ssociated	
			vith the	
			ansmission	
		O		
			ngine	
			ower	
		01		
			raking,	
			noveable	
	parts of the			
			teering	
			nechanism	
			nd	
			ixed	
			arts	
			hall be	
			ufficient	
		to		
			nsure	
		ne		
		ri	sk of	
		fo	ouling	
		aı	nd the	
		W	heels	
			nd	
			heel	
		fi	xings	
			hall be	
		CO	ompatible;	
		(d) th	ne	
		V	ehicle	
			tructure	
		(0	chassis	
		OI	r	
			ntegral	
		cl	hassis-	

body), shall be so

1	2	3		4	5
Item	Subject matter	Requireme	nt	Definitions and supplementary provisions	Exemptions and modifications
		de	esigned		
		ar			
			onstructe	ed	
			to		
			ithstand		
		th	e orces		
		ar			
			bration		
		to			
			hich it		
		is	likely		
			be		
		su	ıbject;		
		(e) al	1		
		er	ntries		
		ar			
			kits		
			ovided		
			or the chicle		
			ecupants	•	
			ther	•	
			an		
			oors)		
			nall		
			e so		
			esigned		
			to		
			low		
			isy id safe		
			se;		
		(f) al			
			perture		
			overs		
			ther		
			an		
			oors)		
		in	cluding		
		ta			
			ites,		
		bo ar	oot		
			onnet		
			ds,		
			as, all be		
			nahla		

capable

l Item	2 Subject matter	3 Requirement	4 Definitions and supplementary provisions	5 Exemptions and modifications
		of be secu latch in th fully close posi	eing rely ned ne	
		axle and whe shal be so desi cons and fitte as to with the force and	ension, s els l o gned, structed d o sstand es ation ch are	
		the fank shal be so desi, cons and fitte towing the force vibrand	em, uding fuel fuel o gned, structed d as thstand	

1	2	3	4	5
Item	Subject matter	Requirement	Definitions and supplementary provisions	Exemptions and modifications
		environi		
		to		
		which it		
		is likely		
		to be		
		subject.		
		It shall		
		also be		
		so fitted		
		as to		
		avoid		
		the		
		risk of		
		damage,	,	
		such as		
		abrasion	l,	
		due to		
		fouling		
		of other		
		parts,		
		and to minimis	0	
		the risk	е	
		of fire		
		in the		
		event		
		of any		
		leakage		
		of fuel.		
		The		
		fuel		
		tank		
		shall		
		comply		
		with		
		regulation	on 39	
		of the		
		Constru	ction	
		and Use		
		Regulati	ions,	
		except		
		that it		
		need		
		not be		
		made of	•	
		metal;		
		and		

Document Generated: 2023-06-19

Changes to legislation: There are outstanding changes not yet made by the legislation.gov.uk editorial team to The Motor Vehicles (Approval) (Amendment) Regulations 2004. Any changes that have already been made by the team appear in the content and are referenced with annotations. (See end of Document for details) View outstanding changes

1	2	3	4	5
Item	Subject matter	Requirement	Definitions and supplementary provisions	Exemptions and modifications
		(i) the		
		electric	al	
		system,		
		includii	ng	
		the		
		battery,		
		electric		
		compoi	nents	
		and		
		wires, shall be		
		securely attache		
		to the	u	
		vehicle		
		In	•	
		particul	ar.	
		the	,	
		maximi	ım	
		distance		
		between	n	
		attachm	nents	
		of		
		wires,		
		except		
		those		
		contain	ed	
		within		
		hollow		
		compor	ients,	
		shall		
		be 300	1	
		mm and wires	1	
		shall be		
		so fitte		
		and	•	
		protecte	ed	
		as to		
		avoid		
		the		
		risk of		
		damage	<b>;</b>	
		to		
		insulati	on,	
		such as		
		abrasio	n.	
		All		

components

1	2	3	4	5
Item	Subject matter	Requirement	Definitions and supplementary provisions	Exemptions and modifications
		shall be so construct and fitted as to minimise the risk of corrosior and fire.	ted	
25	Plate for goods vehicles	Every goods vehicle shall comply with the requirements of paragraphs (2) and (3) of regulation 66 of the Construction and Use Regulations.		For the purpose of this item—  The Construction and Use Regulations shall have effect as if for the reference to 6mm in paragraph 5 of part III of Schedule 8, there were substituted a reference to 4mm.

## SCHEDULE 2

Regulation 5(!)(b)

## APPROVAL REQUIREMENTS FOR RELEVANT VEHICLES EXCEPT SCHEDULE 2 VEHICLES (REPLACING SCHEDULE 4)

## **Commencement Information**

I13 Sch. 2 in force at 1.4.2004, see reg. 1

l Item	2 Subject matter		3 Design, construction and equipment requirements			5 Exemptions and arymodifications
		(a) Date of manufacture of the vehicle	(b) Community Instrument	(c) ECE Regulation	provisions	
3	Protective steering					If any vehicle has been adapted from a vehicle, the effect of which is to change the category of the vehicle, then it shall be sufficient to show compliance either with the protective steering requirements for the category of the unadapted vehicle, or of the adapted vehicle.  If (i) a disabled person's vehicle has been adapted from a vehicle; and (ii) the reason for the adaptation is to enable

1	2	3			4	5
Item	Subject matter	Design, cons requirements	truction and e	equipment	Definitions and supplementa provisions	Exemptions and arymodification.
		(a)	(b)	(c)	•	
		Date of	Community	ECE		
		manufacture of the vehicle	Instrument	Regulation		

person to drive the vehicle or travel as a passenger in it; then the requirements of this item shall not apply, but only insofar as the adaptation prevents the disabled person's vehicle from complying with any of the requirements of this item.

a disabled

1st July	Directive	ECE
1991	74/297/	Regulation
	EEC,	12.01,
	annex 1,	paragraphs
	paragraphs	5 and 6
	5 and 6	
1st October	Directive	ECE
1996	74/297/EEC	Regulation
	as amended	12.03,
	by Directive	paragraphs
	91/662/	5 and 6
	EEC,	
	annex 1,	
	paragraphs	
	5 and 6	

4 Exhaust emissions

If any vehicle has been

Changes to legislation: There are outstanding changes not yet made by the legislation.gov.uk editorial team to The Motor Vehicles (Approval) (Amendment) Regulations 2004. Any changes that have already been made by the team appear in the content and are referenced with annotations. (See end of Document for details) View outstanding changes

1	2	3			4	5
Item	Subject matter	Design, cons requirements	truction and e	quipment	Definitions and supplementa provisions	Exemptions and crymodifications
		(a)	<i>(b)</i>	(c)	-	
		Date of	Community	ECE		
		manufacture of the vehicle	Instrument	Regulation		

from a vehicle, the effect of which is to change the category of the vehicle, then so long as the adaptation has not been to a system which would directly affect the amount of exhaust emissions emitted from the vehicle, it shall be sufficient to show compliance either with the exhaust emission requirements for the category of the unadapted vehicle, or of the adapted vehicle.

adapted

If the exhaust

1	2	3			4	5
Item	Subject matter	Design, cons requirements	truction and e	equipment	Definitions and supplementa provisions	Exemptions and arymodification.
		(a)	<i>(b)</i>	(c)	•	
		Date of	Community	ECE		
		manufacture of the vehicle	Instrument	Regulation		

system of any vehicle has been adapted (as permitted below), then the requirements of this item shall be deemed to be met, so long as the unadapted vehicle complied with the relevant emission requirements for that category of vehicle before it was adapted.

Any adaptation to an exhaust system of a vehicle shall be permitted so long as:

(i) any
adaptation
is
down
stream
of any
emission

1	2	3			4	5
Item	Subject matter	Design, cons requirements	truction and e	equipment	Definitions and supplementa provisions	Exemptions and crymodification.
		(a) Date of manufacture	(b) Community Instrument	(c) ECE Regulation		
		of the vehicle				control

device fitted to the vehicle; and (ii) the emission control device is identical to that which would have been fitted had the vehicle not been adapted.

1st January 1993	Directive 70/220/EEC as amended by: Directive 91/441/ EEC, annex 1, paragraphs 5, 7 and 8 (applies only to passenger cars)	ECE Regulation 83.01, paragraphs 5, 8 and 13	For the purposes of this item— "pas car" mean a moto vehic whice (a)	senger  or cle ch is constructed or adapted to carry
				passengers and

1	2	3			4	5
Item	Subject matter	Design, cons requirements	truction and e	quipment	Definitions and supplementa provisions	Exemptions and arymodification
		(a)	<i>(b)</i>	(c)	-	
		Date of	Community	ECE		
		manufacture of the vehicle	Instrument	Regulation		

is not a goods vehicle;

- vehicle;
  (b) \*
  has
  no
  more
  than
  6
  seats
  including
  the
  driver's
  seat;
  and
- (c) has
  a
  maximum
  gross
  weight
  not
  exceeding
  2,500
  kg.

\*Note: paragraph (b) does not apply to vehicles manufactured after 1st January 2001.

1st October Directive ECE
1994 93/59/EEC, Regulation
annex 1, 83.01,
paragraphs
5, 7 and 5, 8 and 13
8 (applies

l Item	2 Subject matter	3 Design, cons requirements	truction and e	equipment	4 5 Definitions Exemptions and and supplementarymodification provisions	
		(a) Date of manufacture of the vehicle	(b) Community Instrument	(c) ECE Regulation		
			only to vehicles other than passenger cars)			
		1st January 1997	Directive 94/12/EC, annex 1, paragraph 5 (applies only to passenger cars)	ECE Regulation 83.02, paragraph 5		
		1st October 1997	Directive 96/69/EC, annex 1, paragraph 5 (applies from this date to Class I vehicles)	ECE Regulation 83.03, paragraph 5	"Reference mass" has the same meaning as in Directive 70/220/EEC, as amended by Directive 96/69/EC. "Class I vehicle means a goods vehicle (catego N1) which has a reference mass a goods as a reference means a goods which has a reference means a goods which has a reference means a goods which has a reference means a reference means a goods which has a g	g ve ed ve

l Item	2 Subject matter	3 Design, cons requirements	truction and e	equipment	4 Definitions and supplementa provisions	5 Exemptions and arymodifications	
		(a) Date of manufacture of the vehicle	(b) Community Instrument	(c) ECE Regulation			
			Directive 96/69/EC, annex 1, paragraph 5 (applies from this date to vehicles of category M1 other than passenger cars, Class II and Class III vehicles)		mass not exceedi 1,250kg (1,305 kg from 1st January 2001). "Class II vehicle means a goods vehicle (catego N1) which has a referen mass exceedi 1,250 kg (1,305 kg from 2001) but not	ry ce	
					exceedi 1,700 kg (1,760 kg from 2001). "Class III		

vehicle"

l Item	2 Subject matter		3 Design, construction and equipment requirements			5 Exemptions and rymodifications
		(a) Date of manufacture of the vehicle	(b) Community Instrument	(c) ECE Regulation	provisions	
		1st October 1999	Directive 98/77/EC, annex 1, paragraph 5 (applies to vehicles fuelled by liquid petroleum gas or compressed natural gas)	ECE Regulation 83.04, paragraph 5	means a goods vehicle (categor N1) which has a reference mass exceedin 1,700 kg (1,760 kg from 2001).	ce
		1st January 2001	Directive 98/69/EC, annex 1, paragraph 5 (Phase I limits) (applies from this date to passenger cars and			

l Item	2 Subject matter	3 Design, cons requirements	truction and e	quipment	4 Definitions and supplementa provisions	5 Exemptions and erymodifications
		(a) Date of manufacture of the vehicle	(b) Community Instrument	(c) ECE Regulation		
			Class I vehicles)			
		1st January 2002	Directive 98/69/EC, annex 1, paragraph 5 (Phase 1 limits) (applies from this date to vehicles of category M1 other than passenger cars, Class II and Class III vehicles)			
		1st January 2003	Directive 98/69/EC, annex 1, paragraph 5 (Phase 1 limits) (applies from this date to diesel passenger vehicles. Until this date, diesel passenger vehicles are treated as a vehicle of category N1)		"Diesel passeng vehicle means a vehicle of categor M1 the maximu mass of which exceeds 2,000 kg, fitted with a compre ignition engine, and	ger y um ssion

Changes to legislation: There are outstanding changes not yet made by the legislation.gov.uk editorial team to The Motor Vehicles (Approval) (Amendment) Regulations 2004. Any changes that have already been made by the team appear in the content and are referenced with annotations. (See end of Document for details) View outstanding changes

1	2	3		4	5	
Item	Subject matter	Design, construction and equipment requirements			Definitions Exemption and and supplementarymodificati provisions	
		(a)	(b)	(c)	•	
		Date of	Community	ECE		
		manufacture of the vehicle	Instrument			

which

is:

(a) constructed or adapted to carry more than 6 occupants including the driver, or

(b) an off-road vehicle as defined in Annex II to the 1970 Directive.

1st January Directive
2006 98/69/EC
annex 1,
paragraph
5 (Phase
2 limits)
(applies
from this
date to
passenger
cars and
Class I
vehicles)

I Item	2 Subject matter	3 Design, construction and equipment requirements			4 Definitions and supplementa provisions	5 Exemptions and crymodifications
		(a) Date of manufacture of the vehicle	(b) Community Instrument	(c) ECE Regulation		
0		1st January D 2007 99 an po 5 2 (a fr da vo ca of	Directive 98/69/EC annex 1, paragraph 5 (Phase 2 limits) (applies from this date to vehicles of category M1 other than passenger cars, Class II and Class III vehicles)			
8	Anti-theft devices	1st October 1998	Directive 74/61/EEC, as amended by: Directive 95/56/EC, annex V (electronic immobiliser) and annex VI (alarm system if fitted).	ECE Regulation 18.02, paragraph 7 and ECE Regulation 97.01 paragraphs 5, 6 and 7 (alarm system) and paragraphs 31, 32 and 33 (immobiliser)		
10	Seat belt anchorages	1st July 1991	Directive 76/115/EEC as amended by: Directive 82/318/EEC, annex 1, paragraphs 4 and 5	ECE Regulation 14.02, paragraphs 5, 6 and 7		In the case of a seat belt anchorage fitted to a seating position of a disabled person's vehicle after the

11

Changes to legislation: There are outstanding changes not yet made by the legislation.gov.uk editorial team to The Motor Vehicles (Approval) (Amendment) Regulations 2004. Any changes that have already been made by the team appear in the content and are referenced with annotations. (See end of Document for details) View outstanding changes

1	2	3		4		5
Item	Subject matter	Design, cons requirements	truction and e	quipment	Definitions and supplementa provisions	Exemptions and arymodification
		(a)	<i>(b)</i>	(c)		
		Date of	Community	ECE		
		manufacture of the vehicle	Instrument	Regulation		

manufacture of the vehicle, for the requirements of this item, shall be substituted the requirements in item 10 of Schedule 3.

If any vehicle has been adapted to a vehicle of category M1, for the requirements of this item shall be substituted the requirements in item 10 of Schedule 3.

	1st July 1997	Directive 90/629/ EEC, annex 1, paragraphs 4 and 5	ECE Regulation 14.03, paragraphs 5, 6 and 7	
Installation of seat belts	1st July 1997	Directive 77/541/EEC as amended by: Directive		This item shall not apply to a seat belt, fitted to an

I Item	2 Subject matter	3 Design, consrequirements	struction and e	equipment		5 Exemptions and arynodifications
		(a) Date of manufacture of the vehicle	(b) Community Instrument	(c) ECE Regulation	provisions	
			90/628/ EEC, annex 1, paragraphs 3.1 to 3.1.9 and 3.2.1 to 3.2.2.4	EEC, annex 1, paragraphs 3.1 to 3.1.9 and 3.2.1 to		anchorage that has been fitted to a disabled person's vehicle during the course of it being adapted to become a disabled person's vehicle.
		1st October 1999	Directive 96/36/EC, annex 1, paragraphs 3.1 to 3.1.10, 3.1.11, 3.1.12 and 3.2.1 to 3.2.2.5	ECE Regulation 16.04, (Supplement 8) paragraphs 8.1 to 8.1.10.3, 8.1.11 to 8.1.12 and 8.2.1 to 8.2.2.5.2		
12	Brakes	1st April 1995	Directive 71/320/EEC as amended by: Directive 91/422/ EEC, annex 1, paragraph 2	ECE Regulation 13.06 paragraph 5		If any vehicle has been adapted from a vehicle, the effect of which is to change the category of the vehicle, then so long as the adaptation has not been

I Item	2 Subject matter	3 Design, construction and equipment requirements			4 5 Definitions Exemptions and and supplementarymodification provisions	
		(a) Date of manufacture of the vehicle	(b) Community Instrument	(c) ECE Regulation		
						to a system which would directly affect the brakes, it shall be sufficient to show compliance either with the brake requirements for the category of the unadapted vehicle, or of the adapted vehicle.
		1st October 1999	Directive 98/12/EC, annex 1, paragraph 2.1.1.3 (Requiremen for asbestosfree brake linings only)		S	If the braking system of a disabled person's vehicle has been adapted so as to enable a disabled person to drive the vehicle, then the requirements of this item shall not apply to any such

adaptation.

l Item	2 Subject matter		3 Design, construction and equipment requirements			5 Exemptions and crymodifications
	* *	(b) Community Instrument	(c) ECE Regulation			
		31st March 2001	98/12/EC, annex 1, paragraph 2 (All requirements)	ECE Regulation 13.09, paragraph 5 or ECE )Regulation 13H, paragraph 5 (All requirements)		
13	Noise and silencers					If any vehicle has been adapted from a vehicle, the effect of which is to change the category of vehicle, then so long as the adaptation has not been to a system which would directly effect the amount of noise emitted from the vehicle, it shall be sufficient to show compliance either with the requirements

Changes to legislation: There are outstanding changes not yet made by the legislation.gov.uk editorial team to The Motor Vehicles (Approval) (Amendment) Regulations 2004. Any changes that have already been made by the team appear in the content and are referenced with annotations. (See end of Document for details) View outstanding changes

1	2	3			4	5	
Item	Subject matter	Design, construction and equipment requirements			Definitions and supplementa provisions	Exemptions and crymodifications	
		(a)	<i>(b)</i>	(c)	•		
		Date of	Community	ECE			
		manufacture of the vehicle	Instrument	Regulation			

for the category of the unadapted vehicle, or of the adapted vehicle.

If the exhaust system of any vehicle has been adapted (as permitted below), then the requirements of this item shall be deemed to be met, so long as the unadapted vehicle complied with the relevant noise and silencer requirements for that category of vehicle before it was adapted.

Any adaptation to an

1	2	3			4	5
Item	Subject matter	Design, construction and equipment requirements			Definitions Exemption and and supplementarymodification provisions	
		(a)	(b)	(c)	-	
		Date of	Community	ECE		
		manufacture of the vehicle	Instrument	Regulation		

exhaust system of a vehicle shall be permitted so long as:

- (i) any
  adaptation
  is
  downstream
  of any
  emission
  control
  device
  fitted
  within
  the
  system;
  and
- (ii) the emission control device and silencer are identical those which would have been fitted had the vehicle not been adapted.

1st July Directive ECE 1991 70/157/EEC Regulation as amended

90

I Item	2 Subject matter	3 Design, construction and equipment requirements			4 5 Definitions Exemptions and and supplementarymodifications provisions	
		(a) Date of manufacture of the vehicle	(b) Community Instrument	(c) ECE Regulation		
				51.01, paragraph 5		
		1st January 1997	Directive 92/97/EEC or Directive 96/20/EC, annex 1, paragraph 5	ECE Regulation 51.02, paragraph 5		
26	Carbon dioxide emissions and fuel consumption	1st January 1997	Directive 80/1268/ EEC as amended by: Directive 93/116/EC, annex 1, paragraph 5	ECE Regulation 101, paragraph 5		If any vehicle has been adapted from a vehicle, the effect of which is to change the category of vehicle, then so long as the adaptation has not been to a system which would directly affect the carbon dioxide emissions emitted from the vehicle or its fuel consumption, it shall be

1	2	3			4	5	
Item	Subject matter	Design, construction and equipment requirements			Definitions and supplementa provisions	Exemptions and arymodifications	
		(a)	<i>(b)</i>	(c)	-		
		Date of	Community	ECE			
		manufacture of the vehicle	Instrument	Regulation			

sufficient to show compliance either with the carbon dioxide emissions and fuel consumption requirements for the category of the unadapted vehicle, or of the adapted vehicle.

If the exhaust system of any vehicle has been adapted (as permitted below), then the requirements of this item shall be deemed to be met, so long as the unadapted vehicle complied with the relevant carbon dioxide emission

Changes to legislation: There are outstanding changes not yet made by the legislation.gov.uk editorial team to The Motor Vehicles (Approval) (Amendment) Regulations 2004. Any changes that have already been made by the team appear in the content and are referenced with annotations. (See end of Document for details) View outstanding changes

2	3			4	5
Subject matter	_		Definitions Exemptio and and supplementarymodificat provisions		
	(a)	<i>(b)</i>	(c)	-	
	Date of	Community	ECE		
	of the	Instrument	Regulation		
	•	matter requirements  (a)  Date of  manufacture	matter requirements  (a) (b)  Date of Community  manufacture Instrument  of the	matter requirements  (a) (b) (c)  Date of Community ECE  manufacture Instrument Regulation  of the	matter requirements and supplements provisions  (a) (b) (c) Date of Community ECE manufacture Instrument Regulation of the

and fuel consumption requirements for that category of vehicle before it was adapted.

Any adaptation to an exhaust system shall be permitted so long as:

- any (i) such adaptation is downstream of any emission control device fitted within the system; and
- (ii) the emission control device is identical to that which would have

I Item	2 Subject matter	3 Design, construction and equipment requirements			4 5 Definitions Exemptions and and supplementarymodification provisions	
		(a) Date of manufacture of the vehicle	(b) Community Instrument	(c) ECE Regulation	1	
						been fitted had the vehicle not been adapted.
27	Frontal impact	1st October 2003	Directive 96/79/EC, annex 2, paragraph 3	ECE Regulation 94.01, paragraph 5		If any vehicle has been adapted from a vehicle, the effect of which is to change the category of vehicle, then it shall be sufficient to show compliance either with the frontal impact requirements for the category of the unadapted vehicle, or of the adapted vehicle.  If (i) a disabled person's vehicle has been adapted

Changes to legislation: There are outstanding changes not yet made by the legislation.gov.uk editorial team to The Motor Vehicles (Approval) (Amendment) Regulations 2004. Any changes that have already been made by the team appear in the content and are referenced with annotations. (See end of Document for details) View outstanding changes

1	2	3			4	5
Item	Subject matter	Design, cons requirements		uction and equipment Definitions Exe and and supplementarymod provisions		
		(a)	(b)	(c)	-	
		Date of	Community	ECE		
		manufacture of the vehicle	Instrument	Regulation		

vehicle which before it was adapted was of a category which was required to comply with the requirements of this item; and (ii) the reason for the adaptation is to enable a disabled person to drive the vehicle or travel as a passenger in it; then the requirements of this item shall not apply, but only insofar as the adaptation prevents the disabled person's vehicle from complying with any of the requirements of this item.

from a

I Item	2 Subject matter	3 Design, construction and equipment requirements			4 Definitions and supplementa provisions	5 Exemptions and rymodifications
		(a) Date of manufacture of the vehicle	(b) Community Instrument	(c) ECE Regulation		
28	Side impact	1st October 2003	Directive 96/27/EC, annex 2, paragraph 3	ECE Regulation 95.01, paragraph 5		If any vehicle has been adapted from a vehicle, the effect of which is to change the category of vehicle, then it shall be sufficient to show compliance either with the side impact requirements for the category of the unadapted vehicle, or of the adapted vehicle.  If (i) a disabled person's vehicle has been adapted from a vehicle which was of a category, which was required to comply

Changes to legislation: There are outstanding changes not yet made by the legislation.gov.uk editorial team to The Motor Vehicles (Approval) (Amendment) Regulations 2004. Any changes that have already been made by the team appear in the content and are referenced with annotations. (See end of Document for details) View outstanding changes

1	2	3			4	5
Item	Subject matter	Design, cons requirements	truction and e	l equipment Definitions Exempti and and supplementarymodifica provisions		
		(a)	(b)	(c)	-	
		Date of	Community	ECE		
		manufacture of the vehicle	Instrument	Regulation		

requirements of this item; and (ii) the reason for the adaptation is to enable a disabled person to drive the vehicle or travel as a passenger in it; then the requirements of this item shall not apply to the disabled person's vehicle, but only insofar as the adaptationprevents the disabled person's vehicle from complying with any of the requirements of this item.

with the

## SCHEDULE 3

Regulation 11

nmencement Information Sch. 3 in force at 1.4.2004, see reg. 1	
British National Type Approval	
Minister's Approval Certificate	
issued under Section 58(1) of the Road Traffic Act 1988 by virtue of the Motor Vehicles (Approval) Regulations 2001	
The motor vehicle having the identification/ch	nassis number:
having been examined under Section 58 of the l certified that on the date of the examination this relevant requirements prescribed under Section	vehicle complied with the
Make:	Design Weights:
Model:	Axle 1 kg
Wodel.	Axle 2 kg
Class Code: DVLA Model Code:	Axle 3 kg
Category (passenger(M1)/goods(N1)):	Gross Weight kg
	Train Weight kg
Fuel Type e.g. (Petrol/Diesel/Gas Bi-Fuel):	
	NOTE: In the case of a goods vehicle the design weights shown are also the plated weights.
CO2: HC:	Signed by authority of the Secretary of State:
Station Location:	Name in CAPITALS:
	The state of the s
Date of issue:	Authentication Stamp:
Serial Number: AA	

## **EXPLANATORY NOTE**

(This note is not part of the Regulations)

These Regulations amend the Motor Vehicles (Approval) Regulations 2001 (S.I.2001/25).

Regulation 3 transfers the definition of a disabled person's vehicle from Schedule 2 to Regulation 3 of the Regulations.

Regulation 4 substitutes a new paragraph for paragraph 5(2) of the Regulations, the effect of which is to remove the requirement of vehicles which have complied with the items in Schedule 4, from having to comply with the requirements of the items of the same subject matter in Schedule 3 (apart from item 10 in relation to disabled person's vehicles and vehicles that have been adapted to category M1). Regulation 4 also substitutes a new paragraph for paragraph 5 (8) of the Regulations, to recognise certificates granted in accordance with the Northern Ireland single vehicle approval regime. A new paragraph (8A) has also been inserted to update the regulation relating to mutual recognition of equivalent standards in other EEA States.

Regulation 5 makes a minor corrective change and amends the requirement by which an applicant can request a further examination in respect of a further application.

Regulation 6 substitutes a new table into regulation 11.

Regulation 7 amends Schedule 2 of the Regulations. Disabled person's vehicles are excluded from the meaning of "Schedule 2 vehicle" and will now be subject to the requirements in Schedule 4. Paragraph 2 of Schedule 2 is also amended, the effect of which is that a serving member of the Armed Forces will now be able to qualify as a personal importer, even if the vehicle has not been imported into the United Kingdom.

Regulation 8 substitutes a revised Schedule 3 into the Regulations. Various deregulatory, consequential and corrective changes are made to the Schedule on points of detail.

Regulation 9 substitutes a revised Schedule 4 into the Regulations. As Disabled person's vehicles will now be subject to the Schedule 4 requirements, a number of consequential amendments have been made, together with other deregulatory and corrective changes on points of detail.

Regulation 10 substitutes a new certificate into the Regulations.

Regulation 11 updates the Schedule 6 list of Community Instruments and ECE Regulations.

These Regulations have been notified to the European Commission and the other Member States in accordance with Directive 98/34/EC of the European Parliament and the Council (OJNo. L204, 21.7.98, p.37), as amended by Directive 98/48/EC of the European Parliament and of the Council (OJ No. L217, 5.8.98, p.18).

A regulatory impact assessment has been prepared and copies can be obtained from the Department for Transport, Zone 2/03, Great Minster House, 76 Marsham Street, London SW1P 4DR (Telephone 020 7944 2093). A copy has been placed in the Library of each House of Parliament.

## **Changes to legislation:**

There are outstanding changes not yet made by the legislation.gov.uk editorial team to The Motor Vehicles (Approval) (Amendment) Regulations 2004. Any changes that have already been made by the team appear in the content and are referenced with annotations. View outstanding changes

## Changes and effects yet to be applied to:

Regulations revoked by S.I. 2020/818 Sch. 6 para. 43