SCHEDULE 1

Essential Health and Safety Requirements

COMMON REQUIREMENTS FOR EQUIPMENT AND PROTECTIVE SYSTEMS General requirements

Principles of integrated explosion safety

2.—(1) Equipment and protective systems intended for use in potentially explosive atmospheres must be designed from the point of view of integrated explosion safety.

- (2) In this connection, the manufacturer must take measures—
 - (a) above all, if possible, to prevent the formation of explosive atmospheres which may be produced or released by equipment and by protective systems themselves;
 - (b) to prevent the ignition of explosive atmospheres, taking into account the nature of every electrical and non-electrical source of ignition;
 - (c) should an explosion nevertheless occur which could directly or indirectly endanger persons and, as the case may be, domestic animals or property, to halt the explosion immediately or to limit the range of explosion flames and explosion pressures to a sufficient level of safety, or both.

(3) Equipment and protective systems must be designed and manufactured after due analysis of possible operating faults in order as far as possible to preclude dangerous situations.

(4) Any misuse which can reasonably be anticipated must be taken into account.

Commencement Information

II Sch. 1 para. 2 in force at 8.12.2016, see reg. 1(1)

Special checking and maintenance conditions

3. Equipment and protective systems subject to special checking and maintenance conditions must be designed and constructed with such conditions in mind.

Commencement Information

I2 Sch. 1 para. 3 in force at 8.12.2016, see reg. 1(1)

Surrounding area conditions

4. Equipment and protective systems must be so designed and constructed as to be capable of coping with actual or foreseeable surrounding area conditions.

Commencement Information

I3 Sch. 1 para. 4 in force at 8.12.2016, see reg. 1(1)

Marking

5.—(1) All equipment and protective systems must be marked legibly and indelibly with the following minimum particulars—

- (a) name, registered trade name or registered trade mark, and address of the manufacturer;
- (b) [^{F1} UK marking];
- (c) designation of series or type;
- (d) batch or serial number, if any;
- (e) year of construction;
- (f)



the specific marking of explosion protection followed by the symbol of the equipment-group and category;

- (g) for equipment-group II,
 - (i) the letter 'G' (concerning explosive atmospheres caused by gases, vapours or mists); or
 - (ii) the letter 'D' (concerning explosive atmospheres caused by dust); or
 - (iii) both the letter 'G' (concerning explosive atmospheres caused by gases, vapours or mists) and the letter 'D' (concerning explosive atmospheres caused by dust).

(2) Furthermore, where necessary, they must also be marked with all information essential to their safe use.

F1 Words in Sch. 1 para. 5(1)(b) substituted (31.12.2020) by The Product Safety and Metrology etc. (Amendment etc.) (EU Exit) Regulations 2019 (S.I. 2019/696), reg. 1, Sch. 25 para. 36(a) (with Sch. 25 para. 34) (as amended by S.I. 2020/676, regs. 1(1), 2); 2020 c. 1, Sch. 5 para. 1(1)

Commencement Information

I4 Sch. 1 para. 5 in force at 8.12.2016, see reg. 1(1)

Instructions

6.—(1) All equipment and protective systems must be accompanied by instructions, including at least the following particulars—

- (a) a recapitulation of the information with which the equipment or protective system is marked, except for the batch or serial number (see paragraphs 5(1) and (2)), together with any appropriate additional information to facilitate maintenance (e.g. address of the repairer, etc.);
- (b) instructions for safe—
 - (i) putting into service;
 - (ii) use;
 - (iii) assembling and dismantling;
 - (iv) maintenance (servicing and emergency repair);
 - (v) installation;
 - (vi) adjustment;
- (c) where necessary, an indication of the danger areas in front of pressure-relief devices;

- (d) where necessary, training instructions;
- (e) details which allow a decision to be taken beyond any doubt as to whether an item of equipment in a specific category or a protective system can be used safely in the intended area under the expected operating conditions;
- (f) electrical and pressure parameters, maximum surface temperatures and other limit values;
- (g) where necessary, special conditions of use, including particulars of possible misuse which experience has shown might occur;
- (h) where necessary, the essential characteristics of tools which may be fitted to the equipment or protective system.

(2) The instructions must contain the drawings and diagrams necessary for the putting into service, maintenance, inspection, checking of correct operation and, where appropriate, repair of the equipment or protective system, together with all useful instructions, in particular with regard to safety.

(3) Literature describing the equipment or protective system must not contradict the instructions with regard to safety aspects.

Commencement Information

I5 Sch. 1 para. 6 in force at 8.12.2016, see reg. 1(1)

Selection of materials

7.—(1) The materials used for the construction of equipment and protective systems must not trigger off an explosion, taking into account foreseeable operational stresses.

(2) Within the limits of the operating conditions laid down by the manufacturer, it must not be possible for a reaction to take place between the materials used and the constituents of the potentially explosive atmosphere which could impair explosion protection.

(3) Materials must be so selected that predictable changes in their characteristics and their compatibility in combination with other materials will not lead to a reduction in the protection afforded; in particular, due account must be taken of the material's corrosion and wear resistance, electrical conductivity, mechanical strength, ageing resistance and the effects of temperature variations.

Commencement Information

I6 Sch. 1 para. 7 in force at 8.12.2016, see reg. 1(1)

Design and construction

8.—(1) Equipment and protective systems must be designed and constructed with due regard to technological knowledge of explosion protection so that they can be safely operated throughout their foreseeable lifetime.

(2) Components to be incorporated into or used as replacements in equipment and protective systems must be so designed and constructed that they function safely for their intended purpose of explosion protection when they are installed in accordance with the manufacturer's instructions.

Commencement Information

I7 Sch. 1 para. 8 in force at 8.12.2016, see reg. 1(1)

Enclosed structures and prevention of leaks

9.—(1) Equipment which may release flammable gases or dusts must, wherever possible, employ enclosed structures only.

(2) If equipment contains openings or non-tight joints, these must, as far as possible, be designed in such a way that releases of gases or dusts cannot give rise to explosive atmospheres outside the equipment.

(3) Points where materials are introduced or drawn off must, as far as possible, be designed and equipped so as to limit releases of flammable materials during filling or draining.

Commencement Information

I8 Sch. 1 para. 9 in force at 8.12.2016, see reg. 1(1)

Dust deposits

10.—(1) Equipment and protective systems which are intended to be used in areas exposed to dust must be so designed that deposit dust on their surfaces is not ignited.

(2) In general, dust deposits must be limited where possible. Equipment and protective systems must be easily cleanable.

(3) The surface temperatures of equipment parts must be kept well below the glow temperature of the deposit dust.

(4) The thickness of deposit dust must be taken into consideration and, if appropriate, means must be taken to limit the temperature in order to prevent a heat build up.

Commencement Information

I9 Sch. 1 para. 10 in force at 8.12.2016, see reg. 1(1)

Additional means of protection

11.—(1) Equipment and protective systems which may be exposed to certain types of external stresses must be equipped, where necessary, with additional means of protection.

(2) Equipment must withstand relevant stresses, without adverse effect on explosion protection.

Commencement Information

I10 Sch. 1 para. 11 in force at 8.12.2016, see reg. 1(1)

Safe opening

12. If equipment and protective systems are in a housing or a locked container forming part of the explosion protection itself, it must be possible to open such housing or container only with a special tool or by means of appropriate protection measures.

Commencement Information

II1 Sch. 1 para. 12 in force at 8.12.2016, see reg. 1(1)

Protection against other hazards

13.—(1) Equipment and protective systems must be so designed and manufactured as to—

- (a) avoid physical injury or other harm which might be caused by direct or indirect contact;
- (b) assure that surface temperatures of accessible parts or radiation which would cause a danger, are not produced;
- (c) eliminate non-electrical dangers which are revealed by experience;
- (d) assure that foreseeable conditions of overload do not give rise to dangerous situations.

(2) Where, for equipment and protective systems, the risks referred to in paragraph (1) are wholly or partly covered by [F2 any other enactment], these Regulations do not apply or cease to apply in the case of such equipment and protective systems and of such risks upon application of that specific [F3 enactment].

- **F2** Words in Sch. 1 para. 13(2) substituted (31.12.2020) by The Product Safety and Metrology etc. (Amendment etc.) (EU Exit) Regulations 2019 (S.I. 2019/696), reg. 1, Sch. 25 para. 36(b)(i) (with Sch. 25 para. 34) (as amended by S.I. 2020/676, regs. 1(1), 2); 2020 c. 1, Sch. 5 para. 1(1)
- **F3** Word in Sch. 1 para. 13(2) substituted (31.12.2020) by The Product Safety and Metrology etc. (Amendment etc.) (EU Exit) Regulations 2019 (S.I. 2019/696), reg. 1, Sch. 25 para. 36(b)(ii) (with Sch. 25 para. 34) (as amended by S.I. 2020/676, regs. 1(1), 2); 2020 c. 1, Sch. 5 para. 1(1)

Commencement Information

I12 Sch. 1 para. 13 in force at 8.12.2016, see reg. 1(1)

Overloading of equipment

14. Dangerous overloading of equipment must be prevented at the design stage by means of integrated measurement, regulation and control devices, such as over-current cut-off switches, temperature limiters, differential pressure switches, flowmeters, time-lag relays, overspeed monitors or similar types of monitoring devices, or both overspeed monitors and similar types of monitoring devices.

Commencement Information

I13 Sch. 1 para. 14 in force at 8.12.2016, see reg. 1(1)

Flameproof enclosure systems

15. If parts which can ignite an explosive atmosphere are placed in an enclosure, measures must be taken to ensure that the enclosure withstands the pressure developed during an internal explosion of an explosive mixture and prevents the transmission of the explosion to the explosive atmosphere surrounding the enclosure.

Commencement Information

II4 Sch. 1 para. 15 in force at 8.12.2016, see reg. 1(1)

Changes to legislation:

There are currently no known outstanding effects for the The Equipment and Protective Systems Intended for Use in Potentially Explosive Atmospheres Regulations 2016, Cross Heading: COMMON REQUIREMENTS FOR EQUIPMENT AND PROTECTIVE SYSTEMS.