

Status: This is the original version (as it was originally made). This item of legislation is currently only available in its original format.

SCHEDULE 16

Variable message signs

PART 7

Performance classes

Table 1

(1)	(2)	(3)	(4)	(5)	(6)	(7)
	<i>Item Aspect of performance</i>	<i>Requirements or classes for colour</i>	<i>Requirements or classes for colour</i>	<i>Requirements or classes for colour</i>	<i>Requirements or classes for colour</i>	<i>Requirements or classes for colour</i>
1		White	Yellow	Green	Red	Blue
2	Colour Chromaticity Area	Area 10	Area 9 (Yellow C2)	Area 11 (Green C2)	Area 7 (Red C2)	Area 12 (Blue C2)
3	Luminance	L1	L1	L1	L1	L1
		L3	L3	L3	L3	L3
4	Luminance Ratio (On Axis)	R3	R3	R3	R3	R3
		R1	R1	R1	R1	R1
5	Beam Width	Narrow B1	B1	B1	B1	B1
		Wide B3	B3	B3	B3	B3

Table 2

(1)	(2)	(3)
	<i>Item Aspect of Performance</i>	<i>Requirement or Class</i>
1	Temperature	T1
2	Pollution	D1
3	Protection	P2

Table 3

(1)	(2)	(3)	(4)
	<i>Item Visual performance parameter</i>	<i>Class designation - Level 1</i>	<i>Class designation - Level 2</i>
1.	Colour	C2	C2
2.	Luminance	L3	L1

Status: This is the original version (as it was originally made). This item of legislation is currently only available in its original format.

<i>(1)</i>	<i>(2)</i>	<i>(3)</i>	<i>(4)</i>
<i>Item</i>	<i>Visual performance parameter</i>	<i>Class designation - Level 1</i>	<i>Class designation - Level 2</i>
3.	Luminance ratio	R3	R1
4.	Beam Width	B1 or B3	B1 or B3

Table 4

<i>(1)</i>	<i>(2)</i>	<i>(3)</i>
<i>Item</i>	<i>85percentile approach speed (mph)</i>	<i>Class designation</i>
1.	Up to and including 50	1 or 2
2.	Over 50	1